



(19) **United States**

(12) **Patent Application Publication**

Witkowski et al.

(10) **Pub. No.: US 2003/0228879 A1**

(43) **Pub. Date: Dec. 11, 2003**

(54) **COMMUNICATION SYSTEM FOR VEHICLE**

(22) Filed: Feb. 11, 2003

(75) Inventors: **Todd R. Witkowski**, Zeeland, MI (US);
Kurt A. Dykema, Holland, MI (US);
Steven L. Geerlings, Zeeland, MI (US);
Mark L. Zeinstra, Holland, MI (US);
Robert F. Buege, Lowell, MI (US)

Related U.S. Application Data

(63) Continuation of application No. 10/127,982, filed on Apr. 23, 2002.

Publication Classification

(51) **Int. Cl.⁷** **H04M 1/00**
(52) **U.S. Cl.** **455/550.1; 455/575.9; 455/90.2**

(57) **ABSTRACT**


A system for communicating information includes a transceiver provided within a vehicle that is configured for wireless communication with a cellular phone and with a portable computing device. The wireless communication between the transceiver and the cellular phone utilizes a Bluetooth communications protocol.


Correspondence Address:


FOLEY & LARDNER
777 EAST WISCONSIN AVENUE
SUITE 3800
MILWAUKEE, WI 53202-5308 (US)


(73) Assignee: **Johnson Controls Technology Company**


(21) Appl. No.: **10/364,794**














FIG 7









FIG 6




















COMMUNICATION SYSTEM FOR VEHICLE

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 10/127,982, filed Apr. 23, 2002, which is a continuation of U.S. patent application Ser. No. 09/979,199, filed Nov. 20, 2001, which was the National Stage of International Application No. PCT/US00/14692, filed May 26, 2000, which claims the benefit of U.S. Provisional Application No. 60/135,979, filed May 26, 1999.

FIELD

[0002] The present invention relates to communication of information between electronic devices. More specifically, the present invention relates to the transmission of information between a cellular phone, a transceiver, and a computing device utilizing a Bluetooth communications protocol.

BACKGROUND

[0003] With the increasing popularity of various personal electronic information and computing devices, there has been an increasing need to conveniently integrate the operation, and more specifically the transfer of information, between one or more of such devices. These electronic devices may include notebook computers, desktop computers, hand-held computing/organizer devices often termed "personal digital assistants" ("PDAs"), cellular phones, pagers, audio systems, display devices, cordless headsets, digital cameras and virtually any other electronic or electromechanical device that uses electronic information for its operation.

[0004] In many environments, such as within an automobile, it would be desirable to be able to communicate voice and/or data in wireless fashion between various subsystems of the vehicle, such as an overhead display subsystem of the vehicle, a cellular phone, notebook computer, PDA, pager or other personal electronic device which is carried on the person of an individual. The ability to transfer information between various subsystems of the vehicle and the user's personal electronic devices, in wireless fashion, would increase the ease and convenience of use of such personal devices when travelling in the vehicle.

[0005] Until the present, transferring information between one or more of these devices has most often required that cabling be connected between the devices. Usually the cabling is "application specific", meaning that the cabling used to connect, for example, a notebook computer and a hand-held PDA, is specifically designed for only these two components. Thus, the same communications cabling needed for connecting two specific electronic components often can only be used to connect those two components, and not to connect different combinations of other electronic components. Thus, interconnecting different combinations of electronic devices for intercommunication is often possible only with specific and often expensive cabling.

[0006] Communication between more than two electronic devices at one time via cabling presents even greater difficulty. Usually some form of hub or "T" connector, together with a mechanical switch and a suitable plurality of external cables is needed. Thus, the user often has very limited flexibility in linking more than two electronic devices together for communication.

[0007] In certain environments, such as within an automobile, it is often impractical for the user to manually connect and disconnect cabling between two or more electronic devices, especially when the electronic devices are portable devices which the user desires to carry when leaving the vehicle. Additionally, it would be impractical to attempt to connect such personal electronic devices to existing subsystems of a vehicle, such as an overhead display console, with physical cables that would be loose within the vehicle. Such cabling could easily interfere with the driver's convenient operation of the various controls of the vehicle or with the comfort and convenience of other passengers in the vehicle.

[0008] In some instances wireless communications, such as by infrared or radio frequency (RF) signals, have been used to permit communications and information sharing between two electronic devices. However, previously developed implementations of these methods of information transfer have suffered from significant drawbacks. For example, infrared data transmission requires a "line of sight" between the communicating sensors of the two devices. Such a line of sight is often not practical and/or difficult to maintain in certain operating environments, such as while travelling in an automobile. This also constrains the use of portable electronic devices to positions where the sensor on the portable device is in the line of sight of the other device with which the portable device is communicating.

[0009] Radio frequency data communication has traditionally been hampered by the lack of a standard communications protocol for data transfer which permits data to be transmitted between two or more independent electronic devices. A further limitation with RF data transfer systems has been the lack of a low cost, low power RF transceiver able to be inexpensively integrated with compact, portable electronic devices such as notebook computers, cellular telephones, hand-held PDAs, pagers, etc., to enable convenient RF information transfer between two or more of such devices over short distances of up to, for example, about ten meters.

[0010] Still another limitation with traditional methods for transmitting data between electronic devices has been the lack of an "automatic" or "unconscious" connection when the devices are in proximity with one another. By "automatic" or "unconscious" it is meant an immediate communications link which is established between two or more electronic devices as soon as the devices are within a certain range, for example, ten meters, of each other without any command being input to any of the devices by the user. This limitation has up until the present required the user to provide one or more commands to at least one of the electronic devices to begin the process of transferring data between the two devices.

[0011] In view of the foregoing, it would therefore be desirable to provide a wireless communications system adapted for use in automotive applications to permit the wireless exchange of voice and/or data between various portable electronic devices and various electronic subsystems of a motor vehicle. Such a system would preferably include a first electronic component which could be readily integrated with a wide variety of electronic devices such as notebook computers, pagers, PDAs, cellular phones, etc., and a second component which could easily be integrated

with various electronic subsystems of a motor vehicle such as an audio system, microphone, in-dash or overhead display system, on-board navigation system, etc. The first and second components would also preferably be extremely compact, lightweight, have low power requirements, and would therefore be very easily integrated into the various portable electronic devices described above, as well as into the various electronic subsystems of the vehicle. The components would preferably be able to automatically establish a wireless communications link as soon as the electronic device incorporating the first component comes into proximity with the vehicle, where the vehicle incorporates the second component. Such a system may obviate the need for any external cables to be attached between the electronic device(s) and the subsystem(s) of the vehicle.

[0012] Another example of an application where such a system would be highly useful is in the manufacturing of an automobile. If pertinent information concerning one or more of the vehicle's components or electronic subsystems could be quickly and automatically accessed and transmitted, via a high speed wireless communications link, to an electronic diagnostic/verification test system stationed along side an assembly line on which the vehicle is moving, then real time verification tests could be performed on the various electronic subsystems of the vehicle as it being manufactured. Such automatically created wireless communications links would significantly enhance a wide range of other applications.

[0013] Yet another example of an application where such a system would be useful is in servicing a vehicle. For example, a high speed wireless communications link could be established between a vehicle and an electronic device located in a service area (e.g., at an auto dealership, a service station, etc.), such that information relating to the operational status of any of a variety of electronic substations of the vehicle would be automatically transmitted to the electronic device. The information could be transmitted upon arrival of the vehicle within the service area and could also be transmitted while other operations are being performed on a vehicle (e.g., oil change, etc.). Transmission of vehicle diagnostic information using a wireless communications link may reduce the amount of time necessary to diagnose problems with a vehicle and increase the efficiency of providing service for a vehicle.

[0014] It would also be desirable to provide a system that allows for communication of information received by a cellular phone to a computing device using a transceiver provided within a vehicle. It would further be desirable to provide a system that establishes an automatic or unconscious communications link between a cellular phone and a transceiver or other device provided within a vehicle. It would further be desirable to provide a system that allows for the communication of facsimile transmissions and electronic mail messages to a computing device from a cellular phone.

[0015] Furthermore, it would be desirable if such a wireless communications system could be provided which does not add appreciably to the overall costs of such portable electronic devices or to the costs of various electronic subsystems of the vehicle. Preferably, the system would provide a manner of transmission that also ensures very secure wireless transmissions to limit the possibility of the

devices being susceptible to electronic "eavesdropping" or the data being intercepted by other RF devices operating in the same frequency spectrum.

SUMMARY

[0016] In one preferred embodiment, a Bluetooth communications standard is utilized for establishing a wireless communications link between two devices, where each device is equipped with a RF transceiver operating in accordance with the Bluetooth communications standard. This enables two or more devices to be connected via high speed, wireless communications links to permit voice and/or data information to be exchanged between the various devices. The devices communicate on the 2.4 GHz ISM frequency band and employ encryption and authentication schemes, in addition to frequency hopping, to provide a high measure of security to the transmission of data between the devices. Advantageously, the wireless communications link is created automatically as soon as the two devices come into proximity with each other.

[0017] In various preferred and exemplary embodiments, the RF transceivers each comprise low power components providing a limited range of up to about 100 meters. Each RF transceiver has a negligible power consumption, as compared with the device with which it is integrated. Each RF transceiver can automatically form ad hoc communications links with other RF transceivers passing within the predetermined transmission range.

[0018] The various preferred and exemplary embodiments enable voice and/or data information to be transmitted between a wide variety of devices without any command or intervention by the user. The preferred embodiments lend themselves especially well to applications involving the transfer of information between various portable electronic devices and the various electronic subsystems of a motor vehicle. The preferred embodiments further enable the transfer of information between a motor vehicle and other electronic systems outside of the vehicle, which makes these embodiments ideally suited to applications involving assembly of the vehicle, assisting in transmitting diagnostic information to and from a vehicle, and a wide variety of other applications where it is desirable to transmit information to a user traveling in a motor vehicle.

[0019] The various preferred embodiments are also ideally suited to establishing wireless communications links for a wide variety of other home, business, and commercial applications. A wide variety of electronic devices can thus be networked together for information sharing.

[0020] A more specific exemplary embodiment relates to a system communicating information. The system includes a transceiver provided within a vehicle and configured for wireless communication with a cellular phone and with a portable computing device. The wireless communication between the transceiver and the cellular phone utilizes a Bluetooth communications protocol.

[0021] Another exemplary embodiment relates to a wireless communications system for use in a vehicle. The communications system includes a transceiver provided within a vehicle. The communication system also includes a cellular phone in wireless communication with the transceiver, the wireless communication utilizing a Bluetooth

communications protocol. The communications system further includes a computing device in wireless communication with the transceiver. Information received by the cellular phone is communicated to the transceiver and at least a portion of the information is communicated from the transceiver to the computing device.

[0022] A further exemplary embodiment relates to a communications system for a vehicle. The communications system includes means for receiving signals transmitted by a cellular phone, the signals being transmitted in accordance with a Bluetooth communications standard and including information. The communications system also includes means for transmitting signals wirelessly to a computing device. The signals transmitted to the computing device include at least a portion of the information, and at least one of the means for receiving signals and the means for transmitting signals are provided within a vehicle.

[0023] A further exemplary embodiment relates to a method of transferring information to a computing device. The method includes receiving information at a transceiver provided in a vehicle. The information is transmitted from a cellular phone using a Bluetooth communications protocol. The method also includes communicating at least a portion of the information from the transceiver to the computing device using a wireless communications link.

[0024] The various preferred and exemplary embodiments are also ideally suited to establishing wireless communications links for a wide variety of other home, business, and commercial applications. A wide variety of electronic devices can thus be networked together for information sharing.

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] The various advantages of the present inventions will become apparent to one skilled in the art by reading the following specification and by referencing the following drawings in which:

[0026] FIG. 1 is a block diagram drawing of a wireless communications system in accordance with an exemplary embodiment being used to transfer information between an electronic device of the user and an audio system and a display system of a motor vehicle;

[0027] FIG. 2 is a block diagram illustrating a wireless communications system being used to perform vehicle diagnostics on a motor vehicle by creating a wireless communications link between a notebook computer running diagnostics software and a vehicle interface circuit associated with a motor vehicle;

[0028] FIG. 3 is a block diagram of a wireless communications system being used in an assembly operation in which information is transmitted from RF transceivers located in each vehicle to an assembly line monitoring system such that information needed for the manufacture of each vehicle can be requested in advance and thereafter made ready as needed during assembly of the vehicle;

[0029] FIG. 4 is a block diagram of a wireless communications system being used to create a high speed data link between a drive-through restaurant menu and the various electronic subsystems of the motor vehicle to enable infor-

mation from the drive-through menu to be broadcast and/or displayed by the vehicle's electronic subsystems;

[0030] FIG. 5 is a block diagram of a wireless communications system being used in connection with a key fob to enable data to be transmitted from the key fob to a vehicle bus interface of a motor vehicle to control various subsystems of the vehicle;

[0031] FIG. 5A is a block diagram of the major components of the key fob of FIG. 5;

[0032] FIG. 6 is a block diagram drawing illustrating a wireless communications link created between a key fob carried by the user and a work PC to enable data files to be transmitted in wireless fashion between the PC and the key fob;

[0033] FIG. 7 is a block diagram of the key fob of FIGS. 5 and 5A being used to transmit files in wireless fashion from the key fob to a home PC;

[0034] FIG. 8 is a block diagram of an exemplary embodiment being used to create a wireless communications link between a cellular phone and a proprietary voice recording/playback system manufactured by the assignee of the present application and presently used on motor vehicles;

[0035] FIG. 9 is a block diagram of a wireless communications system being used to create a wireless data link between a home PC linked to the Internet and various electronic subsystems of a motor vehicle to thereby enable information from the Internet to be transmitted to the subsystems of the vehicle automatically;

[0036] FIG. 10 is a block diagram of a wireless communications system being used to establish a wireless communications link between a cellular phone and various electronic subsystems of a motor vehicle after the cellular phone has linked with a wireless service organization;

[0037] FIG. 11 is a block diagram of a wireless communications system being used to establish a wireless data link between a cellular phone of a user and one or more subsystems of a vehicle, where the cellular phone is linked with a wireless service organization so that "push" services from an Internet service provider can be used to provide personalized traffic, weather or other information automatically from the Internet to the user as the user travels in the vehicle;

[0038] FIG. 12 is a block diagram of the wireless communications system being used to create a wireless data link between a gas pump kiosk of a service station and the subsystems of a vehicle, where the gas pump is linked to the Internet, such that information from the Internet can be transmitted in wireless fashion to one or more electronic subsystems of the vehicle while the vehicle is parked near the gas pump;

[0039] FIG. 13 is a block diagram of a wireless communications system being used to create a wireless data link for downloading map directions downloaded onto a home PC off of the Internet directly to one or more electronic subsystems of the vehicle while the vehicle is in close proximity to the home PC; and

[0040] FIG. 14 is a block diagram of a wireless communications system being used to transmit corporate information or messages from a wireless service organization to a fleet vehicle, where the information is provided over the

Internet from a corporate computer system, and such that the information can be provided via a wireless data link directly to the various subsystems of a fleet vehicle.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0041] The various preferred and exemplary embodiments disclosed herein are directed broadly to a wireless communications system and method for transmitting information between two or more electronic devices. In one embodiment a transceiver provided within a vehicle is configured for wireless communication with a cellular phone and with a portable computing device. The wireless communication between the transceiver and the cellular phone utilizes a Bluetooth communications protocol. The wireless communications link is established automatically when the devices come within a predetermined proximity to each other.

[0042] Referring to **FIG. 1**, a wireless communications system **10** in accordance with an exemplary embodiment is illustrated. The various preferred and exemplary embodiments are broadly directed to a wireless communications system **10** in which at least one pair of RF transceivers **10a** and **10b** are used to create a wireless communications link between at least two independent electronic devices. Each RF transceiver **10a** and **10b** operates in accordance with a suitable wireless communications protocol or standard to enable wireless communications between the transceivers **10a** and **10b**. The specific protocol or standard used also preferably enables the wireless communications link to be established automatically when the two RF transceivers come into proximity with each other. The specific protocol or standard may be the Bluetooth communications standard or the Shared Wireless Access Protocol-Cordless Access (SWAP-CA) specification, or any other suitable wireless communications specification that enables voice and/or data information to be transmitted between the two RF transceivers **10a** and **10b**.

[0043] The Bluetooth communications standard was established for creating small form factor, low-cost, short range RF links between mobile telephones, notebook computers, PDAs and other portable electronic devices. It is the result of a joint effort between several major commercial organizations to develop a RF communications standard for creating secure, wireless communications links between portable electronic devices such as cellular phones, PDAs, computers and other electronic devices. The Bluetooth communications standard is presently an "open" standard that enables short range, secure, RF transmission of voice and/or data information between such portable electronic devices to thus eliminate the need for physical cables for interconnecting the devices. Its implementation is based on a high performance, but low cost, integrated RF transceiver chip set. The Bluetooth standard further provides the potential for automatic and rapid "ad hoc" wireless connections when two or more devices equipped with RF transceivers operating in accordance with the Bluetooth standard come into proximity with each other.

[0044] The Bluetooth standard makes use of the free, universal 2.4 GHz Industrial, Scientific, and Medical (ISM) band and a frequency hopping scheme using 1600 hops/second. Encryption and authentication are built into the Bluetooth standard along with an automatic "output power

adaption" feature that automatically reduces the output power of the RF transceiver to only (and exactly) that amount of power which is needed to accomplish the data transmission.

[0045] The Bluetooth standard specifies a minimum RF receiver sensitivity of -70 dBm and the nominal output power is specified as 0 dBm (i.e., 1 mW), which eliminates the need for an off-chip power amplifier. With a 0 dBm transmit power, the typical range for the RF transceiver is up to about 10 meters. The range can be extended to about 100 meters by augmenting the RF transceiver chip set with an external power amplifier to increase the transmit power to a maximum of 20 dBm. The maximum data transfer rate between two Bluetooth transceivers is slightly under 1 Mbits/sec. The data rate for a voice channel is 64 kbits/sec (GSM-13 kbits/sec). A suitable RF transceiver for use with the Bluetooth standard can be formed relatively inexpensively as a single CMOS integrated chip. As such, the RF transceiver can be manufactured sufficiently small such that it can be readily incorporated into virtually all portable electronic devices without adding appreciably to the size, cost, weight and power consumption of such devices. Additional information on the Bluetooth standard can be obtained at URL address www.bluetooth.com.

[0046] Advantageously, the Bluetooth standard presently supports wireless communications networks termed "piconets" of between two to eight devices actively communicating with each other. Additional devices can be "parked" and accessed as needed. Within a piconet, one of the devices acts as the "master" device, which determines the frequency hopping pattern, packet timing, and which coordinates transmissions to the other "slave" devices. The slave devices can also be members of more than one piconet at a time, thus forming an ad hoc arrangement of multiple piconets termed a "scatternet". Thus, networked communication of notebook computers, PDAs, mobile phones, and other devices are provided for with the Bluetooth standard.

[0047] The SWAP-CA specification is another wireless communications standard that potentially could be employed by the RF transceivers **10a** and **10b**. The SWAP-CA specification also is intended to use integrated transceivers on a 2.4 GHz frequency hopping scheme for wireless communications between various products and appliances used in homes. With this standard, the data transfer rate for information is 2 Mbits/sec.

[0048] Accordingly, while the Bluetooth or SWAP-CA specifications may be referenced throughout the discussion of the various preferred embodiments, it should be understood that the claims appended hereto should be not be limited to the use of one or the other of these specifications, or necessarily to any specific communications specification.

[0049] In **FIG. 1**, one RF transceiver **10a** is integrated into a first electronic device **12** while the other RF transceiver **10b** is disposed within a motor vehicle **14**. The electronic device **12** may comprise a notebook computer, a hand-held PDA, a cellular phone, a pager, or any other portable electronic component. The first RF transceiver **10a** includes an antenna **16** for enabling two way communications with the RF transceiver **10a**. Likewise, the second RF transceiver **10b** also includes its own antenna **18** for enabling two way communications. The vehicle **14** typically includes an audio system **20** and a display system **22**. The display system **22**

may be mounted in a dashboard or instrument panel, an overhead console, a floor mounted console, a visor, a rear view mirror or at a wide variety of other locations inside the vehicle 14. The display 22 may comprise a small cathode ray tube ("CRT"), a liquid crystal display ("LCD") or various other forms of displays which are easily visible in daytime as well as nighttime driving conditions.

[0050] Each of the RF transceivers 10a and 10b are preferably formed as integrated circuit components which have an extremely low power consumption relative to the device with which they are integrated. Accordingly, the RF transceivers 10a and 10b can be maintained in an "on" state even when the electronic device with which it is associated is turned off. The RF transceivers 10a and 10b are further extremely compact and relatively inexpensive such that the overall dimensions of the electronic device are not appreciably increased by the inclusion of one of the transceivers 10a or 10b, and further such that the overall cost of the electronic device does not increase appreciably.

[0051] In FIG. 1, when the electronic device 12 comes into the vicinity of the vehicle 14, a high speed, automatic, wireless data link is created between the two RF transceivers 10a and 10b. The required proximity will vary depending upon the power output of each transceiver 10a and 10b. For a 0 dBm (1 mW) power output, a transmission range of up to about 10 meters is provided. Providing a suitable external amplifier to increase the output power of each RF transceiver 10a or 10b to a maximum of 20 dBm will increase the transmission range up to about 100 meters. It will be appreciated, however, that with even greater power amplifiers an even greater transmission range can be expected. Currently, the Bluetooth standard identifies a 20 dBm maximum power output.

[0052] Once the wireless communications link is established between the two RF transceivers 10a and 10b, information from the electronic device 12 can be transmitted to transceiver 10b and then output to the vehicle's audio system 20 and/or to the display system 22. Thus, the user is not required to type in or otherwise give any commands to the electronic device 12 before the wireless communications link is established. Once established, the communications link enables information from the electronic device 12 to be automatically transmitted via RF transceiver 10a to the receiving RF transceiver 10b. In this manner, a wide variety of useful information such as personal calendars, e-mail messages, telephone directories, and virtually any other form of text information can be displayed on the vehicle's display system 22. If an external "text-to-speech" module is incorporated for operation with the second RF transceiver 10b, then text information can be converted into audio before being transmitted to the vehicle's audio system 20 for playback. Thus, if the electronic device 12 comprises a notebook computer with a CD player, any information available on the CD can potentially be converted to speech via the external text-to-speech module and the vehicle's audio system 20. Thus, a wide variety of CD-based or Internet-based audio material such as books, educational materials, etc. could be played over the vehicle's audio system 20 while the user is in the vehicle 14.

[0053] Referring to FIG. 2, another implementation of a wireless communications system 10 is shown. This implementation is used to facilitate performing diagnostics on a

motor vehicle 14 via the electronic device 12. In this example, the electronic device may comprise a notebook computer or other electronic instrument loaded with diagnostic software specifically suited to the vehicle being tested. The first RF transceiver 10a is integrated into the electronic device 12 and the second RF transceiver 10b is integrated for communications with a vehicle interface system 24. The vehicle interface system 24 is in turn coupled for two way communications via a data bus 26 with various electronic subsystems of the vehicle 14 such as the vehicle's Electronic Control Module (ECM) 28, a fuel sensor 30, an exhaust sensor 32, a wheel speed sensor 34 or virtually any other form of sensor which provides an electronic output signal related to its operation. Other nonexclusive examples of the types of sensors that may provide an electronic output signal include oxygen sensors, fluid temperature sensors (e.g., engine coolant, fuel, oil), exhaust and emission sensors, oil pressure sensors, transmission sensors, engine timing sensors, or any other type of sensor that may provide signals to an on-board diagnostic module (e.g., OBD II, etc.) or other vehicle system. Further, any of a variety of conditions of the vehicle electronic subsystems may be monitored by such sensors (e.g., high voltage, low voltage, temperature, pressure, malfunctions, and a variety of others), and signals representative of any of the variety of functions and operations may be output by the sensors.

[0054] The wireless data link may be created automatically as soon as the vehicle 14 enters a service bay or other designated service area. The first RF transceiver 10a automatically begins transmitting diagnostics information stored in an associated memory (not shown) to the second RF transceiver 10b to begin the diagnostics testing. Information is transmitted back to the first transceiver 10a by the second transceiver 10b as information is received from the vehicle interface 24 from each of the sensors/components 28-34 under test. This information is then used by service personnel to determine the operational status of each of the sensors/components 28-34 on-board the vehicle 14. While the electronic device 12 has been described as a notebook computer, it will also be appreciated that the device 12 could just as readily comprise a personal computer or other form of computer adapted to run the diagnostics software.

[0055] It will be appreciated that the automatic wireless communications link enables various diagnostics to be performed on a motor vehicle even while other operations, for example, an oil change, are being performed simultaneously with the running of the diagnostics. This implementation can significantly reduce the manpower required to perform various service-related operations on a motor vehicle as well as decrease the length of time needed to perform a full service checkup/tune-up on a vehicle when the vehicle is brought in for routine maintenance such as oil changes, wheel alignments, air and fuel filter changes, wheel balancing, etc.

[0056] Referring now to FIG. 3, an implementation of the wireless communications system 10 is shown being used in the assembly process of a motor vehicle. In this implementation, the first RF transceiver 10a of the system 10 is integrated with an assembly line computer/monitoring system 36. Each one of a plurality of vehicles 14₁-14_n, traveling on assembly line conveyor 38 includes a module 40 having the second RF transceiver 10b integrated therewith. The module 40 can be programmed to include information regarding the specific options that its associated vehicle 14

is to include. Such options could comprise the type of interior, audio system options, interior trim package, powertrain options or any other equipment that will be needed to complete the manufacture of that particular vehicle 14.

[0057] As each vehicle 14₁-14_n, moves along the assembly line conveyor 38 into proximity with the computer/monitoring system 36, an automatic wireless communications link is established between each RF transceiver 10b, one at a time, and the RF transceiver 10a of the computer monitoring system 36. Information regarding the options that each particular vehicle 14₁-14_n, is then transmitted via the wireless communications link to the computer/monitoring system 36, which in turn is transmitted over a communications link 42 to an inventory management computer 44. It will be appreciated that the communications link 42 could be a wire-based link or could even be formed by an additional pair of RF transceivers to form a second wireless link. The only limitation here would be the distance to the inventory computer system 44 from the assembly/monitoring computer system 36.

[0058] The above-described implementation enables the wireless communications system 10 to thus be used to synchronize the supply of needed equipment and materials to each vehicle 14₁-14_n moving on the assembly line conveyor 38 to ensure that exactly the proper equipment is provided for each vehicle.

[0059] It will also be appreciated that the implementations described in connection with FIGS. 2 and 3 could be combined to enable various electronic modules and subsystems of the vehicle to be tested immediately as the vehicle moves along the assembly line conveyor 38. This feature would enable a vehicle diagnostics computer located adjacent to the assembly line conveyor 38 to run tests on the vehicle's modules and electronic subsystems to detect defective components before the vehicle proceeds to the next step of the assembly process. This feature would save the significant costs associated with manually removing various electronic modules and components from the vehicle for testing and repair when a defective component is detected after assembly of the vehicle is complete.

[0060] Referring now to FIG. 4, yet another implementation of the wireless communications system 10 is illustrated. This implementation is in connection with a retail transaction in which a drive-through menu board 46 has a first RF transceiver 10a of the wireless communications system 10, in addition to a secure transaction RF transceiver 48, integrated therewith. The vehicle includes the second RF transceiver 10b in addition to a secure transaction transceiver 50. As the vehicle 14 approaches the drive-through menu board 46, the RF transceivers 10a and 10b automatically establish a high-speed wireless communications link. A secure datalink is established between transceivers 48 and 50 by which electronic payment can be authorized by the driver of the vehicle 14. Menu information is then automatically downloaded over the high-speed communications link between the RF transceivers 10a and 10b onto a system control device 50. The system control device 50 acts as an interface to transmit the information to the vehicle's display system 22 and/or the vehicle's audio system 20 for playback. If a suitable microphone 58 is provided in the vehicle 14, authorization for the transaction may be provided verbally by the driver and transmitted via the communications link

between the secure transaction transceivers 48 and 50 back to the drive-through menu board 46.

[0061] It will be appreciated that the above-described implementation could be modified to enable drive-through banking transactions, drive-through prescription ordering or a wide variety of other retail transactions made from within a vehicle without the need for the driver to leave the vehicle 14 to effect the transaction. Other applications could include toll collecting, fuel purchases at service stations and other transactions that could potentially be made more conveniently and more quickly by the use of the wireless communications system 10.

[0062] Referring to FIG. 5, an implementation involving a programmable key fob 60 is illustrated for setting and adjusting various components of the vehicle 14. The key fob 60 is shown in greater detail in FIG. 5A and includes the first RF transceiver 10a of the wireless communications system 10, the antenna 16, a suitable battery 62 for providing power and a suitable memory 64. The second RF transceiver 10b of the system 10 is integrated into the vehicle electronics to communicate with the vehicle bus interface 24 via the vehicle bus 26, and further with various modules 66-72 for controlling various components of the vehicle 14.

[0063] As the user approaches the vehicle 14 when carrying the key fob 60, a high speed, wireless communications link is automatically established between the two RF transceivers 10a and 10b. Information stored in the memory 64 of the key fob 60 is then transmitted to the second transceiver 10b and used to control various modules of the vehicle 14 in accordance with preprogrammed settings by the user. Thus, information relating to the precise position of a power seat, volume and channel information of the radio 72, climate control information for the HVAC 70, rearview mirror or external mirror position information, etc., can all be stored in the memory 64 and automatically transmitted to the vehicle 14 as the user approaches the vehicle. The seats of the vehicle 14, climate control settings, radio channel and volume settings, mirror positions, etc. can all be automatically adjusted by suitable vehicle electronics even before the user enters the vehicle 14.

[0064] Referring to FIG. 6, another implementation of the wireless communications system 10 using the programmable key fob 60 is illustrated. In this implementation the key fob 60 is used to interrogate a PC 74 at the user's place of business. Selected files stored on the hard drive or in random access memory (RAM) of the PC 74 can be transmitted via a wireless communications link established between the RF transceiver 10a of the key fob 60 and the second RF transceiver 10b, which is integrated with the work PC 74. The information is stored in the memory of the key fob 60 before the user leaves his/her place of business.

[0065] Referring to FIG. 7, as the user arrives at his/her home, a home PC 76 is automatically linked with the key fob 60 by the RF transceiver 10a of the key fob 60 and a second RF transceiver 10b integrated with the home PC 76. The automatically created wireless communications link is used to transmit information stored in the memory 64 (FIG. 5a) of the key fob 60 to the individual's home PC 76.

[0066] Referring now to FIG. 8, yet another implementation of a wireless communications system 10 is shown in which a cellular phone 78 is linked with a proprietary speech

recording/playback system **80** available commercially from the assignee of the present application and marketed under the trademark "Travelnote®". The Travelnote® system enables the driver or other vehicle occupant to speak directly into a microphone **82** to record any notes or other information which the user would otherwise write down on paper, but which cannot be accomplished easily while driving the vehicle **14**. The notes or other information can be played back from the Travelnote® recording/playback system **80** over a speaker **84** once the user reaches his/her destination and prior to exiting the vehicle **14**. The Travelnote® recording/playback system **80** is described in detail in 5,810,420, the disclosure of which is hereby incorporated by reference.

[0067] In this implementation, the RF transceiver **10a** is integrated with the cellular phone **78** and the second RF transceiver **10b** is integrated with the Travelnote® recording/playback system **80**. The Travelnote® recording/playback system **80** may be located within a visor or rear view mirror **86**. Alternatively, it may be located on the dashboard, overhead console, or any other convenient location within the vehicle **14**. The wireless communications system **10** provides a high-speed, wireless communications link between the cellular phone **78** and the Travelnote® recording/playback system **80** to enable "hands free" use of the cellular phone **78**. Thus, the user need not hold the cellular phone **78** in one hand while driving; the phone **78** can be placed on a console or seat **82** adjacent to the user while the user carries on a hands-free conversation via the microphone **82** and speaker **84** of the Travelnote® playback/recording system **80**.

[0068] A further advantage is that the wireless communications link between the RF transceivers **10a** and **10b** is created automatically when the cellular phone **78** comes into proximity with the second RF transceiver **10b** within the vehicle **14**. Thus, the user need only dial a number from the cellular phone **78** to place a call and the conversation thereafter can be conducted via the Travelnote® system **80**. Alternatively, a call could even be placed via commands and numbers spoken into the microphone **82** and transmitted via the wireless communications link to the cellular phone **78**. Useful information received by the cellular phone **78** could even be displayed on a small portion of a rearview mirror. Such information could include auxiliary phone annunciators, a "low battery" warning indicating a low battery power condition for the cellular phone **78** or other incoming call information received via the phone **78**.

[0069] A modification of this implementation involves modifying the above-described Travelnote® system to send and/or receive digital information such that the Travelnote® system can be used to pass digital information to and from a computing device **79** such as a hand-held computing device or a laptop computer. With this capability, the Travelnote® system could be used to transmit information received by a facsimile transmission or email communications to the computing device. This digital information would be first received by the user's cellular phone **78**. Preferably, an infrared communications link **79a** is also established by suitable hardware between the cellular phone **78** and the computing device **79**. The infrared link is used to transmit digital information between the computing device **79** and the cellular phone **78**. Preferably, an infrared link **79b** is also established between the Travelnote® system and the computing device **79** so that digital information can just as

easily be transmitted directly between the computing device **79** and the Travelnote® system. Messages sent to the Travelnote® system could be stored therein for future downloading to another computer. The computing device **79** could also send stored phone numbers stored to the Travelnote® system to simplify the dialing of phone numbers.

[0070] As will be appreciated, other implementations of the various exemplary embodiments could be made in connection with a home and/or vehicle. For example, RF transceiver **10a** could be disposed in a cellular phone while RF transceiver **10b** is disposed in a Homelink® system which is proprietary to the assignee of the present application. The Homelink® system can be programmed to interface with, for example, a garage door opener to open the garage door when a control unit of the Homelink® system is actuated by a user. By incorporating RF transceiver **10b** into the Homelink® system, the user could enter a predetermined code in the cellular phone which is received by the Homelink® system and which causes the Homelink® system to open the garage door. In this manner, if an individual was not in his/her car or vehicle as he/she approached their house, the garage door could still be easily opened without the user having the garage door opener unit.

[0071] In another implementation, one or more RF transceivers **10a** are used in connection with various devices in a home. A second RF transceiver **10b** is placed in a garage. The second transducer **10b** serves as a portal from the user's car to those devices in the home that are equipped with RF transceivers **10a**. The garage-based RF transceiver **10b** is able to interface and interact with those devices incorporating a RF transceiver **10a**, such as a home PC, appliances, etc.

[0072] In still another implementation, one RF transceiver **10a** could be located within a vehicle while a second RF transceiver **10b** could be associated with a computer located either at a vehicle dealership or at a home. When a vehicle is manufactured, all parts could be tagged in the plant so it is known which specific parts are installed on the vehicle. This information could be stored in a database stored in a memory device in the car. In addition, warranty information for those parts, as well as for the car as a whole, could be stored in this database.

[0073] When the vehicle is in proximity to the first RF transceiver **10a** while the vehicle is being serviced at a dealership, service personnel could easily access information stored in the memory device via the wireless link between RF transceivers **10a** and **10b**. This would provide immediate access to information on the various components of the vehicle, as well as warranty information.

[0074] In yet another implementation similar to that described immediately above, only the Vehicle Identification Number ("VIN") is delivered to the computer from the RF transceiver **10b** located in the vehicle. The VIN is then used by the computer to access a database which is remote from the vehicle to obtain warranty and part information. It will be appreciated that this information could also be accessed through a web site of the manufacturer of the vehicle.

[0075] In still another variation of the above-described implementation, if a cellular telephone is located in the vehicle, and the telephone is equipped with an RF transceiver **10b**, then any vehicle malfunctions could be reported to the vehicle manufacturer or dealer via a wireless link

established between the computer and the cellular phone. This information can be used to facilitate repair of the vehicle or the tracking of warranty information pertaining to the vehicle.

[0076] The computer could also be used to personalize the vehicle operation. For example, the vehicle owner could access a manufacturer's website to select the desired operating parameters for the vehicle. These parameters could include selecting a 12 hour or 24 hour clock time display, establishing station pre-selects for the vehicle radio operation, selecting parameters related to the operation of the vehicle lights, enabling voice interactive messages generated by the vehicle, or a variety of other vehicle operating parameters. Once the operating parameters are selected by the vehicle owner, the website could cause the owner's home computer (which is equipped with RF transceiver 10a) to generate an RF signal that is sensed by the vehicle causing the parameters to be stored in a memory device in the vehicle. Alternatively, a compact disc could be provided to the vehicle owner upon purchase of the vehicle, which can be used with the individual's home computer to personalize the vehicle's functions. This information can then be transferred from the home computer to the vehicle via a wireless link between the two RF transceivers 10a and 10b.

[0077] Referring to FIG. 9, another implementation of the wireless communications system 10 is shown in which the system 10 includes the first RF transceiver 10a in communication with a user interface circuit 88. The user interface circuit 88 is in turn linked for communication via a suitable bus 90 with a display system 22 and/or an audio system 20 of the vehicle 14. The second RF transceiver 10b is integrated with a home PC 92. The home PC 92 is linked to the Internet.

[0078] The user uses the home PC 92 to retrieve information from the Internet (e.g., audio books, news, weather, music, etc.) at a convenient time. Once this information is received by the home PC 92 it is transmitted via the high-speed wireless communications link between the two RF transceivers 10a and 10b automatically. For this to occur, it will be appreciated that the vehicle 14 will need to be parked in the proximate vicinity of the home PC 92 (i.e., within about 100 meters of the home PC 92). In this regard it will also be appreciated that a suitable amount of random access memory (RAM) is provided in association with the display 22 and/or the vehicle audio system 20 for storing the information. The user can then display or play back the information while traveling in the vehicle 14 at the user's convenience. If the data is audio data, then it is played back through the vehicle audio system 20. Even text information which is received may be converted to audio information if a suitable text-to-speech conversion circuit is provided. The information stored could comprise traffic information, daily calendar reminders, appointments or events, e-mail messages, etc., in addition to the book, news, weather and music information mentioned above.

[0079] Referring to FIG. 10, the wireless communications system 10 can also be used to enable information relating to various "points of interest" along a route being traveled by the user. This information could also be "personalized" information for the user from an Internet-based information service.

[0080] In this implementation, a cellular phone 98 is used by the user to make a connection with a wireless service

organization 96. The cellular phone 98 includes the first RF transceiver 10a while the vehicle 14 includes the second RF transceiver 10b. A Global Positioning System ("GPS") device 100 on-board the vehicle 14 can be used to transmit, latitude/longitude information to the cellular phone 98 over the wireless communications link established between the two RF transceivers 10a and 10b. The cellular phone 98 in turn can be used to link this information back to the wireless service organization 96. The wireless service organization 96 then transmits information on various points of interest near the vehicle's latitude and longitude coordinates back to the cellular phone 98, which in turn transmits this information via a wireless, high speed data link from its RF transceiver 10a to the RF transceiver 10b. The information is then displayed on the vehicle's display 22 and/or played over the vehicle's audio system 20. The point of interest information can include a wide variety of useful information such as restaurants, shopping, service stations, hospitals and other establishments in the vicinity of the vehicle. The information could be displayed in a menu format in which the user is able to select establishments and is provided with directions on the display system 22 to each establishment selected. Additional information concerning traffic conditions, road construction, etc., could also be provided.

[0081] Referring to FIG. 11, another implementation of the wireless communications system 10 is illustrated where "Push" technology is used to download information from the Internet automatically to the user traveling in the vehicle 14. A cellular phone 98 having the first RF transceiver 10a of the wireless communications system 10 establishes an automatic, high-speed wireless communications link with the second RF transceiver 10b located in the vehicle 14. The transceiver 10b is in communication with the vehicle's display system 22 and/or the vehicle's audio system 20.

[0082] The wireless service organization 96 is linked to the Internet and to the cellular phone 98. The user can use his/her home PC 92 (or alternatively a business PC) to create a "personalized" website through one of the presently available Internet-based news/search companies so that various personalized information such as selected financial information (i.e., stock price information), world or local news, traffic information along a specified route of travel, phone directory or personal calendar information, weather information, e-mail, etc., can be downloaded by the wireless service organization 96 and provided to the cellular phone 98. The RF transceivers 10a and 10b can then be used to transmit the information to the vehicle's display system 22 or audio system 20.

[0083] Referring to FIG. 12, a variation of the implementation shown in FIG. 11 is illustrated in which existing Push technology is used to download personalized information from an Internet based information service to a suitable electronic system located at or closely adjacent to a gasoline pump 100, or at a kiosk including the gasoline pump 100, when the user's vehicle 14 comes within the vicinity of the gasoline pump 100. In this implementation, the gasoline pump 100 includes the electronic device 12 which includes the RF transceiver 10b, and the vehicle 14 includes the RF transceiver 10a. The RF transceiver 10a is in communication with the vehicle's display 22 and/or audio system 20. When the vehicle 14 comes into reasonably close proximity (e.g., within 10 meters of the gasoline pump 100), the RF transceiver 10a automatically establishes a high speed, wire-

less communications link with the RF transceiver **10b** of the electronic device **12**. The RF transceiver **10a** transmits appropriate identifying information to the RF transceiver **10b** via the automatically established wireless communications link. This information is then linked to the Internet-based information service. Information is then transmitted back to the electronic system **12** associated with the gasoline pump **100**. The information is then transmitted over the wireless communications link to the RF transceiver **10a** located in the vehicle **14**. It will be appreciated that this personalized information could also be obtained from the Internet by establishing wireless communications links with electronic devices located on road signs, freeway overpasses, at traffic lights and other points along a road or highway.

[0084] Referring to **FIG. 13**, another implementation somewhat similar to that described in connection with **FIG. 12** is provided. The implementation of **FIG. 13** enables a wireless communications system **10** to provide a subset of map information needed for assisting a user of the vehicle **14** in traveling to a designated destination. In this implementation one RF transceiver **10a** is located in the vehicle **14** and the other RF transceiver **10b** is integrated with a PC **92**, which may be located at the user's home or place of business. The user **14** can enter a command from either the PC **92** or from a suitable keyboard or control panel within the vehicle **14**, or even from a cellular phone carried within the vehicle **14** and linked by two RF transceivers, requesting directions for traveling to a particular destination. This request is transmitted to an Internet-based information organization where it is thereafter downloaded onto the PC **92**. The information is then transmitted via the high-speed wireless communications link created by the RF transceivers **10a** and **10b** back to the vehicle **14** where it may be displayed on the vehicle's display **22** or possibly played on the vehicle's audio system **20**. Since only a limited amount of information pertaining to the specific directions requested is transmitted back to the vehicle **14**, this significantly reduces the amount of memory required to be located on-board the vehicle **14**. It will be appreciated that this map information could just as easily be provided by linking to an electronic subsystem associated with the gasoline pump **100** (**FIG. 12**) or at some other location if the user becomes lost and suddenly requires directions to a different destination.

[0085] Referring now to **FIG. 14**, another implementation of the wireless communications system **10** is provided in which information from a business or a company is "pushed" into a company vehicle **14** from a corporate message center or corporate PC **102**. The information from the corporate message center or PC **102** is transmitted via the Internet to the wireless service organization **96**. A communications link is established between the wireless service organization **96** and the user's cellular phone **98**. The cellular phone **98** includes one RF transceiver and the vehicle **104** includes the second RF transceiver **10b**. Again, the RF transceiver **10b** is in communication with the vehicle's display **22** and/or the vehicle's audio system **20**. Important business information received by the cellphone **98** can then be downloaded via the wireless communications link created by the RF transceivers **10a** and **10b** to the user to apprise the user of important corporate news, events, scheduling or other information which needs to be transmitted to the user on a timely basis. Again, this information could be relayed through suitable electronic relaying devices pro-

vided at gasoline pumps or at other points such as intersections, freeway overpasses, etc. that the vehicle **14** is expected to pass in proximity to during use.

[0086] It will be appreciated that an extremely large variety of useful implementations of the wireless communications system may be created. While the Bluetooth communications standard or the SWAP-CA standard may be used with the RF transceivers **10a** and **10b**, it will be appreciated that other communications specifications may also be employed. Additionally, while many of the implementations described herein have made use of a motor vehicle, it will be appreciated that the RF transceivers **10a** and **10b** could just as easily be used to effect high-speed wireless communications links between virtually any two electronic devices which come into proximity with one another, and where it would be useful to transfer information from one device to the other.

[0087] Those skilled in the art can now appreciate from the foregoing description that the broad teachings of the present disclosure can be implemented in a variety of forms. Therefore, while this invention has been described in connection with particular examples thereof, the true scope of the claims appended hereto should not be so limited since other modifications will become apparent to the skilled practitioner upon a study of the drawings and the present specification.

What is claimed is:

1. A system for communicating information comprising:
 - a transceiver provided within a vehicle and configured for wireless communication with a cellular phone and with a portable computing device;
 - wherein the wireless communication between the transceiver and the cellular phone utilizes a Bluetooth communications protocol.
2. The system of claim 1, wherein the transceiver is coupled to at least a portion of a vehicle.
3. The system of claim 1, wherein information is communicated from the cellular phone to the transceiver and the transceiver communicates at least a portion of the information to the portable computing device.
4. The system of claim 3, wherein the information comprises at least one of a facsimile transmission and an electronic mail message.
5. The system of claim 1, wherein information is transmitted from the computing device to the transceiver.
6. The system of claim 5, at least a portion of the information is transmitted from the transceiver to the cellular phone.
7. The system of claim 5, wherein the information comprises a phone number.
8. The system of claim 1, wherein the wireless communication between the transceiver and the portable computing device utilizes a Bluetooth communications protocol.
9. The system of claim 1, wherein the wireless communication between the transceiver and the portable computing device utilizes an infrared communications link.
10. The system of claim 1, wherein the portable computing device is a laptop computer.
11. The system of claim 1, wherein the portable computing device is a hand-held computing device.

12. The system of claim 1, wherein a communications link is automatically established when the cellular phone comes within a predetermined distance of the transceiver.

13. The system of claim 1, further comprising a microphone coupled to the transceiver, wherein sounds input at the microphone may be transmitted from the transceiver to the cellular phone.

14. The system of claim 1, wherein the transceiver is a trainable transceiver.

15. A wireless communications system for use in a vehicle comprising:

a transceiver provided within a vehicle;

a cellular phone in wireless communication with the transceiver, the wireless communication utilizing a Bluetooth communications protocol; and

a computing device in wireless communication with the transceiver;

wherein information received by the cellular phone is communicated to the transceiver and at least a portion of the information is communicated from the transceiver to the computing device.

16. The communications system of claim 15, wherein the computing device is at least one of a laptop computer and a hand-held computing device.

17. The communications system of claim 15, wherein the information is selected from a facsimile transmission and an electronic mail message.

18. The communications system of claim 15, wherein the computing device communicates with the transceiver using a Bluetooth communications protocol.

19. The communications system of claim 15, wherein the computing device communicates with the transceiver using an infrared communications link.

20. The communications system of claim 15, wherein the transceiver is a trainable transceiver configured to interface with a garage door opener system.

21. A communications system for a vehicle, the communications system comprising:

means for receiving signals transmitted by a cellular phone, the signals being transmitted in accordance with a Bluetooth communications standard and including information; and

means for transmitting signals wirelessly to a computing device;

wherein the signals transmitted to the computing device include at least a portion of the information; and

wherein at least one of the means for receiving signals and the means for transmitting signals are provided within a vehicle.

22. The communications system of claim 21, wherein the means for receiving signals and the means for transmitting signals are included in a transceiver coupled to a vehicle.

23. The communications system of claim 21, wherein the means for transmitting signals communicates with the computing device using a Bluetooth communications protocol.

24. The communications system of claim 21, wherein the means for transmitting signals communicates with the computing device using an infrared communications link.

25. The communications system of claim 21, wherein the information comprises at least one of a facsimile transmission and an electronic mail message.

26. The communications system of claim 21, further comprising means for receiving information from the computing device and means for transmitting at least a portion of the information received from the computing device to the cellular phone.

27. The communications system of claim 26, wherein the computing device is one of a laptop computer and a hand-held computing device.

28. A method of transferring information to a computing device comprising:

receiving information at a transceiver provided in a vehicle, the information transmitted from a cellular phone using a Bluetooth communications protocol; and

communicating at least a portion of the information from the transceiver to the computing device using a wireless communications link.

29. The method of claim 28, wherein the step of receiving information at the transceiver comprises receiving at least one of a facsimile transmission and an electronic mail message.

30. The method of claim 28, wherein the computing device is at least one of a laptop computer and a hand-held computing device.

31. The method of claim 28, wherein the wireless communications link is an infrared communications link.

32. The method of claim 28, wherein the wireless communications link utilizes a Bluetooth communications protocol.

33. The method of claim 28, wherein the transceiver is a trainable transceiver that is also configured to transmit signals to at least one of a garage door opener system and a home security system.

* * * * *