



US010511557B2

(12) **United States Patent**
Katis et al.

(10) **Patent No.:** **US 10,511,557 B2**
(45) **Date of Patent:** **Dec. 17, 2019**

(54) **TELECOMMUNICATION AND MULTIMEDIA
MANAGEMENT METHOD AND APPARATUS**

(71) Applicant: **Voxer IP LLC**, San Francisco, CA (US)

(72) Inventors: **Thomas E. Katis**, Jackson, WY (US);
James T. Panttaja, San Francisco, CA
(US); **Mary G. Panttaja**, San
Francisco, CA (US); **Matthew J.**
Ranney, Oakland, CA (US)

(73) Assignee: **VOXER IP LLC**, San Francisco, CA
(US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/161,474**

(22) Filed: **Oct. 16, 2018**

(65) **Prior Publication Data**

US 2019/0052590 A1 Feb. 14, 2019

Related U.S. Application Data

(63) Continuation of application No. 15/923,287, filed on
Mar. 16, 2018, now Pat. No. 10,129,191, which is a
(Continued)

(51) **Int. Cl.**
H04N 7/14 (2006.01)
H04M 11/00 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 51/10** (2013.01); **G06F 15/16**
(2013.01); **H04L 12/1831** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC H04L 12/58; H04L 12/18; H04L 29/12;
H04L 29/06; H04N 7/15; H04N 7/14;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,807,224 A 2/1989 Naron et al.
5,117,422 A 5/1992 Hauptschein et al.
(Continued)

FOREIGN PATENT DOCUMENTS

CN 1393090 A 1/2003
CN 1852421 10/2006
(Continued)

OTHER PUBLICATIONS

"About Gmail," <http://mail.google.com/mail/help/chat.html>, Down-
loaded on Aug. 20, 2009, 3 pages.

(Continued)


Primary Examiner — Melur Ramakrishnaiah

(74) *Attorney, Agent, or Firm* — Beyer Law Group LLP

(57) **ABSTRACT**

A telecommunication and multimedia management apparatus and method that supports voice and other media communications and that enables users to: (i) participate in multiple conversation modes, including live phone calls, conference calls, instant voice messaging or tactical communications; (ii) review the messages of conversations in either a live mode or a time-shifted mode and to seamlessly transition back and forth between the two modes; (iii) participate in multiple conversations either concurrently or simultaneously; (iv) archive the messages of conversations for later review or processing; and (v) persistently store media either created or received on the communication devices of users. The latter feature enables users to generate or review media when either disconnected from the network or network conditions are poor and to optimize the delivery of media over the network based on network conditions and the intention of the users participating in conversations.

59 Claims, 33 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/584,224, filed on May 2, 2017, now Pat. No. 10,142,270, which is a continuation of application No. 15/231,240, filed on Aug. 8, 2016, now Pat. No. 9,674,122, which is a continuation of application No. 14/799,528, filed on Jul. 14, 2015, now Pat. No. 9,456,087, which is a continuation of application No. 14/198,043, filed on Mar. 5, 2014, now Pat. No. 9,154,628, which is a continuation of application No. 13/555,034, filed on Jul. 20, 2012, now Pat. No. 8,705,714, which is a continuation of application No. 12/037,256, filed on Feb. 26, 2008, now Pat. No. 8,243,894, which is a continuation of application No. 12/028,400, filed on Feb. 8, 2008, now Pat. No. 8,180,029.

- (60) Provisional application No. 60/937,552, filed on Jun. 28, 2007, provisional application No. 60/999,619, filed on Oct. 19, 2007.

(51) Int. Cl.

H04L 12/58 (2006.01)
H04W 4/12 (2009.01)
H04L 12/18 (2006.01)
H04L 29/06 (2006.01)
G06F 15/16 (2006.01)
H04M 1/64 (2006.01)
H04M 3/53 (2006.01)
H04L 29/12 (2006.01)
H04L 29/08 (2006.01)
H04N 7/15 (2006.01)

(52) U.S. Cl.

CPC **H04L 51/04** (2013.01); **H04L 51/16** (2013.01); **H04L 51/22** (2013.01); **H04L 51/26** (2013.01); **H04L 61/2503** (2013.01); **H04L 65/1083** (2013.01); **H04L 65/403** (2013.01); **H04L 65/4015** (2013.01); **H04L 65/604** (2013.01); **H04L 67/24** (2013.01); **H04M 1/64** (2013.01); **H04M 3/53** (2013.01); **H04M 3/5307** (2013.01); **H04M 11/00** (2013.01); **H04N 7/147** (2013.01); **H04N 7/15** (2013.01); **H04W 4/12** (2013.01)

(58) Field of Classification Search

CPC H04M 3/53; H04M 11/00; H04M 1/64; H04W 4/12
 USPC 379/93.01; 348/14.01–14.16
 See application file for complete search history.

(56) References Cited

U.S. PATENT DOCUMENTS

- | | | | | | |
|-------------|---------|-------------------|--------------|---------|--------------------|
| 5,128,932 A | 7/1992 | Li | 6,092,120 A | 7/2000 | Swaminathan et al. |
| 5,283,818 A | 2/1994 | Klausner et al. | 6,104,757 A | 8/2000 | Rhee |
| 5,375,018 A | 12/1994 | Klausner et al. | 6,175,619 B1 | 1/2001 | DeSimone |
| 5,390,236 A | 2/1995 | Klausner et al. | 6,212,535 B1 | 4/2001 | Weikart et al. |
| 5,487,167 A | 1/1996 | Dinallo et al. | 6,233,389 B1 | 5/2001 | Barton et al. |
| 5,524,140 A | 6/1996 | Klausner et al. | 6,262,994 B1 | 7/2001 | Dirschedl et al. |
| 5,572,576 A | 11/1996 | Klausner et al. | 6,335,966 B1 | 1/2002 | Toyoda |
| 5,651,054 A | 7/1997 | Dunn et al. | 6,378,035 B1 | 4/2002 | Parry et al. |
| 5,692,213 A | 11/1997 | Goldberg et al. | 6,411,685 B1 | 6/2002 | O'Neal |
| 5,734,963 A | 3/1998 | Fitzgerald et al. | 6,480,783 B1 | 11/2002 | Myr |
| 5,737,011 A | 4/1998 | Lukacs | 6,507,586 B1 | 1/2003 | Satran et al. |
| 5,889,764 A | 3/1999 | Needham et al. | 6,564,261 B1 | 5/2003 | Gudjonsson et al. |
| 5,918,158 A | 6/1999 | LaPorta et al. | 6,577,599 B1 | 6/2003 | Gupta et al. |
| 5,958,005 A | 9/1999 | Thorne et al. | 6,580,694 B1 | 6/2003 | Baker |
| 5,963,551 A | 10/1999 | Minko | 6,594,693 B1 | 7/2003 | Borwankar et al. |
| 5,970,122 A | 10/1999 | LaPorta et al. | 6,671,732 B1 | 12/2003 | Weiner |
| 6,037,932 A | 3/2000 | Feinleib | 6,690,654 B2 | 2/2004 | Elliott et al. |
| | | | 6,700,902 B1 | 3/2004 | Meyer |
| | | | 6,717,925 B1 | 4/2004 | Leppisaari et al. |
| | | | 6,721,703 B2 | 4/2004 | Jackson et al. |
| | | | 6,721,784 B1 | 4/2004 | Leonard et al. |
| | | | 6,791,949 B1 | 9/2004 | Ryu et al. |
| | | | 6,792,085 B1 | 9/2004 | Rigaldies et al. |
| | | | 6,807,565 B1 | 10/2004 | Dodrill et al. |
| | | | 6,807,578 B2 | 10/2004 | Satran et al. |
| | | | 6,829,473 B2 | 12/2004 | Raman et al. |
| | | | 6,834,039 B1 | 12/2004 | Kelly et al. |
| | | | 6,850,965 B2 | 2/2005 | Allen |
| | | | 6,912,544 B1 | 6/2005 | Weiner |
| | | | 6,931,114 B1 | 8/2005 | Martin |
| | | | 6,970,926 B1 | 11/2005 | Needham et al. |
| | | | 6,973,309 B1 | 12/2005 | Rygula et al. |
| | | | 6,993,009 B2 | 1/2006 | Kelly et al. |
| | | | 6,996,624 B1 | 2/2006 | LeCroy et al. |
| | | | 7,002,913 B2 | 2/2006 | Huang et al. |
| | | | 7,002,973 B2 | 2/2006 | McLampy et al. |
| | | | 7,039,040 B1 | 5/2006 | Burg |
| | | | 7,039,675 B1 | 5/2006 | Kato |
| | | | 7,039,761 B2 | 5/2006 | Wang et al. |
| | | | 7,047,030 B2 | 5/2006 | Forsyth |
| | | | 7,058,392 B1 | 6/2006 | Weinman, Jr. |
| | | | 7,082,164 B2 | 7/2006 | Chaddha |
| | | | 7,111,044 B2 | 9/2006 | Lee |
| | | | 7,113,767 B2 | 9/2006 | Väänänen |
| | | | 7,117,521 B2 | 10/2006 | Puthiyedath |
| | | | 7,139,371 B2 | 11/2006 | McElvaney |
| | | | 7,171,491 B1 | 1/2007 | O'Toole et al. |
| | | | 7,180,944 B2 | 2/2007 | Lin et al. |
| | | | 7,187,941 B2 | 3/2007 | Siegel |
| | | | 7,218,709 B2 | 5/2007 | Garg et al. |
| | | | 7,228,359 B1 | 6/2007 | Monterio |
| | | | 7,233,589 B2 | 6/2007 | Tanigawa et al. |
| | | | 7,236,738 B2 | 6/2007 | Settle |
| | | | 7,240,105 B2 | 7/2007 | Satran et al. |
| | | | 7,277,453 B2 | 10/2007 | Chin et al. |
| | | | 7,283,809 B1 | 10/2007 | Weinman, Jr. |
| | | | 7,304,951 B2 | 12/2007 | Rhee |
| | | | 7,305,438 B2 | 12/2007 | Christensen et al. |
| | | | 7,313,593 B1 | 12/2007 | Pulito et al. |
| | | | 7,339,937 B2 | 3/2008 | Mitra et al. |
| | | | 7,349,871 B2 | 3/2008 | Labrou et al. |
| | | | 7,382,881 B2 | 6/2008 | Uusitalo et al. |
| | | | 7,403,775 B2 | 7/2008 | Patel et al. |
| | | | 7,415,284 B2 | 8/2008 | Hoover et al. |
| | | | 7,415,291 B1 | 8/2008 | Kirkpatrick |
| | | | 7,426,191 B2 | 9/2008 | Salesky et al. |
| | | | 7,444,306 B2 | 10/2008 | Varble |
| | | | 7,483,899 B2 | 1/2009 | Berry et al. |
| | | | 7,613,773 B2 | 11/2009 | Watt |
| | | | 7,626,951 B2 | 12/2009 | Croy et al. |
| | | | 7,634,652 B2 | 12/2009 | McEnroe et al. |
| | | | 7,636,327 B1 | 12/2009 | Doran |
| | | | 7,656,836 B2 | 2/2010 | Baker et al. |
| | | | 7,719,975 B2 | 5/2010 | Mallet et al. |
| | | | 7,730,142 B2 | 6/2010 | LeVasseur |
| | | | 7,742,429 B1 | 6/2010 | Huang et al. |
| | | | 7,809,388 B1 | 10/2010 | Othmer |
| | | | 7,899,045 B2 | 3/2011 | Shankara |
| | | | 7,908,389 B2 | 3/2011 | Zuckerman et al. |

US 10,511,557 B2

Page 3

(56)

References Cited

U.S. PATENT DOCUMENTS

7,913,053 B1	3/2011	Newland	2003/0163580 A1	4/2003	Lee
7,957,363 B2	6/2011	Deen et al.	2003/0084106 A1	5/2003	Erev et al.
7,970,918 B2	6/2011	Thompson et al.	2003/0099198 A1	5/2003	Kiremidjian et al.
7,996,553 B2	8/2011	Keller et al.	2003/0126162 A1	7/2003	Yohe et al.
8,027,276 B2	9/2011	Nierhaus	2003/0172116 A1	9/2003	Curry et al.
8,045,682 B2	10/2011	Jönsson	2003/0172233 A1	9/2003	Mugitani et al.
8,086,222 B2	12/2011	Vaananen	2003/0186722 A1	10/2003	Weiner
8,094,647 B2	1/2012	Elliott et al.	2003/0208543 A1	11/2003	Enete et al.
8,099,512 B2	1/2012	Katis et al.	2003/0210265 A1	11/2003	Haimberg
8,121,270 B2	2/2012	Katis et al.	2004/0017905 A1	1/2004	Warfier et al.
8,130,921 B2	3/2012	Katis et al.	2004/0019539 A1	1/2004	Raman et al.
8,175,234 B2	5/2012	Katis et al.	2004/0039839 A1	2/2004	Kalyanaraman et al.
8,180,029 B2	5/2012	Katis et al.	2004/0045036 A1	3/2004	Terasaki
8,180,030 B2	5/2012	Katis et al.	2004/0052218 A1	3/2004	Knappe
8,243,894 B2	8/2012	Katis et al.	2004/0074448 A1	4/2004	Bunt
8,271,003 B1	9/2012	Othmer et al.	2004/0090959 A1	5/2004	Cinghita et al.
8,296,366 B2	10/2012	Huai	2004/0095900 A1	5/2004	Siegel
8,311,050 B2	11/2012	Katis et al.	2004/0117722 A1	6/2004	Harada
8,315,377 B2	11/2012	Daloz	2004/0125816 A1	7/2004	Xu et al.
8,345,836 B2	1/2013	Katis et al.	2004/0127279 A1	7/2004	Gatto et al.
8,401,582 B2	3/2013	Katis et al.	2004/0151158 A1	8/2004	Gannage et al.
8,401,583 B2	3/2013	Katis et al.	2004/0170158 A1	9/2004	Man-Hak Tso et al.
8,463,927 B2	6/2013	Liang	2004/0179092 A1	9/2004	LaPoint
8,526,456 B2	9/2013	Katis et al.	2004/0192353 A1	9/2004	Mason et al.
8,532,270 B2	9/2013	Katis et al.	2004/0192378 A1	9/2004	Wulkan
8,533,611 B2	9/2013	Katis et al.	2004/0203670 A1	10/2004	King et al.
8,559,319 B2	10/2013	Katis et al.	2004/0207724 A1	10/2004	Crouch et al.
8,565,149 B2	10/2013	Katis et al.	2004/0207870 A1	10/2004	Takahashi et al.
8,645,477 B2	2/2014	Katis et al.	2004/0213211 A1	10/2004	Green et al.
8,670,531 B2	3/2014	Katis et al.	2004/0252679 A1	12/2004	Williams et al.
8,687,779 B2	4/2014	Katis et al.	2004/0255148 A1	12/2004	Monteiro et al.
8,688,789 B2	4/2014	Katis et al.	2004/0258220 A1	12/2004	Levine et al.
8,693,647 B2	4/2014	Katis et al.	2005/0020246 A1	1/2005	Kang
8,705,714 B2	4/2014	Katis et al.	2005/0021819 A1	1/2005	Kilkki
8,744,050 B2	6/2014	Katis et al.	2005/0025308 A1	2/2005	Tischer et al.
8,817,955 B2	8/2014	Milstein	2005/0030932 A1	2/2005	Kelly et al.
8,825,772 B2	9/2014	Katis et al.	2005/0037706 A1	2/2005	Settle
8,832,299 B2	9/2014	Katis et al.	2005/0053033 A1	3/2005	Kelly et al.
8,849,927 B2	9/2014	Katis et al.	2005/0058070 A1	3/2005	Burghardt et al.
8,902,749 B2	12/2014	Katis et al.	2005/0076084 A1	4/2005	Loughmiller et al.
8,924,593 B2	12/2014	Katis et al.	2005/0086311 A1	4/2005	Enete et al.
8,948,354 B2	2/2015	Katis et al.	2005/0095981 A1 *	5/2005	Benco H04W 4/12 455/3.06
9,154,628 B2	10/2015	Katis et al.	2005/0102358 A1	5/2005	Gold et al.
9,178,916 B2	11/2015	Katis et al.	2005/0135333 A1	6/2005	Rojas
9,338,113 B2	5/2016	Katis et al.	2005/0144247 A1	6/2005	Christensen et al.
9,456,087 B2	9/2016	Katis et al.	2005/0160345 A1	7/2005	Walsh et al.
9,608,947 B2	3/2017	Katis et al.	2005/0202807 A1	9/2005	Ayyasamy
9,621,491 B2	4/2017	Katis et al.	2005/0207487 A1	9/2005	Monroe
9,634,969 B2	4/2017	Katis et al.	2005/0210394 A1	9/2005	Crandall et al.
9,674,122 B2	6/2017	Katis et al.	2005/0215228 A1	9/2005	Fostick et al.
9,742,712 B2	8/2017	Katis et al.	2005/0220137 A1	10/2005	Prigent et al.
9,762,861 B2	9/2017	Kalaboukis	2005/0237999 A1	10/2005	Shores et al.
9,800,528 B2	10/2017	Katis et al.	2005/0259682 A1	11/2005	Yosef et al.
2001/0000540 A1	4/2001	Cooper et al.	2005/0288101 A1	12/2005	Lockton et al.
2001/0025377 A1	9/2001	Hinderks	2006/0007943 A1	1/2006	Fellman
2001/0038610 A1	11/2001	Decker	2006/0023969 A1	2/2006	Lara et al.
2001/0043602 A1	11/2001	Brown	2006/0041815 A1	2/2006	Haymond
2001/0049745 A1	12/2001	Schoeffler	2006/0045038 A1	3/2006	Kay et al.
2001/0052019 A1	12/2001	Walters et al.	2006/0046758 A1	3/2006	Emami-Nouri et al.
2002/0006802 A1	1/2002	Saarela et al.	2006/0059199 A1	3/2006	Lappalainen et al.
2002/0016818 A1	2/2002	Kirani et al.	2006/0059267 A1	3/2006	Cugi et al.
2002/0032799 A1	3/2002	Wiedeman et al.	2006/0059342 A1	3/2006	Medvinsky et al.
2002/0067739 A1	6/2002	Wilkes et al.	2006/0062215 A1	3/2006	Lam
2002/0091848 A1	7/2002	Agresta et al.	2006/0080704 A1	4/2006	Le Huerou et al.
2002/0120666 A1	8/2002	Landsman et al.	2006/0093304 A1	5/2006	Bathey et al.
2002/0126817 A1	9/2002	Hariri et al.	2006/0107285 A1	5/2006	Medvinsky
2002/0128029 A1	9/2002	Nishikawa et al.	2006/0111130 A1	5/2006	Lee et al.
2002/0143959 A1	10/2002	El-Baze et al.	2006/0116167 A1	6/2006	Raviv
2002/0150094 A1	10/2002	Cheng et al.	2006/0121925 A1	6/2006	Jung
2002/0154745 A1	10/2002	Shtivelman	2006/0146822 A1	7/2006	Kolakowski et al.
2002/0159600 A1	10/2002	Weiner	2006/0160522 A1	7/2006	Jennings
2002/0184368 A1	12/2002	Wang	2006/0168003 A1	7/2006	Vau et al.
2003/0027566 A1	2/2003	Weiner	2006/0172754 A1	8/2006	Shin et al.
2003/0028632 A1	2/2003	Davis	2006/0176902 A1	8/2006	Bellordre
2003/0040301 A1	2/2003	Fukuzato	2006/0187897 A1	8/2006	Dabbs et al.
			2006/0189305 A1	8/2006	Ando et al.
			2006/0203802 A1	9/2006	Chou et al.
			2006/0211411 A1	9/2006	Haaramo et al.

US 10,511,557 B2

Page 4

(56)

References Cited

U.S. PATENT DOCUMENTS

(56)	References Cited			2008/0178251	A1	7/2008	Shin	
	U.S. PATENT DOCUMENTS			2008/0189295	A1	8/2008	Khedouri et al.	
				2008/0205444	A1	8/2008	Campbell et al.	
				2008/0231684	A1	9/2008	Underwood et al.	
2006/0212582	A1	9/2006	Gupta et al.	2008/0256255	A1	10/2008	Mordovskoi et al.	
2006/0212592	A1	9/2006	Gupta et al.	2008/0267377	A1	10/2008	Siegrist	
2006/0221174	A1	10/2006	Yang	2008/0273077	A1	11/2008	Cowherd	
2006/0221995	A1	10/2006	Berkman	2008/0288989	A1	11/2008	Zheng	
2006/0224748	A1	10/2006	Gupta et al.	2009/0003544	A1	1/2009	Katis et al.	
2006/0229934	A1	10/2006	Law	2009/0003545	A1	1/2009	Katis et al.	
2006/0232663	A1	10/2006	Gandhi et al.	2009/0003547	A1	1/2009	Katis et al.	
2006/0244588	A1	11/2006	Hannah et al.	2009/0003560	A1	1/2009	Katis et al.	
2006/0245367	A1	11/2006	Jeffery et al.	2009/0003563	A1	1/2009	Katis et al.	
2006/0248149	A1	11/2006	Kraft et al.	2009/0006609	A1	1/2009	Lindberg et al.	
2006/0251167	A1	11/2006	Van Der Schaar et al.	2009/0024743	A1	1/2009	Zhang	
2006/0253599	A1	11/2006	Monteiro et al.	2009/0037541	A1	2/2009	Wilson	
2006/0268750	A1	11/2006	Weiner	2009/0049140	A1	2/2009	Stoddard et al.	
2006/0274698	A1	12/2006	Twitchell	2009/0063698	A1	3/2009	Xu et al.	
2006/0274721	A1	12/2006	Flanagan	2009/0103689	A1	4/2009	Katis et al.	
2006/0276714	A1	12/2006	Holt et al.	2009/0124238	A1	5/2009	Wilson	
2006/0282544	A1	12/2006	Monteiro et al.	2009/0175211	A1	7/2009	Jakobsen	
2006/0288391	A1	12/2006	Puthiyedath	2009/0175425	A1	7/2009	Lee	
2006/0294259	A1	12/2006	Matefi et al.	2010/0005168	A1	1/2010	Williams et al.	
2007/0001869	A1	1/2007	Hunzinger	2010/0030864	A1	2/2010	Petry et al.	
2007/0002832	A1	1/2007	Sylvain	2010/0046535	A1	2/2010	Bugenhagen et al.	
2007/0006021	A1	1/2007	Nicholson et al.	2010/0074324	A1 *	3/2010	Qian	H04L 47/10 375/240.02
2007/0008884	A1	1/2007	Tang					
2007/0067407	A1	3/2007	Bettis et al.	2010/0199133	A1	8/2010	Katis et al.	
2007/0081622	A1	4/2007	Bruder et al.	2010/0255818	A1	10/2010	Bozionek et al.	
2007/0110046	A1	5/2007	Farrell et al.	2010/0279663	A1	11/2010	Wang et al.	
2007/0123267	A1	5/2007	Whinnett et al.	2011/0010459	A1	1/2011	Stokking et al.	
2007/0123284	A1	5/2007	Schliwa-Bertling et al.	2011/0019662	A1	1/2011	Katis et al.	
2007/0147263	A1	6/2007	Liao et al.	2012/0114108	A1	5/2012	Katis et al.	
2007/0150555	A1	6/2007	He et al.	2015/0035934	A1 *	2/2015	Chen	H04M 3/5315 348/14.02
2007/0155346	A1	7/2007	Mijatovic et al.					
2007/0168863	A1	7/2007	Blattner et al.	2015/0350270	A1 *	12/2015	Caras	H04L 51/10 709/203
2007/0177549	A1	8/2007	Lo et al.					
2007/0180032	A1	8/2007	Pearson	2016/0352666	A1	12/2016	Katis et al.	
2007/0182819	A1	8/2007	Monroe	2017/0237695	A1	8/2017	Katis et al.	
2007/0184868	A1	8/2007	Allen et al.	2017/0272489	A1	9/2017	Katis et al.	
2007/0189327	A1	8/2007	Konda	2018/0013704	A1	1/2018	Katis et al.	
2007/0190987	A1	8/2007	Vaananen					
2007/0192427	A1	8/2007	Berstis et al.					
2007/0195742	A1	8/2007	Erdman et al.					
2007/0207782	A1	9/2007	Tran					
2007/0207785	A1	9/2007	Chatterjee et al.	EP	1202531	5/2002		
2007/0226804	A1	9/2007	Somkiran et al.	GB	2418566	A	3/2006	
2007/0238472	A1	10/2007	Wanless	JP	09-261155		10/1997	
2007/0263575	A1	11/2007	Choe	JP	2001- 045560		2/2001	
2007/0268887	A1	11/2007	Schwartz	JP	2001-128133		5/2001	
2007/0271331	A1	11/2007	Muth	JP	2001-160858		6/2001	
2007/0288574	A1	12/2007	Koster	JP	2001-292090		10/2001	
2007/0294333	A1	12/2007	Yang et al.	JP	2002-044360		2/2002	
2007/0300007	A1	12/2007	Bulusu et al.	JP	2002-176510		6/2002	
2008/0000979	A1	1/2008	Poisner	JP	2002-199019		7/2002	
2008/0002621	A1	1/2008	Ginzburg et al.	JP	2002-199088		7/2002	
2008/0002691	A1	1/2008	Qi et al.	JP	2003-143237		5/2003	
2008/0025300	A1	1/2008	Lide et al.	JP	2003-174681		6/2003	
2008/0031250	A1	2/2008	Mehta et al.	JP	2003-209611		7/2003	
2008/0031448	A1	2/2008	Dang et al.	JP	2004-038575		2/2004	
2008/0062246	A1	3/2008	Woodworth et al.	JP	2004-201096		7/2004	
2008/0086700	A1	4/2008	Rodriguez et al.	JP	2005-509337		7/2005	
2008/0091804	A1	4/2008	Swanburg et al.	JP	2005-223650		8/2005	
2008/0091839	A1	4/2008	Mitchell et al.	JP	2005-244522		9/2005	
2008/0095173	A1	4/2008	Bugenhagen	JP	2005-278109		10/2005	
2008/0095338	A1	4/2008	Cosky	JP	2005-348192		12/2005	
2008/0109865	A1	5/2008	Su et al.	JP	2006-080919		3/2006	
2008/0115087	A1	5/2008	Rollin et al.	JP	2006-507765		3/2006	
2008/0117901	A1	5/2008	Klammer	JP	2006-166284		6/2006	
2008/0119210	A1	5/2008	Snyder et al.	JP	2006-287422		10/2006	
2008/0123623	A2	5/2008	Kurganov et al.	JP	2007-019767		1/2007	
2008/0123628	A1	5/2008	Everard	JP	2007-060016		3/2007	
2008/0134054	A1	6/2008	Clark et al.	JP	2007-110395		4/2007	
2008/0147910	A1	6/2008	Hibbard et al.	JP	2007-172264		7/2007	
2008/0155032	A1	6/2008	Toeroe	WO	WO 01/93503		12/2001	
2008/0163312	A1	7/2008	Faust et al.	WO	WO 02/11398		2/2002	
2008/0165707	A1	7/2008	Baird et al.	WO	WO 03/015384		2/2003	
2008/0165791	A1	7/2008	Degrazia	WO	WO 03/073642		9/2003	
2008/0168173	A1	7/2008	Munie et al.	WO	WO 2004/008336		1/2004	
				WO	WO 2004/049608		6/2004	

(56)

References Cited

FOREIGN PATENT DOCUMENTS

WO	WO/2006/028850	3/2006
WO	WO 2006/114673	11/2006
WO	WO 2007/007847	1/2007
WO	WO 2007/026320	3/2007
WO	WO 2007/036032	4/2007

OTHER PUBLICATIONS

"Aspera—Next Generation File Transport—Broadcasting & Entertainment Media," Asperasoft.com, http://www.asperasoft.com/en/industries/digital_media_10/Broadcast_Entertainment_Media_5, Downloaded on Sep. 22, 2009, 2 pages.

"Aspera—Next Generation File Transport—fasp technology overview" Asperasoft.com, http://www.asperasoft.com/en/technology/fasp_overview_1/fasp_technology_overview_1, Downloaded on Sep. 22, 2009, 2 pages.

"Aspera—Next Generation File Transport—fasp™ transfer times," Asperasoft.com, http://www.asperasoft.com/en/technology/fasp_transfer_times_14/fasp_transfer_times_14, Downloaded on Sep. 22, 2009, 1 page.

"Aspera—Next Generation File Transport—the fasp solution," Asperasoft.com, http://www.asperasoft.com/en/technology/fasp_solution_3/the_fasp_solution_3, Downloaded on Sep. 22, 2009, 3 pages.

"Aspera—Next Generation File Transport—the shortcomings of TCP file transfer," Asperasoft.com, http://www.asperasoft.com/en/technology/shortcomings_of_TCP_2/the_shortcomings_of_TCP_file_transfer_2, Downloaded on Sep. 22, 2009, 2 pages.

"Aspera fasp™ High Speed Transport—A Critical Technology Comparison," White Paper, Asperasoft.com, http://www.asperasoft.com/en/technology/white_papers_13/aspera_fasp_high_speed_transport_13, Downloaded on Sep. 22, 2009, 11 pages.

"Dirproxy," <http://home.pcisys.net/~tbc/hacks/dirproxy.htm>, Downloaded on Sep. 26, 2008, 1 page.

"Eudora," Answers.com, <http://www.answers.com/topic/eudora-e-mail-client>, Downloaded on Aug. 20, 2009, 4 pages.

"Palringo Brings First Push-to-Talk Application to the iPhone," RedOrbit.com, http://www.redorbit.com/news/technology/1525545/palringo_brings_first_push_totalk_application_to_the_iphone/index.html, Downloaded on Aug. 13, 2009, 2 pages.

"Protocol for Multimedia Application Text Conversion," International Telecommunication Union, Published Feb. 1998, 17 pages.

"Store and Forward," Wikipedia, the free encyclopedia, URL: http://en.wikipedia.org/wiki/Store_and_forward, Downloaded on Oct. 26, 2011, 2 pages.

"The Eudora Open Messaging Advantage," Qualcomm, 1997, Part No. 100-50030-1, 23 pages.

2nd Patent Examination Report from AU 2008270895, dated Nov. 1, 2012.

About.com, "Linux / Unix Command: talk," http://linux.about.com/od/commands1/blcmd11_talk.htm, Downloaded on Sep. 26, 2008, 2 pages.

Allen et al., "The P-Answer-State Header Extension to the Session Initiation Protocol for the Open Mobile Alliance Push to Talk over Cellular," URL: <http://tools.ietf.org/html/rfc4964>, Sep. 2007, 32 pages.

Amir et al., "An Overlay Architecture for High Quality VoIP Streams," IEEE Transactions on Multimedia, Publication Date: Dec. 2006, vol. 8, Issue:6, On pp. 1250-1262.

Anonymous: "VoiceEmotion", Jun. 3, 2006 (Jun. 3, 2006). XP55058210. Retrieved from the Internet: URL: <http://jweb.archive.org/web/20060603021611/http://www.voiceemotion.com/tutorial.htm> [retrieved on Apr. 2, 2013].

Anonymous: "VoiceEmotion", May 5, 2006 (May 5, 2006). XP55058207. Retrieved from the Internet: URL: <http://jweb.archive.org/web/20060505064512/http://www.voiceemotion.com/index.htm> [retrieved on Apr. 2, 2013].

Apple Inc., "iPhone User's Guide," http://manuals.info.apple.com/en_US/iPhone_User_Guide.pdf, Downloaded on Oct. 3, 2008, 154 pages.

Apple Inc., "iPhone: About Visual Voicemail," <http://www.support.apple.com/kb/HT1486>, Downloaded on Sep. 26, 2008, 3 pages.

Australian Office Action dated Nov. 12, 2013 from Australian Application No. 2009338743.

Azuri, Calvin, "Palringo Gold Launched on BlackBerry Smartphone", Apr. 20, 2009, <http://ivr.tmcnet.com/topics/ivr-voicexml/articles/54573-palringo-gold-launched-blackberry-smartphone.htm>, Downloaded on Aug. 13, 2009, 3 pages.

Baset et al., "An Analysis of the Skype Peer-to-Peer Internet Telephony Protocol," INFOCOM 2006. 25th IEEE International Conference on Computer Communications. Proceedings (2006), pp. 1-11.

Brandx.net, "Using Talk," <http://www.brandx.net/support/usingtelnet/talk.shtml>, Downloaded on Sep. 19, 2008, 2 pages.

Businesswire.com "LignUp 4.0 Delivers Industry's Most Comprehensive Suite of Communications Web Services," http://www.businesswire.com/portal/site/google/index.jsp?ndmViewId=news_view&newsId=20070430005498&newsLang=en, Downloaded on Nov. 21, 2008, 10 pages.

BusinessWire.com, "LignUp 4.0 Delivers Industry's Most Comprehensive Suite of Communications Web Services," Apr. 30, 2007, http://www.businesswire.com/portal/site/google/?ndmViewId=news_view&newsId=20070430005498&newsLang=en, Downloaded on Sep. 26, 2008, 6 pages.

Calore, Michael, "SpinVox Moves Into VoIP, Brings Voice-to-Text to Skype Users," Monkey Bites, <http://blog.wired.com/monkeybites/2007/08/spinvox-moves-i.html>, Downloaded on Oct. 3, 2008, 4 pages.

Cardei et al., "MAC Layer QoS Support for Wireless Networks of Unmanned Air Vehicles," Proceedings of the 37th Hawaii International Conference on System Sciences—2004, Jan. 5-8, 2004 pp. 9 pp.

Cerf et al., "A Protocol for Packet Network Intercommunication," Communications, IEEE Transactions on, vol. 22, Issue 5, May 1974 pp. 637-648.

Charny, Ben, "Nextel pushes new 'push to talk' features," URL: http://news.zdnet.com/2100-9584_22-134945.html, Mar. 18, 2004, 3 pages.

Chen et al., "An Adaptive Multimedia Transmission Protocol for Distributed Multimedia Applications," Proceedings of the 5th International Workshop on Multimedia Network Systems and Applications (MNSA'2003), in conjunction with the 23rd International Conference on Distributed Computing Systems (ICDCS-2003), 6 pages.

Chinese Office Action from 200880021723.2, dated May 4, 2012 with English translation.

Chuah et al., "Store-and-Forward Performance in a DTN," Vehicular Technology Conference, 2006. VTC 2006-Spring. IEEE 63rd, Publication Date: May 7-10, 2006, vol. 1, on pp. 187-191.

CNETNews.com, "Kadoink's phonecast lines officially open for texting," http://news.cnet.com/8301-17939_109-9829877-2.html, downloaded on Sep. 26, 2008, 1 page.

Dannen, Chris, "Technology: The Skype Mobile Phone Will Blow Your Mind," Dec. 18, 2007, URL: <http://www.fastcompany.com/blog/chris-dannen/lab/technology-skype-mobile-phone-will-blow-your-mind>, 2 pages.

Erwu et al., "Packet-late indication based (PLIB): adaptive jitter buffer," ACM International Conference Proceeding Series; vol. 58, Proceedings of the winter international symposium on Information and communication technologies, Cancun, Mexico, Session: Performance, reliability, and quality of service, pp. 1-5 Year of Publication: 2004.

European Search Report dated Jan. 6, 2012 in EP application 11174497.

Examination Report from Australian Application No. 2008270956, dated Feb. 7, 2012.

Examination Report from Australian application No. 2008270956, dated Jan. 12, 2011.

Extended EP Search Report in EP Application No. 11170723.8, dated Apr. 22, 2013.

(56)

References Cited

OTHER PUBLICATIONS

- Extended EP Search Report in EP Application No. 11179399.8, dated Apr. 11, 2013.
- Fall, Kevin, "A Delay-Tolerant Network Architecture for Challenged Internets," Feb. 2003, <http://www.dtnrg.org/docs/papers/IRB-TR-03-003.pdf>, 15 pages.
- FAQS.org, "RFC1644—TCP—TCP Extensions for Transactions Functional S," <http://www.faqs.org/rfcs/rfc1644.html>, Downloaded on Sep. 19, 2008, 26 pages.
- FluidVoice "Overview of Fluid Voice," <http://viral.media.mit.edu/wiki/tiki-index.php?page=FluidVoice>, Downloaded on Sep. 16, 2008, 2 pages.
- GrandCentral.com, "Call Record," http://www.grandcentral.com/howitworks/call_record, Downloaded on Sep. 26, 2008, 1 page.
- GrandCentral.com, "One Voicemail Box," http://www.grandcentral.com/home/one_voicemail, Downloaded on Sep. 26, 2008, 1 page.
- GrandCentral.com, "So Many Features, You Won't Believe it," <http://www.grandcentral.com/support/howitworks/>, Downloaded on Sep. 26, 2008, 1 page.
- GrandCentral.com, "Voicemail forwarding," http://www.grandcentral.com/howitworks/voicemail_forwarding, Downloaded on Sep. 26, 2008, 1 page.
- Henshall, Stuart, "HotRecorder—Record Skype Calls," Skype Journal, URL: http://skypejournal.com/blog/archives/2005/03/hotrecorder_rec.php, Mar. 25, 2005, 11 pages.
- HotRecorder.com, "FAQs," http://www.hotrecorder.com/music_support.asp, downloaded on Sep. 26, 2008, 1 page.
- HotRecorder.com, "Features," http://www.hotrecorder.com/music_features.asp, downloaded on Sep. 26, 2008, 1 page.
- HotRecorder.com, "Help," http://www.hotrecorder.com/music_help.asp, downloaded on Sep. 26, 2008, 3 pages.
- International Preliminary Report on Patentability in PCT/US2009/057893, dated Apr. 19, 2011.
- International Search Report from PCT/US2008/062049, dated Jan. 12, 2009.
- International Search Report from PCT/US2008/062941, dated Oct. 24, 2008.
- International Search Report from PCT/US2008/063117 dated Oct. 24, 2008.
- International Search Report in PCT/US2009/057893, dated Apr. 21, 2010.
- IRCHelp.org, "An IRC Tutorial," <http://www.irchelp.org/irchelp/irtutorial.html>, Downloaded on Sep. 26, 2008, 14 pages.
- Jabber.org, "FAQ," <http://www.jabber.org/web/faq>, Sep. 4, 2008, downloaded on Sep. 26, 2008, 2 pages.
- Jabber.org, "Main page," http://www.jabber.org/web/main_page, Sep. 2, 2008, downloaded on Sep. 26, 2008, 1 page.
- Jabber.org, "Products // Jabber Clients," <http://www.jabber.com/CE/JabberClients>, downloaded on Sep. 26, 2008, 1 page.
- Jabber.org, "Products // Jabber XCP // Benefits," <http://www.jabber.com/CE/JabberXCPBenefits>, downloaded on Sep. 26, 2008, 1 page.
- Jabber.org, "Products // JabberNow" <http://www.jabber.com/CE/JabberNow>, downloaded on Sep. 26, 2008, 1 page.
- Japanese Office Action dated Nov. 5, 2013 from Japanese Application No. 2011-547919.
- JustAnotheriPhoneBlog.com, "Nikotalkie—Just Talk, Don't Type," <http://justanotheriphoneblog.com/wordpress/2007/10/13/nikotalkie-just-talk-dont-type/>, Downloaded on Sep. 26, 2008, 10 pages.
- Kadoink.com, "Get a Widget," <http://www.kadoink.com/index.cfm?action=getWidgets>, Downloaded on Sep. 19, 2008, 3 pages.
- KillerStartups.com, "Kadoink.com—Mobilizing your Socializing," <http://www.killerstartups.com/Web20/kadoink-com-mobilizing-your-socializing>, Downloaded on Sep. 26, 2008, 3 pages.
- Korean Office Action in KR 10-2013-701111 dated Nov. 15, 2013, with English translation.
- Krishnan, et al., "EVRC-Wideband: The New 3GPP2 Wideband Vocoder Standard," IEEE International Conference on Acoustics, Speech and Signal Processing, 2007. ICASSP 2007, Publication Date: Apr. 15-20, 2007, vol. 2, on pp. II-333-11-336, Honolulu, HI.
- Krishnan, et al., "The SPINDLE Disruption-Tolerant Networking System," Military Communications Conference, 2007. MILCOM 2007. IEEE vol. , Issue , Oct. 29-31, 2007 pp. 1-7.
- Layton, Julia, "How Slingbox Works," Jan. 4, 2006, HowStuffWorks.com, <http://electronics.howstuffworks.com/slingbox.htm>, 9 pages.
- Liaw, Kim Poh, "Palringo launches its IM Software for Android Phones," Slashphone.com, Mar. 24, 2009, <http://www.slashphone.com/palringo-launches-its-im-software-for-android-phones-245111>, Downloaded on Aug. 13, 2009, 8 pages.
- LignUp.com, "LignUp Communications Applications Server," <http://www.lignup.com/platform/index.html>, Downloaded on Sep. 19, 2008, 1 page.
- Moren, Dan, "Palringo Brings Picture Messaging to Iphone," http://www.pcworld.com/article/149108/palringo_brings_picture_messaging_to_iphone.html, Downloaded on Aug. 13, 2009, 3 pages.
- Network Dictionary, "Instant Message (IM) Technology Overview," <http://www.networkdictionary.com/networking/im.php>, Downloaded on Sep. 16, 2008, 2 pages.
- Nikotalkie.com, "Nikotalkie—Home," <http://www.nikotalkie.com/>, Downloaded on Sep. 19, 2008, 2 pages.
- Nikotel.com, "Click-Pop-Talk WebStart Phone," <http://www.nikotel.com/nikotel-click-pop-talk-java-phone.html>, Downloaded on Sep. 19, 2008, 1 page.
- Notaras, George, "dirproxy IRC Proxy," <http://www.g-loaded.eu/2007/02/01/dirproxy-irc-proxy/>, Downloaded on Sep. 26, 2008, 4 pages.
- Office Action from EP Application No. 11179399.8 dated Feb. 3, 2014.
- Office Action in Chinese Application No. 200880016045.0, dated Jun. 25, 2012, with English translation.
- Office Action in Chinese Application No. 200880021553.8, dated May 17, 2012, with English translation.
- Office Action in Chinese Application No. 200880021664.9, dated May 3, 2012, with English translation.
- Office Action in Chinese Application No. 200880021725.1, dated May 17, 2012, with English translation.
- Office Action in Chinese Patent Application No. 200880016045.0 dated Feb. 25, 2013, with English Translation.
- Office Action in Chinese Patent Application No. 200880021664.9 dated Jan. 14, 2013, with English Translation.
- Office Action in EP 08747806.1, dated Apr. 27, 2010.
- Office Action in EP 08769254.7, dated Jul. 12, 2010.
- Office Action in EP Application No. 111637880 dated Feb. 24, 2015.
- Office Action in EP Application No. 11179399.8 dated Feb. 27, 2015.
- Office Action in Japanese Patent Application No. 2010-514894 dated Oct. 30, 2012, with English Translation.
- Office Action in Japanese Patent Application No. 2010-514896 dated Dec. 7, 2012, with English Translation.
- Office Action in Japanese Patent Application No. 2010-514896, dated Aug. 7, 2012, with English translation.
- Office Action in Japanese Patent Application No. 2010-514916 dated Dec. 18, 2012, with English Translation.
- Office Action in Japanese Patent Application No. 2013-073423 dated Feb. 10, 2014.
- Office Action in Japanese Patent Application No. JP 2013-073422 dated Mar. 10, 2014.
- Office Action in Japanese Patent Application No. JP 2013-081798 dated Apr. 8, 2014.
- Office Action in Korean Patent Application No. 10-2013-701111 dated May 12, 2014.
- Office Action in Korean. Patent Application No. 10-20107001868 dated Jan. 6, 2014.
- Office Action in Korean. Patent Application No. 10-20107001879 dated Jan. 6, 2014.
- Office Action in Korean. Patent Application No. 10-20107020536 dated Jan. 6, 2014.
- Palringo—Features, Palringo.com, <http://www.palringo.com/en/gb/features/>, Downloaded on Aug. 13, 2009, 1 page.
- Pash, Adam, "Consolidate Your Phones with GrandCentral," <http://techgroup.groups.vox.com/library/post/6a00cd978d0ef7f9cc00e398b8f7a0002.html>, Downloaded on Sep. 19, 2008, 5 pages.

(56)

References Cited

OTHER PUBLICATIONS

- Patel, Nilay, "Apple patent reveals data-to-voice translation system for cellphones," Jul. 28, 2007, URL: <http://www.engadget.com/2007/07/28/apple-patent-reveals-data-to-voice-translation-system-for-cellph/>, 5 pages.
- Patent Examination Report from AU 2008270895, dated Sep. 11, 2012.
- Paul, Ryan, "Gmail gets Google Talk integration," Arstechnica.com, <http://arstechnica.com/old/content/2006/02/6128.ars>, Downloaded on Aug. 20, 2009, 1 page.
- Peter, I., et al., "The Wavelet Stream: Progressive transmission of compressed light field data" In IEEE Visualization 1999 (pp. 69-72).
- Piecuch et al., "A Selective Retransmission Protocol for Multimedia on the Internet," In Proceedings of SPIE Multimedia Systems and Applications, Nov. 2000, Boston MA, USA, 12 pages.
- Qiao et al., "SCTP Performance Issue on Path Delay Differential," Lecture Notes in Computer Science, Springer Berlin / Heidelberg ISSN 0302-9743 (Print) 1611-3349 (Online) vol. 4517/2007, Wired/Wireless Internet Communications, pp. 43-54 Sunday, Jun. 24, 2007.
- Ramo et al., "On comparing speech quality of various narrow- and wideband speech codecs," Proceedings of the Eighth International Symposium on Signal Processing and Its Applications, 2005. Publication Date: Aug. 28-31, 2005, vol. 2, on pp. 603-606.
- Rey et al., "I-D ACTION:draft-ietf-avt-rtp-retransmission-09.txt," Aug. 5, 2003, <http://osdir.com/ml/ietf.avt/2003-08/msg00003.html>, Downloaded on Sep. 19, 2008, 2 pages.
- Ribbit.com, "Amphibian," <http://www.ribbit.com/everyday/>, Downloaded on Sep. 26, 2008, 1 page.
- Ribbit.com, "Enhanced Visual Voicemail," http://www.ribbit.com/everyday/tour/enhanced_visual_voicemail.php, Downloaded on Sep. 26, 2008, 2 pages.
- Ribbit.com, "What is Ribbit? Features," <http://www.ribbit.com/platform/features.php>, Downloaded on Sep. 26, 2008, 1 page.
- Ribbit.com, "What is Ribbit? Overview," <http://www.ribbit.com/platform/index.php>, Downloaded on Sep. 26, 2008, 1 page.
- Ribbit.com, "What is Ribbit? Voice Architecture," <http://www.ribbit.com/platform/architecture.php>, Downloaded on Sep. 26, 2008, 2 pages.
- Rosenberg, J. et al., "SIP: Session Initiation Protocol," The Internet Society, Jun. 2002, 270 pages.
- Rothermel et al., "An Adaptive Stream Synchronization Protocol," Lecture Notes in Computer Science; vol. 1018, Proceedings of the 5th International Workshop on Network and Operating System Support for Digital Audio and Video, pp. 178-189, Year of Publication: 1995.
- Saito et al., "IP Packet Loss Compensation Scheme with Bicast and Forwarding for Handover in Mobile Communications," 2006 IEEE 17th International Symposium on Personal, Indoor and Mobile Radio Communications, Sep. 2006, pp. 1-5, Helsinki.
- Sherman, Chris, "Google Integrates Chat with Gmail," Search Engine Watch, <http://searchenginewatch.com/3583121>, Feb. 7, 2006, Downloaded on Aug. 20, 2009, 2 pages.
- Skype.com, "Making calls is just the start," URL: <http://www.skype.com/features/>, Downloaded on Sep. 16, 2008, 2 pages.
- Spinvox.com, "Home Page," <http://www.spinvox.com/>, Downloaded on Sep. 26, 2008, 3 pages.
- Spinvox.com, "How Does it Work?," http://www.spinvox.com/how_it_works.html, Downloaded on Sep. 19, 2008, 2 pages.
- Swissvoice.net, "PSTN," http://www.swissvoice.net/www/htm_ww/08_technology/content_pstn.html, Downloaded on Sep. 19, 2008, 3 pages.
- Tektronix, "VOIP Technology Overview; Protocols, Convergence, Testing," <http://www.tektronix.com/voip>, May 12, 2006.
- The Jabber Extensible Communications Platform™, "Products // Jabber XCP," URL: <http://www.jabber.com/CE/JabberXCP>, Downloaded on Sep. 16, 2008, 2 pages.
- ThunkDifferent.com, "YouMail vs. Google Grandcentral Voice Mail Service," <http://thunkdifferent.com/2007/10/11/youmail-vs-google-grandcentral-voice-mail-service/>, Downloaded on Oct. 3, 2008, 6 pages.
- Trial Decision in JP Application No. 2010-514896, dated Feb. 4, 2014 with English Summary.
- VOIP-News.com, "Company Profile—LignUp," <http://www.voip-news.com/vendors/lignup/>, Downloaded on Oct. 3, 2008, 6 pages.
- VOIP-News.com, "Company Profile, LignUp," <http://www.voip-news.com/vendors/lignup/>, Downloaded on Dec. 5, 2008, 6 pages.
- WikiBooks, "Internet Technologies/IRC," http://en.wikibooks.org/wiki/Internet_Technologies/IRC, Downloaded on Sep. 19, 2008, 4 pages.
- Wikipedia—The Free Encyclopedia, "E-mail," <http://en.wikipedia.org/wiki/E-mail>, Downloaded on Sep. 19, 2008, 8 pages.
- Wikipedia—The Free Encyclopedia, "Eudora (email client)," [http://en.wikipedia.org/wiki/Eudora_\(e-mail_client\)](http://en.wikipedia.org/wiki/Eudora_(e-mail_client)), Downloaded on Aug. 20, 2009, 3 pages.
- Wikipedia—The Free Encyclopedia, "Google Talk," http://en.wikipedia.org/wiki/Google_Talk, Downloaded on Aug. 20, 2009, 8 pages.
- Wikipedia—The Free Encyclopedia, "Internet Relay Chat," http://en.wikipedia.org/wiki/Internet_Relay_Chat, Downloaded on Oct. 13, 2008, 11 pages.
- Wikipedia—The Free Encyclopedia, "Palringo," <http://en.wikipedia.org/wiki/Palringo>, Downloaded on Aug. 13, 2009, 1 page.
- Wikipedia—The Free Encyclopedia, "Push to Talk," http://en.wikipedia.org/wiki/Push_to_talk, Downloaded on Sep. 26, 2008, 3 pages.
- Wikipedia—The Free Encyclopedia, "Skype Protocol," <http://en.wikipedia.org/wiki/Skype>, Downloaded on Sep. 26, 2008, 4 pages.
- Wikipedia—The Free Encyclopedia, "Skype," <http://en.wikipedia.org/wiki/Skype>, Downloaded on Sep. 26, 2008, 7 pages.
- Wikipedia—The Free Encyclopedia, "Slingbox," <http://en.wikipedia.org/wiki/Slingbox>, Downloaded on Sep. 26, 2008, 4 pages.
- Wikipedia—The Free Encyclopedia, "Spinvox," <http://en.wikipedia.org/wiki/Spinvox>, Downloaded on Sep. 26, 2008, 1 page.
- Wikipedia—The Free Encyclopedia, "TiVo," <http://en.wikipedia.org/wiki/TiVo>, Downloaded on Sep. 16, 2008, 6 pages.
- Wikipedia—The Free Encyclopedia, "Visual Voicemail," http://en.wikipedia.org/wiki/Visual_voicemail, downloaded on Sep. 26, 2008, 1 page.
- Wikipedia encyclopedia definition "User Datagram Protocol" http://en.wikipedia.org/wiki/User_Datagram_Protocol, last modified Mar. 9, 2012.
- Written Opinion from PCT/US2008/062049, dated Jan. 12, 2009.
- Written Opinion from PCT/US2008/062941, dated Oct. 24, 2008.
- Written Opinion from PCT/US2008/063117, dated Oct. 24, 2008.
- Written Opinion in PCT/US2009/057893, dated Apr. 21, 2010.
- Wurmlin, S., et al. "3D Video Recorder: A System for Recording and Playing Free-Viewpoint Video" Computer Graphics forum vol. 22(2003), No. 2 pp. 181-193.
- Yavuz et al., "VoIP over cdma2000 1xEV-DO Revision A," IEEE Communications Magazine, Feb. 2006, pp. 88-95.
- Japanese Office Action dated Nov. 10, 2015 from Japanese Application No. 2014-261237.
- Japanese Office Action dated Jul. 26, 2016 from Japanese Application No. 2014-261237.
- Wikipedia, "Connectionless Communication", https://en.wikipedia.org/wild/Connectionless_communication, May 26, 2016.
- Decision of Rejection dated Jul. 10, 2013, from Chinese Application No. 200880016045.0.
- Notification of Reexamination dated Nov. 2, 2015, from Chinese Application No. 200880016045.0.
- Decision on Reexamination dated Mar. 31, 2016, from Chinese Application No. 200880016045.0.
- Chinese Office Action dated Jun. 21, 2016, from Chinese Application No. 200880016045.0.
- Chinese Office Action dated Feb. 17, 2013, from Chinese Application No. 200880021553.8.
- Chinese Office Action dated Sep. 11, 2013, from Chinese Application No. 200880021553.8.

(56)

References Cited**OTHER PUBLICATIONS**

Chinese Office Action dated Apr. 28, 2014, with English translation from Chinese Application No. 200880021553.8.
 Chinese Office Action dated Sep. 18, 2013, from Chinese Application No. 200980155405.X.
 Chinese Office Action dated Apr. 9, 2014, from Chinese Application No. 200980155405.X.
 Chinese Office Action dated Feb. 17, 2013, from Chinese Application No. 200880021725.1.
 Chinese Office Action dated Sep. 12, 2013, from Chinese Application No. 200880021725.1.
 Chinese Office Action dated Apr. 3, 2014, from Chinese Application No. 200880021725.1.
 Chinese Office Action dated Jul. 16, 2013, from Chinese Application No. 200880021664.9.
 Japanese Office Action (Hearing) dated Jun. 25, 2013 from Japanese Application No. 2010-514896.
 Japanese Office Action dated Aug. 5, 2014 from Japanese Application No. 2013-073423.
 Japanese Office Action (Decision of Rejection) dated Aug. 26, 2014 from Japanese Application No. 2013-081798.
 Australian Patent Examination Report dated Feb. 12, 2013 from Australian Application No. 2008270895.
 Australian Patent Examination Report dated Apr. 7, 2014 from Australian Application No. 2013201918.
 Australian Patent Examination Report dated May 27, 2014 from Australian Application No. 2013201918.
 Australian Patent Examination Report dated Apr. 21, 2015 from Australian Application No. 2013201918.
 Australian Patent Examination Report dated Apr. 30, 2014 from Australian Application No. 2013202611.
 Australian Patent Examination Report dated Oct. 19, 2012 from Australian Application No. 2008270959.
 Australian Patent Examination Report dated Aug. 24, 2012 from Australian Application No. 2008270959.
 Australian Patent Examination Report dated Aug. 30, 2012 from Australian Application No. 2008270967.
 European Office Action dated Sep. 8, 2009 from European Application No. 08747114.0.
 European Office Action dated Aug. 26, 2010 from European Application No. 08747114.0.
 European Search Report dated Apr. 11, 2013 from European Application No. 11163788.0.
 European Office Action dated Dec. 4, 2013 from European Application No. 11163788.0.
 European Office Action dated Feb. 9, 2016 from European Application No. 11163788.0.
 European Office Action dated May 4, 2016 from European Application No. 11163788.0.
 European Office Action dated Sep. 25, 2015 from European Application No. 11179399.8.
 European Office Action dated May 28, 2010 from European Application No. 08756317.7.
 European Office Action dated Nov. 11, 2010 from European Application No. 08756317.7.
 European Office Action dated Nov. 18, 2010 from European Application No. 08747806.1.
 European Office Action dated Apr. 13, 2012 from European Application No. 09804087.6.
 Canadian Office Action dated Mar. 12, 2014 from Canadian Application No. 2,837,950.

Canadian Office Action dated Nov. 18, 2013 from Canadian Application No. 2,682,184.
 Canadian Office Action dated Jan. 26, 2015 from Canadian Application No. 2,692,976.
 Canadian Office Action dated Aug. 19, 2015 from Canadian Application No. 2,691,814.
 Canadian Office Action dated Jan. 26, 2015 from Canadian Application No. 2,692,928.
 Canadian Office Action dated Nov. 13, 2014 from Canadian Application No. 2,746,734.
 Canadian Office Action dated Jan. 23, 2015 from Canadian Application No. 2,691,814.
 Korean Office Action dated Sep. 5, 2013 from Korean Application No. 10-2009-7020536.
 Korean Office Action dated Sep. 5, 2013 from Korean Application No. 10-2010-7001879.
 Korean Office Action dated Aug. 8, 2014 from Korean Application No. 10-2013-7011111.
 Korean Office Action dated Feb. 9, 2015 from Korean Application No. 10-2011-7019515.
 Korean Office Action dated Jun. 21, 2013 from Korean Application No. 10-2009-7026979.
 Korean Office Action dated Oct. 18, 2013 from Korean Application No. 10-2009-7026979.
 Korean Office Action dated Mar. 13, 2014 from Korean Application No. 10-2013-7011235.
 Korean Office Action dated Sep. 19, 2014 from Korean Application No. 10-2013-7011235.
 Korean Office Action dated Sep. 5, 2013 from Korean Application No. 10-2010-7001868.
 J. Bellamy: "Digital Telephony, 2nd Edition", In: "Digital Telephony, 2nd Edition", Jan. 1, 1991, John Wiley & Sons, New York, US, XP055264025, pp. 547 and 561.
 ITU-T Recommendation, T.140, "Series T: Terminals for Telematic Services Protocol for Multimedia Application Text Conversation", Feb. 1998.
 Shinsuke Suzuki, "Searching for the Path to a Destination IP Address—Connection Between Routing Control and Neighborhood Searches", Nikkei Network, Nikkei Business Publications, Inc. Oct. 22, 2000, vol. 7, pp. 165-169.
 Katis et al., U.S. Appl. No. 15/923,287, filed Mar. 16, 2018.
 Katis et al., U.S. Appl. No. 15/923,869, filed Mar. 16, 2018.
 Katis et al., U.S. Appl. No. 15/584,224, filed May 2, 2017.
 Katis et al., U.S. Appl. No. 15/937,361, filed Mar. 27, 2018.
 Katis et al., U.S. Appl. No. 15/710,627, filed Sep. 20, 2017.
 Katis et al., U.S. Appl. No. 15/615,406, filed Jun. 6, 2017.
 An Interactive and Cooperative VideoRecording on demand System over Mbone 1-6 pgs.
 Office Action in U.S. dated Dec. 18, 2017 from U.S. Appl. No. 15/584,224.
 Final Office Action in U.S. dated Apr. 20, 2018 from U.S. Appl. No. 15/584,224.
 Office Action in U.S. dated May 23, 2018 from U.S. Appl. No. 15/584,224.
 Office Action in U.S. dated May 7, 2018 from U.S. Appl. No. 15/923,287.
 Office Action in U.S. dated Jun. 4, 2018 from U.S. Appl. No. 15/937,361.
 Office Action in U.S. dated Aug. 10, 2018 from U.S. Appl. No. 15/923,869.
 Office Action in U.S. dated Jan. 10, 2019 from U.S. Appl. No. 15/923,869.

* cited by examiner




FIG. 1






FIG. 2A

FIG. 2A FIG. 2B



**FIG. 3**




FIG. 4A




FIG. 4B




FIG. 4C







FIG. 4D

**FIG. 5**

**FIG. 6**

**FIG. 7**









FIG. 8A


**FIG. 8B**


**FIG. 8C**

**FIG. 8D**

**FIG. 8E**

**FIG. 8F**

**FIG. 9A**

**FIG. 9B**






FIG. 9C

**FIG. 9D**












FIG. 9F


**FIG. 10**



**FIG. 11A**

**FIG. 11B**

**FIG. 11C**

**FIG. 11D****FIG. 11E**

**FIG. 11F**

**FIG. 12A****FIG. 12B**




FIG. 12C




FIG. 13A





FIG. 13B

MCMS-C




FIG. 13C





FIG. 13D


DEVICE 13 Running Client Application 12



140

FIG. 14A

SERVER 16 Running Server Application 78



150

FIG. 14B

**TELECOMMUNICATION AND MULTIMEDIA
MANAGEMENT METHOD AND APPARATUS****CROSS-REFERENCE TO RELATED
APPLICATIONS**

This application is a Continuation of U.S. application Ser. No. 15/923,287, filed on Mar. 16, 2018, which is a Continuation of Ser. No. 15/584,224, filed on May 2, 2017. U.S. application Ser. No. 15/584,224 is a Continuation of U.S. application Ser. No. 15/231,240, filed on Aug. 8, 2016 (now U.S. Pat. No. 9,674,122), which is a Continuation of U.S. application Ser. No. 14/799,528, filed Jul. 14, 2015 (now U.S. Pat. No. 9,456,087). U.S. application Ser. No. 14/799,528 is a Continuation of U.S. application Ser. No. 14/198,043, filed on Mar. 5, 2014 (now U.S. Pat. No. 9,154,628), which is a Continuation of U.S. application Ser. No. 13/555,034 (now U.S. Pat. No. 8,705,714), filed Jul. 20, 2012, which is a Continuation of U.S. application Ser. No. 12/037,256 (now U.S. Pat. No. 8,243,894), filed on Feb. 26, 2008, which is Continuation of Ser. No. 12/028,400 (now U.S. Pat. No. 8,180,029), filed on Feb. 8, 2008, which claims the benefit of U.S. Provisional Patent Application Nos. 60/937,552, filed Jun. 28, 2007 and 60/999,619, filed on Oct. 19, 2007. All of the foregoing applications are incorporated herein by reference in their entirety for all purposes.

BACKGROUND**Field of the Invention**

This invention pertains to telecommunications, and more particularly, to a telecommunication and multimedia management method and apparatus that enables users to review the messages of conversations in either a live mode or a time-shifted mode and to transition the conversation back and forth between the two modes, participate in multiple conversations and to archive the messages of conversations for later review or processing.

Description of Related Art

The current state of voice communications suffers from inertia. In spite of automated switching, high bandwidth networks and technologies such as satellites, fiber optics, Voice over IP (VoIP), wireless and cellular networks, there has been little change in how people use telephones. One is still required to pick up the phone, dial another party, wait for a connection to be made, and then engage in a full-duplex, synchronous conversation with the dialed party. If the recipient does not answer, no connection is made, and the conversation does not take place.

At best, a one-way asynchronous voice message may be left if the recipient has voice mail. The process of delivering the voice mail, however, is burdensome and time consuming. The caller is required to wait for the phone on the other end to stop ringing, transition into the voice mail system, listen to a voice message greeting, and then leave the message. Current voice mail systems are also inconvenient for the recipient. The recipient has to dial a code to access their voice mail, navigate through a series of prompts, listen to any earlier received voice messages in the queue, and then finally listen to the message of the sender.

Another drawback with typical voice mail systems is the inability to organize or permanently archive voice messages.

With some voice mail systems, a user may save a message, but it is automatically deleted after a predetermined period of time and lost forever.

Yet another problem with current voice mail systems is that a connection must be made between the caller and the voice mail system before a message can be left. If no connection is made, there is no way for the caller to leave a message.

Current telephone systems are based on relatively simplistic usage patterns: real-time live calls or disjointed voice mail messages, which are typically deleted as they are heard. These forms of voice communications do not capture the real power that can be achieved with voice communication or take advantage of the advances of network speed and bandwidth that is now available. Also, if the phone network is down, or is inaccessible, (e.g., a cell phone user is in an area of no coverage or the phone lines are down due to bad weather), no communication can take place.

In general, telephone based communications have not kept pace with the advances in text-based communications. Instant messaging, emailing, faxing, chat groups, and the ability to archive text messages, are all commonplace with text based communications. Other than voice mail, there are few existing tools available to manage and/or archive voice messages. In comparison, the tools currently available to manage telephone communications are primitive compared to text communications.

The corporate environment provides just one example of the weakness in current voice communication tools. There is currently no integrated way to manage voice communications across an organization as a corporate asset. Employees generally do not record or persistently store their phone conversations. Most business related voice communication assets are gone as quickly as the words are spoken, with no way to manage or store the content of those conversations in any manageable form.

As an illustrative example, consider a sales executive at a company. During the course of a busy day, the executive may make a number of calls, and close several sales, with customers over the phone. Without the ability to organize, store, and later retrieve these conversations, there is no way for the executive to resolve potential issues that may arise, such as recalling the terms of one deal versus another, or challenging a customer who disputes the terms of a previously agreed upon sale. If this executive had the ability to easily retrieve and review conversations, these types of issues could be easily and favorably resolved.

Current tactical radio systems, such as those used by the military, fire, police, paramedics, rescue teams, and first responders, also suffer from a number of deficiencies. Most tactical radio communication must occur through a "live" radio connection between the sender of a message and a recipient. If there is no radio connection between the two parties, there can be no communication. Urgent messages cannot be sent if either the sender or the receiver does not have access to their radio, or a radio circuit connection is not established. Tactical communications are therefore plagued with several basic problems. There is no way (i) to guarantee the delivery of messages, (ii) for a recipient to go back and listen to a message that was not heard in real time; (iii) to control the granularity of the participants in a conversation; (iv) for the system to cope when there is a lack of signal integrity for a live conversation. If a message is not heard live, it is missed. There are no tools for either the sender or a recipient to manage, prioritize, archive and later retrieve (i.e. time-shift) the messages of a conversation that were previously sent.

3

Yet another drawback with tactical radio communication systems is that only one message can be sent at a time per channel. Consider an example of a large building fire, where multiple teams of fire fighters, police and paramedics are simultaneously rescuing victims trapped in the building, fighting the fire, providing medical aid to victims, and controlling bystanders. If each of the teams is using the same channel, communications may become crowded and chaotic. Transmissions get "stepped on" when more than one person is transmitting at the same time. Also there is no way to differentiate between high and low priority messages. A team inside the burning building fighting the fire or rescuing trapped victims should have a higher priority over other teams, such as those controlling bystanders. If high priority messages are stepped on by lower priority messages, it could not only hamper important communications, but could endanger the lives of the fire fighters and victims in the building.

One possible solution to the lack of ability to prioritize messages is to use multiple channels, where each team is assigned a different channel. This solution, however, creates its own set of problems. How does the fire chief determine which channel to listen too at any point in time? How do multiple teams communicate with one another if they are all on different channels? If one team calls for urgent help, how are other teams to know if they are listening to other channels? While multiple channels can alleviate some issues, it can also cause confusion, creating more problems than if a single channel is used.

The lack of management tools that effectively prioritize messages, that allow multiple conversations to take place at the same time, that enable the time-shifting of messages to guarantee delivery, or that support archiving and storing conversations for later retrieval and review, all contribute to the problems associated with tactical radios. In first responder situations, such as with the military, police, and fire, effective communication tools can literally mean the difference between life and death, or the success or failure of a mission. The above burning building example is useful in illustrating just some of the issues with current tactical radio communications. Similar problems exist with the military, police, first responders and others who use tactical communications.

With packet-based networks, commonly used protocols include Transmission Control Protocol (TCP) and User Datagram Protocol (UDP). UDP offers the advantage of fast delivery of data, but at the expense of completeness. Packets may be dropped in transit and not available when attempting to render the data as soon as possible at the destination. In spite of the shortcomings, UDP is the standard for Voice over Internet Protocol (VoIP) transmissions due to its speed attributes. On the other hand TCP does guarantee the delivery of perfect (i.e., an exact copy of the transmitted data) data, but at the expense of latency. All packets are delivered, regardless of how long it takes. This delay makes TCP impractical for use with "live" phone calls. Currently there are no known protocols that offer the performance advantages of both TCP and UDP, where "good enough" media can be transmitted for rendering as soon as possible, with the eventual delivery of a perfect copy of the media. Also there is no protocol that determines how much information should be sent over the network based on the presence of recipients on the network and their intentions to render the data either live or in a time-shifted mode. In addition, other factors commonly considered, such as network latency, network degradation, packet loss, packet damage, and general bandwidth conditions, are used in determining how much data to

4

transmit. Prior art systems, however, do not consider the presence and intentions of recipients. As a result, the default assumption is that the data is rendered by the recipient in real time. When a recipient is not going to render data immediately, these prior art systems unnecessarily use bandwidth when it is not needed, degrading the overall performance of the network.

For the reasons recited above, telephone, voicemail and tactical voice communications systems are inadequate. An improved voice and media communication and management system and method, and improvements in delivering voice and other media over packet-based networks, is therefore needed.

SUMMARY OF THE INVENTION

The above-described problems are solved by a communication application, method and apparatus that supports new modes of engaging in conversations and/or managing multiple conversations using a variety of media types, such as voice, video, text, location, sensor information, and other data. Users can engage in conversations by sending messages to designated recipients. Depending on preferences and priorities, the recipient(s) might participate in the conversation in real time, or they might simply be notified that the message is ready for retrieval. In the latter case, the recipient participates in the conversation in a time-shifted mode by reviewing and replying to the recorded message at their convenience.

Users are empowered to conduct communications in either: (i) a near-synchronous or "live" conversation, providing a user experience similar to a standard full duplex phone call; or (ii) in a series of back and forth time-delayed transmissions (i.e., time-shifted mode). Further, users engaged in a conversation can seamlessly transition from the live mode to the time-shifted mode and back again. This attribute also makes it possible for users to engage in multiple conversations, at the same time, by prioritizing and shifting between the two modes for each conversation. Two individuals using the system can therefore send recorded voice messages back and forth to each other and review the messages when convenient, or the messages can be sent at a rate where they essentially merge into a live, synchronous voice conversation. This new form of communication, for the purposes of the present application, is referred to as "Voxing."

When you "Vox" someone, the conversation consists of a series of discrete recorded messages, which are recorded in a number of locations, which may include the encoding device of the sender, (e.g. a phone or computer), servers on multiple transmission hops across the network, and the receiver's rendering device. Unlike a standard phone call or voice mail, the system provides the following features and advantages: (i) the conversation can transition between live and time-shifted or vice versa; (ii) the discrete messages of the conversation are semantically threaded together and archived; (iii) since the messages are recorded and are available for later retrieval, attention can be temporarily diverted from the conversation and then the conversation can be later reviewed when convenient; (iv) the conversation can be paused for seconds, minutes, hours, or even days, and can be picked up again where left off; (v) one can rejoin a conversation in progress and rapidly review missed messages and catch up to the current message (i.e., the live message); (vi) no dedicated circuit is needed for the conversation to take place, as required with conventional phone calls; and (vii) lastly, to initiate a conversation, one can

5

simply begin transmitting to an individual or a group. If the person or persons on the other end notice that they are receiving a message, they have the option of reviewing and conducting a conversation in real time, or reviewing at a later time of their choice.

The communication media management system also supports new modes of optimizing the transmission of data over a network. The system actively manages the delivery of payloads to a recipient engaged in a conversation in real time when network conditions are less than ideal. For example when network conditions are poor, the system intentionally reduces the quality of the data for transmission to the point where it is "good enough" to be rendered upon receipt by the recipient, allowing the real time participation of the conversation. The system also guarantees the eventual delivery of an "exact" copy of the messages over time. The system and method therefore provides the advantages of both speed and accuracy. The utilization of network bandwidth is optimized by making tradeoffs between timeliness and media quality, using the presence and intentions of whether or not recipient(s) intend to review the message immediately in real time, as well as measures of network latency, network degradation, packet loss or damage, and/or current bandwidth conditions.

It should be noted that the messages of conversations may contain voice only or voice, video and other data, such as sensor information. When the messages are reviewed, they are listened to or visually reviewed, or a combination thereof, depending on the type of media contained in the messages. Although as of the filing of the present application, most conversations are voice only, it is intended that the communication system and method described herein broadly includes conversations including multiple media types, such as voice and video for example.

BRIEF DESCRIPTION OF THE DRAWINGS

The invention may best be understood by reference to the following description taken in conjunction with the accompanying drawings, which illustrate specific embodiments of the invention.

FIG. 1 is a diagram of the architecture of the communication and media management system of the invention.

FIGS. 2A and 2B illustrate a block diagram of a Client running on a Device in the communication and management system of the invention.

FIG. 3 is a block diagram of a Server used in the communication and media management system of the invention.

FIGS. 4A through 4D illustrate various embodiments of data payloads used in the communication and management system of the invention.

FIG. 5 is a diagram illustrating data being transmitted over a shared IP network in accordance with the invention.

FIG. 6 is a diagram illustrating data being transmitted over a circuit based network in accordance with the invention.

FIG. 7 is a diagram illustrating data being transmitted across both a cellular network and the Internet in accordance with the invention.

FIGS. 8A through 8F are a series of flow diagrams illustrating a store and stream function of the communication and management system of the invention.

FIGS. 9A through 9C are flow diagrams illustrating the operation of a Payload Quality Manager (PQM) and FIGS.

6

9D through 9F are flow diagrams illustrating the Data Quality manager (DQM), both used by the Clients and Servers of the invention.

FIG. 10 is an exemplary device having a graphical user interface that may be used with the system of the invention.

FIGS. 11A through 11F are diagrams illustrating multiple conversation management (MCMS) features of the invention.

FIGS. 12A through 12C are diagrams illustrating the multiple conversation management system-consecutive (MCMS-C) features of the invention.

FIGS. 13A through 13D illustrate a series of diagrams detailing the operation of the invention.

FIGS. 14A and 14B are block diagrams that illustrate the hardware used for running the Client and Server applications of the invention.

It should be noted that like reference numbers refer to like elements in the figures.

DETAILED DESCRIPTION OF SPECIFIC EMBODIMENTS

The invention will now be described in detail with reference to various embodiments thereof as illustrated in the accompanying drawings. In the following description, specific details are set forth in order to provide a thorough understanding of the invention. It will be apparent, however, to one skilled in the art, that the invention may be practiced without using some of the implementation details set forth herein. It should also be understood that well known operations have not been described in detail in order to not unnecessarily obscure the invention.

A. Functional Overview

An improved voice and other media communication application, method and apparatus is disclosed which provides one or more of the following features and functions:

- i. enabling users to participate in multiple conversation types, including live phone calls, conference calls, voice messaging, consecutive or simultaneous communications;
- ii. enabling users to review the messages of conversations in either a live mode or a time-shifted mode (voice messaging);
- iii. enabling users to seamlessly transition a conversation between a synchronous "live" mode and a time shifted mode;
- iv. enabling users to participate in conversations without waiting for a connection to be established with another participant or the network. This attribute allows users to begin conversations, participate in conversations, and review previously received time-shifted messages of conversations even when there is no network available, when the network is of poor quality, or other participants are unavailable;
- v. enabling the system to save media payload data at the sender and, after network transmission, saving the media payload data at all receivers;
- vi. enabling the system to organize messages by threading them sequentially into semantically meaningful conversations in which each message can be identified and tied to a given participant in a given conversation;
- vii. enabling users to manage each conversation with a set of user controlled functions, such as reviewing "live", pausing or time shifting the conversation until it is convenient to review, replaying in a variety of modes (e.g., playing faster, catching up to live, jump to the head of the

- conversation) and methods for managing conversations (archiving, tagging, searching, and retrieving from archives);
- viii. enabling the system to manage and share presence data with all conversation participants, including online status, intentions with respect to reviewing any given message in either the live or time-shifted mode, current attention to messages, rendering methods, and network conditions between the sender and receiver;
 - ix. enabling users to manage multiple conversations at the same time, where either (a) one conversation is current and all others are paused; (b) multiple conversations are rendered consecutively, such as but not limited to tactical communications; or (c) multiple conversations are active and simultaneously rendered, such as in a stock exchange or trading floor environment.
 - x. enabling users to store all conversations, and if desired, persistently archive them in a tangible medium, providing an asset that can be organized indexed, searched, transcribed, translated and/or reviewed as needed;
 - xi. enabling the system to provide real time call functionality using a best-efforts mode of message delivery at a rate “good enough” for rendering as soon as possible (similar to UDP), and the guaranteed eventual delivery of exact copies of the messages as transmitted by requesting retransmission of any missing or defective data from the originally saved perfect copy (similar to TCP); and
 - xii. enabling the system to optimize the utilization of network bandwidth by making tradeoffs between timeliness and media quality, using the presence and intentions of the recipient(s) (i.e., to either review the media in real-time or in a time-shifted mode), as well as measures of network latency, network degradation, packet loss or damage, and/or current bandwidth conditions.

In various embodiments, some or all of the numerous features and functions listed above may be implemented. It should be understood, however, that different embodiments of the invention need not incorporate all of the above listed features and functions.

B. Glossary

Prior to explaining the details of the invention, it is useful to define some of the terms and acronyms used throughout the written description. This glossary of terms is organized into groups of System Components, Media, Media Management, People and Conversation Management.

B.1. System Components

Client: A Client is the user application in the communication system, which includes a user interface, persistent data storage, and “Voxing” functionality. Users interact with the Client application, and the Client application manages all communications (messages and signals) and payload (Media) transfers that are transmitted or received over a network. The Client supports encoding of media (e.g., the capturing of voice, video, or other data content) and the rendering of media and supports security, encryption and authentication as well as the optimization of the transmission of data across the network. A Client may be used by one or multiple Users (i.e., multi-tenant).

Device: A physical device that runs the Client application. A User may be actively logged into a single Device or multiple Devices at any given point of time. In various embodiments, a Device may be a general-purpose computer, a portable computing device, a programmable phone, a programmable radio, or any other programmable communication device.

Servers: A computer node on the communication network. Servers are responsible for routing Messages sent back and forth between Users over the network and the persistent storage and archiving of Media payloads. Servers provide routing, transcoding, security, encryption and authentication and the optimization of the transmission of data across the network.

B.2. Media

Message: An individual unit of communication from one User to another. Each Message consists of some sort of Media, such as voice or video. Each Message is assigned certain attributes, including: (i) the User sending the message; (ii) the Conversation it belongs to; (iii) an optional or user created Importance Tag; (iv) a time stamp; and (v) the Media payload.

Media: Audio, video, text, position, sensor readings such as temperature, or other data.

Conversation: A thread of Messages (identified, persistently stored, grouped, and prioritized) between two or more Users on their Devices. Users generally participate in a Conversation using their Devices by either Reviewing Messages in real time or in a time-shifted mode, or creating and sending Messages of a Conversation as desired. When new Messages are created, they either define a new Conversation, or they are added to an existing Conversation.

Head of a Conversation: The most recent Message of a conversation that has been encoded by the most recent speaker. It is where a User is positioned in a Conversation when reviewing “live” or where one jumps to if the “Jump To Live” feature is used.

Multiple Conversation Management System or MCMS: An application that runs as part of a Client application, which enables a User to engage in multiple Conversations using a variety of Media types. With the MCMS application, a User selects one Conversation among the multiple Conversations as current, where only the Messages of current conversation are rendered. For the selected current Conversation, the User may transition from a series of back and forth Messages in time-shifted mode to near-synchronous “live” mode, similar to a standard telephone conversation, and back again. The Messages of the non-selected Conversations are in a paused state. Messages associated with the non-selected Conversation will accumulate if others are still participating in those Conversations. The User may selectively transition the current Conversation among the multiple Conversations and Review the accumulated Messages of the selected current Conversation.

Multiple Conversation Management System-Consecutive or MCMS-C: Similar to MCMS, with the added feature of rendering and enabling Users to manage and participate in multiple Conversations consecutively through a hierarchical system of Priorities and time-shifting, which are automatically managed by the system. The MCMS-C application allows the Messages of consecutive Conversations to be rendered in a prioritized order, as opposed to MCMS where only the Messages of the currently selected Conversation are rendered. MCMS-C is particularly applicable in situations where it is important that the Messages of the consecutive Conversations are rendered, in the prioritized order, and/or the receipt of all Messages, even those belonging to lower priority Conversations, is more important than receiving the Messages in real-time. Examples of situations where MCMS-C may be suitable include, but are not limited to, hospitals, taxi fleet management, or tactical communications.

Multiple Conversation Management System-Simultaneous or MCMS-S: Similar to MCMS, with the added feature

of enabling With MCMS-S, multiple Conversations are selected for simultaneous rendering, as opposed to MCMS where the Messages of only the selected current Conversation are rendered. The MCMS-S application is particularly applicable in situations where a User is listening to multiple Conversations at the same time, such as a trader listening to multiple brokers on different exchanges and periodically sending trading requests to one or multiple of them simultaneously. MCMS-S may also be suitable for tactical communications as well.

Priority: The mechanism through which the system determines which Message to render next when a User is participating in MCMS-C. Priority is automatically managed by the system. A User can set default Priorities, or a predetermined set of system Priorities may be used. In the event of a conflict, where more than one Message is ready to be rendered at the same time, the system resolves the conflict at least partly based on Priority, to determine what Message to render immediately and what Message to time shift.

Tags: a set of attributes a User or the system may assign to a Conversation or a message, such as a topic (a company name), a directive ("action items"), an indicator ("conversation summary"), or any other label by which one might want to search or organize the data.

Importance Tags: A special Message attribute that enables a sender to specify when a Message is to be rendered, regardless of other Priority settings. An "urgent" Importance tag will override other Priorities for example. This feature is critical for tactical systems, though any system can be configured to use or disable this feature.

Packet: Any unit of binary data capable of being routed through a computer network. Each packet consists of header (meta data) and payload (media data). Includes standard packet protocols such as, but not limited to, Internet Protocol (IP), EvDO, UMTS or any other packet-based network, either radio, fiber optic, or wired.

Header or Packet Header: The portion of a packet that describes the packet; the meta data concerning the payload, its encoding type and destination.

Vox packet: A proprietary packet that enables the system and method to further refine and optimize the delivery of Messages, Media and other signaling information.

Media Payload (or Payload): The actual Media portion of a Packet.

B.3. Media Management

Time Shift Delay (TSD): The amount of time between the arrival of a Vox Packet and the rendering of the Packet on a Device. The TSD must exceed the Minimum Time Shift Delay. The TSD is typically determined by the User's behavior in choosing to review the Messages of a Conversation some time after receipt.

Minimum Time Shift Delay (MTSD): The time shift delay enforced by the Client to allow for jitter processing using jitter buffer techniques. This causes the system to delay rendering until an adequate number of the packets have arrived to create a usable media stream. The system will typically adaptively adjust the MTSD over time to compensate for variable conditions in the network.

Rendering: Delivering a Media stream to a User in a form suitable for User consumption (e.g., voice, text, graphic display, video, or a combination thereof).

Mixing: The Rendering of one or more Media streams. For example, the Media stream from two Participants of a Conversation may be Mixed when Rendered, creating a User experience similar to a conversation where multiple people are speaking at the same time.

Encoding: The process of translating Media either created by a User (such as voice or video) or otherwise originating on a Device (such as GPS or other sensor data), and converting the media into digital data to be processed by a Client.

Adaptive Jitter Buffer: Jitter buffers or de-jitter buffers are used to counter jitter (i.e., either the arrival of out of sequence packets or the delayed arrival of packets) introduced by packet switched networks, so that the continuous rendering of audio (or video) signals transmitted over a network can be performed without disruption. The data is stored in a buffer before Rendering to allow a reasonably sized buffer of Media to arrive. The Media may be rendered before all the Packets are received, trading off quality for currency. An Adaptive Jitter Buffer is capable of dynamically changing its size to optimize the delay/quality tradeoff.

Persistent Infinite Message Buffer (PIMB): The PIMB is a storage management system for the storage of time-based Media that performs both the de-jittering of "live" data and the storage and retrieval of archive data. The PIMB further includes the additional attributes of potentially infinite and persistence storage of Media. The PIMB maintains "exact" or full copies of Vox Packets of a Message and Conversations at some or all Participant Devices and/or Servers.

Packet Loss Compensation or Concealment (PLC): During Rendering of a Media stream, the PLC component compensates for missing Packets, interpolating the results to present the stream to a reviewer. Missing Packets may be rendered as silence, or information from adjacent Packets may be used to present an interpolated sound or image. The particular method to be used will be dependent on the media, Codescs in use, and other generally known parameters.

B.4. People

User: A person who is authorized to use the system.

Contact: A record of either a User or non-user of the system. Users typically engage in Conversations with members on their list of Contacts. A non-user is a user that accesses or uses the system using a legacy phone, radio or other non-Client 12 enabled device.

Group: The association of multiple Contacts. Contacts may be selectively added or deleted from a Group. When a Conversation takes place among a Group, all the members of the Group may or may not participate.

Channel: Typically used for tactical communication systems. A Channel is similar to a Group in that it associates multiple Contacts with the Channel.

Participant: A person who is identified as a member of a Conversation. Could be a User or a non-User participant.

B.5. Conversation Management

Time Shifting: Time shifting is the ability to play any Message at any time after it has been received as determined by the User-recipient. By Time-Shifting, a User may Review a Message: (i) immediately on demand by Rendering immediately after the MTSD; or (ii) time-shifted in a mode of reviewing the Message upon the discretion of the User; (iii) from the archive for searching, reconstructions, etc. of old Conversations; (iv) after a delayed period of time to accommodate the Reviewing of other higher Priority Messages (or Conversations) that need to be reviewed first; (v) and/or repeatedly if necessary for the Message to be reheard and understood. In other words, Time Shifting is the ability of a user to render a Message at any time after the system imposed MTSD.

Reviewing: Listening, viewing, reading or otherwise observing the Media content in Messages. Reviewing may take place in either a near synchronous real-time "live mode" or the time-shifted mode.

11

Intention: Either (i) a User-defined attribute capturing whether the User wants to Review the Messages of a Conversation either as soon as possible or Review the Messages in a time-shifted mode; (ii) implied by a User's behavior; or a combination of (i) and (ii).

Attention: A user attribute capturing whether the User is Reviewing the Messages of a given Conversation at the moment.

Catch Up To Live (CTL): A rendering mode that allows a User, who is not at the Head of a Conversation, to Review previous Messages more quickly to "Catch Up To Live" (i.e., the Head of the Conversation). The CTL feature may use any of a number of catch up techniques, such as the faster replay of Messages, the removal of gaps in the Media of the Messages, removal of hesitation particles, etc. When the User has caught up to live, the system seamlessly flows into the live Conversation. This is a very useful feature with conference calls, for example, in situations where a User needs to temporarily shift their attention away from the Conversation, but wishes to hear the entire Conversation upon their return.

Catch Up Mode: A user-configured or pre-configured mode that determines how the CTL process will catch-up (i.e., replay faster, remove silence, and hesitation particles, or a combination thereof).

Jump To Live (JTL): This feature allows a user to jump from their current position to the Head of a Conversation. A user will typically use the JTL feature when they do not want to Review all of the Messages between their current position in the Conversation and the Head. When the JTL feature is implemented, the user skips over any intervening Messages and starts Rendering the "live" Messages at the head of the Conversation.

MCMS Participant Attributes: A set of attributes, either defined by a User, interpreted by the system from the User's behaviors, assigned by an administrator, or a combination thereof, which define the Intention, Attention, Priority, and rendering preferences of a receiver for a given Conversation. The attributes include, but are not limited to: (i) the Intention of when a receiver would like to render to the Messages of the Conversation. Possible Intention values include: "now", "time-shifted", "Catch Up To Live" (CTL), "paused", and "never"; (ii) Catch Up Mode, which is a configuration setting which determines how the CTL process should catch the receiver up to live (e.g., play faster, skip silence gaps or hesitations, or play at normal speed); (iii) Time Shift Delay (TSD), which defines how far the receiver's current position in the conversation is from the Head of the Conversation, and (iv) the Priority of the Message with regard to the receiver's other Conversations.

C. System Architecture

Referring to FIG. 1, a block diagram of the telecommunication and media management system according to one embodiment of the invention is shown. The system 10 includes a plurality of Clients 12₁ through 12_n, running on Devices 13₁ through 13_n, respectively. The Devices 13 communicate with one another over a communication services network 14, including one or more Servers 16. One or more networks 18₁ through 18_n, is provided to couple the plurality of Devices 13₁ through 13_n to the communication services network 14. In various embodiments, the networks 18 may be the Public Switched Telephone Network (PSTN), a cellular network based on CDMA or GSM for example, the Internet, a tactical radio network, or any other communication network, or a combination thereof. The communication

12

services network 14 is a network layer on top of or otherwise in communication with the various networks 18₁ through 18_n. In various embodiments, the network layer 14 is either heterogeneous or homogeneous. Clients 12₁ through 12_n communicate with one another and with Servers 16 over the networks 18₁ through 18_n and network 14 using individual message units referred to as "Vox packets", which are described in detail below.

D. Client Architecture

Referring to FIGS. 2A and 2B, a block diagram of a Client 12 running on a Device 13 is illustrated. As illustrated in FIG. 2A, the Client 12 includes Multiple Conversation Management System (MCMS) application 20, a rendering and encoding module 21, and an MCMS applications database 22. As illustrated in FIG. 2B, the Client 12 further includes a Store and Stream (SAS) module 24 with a Persistent Infinite Message Buffer (PIMB) reader 26, a PIMB writer 28, PIMB database 30, a data and network quality (DNQS) store 32, and Media driver and encoder hardware 34. The MCMS application 20 and the Store and Stream module 24 communicate with one another through message handling modules 25a and 25b respectively. The Client 12 further includes an authentication-encryption-security module 40 and a communication protocol module 44.

The module 40 provides authentication, encryption and security services during the transmission and receipt of "Vox" packets to and from the Client 12. The communication protocol module 44 encapsulates Vox packets into the native packets used by the underlying network 18 connected to the Device 13 running the Client 12 when transmitting data and de-encapsulating Vox packets from the native packets when receiving data. With the modules 40 and 44, multi-party end-to-end authentication, encryption and security is provided between Clients 12. Messages are authenticated, encrypted and secured across the networks 18₁ through 18_n and network 14, from a first sending Device 13 to second receiving Device 13.

D.1.1. The MCMS Database

The database 22 stores and manages the persistent meta data for a number of entities in the system 10, including Contacts and Participants, Conversations and Messages (live and stored), and default Priorities, and information regarding the Servers 16. In addition, the MCMS database 22 stores the moment-to-moment operational data of a User's Conversations, presence, and status, as well as that of all the Participants conversing with the User or on the User's Contact list. For example, with regard to Conversations and Messages, the database 22 keeps track of status information, such as what Messages of a Conversation a User has or has not Reviewed, Priorities, and Catch Up To Live status for each Conversation in which the Client 12 is a Participant, the presence and status of all Participants, and other network and other system management data.

D.1.2. The MCMS Application

MCMS application 20 supports the different Voxing modes of engaging in conversations and/or managing multiple conversations using a variety of media and data types (voice, video, text, location, data, etc.). Users engage in Conversations by sending Messages to designated recipients using their Client 12 enabled Devices 13. Depending on preferences and Priorities, the recipient might Review the Message in real time, or they might simply be notified that the Message is ready for Reviewing. Users can transition from a series of back and forth Messages, which are

13

Reviewed in a time-shifted (or voice messaging) mode or in a near synchronous, full duplex conversation (similar to standard “live” phone calls) and then back to voice messaging again. The MCMS application 20 allows a User to control their interactions with their most important Conversations in real-time without missing any Messages in other ongoing Conversations. For example, the MCMS application 20 notifies a User of urgent or high priority communications from a Conversation that they are not currently Reviewing. MCMS application 20 also enables all Messages from all Conversations to be stored for later retrieval so they can be reviewed at any time.

In accordance with various embodiments, there are several different operational modes of the MCMS application 20, including MCMS-Consecutive (MCMS-C) and MCMS-Simultaneous (MCMS-S), which support the consecutive and simultaneous rendering of Messages respectively. Each of these embodiments is described in more detail below. Unless specifically specified, the term “MCMS” is intended to generally mean the MCMS application 20, which includes the aforementioned different modes.

The MCMS application 20 is a multi-tiered architecture that includes a number of modules and services. The modules and services include the MCMS Database Module 20a, the SAS Services Module 20b, the Messaging and Signaling Services Module 20c, the User Interface Application Programming Interface (API) 20d, the User Interface Module 20e, the Conversations/Messages Management Services 20f, the Priorities Services 20g, the Contacts Service 20h, the Presence/Status Services 20i, and the Messages/Signals Services 20j.

D.1.2.1 The MCMS Database Module

The MCMS database module 20a is a service module that manages all function calls necessary for the MCMS application 20 to access the MCMS database 22.

D.1.2.2 The SAS Services Module

The SAS Services module 20b includes a set of function calls that enable communication and coordination between the MCMS application 20 and the Store and Stream module 24, and which are passed back and forth through the message handling modules 25a and 25b respectively. The set of function calls enable both the MCMS application 20 and the Store and Stream module 24 to operate as necessary to implement the various Voicing functions when invoked by Users and/or as dictated by network conditions. Some of the functionality performed by the SAS Services module 20b includes maintaining and communicating the status of Message transmissions and Message acknowledgments, the instructions for rendering of Messages, and the status and presence of Users.

D.1.2.3 the Messaging and Signaling Services Module

The Messaging and Signaling Services module 20c runs on both Clients 12 and Servers 16 and enables communication between the Client 12 and the Servers 16 of the system 10. This communication, which includes messages, data and other signals, allows the Client 12 and the system 10 to track and administer communications, network status, Users, and User status. Types of messages and signals sent between the Message and Signaling Services modules 20c running on the Clients 12 and the Servers 16 include, for example, network availability of Users, tracking of Messages that the Server 16 has sent to the Client 12 (possibly including a “high water mark”) to determine if an entire message or some portion of a message is missing, (e.g., a sequence number per Participant per Conversation created by the “generating” Client), whether a user is speaking or Reviewing Messages of a given Conversation, where a User

14

is with respect to the Head of a Conversation, or when a Participant is no longer Reviewing a Conversation live. These are examples a few of the many types of messages and signals sent between the Message and Signaling Services modules on the Clients 12 and Servers 16 and in no way should be construed as limiting the invention.

D.1.2.4 The User Interface API

The User Interface API 20d is a module that defines a set of function calls that define the programming interface between the User Interface module 20e and the underlying services of the MCMS application 20. The User Interface API 20d supports general-purpose methods such as UI application support, and all function calls necessary for a User Interface to operate the MCMS Application 20. In various embodiments, the User Interface API 20d enables the Client 12 to support a wide variety of user interfaces and device types, such as Adobe Flash-based and/or Microsoft Windows applications, cellular or mobile phone devices, PSTN devices driven with tones, a voice user interface (VUI), and physical radio communication interfaces. In various embodiments, the User Interface API module 20d enables the design of both highly flexible and highly constrained user interfaces to support the functionality of the MCMS application 20.

D.1.2.5 The MCMS User Interface Module

The MCMS User Interface module 20e supports the operation and functions of the audio and video user interface of the Client 12. The User Interface module 20e supports a host of user interactions and can be implemented with various interaction mediums, such as, an array of graphical user interface screens, an Audio/DTMF interface, or voice user interface on the Device 13, all of which enable a User to interface with the system 10. A partial list of User interactions that are supported include, for example, functions to: log-in; manage, join, and monitor Conversations; control Conversation rendering; manage Priorities; and requests to review archived Conversations. It should be noted that this list is exemplary and in no way should be construed as limiting the invention.

D.1.2.6 Conversation/Message Management Services

The Conversation/Message management services 20f is a module which defines a set of functions that manage the data structures and processes responsible for managing and retaining all information needed for the User to manage the receipt and Review of transmitted and received Media (e.g., voice or video content Messages) between the participants of a Conversation. The Messages are organized into Conversations. Media that is sent or received by the Device 13 running the application 12 is available for immediate Review while being received. The received Media is also recorded for Review in a time-shifted mode, Conversation management, and archival purposes. In an alternative embodiment, Messages or Conversations can be optionally marked for transience, specifying their desired retention requirements (e.g., some Messages will not be retained or stored beyond the requirements for immediate rendering). In yet another embodiment, Media can be optionally marked for review in a time-shifted mode only and cannot be reviewed immediately upon receipt.

The Conversation/Message management services 20f further enables, for each current or ongoing Conversation of the User, the sending of Media to a receiving Client 12 at any time, and the receiving Client 12 seamlessly associates these Messages with the appropriate Conversation, regardless of the actions or inaction of the receiver.

With the Conversation/Message management services 20f, all Conversations are essentially asynchronous. If two

15

Users are actively engaged in a given Conversation and the User controlled delay between transmissions is minimal, the experience will be one of a synchronous full duplex conversation, as with current telephone or VoIP conversations. If either User delays their participation, for whatever reason, the Conversation drifts towards an asynchronous voice (or other Media) messaging experience. In alternative embodiments, Conversations can be optionally Tagged as asynchronous Messages only or synchronous Messages only. In either of these cases, the Conversation cannot drift between the two modes, unless the Tag is reset. After the Tag is reset, the Conversation again may flow between near synchronous (i.e. live or real-time) and asynchronous (i.e., time-shifted or voice messaging) modes.

The Conversation/Message management service **20f** processes the transmission and receipt of Messages in a progressive fashion. When transmitting, Media may be created while Messages are simultaneously encoded, stored and transmitted. In other words, the transmission of Messages may occur simultaneously with the generation of Media by the User (i.e., while speaking into their Device **13** or generating video). On the receiving side, the receipt, storage, and Rendering of Messages also all occur progressively. Messages do not need to be completely received before they can be Rendered. The Rendering of Messages may occur at the same time Messages are being delivered, right up to the MTSD. Further, the service **20f** is also capable of the simultaneous transmission of outgoing Messages and Rendering of incoming Messages. The progressive nature of the service **20f** allows a User to be engaged in a live Conversation while storing and streaming the media of the Conversation for later retrieval and review as well other functions described herein.

The time-shifting of Messages by the Conversation/Message management services **20f** allows a User to "Catch Up To Live" on a Conversation if they missed earlier Messages or were involved in another Conversation. This time-shifting process eliminates the need for Users to broadcast a request to their entire Group or Channel to have Messages repeated. Older Messages may be replayed at any time at potentially higher speeds to save time. Users may easily skip forward and backward through their Messages and within individual Messages. The Reviewing process may be configured on a Message-Priority basis to potentially skip lower priority Messages.

In one embodiment, the Conversation/Message management service **20f** also identifies Messages by a specific Participant (speaker) and, by default, mixes Messages of a Conversation that were delivered at the same time (MCMS-S). In an optional embodiment, a User could Review the transmissions of different Participant speakers of a Conversation separately.

The Conversation/Message management module **20f** further allows Conversation sharing among Participants, who can be added to an active or archived Conversation. In one embodiment, an added Participant to a Conversation is provided access to the Conversation and has the ability to retrieve the previous Messages of the Conversation for Review. In an alternative embodiment, the added Participant is provided access to the Messages of the Conversation only from the point where the new Participant joined, and not any previous Messages of the Conversation.

The Conversation/Message management module **20f** is also responsible for managing the functions used to control all rendering tasks performed by the Store and Stream module **24**. These tasks include rendering Media (i.e., voice, video, etc.) appropriately for the Device **13** running appli-

16

cation **12**. These rendering tasks include, but are not limited to, the rendering of Mixed Messages (i.e., overlapping messages), as well as rendering according to user-defined criteria, such as playing faster, catching up to live, removing silence, removing hesitation particles, frequency shifting, and the ability to apply independent gain control to individual senders in a multi-party conversation.

D.1.2.7 Priority Services

The Priority service **20g** is a module that defines a set of functions that manage the data structures and processes responsible for managing and retaining all information needed for a User to manage the Priority of the consecutive Conversations (i.e., MCMS-C) in which the User is engaged. When a User participates in a number of consecutive live Conversations, the User is required to prioritize the Conversations. Issues arise when Messages of different Conversations are ready to be rendered at the same time. An algorithm is used to determine the order in which the Messages are rendered that considers the availability of Messages to be rendered and the Priorities set by the User. The algorithm determines that the available Messages with the highest priority are rendered first while any concurrently available Messages are time shifted automatically just enough to allow for the rendering of the higher priority Message. As rendering time becomes available, the system will automatically render the time-shifted messages according to the User's Priorities.

D.1.2.8 Contacts Services

The Contacts services **20h** is a module that defines a set of functions that manage the data structures and processes responsible for managing and retaining all information needed for authenticating and associating one or more Contacts with Conversations. When sending a Message as part of a Conversation that is associated with a number of Contacts, all of the Contacts receive the Message.

D.1.2.9 Presence/Status Services

The Presence/Status services **20i** is a module that defines a set of functions that maintain the data structures and processes responsible for managing and sharing presence and status information between certain Users and/or non-users of the system. In various embodiments, the presence and status information is maintained for all User and non-users engaged in the Conversations the User of the Client **12** is engaged in, all Users and non-users in the Contacts list, or Users within a predefined domain (e.g., the members of a corporation or other organization). These examples are merely illustrative and should not be construed as limiting. The Presence/Status services **20i** module may manage and share presence and status information on any defined set of Users and/or non-users.

The Presence/Status service **20i** enables Users to monitor the status of other User's Intentions, Attention, and their Time Shift delay on any given Conversation (i.e., how far back they are from Reviewing the Messages of the Conversation live). In one embodiment, privacy controls are provided concerning availability of Presence and Status data. The Presence/Status module **20i** further controls the data that enables the system **10** to deliver Messages that match the behavior and Intentions of Users. For example, a User may indicate their Status by designating an Intention to either Review or not Review a Conversation live. In response, the Presence/Status services **20i** issues commands that cause the rendering of Messages either "live" or time-shifted, in accordance with the Intention of the User. In addition, the Intentions of Users are shared with the other Participants of the Conversation. The service **20i** is also capable of inferring other Status values from the User's

17

behaviors. The Presence and Status information is also used to optimize network traffic and bandwidth, as described in more detail below.

D.1.2.10 Messages/Signals Services

The Messages/Signals services 20j is a module that defines a set of functions that manage the data structures and processes responsible for messaging and signaling Users of the system 10, using special messages or audible tones. The special messages or tones may include for example an indication if a Message or Messages are live or time-shifted, whom the Message(s) are from, Priority, and other factors. The Message/Signal service 20j further has the ability to (i) signal the presence or absence of Users on the network, as well as the ability to notify if one or more Users are no longer actively Reviewing the Messages of a Conversation; (ii) "ring" or otherwise notify another User to get their attention when they are paying attention to another Conversation or not paying attention to their Device 13 at all; (iii) leave a Message for Users currently not on the network 18 to immediately review the Message the next time the individual re-connects to the network 18; (iv) generate an audible or visible feedback that alerts the sender that a sent Message was not received by recipient(s), generate a confirmation when the Message has been received by the recipient(s), and/or a confirmation indicating when the Message has been Listened to by the recipient(s); and (v) implement a Priority scheme where individuals on a Conference or tactical call may be notified that their attention is immediately needed on the call. This indication may convey multiple levels of urgency and an acknowledgement of some kind by the recipient.

D.1.2.11 Rendering and Encoding

The rendering and encoding module 21 is responsible for performing all rendering tasks for the MCMS application 20. These tasks include rendering Media appropriately for the device 13 running application 12.

D.2 The Store and Stream Module

The Store and Stream module 24 supports a number of functions and performance attributes, which are described below.

With the Store and Stream module 24, Message transmission is essentially "full-duplex", enabling any party to send a Message at any time, even while another party is also sending a Message, or if the other party is unavailable or otherwise engaged. The Store and Stream module is able to render messages as in a live PSTN or VoIP call or deliver them for time shifted messaging modes. It is able to optimize transmission and control Rendering according to the desires of the User.

The Store and Stream module 24 maintains connectivity with all target recipients (e.g., Servers 16 or other Devices 13) on the underlying network 18, manages all message, signal, and media transmissions, and optimizes the delivery speed and bandwidth usage across the network 18 to meet a User's immediate performance requirements, while managing network quality and capacity. The module 24 adapts and optimizes Media delivery commensurate with the quality and capacity of the underlying network 18. When insufficient underlying network resources are available, the quality of the transmitted Media streams can be degraded. As bandwidth becomes available, the quality of the transmitted Media streams may be increased. In addition to tradeoffs of Media quality, the Store and Stream functionality can make tradeoffs in the amount of Media transmitted in each packet based on Users' intentions to render data in real time as described below.

18

By dynamically controlling the delivery rate of Media based on the conditions of the underlying network 18, the Store and Stream module 24 is optimized to deliver time-sensitive Media that is "good enough" to Render upon receipt, and the guarantee eventual delivery of exact or full copies of the Media for archival purposes through a background process of requesting retransmission of missing, low quality, or damaged packets. As long as sufficient network resources exist to meet minimum Media quality levels, this retransmission does not impede the Rendering of live call Media. The Clients 12 of the system 10 are thus designed to bridge the performance gap between the delivery of an exact or complete copy of the Media at the expense of substantial potential latency versus the quick delivery of Media, but with no guarantees of completeness. In the context of this application, the term "good enough" means that the quality of the Media is sufficient so that when it is rendered, it is intelligible. The notion of "good enough" is therefore subjective and should not be construed in absolute terms. For example, the quality level of certain Media to be good enough may vary depending on the type of Media, circumstances, and other factors.

The Store and Stream module 24 further persistently stores all Media created by or otherwise originating using a Device 13 or received over the network 18 from other Device 13 and/or users. There are several significant advantages of storing this Media on the Device 13 running the Client 12: (i) it enables Users to leave a Message for another party, even when the sender and/or the recipient has either unavailable or poor network connectivity. In the case of insufficient bandwidth, the Message will be transmitted as fast as available bandwidth can be effectively used. In the case of no connectivity, the Message is queued for transmission as soon as network connectivity becomes available, resulting in a time-shifted delivery; (ii) the User has the ability to pause, replay, fast-forward, and Catch-Up-To-Live with an ongoing Conversation, as well as retrieve and review the archived Messages of previous Conversations; and (iii) it enables the optimization of data payloads over the system 10 and improves system resilience against network bandwidth and connectivity problems that may occur from time to time.

The Store and Stream module 24 is also responsible for: Mixing Messages as appropriate to create overlapping Messages (generated by the normal overlap of speakers in a Conversation or background noise), simulating an actual Conversation where multiple parties are speaking; rendering transcriptions or translations of audio media; adjusting the rendering of Media according to a number of User-defined criteria including playing faster, removing silence gaps between spoken words, removing hesitation particles, and frequency shifting; and the ability to apply independent gain control to individual senders in a multi-party Conversation; as well as other potential Rendering options.

The Store and Stream module 24 manages control and informational messaging between itself and MCMS.

D.2.1 the Persistent Infinite Message Buffer (PIMB)

The Persistent Infinite Message Buffer or PIMB 30 is a set of indexed (i.e., time-stamped and sequentially numbered) Media payload data structures and a system for their storage and retrieval. In one embodiment, the data in the PIMB 30 is arbitrarily persistent, meaning it is available virtually forever or at least until the system runs out of storage. Various retention rates and strategies may be employed to make effective use of storage resources. Many possible implementations exist for the physical storage implementation of the PIMB 30, including, but not limited to: RAM,

Flash memory, hard drives, optical media, or some combination thereof. The PIMB 30 is also “infinite” in size, meaning the amount of data that can be stored in the PIMB 30 is not inherently limited. This lack of limit is in comparison to existing jitter buffer technology that discards data as soon as it is rendered. In one specific embodiment, the PIMB 30 may be implemented using a small and relatively fast RAM cache memory coupled with a hard drive for persistent storage. As the physical storage capacity of the PIMB 30 is exceeded, the data is maintained on the Server 16 (as described below) for later retrieval on demand. User criteria or a replacement algorithm, such as least-recently-used, or first-in-last-out, is used to control the actual data stored in the PIMB 30 and the data that is maintained on the Server 16 or archived at any point in time. The PIMB 30 further provides the attributes of file system storage and the random access attributes of a database. Any number of Conversations, regardless of their duration or the number of Messages in each, may be stored and later retrieved for Review. In addition, the meta data associated with the Messages of a Conversation, such as its originator and its length, may be also stored in the PIMB 30. In alternative embodiments, the indexed Media payloads and other data can be stored for a designated period of time (e.g. 30 days). Once the age of the media exceeds the designated period, the payloads and data are discarded. In another embodiment, payloads can be discarded based on the sender and/or the recipient of the Message containing the payload, or the topic of the Conversation or Messages associated with the payload. In yet other embodiments, payloads and data may be marked for transience, meaning the Messages will not be stored in the PIMB 30 beyond the requirements for immediate Rendering.

D.2.2 The Data and Network Quality Store

The data and network quality store (DNQS) 32 is a data store for storing information regarding Media payloads and Vox packets that are either read from or written to the PIMB 30.

D.2.3 The PIMB Writer

The PIMB writer 28 writes data to the PIMB 30 for two basic purposes. The PIMB writer 28 writes data from a Media capturing device (e.g., a microphone or camera) on the Device 13 running the Client 12 (“Encode Receive”). The PIMB writer 28 also writes data received over the network 18 from other Clients 12 into the PIMB 30 (“Net Receive”).

D.2.3.1 Encode Receive

For capturing Media from the Device 13, the PIMB writer 28 includes Encoder Receiver 28a and a Data Storer 28c. When a User speaks into the microphone or generates video images with the Device 13 for example, the hardware 34 receives the raw audio and/or video signals and provides them to the Encoder Receiver 28a, which encodes the signals into indexed media payloads (hereafter sometimes simply referred to as “payload” or “payloads”). The Data Store 28c stores the payloads into the PIMB 30. Other types of Media, such as sensor data is converted into payloads in a similar manner.

D.2.3.2 Net Receive

For storing Media received over the network 18 into the PIMB 30, the Net Receive function of PIMB writer 28 includes a Network Receiver 28d, a Data Bufferer 28e, a Data Storer 28f, a Data Quality Manager 28g, and a Network Quality Manager 28h. The Network Receiver 28d receives Vox packets over the network 18. The Data Bufferer 28e places the received Vox packets into their proper sequence and prevents the Rendering of the incoming Vox packets for

at least the Minimum Time Shift Delay (MTSD) delay. The Data Storer 28f transforms the packets into indexed media payloads and stores the indexed media payloads in the PIMB 30. As the payloads are stored, the Data Quality Manager (DQM) 28g notes any missing or defective packets. If packets are missing or defective, the DQM 28g schedules a request for retransmission over the network 18. The sending device replies by resending the missing or defective packets. Eventually these packets are converted into indexed media payloads and stored in the PIMB 30. By retrieving the missing or defective packets, an “exact” copy of a sender’s Message is eventually stored in the PIMB 30. The retransmission of missing and/or defective packets does not delay the rendering of Messages in real time, provided that the packets that have been delivered are of “good enough” quality and quantity. Retransmission requests may be delayed by the DQM 28g if insufficient network resources are available to support both the new “live” data as well as the retransmission.

D.2.4 The PIMB Reader

The PIMB reader 26 reads data from the PIMB 30 for two basic purposes. The PIMB reader 26 accesses the PIMB 30 when data is to be rendered (“Render”) for the local Client 12. Data is also read from the PIMB 30 when data is to be transmitted (“Transmit”) by the Client 12 over the network 18.

D.2.4.1 Render

For the rendering of messages on the Client 12, the PIMB reader 26 includes a Data Prioritizer 26a, a Data Retriever 26b, a Packet Loss Compensation/Interpolator (“PLC/Interpolator”) 26c, a Data Mixer 26d and a Data Renderer 26e. The Prioritizer 26a prioritizes the data to be rendered by building an ordered queue of messages that could potentially be Rendered. It uses User configured Priority for the rendering of consecutive Conversations (MCMS-C). In addition, the Data Prioritizer uses the availability of media data to render within the limits imposed by the MTSD, the User’s current Attention, and the User’s defined and implied Intentions. The Data Retriever 26b retrieves the prioritized indexed media payloads from the PIMB 30. The PLC/Interpolator 26c performs packet loss compensation and interpolation on the retrieved payloads, using known packet loss compensation and interpolation algorithms. The particular method to be used is dependent on the media Codescs in use, and other well-known parameters. The Mixer 26d is used to appropriately mix concurrent data streams from multiple Messages of a single Conversation together. For example, if two or more Participants of a Conversation are speaking at the same time, the Mixer 26d mixes the Messages, creating the effect of both Participants speaking at the same time. In an alternative embodiment, the User has the option of Reviewing the multiple streams from one Participant at a time. If only one Participant in the Conversation is speaking, the Mixer 26d may simply pass the single Message stream, without performing any mixing. The Renderer 26e takes the data from the Mixer module 26d and converts it into a form suitable for the hardware driver 34. The hardware 34 then drives either the speaker or video display of the Device 13, depending on the type of Media, creating voice, video or some other audible and/or visible notifier on the Device 13.

D.2.4.2 Transmit

To prepare messages for transmission from the Client 12 over a network 18, the PIMB reader 26 includes a Data Prioritizer 26f, a Packet Quality Manager (PQM) 26g, a Data Retriever 26h, Packetizer 26i, a Transmitter 26j and an Acknowledger 26k. The Data Prioritizer 26f prioritizes the

21

Messages for transmission over the network **18**. Priority is determined using the MCMS Participant Attributes related to payloads available for transmission, network connectivity and bandwidth conditions, and the Intentions of Users beyond the next hop to either Render live or time-shifted, and, in some embodiments, possible optimizations of transmission bundling where multiple packets to any given next network hop are available. The prioritized packets are then optimized, using the PQM **26g**, which assures the timely delivery of “good enough” data quality for live Messages, while minimizing real-time bandwidth, as described in more detail below. The Data Retriever **26h** retrieves the appropriate payloads from the PIMB **30**. The Packetizer **26i** assembles the payloads into Vox Packets, which are then transmitted by the Transmitter module **26j** over the network **18**. When the recipient receives the Vox packets, an acknowledgement is sent back to Acknowledger **26k** over the network **18** for notifying the sending User that a Message has arrived at its destination.

D.2.5 The Packet Quality Manager

The PQM **26g** has several optimization goals: (i) the timely delivery of an adequate copy of time-sensitive Media (“as soon as possible to be good enough” for Rendering); (ii) the efficient use of available bandwidth, meaning using the optimal transmission frequency, payload quality, and packet size for the underlying network; and (iii) the ability to dynamically adjust or make changes in the transmission frequency, payload content, payload quality, packet size, etc. as network conditions change.

D.2.6 The Network Quality Manager

On the receiving side of a network transmission is the Network Quality Manager **28h** (NQM). The NQM is responsible for observing specific properties of network performance for each sender that has sent media to the Client **12**, comparing expectations of jitter, loss, and throughput to their actual values. This is used to compute a Network Quality Rating (NQR) for every sender. This NQR is used to indicate sender availability and Conversation live-ness to the User of the receiving device.

D.2.7 The Data Quality Manager

The Data Quality Manager **28g** measures the quality of the data being received over the network by observing packet loss, jitter, and throughput. The DQM **28g** uses these measurements for three purposes: (i) to send receipt reports back to the sender; (ii) optionally using those receipt reports to request retransmission of certain data; and (iii) making these measurements available to the NQM **28h**.

E. Server Architecture

Referring to FIG. 3, a block diagram of the application **78** that runs on the Server(s) **16**. The application **78** is similar to the Client application **12** in many regards and includes an MCMS server application **80**, an MCMS database **82**, a store and stream module **84**, a PIMB **85**, a data and network quality store (DNQS) **86**, MCMS-SAS message handling modules **87a** and **87b** which manage messages and signals back and forth between the MCMS server application **80** and Store and Stream module **84**, an archive/retriever **88**, and an archive **89**. The application **78** further includes an authentication-encryption-security module **40** and a communication protocol module **44**.

The MCMS server application **80** is a multi-tiered architecture including a MCMS Database Module **20a**, a Store and Stream (SAS) Module **20b**, a Messaging/Signaling Module **20c**, Conversations/Messages management services **20f**, Priority services **20g**, Contacts (including User and

22

Authentication) services **20h**, Presence/Status service **20i**, and Messages/Signals services **20**. The aforementioned modules and services of the application **78** are similar or the same as the modules and services having like reference numerals as the Client **12**, and therefore are not described in detail herein, except for one notable exception. In various embodiments, the MCMS server application **80** and Store and Stream module **84**, including the MCMS database **82**, is configured to support many Users in one instance of the application. The one instance may be further configured to support multiple domains, where each domain is defined as a group of Users (i.e., a corporation or other group of Users belonging to a common organization). This architecture allows each application **78** on Server **16** to serve multiple users (or domains), where each user (or domain) is not visible to other Users. This partitioning is referred to as “multi-tenancy”.

The server Store and Stream **84** module performs the functions of Net Receive and Transmit. For the Net Receive function, the module **84** includes a Net Receiver **28d**, Data Bufferer **28e**, a Data Storer **28f**, a Data Quality Manager (DQM) **28g**, and a Network Quality Manager **28h**. For Transmit functions, the module **84** includes a Data Prioritizer **26f**, Packet Optimizer **26g**, Data Retriever **26h**, Packetizer **26i**, Transmitter **26j** and an Acknowledger **26k**. The aforementioned elements of the Store and Stream module **84** are similar or the same elements having like reference numerals as the Client **12**, and therefore are not described in detail herein.

Since the Server **16** does not directly interact with Users, the encoding and rendering functions provided in the Store and Stream module **24** of the Clients **12** need not be present. The MCMS application **80**, when running on Servers **16**, does not interact directly with Users. Consequently, the user interface and user interface API modules and services **20e** and **20d** are not needed.

The application **78** on each Server **16** potentially serves multiple tenants, meaning it serves multiple Users of the system **10**. The PIMB **85** of the server application **78** is therefore significantly larger and is used to store the media payloads of multiple Users, as opposed to the PIMB **30**, which is used to store just the generated or received payloads of only a single User. The main purpose of the Store and Stream module **84** is to receive Messages transmitted by the Clients **12** and transmit Messages to other Clients **12**. When a Client **12** transmits a message, the message contains an identifier associated with the target recipient. In response, the Server **16** finds a delivery route to a Client **12** associated with the intended or targeted recipient. As Messages are received, they are stored in the PIMB **85** and transmitted to the next Server **16** (i.e., the net “hop”) of the network layer **14** along the path to the intended recipient(s), or to the recipient(s) directly depending on the system configuration. The archive-retriever **88** is responsible for archiving the media payloads stored in the PIMB **85** in archive **89**. As the physical space in the PIMB **85** is exhausted, media payloads in the PIMB **85** are moved to the archive **89**, which is a mass storage device. In various embodiments, the payloads stored in the PIMB **85** may be archived in accordance with User defined criteria and/or any known replacement algorithm, such as first-in-first-out (FIFO) or least recently used (LRU). It should be noted that only a single Server **16** is illustrated in FIG. 1 for simplicity. It should be understood that in actual embodiments, multiple servers or a “server farm” may be used for a network with a large number of Users.

The terms “persistent” and “infinite” used to describe the PIMB **30** and the PIMB **85** should not be construed literally

23

as absolute terms. A User may wish to indefinitely store some Messages that are considered important. In other situations, such as a casual chat between two friends, the Messages may be deleted after a certain period of time to save space. According to various embodiments of the invention, different retention policies may be used, either set by the system 10 or configured by the User. The use of the word “infinite” refers to the lack of any preset time boundaries enforced by the PIMB. This is contrasted with current jitter buffer systems, which discard media after it has been rendered. The terms persistent and infinite should therefore be broadly construed to mean that the PIMB 30 and PIMB 85 have no internal limitations on the time ranges and quantities of Messages that can be stored therein.

There are a number of advantages to archiving the Messages of Conversations in a persistent storage medium. Voice messages and other Media can be organized, indexed, searched, transcribed, translated, and Reviewed as needed. Voice, as well as other Media, therefore becomes an asset that can be managed both by Users and organizations. These Media assets have value to corporations, first responders, police and fire departments, as well as the military.

F. The Vox Protocol and Indexed Media Payloads

As noted above, the Vox protocol is used by the Store and Stream module 24 to support all facets of payload transmission, storage, and optimization. The Vox packet is a structured message format designed for encapsulation inside a transport packet or transport packets of the underlying technology of the network 18. This arrangement significantly improves the flexibility of the system 10. By embedding the Vox packets into existing transport packets, as opposed to defining a new transport layer for “Voxing” applications, the system 10 takes advantage of current packet based communication networks running over the existing telecommunications infrastructure. A new network infrastructure for handling the Vox packets therefore need not be created to take advantage of all the benefits of the system and method described herein.

Referring to FIG. 4A, the general format structure of a Vox packet 95 is illustrated. The format of the Vox packet 95 includes fields for type, sub-type, length, and payload. The different types of Vox packets include authentication, signaling, media payload, media multiplex (one message), and media multiplex (multiple messages). The sub-type field is used to designate different types of authentication, signaling or media type messages. Possible sub-types for authentication Messages include those necessary for key exchanges and Authentication. Possible sub-types for signaling Messages include registration, routing, message set-up, and network management. Possible sub-types for Media messages include different Codec styles and different payload aggregation techniques. The length field defines the overall length or size of the payload. The payload field contains the actual payload or media of the packet 95.

Referring to FIG. 4B, a diagram illustrating a Vox packet 95 encapsulated in an exemplary protocol used by the network 18 is shown. In this example, the Vox packet 95 is embedded in underlying UDP, IP and Ethernet transport packets 96 respectively. In this manner, the Vox packet 95 can be transported across underlying UDP, IP and Ethernet layers of the network 18. This is a standard protocol encapsulation technique used by packet networks.

Referring to FIG. 4C, a diagram illustrating a media multiplex Vox packet 95 encapsulated in UDP, IP, and Ethernet 97 is illustrated. In this example, the Vox packet 95

24

includes a Media type field, a Media sub-type field, a length field, a message ID field, a time stamp field, a sequence ID field, and a Media payload field.

Referring to FIG. 4D, the format of an indexed media payload 98 is illustrated. The indexed media payload includes a sub-type field, a length field, a message identifier (ID) field, a time-stamp field, a sequence identifier (ID) field, and field for the Media payload.

The encapsulation of Vox packets 95 into the transport packets of the underlying network allows the Media, Messages and Conversations to each be defined by a number of attributes.

When Media is created or otherwise originated on a Device 13, it is typically time-based, meaning it changes in some meaningful way over time. As a person engages in a Conversation for example, their spoken words are strung together into sentences or statements, which vary over time, and the resulting data (streams and packets) will maintain the same variance over time. Similarly video (as opposed to a still photo) as well as GPS or other sensor data will vary over time. Regardless of the type or how it is originated, the Media is segmented and placed into the payloads of a plurality of Vox packets 95. The packets are then continually, stored, transmitted, received, stored and rendered in streams (i.e., streaming media) at the transmitting and receiving Devices 13 respectively. Since each packet 95 is indexed, time-stamped, and given a sequence identifier, the individual packets can be segmented into Messages. By sequentially threading the individual Messages together, Conversations may be constructed.

One further unique aspect of the system 10 is that the media payloads generated by a Client 12 are stored in multiple locations. Not only are the payloads stored in the PIMB 30 of the generating Device 13, but also in the PIMB 85 of the Server(s) 16 and the PIMB 30 of the receiving Devices 13. This basic feature enables or makes possible much of the Voxing functionality described above and provides the system 10 with both resilience and operability, even when network conditions are poor or when a Participant of a Conversation is not connected to the network.

G. Interoperability with Underlying Telecommunication Protocols

The system 10 is intended to run or be layered over a variety of existing communication networks 18, such as the Internet, fixed PSTN type circuit networks, and mobile or cellular phone networks, or a combination thereof. The system 10 is designed around the concept of moving many small units of information (i.e., the Vox packets) between different Clients 12 and Servers 16 in the system 10. While Vox packets may vary in size, depending on their function and payload, they all appear to be the same kind of data to the underlying network layer. In one embodiment, the system 10 has been designed and optimized for IPv4 networks such as the Internet, but other types of networks may be supported as well. For the purposes of this document, the term “IP” should be taken to mean IPv4, IPv6 or any other current or future implementation of the Internet Protocol.

Referring to FIG. 5, a diagram of a Client 12 running on Device 13 and communicating with a Server 16 over a shared IP network 100 is shown. As illustrated, the Client 12 is coupled to the shared IP network 100 through a first Internet service provider A and the Server 16 is coupled to the shared IP network 100 by a second Internet service provider B. During communication, the Vox packets 95 (designed “VP” in the figure) are encapsulated within UDP/

25

IP packets and then interleaved among other IP protocol packets as is well known in the art and transmitted across the shared IP network 100 from the Client 12 to Server 16, or vice versa. As is well known, each lower packet layer encapsulates the entire packet of the layer immediately above it. Packets can also be sent in a similar manner between two Servers 16. Messages are sent from one Client 12 enabled Device 13 to another over a shared IP network 100. At each hop, the Vox packets 95 are embedded in the underlying IP protocol and transmitted, until they reach the target destination.

The diagram of FIG. 5 is merely exemplary, showing only a single Client 12 and Server 16 connected to the network 100 for the sake of illustration. In actual embodiments of the system 10, a large number of Clients 12 and one or more Servers 16 are typically connected to the shared IP network 100. It is also useful to note that the Client 12 and Server 16 do not have exclusive use of the IP network 100. In the example shown, an HTTP client, which is coupled to the network 100 through Internet provider A, can send packets back and forth with an HTTP server, coupled to the network 100 through a third Internet provider C. The system 10 does not control the manner in which the VPs embedded in the IP packets traverse the network 100. Rather, all packets that traverse and share the network 100 do so in accordance with the standard procedures of the underlying shared IP network 100.

Referring to FIG. 6, a “circuit” based network 104 such as a GSM mobile phone network is illustrated. The circuit network 104 is coupled between Client 12 running on Device 13 and Server 16. Once a circuit is established between the Client 12 and Server 16, the system 10 layers Vox packets (VP1, VP2, VP3, VP4, VP5, etc.) onto the underlying packets used by the network 104 and transmits them across the network 104, creating “virtual Vox” circuit. The Vox Packets sequentially traverse the circuit network 104, typically with spacing or framing data as is well known in the art for transmitting data over a circuit network. In addition, packet construction parameters, such as the payload size and the number of header fields included may be used to exploit the lack of per-packet overhead and to increase speed and/or efficiency of data transfer across the network 104. It should be noted again that for the sake of simplicity, only a single Client 12 and Server 16 are shown connected to the network 104. It should be understood, however, that additional circuits between Clients 12 and Servers 16 as well as other components may be established concurrently through the network 104. The network 104 is therefore not dedicated for the transmission of Vox Packets, but rather may be shared with other types of network traffic.

Referring to FIG. 7, a diagram illustrating communication between a first Client 12A enabled Device 13A associated with a first network A and a second Client 12B enabled Device 13B associated with a second network B is illustrated. The networks A and B further each include gateway Servers 16A and 16B respectively. The Gateway Server pair 16A and 16B facilitate communication between the two networks A and B, allowing the Devices 13A and 13B to communicate with each other. In various embodiments, the networks A and B could each be any type of network. For example, each network A and/or B could be an IP network, a circuit type network, or a wireless or cellular network (i.e., CDMA, GSM, TDMA, etc.). The Servers 16 that straddle the two networks A and B are considered gateway servers because they route traffic or serve as a “gate” between the two networks.

26

With the system 10, there are several basic network interaction considerations to optimize system performance. These considerations include factors such as resolving the underlying address to which the Vox packets 95 are to be sent, the integrity of any sent Vox packets, and the management of the Maximum Transmission Unit (MTU) of a single Message that may be sent across a given network or combination of networks.

The address of a target Client 12 needs to be known so that the underlying network delivers the Vox packet 95 to the correct location. With IPv4 networks, the address is typically an IPv4 Address, which is a 32-bit number that uniquely identifies a host within the network. For other networking technologies, the address could be some other type of identifier. IP networks use the Domain Name System (DNS) to resolve human-readable names into IP addresses, and the Address Resolution Protocol (ARP) to resolve IP addresses into physical addresses. Regardless of the underlying networking technology, the system 10 uses one of the above-mentioned or other known addressing schemes for delivery of Vox packets 95 to the correct location.

As with almost any packet-based communication system, transmitted Vox packets might not be delivered to their addressed location if the underlying network is unable to deliver the packets in which the Vox packets are encapsulated. Most packet networks do not inform transmitters when packets are dropped. Instead they rely on the transmitters and receivers to notice and compensate for any dropped packets. The system 10 is designed to use these receiver receipt report messages to coordinate this packet loss management. If the underlying network is able to inform the sender of lost or dropped packets, the system 10 utilizes this information in its retransmission protocol.

The management of MTU is the determination of the Maximum Transmission Unit (i.e., the maximum size of a single message) that may be sent across a network. For packet-based networks, the underlying network imposes the MTU. For circuit-switched networks, the MTU may be a tunable parameter for network efficiency and performance. Thus in most cases, the underlying network imposes or determines the maximum size of the Vox packet 95 that may be transmitted efficiently. For example with IP networks, packets may be fragmented if the payload exceeds the MTU, but at a substantial performance penalty. With IP over Ethernet networks, the transmitting device has an MTU of 1518 bytes, as enforced by Ethernet. The largest IP packet must leave room for the Ethernet headers. The largest UDP packet must leave room for both IP and Ethernet headers and the largest Vox protocol that may be generated on Ethernet for example is the Ethernet MTU (1518)—IP header (20)—UDP header (8)=1490 bytes. Since the Vox protocol will have a header of its own, the actual Vox media payload will be less than 1490 bytes on an Ethernet network. For Gigabit Ethernet, the MTU could be much larger, but would be determined using a similar formula.

In a purely packet-based network, there are two potential values for MTU, the local link MTU and the path MTU. Determining the local link MTU yields the maximum size for Vox packets to be efficiently sent out to the local network interface. The path MTU yields the maximum size of Vox packet that may be sent intact all the way to the remote node. If a sender is connected via Ethernet, the Vox packet might pass through various other systems with smaller MTUs en-route to the recipient. The smallest MTU on the path to the destination needs to be resolved and known by the sender. In the IP world, there is a standard procedure for discovering the smallest MTU called “Path MTU Discov-

27

ery". For other kinds of networks, an equivalent procedure may be used. Again, since the system 10 is layered on top of other networks, any of the above MTU algorithms may be used.

H. Operation Flow Diagrams

H.1 Store and Stream

Referring to FIGS. 8A through 8F, a series of flow diagrams are provided to illustrate the operation of the store and stream module 24 and 84 on Clients 12 and Servers 16 respectively. FIG. 8A shows the sequence of operation for a first Client 12₁ transmitting Messages to a second Client 12₂. FIGS. 8B and 8C illustrate the operation of the PIMB writer 28 and PIMB Reader 26 on the transmitting Client 12₁. FIGS. 8D and 8E illustrate the operation of the PIMB Writer 28 and PIMB Reader 26 on the receiving Client 12₂. FIG. 8F illustrates a flow diagram of the Store and Steam module 84 on a server 16.

In FIG. 8A, the User of Client 12₁ running on a Device 13₁ originates Media to be transmitted. The Media can be originated at the Device 13 in a number of different ways such the User creating Media by speaking into a microphone or creating video content on their Device 13. Media is also originated by a Device 13 by receiving sensor data, such a GPS information or a temperature reading. Regardless of how the Media is originated, the Media is encoded by the PIMB Writer 28 (box 130), which converts the Media into indexed media payloads and stores them in the PIMB 30 (box 132) on Client 12₁. The PIMB Reader 26 on the Client 12₁ reads the payloads out of the PIMB 30, creates Vox packets, and transmits the packets to the receiving Client 12₂ (box 134) over the network 18. Each Server 16 along the path between the sending Client 12₁ and the receiving Client 12₂ stores the transmitted payloads in the PIMB 85 and transmits the Vox packets to the next hop (box 133). At the receiving Client 12₂, the net receive function of the PIMB Writer 28 converts the Vox packets into indexed media payloads (box 136) and stores the payloads into the PIMB 30 of Client 12₂ (box 138). The rendering module of the PIMB reader 26 on Client 12₂ renders the payload information read from the PIMB 30 into a medium suitable for human consumption, such as voice or video (box 140). Each of these steps are described in more detail below with respect to FIGS. 8B through 8E.

In FIG. 8B, a sequence of the Encode Receive function performed by the PIMB Writer 28 (step 130 of FIG. 8A) is provided in detail. In the initial step 130₁, the User of the Device 13 running the Client 12₁ originates the Media to be transmitted. As noted above, the Media may be derived by speaking into a microphone, using a camera, receiving sensor data, or by some other Media generating component. In the next step 130₂, the Encode Receiver 28a encodes the Media and creates the indexed media payloads (step 130₃), which are then stored in the PIMB 30 (step 132) by the Data storer 28c.

In FIG. 8C, the sequence of the Transmit function performed by the PIMB Reader 26 (step 134 of FIG. 8A) on the sending client 12₁ is provided in detail. In decision loop 134₁, the transmit function of the PIMB Reader 26 continuously checks to see if indexed media payloads that are to be transmitted have been written into the PIMB 30 and are available for transmission. If such payloads are available in the PIMB 30, the Data Prioritizer 26f prioritizes the payloads that should be sent first, using the MCMS Participant Attributes information, as illustrated in step 134₂. Information about the highest priority payloads are passed to the

28

Packet Optimizer module 26g which runs the PQM (step 134₃), as described in more detail below with respect to FIGS. 9A-9C. The appropriate payloads are then retrieved from the PIMB 30 (step 134₄) by the Data Retriever 26h and converted into Vox packets 95 by the Packetizer 26i (step 134₅). The Vox packets 95 are then transmitted (step 134₆) by the Transmitter 26j over the network 18 to the receive Client 12₂, which sends back receipt reports reflecting the properties (loss, jitter, throughput) of the packets that have been received. These receipt reports provide the information necessary for the PQM to calculate the MABR for a given receiver. The aforementioned process is repeated for each transmission loop as indicated by the return arrow from the transmit step to the top of the flow chart.

In the embodiment described above, the media is encoded, stored in the PIMB 30 and then transmitted over the network in a serial fashion. In an alternative embodiment, the encoded media can be stored in the PIMB 30 and transmitted over the network in parallel, meaning the two functions occur substantially at the same time.

In FIG. 8D, the sequence for the Net Receive function (step 136 of FIG. 8A) of the PIMB Writer 28 on the receiving Client 12₂ is illustrated. In the initial step 136₁, the network receiver 28d receives the Vox packets 95 over the network 18. The Data Storer 28f converts the packets into indexed media payloads (step 136₃), which are stored in the PIMB 30 (step 136₄). As the payloads are stored, the Data Quality Manager (DQM) 28g is run. The DQM 28g checks for missing or corrupted packets, ensures the eventually storage of an exact copy of the transmitted data, and the sends receipt reports regarding the conditions of the network to the transmitter. Each of these functions of the DQM 28g are described in more detail below with regard to FIGS. 9D through 9F.

In FIG. 8E, the sequence for the Render function of the PIMB Reader 26 (box 140 of FIG. 8A) on the receive Client 12₂ is illustrated. In the initial step 140₁, the Data Prioritizer 26a prioritizes the indexed media payloads to be rendered as determined by the MCMS application 20 using the MTSID information as well as User status and presence information, including the User's Intentions and Attention status. The prioritized payloads are then read from the PIMB 30 (step 140₂) by the Data Retriever 26b. The PLC/Interpolator 26c performs packet loss compensation and interpolation (step 140₄) on the retrieved payloads, using known packet loss compensation and interpolation algorithms depending on which Codecs are used. In the next step, the Mixer 26d mixes (step 140₄) multiple Messages of a Conversation if two or more Participants have generated Media at the same time within the same Conversation (e.g., both are speaking at the same time). The Renderer 26e renders (step 140₅) the data stream from the Mixer 26d, generating sound, video, or other Media (step 140₆) for the recipient User.

In FIG. 8F, the sequence for a Server 16 to receive Vox packets from the previous hop on the network 18, store, archive and transmit the Vox packets to the next hop is illustrated. In the initial step, the Server 16 performs the Net Receive function of the PIMB writer (similar to FIG. 8D) to store the indexed media payloads of the received data in the PIMB 85 and archive 89 or the Server 16. The server 16 also performs the Transmit function of the PIMB writer (similar to FIG. 8C) to forward the received packets onto the next hop on the network 18. In this manner, a copy of the media generated by the transmit Client 12₁ is received, stored and transmitted at each hop along the path to the receive Client 12₂.

In the aforementioned embodiment, the writing of received indexed media is stored in the PIMB 91 of the Server 16 and transmitted to the next hop in a serial fashion. In an alternative embodiment, the received indexed media payloads can be stored in the PIMB 91 and transmitted to the next hop substantially at the same time. The storage of Media on the PIMB 30 of both transmitting and receiving Devices 13 allows for the progressive transmission and rendering of Media. On the transmit side, the Media originating on the transmitting device may be progressively transmitted over the network as it is being received. In various embodiments, the encoded Media (regardless of how it is originated) may be progressively transmitted before, after, or at substantially the same time it is stored in the PIMB 30. On the receive side, the incoming Media may also be progressively rendered as it is received over the network, provided the User has opted to Review the Media in the near real-time mode. In various embodiments, the incoming Media may be progressively rendered before, after or substantially at the same time as it is stored in the PIMB 30 of the receiving Device 13. If the received Media is to be Reviewed in the time-shifted mode, then the Media is retrieved from the PIMB 30 (or possibly a PIMB 85 on a Server 16 if replaced on the local PIMB 30) for later Review at a time designated by the User.

In the context of the present application, the term progressive or progressively is intended to be broadly construed and generally mean the continuous processing of a data stream based on availability of the data. For example, as Media is created or otherwise originated on a Device 13, the progressive encoding, storage, packetization and transmitting of that media is continuous, so long as the Media is available. As a person speaks, that Media is progressive or continuously encoded, stored, packetized and transmitted for the duration of the persons speech. When the person pauses or stops speaking, there is no media to progressively process. When the person resumes speaking again, the progressive processing of the Media resumes. On the receive side, the Media is also progressive processed as the Media is being received (i.e., available). As the Media is received it is continuously stored. It will also be continually rendered as the Media is being received when in the near real-time mode or from storage when in the time-shifted mode. Although the above explanation was provided in the context of voice, it should be understood that all types of Media can be progressively processed in a similar manner. Also the progressive processing of Media does not necessarily have to be progressively processed in time-indexed order. Rather the Media is processed in the order in which it is received. If Media is received out of index order, in one embodiment, the Media is progressively processed in the order it was received and then organized into the indexed sequence in the PIMB 30. In an alternative embodiment, the received Media can be organized into its indexed sequence and then progressively rendered.

H.2 PQM Operation Flow Diagrams

The PQM 26g relies on a metric called the Maximum Available Bit Rate (MABR), which is a continually computed approximation of actual transmission capacity or bandwidth (i.e., a measure of the capability of the network at a given point in time) between a sending and receiving node pair. As instantaneous network conditions change, the MABR is updated. Regular measurements of network throughput, packet loss, and jitter are considered in computing the MABR. In an alternative embodiment, the MABR may also be manually set or limited based on time of day, type of network, other conditions or parameters.

The PQM also considers the Intention of the recipient(s) to optimize transmission for time-sensitivity. A transmission is considered time-sensitive if either (i) the Intention of the recipient(s) is to Review the transmission "live" or in the near real-time mode, or (ii) the recipient would like to immediately Review a Message that for some reason is not currently stored on their Device 13 (e.g., the Message was previously stored in the archive 89). The Intention of the recipient can be either inferred by the behavior of the recipient or the recipient may set or otherwise designate their Intention. On the other hand, a transmission is considered to be not time-sensitive if the Intention of the recipient is to Review the Message in the time-shifted mode. The Intention of the recipient to Review the transmission in either the live or time-shifted mode at least partially defines the "timeliness requirements" of the transmission. In various other embodiments, factors such as the urgency or priority of transmissions may also be considered in defining the timeliness requirement of the transmission.

The nodes in the network path between a sender and a receiving pair also need to be consistent regarding the status of intentions of the recipients. If one target recipient indicates timeliness, meaning they wish to Review the transmission immediately or live, then all the intermediate nodes on the network along the sender-receiver path need to have the same timeliness requirement, regardless of the requirements of other recipients. The timeliness requirement of each of the intermediate nodes is therefore dependent on the receiving nodes the transmission is being sent to. This dependency is sometimes referred to as a "union of requirements" for target nodes in the network transmission path.

The PQM further considers an Ideal Bit Rate or "IBR" for each scheduled Message payload transmission. For time-sensitive transmissions, the IBR is computed based on the packetization rate needed for substantially real time or live communication (referred to herein as the Real Time Bit Rate or RTBR). With voice for example, a packetization rate of a packet every 20 milliseconds containing 20 milliseconds of audio data is considered an acceptable IBR for conducting live conversations. The RTBR for such a system in kilobits per second would be the size of 1 second of audio payload data plus the size of all network headers that would be generated for the transmission. For video media or a combination of voice and video, the RTBR will likely be substantially higher than simply voice. For other types of media such as sensor or GPS positioning data, the RTBR will likely be lower than that of voice. For non time-sensitive transmissions, the IBR is set to a Maximum Efficiency Bit Rate (MEBR) to optimize the usage or efficiency of transmissions over the network. The MEBR is calculated by adjusting the packetization rate to its largest possible value for the underlying network. If multiple messages or payloads are to be sent between a sending and receiving pair, then an Aggregate IBR (AIBR) is considered for the transmission.

The PQM operates by sending data in a series of transmission loops for each sending and receiving pair. The transmission loops for each sending and receiving pair are independent. Any transmission on the network may affect the MABR of other sending-receiving pairs. Accordingly, the MABR is preferably continually computed for all recipients.

Referring to FIGS. 9A through 9C, flow charts illustrating the sequence of operation of the PQM for a single sending and receiving pair is illustrated. In FIG. 9A, the steps in determining the MABR between the single sending and receiving pair are illustrated. In FIG. 9B, a flow chart

31

illustrating the steps for calculating the AIBR for each transmission loop for the single sending and receiving pair are illustrated. In FIG. 9C, a sequence for determining the amount of data to transmit between the sending and receiving pair per loop is illustrated. The processes illustrated in the three diagrams run simultaneously and interact with one another, as described in more detail below.

In FIG. 9A, a flow chart 50 for calculating the MABR for the network interface between the sending and receiving pair is shown. In the initial step 50₁, the network interface between the sending and receiving pair is monitored. The sender periodically receives reports, which contain information regarding the status of the network connection at the receiver in step 50₂. The reports include information regarding the current status of data throughput 50₃, packet loss 50₄, and jitter 50₅ as observed by the receiver at the network interface. In step 50₆, the MABR is calculated at the sender based on these observations contained in the reports. By monitoring or observing the data in these reports, the MABR value is continually adjusted based on current network capabilities or conditions between the sending and receiving pair. As network capabilities become more favorable for data transmission, the MABR will increase. If the network capabilities become less favorable for transmission, the MABR will decrease, potentially all the way to zero for an unusable network. The reports are similar to the packet loss reports generated by nodes in TCP networks, but additionally include throughput and jitter information as well.

If there are several network interfaces between the sending and receiving pair, an MABR is calculated for each interface for which a receipt report is received. If no traffic has been recently sent on the network, or no receipt reports have been received, the MABR may not reflect current network conditions. However, since receipt reports are generated continually by receivers while data is transmitted, the sender's MABR metrics will quickly converge to a more accurate value.

Referring to FIG. 9B, a flow chart 52 illustrating the steps for calculating the AIBR for a transmission loop is illustrated. In the initial step 52₁, the Messages with Media (by which we mean portions of the time indexed media that belongs to this Message) ready to be transmitted between the sending and receiving pair in the current loop are ascertained. A list of Messages with Media is then built 52₂. For each Message in the list 52₃, the time-sensitivity or timeliness requirement of each Message is considered 52₄. If a particular Message is not time-sensitive, then the IBR is set to the Maximum Efficiency Bit Rate (MEBR) 52₅. On the other hand, if a Message is time-sensitive, then the IBR is set to the Real Time Bit Rate (RTBR) 52₆. In the next step 52₇, the previously computed IBRs for each of the Messages in the list are summed together, resulting in the Aggregate Ideal Bit Rate (AIBR) 52₈ for the transmission loop. As signified by the return arrow 52₉, the above-described process is repeated for each transmission loop between the sending and receiving pair.

Referring to FIG. 9C, a flow chart 54 illustrating the sequence for determining the rate of data to transmit between the sending and receiving pair per transmission loop is illustrated. In the initial step 54₁, the MABR (as calculated in FIG. 9A) is compared to the AIBR (as determined in FIG. 9B) for the next transmission.

If the MABR is greater than or equal to the AIBR, then all the Messages identified as ready for transmission in the loop are packetized at the IBR rate 54₂ and transmitted 54₃.

On the other hand, if the MABR is less than the AIBR, then a series of procedures are applied to so that the PQM

32

meets its goals of the timely delivery of an adequate copy of the data, the efficient use of available bandwidth, and/or adjustments to the payload content and quality, packet size, and transmission rate to meet current network conditions.

In the initial step, the Messages in the list are reviewed for time sensitivity 54₄. If there are no time sensitive Messages, then the bit rate is reduced to the MABR 54₅, and the Messages are transmitted 54₃.

If the list includes time-sensitive Messages, the bit rate allocated for the non time-sensitive Messages is reduced 54₆ until it meets the MABR limits. If reducing the bit rate all the way to zero is insufficient to meet the MABR, then these non time-sensitive Messages are removed from the list of Messages to be transmitted in the loop. If the bit rate has been reduced so that it is less than or equal to the MABR, then the remaining Messages are Packetized and transmitted 54₃.

If the removal of non time-sensitive Messages was not sufficient to meet MABR, then another procedure involving the use of a lower quality Codec (or Codecs) for the remaining time-sensitive Messages 54₇ is used. An attempt is made to transmit the payload data as fast as possible by sending fewer bits during the transmission loop. In other words, by reducing the quality of the payload, the transmission sends fewer bits in a given period of time. In various embodiments, different Codec or Codecs, each having a different bit rate versus quality tradeoff, may be used. If the use of the lower quality Codec or Codecs is sufficient, meaning the MABR limit is met, then the Messages are transmitted 54₃.

If the use of lower quality Codec(s) still does not meet the MABR, then the packetization interval of the time-sensitive Messages is increased 54₈. With this procedure, the header-to-payload ratio is increased, which lowers the overall bit rate but introduces latency (i.e., a delay in the delivery of the transmission to the recipient). If this procedure results in the reduction of the AIBR to less than or equal to the MABR, then the transmission 54₃ occurs.

If after changing the packetization interval the MABR is still not met, then the bit rate may be progressively lowered 54₉ to be within the MABR limit. When the bit rate is lowered in this manner, time-sensitive messages are sent at a rate that is not sufficient to maintain a live conversation. Therefore, the Conversation is forced out of "live". If the network is down or conditions are very poor, it is possible that no data transmission may occur. Again, the aforementioned sequence is repeated for each transmission loop 54₁₀ between the sending and receiving pair.

If there are multiple network interfaces between the sending and receiving pair, the sequence described in relation to FIG. 9C is performed for each interface for which receipt reports are available. In various embodiments, the sender may contain logic to distribute the transmission load among the multiple interfaces. In different examples, the payloads can be sent only on one interface, while in other embodiments, some or all of the interfaces may be used.

The aforementioned description pertains to any sending and receiving pair in the system 10. In most situations, the sending and receiving pair will include a Client 12, enabled Device 13 and Server 16, two Servers 16, a Server 16 and Client 12 enabled Device 13, or even possibly two Clients 12 respectively. If a sending node is transmitting to two (or more) receiving nodes at the same time, the above mentioned sequence as described in relation to FIGS. 9A-9C occurs concurrently for each receiving-sending pair.

33

H.3 DQM Operation Flow Diagrams

The DQM 28g determines if data received at the Client 12 is either corrupted or if there are missing packets. In addition, the DQM 28g of a receiving Client 12 generates of the receipt reports, which are sent back to the transmitting node on the network. The DQM 28g also runs a background process to ensure that an exact copy of transmitted data is eventually received and stored. These functions are described below in FIGS. 9D through 9F respectively.

Referring to FIG. 9D, a flow diagram illustrating the operation of the DQM 28g for checking for missing and/or corrupted data is illustrated. In the initial step 56₁, the DQM 28g checks for corrupted packets using well-known techniques, such as CRC or similar integrity checking mechanisms. If a packet is corrupted, that packet is treated as missing 56₂. The DQM 28g next ascertains if any packets are missing 56₃. If an out of sequence packet is not received after a predetermined period of time, it is assumed to be missing. The DQM 28g notes any missing or corrupted packets 56₄ in the DNQS 32. On the other hand if no corrupted or missing packets are detected, the DQM 28g determines if the quality of the received data was intentionally degraded by the sender 56₅ for the purpose of saving bandwidth. The degraded quality is noted in the DNQS 32 56₆. Regardless if the quality of the received data is degraded or not, receipt information (e.g., a packet sequence number, time stamp, and the network address of the next node in the network the packet is to be sent) of the data is stored 56₇ in the DNQS 32. The aforementioned process is continually repeated, as signified by the return arrow to the start of the flow diagram.

As a result of the process detailed in FIG. 9D, information regarding the receipt of non-degraded packets, the deficiency of degraded quality packets, and missing packets, are all stored in the DNQS 32. As Media is received, the DNQS 32 maintains up-to-date information regarding the status of the Media.

Referring to FIG. 9E, a flow diagram illustrating the operation of the receipt report generator function of the DQM 28g is illustrated. In the initial step, the DNQS 32 is periodically scanned 58₁ to determine if there is any Media for which a receipt report needs to be generated 58₂. If the answer is no, then the above scanning process is repeated. On the other hand if Media is identified, then the process determines if the Media is time-sensitive 58₃, meaning either the User intends to Review the Media live or the user would like to immediately Review Media that is not stored on their Device 13.

If not time-sensitive, then the recipient informs the sender to set the retransmission priority (as defined below) to low 58₄. If time-sensitive, then the amount of packet loss is considered 58₅. If the amount of packet loss is outside a usable quality range, the retransmission priority is set to high 58₆. As noted above, if the amount of packet loss is too large, the recipient may not be enabled to Review the Media upon receipt. If the quality is within an acceptable range, meaning the quality of the transmission is sufficient that it can be understood when rendered, then the priority for the sending of the receipt report is set to low 58₄. Regardless if the recipient is Reviewing upon receipt or not, a receipt report is sent 58₇, the DNQS 32 is updated 58₈, and the Network Quality Manager (NQM) 28h is updated 58₉. The retransmission requests defined in step 58₄ is therefore conditional based on time-sensitivity. The transmission request defined in step 58₆ is conditional on both time-sensitivity and quality.

34

The retransmission priority informs the PQM 26g of the sender to properly prioritize the transmission rate for the Media that requires retransmission. For example when the retransmission priority is set to high, then the sending PQM 26g of the sender should send any retransmissions before any new Media. If the priority is low, the PQM 26g should send the retransmitted Media after any new Media.

The aforementioned process is continuously repeated so that receipt reports are generated as Media is received. If the sender does not receive receipt reports in a timely manner, the PQM 26g of the sender will reduce the transmission rate, eventually stopping the transmission if no receipt reports are received.

Referring to FIG. 9F, a flow diagram illustrating the sequence for requesting of missing or degraded Media is illustrated. In the initial step 60₁, the DNQS 32 is periodically scanned for missing or degraded Media 60₂. If there is no missing or degraded Media, then the above defined scan is periodically repeated.

Media is considered missing if an out of sequence packet does not arrive after a predetermined threshold period of time 60₃. If the packet arrives before the threshold, then it is no longer considered missing. On the other hand if the packet does not arrive after the threshold is exceeded, then it is deemed missing. With missing packets, a low priority request for retransmission is made 60₄, and the time of the request is noted 60₅ in the DNQS 32. This process is repeated until the missing packet is received. When the missing packet arrives and the corresponding Media is available in the PIMB 30, the missing status of the Media is removed from the DNQS 32. The retransmission request defined in step 60₄ is therefore conditional based on whether the Media is determined to be missing.

If degraded, the DQM 32 determines if the Media is part of a live Conversation 60₆. If not, a request for a full quality copy of the degraded Media is made 60₇, the full quality Media is designated as missing 60₈, and the request time is noted 60₉, in the DNQS 32. If the Media is part of a live Conversation, then no action is immediately taken in order to preserve network bandwidth. When the Conversation transitions out of the live mode, then the steps 60₇ through 60₉ are performed to ensure that a full quality (i.e. an exact or perfect) copy of the degraded Media is eventually received. When the data becomes available in the PIMB 30 of the recipient Client 12, the degraded status of the associated Media is removed from the DNQS 32. The transmission request defined in step 60₇ is conditional on whether the Media is both degraded and not part of a live conversation.

The aforementioned process is continually repeated, as signified by the return arrows from 60₅ and 60₉ to the top of the flow diagram at 60₁. By repeating the process outlined in FIG. 9F, exact copies of all transmitted Media is eventually stored in the PIMB 30 of the receiving Device 13. In this manner, the storage of exact copies of transmitted Media is guaranteed at the recipient Device 13.

I. Graphical User Interface

Referring to FIG. 10, an exemplary Device 13 running Client application 12 is illustrated. The Device 13 includes a graphical user interface display 110, data entry buttons, keys, or keyboard 112, a microphone 114, and a transducer 116 for converting electrical signals into sound, such as a speaker. The display 110 may also accept input as a touch screen. Further, the display 110 and keyboard 112 may be combined using a touch screen interface. As noted above, the Device 13 may be a variety of different communication

tools, such as a desktop computer, laptop or other mobile computers, personal digital assistants, a programmable land-line or cellular phone, or programmable radios, or just about any other type of programmable communication device. The exemplary Device 13 illustrated in the figure is intended to be “generic”, in the sense that it is supposed to represent or encompass all of the communication devices listed above. In addition, the term “graphical” user interface should not be construed as limiting. Other types of user interfaces which can be implemented on a Device 13 as well including Audio/DTMF interfaces, Voice User Interfaces (VUI), radio switch interfaces, or a combination thereof, can all be used to implement the various functions described below. For the sake of simplicity, each of these types of methods by which a User may interact with their Device 13 are generically referred to as a “user interface”.

All Devices 13, regardless of their type, preferably have a user interface that enables the user to operate the Device 13 and communicate with other User's in the system 10. Although the user interface can be designed to have virtually an infinite number of different look and feel implementations, there are certain functions and features that all Devices 13 should have in common. These functions and features are listed below.

The user interface preferably includes one or more of the following status indicators or flags: (i) battery indicator; (ii) connectivity indicator; (iii) clock; (iv) transmitter status; (v) transmission sync status; (vi) Reviewing status; (vii) Priority Messages needing attention; and (viii) missed Messages.

The user interface preferably includes the following functions, flags and components to conduct and manage a single Conversation: (i) name of a Conversation and/or list of Participants; (ii) Conversation status; (iii) Conversation type; (iv) Conversation duration; (v) time behind the Head of the Conversation; (vi) outstanding Messages; (vii) presence/status of Participants; (viii) meta data with navigation; (ix) Conversation attributes or designators; (x) Conversation set-up including title, scheduling, Participants, Conversation summary; and (xi) indicators showing which Participants have contributed Messages and which have Listened to or Reviewed messages.

The user interface also preferably includes, in addition to those listed immediately above, the following functions, flags and components to conduct and manage multiple Conversations: (i) a name/identifier for each Conversation; (ii) live/active or standing/inactive indicator; (iii) Review position, either at Head or Time shifted; (iv) Priority and other attributes; and (v) indicators of what portions of Conversations were missed.

The user interface also preferably includes, a number of navigation features, such as: (i) DVR style fast back/forward per conversation; (ii) instant messaging style personal message navigation; (iii) Conversation Time indicators; (iv) time scale shifting (i.e. zooming backward and forward through a Message or the Messages of a Conversation); (v) changing Priority of Conversations; (vi) hanging up; and (vii) home.

The aforementioned functions and features may be implemented in a variety of ways, for example using a touch-screen graphical user interface 110, or other input devices, such as the data entry buttons, keys, or keyboard 112, a mouse, by voice-activated commands, or a combination thereof. Again the functions and features listed above and how they are implemented is not intended to be exhaustive. The various methods and technologies that could be used is so comprehensive, that it is not practical to list or discuss them all herein.

The MCMS application 20 supports a number of different types of Conversations, such as a near real time or “live” calls where the delay from when a Participant speaks and the other Participant(s) hear the first Participant is very small, Conversations where Participants exchange voice Messages back and forth with a longer delay between Messages, “live” conference calls involving multiple Users, standing Conference calls at a regularly scheduled times, or configurable structured call types such as a simultaneous briefing, where Participants each leave a Message briefing beforehand for others to Review to before everyone joins the live conference call. Yet another unique attribute of the MCMS application 20 is the ability for Users to transition between the different types of Conversations. For example, the Participants can seamlessly transition from a voice-messaging mode to a live call and back again. Or the Participants of a live conference call can transition to a voice-messaging mode and send updates or action items to each other after the conference call. While several examples have been noted, it should be understood that the system 10 is extremely flexible and provides numerous options to transition between different types of calls or Conversations and between multiple conversations. By varying the delay between Messages, the Participants effectively flows between the type of Conversation that best suits their needs. The above examples should therefore not be construed as limiting.

As noted above, Conversations consist of Messages maintained in their original context and sequence. A sent Message either belongs to an existing Conversation or begins a new Conversation. A typical Conversation includes a set of Messages that are organized around a defined subject matter, topic, time, Group or Channel. For example, Conversations may involve a common Group of people such as the members of a club, a company may have a standing Conversation at a fixed time, such as a weekly sales meeting, or friends may have ad-hoc Conversations on various topics, such as making dinner plans.

Each Conversation is defined by a set of attributes, including a name, a list of Participants, begin and end time, and state including at least pending, active, or terminated. Other Conversation states are possible in other embodiments. A User interacts with the MCMS application 20 on their Devices 13. In preferred embodiments, the interface allows a User to organize Conversations by any of the various attributes.

The relationship between a Participant and a Conversation also has attributes. These attributes include, but are not limited to, Priority, Status (states of participation in a Conversation). The values of Participant status include active, participation in more than one Conversation at a time, Reviewing a Conversation in a time-shifted mode, Catching Up To Live, passively participating (i.e., not actively Reviewing, but receiving high Priority Messages), standby, or ignoring a Conversation (i.e., declined to participate or record the Conversation).

From a recipient's perspective, a User may select or define the relative priority of Messages. For example, Messages from a person's boss would typically be given a higher Priority than a social acquaintance. In some embodiments, a recipient has the ability to set their own Priorities. In the implementation of MCMS-C the User selects a subset of their Conversations to be rendered consecutively. The User then sets ordered Priorities for these Conversations. The system uses the priorities set by the user to order the

37

Messages to be rendered. The aforementioned algorithm queues the Messages to be rendered using User Priorities and information concerning Message data available (beyond MTSD).

In other embodiments, such as tactical communications, the recipient may have no or limited ability to set Priorities. For example, a fire fighter may have no ability to lower the Priority of Messages from the fire chief. A sending-User, however, has the ability to send urgent or highly important Messages. By Tagging a Message as urgent or an emergency, the Message is rendered as soon as possible at the recipient(s), overriding any Priority settings of the recipient. Any conflicts among multiple emergency messages are resolved based on a predetermined priority scheme.

K. MCMS Operation

Referring to FIG. 11A, an organizational diagram 1100 grouping the major functions of the MCMS application 20 is illustrated. The major functions include account management 1102, conversation management 1104, aggregate conversation list management 1106, conversation participation 1108, call controls 1110, and contact management 1112. After registering and logging into the system 10, the User may navigate through the user interface of their Device 13 implementing the various management functions, described in detail below. In some embodiments, this functionality will provide a great deal of flexibility. In other embodiments, such as tactical or communication radios, the implementation of the user interface may be constrained with many of the user functionality and options preconfigured to meet the utility of the device. The discussion here is exemplary and is not intended to be an exhaustive explanation of the MCMS functionality, but rather is intended to provide just an overview of some of the MCMS attributes.

K.1 Account Management

Under the account management function 1102, a registered User may change certain settings and preferences. A User may change their email address, password, name, phone number, phone password, call-in number, default and/or User defined rendering speeds, Tags, gain or volume levels for Reviewing Messages, Catch Up to Live mode, etc. To make these changes, the User enters the appropriate information through the interface 110 of their Device 13. The MCMS application 20 responds by writing the updated preferences into the MCMS database 22.

K.2 Conversation Management

As illustrated in FIG. 11B, conversation management 1104 is a set of functions that allow a User to view their aggregate Conversation lists, create a new Conversation, update the details of a Conversation, delete a Conversation, and close a Conversation. Each of these functions are described below.

View Conversations 1104a—For each Conversation, the MCMS application 20 may provide the User the one or more of the following attributes: the name of the Conversation, the actual start time, the last activity, Tags, duration, and the list of Participants. For each Participant, the name and/or phone number, status (live, other call, in past, catch-up-mode, offline-reachable, offline-unavailable.)

Create a Conversation 1104b—A User creates a Conversation through the interface 110 by inputting a Conversation name, a list of Contacts, and an optional scheduled start time. If no start time is designated, it is assumed the start time is immediate. In response, the MCMS application 20 creates a new Conversation in the database 22, associating records for each Participant on the Contacts list. The MCMS

38

application 20 also creates in the database 22 Participant records for each User on the Contact list, allowing the caller to receive the presence information of the others on the Contact list. If the Conversation is scheduled, the MCMS application 20 starts the Conversation at the designated time. Otherwise, the Conversation starts right away.

Update Conversation Details 1104c—The User may make changes to a Conversation through the user interface 110. For example, Participants may be added or removed. Any change in status of the participants is updated in the MCMS database 22.

Delete a Conversation 1104d—A User may delete a specific Conversation from their list of Conversations through the interface 110. In response, the MCMS application 20 notes the change in the database 22, and designates the Conversation as deleted.

Close a Conversation 1104e—A User may elect to terminate or close a Conversation. In one embodiment, only the User that creates a Conversation can elect to terminate that Conversation.

K.3 Aggregate Conversation List Management

As illustrated in FIG. 11C, the aggregate conversation list management 1106 is a set of functions that allow a User to engage in multiple Conversations (i.e., the User's aggregate conversation list). The aggregate conversation list management functions allow a User, through the interface 110 on their device, to participate in one Conversation "live", while participating in other Conversations in a time-shifted mode.

Chose Conversation 1106a—Through the interface 110, a User may select one Conversation among the User's aggregate conversation list as current. The Messages of the current Conversation may be rendered in either the "live" or time-shifted modes. The User may switch the current conversation among the aggregate conversation list from time-to-time.

Switch Conversations Modes 1106b—In an optional embodiment, a User may be able to switch from the MCMS, MCMS-C and MCMS-S modes of operation.

K.4 Conversation Participation

As illustrated in FIG. 11D, conversation participation 1108 is a set of functions that allow a User to start a Conversation, receive a notification to join a Conversation, obtain Conversation status information, and hang up on a Conversation.

Start a Conversation 1108a—After a Conversation has been created, either by the User through the interface 110 or the scheduler in the MCMS application, the status of each Participant is checked. If a Participant is offline, then an effort is made to contact that person. If a Participant is online but engaged in another Conversation, then the MCMS application 20 notifies that Participant. The presence status of all online Participants is updated in the database 22.

Receive a Notification 1108b—The system may notify a User that their attention has been requested on a Conversation through a graphic display and/or audible notification via the user interface 110.

Conversation Status 1108c—A user may request the status of a Conversation through the interface 110 of their Device 13. In response, the MCMS application 20 assembles the status information stored in the database 22 and presents the information to the User.

Conversation Pause 1108d—Through user interface 110, a User may hang up or switch away from an active Conversation. In response, the MCMS application 20 updates the User's participant status for active Conversations in the database 22 and directs the Store and Stream module 24 to remove the User from the Conversation.

K.5 Conversation Controls

As illustrated in FIG. 11E, conversation control 1110 is a set of functions that allow a User to control their participation in a Conversation. These functions allow a User to catch-up-to live, skip to the Head, jump to a past location, pause, play faster and play slower when Reviewing the Messages of a Conversation. Each of these functions is triggered by the User through the interface 110 on the Device 13.

Catch-up-to-live 1110a—A User may Catch Up To Live in an ongoing Conversation using the “CTL” function. When this function is activated, the MCMS application 20 checks the last point in the Conversation the User has reviewed and directs the Store and Stream module 24 to render the Messages not previously heard, using a faster than normal rendering option designated by the User, and to seamlessly transition to live mode when it reaches the head.

Jump to Head 1110c—This function enables a User to jump to the Head of a Conversation, skipping over any intervening Messages between the current point of the User in the Conversation and the Head. When implemented, the MCMS application 20 instructs the Store and Stream module to immediately render the Messages at the Head of the Conversation. (If the Head of the Conversation is currently live this is called Jump to Live (JTL)).

Jump to past 1110d—This function enables a User to jump back to a previous Message or point in the Conversation, similar to a rewind or replay function. When implemented, the MCMS application 20 instructs the Store and Stream module 24 to render Media starting from the rewind point.

Pause 1110e—This function enables the User to pause the Reviewing of the Messages of a Conversation. In response, the Store and Stream module 24 stops the rendering of Messages until another command is issued.

Play faster 1110f—This function enables a User to render Messages more quickly. In response, the Store and Stream module 24 renders the Messages at a faster rate than normal. The rendering rate may be either specified by the User or the User may select from a number of preset options.

Play slower 1110g—This function enables a User to render Messages more slowly. In response, the Store and Stream module 24 renders the Messages at a slower rate than normal. The rendering rate may be either specified by the User or the User may select from a number of preset options.

K.6 Contact Management

As illustrated in FIG. 11F, the system 10 provides the User with a host of functions for managing Contact lists and user Groups. These functions include the adding, editing, deleting Contacts and user Groups. Each of these functions are implemented by a User through the interface of their Device 13. Any revisions or deletions in a User's Contact list or Group list is stored in the MCMS database 22.

Add a Contact 1112a—This function enables a User to add a new Contact to their contact list. The new Contact can be either a registered User or an external contact. Typically the name, phone number(s), type of number (cell, office, home, computer, etc.), email address and other personal information are provided for each contact record.

Edit a Contact 1112b—This function enables a User to edit or update an existing contact record.

Delete a Contact 1112c—This function enables a User to remove or delete an existing contact record.

Search for a Contact 1112d—This function enables a User to search for a specific Contact in their contact list. The

search may be conducted using a number of criteria, such as name, phone number, most recently called, most frequently called, Group, etc.

Get a Participant list 1112e—This function enables a User to search and retrieve a list of Participants of a Conversation by a number of different search criteria, including for example by name, most recent outgoing calls, most recent incoming calls, most frequently called, etc.

Authorize a caller to review status 1112f—This function enables a first User to authorize other Users to view the first User's status. Non-authorized Users may not view the status of the first User.

Create a Group of Contacts 1112g—This function enables a User to associate a number of Contacts into a Group. When a User defines a Group, the list of Contacts in that Group are stored in the MCMS database 22.

Edit a Contact Group 1112h—This function enables a User to edit a Group, or update the contact information for a member of the Group.

Delete a Contact Group 1112i—This function enables a User to delete a Group.

L. MCMS Operation

L.1 MCMS-C

As noted above, the MCMS-C operation is similar to MCMS, with the added feature of enabling Users to manage and participate in multiple conversations consecutively through a hierarchical system of Priorities and the time-shifting of Messages, which are automatically managed by the system. Implementing the MCMS-C functionality includes three basic processes. As illustrated in FIG. 12A, the first process involves defining a set of Conversations for consecutive rendering. Once the list is defined, a hierarchical set of Priorities and other factors are applied to the indexed media payloads associated with the set of Conversations. The indexed media payloads are then sequenced into a sequencing order. By rendering the media in the sequence order, the Messages of the set of Conversations are consecutively rendered.

Referring to FIG. 12A, a flow chart illustrating the steps for defining the list of Conversations to render consecutively is shown. In the initial step 1202, the User's aggregate list of Conversations is defined. Either the User or pre-configuration data (step 1204) is next used to select the Conversations among the aggregate list for consecutive rendering (step 1206). With a tactical communication system for example, typically pre-configuration data is used to impose the Conversations to be consecutively rendered. With non-tactical applications, the User is typically given a higher degree of flexibility to select the Conversations for consecutive rendering.

Referring to FIG. 12B, a flow chart illustrating the steps for defining hierarchical set of priorities for rendering the Messages of consecutive Conversations is illustrated. In the initial step (1208), a set of priority rules are defined and applied to the list of Conversations to be rendered consecutively (1206). In various embodiments, the set of priority rules may range from a rigid, hierarchical communication protocol to a highly flexible communication protocol. For example in a tactical communication system where a rigid hierarchy is often desirable, the set of priority rules will preferably impose a specific order in which concurrent Messages are rendered. For example with a first-responder tactical system, Messages from a fire chief may be given the highest priority. The next level of priority may be given to fire fighters inside a burning building. At the next level,

priority may be given to fire fighters outside the building, etc. By defining a rigid priority, the current Messages of those supervising the efforts to fight the fire, or those in harm's way, are rendered ahead of those performing a less critical role. With non-tactical communications, a User may be given a great deal of flexibility to define their own priority scheme to meet personal needs. A sales executive may for example define a priority scheme listing consecutive Conversations with clients from the most important to the least important. Or a User may prioritize consecutive Messages among family and friends. Regardless of the scheme used, a priority list for consecutive Conversations is defined (step 1210) in this process.

Referring to FIG. 12C, a flow diagram illustrating the construction of a queue of Messages received from the various consecutive Conversations is illustrated. In the initial step, the availability of non-rendered indexed media payloads of Messages (i.e., media streams) is continually detected (step 1212) for each of the Conversations to be consecutively rendered. The priority hierarchy is applied to the available indexed media payload streams (step 1214). Based at least partially on the priority hierarchy, and possible other parameters as mentioned below, the available indexed media payloads are arranged into a sequence order (step 1216). The indexed media payloads are then continuously rendered in the sequence order (step 1218). By continuously repeating the above-described process, the Messages of multiple Conversations are consecutively rendered.

In one embodiment, the sequencing order is based either partly or fully on the priority hierarchy. In alternative embodiments, other parameters in addition to the hierarchy and availability may be considered as well. For example, the sequence order may be defined using one or more parameters such as the switching costs associated with interrupting a currently rendered stream of indexed media payloads with the indexed media payloads of a higher priority Conversation, the quality of the available streams of indexed media payloads, the relative time the indexed media payloads were received, a shuffling order, or from input of a controller of the system.

Typically when conflicts between the Messages of different Conversations occur, the indexed media payloads first in sequence order are rendered while the rendering of other available indexed media payloads are paused or delayed. When there no conflicts, indexed media payloads are immediately rendered as they become available.

In yet another embodiment, the Messages of the consecutively rendered Conversations may be optionally reviewed in a time-shifted mode. If the User of the first communication device generated any Media associated with the consecutively rendered Conversations, that media is indexed and stored in the PIMB 30 of the Device as well as the PIMB(s) 85 of the Servers 16 on the network. Thus when a Conversation is reviewed in the time shifted mode, the User has the option of reviewing just the incoming Messages associated with the Conversation, or both the incoming Messages as well as the Media created by the first User associated with the Conversation in time index order.

L.2 MCMS-S Operation

In the MCMS-S or simultaneous mode, a User of a Client 12 enabled Device 13 may define a set of Conversations for simultaneous rendering. Once the set of Conversations is defined, the indexed media payload streams associated with the set of Conversations are simultaneously rendered on the Device 13, regardless if they overlap or not. In alternative embodiments, the User may optionally render the received indexed media payloads from the set of media streams

separately. The indexed media payloads of the simultaneous Conversations may also be optionally rendered in near real-time or in the time-shifted mode.

L.3 MCMS, MCMS-C and MCMS-S Examples

In FIGS. 13A through 13D, a series of diagrams illustrating the attributes of a Conversation and the operation of MCMS, MCMS-C and MSMS-S is illustrated.

In FIG. 13A, a time diagram illustrating the sequence of rendering the indexed media payloads of the Messages of a Conversation labeled "A" between a User "X" and two other users, designated "Y" and "Z". In this example, Media is generated by user Y during the time intervals designated by t1, t5, t6, t7 and t9. Media is generated by user Z during the time intervals designated t3, t6 and t9 through t10.

The rendering sequence at the Device 13 of User X is illustrated at the bottom of the figure. During intervals t1, t5, and t7, Media derived only from Y is rendered. During intervals t3 and t10, only Media derived from Z is rendered. In intervals t6 and t9, Media from both Y and Z is rendered. In intervals t2, t4 and t8, nothing is being rendered because neither users Y or Z are generating Media during these periods. It should be noted that intervals t1 through t10 are not intended to mean fixed time intervals, but rather, just periods of time when Media is being generated.

The diagram of FIG. 13A is useful in illustrating the attributes of Conversations. When one user is generating Media (either Y or Z), that Media is received at the Device 13 of X and is available for rendering. When both users X and Y are generating Media, both Media streams are received at Device 13 of X and is available for Mixing. When neither user X or Y is generating Media, no Media is received at Device 13 of X. As noted above, User X has the option of Reviewing the Media generated during Conversation A in either the near real-time or time-shifted modes. Also the User X has the option of Reviewing the Media in the Mixed format as illustrated, or to separately Reviewing the Media from Y and Z in the time-shifted mode.

FIG. 13B illustrates the operation of MCMS. In this example, the User is Participating in three Conversations, designated A, B and C. For Conversations A, B, and C, the User either generates or receives Messages designated (A1, A2, A3, and A4), (B1, B2 and B3) and (C1 and C2) respectively. The timing and duration of each Message is indicated by the starting point along the time-line. It is useful to note that in this example, all of the Messages overlap in time to some degree, except Message B2.

With the MCMS application, the User selects one Conversation as current. For the selected Conversation, the User may Review incoming Messages and generate Messages which are transmitted to the other Participants of the Conversation. In this example, the User selects in order Conversation B, C and A as current respectively. The Message sequence is therefore initially B1, B2, and B3, followed by C1 and C2, and then finally A1 through A4. Again, while a particular Conversation is selected as current, the User may transition between the near real-time and the time-shifted modes and back again. The final rendering as illustrated in the diagram is not intended to correspond in timing of the received Messages as illustrated in the top portion of the diagram. Rather the lower portion of the diagram is intended to show only the rendering order of the Messages, based on Conversation order selected by the User.

The example of FIG. 13B is thus useful in illustrating the attributes of the MCMS application. A User selects one Conversation as current. The other Conversations are paused. The User may also transition the current Conversation among all the Conversations at any time.

43

Referring to FIG. 13C, a diagram illustrating the operation of MCMS-C is illustrated. In this example, the User is Participating in two consecutive Conversations, A and B. With Conversation A, three Messages are received A1, A2, and A3. With Conversation B, three Messages are received B1, B2 and B3. It is useful to note that with this example, Message B1 conflicts with Messages A1. Also Conversation A has a higher priority than Conversation B.

During the consecutive rendering of the two Conversations, the higher priority Messages A1 and A2 are first rendered in near real-time, as represented by the vertical dashed lines in the figure. Since there is a relatively large time gap between Messages A2 and A3, this space is filled by time shifting and rendering Messages B1 and B2. When A3 arrives, it is rendered in near real-time, while Message B3 is rendered only after the higher priority Message A3 is rendered. By time-shifting rendering of the lower priority Messages between the higher Priority Messages, consecutive multiple conversations can be managed. It should be noted that in this simple example, priority is the only parameter used to determine the consecutive order for rendering. As noted above, a number of other parameters may be used as well.

Referring to FIG. 13D, a diagram illustrating MCMS-S is illustrated. In this example, a User is engaged in three simultaneous Conversations, A, B and C. The Messages A1, A2 and A3, B1, B2 and B3, and C1 and C2 are received for each Conversation A, B and C are shown in the diagram respectively. With the MCMS-S, the incoming Messages are rendered at a recipient's Device 13 as they are received. The rendering sequence of the Messages of the three Conversations A, B and C, as illustrated in the lower portion of the diagram, are therefore the same as when the Messages were received. In this manner, multiple Conversations may be simultaneously rendered.

In the aforementioned examples, several variations of the MCMS application were described, including MSMS-C and MCMS-S. Regardless of the specific type of MCMS application used, they all share several common characteristics. In each case, the Conversations are defined by a threaded sequence or organization of Messages. The Messages are segmented from a stream of Media, with each Message given a sequence identifier and indexed by the time the Media was created. Depending on the variation of the MCMS application, Messages can be rendered in accordance with one or more rendering options. The rendering options include, in one form or another, the filtering, grouping, overlapping and/or serialization of Messages, using anywhere from zero to a plurality of different attributes. In this manner, multiple Conversations, each including a string of Messages, can be conducted on a single Client 12 enabled Device 13. Lastly, each of the variations of MCMS may handle the receipt of interrupt Messages in the same way. When an interrupt Message is received, it typically takes precedent over and is rendered before other Messages belonging to other Conversations.

M. Client and Server Hardware

Referring to FIG. 14A, a block diagram 140 illustrating the hardware of a Device 13 used for storing and executing the Client application 12 is shown. The hardware includes a CPU 142, main memory 144 and mass storage 146. As is well known in the art, the Client application 12 is loaded and stored in main memory 144 and mass storage 146 and executed by the CPU 142.

44

Referring to FIG. 14B, a block diagram 150 illustrating the hardware of a Server 16 used for storing and executing the server application 78 is shown. The hardware includes a CPU 152, main memory 154, mass storage 156, and the archive 89. As is well known in the art, the server application 78 is loaded and stored in main memory 154 and mass storage 156 and executed by the CPU 152. As noted above, indexed media payloads of one or more Users are stored in the archive 89.

Although many of the components and processes are described above in the singular for convenience, it will be appreciated by one of skill in the art that multiple components and repeated processes can also be used to practice the techniques of the system and method described herein. Further, while the invention has been particularly shown and described with reference to specific embodiments thereof, it will be understood by those skilled in the art that changes in the form and details of the disclosed embodiments may be made without departing from the spirit or scope of the invention. For example, embodiments of the invention may be employed with a variety of components and should not be restricted to the ones mentioned above. It is therefore intended that the invention be interpreted to include all variations and equivalents that fall within the true spirit and scope of the invention.

What is claimed is:

1. A method for operating a video message service infrastructure on a network, the method comprising:

receiving, at the video message service infrastructure, a video message transmitted by a sending device, the video message containing video media, the video media being transmitted as the video media is created; generating, by the video message service infrastructure, two or more degraded versions of the video media of the video message, where each of the two or more degraded versions is created by degrading the quality of the video media by a different amount;

selecting one of the degraded versions of the video media based on an ascertained bandwidth on the network for delivering the video media from the video message service infrastructure to a recipient device on the network; and

transmitting the selected degraded version of the video media from the video message service infrastructure to the recipient device so that the recipient device can render at least a portion of the video media on the recipient device, the video message service infrastructure operating so that the rendering occurs:

- (i) while the video media of the video message is being created and transmitted over the network by the sending device; and
- (ii) without having to first establish an end-to-end connection over the network between the sending device and the recipient device before the sending device begins to transmit the video media of the video message.

2. The method of claim 1, wherein at least one of the two or more degraded versions of the video media of the video message is generated by reducing a bit rate used to represent the video media relative to a complete bit rate representation of the video media as received by the video message service infrastructure.

3. The method of claim 1, further comprising transmitting one or more of the two or more degraded versions to two or more additional recipient devices, wherein the transmitted one or more degraded versions are selected at least partially based on being commensurate with ascertained bandwidths

45

on the network along delivery paths for delivering the video message to the two or more additional recipient devices respectively.

4. The method of claim 1, wherein generating the two or more degraded versions of the video media further comprises trans-coding the video media from one video codec into one of two or more second video codec(s).

5. The method of claim 4, wherein each of the two or more second video codec(s) defines a different tradeoff between a transmission bit rate versus quality.

6. The method of claim 1, wherein generating a first of the two or more degraded versions further comprises increasing a packetization interval for packets containing the video media when transmitting the first degraded version.

7. The method of claim 1, further comprising storing, by the video message service infrastructure, each of the degraded versions of the video media of the video message, as the video message is received.

8. The method of claim 1, wherein the video message is received at the video message service infrastructure using a first real-time streaming protocol, and the selected degraded version of the video media is transmitted from the video message service infrastructure to the recipient device using a second real-time streaming protocol.

9. The method of claim 8, wherein the first real-time streaming protocol is different from the second real-time streaming protocol.

10. The method of claim 8, wherein the first and second real-time streaming protocols are higher-level protocols that operate over a lower-level transmission protocol.

11. The method of claim 10, wherein the lower-level transmission protocol is either:

- (i) Transmission Control Protocol (TCP); or
- (ii) User Datagram Protocol (UDP).

12. The method of claim 1, wherein the video message service infrastructure is further configured to perform one of the following:

- (i) trans-code the video message;
- (ii) encrypt and authenticate the video message; or
- (iii) both (i) and (ii).

13. The method of claim 1, wherein the selected degraded version of the video media improves the ability of the recipient device to render at least the portion of the video message as the video media is being transmitted by the sending device when network conditions are insufficient to support transmission of a complete version of the video media as received by the video message service infrastructure.

14. The method of claim 1, further comprising:

ascertaining a first codec that was used by the sending device to encode the video media of the video message when sent;

ascertaining a second codec to be used by the recipient device to decode the video media of the video message when received;

trans-coding the video media of the video message from the first codec to the second codec; and transmitting, to the recipient device, the trans-coded video media.

15. The method of claim 1, further comprising:

storing the video media of the video message in a storage location accessible by the video message service infrastructure; and

providing from the storage location to the recipient device a complete copy of the video media of the video message for rendering in a time-shifted mode, wherein

46

the complete copy is the same quality as received by the video message service infrastructure from the sending device.

16. The method of claim 1, further comprising:

receiving, at the video message service infrastructure, a second video message transmitted by a second sending device, the second video message including second video media, wherein the second video media being transmitted by the second sending device as the second video media is created;

transmitting the second video media from the video message service infrastructure over the network to the recipient device so that the recipient device can render at least a portion of the second video media, the video message service infrastructure operating so that the rendering occurs:

- (i) as the second video media of the second video message is created and transmitted over the network by the second sending device;
- (ii) without having to first establish an end-to-end connection over the network between the second sending device and the recipient device before the second sending device begins to transmit the second video media of the second video message; and
- (iii) simultaneously with the rendering of the video media of the video message.

17. The method of claim 1, further comprising providing an application for execution on the sending device, the application enabling a sender using the sending device to transmit the video media of the video message as the video media is created and encoded.

18. The method of claim 1, further comprising providing an application for execution on the recipient device, the application enabling a recipient using the recipient device to selectively render the video media of the video message:

at least partially as the video media of the video message is created and transmitted by the sending device and delivered by the video message service infrastructure; and

in a time-shifted mode by rendering the video media of the video message out of storage.

19. The method of claim 1, wherein the sending device is arranged to initiate transmission of the video message to the video message service infrastructure independently of the video message service infrastructure ascertaining a location of the recipient device or any other location(s) of other recipient device(s) on the network.

20. The method of claim 1, wherein the sending device is arranged to transmit the video message to the video message service infrastructure regardless of whether the recipient device or any other recipient device(s) is/are available or not available on the network.

21. The method of claim 1 further configured to provide a notification of the video message to the recipient device.

22. The method of claim 1, further comprising:

receiving an identifier from the sending device, the identifier identifying the recipient of the video message; resolving the identifier into an IP address on the network, the IP address identifying the recipient device on the network; and;

using the IP address to transmit the video media of the video message to the recipient device.

23. The method of claim 1, further comprising:

configuring the video message service infrastructure to include a plurality of servers located on the network, the plurality of servers collectively configured for performing;

47

receiving the video message;
 ascertaining locations on the network for multiple recipient devices including the recipient device, the locations derived from multiple identifiers provided by the sending device;
 transmitting the video message to the multiple recipient devices so that each of the multiple recipient devices can render at least a portion of the video message as the sending device is sending the video message;
 storing the video message as the video media is received by the video message service infrastructure; and
 providing the video media of the video message to any of the multiple recipient devices for rendering in a time-shifted mode.

24. A method for operating a video message service infrastructure on a network, the method comprising:

receiving a video message sent by a sending device, the video message containing video media that is transmitted over the network by the sending device as the video media is being created;

ascertaining bandwidth over the network for delivering the video media of the video message from video message service infrastructure to a recipient device on the network;

generating an adjusted bit rate representation of the video media of the video message commensurate with the ascertained bandwidth; and

transmitting the adjusted bit rate representation of the video media over the network to the recipient device so that a recipient can render at least a portion of the video message on the recipient device, the video message service infrastructure operating so that rendering occurs:

(i) while the video media of the video message is being created and transmitted over the network by the sending device; and

(ii) without having to first establish an end-to-end connection over the network between the sending device and the recipient device before the sending device begins to transmit the video media of the video message,

whereby generating the adjusted the bit rate representation of the video media of the video message improves the ability of the recipient to render the portion of the video message on the recipient device as the video media is being transmitted by the sending device when network conditions are insufficient to support transmission of a complete version of the video media, wherein the complete version is the same quality as received by the video message service infrastructure.

25. The method of claim 24, further comprising:

ascertaining bandwidth over the network for delivering the video media of the video message to each of multiple recipient devices on the network, the multiple recipient devices including the recipient device;

generating within the video message service infrastructure one or more adjusted bit rate representations of the video media of the video message;

ascertaining a selected bit rate representation, among the one or more adjusted bit rate representation, for each of the multiple recipient devices based on the ascertained bandwidth for each of the multiple recipient devices respectively;

transmitting over the network each of the selected adjusted bit rate representations of the video media from the video message service infrastructure to the multiple recipient devices respectively, the

48

wherein the transmission of the one or more adjusted bit rate representations of the video media of the video message enables each of the multiple recipient devices to render at least portions of the video media of the video message respectively,

the video message service infrastructure operating so that rendering occurs:

(i) while the video media of the video message is being created and transmitted over the network by the sending device; and

(ii) without having to first establish an end-to-end connection over the network between the sending device and any of the multiple recipient devices before the sending device begins to transmit the video media of the video message.

26. The method of claim 24, wherein generating the adjusted bit rate representation of the video media of the video message comprises degrading the quality of the video media of the video message.

27. The method of claim 24, wherein generating the adjusted bit rate representation of the video media of the video message comprises selecting one of multiple codecs, each of the multiple codecs defining a different tradeoff between a transmission bit rate versus quality, and the selection of one of the multiple codecs is at least partially based on the ascertained bandwidth.

28. The method of claim 24, wherein generating the adjusted bit rate representation of the video media of the video message comprises increasing a packetization interval for packets containing the video media when transmitting the video message.

29. The method of claim 24, further comprising storing, by the video message service infrastructure, the adjusted bit rate representation of the video media of the video message.

30. The method of claim 24, wherein the video message is received at the video message service infrastructure using a first real-time streaming protocol, and the adjusted bit rate representation of the video media of the video message is transmitted from the video message service infrastructure to the recipient device using a second real-time streaming protocol.

31. The method of claim 30, wherein the first real-time streaming protocol is different from the second real-time streaming protocol.

32. The method of claim 30, wherein the first and second real-time streaming protocols are higher-level protocols that operate over a lower-level transmission protocol.

33. The method of claim 32, wherein the lower-level transmission protocol is TCP.

34. The method of claim 32, wherein the lower-level transmission protocol is UDP.

35. The method of claim 24, wherein the video message service infrastructure is further configured to perform one of the following:

(i) trans-code the video message;
 (ii) encrypt and authenticate the video message; or
 (iii) both (i) and (ii).

36. The method of claim 24, further comprising:

ascertaining a first codec that was used by the sending device to encode the video media of the video message when transmitted;

ascertaining a second codec to be used by the recipient device to decode the video media of the video message when received;

trans-coding the video media of the video message from the first codec to the second codec; and

49

delivering the trans-coded video media when transmitting the adjusted bit rate representation of the video media of the video message to the recipient device.

37. The method of claim 24, further comprising:
storing the video media message in a storage location accessible by the video message service infrastructure; and
providing from the storage location to the recipient device a complete copy of the video message for rendering in a time-shifted mode, wherein the complete copy is the same quality of the video media as received by the video message service infrastructure from the sending device.

38. The method of claim 24, further comprising providing an application for execution on the sending device, the application enabling a sender using the sending device to transmit the video media of the video message as the video media is created and encoded.

39. The method of claim 24, further comprising providing an application for execution on the receiving device, the application enabling the recipient using the recipient device to selectively render the video media of the video message: at least partially as the video media of the video message is being created and transmitted by the sending device and delivered by the video message service infrastructure; and
in a time-shifted mode by rendering the video media of the video message received from storage.

40. The method of claim 24, further comprising configuring the sending device to initiate transmission of the video message to the video message service infrastructure independently of the video message service infrastructure ascertaining a location of the recipient device and any other recipient device(s) on the network.

41. The method of claim 24, further comprising configuring the sending device to transmit the video message to the video message service infrastructure regardless of whether the recipient device and any other recipient device(s) are available or not available on the network.

42. The method of claim 24, further comprising providing a notification of the video message to the recipient device.

43. The method of claim 24, comprising configuring the video message service infrastructure for:
receiving an identifier, the identifier identifying the recipient for receiving the video message;
resolving the identifier into an IP address on the network, the IP addresses identifying the recipient device on the network; and
using the IP address for transmitting the video media of the video message from the video service infrastructure to the recipient device.

44. The method of claim 24, further comprising configuring the video message service infrastructure to include a plurality of servers located on the network, the plurality of servers collectively configured for performing the following:

receiving the video message;
ascertaining multiple locations on the network for multiple recipient devices including the receiving device, the multiple locations derived from one or more identifiers provided by the sending device for identifying multiple recipients including the recipient for receipt of the video message;
transmitting the video message to the multiple recipient devices so that portions of the video message can be

50

respectively rendered by the multiple recipient devices at the same time as the sending device is transmitting the video message;

storing the video message in a storage location accessible by the video message service infrastructure; and
providing the stored video message to one or more of the multiple recipient devices for rendering in a time-shifted mode.

45. A method for operating a video message service infrastructure on a network, the method comprising:

receiving, at the video message service infrastructure, a first video message transmitted by a first sending device, the first video message containing first video media, the first video media being transmitted as the first video media is created;

receiving, at the video message service infrastructure, a second video message transmitted by a second sending device, the second video message containing second video media, the second video media being transmitted as the second video media is created;

transmitting from the video message service infrastructure over the network:

(a) the first video media of the first video message to a recipient device; and

(b) the second video media of the second video message to the recipient device;

the transmission of (a) and (b) occurring so that the recipient device can simultaneously render at least a first portion of the first video message and at least a second portion of the second video message, the simultaneous rendering occurring:

(c) as the first video media of the first video message and the second video media of the second video message are each being created and transmitted over the network by the first and the second sending devices respectively; and

(d) without having to first establish an end-to-end connection over the network between either of:

(i) the first sending device and the recipient device before the first sending device begins to transmit the first video media of the first video message; and

(ii) the second sending device and the recipient device before the second sending device begins to transmit the second video media of the second video message.

46. The method of claim 45, further comprising providing an application for execution on the first sending device and the second sending device,

the application enabling a first sender using the first sending device to:

(e) identify on the first sending device a first group of one or more recipients for receipt of the first video message; and

(f) transmit the first video message as the first video media is being created; and

the application enabling a second sender using the second sending device to:

(g) identify on the second sending device a second group of one or more recipients; and

(d) transmit the second video message as the second video media is being created,

wherein the recipient device receives both the first media and the second media of the first and second video messages because the recipient is included in both the first and second groups respectively.

51

47. The method of claim 45, further comprising providing an application for execution on the recipient device, the application enabling a recipient using the recipient device to selectively render:

- (e) the at least first and second portions simultaneously; and
- (f) the first video message and the second video message each selectively out of storage in a time-shifted mode.

48. The method of claim 45, wherein the first sending device is arranged for transmitting the first video message to the video message service infrastructure both:

- (e) independently of the video message service infrastructure ascertaining a location of the recipient device or any other recipient devices on the network; and
- (f) regardless of whether the recipient device or any other recipient devices are available or not available on the network.

49. The method of claim 45, further comprising providing a first notification and a second notification at the recipient device for notifying the recipient of the first video message and the second video message respectively.

50. The method of claim 45, wherein the video message service infrastructure is further arranged for:

- receiving a first identifier, the first identifier identifying a recipient user of the recipient device;
- receiving the identifier with the second video message;
- resolving an IP address for the recipient device from the identifier; and

using the IP address for transmitting, from the video message service infrastructure to the recipient device, the first video media of the first video message and the second video media of the second video message.

51. The method of claim 45, further comprising configuring the video message service infrastructure to include a plurality of servers located on the network, the plurality of servers collectively configured for performing:

- receiving the first video message and the second video message;
- transmitting the first video message to first multiple recipient devices, including the recipient device, the first multiple recipient devices each capable of rendering first portions of the first video message as the first sending device is transmitting the first video message; and
- transmitting the second video message to second multiple recipient devices, including the recipient device, the second multiple recipient devices each capable of rendering second portions of the second video message as the second sending device is transmitting the second video message.

52. The method of claim 45, further comprising degrading the quality of the first video media of the first video message for the purpose of enhancing the ability of a recipient to render the first video message on the recipient device when network conditions are insufficient to support transmission of a complete representation of the first video media as received by the video message service infrastructure from the first sending device.

53. The method of claim 45, further comprising degrading the quality of the first video media of the first video message by reducing a bit rate used to represent the first video media, wherein the bit rate is reduced relative to a complete bit representation of the first video media as received by the video message service infrastructure from the first sending device.

52

54. The method of claim 45, further comprising generating two or more bit rate versions used to represent the first video media of the first video message, each of the two or more bit rate versions representing different degraded quality versions of the first video media of the first video message.

55. The method of claim 45, further comprising degrading the quality of the first video media of the first video message by selecting one of multiple codecs, each of the multiple codecs defining a different tradeoff of transmission bit rate versus quality, wherein the selection of one of the multiple codecs is at least partially based on available bandwidth on at least a portion of a delivery path over the network for delivering the first video message to the recipient device.

56. The method of claim 45, further comprising degrading a quality of the first video media of the first video message by increasing a packetization interval for packets containing the first video media when transmitting the first video message from the video message service infrastructure to the recipient device.

57. The method of claim 45, further comprising simultaneously transmitting from the video message service infrastructure over the network to the recipient device the first portion of the first video message and the second portion of the second video message so that the recipient device can mix and simultaneously render the first and second portions of the two video messages.

58. The method of claim 45, further comprising configuring the video message service infrastructure to include a plurality of servers located on the network, the plurality of servers collectively configured for performing the following:

- receiving the first video media of the first video message and the second video media of the second video message;
- storing the first video media of the first video message and the second video media of the second video message; and
- simultaneously transmitting first packets containing the first video media of the first video message and second packets containing the second video media of the second video message to the recipient device so that at least the first and second portions of the first video message and the second video message can be mixed and simultaneously rendered as the first and second sending devices are transmitting the first video message and the second video message.

59. The method of claim 45, further comprising configuring the video message service infrastructure to include a plurality of servers located on the network, the plurality of servers collectively configured for performing one of the following:

- (i) trans-coding the first video media of the first video message and the second video media of the second video message; and
- (ii) encrypting the first video media of the first video message and the second video media of the second video message; and
- (iii) authenticating the first video message and the second video message; or
- (iv) any combination of (i) through (iii).

* * * * *



US010511557C1

(12) **EX PARTE REEXAMINATION CERTIFICATE** (12909th)
United States Patent
Katis et al.

(10) **Number:** **US 10,511,557 C1**
(45) **Certificate Issued:** **Apr. 30, 2025**

(54) **TELECOMMUNICATION AND MULTIMEDIA MANAGEMENT METHOD AND APPARATUS**

H04L 65/1083 (2013.01); **H04L 65/4015** (2013.01); **H04L 65/403** (2013.01); **H04L 65/764** (2022.05);

(71) Applicant: **Voxer IP LLC**, San Francisco, CA (US)

(Continued)

(72) Inventors: **Thomas E. Katis**, Jackson, WY (US); **James T. Panttaja**, San Francisco, CA (US); **Mary G. Panttaja**, San Francisco, CA (US); **Matthew J. Ranney**, Oakland, CA (US)

(58) **Field of Classification Search**

CPC **H04L 51/10**; **H04L 12/1831**; **H04L 51/04**; **H04L 51/216**; **H04L 51/226**; **H04L 51/42**; **H04L 61/2503**; **H04L 65/1083**; **H04L 65/4015**; **H04L 65/403**; **H04L 65/764**; **H04L 67/54**; **G06F 15/16**; **H04M 1/64**; **H04M 3/53**; **H04M 3/5307**; **H04M 11/00**; **E04H 3/126**; **H04N 7/147**; **H04N 7/15**; **H04W 4/12**

See application file for complete search history.

Reexamination Request:

No. 90/019,211, May 18, 2023

Reexamination Certificate for:

Patent No.: **10,511,557**
Issued: **Dec. 17, 2019**
Appl. No.: **16/161,474**
Filed: **Oct. 16, 2018**

(56)

References Cited

To view the complete listing of prior art documents cited during the proceeding for Reexamination Control Number 90/019,211, please refer to the USPTO's Patent Electronic System.

Primary Examiner — Mark Sager

Related U.S. Application Data

(63) Continuation of application No. 15/923,287, filed on Mar. 16, 2018, now Pat. No. 10,129,191, which is a
(Continued)


(51) **Int. Cl.**
H04L 51/04 (2022.01)
E04H 3/12 (2006.01)
(Continued)

(52) **U.S. Cl.**
CPC **H04L 65/752** (2022.05); **E04H 3/126** (2013.01); **G06F 15/16** (2013.01); **H04L 12/1831** (2013.01); **H04L 51/04** (2013.01); **H04L 51/10** (2013.01); **H04L 51/216** (2022.05); **H04L 51/226** (2022.05); **H04L 51/42** (2022.05); **H04L 61/2503** (2013.01);

(57)

ABSTRACT

A telecommunication and multimedia management apparatus and method that supports voice and other media communications and that enables users to: (i) participate in multiple conversation modes, including live phone calls, conference calls, instant voice messaging or tactical communications; (ii) review the messages of conversations in either a live mode or a time-shifted mode and to seamlessly transition back and forth between the two modes; (iii) participate in multiple conversations either concurrently or simultaneously; (iv) archive the messages of conversations for later review or processing; and (v) persistently store media either created or received on the communication devices of users. The latter feature enables users to generate or review media when either disconnected from the network or network conditions are poor and to optimize the delivery of media over the network based on network conditions and the intention of the users participating in conversations.



Related U.S. Application Data

continuation of application No. 15/584,224, filed on May 2, 2017, now Pat. No. 10,142,270, which is a continuation of application No. 15/231,240, filed on Aug. 8, 2016, now Pat. No. 9,674,122, which is a continuation of application No. 14/799,528, filed on Jul. 14, 2015, now Pat. No. 9,456,087, which is a continuation of application No. 14/198,043, filed on Mar. 5, 2014, now Pat. No. 9,154,628, which is a continuation of application No. 13/555,034, filed on Jul. 20, 2012, now Pat. No. 8,705,714, which is a continuation of application No. 12/037,256, filed on Feb. 26, 2008, now Pat. No. 8,243,894, which is a continuation of application No. 12/028,400, filed on Feb. 8, 2008, now Pat. No. 8,180,029.

(60) Provisional application No. 60/937,552, filed on Jun. 28, 2007, provisional application No. 60/999,619, filed on Oct. 19, 2007.

(51) Int. Cl.
G06F 15/16 (2006.01)
H04L 12/18 (2006.01)

H04L 51/10 (2022.01)
H04L 51/216 (2022.01)
H04L 51/226 (2022.01)
H04L 51/42 (2022.01)
H04L 61/2503 (2022.01)
H04L 65/1083 (2022.01)
H04L 65/401 (2022.01)
H04L 65/403 (2022.01)
H04L 65/75 (2022.01)
H04L 65/752 (2022.01)
H04L 67/54 (2022.01)
H04M 1/64 (2006.01)
H04M 3/53 (2006.01)
H04M 11/00 (2006.01)
H04N 7/14 (2006.01)
H04N 7/15 (2006.01)
H04W 4/12 (2009.01)

(52) U.S. Cl.
CPC H04L 67/54 (2022.05); H04M 1/64 (2013.01); H04M 3/53 (2013.01); H04M 3/5307 (2013.01); H04M 11/00 (2013.01); H04N 7/147 (2013.01); H04N 7/15 (2013.01); H04W 4/12 (2013.01)

1
EX PARTE
REEXAMINATION CERTIFICATE

THE PATENT IS HEREBY AMENDED AS
INDICATED BELOW.

Matter enclosed in heavy brackets [] appeared in the patent, but has been deleted and is no longer a part of the patent; matter printed in italics indicates additions made to the patent.

ONLY THOSE PARAGRAPHS OF THE
SPECIFICATION AFFECTED BY AMENDMENT
ARE PRINTED HEREIN.

Column 10, after line 46:

Broadcast: a message can be designated as a broadcast.

Column 20, line 63 through Column 21, line 19:

To prepare messages for transmission from the Client **12** over a network **18**, the PIMB reader **26** includes a Data Prioritizer **26f**, a Packet Quality Manager (PQM) **26g**, a Data Retriever **26h**, Packetizer **26i**, a Transmitter **26j** and an Acknowledger **26k**. The Data Prioritizer **26f** prioritizes the Messages for transmission over the network **18**. Priority is determined using the MCMS Participant Attributes related to payloads available for transmission, network connectivity and bandwidth conditions, and the Intentions of Users beyond the next hop to either Render live or time-shifted, and, in some embodiments, possible optimizations of transmission bundling where multiple packets to any given next network hop are available. The prioritized packets are then optimized, using the PQM **26g**, which assures the timely delivery of “good enough” data quality for live Messages, while minimizing real-time bandwidth, as described in more detail below. The Data Retriever **26h** retrieves the appropriate payloads from the PIMB **30**. The Packetizer **26i** of the PIMB reader **26** assembles the payloads into Vox Packets, **[which]** *which include the available media and at least one identifier that is associated with an outgoing message. Representative example identifiers include an identifier that identifies or is indicative of a recipient, a Conversation, a Message, a meeting, a channel, a group, and/or the sender, and/or any other identifier(s) that may be used identify or otherwise ascertain transmission target(s) (i.e., recipient(s)). The Vox packets are then transmitted by the Transmitter module **26j** over the network **18**. When the recipient receives the Vox packets, an acknowledgement is sent back to Acknowledger **26k** over the network **18** for notifying the sending User that a Message has arrived at its destination.*

AS A RESULT OF REEXAMINATION, IT HAS BEEN DETERMINED THAT:

The patentability of claims **1**, **8** and **9** is confirmed.

Claims **6**, **21** and **43** are determined to be patentable as amended.

New claims **60-103** are added and determined to be patentable.

Claims **2-5**, **7**, **10-20**, **22-42**, **44-59** were not reexamined.

6. The method of claim **1**, wherein generating **[a first]** *the selected one degraded version* of the two or more degraded versions further comprises:

2

increasing a packetization interval for packets containing the video media when transmitting the **[first]** *selected one* degraded version.

21. The method of claim **1**, further **[configured to provide]** *comprising: providing* a notification of the video message to the recipient device.

43. The method of claim **24**, further comprising:
configuring the video message service infrastructure for:
receiving an identifier, the identifier identifying the recipient for receiving the video message;
resolving the identifier into an IP address on the network, the IP **[addresses]** *address* identifying the recipient device on the network; and
using the IP address for transmitting the video media of the video message from the video service infrastructure to the recipient device.

60. *The method of claim 1, wherein the video message includes an identifier and the method further comprises inserting data indicative of the identifier into one or more packets used for transporting the video message.*

61. *The method of claim 1, wherein the video message includes an identifier that identifies the video message.*

62. *The method of claim 1, wherein the video message includes an identifier that associates the video message with a conversation and a recipient user of the recipient device is identified as a participant in the conversation.*

63. *The method of claim 1, wherein the video message includes an identifier that identifies a sending user of the sending device and the method further comprises:*

identifying a plurality of recipient users having a plurality of recipient devices, including the recipient device, based on the identity of the sender user; and
transmitting the video media of the video message to the plurality of recipient devices, the transmission to each of the plurality of recipient devices involving selecting among the two or more degraded versions based on ascertained bandwidth on the network for each of the plurality of recipient devices respectively.

64. *The method of claim 1, wherein the video message is a broadcast.*

65. *The method of claim 1, wherein a recipient user of the recipient device is part of a group that is affiliated with the sender.*

66. *The method of claim 1, wherein:*
the video message includes an identifier;
the identifier is used to identify a group, or a channel; and
a recipient user of the recipient device is identified as a member of the group or the channel.

67. *The method of claim 66, further comprising notifying and delivering the video message to one or more members of the group or the channel.*

68. *The method of claim 1, wherein a recipient user of the recipient device is a member of a group or a channel and the method further comprises:*

notifying members of the group or the channel, wherein the notification is indicative of availability of the video message; and
delivering the video message to one or more members of the group or the channel, including the recipient user of the recipient device.

69. *The method of claim 1, wherein the video message includes an identifier and the method further comprises:*
identifying a plurality of receiving users, including a recipient user of the receiving device, from the identifier;

3

generating a notification for the plurality of receiving users, the notification indicative of availability of the video message;

enabling one or more of the plurality of receiving users, including the recipient user, to selectively render the video message as the sending device is transmitting the video message. 5

70. The method of claim 69, further comprising: enabling one or more of the plurality of receiving users or the sending user to exchange second messages in response to the video message; and 10 organizing the exchange of second messages into a conversation thread.

71. The method of claim 1, wherein the video message includes an identifier that identifies a recipient user of the receiving device as a target recipient of the video message. 15

72. The method of claim 1, further comprising: notifying and delivering the video message to one or more participants of a conversation that is initiated by the video message, wherein the one or more participants of the conversation includes a recipient user of the receiving device. 20

73. The method of claim 1, wherein the video message includes an identifier and the method further comprises: identifying a sending user of the video message from the identifier; and 25 identifying a recipient user of the receiving device based on the identification of the sending user.

74. The method of claim 1, wherein a recipient user of the receiving device is a member of a group or a channel and the method further comprises: 30

providing notification to members of the group or the channel, the notification indicative of availability of the video message; and 35 delivering the video message to one or more members of the group or the channel, including the recipient user, for selective rendering.

75. The method of claim 74, further comprising: enabling the members of the group or the channel to exchange messages in response to the video message; and 40 organizing the exchange of messages into a conversation thread.

76. The method of claim 1, wherein the video message includes an identifier that identifies a sending user of the sending device and the method further comprises identifying one or more recipient users having a plurality of recipient devices, including the recipient device, based on the identity of the sender user. 45

77. The method of claim 1, wherein the video message includes an identifier and the method further comprises ascertaining a recipient user of the recipient device from the identifier.

78. A method for operating a video message service infrastructure on a network, the method comprising: 55

receiving, at the video message service infrastructure, a video message transmitted by a sending device, the video message including an identifier and containing video media, the video media being transmitted as the video media is created at the sending device; 60

using the identifier, within the video message service infrastructure, to ascertain one or more recipients of the video message;

generating within the video message service infrastructure two or more degraded versions of the video media of the video message, wherein each of the two or more 65

4

degraded versions is created by degrading the quality of the video media by a different amount;

for each of the one or more recipients, selecting one of the two or more degraded versions of the video media based on an ascertained bandwidth on the network for delivering the video media from the video message service infrastructure to one or more recipient devices associated with the one or more recipients respectively; transmitting and delivering the selected one degraded version of the video media of the video message from the video message service infrastructure to the one or more recipient devices respectively so that the one or more recipients can render at least a portion of the video media of the video message, 15

the receiving, the transmitting, the delivering, and the rendering occurring:

(i) while the video media of the video message is being created and transmitted over the network by the sending device; and

ii) without having to first establish an end-to-end connection over the network between the sending device and any of the one or more recipient devices before the sending device begins to transmit the video media of the video message; 25

wherein the transmitting and delivery by the video message service infrastructure enabling the one or more recipient devices to selectively render the selected one of the two or more degraded versions of the video media respectively.

79. The method of claim 78, further comprising notifying the one or more recipients of the availability of the video message.

80. The method of claim 78, further comprising: inserting data indicative of the identifier into one or more packets used for transporting the identifier, and the video media of the video message. 35

81. The method of claim 78, wherein the identifier identifies the video message.

82. The method of claim 78, wherein the identifier associates the video message with a conversation and the one or more recipients is/are ascertained based on their status as participant(s) in the conversation.

83. The method of claim 78, wherein the identifier identifies a sender of the video communication and the one or more recipients is/are ascertained based on their status as being associated with the sender.

84. The method of claim 78, wherein the video message is a broadcast. 50

85. The method of claim 78, wherein the one or more recipients is/are part of a group, a conversation, or a channel that is initiated by a sender of the video message.

86. The method of claim 78, wherein: the identifier identifies a group, a channel, or a conversation; and

at least one of the one or more recipients is ascertained based on their status as being a member of the group, the channel, or the conversation.

87. The method of claim 78, wherein the one or more recipients is/are members of a group, a channel, or a conversation, and the method further comprises:

notifying members of the group, the channel, or the conversation, the notification indicative of availability of the video message; and

delivering the video message to the one or more members of the group, the channel, or the conversation.

5

88. The method of claim 78, further comprising:
enabling the one or more recipients to exchange second
messages in response to the video message; and
organizing the exchange of second messages into a thread
of messages.

89. The method of claim 78, wherein the video message
further includes multiple identifiers including the identifier
and the multiple identifiers identify multiple users of the
video message service infrastructure including the one or
more recipients.

90. The method of claim 78, further comprising:
identifying a sending user of the video message from the
identifier; and
ascertaining the one or more recipients based on the
identification of the sending user.

91. The method of claim 78, wherein the one or more
recipients is/are members of a group, a channel, or a
conversation and the method further comprises:

enabling the members of the group, the channel, or the
conversation to exchange messages in response to the
video message; and
organizing the exchange of messages into a thread of
messages.

92. A method for operating a video message service
infrastructure on a network, the method comprising:

receiving, at the video message service infrastructure, a
video message transmitted over the network by a send-
ing device, the video message including an identifier
and containing video media and received as the video
media is being created by the sending device;

using the identifier, within the video message service
infrastructure, to ascertain one or more recipients of
the video message;

ascertaining bandwidth over the network for delivering
the video media of the video message from the video
message service infrastructure to one or more recipient
devices associated with the one or more recipients;

generating one or more adjusted bit rate representations
of the video media of the video message commensurate
with the ascertained bandwidth for delivering the video
media of the video message from the video message
service infrastructure to the one or more recipient
devices respectively;

transmitting and delivering one of the one or more
adjusted bit rate representations of the video media of
the video message over the network from the video
message service infrastructure to the one or more
recipient devices respectively, the transmitting and
delivering such that the one or more recipients can
render at least a portion of the video media of the video
message,

the video message service infrastructure operating such
that the receiving, the transmitting, the delivering, and
the rendering occurring:

(i) while the video media of the video message is being
created and transmitted over the network by the send-
ing device; and

6

(ii) without having to first establish an end-to-end con-
nection over the network between the sending device
and any of the one or more recipient devices before the
sending device begins to transmit the video media of
the video message,

whereby generating the one or more adjusted bit rate
representations of the video media of the video message
improves the ability of the one or more recipients to
render the at least portions of the video message on the
one or more recipient devices as the video media is
being transmitted by the sending device when network
conditions are insufficient to support transmission of a
complete version of the video media, wherein the
complete version is the same quality as received by the
video message service infrastructure.

93. The method of claim 92, further comprising inserting
the identifier into one or more packets used for transporting
the video message.

94. The method of claim 92, wherein the identifier iden-
tifies the video message.

95. The method of claim 92, wherein the identifier asso-
ciates the video message with one of a conversation, a
group, or a channel, wherein the one or more recipients
is/are identified based on their status as being a participant
in the conversation, the group, or the channel.

96. The method of claim 92, wherein the video message
further includes multiple identifiers including the identifier
and the multiple identifiers identify multiple users of the
video message service infrastructure including the one or
more recipients.

97. The method of claim 92, further comprising:
identifying a sending user of the video message from the
identifier; and

ascertaining the one or more recipients based on their
status as being associated with the sending user.

98. The method of claim 92, further comprising:
enabling the one or more recipients and a sending user of
the sending device to exchange one or more second
messages that are associated with the video message.

99. The method of claim 98, wherein the one or more
second messages is/are text messages.

100. The method of claim 99, wherein the one or more
second messages is/are second video message(s) that is/are
transmitted and rendered simultaneously with the video
message.

101. The method of claim 92, wherein the identifier
identifies a sender of the video communication and the one
or more recipients is/are ascertained based on their status as
being associated with the sender.

102. The method of claim 92, wherein the video message
is a broadcast.

103. The method of claim 92, further comprising:
storing the video message in a storage location accessible
by the video message service infrastructure; and
enabling the one or more recipients, or a sending user of
the sending device, to render the video media of the
video message in a time-shifted mode out of storage.

* * * * *