



US008411662B1

(12) **United States Patent**
Saund et al.(10) **Patent No.:** **US 8,411,662 B1**
(45) **Date of Patent:** **Apr. 2, 2013**(54) **BEACON BASED PROXIMITY SERVICES**(75) Inventors: **Saran Saund**, Mountain View, CA (US);
Paul A. Lambert, Mountain View, CA (US)(73) Assignee: **PICO Mobile Networks, Inc.**,
Sunnyvale, CA (US)(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 1286 days.(21) Appl. No.: **11/542,394**(22) Filed: **Oct. 3, 2006****Related U.S. Application Data**(60) Provisional application No. 60/723,299, filed on Oct.
4, 2005.(51) **Int. Cl.**
H04J 3/00 (2006.01)(52) **U.S. Cl.** **370/345; 370/328**(58) **Field of Classification Search** **370/345,**
370/338

See application file for complete search history.

(56) **References Cited****U.S. PATENT DOCUMENTS**

5,738,583	A	4/1998	Comas et al.
6,272,120	B1	8/2001	Alexander
6,600,726	B1	7/2003	Nevo et al.
6,690,935	B1	2/2004	Calot et al.
6,704,866	B1	3/2004	Benayoun et al.
6,707,801	B2	3/2004	Hsu
6,760,587	B2	7/2004	Holtzman et al.
6,785,892	B1	8/2004	Miller
6,788,675	B1	9/2004	Yang
6,793,580	B2	9/2004	Sinclair et al.
6,795,701	B1	9/2004	Hui et al.
6,799,056	B2	9/2004	Curley et al.
6,859,460	B1	2/2005	Chen
6,879,574	B2	4/2005	Naghian et al.
6,879,812	B2 *	4/2005	Agrawal et al. 455/67.11
6,909,705	B1	6/2005	Lee et al.
6,932,698	B2	8/2005	Sprogis
7,013,391	B2 *	3/2006	Herle et al. 713/182
7,072,323	B2	7/2006	Roberts et al.
7,073,129	B1	7/2006	Robarts et al.
7,085,257	B1	8/2006	Karves et al.
7,097,562	B2	8/2006	Gagner
7,143,171	B2	11/2006	Eriksson et al.
7,181,544	B2	2/2007	Vangal et al.
7,224,964	B2	5/2007	Souissi et al.
7,236,772	B1	6/2007	Botzas
7,251,235	B2	7/2007	Wentink
7,324,444	B1	1/2008	Liang et al.
7,400,722	B2	7/2008	Qi et al.
7,440,430	B1	10/2008	Jagadeesan et al.
7,452,278	B2	11/2008	Chen et al.
2002/0151366	A1 *	10/2002	Walker et al. 463/42
2002/0152388	A1 *	10/2002	Linnartz et al. 713/176
2002/0191560	A1	12/2002	Chen et al.
2002/0199124	A1	12/2002	Adkisson
2003/0069018	A1	4/2003	Matta et al.
2003/0182454	A1	9/2003	Huth et al.
2003/0231625	A1	12/2003	Calvignac
2004/0066751	A1	4/2004	Tseng et al.

2004/0105415	A1 *	6/2004	Fujiwara et al. 370/338
2004/0127277	A1	7/2004	Walker et al.
2004/0174829	A1	9/2004	Ayyagari
2004/0185851	A1	9/2004	Nagai
2004/0196808	A1	10/2004	Chaskar et al.
2005/0025163	A1	2/2005	Christie
2005/0032577	A1	2/2005	Blackburn et al.
2005/0041660	A1	2/2005	Pennec et al.
2005/0041793	A1	2/2005	Fulton et al.
2005/0073980	A1 *	4/2005	Thomson et al. 370/338
2005/0079873	A1	4/2005	Caspi et al.
2005/0099977	A1 *	5/2005	Williams et al. 370/338
2005/0157661	A1	7/2005	Cho
2005/0177639	A1 *	8/2005	Reunamaki et al. 709/227
2005/0181872	A1	8/2005	Acharya et al.
2005/0197189	A1	9/2005	Schultz
2005/0250487	A1 *	11/2005	Miwa et al. 455/422.1
2005/0250497	A1	11/2005	Ghosh et al.
2005/0268003	A1 *	12/2005	Wang et al. 710/36
2005/0286456	A1 *	12/2005	McNew et al. 370/312
2006/0041750	A1 *	2/2006	Carter et al. 713/168
2006/0045138	A1	3/2006	Black et al.
2006/0063539	A1	3/2006	Beyer
2006/0135262	A1	6/2006	Kennedy et al.
2006/0172736	A1	8/2006	Nevo
2006/0205409	A1	9/2006	Chiou et al.
2006/0221857	A1	10/2006	Bushnell et al.
2006/0268711	A1	11/2006	Doradla et al.
2007/0026866	A1	2/2007	Krishnamurthi et al.
2007/0035513	A1	2/2007	Sherrard et al.
2007/0047547	A1	3/2007	Conner et al.
2007/0047697	A1	3/2007	Drewry et al.
2007/0060355	A1	3/2007	Amaitis et al.
2007/0076683	A1	4/2007	Chung
2007/0082671	A1	4/2007	Feng et al.
2007/0086394	A1 *	4/2007	Yamada et al. 370/338
2007/0099703	A1	5/2007	Terebilo
2007/0197237	A1	8/2007	Powell et al.
2007/0202910	A1	8/2007	Brewer et al.
2008/0039015	A1	2/2008	Nakata et al.

(Continued)

OTHER PUBLICATIONSIEEE Standards Board, IEEE 802.11 Standard, 1999, 1999 Edition
(R2003).*Newton, Harry. Newton's Telecom Dictionary. 15th Edition. Miller
Freeman Inc., 1999. 762. (3 pages).*Primary Examiner* — Rafael Pérez-Gutiérrez*Assistant Examiner* — German Viana Di Prisco(57) **ABSTRACT**

The invention includes additional uses for the SSID of the IEEE 802.11 beacon to include reliable and secure capability encoding. The SSID in the system can be controlled by applications and transmitted with periodic broadcasting or point to point communication, so interoperable communication of application or user preferences/capabilities/membership can be transmitted and quickly determined by peers.

17 Claims, No Drawings**Apple EX1036****Apple Inc. v. Secure Comm. Techs., LLC****IPR2026-00447**

US 8,411,662 B1

Page 2

U.S. PATENT DOCUMENTS

2008/0069105 A1 3/2008 Costa et al.
2008/0095112 A1 4/2008 Wiemann et al.
2008/0123608 A1 5/2008 Edge et al.

2009/0191878 A1 7/2009 Hedqvist et al.
2009/0222358 A1 9/2009 Bednarek
2010/0093374 A1 4/2010 Dacosta et al.

* cited by examiner

BEACON BASED PROXIMITY SERVICES

The present application claims benefit of Provisional Application No. 60/723,299 filed Oct. 4, 2005, the contents of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention relates to wireless networks. More particularly, the present invention relates to the wireless communication protocol IEEE 802.11.

BACKGROUND OF THE INVENTION

It is well known that wireless devices such as telephones, email devices, and PDA's have been enabled for local wireless network communication with Internet protocol backbone networks by way of protocols such as the several forms of IEEE 802.11.

Alternately, automatic connection and communication systems may create a Personal-Area Networks (PAN). Other wireless standards that may be used include IRDA, hiperlan/2, and HomeRF. When a PAN is established, such as between one VoIP mobile phone and another, the members of the PAN can communicate directly. The more generally preferred mode of operation for such a mobile telephone is connection to a local access point, whereby the user can contact any source available to the Internet for conversation or gaming.

In a local area network communication, the access point transmits information separately to each local wireless device. An advantage to using a point-to-point communication is that different information (e.g., customization) may be sent to each wireless device. Even if the same information is being sent to several recipients (e.g., ensuring uniformity of a game's state for all local users coordinated by a remote server), however, in a point-to-point communication with multiple recipients, the information is transmitted redundantly to each recipient. However, an access point, comprising a wireless communication module and access point server which connects to an IP network, game state information may be transmitted, daisy chain, along point-to-point communications from an access point within range of only one wireless device, thereby extending the effective communication range of the access point.

IEEE 802.11 protocols comprise negotiation-of-device or device-type negotiation using Information Elements. In a specific example, a server may send to a client a device-type inquiry, to which a device-type response is made by the client. These information elements carry only device information.

It is well known that vendor specific information can be carried in the information elements (IE's). However, information in IE's which is vendor specific cannot be used by wireless devices which are made by another vendor. In addition, information in IE's which is vendor specific cannot be used by applications available via the wireless network.

There is a need for a system which uses information elements for additional purposes.

SUMMARY OF THE INVENTION

The present invention relates to providing new capabilities for the IEEE 802.11 beacon.

In 802.11, data frames carry information from higher layers. However, management and control frames must be provided that support data transfer. The beacon frame is a type of

management frame. A wireless local network requires these management frames for stations to establish and maintain communications.

A typical beacon frame is about fifty bytes long. It contains a common frame header and cyclic redundancy checking field, including others. The beacon also contains a service set identifier (SSID). The SSID identifies a specific wireless local area network. Before associating with said network, a wireless device must have the same SSID as the access point.

In ad hoc networks, the communication is point-to-point, not through access points. Thus, one of the wireless devices must take on responsibility for sending the beacon.

It is an object of the invention to provide application protocols for local wireless networks and personal area networks that provide for connection of one wireless device to another and thereafter having the wireless devices exchange capabilities. Capabilities of the devices are those known in the art. This mode of the invention may not work if the peer wireless devices do not or cannot associate at that time. For example, a wireless device enabled for IEEE 802.11 communication can only associate to one other wireless device at a time. Under that current protocol, it is impossible to connect to another network or system to determine capabilities beyond those in the devices beacon.

The IEEE 802.11 beacon is able to transmit a 32-character network identifier. This network identifier is only intended to carry the name of the network. Actual capabilities of the network are carried in other IE's. The invention system comprises additional uses for the SSID to include reliable and secure capability encoding. The SSID in the system can be controlled by applications and transmitted with periodic broadcasting or point to point communication, so interoperable communication of application or user preferences/capabilities/membership can be transmitted and quickly determined by peers.

BRIEF DESCRIPTION OF THE DRAWINGS

There are no drawing figures.

DETAILED DESCRIPTION OF THE INVENTION

The following are specific examples of the invention system.

The IEEE 802.11 beacon SSID is adapted to serve as a capabilities encoding channel.

For example, encoded capabilities and preferences are incorporated into the SSID to determine:

Group membership: such as invited members of a conference or game playing group.

User preferences:

Device capabilities:

System location:

Game state: such as a point of play in a computer game.

Encryption and security preferences:

Application software state: such as viewing a specific file.

The following are further examples of the invention system incorporating the use of SSID transmission of information:

Encoding of information where the information is encrypted.

Encoding of information: such as where information is integrity protected (checksum, secure hash, keyed hash, digital signature).

Encoding of information as a unique hash of capabilities.

Encoding as bit string with bits indicating capabilities.

Encoding where a bit string can have different encoding semantics based on receiver context.

3

Encoding used by peer mobile devices to alert user of proximity to another device.

Proximity used to indicate preferences of peer device user.

Proximity used as part of a game.

Encoding is encrypted to only allow access to information by approved peers.

Encoding is used as part of process to create encryption keys for subsequent communications.

After obtaining encoded SSID, device may use central server to assist in decoding.

Central server may return additional identity or location information.

Multiple different SSIDs can be used to define a single BSS.

Multiple different SSIDs can be used to define a single iBSS.

The above design options will sometimes present the skilled designer with considerable and wide ranges from which to choose appropriate apparatus and method modifications for the above examples. However, the objects of the present invention will still be obtained by that skilled designer applying such design options in an appropriate manner.

We claim:

1. A system comprising:

a plurality of wireless devices configured for wireless communication in a wireless network, wherein the wireless network is compliant with an Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, wherein a beacon is respectively transmittable by each of the plurality of wireless devices, wherein the beacon contains a service set identifier (SSID) that

i) identifies the wireless network, and

ii) is encoded to include a capability or a preference of the wireless device transmitting the beacon, and

wherein in response to a first wireless device of the plurality of wireless devices receiving a beacon containing the service set identifier (SSID) from a second wireless device of the plurality of wireless devices, the first wireless device transmits the service set identifier (SSID) to a central server,

wherein, responsive to receiving the service set identifier (SSID), the central server is configured to

i) decode the service set identifier (SSID) to retrieve the capability or the preference of the second wireless device as encoded into the service set identifier (SSID), and

ii) transmit, to the first wireless device, the capability or the preference of the second wireless device.

2. A system comprising:

N wireless devices configured for communication in a wireless network, wherein the wireless network is compliant with an Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, wherein N is an integer greater than 1,

wherein a first wireless device of the N wireless devices is configured to transmit a beacon, wherein the beacon includes a service set identifier (SSID) that

i) identifies the wireless network, and

ii) is encoded to include a capability or a preference of the first wireless device,

wherein, in response to a second wireless device of the N wireless devices receiving the beacon containing the service set identifier (SSID) from the first wireless device, the second wireless device is configured to transmit the service set identifier (SSID) to a central server, and

4

wherein, responsive to receiving the service set identifier (SSID) from the second wireless device, the central server is configured to

i) decode the service set identifier (SSID) to retrieve the capability or the preference of the first wireless device as encoded into the service set identifier (SSID), and

ii) transmit, to the second wireless device, the capability or the preference of the first wireless device.

3. The system of claim 2, wherein the wireless network comprises an ad-hoc network or an infrastructure network.

4. The system of claim 2, wherein the second wireless device is configured to connect to the first wireless device in accordance with the capability or the preference of the first wireless device as received from the central server.

5. The system of claim 2, wherein the first wireless device is configured to transmit the service set identifier (SSID) by:

periodically broadcasting the service set identifier (SSID); or

transmitting the service set identifier (SSID) in accordance with point-to-point communication.

6. The system of claim 2, wherein the capability or the reference encoded in the service set identifier (SSID) comprises one or more of membership information, user preferences, device capabilities, location information, encryption and security preferences, or a state of a software of the first wireless device.

7. The system of claim 2, wherein:

based on the service set identifier (SSID), the second wireless device is configured to alert a user of the second wireless device of a proximity of the first wireless device to the second wireless device, wherein the capability or the preference of the first wireless device is indicated based on the proximity.

8. The system of claim 2, wherein the service set identifier (SSID) is encrypted to allow access to the wireless network by authorized ones of the N wireless devices.

9. The system of claim 2, wherein the N wireless devices generate encryption keys for communication based on the service set identifier (SSID).

10. A method comprising:

receiving, at a first wireless device, a beacon transmitted from a second wireless device, wherein the beacon is transmitted from the second wireless device to the first wireless device through a wireless network that is compliant with an Institute of Electrical and Electronics Engineers (IEEE) 802.11 standard, and wherein the beacon is encoded to include a capability or a preference of the second wireless device;

transmitting the service set identifier (SSID) from the first wireless device to a central server, wherein the service set identifier (SSID) is decodable by the central server to retrieve the capability or the reference of the second wireless device as encoded into the service set identifier (SSID); and

subsequent to transmitting the service set service set identifier (SSID) from the first wireless device to a central server, receiving, at the first wireless device, the capability or the preference of the second wireless device from the central server.

11. The method of claim 10, wherein the wireless network comprises an ad-hoc network or an infrastructure network.

5

12. The method of claim **10**, further comprising:
in accordance with the capability or the preference of the
second wireless device received from the central server,
connecting the first wireless device to the second wire-
less device.

13. The method of claim **10**, wherein the beacon is trans-
mitted from the second wireless device by being periodically
broadcasted throughout the wireless network or by being
periodically transmitted in accordance with point-to-point
communication.

14. The method of claim **10**, wherein the capability or the
preference of the second wireless device comprises one or
more of membership information, user preferences, device
capabilities, location information, encryption and security
preferences, or a state of a software of the second wireless
device.

6

15. The method of claim **10**, further comprising:
based on the service set identifier (SSID), alerting a user of
the first wireless device of a proximity of the second
wireless device to the first wireless device; and
indicating the capability or the reference of the second
wireless device based on the proximity.

16. The method of claim **10**, wherein the service set iden-
tifier (SSID) is encrypted.

17. The method of claim **10**, further comprising:
based on the service set identifier (SSID), generating
encryption keys for communication in the wireless net-
work.

* * * * *