



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
62/193,992	07/17/2015		260	12361-624		

CONFIRMATION NO. 6073

FILING RECEIPT

757
BGL
P.O. BOX 10395
CHICAGO, IL 60610



Date Mailed: 08/04/2015

Receipt is acknowledged of this provisional patent application. It will not be examined for patentability and will become abandoned not later than twelve months after its filing date. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. **If an error is noted on this Filing Receipt, please submit a written request for a Filing Receipt Correction. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections**

Inventor(s)

Robert C. Fortmann, Grayslake, IL;
Frank G. Marolda, Vernon Hills, IL;

Applicant(s)

Carter-Hoffmann, Inc., Mundelein, IL

Power of Attorney:

Stephen Smith--56250

Permission to Access - A proper **Authorization to Permit Access to Application by Participating Offices** (PTO/SB/39 or its equivalent) has been received by the USPTO.

If Required, Foreign Filing License Granted: 08/03/2015

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 62/193,992**

Projected Publication Date: None, application is not eligible for pre-grant publication

Non-Publication Request: No

Early Publication Request: No

Title

MODULAR HOLDING CABINET

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

page 1 of 3

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER

Title 35, United States Code, Section 184

Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

CERTIFICATE OF EFS FILING

I hereby certify that this correspondence is being electronically transmitted to the United States Patent and Trademark Office, Commissioner for Patents, via the EFS on the below date:

Date: July 17, 2015 Name: Stephen C. Smith, Reg. No. 56,250 Signature: /Stephen C. Smith/

**BRINKS
GILSON
& LIONE**

PROVISIONAL APPLICATION FOR PATENT COVER SHEET

This is a request for filing a PROVISIONAL APPLICATION under 37 CFR 1.53(c).

Commissioner for Patents
PO Box 1450
Alexandria, VA 22313-1450

INVENTOR(S)		
Given Name (first and middle, if any)	Family Name or Surname	Residence (City and either State or Foreign Country)
Robert C. Frank G.	Fortmann Marolda	Grayslake, IL 60030 Vernon Hills, IL 60061
Additional inventors are being named on the _____ separately numbered sheets attached hereto.		
TITLE OF INVENTION (500 characters max):		
MODULAR HOLDING CABINET		
CORRESPONDENCE ADDRESS		
Direct all correspondence to: ☒ The address corresponding to: Customer No: 00757 - Brinks Gilson Lione ☐ Firm or Individual Name Address City _____ State _____ Zip _____ Country _____ Telephone _____ Email _____		
ENCLOSED APPLICATION PARTS (check all that apply)		
☒ Application Data Sheet. See 37 CFR 1.76 ☐ CD(s), Number of CDs _____ ☒ Specification: Number of Pages <u>22</u> ☒ Other (specify): <u>Cover Sheet (1 page)</u> ☒ Drawing(s): Number of Sheets <u>12</u>		
Fees Due when filed via EFS: ☒ \$260 Filing Fee - Large Entity ☐ \$130 Filing Fee - Small Entity ☐ \$65 Filing Fee - Micro Entity Application Size: ☐ Fee: No. of pages _____ x .75 = _____ - 100 = * _____ / 50 = _____ x \$400 = \$ _____ ☐ Small Entity: No. of pages _____ x .75 = _____ - 100 = * _____ / 50 = _____ x \$200 = \$ _____ ☐ Micro Entity: No. of pages _____ x .75 = _____ - 100 = * _____ / 50 = _____ x \$100 = \$ _____ *If the difference is less than zero, enter "0" in last field. (See MPEP 607 Filing Fee)		
METHOD OF PAYMENT OF FILING FEES AND APPLICATION SIZE FEE FOR THIS PROVISIONAL APPLICATION FOR PATENT		
☐ Per 37 CFR 1.27, Applicant claims: ☐ small entity status ☐ micro entity status. ☐ A check or money order is enclosed to cover the filing fee and application size fee. ☐ Payment by credit card (Form PTO-2038 is attached). WARNING: Information on this form may become public. Credit card information should not be included on this form. ☒ The Director is hereby authorized to charge payment of the filing fee(s) to Deposit Account No. 23-1925. ☒ The Director is hereby authorized to charge any deficiency in the filing fees or credit any overpayment to Deposit Account Number 23-1925.		260 Total Fee Amount (\$)
The invention was made by an agency of the United States Government or under a contract with an agency of the U.S. Government. ☒ No. ☐ Yes. U.S. government agency: _____; Government Contract No.: _____.		

/Stephen C. Smith/

Signature

Stephen C. Smith

Typed or Printed Name

312-321-4200

Telephone

July 17, 2015

Date

56,250

Registration No.

12361-624

Docket Number

USE ONLY FOR FILING A PROVISIONAL APPLICATION FOR PATENT

Electronic Patent Application Fee Transmittal				
Application Number:				
Filing Date:				
Title of Invention:		MODULAR HOLDING CABINET		
First Named Inventor/Applicant Name:		Robert C. Fortmann		
Filer:		Stephen Conrad Smith		
Attorney Docket Number:		12361-624		
Filed as Large Entity				
Filing Fees for Provisional				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
Provisional Application Filing	1005	1	260	260
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Extension-of-Time:				
Miscellaneous:				
Total in USD (\$)				260

Electronic Acknowledgement Receipt

EFS ID:	22953310
Application Number:	62193992
International Application Number:	
Confirmation Number:	6073
Title of Invention:	MODULAR HOLDING CABINET
First Named Inventor/Applicant Name:	Robert C. Fortmann
Customer Number:	757
Filer:	Stephen Conrad Smith/Laura Austing
Filer Authorized By:	Stephen Conrad Smith
Attorney Docket Number:	12361-624
Receipt Date:	17-JUL-2015
Filing Date:	
Time Stamp:	17:12:34
Application Type:	Provisional

Payment information:

Submitted with Payment	yes
Payment Type	Deposit Account
Payment was successfully received in RAM	\$ 260
RAM confirmation Number	3672
Deposit Account	231925
Authorized User	SMITH, STEPHEN

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Charge any Additional Fees required under 37 C.F.R. Section 1.16 (National application filing, search, and examination fees)

Charge any Additional Fees required under 37 C.F.R. Section 1.47 (Patent application and reexamination processing fees)

Charge any Additional Fees required under 37 C.F.R. Section 1.19 (Document supply fees)

Charge any Additional Fees required under 37 C.F.R. Section 1.20 (Post Issuance fees)

Charge any Additional Fees required under 37 C.F.R. Section 1.21 (Miscellaneous fees and charges)

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Drawings-only black and white line drawings	2015-0717-Drawings-FINAL.pdf	2441206	no	12
			a5c6dd43defb8e84762fcee4b1c2f972d330a803		
Warnings:					
Information:					
2		2015-0717-PatentApp-FINAL.pdf	104576	yes	23
			1220a35281e01dc9bed43186a543e8c61db67fec		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	17	
	Claims		18	22	
	Abstract		23	23	
Warnings:					
Information:					
3	Application Data Sheet	2015-0717-ADS-FINAL.pdf	1190255	no	7
			d345a48207dcd052efb9b19a955a170fed83f7e7		
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
4	Transmittal of New Application	2015-0717-Transmittal-FINAL.pdf	141275	no	1
			710c710779616946c7dcdbe1867d8a061938dc56		
Warnings:					
Information:					
5	Fee Worksheet (SB06)	fee-info.pdf	29901	no	2
			399bb0bfa1d3dd2fa9a7398e47a937c342c76687		
Warnings:					
Information:					
Total Files Size (in bytes):			3907213		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111


If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371


If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.


New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.



3/14





F/b.5b




Fig. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10

CERTIFICATE OF EFS FILING UNDER 37 CFR §1.8

I hereby certify that this correspondence is being electronically transmitted to the United States Patent and Trademark Office, Commissioner for Patents, via the EFS pursuant to 37 CFR §1.8 on the below date:

Date: July 17, 2015 Name: Stephen C. Smith, Reg. No. 56,250 Signature: /Stephen C. Smith/

Our Case No. 12361-624

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE
PROVISIONAL APPLICATION

INVENTORS: Robert C. Fortmann; Grayslake, IL
Frank G. Marolda; Vernon Hills, IL

TITLE: MODULAR HOLDING CABINET

ATTORNEY: Stephen C. Smith (Reg. No. 56,250)
BRINKS GILSON & LIONE
POST OFFICE BOX 10395
CHICAGO, ILLINOIS 60610
(312) 321-4200

MODULAR HOLDING CABINET

TECHNICAL FIELD

[0001] Modular holding cabinets are often used in commercial restaurant kitchens for food preparation lines where various different food products and ingredients are needed to be readily available for the food service professionals to access as they prepare food orders. Modular holding cabinets are normally used to receive food products that have previously been cooked in a heated environment where the food product can be quickly and efficiently prepared for sale or presentation to a customer.

BRIEF SUMMARY

[0002] A representative embodiment of the disclosure is provided. The embodiment includes a modular holding cabinet. The cabinet includes a housing comprising left and right side walls and a top wall above the left and right walls defining an internal volume therewithin and an open front that allows access into the internal volume. The housing supporting at least one plate disposed within the internal volume, the at least one plate extends between the left and right side walls and below the top wall. The housing supports one or more end walls that are each aligned in parallel with and spaced outboard from an end face of a respective one of the one or more plates such that an air gap is established therebetween. The internal volume defines a plurality of discrete heating zones located above each of the one or more plates, each of the one or more discrete heating zones are configured to selectively receive heat from a first heater disposed within the respective plate and one of a plurality of second heaters disposed above the respective plate, wherein each of the plurality of discrete heating zones includes a different one of the plurality of second heaters which is disposed vertically above the discrete heating zone. The housing further comprises a plurality of displays and a plurality of inputs, with one of the plurality of displays and one of the plurality of

inputs associated with each discrete heating zone, wherein each input is configured to receive user inputs associated with the operation of the respective discrete heating zone, and wherein each input is associated with controlling an operation of at least the second heater associated with the respective discrete heating zone.

[0003] Advantages of the disclosed devices will become more apparent to those skilled in the art from the following description of embodiments that have been shown and described by way of illustration. As will be realized, other and different embodiments are contemplated, and the disclosed details are capable of modification in various respects. Accordingly, the drawings and description are to be regarded as illustrative in nature and not as restrictive.

BRIEF DESCRIPTION OF THE DRAWINGS

[0004] FIG. 1 is a perspective view of a modular holding cabinet.

[0005] FIG. 2 is a view of detail B of FIG. 1.

[0006] FIG. 3 is the view of FIG. 2 with two covers removed.

[0007] FIG. 4 is a perspective cross-sectional view of the modular holding cabinet of FIG. 1 showing a pan disposed on the control bar and the pan open.

[0008] FIG. 5 is a cross-sectional view of the modular holding cabinet of FIG. 1 showing the pan disposed upon the plate and the pan closed by the cover.

[0009] FIG. 5a is a view of detail A of FIG. 5 showing the cover cut to remove the right side wall.

[0010] FIG. 5b is a view of detail A of FIG. 5.

[0011] FIG. 6 is a detail cross-sectional view of the modular holding cabinet of FIG. 1 showing the pan disposed upon the control bar and the pan open.

[0012] FIG. 7 is a perspective view of the modular holding cabinet of FIG. 1 showing the end of the pan disposed over the front air gap and the pan open.

[0013] FIG. 8 is a cross-sectional view of the modular holding cabinet of FIG. 1 showing an end of each pan disposed over the front air gap and the pan open.

[0014] FIG. 9 is a perspective cross-sectional view of the modular holding cabinet of FIG. 1 showing the rear end of the cover engaging the rear bar.

[0015] FIG. 10 is an exploded view of two sets of plates that collectively define several discrete heating zones of the modular holding cabinet of FIG. 1.

DETAILED DESCRIPTION OF THE DRAWINGS AND THE PRESENTLY PREFERRED EMBODIMENTS

[0016] Turning now to FIGs. 1-10, a modular holding cabinet 10 is provided. The modular holding cabinet 10 may be configured for use in the restaurant industry, such as the “fast food” industry or for other types of food service facilities, such as restaurants, cafeterias, banquet halls, or the like.

[0017] The modular holding cabinet 10 includes a housing 20 that is formed from left and right side walls 21, 22, a top wall 23, and a bottom wall 24. In some embodiments, some or all of these walls may be made from a single sheet of material, such as metal, while in other embodiments, some or all of these walls may be made from multiple sheets (or other geometries) of the same or different materials that are fixed together. In embodiments with multiple materials, some or all of the sheets may be disposed in parallel and either in contact with each other or may be spaced from each other. In some embodiments, other components may be associated with one or more of the left and right walls 21, 22, the top wall 23, and the bottom wall 24, such as insulation, electrical wiring, a controller 1000 (shown schematically in FIG. 1), or the like.

[0018] The housing 20 partially encloses an internal volume 27 therewithin, which is accessible through an open front 28 of the cabinet 10. In some embodiments, the internal volume 27 may also be accessible by a rear opening 29 that is defined on the opposite side of the housing 20 from the open front 28. The open front 28 (and rear opening 29, when provided) may be between the left and right walls 21, 22, below the top wall 23, and above the bottom wall 24.

[0019] The housing 20 includes one or more plates 40 that serve as shelves within the open volume 27. The plates 40 may be rigidly attached to one or both of the left and right walls 21, 22. In some embodiments one, some, or all of the plates 40 may be positioned in parallel with one or both of the top wall 23 and the bottom wall 24, and in some embodiments the one, all, or some of the plates 40 may be perpendicular to one or both of the left and right walls 21, 22.

[0020] Some or all of the plates 40 may extend to an end face, or end wall, 44 that establishes an end of the plate 40 that faces and is proximate to the open front 28. The end face 44 may extend along the entire width of each plate 40 between the left and right walls 21, 22. Some or all of the plates 40 may extend to a rear end face/wall 45 that is proximate to the open rear end 29 when provided.

[0021] In some embodiments, the cabinet 10 is configured such that each plate 40 establishes a plurality, such as 2, 3, 4, 5, or more discrete heating zones 100. Each discrete heating zone 100 may be disposed above a top surface 43 of one of the plates 40 and established below the plate 40 that is above the respective plate 40 (or top wall 23 in embodiments where the discrete heating zone 100 is established upon the upper most plate 40) within the internal volume 27. The discrete heating zones 100 are each configured such that a food product that is disposed within the discrete heating zone 100 (such as within a pan 400 that is disposed within the discrete heating zone 100 and rests upon the plate 40) is heated by the heat generated within the discrete heating zone 100. As discussed herein, the heat may be from the first (lower) heater 501 that is located within the plate 40 upon which the food product rests (normally within the pan 400), and the heat may additionally or alternatively be from the second (upper) heater 521 that is associated with the discrete heating zone 100 that is in the plate 40 (or top wall 23) that is above the food product. The first and second heaters 501 and 521, 522, 523, 524 are discussed in further detail below.

[0022] The cabinet 10 may further include one or more end walls 60 that are each aligned in parallel with and spaced outboard from an end face 44 of one of the respective plates 40, such that each plate 40 has one end wall 60 that is disposed outboard of it. All or a portion of the end wall 60 (as well as the similar rear wall 70, discussed below) may extend out of the housing 20 and specifically out of the internal volume of the cabinet, which is the heated environment of the housing 20. Each respective end wall 60 may be positioned with respect to each respective plate 40 such that an air gap, i.e. a space 80, is established therebetween, as best shown in FIGs. 4-8. In some embodiments, the air gap 80 may extend the entire distance between the left and right walls 21, 22, while in other embodiments, the air gap 80 may extend only a portion of the distance between the left and right walls 21, 22. In these embodiments, the air gap 80 may be discontinuous due to the placement of material within the space that would define the air gap (such as insulation, electrical conduit, or structure).

[0023] In some embodiments, one or more of the end walls 60 may be disposed such that a top surface 62 of the end wall 60 is disposed along the same plane as the top surface 43 of the associated plate, as shown schematically in FIG. 5a.

[0024] Each end wall 60 may include a plurality of displays 130 and inputs 140, and more specifically, each end wall 60 may include a display 130 and input 140 that is associated with each discrete heating zone 100 that is provided above the plate 40. In these embodiments, the end bar 60 is a control bar. In other embodiments, the end walls 60 (other than the lower most end wall 60) and the top wall 23 may include a plurality of displays 130 and inputs 140 that are associated with the discrete heating zone 100 that is located below the specific plate 40 and top wall. With reference to FIG. 1, in this embodiment a plurality of displays 130 and inputs 140 would be positioned upon the top wall at position “T”, and the displays 130 and inputs 140 that are depicted at position “S” in FIG. 1 would not be provided. In still other embodiments, the displays 130 and inputs 140 associated with each of

the discrete heating zones 100 in the housing may be disposed upon other surfaces than on the end wall 60, such as the side walls, or in a unified display and control device, such as a monitor and an input keyboard.

[0025] As mentioned above, in some embodiments, the housing 20 may include a rear opening 29 that provides for access to the plates 40, and more specifically to the discrete heating zones 100 above (and below) the plates 40. The rear opening 29 may be a full opening (other than the existence of the plates 40, and the rear end walls 70, discussed below). In these embodiments, the user may remove or insert pans 400 through the rear opening 29 as well as through the front opening 28. In other embodiments, a portion of the rear opening 29 may be blocked, such as with bars 700 (FIGs. 8 and 9) to prevent pans 400 from being withdrawn through the rear opening 29. In other embodiments, the housing 20 may not include a rear opening 29, but instead may include a rear wall (not shown) that further partially or fully encloses the internal volume 27 from the rear of the housing 20.

[0026] In embodiments where rear end walls 70 are provided in conjunction with one or more of the plates 40, the rear end walls 70 may be disposed outboard of the plate 40, and specifically a second end/face/wall 45 of the plate 40, to establish a second air gap 90 (i.e. a second space) between the respective rear end wall 70 and a second end face 45 of each plate 40, with the second end face 45 on an opposite side of the plate 40 from the first end face 44. When provided, the rear end walls may include a plurality of displays 130 and a plurality of inputs 140 that are associated with the discrete heating zones 100 that are above the plate 40 that is associated with the rear end wall 70 (or in other embodiments, the displays 130, and inputs 140 associated with the discrete heating zones 100 that are below the plate 40 with which the rear end wall 70 is associated). In embodiments where the plurality of displays 130 and inputs 140 are provided on both the front and rear end walls 60, 70, the respective displays 130 may be operated simultaneously, and one or both of the inputs 140 may be configured to accept user instructions.

[0027] In some embodiments, one or more of the rear end walls 70 may be disposed such that a top surface 73 of the rear end wall 70 is disposed along the same plane as the top surface 43 of the associated plate 40, as shown schematically in FIG. 5a.

[0028] Similar to the air gap 80 discussed above, in some embodiments the rear end wall 70 and the plate 40 may establish an air gap 90 that extends all of the way between the left and right side walls 21, 22, while in other embodiments, the air gap 90 may be discontinuous, and be oriented and provided (or not provided) in the same manner as the air gap 80 discussed above.

[0029] In some embodiments the holding cabinet 10 may include one or a plurality of removable covers 200 that are configured to be positioned within the open volume 27 and within one of the plurality of discrete heating zones 100. The cover extends between a first end 201 and a second end 202, and in some embodiments, the first and second ends 201, 202 of the cover may be symmetrical, such that, when the cover 200 is installed within the housing, either end may be disposed proximate to the open front portion 28 of the housing 20 with the opposite end proximate to the rear end of the housing 20.

[0030] The covers 200 may each include a top wall 223 and opposed left and right walls 221, 222 that each extend downwardly from the top wall 223. The left and right walls 221, 222 extend between front ends 221a, 222a and rear ends 221b, 222b with a central portion 222d (central portion of the left wall 221 like central portion 222d of the right wall 222) therebetween. The front and rear ends 223a, 223b of the top wall 223 each include an angled portion at the respective front and rear edge of the top wall, each angled portion is angled upwardly from the top wall 223.

[0031] The front ends 221a, 222a of the left and right side walls 221, 222 each include a horizontal ledge 251, 252 that is configured to rest upon the top surface 62 of the front wall 60 when the cover 200 is disposed within the housing and extends

over the plate 40. A foot 231, 232 extends below the ledge 251, 252 and is positioned behind the ledge. Each foot 231, 232 is configured to extend into the front air gap 80, with a front edge 231a, 232a of each foot 231, 232 resting against a rear end 64 of the front wall 60. The foot 231, 232 when properly resting within the air gap 80 does not contact the front wall 44 of the plate 40, and a space X (FIG. 5 is established between each foot 231, 232 and the front wall 44 of the plate 40 when the cover 200 is properly installed.

[0032] The rear ends 221b, 222b of the left and right side walls 221, 222 are configured in the same manner as the front ends 221a, 222b. Specifically, the each rear end includes a horizontal ledge 261, 262 that that is configured to rest upon the top surface 72 of the rear wall 70 when the cover 200 is disposed within the housing and extends over the plate 40. A foot 241, 242 extends below the ledge 261, 262 and is positioned behind the ledge. Each foot 241, 242 is configured to extend into the rear air gap 90, with a rear edge 241a, 242a of each foot 241, 242 resting against a front end 74 of the rear wall 70. The foot 241, 242 when properly resting within the air gap 90 does not contact the rear side 45 of the plate 40, and a space Y (FIG. 5) is established between each foot 241, 242 and the rear side 45 of the plate 40 when the cover 200 is properly installed.

[0033] When the cover 200 is installed within the housing 20, the cover extends over the plate 40, but does not contact or engage the plate 40 in any manner.

[0034] The central portion 221d, 222d, specifically the portion inboard of each of the front and rear feet 231, 241 and 232, 242 of each of the left and right walls 221, 222 each include a bottom edge 221c, 222c that is scalloped upwardly as it extends between the feet, such that the bottom edge 221c, 222c does not contact or engage in any manner the plate 40. The bottom edge 221c, 222c of each wall may be curved or include straight portions, or a combination of both. In some embodiments, and as shown in FIG. 5 the central portion (222d specifically shown in the figure, but the central portion 221d of the left wall 221 is similar) includes straight edges that

extend upwardly to a vertex at the center of the cover 200. In other embodiments, the scalloped portion may be horizontal along its length, at a height where the respective bottom edge 221d, 222d does not contact the top surface 43 or the ends 44, 45 of the plate 40 or otherwise engage the plate 40.

[0035] As can be understood with review of FIG. 5, the engagement of the feet 231, 232 into the air gaps 80, 90, and specifically the contact between the feet 231, 232 and the respective side wall 64, 74 of the respective front or end wall 60, 70 fixes the position of the cover 200 within the housing 20 and prevents the cover 200 from moving into and out of the housing 20 when pans 400 (which are positioned within a cover 200, as discussed below) are slidingly pulled out of and pushed into the housing 20, such as by the handle 401, when provided.

[0036] As can be best appreciated with a review of FIGs. 5-6 and 9, the engagement between the feet 231, 232 and 241, 242 and the air gaps 80, 90 fixes the cover 200 longitudinally within the housing 20, while the cover 200 may be able to slide horizontally within the housing 20 such as toward or away from the left or right side walls 21, 22. In some embodiments, the housing 20 is sized so that when each discrete heating zone 100 receives a cover 200, the neighboring side walls of the covers contact each other or are in close proximity with each other, and in some embodiments, the side wall of the outermost covers contact the neighboring side wall of the housing 21, 22, such that the covers 200 are fixed horizontally. In some embodiments, the housing 20 may include one or more tracks or barriers that fix the covers 200 horizontally with respect to the desired discrete heating zone 100 when installed.

[0037] The covers 200 are configured to be removable from the housing 20 without any tools. Specifically, the cover 200 can be removed from the housing by raising the cover 200 upward within the internal volume 27 until the feet 231, 232, 241, 242 no longer extend within the respective air gap 80 (90), and then the cover 200 may be slidingly withdrawn from the internal volume 27. Conversely, the cover

200 may be slidably installed into the internal volume 27, and slid until the feet 231, 232, 241, 242 extend into the air gap 80 (90).

[0038] The cover 200, container 400, and the plate 40 are configured such that the cover 200 closes a top opening 402 into the pan 400 when the container rests upon the plate 40, as shown in FIGs. 5-5b. As depicted in FIG. 5a, the front end 404 of the pan 400 is positioned upon the plate 40 such that the front end 404 of the pan is behind the front wall 44 of the plate by a distance Z. In some embodiments, the cover 200 (and specifically the top wall 223 of the cover 200), is configured such that the opening 402 into the pan 400 is fully closed by the top surface 223 (resting upon the top 403 of the pan) (therefore sealing the pan against humidity escaping from the volume of the pan 400) when the front end 404 of the pan rests upon the plate 40 such that the front surface of the pan 400 is aligned with or just slightly inboard of the front side 44 of the plate 40.

[0039] In other embodiments, the cover 200 may be configured such that the cover does not fully close the opening 402 into the pan 400 until the pan 400 is disposed rearwardly of the front end 44 of the plate, such as the distance Z, which may be 1, 2, 3, 4 inches or another suitable distance from the front wall 44. In this embodiment, user would be prompted to push the pan 400 further into the internal volume 27 in order to fully cover the opening 402 of the pan (than embodiments where the pan was fully closed when the front end 404 rested on or just rearwardly the front end wall 44 of the plate), which may make the entire pan 400 be maintained warmer (or be heated in a more thermal efficient manner) due to the heat loss through the open front 28 of the housing 20 or potentially less heat generation of the upper or lower heaters 521, 501 in the at the end of the plate than in the relative middle of the plate 40.

[0040] As shown in FIGs. 4 and 6, the opening 402 of the pan 400 is exposed (allow access into the volume of the pan to add and remove food from the pan 400) when the pan rests upon the control bar 60. Specifically, when the pan (any portion

of the pan) rests upon the control bar 60, the top surface 223 of the cover 200 does not extend completely over the opening 402. When the user desires to fully close the opening 402 of the pan from this position, the user pushes the pan 400 further onto the plate 40 until the top wall 223 of the cover 200 fully covers the opening into the pan 400, and when the pan 400 is entirely on the plate 40. It may be beneficial to design the cover 200 so that the pan 40 is partially open when the pan rests upon the control bar 60, because the control bar supports the pan 400 in this orientation thereby allowing the user to let go of the pan temporarily if their hand is needed for a cooking operation (with their opposite hand being used to add or remove food from the volume of the pan 400 through the opening), as well as to minimize the distance that the pan 400 needs to be withdraw from the discrete heating zone 100 to thereby minimize the amount of food within the pan 400 that leaves the discrete heating zone 100 while the cook temporarily pulls the pan 400 out to obtain some food within the pan.

[0041] While not specifically shown, in “pass-through” models of the cabinet 10, the opening 402 into the pan may be accessible when the pan 400 rests upon the rear bar (i.e. the orientation of FIGs. 4 and 6 as applied to the opposite end 405 of the pan and the rear bar 70), which would be beneficial in operation for the same reasons as discussed above. Similarly, in pass-through models of the cabinet, the cover 200, pan 400, and the plate 40 are configured such that opening 402 into the pan 400 is not closed (by the top wall 223 of the cover 200) until the pan fully rests upon the plate 40. In some embodiments, the opening 402 into the pan 400 isn't closed until the pan is rests upon the plate 40 past the rear end 45, such as a distance the same or similar to the distance Z of FIG. 5a, for the same reasons as discussed above.

[0042] As FIGs. 7 and 8 provide views of the front end 404 of the pan 400 disposed above the air gap 80, and FIG. 7 shows that the opening 402 into the pan 400 is partially visible and therefore is not fully closed. In pass through

embodiments, the opening 402 into the pan 400 would also not be fully closed when the opposite end 405 (FIG. 9) of the pan 400 is disposed over the rear air gap 90, and would be in a position similar to the position of FIGs. 7 and 8.

[0043] The covers 200, when provided, may be configured to partially enclose one of the discrete heating zones 100 and specifically the zone above the plate 40. The covers 200 may be sized to be larger than the pan 400 that is received within the cover and between the side walls 221, 222, or at least larger than the opening of the pan 400 to allow receipt of the food product therein. The covers 200 are sized such that the pan 400 can freely slide into and out of the cover 200 (such as with the handle 401), either with sliding contact between the pan 400 and the inner surfaces of the cover 200 (one, two or all of the left and right walls 221, 222 and the top wall 223), or with a space between the walls of the pan 400 and one, two, or all of the left and right walls 221, 222 and the top wall 223 of the cover 200.

[0044] As easily understood by one of ordinary skill, the covers 200 are readily removable and replaceable within the internal volume 27 of the housing 20, and the device 10 may be operated with some covers 200 enclosing some discrete heating zones 100 and other discrete heating zones 100 free of covers (but including pans 400). For example, when it is desired to heatingly store food products in a moist environment, the cover 200 may be installed in the discrete heating zone such to enclose (or only leave a small space above) the opening 402 into the pan 400 and to prevent moisture from the food products within the pan 400 from leaving the pan 400. In other words, the internal volume 228 of the cover 200 closely matches (and is slightly larger) than the geometry of the opening 402 into pan 400, and specifically, the top wall 223 of the cover 200 rests upon the top 403 of the pan 400 or is only slightly above the top 403 of the pan 400. Conversely, where a relatively dry environment is desired, the cover 200 may be removed from the discrete heating zone 100 to allow any moisture within the food product disposed within the opening 402 of the pan 400 to travel away from the pan 400 due to the large space between

the pan's opening 402 and the bottom surface of the plate 40 (or the top wall 23) above the pan 400.

[0045] As discussed above, each plate 40 may include one or a plurality of discrete heating zones 100. As shown schematically in FIG. 2, discrete heating zones 100 may be positioned adjacent to each other upon a plate 40, with the width of two neighboring discrete heating zones identified by 100w and 100w' (and a portion of another neighboring zone depicted as 100w''), with the height of both of these discrete heating zones identified by 100h, i.e. above the plate 40 and below the top wall 23.

[0046] FIG. 3 depicts the view of FIG. 2 with covers 200 removed from the discrete heating zones identified by width 100w' and 100w''.

[0047] As discussed above and as depicted schematically in FIG. 10, which shows a plate 40 and a second plate (40') that normally rests above the plate 40 within the housing 20 exploded above the plate 40, each discrete heating zone (schematically shown with their neighboring widths 100w, 100w', 100w'', 100w''') may receive heat from a lower heater 501 that is disposed within the plate 40 and an upper heater that is disposed within the plate 40' (which, when assembled is located above the plate 40). The lower heater 501 may be disposed within the plate 40 above which the cover 200 extends and, when provided, the pan 400 rests) (with the discrete heating zone 100 above that plate 40) and the upper heaters 521, 522, 523, 524 disposed within the plate 40 (or upper wall 23) that is above the plate 40. In embodiments where discrete heating zones 100 are disposed above the bottom of the housing, the lower heater 501 may be within the bottom wall 24.

[0048] In some embodiments, the lower heater 501 (depicted schematically as a solid line within the plates 40, 40') may be a single electric heating element such as a resistance heating element that extends about the entire width of the plate 40. In some embodiments, the lower heater 501 may be a straight heating element,

multiple straight heating elements powered from the same source, or a single heating element that is in a serpentine (as depicted) or in other patterns.

[0049] In some embodiments, the lower heater 501 may produce the same heat output per unit of length and may be disposed within the plate 40 such that the heat flow through upper surface of the plate 40 (i.e. the surface that the pan 400 and the rests upon) may be uniform (when the heater is disposed in a uniform manner), or substantially uniform through the entire surface of the plate 40. In other embodiments, the lower heater 501 may be formed from a heating element that generates more heat per unit length in some sections, and lower heat per unit length in other sections. In some embodiments, the lower heater 501 may be disposed such that the middle of the plate 40 may have more heat than the front and back and/or left and right side portions of the plate 40. One of ordinary skill in the art with a thorough review of this specification will appreciate that a suitable selection for a layout of the lower heater 501 would be only a product of routine optimization based upon the desired heating profile (either constant or cyclical, or based upon feedback control). In embodiments where the heater 501 is a single heater, the heater 501 may be controlled to be always on when the device 10 is on, or in other embodiments, a controller (1000, FIG. 1, shown schematically) may operate the heater 501 to maintain the temperature in the discrete heating zones 100 as desired, such as cyclically.

[0050] In other embodiments, the plate 40 may include multiple heaters 501, such as one heater 501 per discrete heating zone 100, with the controller 1000 controlling the heat to each heater 501 to maintain the desired temperature in the specific discrete heating zone 100.

[0051] One or more upper heaters 521 (522, 523, 524) may be provided within each plate 40 (and within the upper wall 23) to generate heat that is transferred into the discrete heating zone 100 that is below the respective plate 40 (and upper wall 23). As schematically depicted in FIG. 7, the upper heaters 521, 522, 523, 524 may

be disposed above the discrete heating zone (100w, 100w', 100w'', 100w''', respectively) such that the heat generated by the specific upper heater is directed to the discrete heating zone 100 disposed below the respective heater, but the neighboring discrete heating zones 100 do not receive a significant heat input from the upper heaters that are not directly thereabove. As can be understood with review of FIG. 7, discrete heating zone 100w receives heat from the lower heater 501, as well as the upper heater 521, the discrete heating zone 100w' receives heat from the lower heater 501 and the upper heater 522, etc. For ease of understanding the upper heaters 521, 522, 523, 524 are depicted in broken lines to visually differentiate them from the lower heater 501.

[0052] As shown in FIG. 10, each plate 40 (40') may include both a lower heater 501, and one or more upper heaters 521, 522, 523, 524 to allow the housing to maintain discrete heating zones in multiple levels of the housing 20.

[0053] The upper heaters 521, 522, 523, 524 may be similar heaters to the lower heater, and may be disposed in the specific or general orientation, or in a different orientation as the lower heaters. In FIG. 10, the upper and lower heaters are drawn to serpentine in opposite directions, which is drawn for the sake of differentiating the heaters in the figure, but the upper and lower heaters may be disposed in the same orientation and direction, or in different directions. In some embodiments, insulation may be provided between the upper heaters 521, 522, 523, 524 in a plate 40 and the lower heater 501 in the same plate, so that the heat generated by the respective heater travels generally through the surface of the plate 40 proximate to the plate and not in the direction of the other heater within the plate 40. While the name “upper” heater is used for elements 521, 522, 523, 524, the term “upper” refers to the location of that heater with respect to the discrete heating zone 100 that the heater interacts with, i.e. the “upper” heaters 521, 522, 523, 524 are disposed above the discrete heating zones, while the “upper heaters” may be disposed within the relative lower portion of the plate 40. Conversely, the “lower” heater 501 refers to

the location of the heater with respect to the discrete heating zone 100 that the heater interacts with, i.e. the lower heater interacts with the discrete heating zone 100 that is directly above the plate 40 and the “lower” heaters 501 may be disposed in the upper portion of the plate 40.

[0054] The upper heaters 521, 522, 523, 524 may be individually controlled to maintain the temperature within the respective discrete heating zone 100 associated with the heater, such as controlled with a set duty cycle, or controlled based upon feedback from one or more temperature sensors that are disposed proximate to the specific discrete heating zone 100. As can be appreciated, the housing (and specifically the front end wall 60, and/or rear end wall 70) includes inputs 140 and displays 130 that are associated with each discrete heating zone 100, and the instructions inputted by the user (such as a timer, or controls to set a desired temperature or temperature range) may be used by the controller 1000 to operate the respective upper heater (and lower heater 501 in embodiments where the lower heater (or a portion of the lower heater may be controlled) as necessary to maintain the desired temperature within the zone). One of ordinary skill in the art will appreciate that controllers are well known that are capable of controlling one or more heaters based upon feedback systems to maintain a monitored location (such as a discrete heating zone) within a temperature range.

[0055] While the preferred embodiments of the disclosure have been described, it should be understood that the disclosure is not so limited and modifications may be made without departing from the invention. The scope of the invention is defined by the appended claims, and all devices that come within the meaning of the claims, either literally or by equivalence, are intended to be embraced therein.

CLAIMS

1. A modular holding cabinet, comprising:

a housing comprising left and right side walls and a top wall above the left and right walls defining an internal volume therewithin, an open front that allows access into the internal volume, the housing supporting at least one plate disposed within the internal volume, the at least one plate extends between the left and right side walls and below the top wall,

the housing supports one or more end walls that are each spaced outboard from an end face of a respective one of the one or more plates such that an air gap is established therebetween;

the internal volume defining a plurality of discrete heating zones located above each of the one or more plates, each of the one or more discrete heating zones are configured to selectively receive heat from a first heater disposed within the respective plate and one of a plurality of second heaters disposed above the respective plate, wherein each of the plurality of discrete heating zones receives heat from a different one of the plurality of second heaters which is disposed vertically above the discrete heating zone,

the housing further comprising a plurality of displays and a plurality of inputs, with one of the plurality of displays and one of the plurality of inputs associated with each discrete heating zone, wherein each input is configured to receive user inputs associated with the operation of the respective discrete heating zone, and wherein each input is associated with controlling an operation of at least the second heater associated with the respective discrete heating zone.

2. The modular holding cabinet of claim 1, wherein each end wall includes the collective displays and inputs that are associated each of the discrete heating zones that are disposed above the plate associated with that end wall.

3. The modular holding cabinet of claim 1, wherein each end wall includes the collective displays and inputs that are associated with each discrete heating zone that is disposed below the plate that the collective displays and inputs are disposed upon.

4. The modular holding cabinet of claim 1, further comprising a rear opening into the internal volume from an opposite side of the housing as the open front, and further comprising one or more rear end walls that are each spaced outboard from a respective one of the one or more plates, wherein each of the rear end walls are spaced outboard of the respective plate with a second space provided between the rear end wall and a second end face, opposite the end face, of the respective plate.

5. The modular holding cabinet of claim 4, wherein the second space provided between the respective end rear wall and the second end face of the respective plate extends between the left and right walls.

6. The modular holding cabinet of claim 1, further comprising one or more covers that are configured to be removably disposed within the internal volume, wherein the covers are dimensioned such that when positioned over the plate the cover partially encloses one of the discrete zones upon the plate and when centered above one discrete zone the cover does not interact with other discrete zones over the plate.

7. The modular heating cabinet of claim 6, wherein when the cover is installed within the housing and within a discrete heating zone the cover does not contact the plate.

8. The modular holding cabinet of claim 6, wherein the cover fully encloses an opening to a pan disposed therein when the pan is entirely disposed upon the plate.

9. The modular holding cabinet of claim 8, wherein a portion of the opening into the pan is not enclosed by the cover when a portion of the pan is disposed upon the end wall.

10. The modular holding cabinet of claim 8, wherein a portion of the opening into the pan is not enclosed by the cover when a portion of the pan is disposed over the air gap.

11. The modular holding cabinet of claim 6, wherein each of the plurality of covers include a top wall and opposed left and right walls that extend from the top wall, wherein a front portion of one or both of the left and right walls includes a front foot that extends below a bottom edge of the respective left or right wall along a central portion of the cover, wherein the foot is configured to extend within the first air gap.

12. The modular holding cabinet of claim 11, wherein the bottom edge of each of the left and right walls is scalloped above the foot such that when the foot extends within the air gap the bottom edge does not contact any portion of the plate.

13. The modular holding cabinet of claim 11, wherein the first portion of each of the left and right side walls includes a horizontal portion that rests upon the front wall when the front foot extends into the air gap.

14. The modular holding cabinet of claim 13, wherein the front foot contacts a rear side of the front wall when the front foot extends into the air gap.

15. The modular holding cabinet of claim 11, further comprising a rear opening into the internal volume from an opposite side of the housing as the open front, and further comprising one or more rear end walls that are each spaced outboard from a respective one of a second end face of the one or more plates, wherein each of the rear end walls are spaced outboard of the respective plate with a second air gap provided between the rear end wall and a second end face, opposite the end face, of the respective plate,

wherein a rear portion of one or both of the left and right walls of the cover includes a second foot that extends below the bottom edge of the respective left or right wall along the central portion of the cover, wherein the second foot is configured to extend within the second air gap when the cover is positioned over the plate.

16. The modular holding cabinet of claim 11, wherein the cover can be removed from and installed into the housing to partially enclose one of the discrete heating zones without any tools.

17. The modular holding cabinet of claim 1, wherein the at least one plate is disposed within the housing in parallel with the top wall.

18. The modular holding cabinet of claim 1, wherein the at least one plate extends horizontally between the left and right side walls.

19. The modular holding cabinet of claim 1, wherein the one or more end walls each are aligned in parallel with a respective one of the one or more end plates that is associated with the respective end wall.

20. The modular holding cabinet of claim 1, wherein a top surface of each of the one or more end walls extends along the same plane as a top surface of the respective plate that is associated with the respective end wall.

21. The modular holding cabinet of claim 1, wherein one or more end walls extend outside of the internal volume of the housing.

ABSTRACT OF THE DISCLOSURE

A modular holding cabinet is provided. The cabinet includes a housing defining an internal volume and an open front providing access into the internal volume. The housing supports at least one plate therewithin. The housing supports one or more end walls that are each aligned spaced outboard from an end face of a plate such that an air gap is established therebetween. The internal volume defines a plurality of discrete heating zones located above each of the one or more plates, each discrete heating zone receives heat from a first heater disposed within the respective plate and a plurality of second heaters disposed above the respective plate. The housing includes a plurality of displays and a plurality of inputs, with one of the plurality of displays and one of the plurality of inputs associated with each discrete heating zone.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	12361-624
		Application Number	
Title of Invention	MODULAR HOLDING CABINET		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Inventor Information:

Inventor 1					Remove	
Legal Name						
Prefix	Given Name	Middle Name	Family Name	Suffix		
	Robert	C.	Fortmann			
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service						
City	Grayslake	State/Province	IL	Country of Residence	US	
Mailing Address of Inventor:						
Address 1		33000 N. Forest Drive				
Address 2						
City	Grayslake	State/Province	IL			
Postal Code	60030	Country	US			
Inventor 2					Remove	
Legal Name						
Prefix	Given Name	Middle Name	Family Name	Suffix		
	Frank	G.	Marolda			
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service						
City	Vernon Hills	State/Province	IL	Country of Residence	US	
Mailing Address of Inventor:						
Address 1		151 N. Fiore Parkway				
Address 2						
City	Vernon Hills	State/Province	IL			
Postal Code	60061	Country	US			
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.						
Add						

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).
--

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	12361-624
		Application Number	
Title of Invention	MODULAR HOLDING CABINET		

☐ An Address is being provided for the correspondence information of this application.

Customer Number	00757		
Email Address		Add Email	Remove Email

Application Information:

Title of the Invention	MODULAR HOLDING CABINET		
Attorney Docket Number	12361-624	Small Entity Status Claimed	☐
Application Type	Provisional		
Subject Matter	Utility		
Total Number of Drawing Sheets (if any)	12	Suggested Figure for Publication (if any)	

Filing By Reference :

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)

☐ **Request Not to Publish.** I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application **has not and will not** be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)
Customer Number	00757		

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	12361-624
		Application Number	
Title of Invention	MODULAR HOLDING CABINET		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.

When referring to the current application, please leave the application number blank.

Prior Application Status		Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the **Add** button.

Foreign Priority Information:

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX)ⁱ the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Application Number	Country ⁱ	Filing Date (YYYY-MM-DD)	Remove
			Access Code ⁱ (if applicable)

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

☐ This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013. NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	12361-624
		Application Number	
Title of Invention	MODULAR HOLDING CABINET		

Authorization to Permit Access:

☒ Authorization to Permit Access to the Instant Application by the Participating Offices
If checked, the undersigned hereby grants the USPTO authority to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the World Intellectual Property Office (WIPO), and any other intellectual property offices in which a foreign application claiming priority to the instant patent application is filed access to the instant patent application. See 37 CFR 1.14(c) and (h). This box should not be checked if the applicant does not wish the EPO, JPO, KIPO, WIPO, or other intellectual property office in which a foreign application claiming priority to the instant patent application is filed to have access to the instant patent application. In accordance with 37 CFR 1.14(h)(3), access will be provided to a copy of the instant patent application with respect to: 1) the instant patent application-as-filed; 2) any foreign application to which the instant patent application claims priority under 35 U.S.C. 119(a)-(d) if a copy of the foreign application that satisfies the certified copy requirement of 37 CFR 1.55 has been filed in the instant patent application; and 3) any U.S. application-as-filed from which benefit is sought in the instant patent application. In accordance with 37 CFR 1.14(c), access may be provided to information concerning the date of filing this Authorization.

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.		
Applicant 1		
If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.		
Clear		
☐ Assignee	☐ Legal Representative under 35 U.S.C. 117	☐ Joint Inventor
☒ Person to whom the inventor is obligated to assign.		☐ Person who shows sufficient proprietary interest
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:		
Name of the Deceased or Legally Incapacitated Inventor :		
If the Applicant is an Organization check here. ☒		
Organization Name	Carter-Hoffmann, Inc.	

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	12361-624
		Application Number	
Title of Invention	MODULAR HOLDING CABINET		

Mailing Address Information For Applicant:			
Address 1		1551 McCormick Avenue	
Address 2			
City	Mundelein	State/Province	IL
Country	US	Postal Code	60060
Phone Number		Fax Number	
Email Address			
Additional Applicant Data may be generated within this form by selecting the Add button.			

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.			
Assignee 1			
Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.			
If the Assignee or Non-Applicant Assignee is an Organization check here. ☒			
Organization Name	Carter-Hoffmann, Inc.		
Mailing Address Information For Assignee including Non-Applicant Assignee:			
Address 1		1551 McCormick Avenue	
Address 2			
City	Mundelein	State/Province	IL
Country	US	Postal Code	60060
Phone Number		Fax Number	
Email Address			
Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.			

Signature:

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications.			
Signature	/Stephen C. Smith/	Date (YYYY-MM-DD)	2015-07-17

Application Data Sheet 37 CFR 1.76		Attorney Docket Number		12361-624	
		Application Number			
Title of Invention		MODULAR HOLDING CABINET			
First Name	Stephen C.	Last Name	Smith	Registration Number	56250
Additional Signature may be generated within this form by selecting the Add button.					

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.