previously unthinkable (e.g. providing medical info to mountain rescue scenes) and to accompany everyone as easily as they carry the time on their wristwatches.

Finally, today, many more people have access to mobile devices than access to a desktop computer. This is likely to be very significant in developing countries, where Web-capable mobile devices may play as similar a role in deploying wide-spread Web access as the mobile phone has played for providing "plain old telephone service".

3 Delivery Context

Delivery Context is used with the specific meaning defined in the Device Independence Glossary [DIGLOSS].

3.1 One Web

The recommendations in this document are intended to improve the experience of the Web on mobile devices. While the recommendations are not specifically addressed at the desktop browsing experience, it must be understood that they are made in the context of wishing to work towards "One Web".

As discussed in the Scope document [Scope], *One Web* means making, as far as is reasonable, the same information and services available to users irrespective of the device they are using. However, it does not mean that exactly the same information is available in exactly the same representation across all devices. The context of mobile use, device capability variations, bandwidth issues and mobile network capabilities all affect the representation. Furthermore, some services and information are more suitable for and targeted at particular user contexts (see 5.1.1 Thematic Consistency of Resource Identified by a URI).

Some services have a primarily mobile appeal (location based services, for example). Some have a primarily mobile appeal but have a complementary desktop aspect (for instance for complex configuration tasks). Still others have a primarily desktop appeal but a complementary mobile aspect (possibly for alerting). Finally there will remain some Web applications that have a primarily desktop appeal (lengthy reference material, rich images, for example).

It is likely that application designers and service providers will wish to provide the best possible experience in the context in which their service has the most appeal. However, while services may be most appropriately experienced in one context or another, it is considered best practice to provide as reasonable experience as is possible given device limitations and not to exclude access from any particular class of device, except where this is necessary because of device limitations.

From the perspective of this document this means that services should be available as some variant of HTML over HTTP (see 3.7 Default Delivery Context).

3.2 Background to Adaptation

The widely varying characteristics of mobile devices can make it difficult for a Web site to provide an acceptable user experience across a significant range of devices. For example different devices support different markup features and different screen sizes may demand different sized images. Consequently, it is very common when delivering content to mobile devices to vary the details of the markup, format of images, image sizes, color depths and so on to suit the characteristics of the device in question. The process of altering content to enhance the user experience on particular devices is referred to as *Content Adaptation*.

We do not describe adaptation in detail in this document. For a more detailed description, readers are referred to the Device Independence Principles [DIP].

In addition, the sister group of the Best Practices Working Group, the Device Description Working Group, is currently defining requirements for a repository of mobile device characteristics that are relevant to content adaptation.

3.3 Adaptation Implementation Model

There are a number of different implementation models for content adaptation. On the one hand, adaptation may be quite simple and consist of determining the device type and choosing the most appropriate set of previously prepared content to match the device characteristics. At the other extreme it may be carried out in a completely dynamic way, with content formatted at the time of retrieval, taking into account not only statically determined properties, such as screen dimension, but also dynamically determined properties, such as the temporary attachment of a fully featured keyboard.

Adaptation can be carried out in a number of different points in the delivery of content to the device [DCODI]:

Server Side adaptation implies that the content is delivered by the originating content server or application.

In-Network adaptation is where the content is altered as it passes through one or more network components. Some network operators, for example, compress images before they are passed over the air to the mobile device.

Client Side adaptation consists of the device accepting content and displaying it in an appropriate way for its characteristics.

Whatever the adaptation model at work, the process of adaptation should not diminish accessibility.

3.4 Assumptions about Adaptation

In phase 1 (See 1.4.1 Phasing) it is assumed that content adaptation, if any, is carried out Server Side. Future phases may consider the implications of content adaptation elsewhere, especially the issues concerning the granting of authority to third parties to carry out adaptation, prohibiting adaptation and so on. Later phases may also address multiple adaptation - i.e. the possibility that adaptation can be applied at more than one point and that In-Network adaptation may occur more than once.

It is also assumed that it is possible to create a site that is consistent with the Best Practice recommendations without carrying out adaptation at all. However it is likely that a more sophisticated and enhanced user experience will be achieved if adaptation is used.

3.5 Establishing Context

Providing variations on the user experience that are appropriate in different cases requires the content provider to know a significant amount about the characteristics of the device, the properties of the browser in use and the transparency of the network connection to the device.

For simple sites that present an interface which is similar across a broad range of contexts the need for such information is diminished when compared with a sophisticated site that has an optimized navigation structure, presents different size images or carries out other adaptations to suit the particular delivery context.

There are several methods by which a content provider can discover information about the delivery context, such as CC/PP, UAPROF, CSS Media Queries and various outputs of the Device Independence Working Group. The companion Techniques [Techniques] document describes these methods.

3.6 Choice of User Experience

In the interests of "One Web" (see 3.1 One Web) considerations, the content provider may choose to allow the user to select from broad categories such as mobile or desktop presentation, where these are distinguished in the application. If the presentation option has been determined automatically, the content provider may choose to allow the user to override the automatic determination. Where a choice of presentations is available, it is good practice to record the user's preferences and to allow them to be changed.

Given an appropriate server environment, it is unlikely that the content provider will be unable to find out anything about the delivery context. However this can

happen, either because details of the delivery context are not available in sufficient detail or because the server does not provide the ability to inspect and act on the information provided. In this case a "reasonable default experience" should be provided.

The details of the default experience depend upon a number of factors including, but not limited to, the geographic region in which the service is offered and the primary intention of the service (e.g. considering whether the service is primarily desktop focused vs. primarily mobile focused).

3.7 Default Delivery Context

In order to allow content providers to share a consistent view of a default mobile experience the BPWG has defined the Default Delivery Context. This allows providers to create appropriate experiences in the absence of adaptation and provides a baseline experience where adaptation is used. The Default Delivery Context has been determined by the BPWG as being the minimum delivery context specification necessary for a reasonable experience of the Web. It is recognized that devices that do not meet this specification can provide a reasonable experience of other non-Web services.

It is also recognized that this specification is made against the background of demographic, cultural and economic assumptions. Content providers may choose to provide services that demand a different or lower delivery context specification, but should try to provide an experience that exploits the capabilities of the Default Delivery Context in order to provide the best possible experience for that context.

It is stressed that many devices exceed the capabilities defined by the DDC. Content providers are encouraged not to diminish the user experience on those devices by developing only to the DDC specification, and are encouraged to adapt their content, where appropriate, to exploit the capabilities of the actual device.

In summary, the purpose of defining the DDC is to support the following rules:

- If an adaptation process is used, then information that is known about the actual Delivery Context should (see 5.1.2 Exploit Device Capabilities) be used to vary the delivered content to make it more suitable for that specific Delivery Context or to provide an enhanced user experience.
- If the delivered content does not result from an adaptation process - e.g. the content is statically defined as HTML stored in files, or the details of the Delivery Context cannot adequately be determined, then the delivered content should be suitable for the Default Delivery Context and should comply with the Best Practice statements.

The Default Delivery Context is defined as follows:

Usable Screen Width

120 pixels, minimum.

Markup Language Support

XHTML Basic 1.1 [XHTML-Basic] delivered with content type `application/xhtml+xml`.

Character Encoding

UTF-8 [UTF-8].

Image Format Support

JPEG.

GIF 89a.

Maximum Total Page Weight

20 kilobytes.

Colors

256 Colors, minimum.

Style Sheet Support

CSS Level 1 [CSS]. In addition, CSS Level 2 [CSS2] `@media` rule together with the `handheld` and `all` media types (see CSS 2 Media Types).

HTTP

HTTP/1.0 [HTTP1.0] or more recent [HTTP1.1].

Script

No support for client side scripting.

4 Structure of Best Practice Statements

The Heading

The functional area that is addressed by the statements.

The Statements

One or more Best Practice statements, identified in the following way:

> [EXAMPLE] This is a Best Practice statement.

What it means

An explanation of the significance of the statements under this heading.

How to do it

A discussion of techniques and some suggestions as to how to implement. The BPWG is creating a separate document describing techniques [Techniques] in more detail.

What to Test

The aspects of the delivered content that an external validator could examine to assess conformance with the Best Practice statements. This section is not

This aspects of the delivered content that an external validator could examine to assess conformance with the Best Practice statements. This section is not present for process related statements.

In this section it is noted whether the statement is *Machine Testable* (Automated testing is possible) or *Human Testable* (Testing requires human assessment). Some Best Practices are partially machine testable, i.e. based on the result of an automated test, some human interaction may be required. In such cases both a Machine Testable and a Human Testable statement are present.

Some Best Practice statements use words such as "minimize" and "avoid" which are intentionally non-prescriptive. This is in order to provide guidance while leaving room to accommodate a wide variety of applications whose requirements cannot be anticipated. It also allows creativity and diversity within the same Best Practice framework. More prescriptive advice can be found in the Techniques document [Techniques].

References

Where appropriate, references to related WCAG points and other immediate references from the preceding text.

5 Best Practice Statements

The Best Practice statements are grouped under the following headings

- 5.1 Overall Behavior
- 5.2 Navigation and Links
- 5.3 Page Layout and Content
- 5.4 Page Definition
- 5.5 User Input

5.1 Overall Behavior

There are some general principles that underlie delivery to mobile devices.

5.1.1 Thematic Consistency of Resource Identified by a URI

[THEMATIC_CONSISTENCY] Ensure that content provided by accessing a URI yields a thematically coherent experience when accessed from different devices.

5.1.1.1 What it means

This is a realization of the One Web (see 3.1 One Web) principle, whereby content should be accessible on a range of devices irrespective of differences in presentation capabilities and access mechanism. Web sites may paginate their content in various ways corresponding to differences in device characteristics; therefore the navigation structure of the site, and possibly its technical realization, may vary according to the device class that is being served. (See also [WebArch] Section 3.5.1).

A bookmark captured on one device should be usable on another, different type of device even if it does not yield exactly the same experience. If the page that was bookmarked is not appropriate for the device that is now using it, an alternative that is suitable should be provided.

URIs may be decorated to provide session or other information. If a URI is decorated with session information that is no longer current, then the user should be directed to a point in the navigation hierarchy that is appropriate to their device, in order to establish appropriate session and other parameters.

5.1.2 Exploit Device Capabilities

[CAPABILITIES] Exploit device capabilities to provide an enhanced user experience.

5.1.2.1 What it means

While encouraging content providers to be sensitive to the needs of the Default Delivery Context, it is not intended that this will result in a diminished experience on more capable devices. Develop sites that target the Default Delivery Context. In addition, where appropriate, use device capabilities to provide a better user experience on more capable devices.

5.1.3 Work around Deficient Implementations

[DEFICIENCIES] Take reasonable steps to work around deficient implementations.

5.1.3.1 What it means

Just as in the desktop world, there are browsers that do not respect the intentions of the content provider. There are differences in interpretation between browsers and there are also deficiencies in implementation. By deficient we mean non-support of mandatory features of a relevant standard or recommendation and other bugs or errors in implementation.

Because the software in mobile devices is frequently embedded in the device, there is no easy way to correct or enhance it once it is in the field. It is a particular challenge to provide work-arounds for these deficiencies and differences in interpretation. It is recognized that content providers may need to violate specific Best Practices in order to support their intentions on devices that exhibit deficiencies in implementation. If a device is not known to have specific limitations then content providers must comply with Best Practices.

Just as it is not the intention to recommend a least common denominator approach, neither is it the intention to recommend avoiding features that exhibit problems on some class of devices.

It is also not the intention to suggest that content providers should restrict their support to certain device types. Content providers should aim to support as wide a range of device types as is practical.

5.1.4 Testing

[TESTING] Carry out testing on actual devices as well as emulators.

5.1.4.1 What it means

Any Web site should be tested in a range of browsers. Mobile browsers often show markedly different characteristics to desktop browsers. As well as assessing a site's suitability for display in reduced format, content providers are encouraged to test that the features they rely on work in actual devices.

Content providers should also test with specific features disabled, such as using text-only modes and with scripting disabled.

5.1.4.2 How to do it

Many manufacturers provide emulators for their device that can provide a convenient preliminary means of testing. However, in practice, many of the emulators behave in a different way to the devices they emulate. Consequently testing should be carried out in as wide a range of real devices and specific software versions as is practical.

5.2 Navigation and Links

Because of the limitations in display and of input mechanisms, the possible absence of a pointing device and other constraints of mobile devices, care should be exercised in defining the structure and the navigation model of a Web site.

5.2.1 URIs of Site Entry Points

[URIS] Keep the URIs of site entry points short.

5.2.1.1 What it means

Typing URIs on mobile devices can be difficult, and it is expected that users will prefer to use alternative methods of obtaining URIs when available - such as following a hyperlink (from an e-mail, SMS or other Web page), WAP Push, 2D bar code, color bar code, RFID tag and Bluetooth. However, typing a URI may in some cases be the only option available. By keeping site entry point URIs short it is possible to reduce the chance of error and provide a more satisfactory user experience.

5.2.1.2 How to do it

When accessing site entry points users should not have to enter a filename as part of the URI. If possible, configure Web sites so that they can be accessed without having to specify a sub-domain as part of the URI.

Example: Instead of requiring users to type

```
"http://www.example.org/index.html"
```

allow

```
"http://example.org"
```

and instead of

```
"http://www.example.org/example.html"
```

allow

```
"http://example.org/example"
```

5.2.2 Navigation Bar

[NAVBAR] Provide only minimal navigation at the top of the page.

5.2.2.1 What it means

Provide basic navigation, which should be placed on the top of the page. Any other secondary navigational element may be placed at the bottom of the page if really needed. It is important the users should be able to see page content once the page has loaded without scrolling (see 5.3.4 Navigation Bars etc. (Extraneous material)).

5.2.2.2 How to do it

Provide the basic links on a single line.

5.2.3 Balanced Structure

[BALANCE] Take into account the trade-off between having too many links on a page and asking the user to follow too many links to reach what they are looking for.

5.2.3.1 What it means

The design should aim to provide a balance between having a large number of navigation links on a page and the need to navigate multiple links to reach content.

Scrolling a page when there are many links on it can be very cumbersome, as the scrolling action on many mobile devices selects each link in turn. On the other hand, each retrieval of a navigation page takes time and adds cost, so the number of links on a page should not be minimized at the expense of adding page retrievals.

Design the service so that frequently accessed information is easily reached with a minimum number of page retrievals. Navigation to less frequently accessed information may take more retrievals as a result. A guideline is that users become frustrated if it takes more than four retrievals to reach their objective. Whether this can be achieved depends on the nature of the site and, in particular, how items in menus group together to provide understandable themes.

5.2.4 Navigation Mechanisms

[NAVIGATION] Provide consistent navigation mechanisms.

5.2.4.1 What it means

Using the same navigation mechanisms across a service helps users orient themselves and allows them to identify navigation mechanisms more easily.

Users of devices that do not have pointing devices have to scroll between hyperlinks using the keypad. Intelligent grouping, perhaps optimized through adaptation according to usage patterns, can assist usability.

5.2.4.2 How to do it

A "drill-down" method, based on major headings, can often provide an effective means of navigation; because of the linearized arrangement of content, small screen size and lack of pointing device, it is often useful to provide a means to jump entire sections of content.

At each target of the drill-down navigation an "up" link should be provided to allow the user to jump up an entire section.

5.2.4.3 References

This relates to WCAG 13.4.

5.2.5 Access Keys

[ACCESS_KEYS] Assign access keys to links in navigational menus and frequently accessed functionality.

5.2.5.1 What it means

Where there is no pointing device, assigning an access key (keyboard short cut) to a link can provide a convenient way for users to access the link and avoid navigating to the link by repeated pressing of the navigation key.

Provide the same access key for links that are repeated across pages such as links to the home page.

5.2.5.2 What to test

Machine Test: Test for the presence of the `accesskey` attribute.

Human Test: Verify the presence of the `accesskey` attribute on links such as the home page.

5.2.5.3 References

This relates to WCAG 9.5.

5.2.6 Link Target Identification

[LINK_TARGET_ID] Clearly identify the target of each link.

[LINK_TARGET_FORMAT] Note the target file's format unless you know the device supports it.

5.2.6.1 What it means

Users of mobile devices may suffer undue delay and cost as a result of following links. It is important to identify where a link leads so users can make an assessment of whether following it will be of interest to them. While it is unlikely that the cost in monetary terms of a particular user following a particular link can be specified, it should be possible to give an idea of the size of the resource (in bytes or in an abstract way, e.g. large file).

Links to content that is in a different format or different language to that of the page the link is on (i.e. content that can only be interpreted by other applications or downloads) should be human signposted, so that users are not lead to download content that their device may not be able to use. However, bear in mind that some devices support the rendering of those formats by other applications once downloaded (e.g. music files). Additionally, users may wish to download content for later transfer to other devices altogether. So even if it is known that the user agent does not support a particular content type, that content should still be made available.

5.2.6.2 How to do it

Use clear, concise, descriptive link text to help users decide whether to follow a link. Identify the implications of following a link if the target is notably large and the user might not anticipate this from the context.

For the Default Delivery Context all formats other than XHTML, GIF and JPG should be noted.

5.2.6.3 What to test

Human Test: Check for proper descriptions (e.g. no use of "Click here").

Machine Test: Check for links to non-HTML formats.

Human Test: If present, check whether there is information about the format of the target of the link.

Human Test: If present check whether there is information about the format of the target of the link.

5.2.6.4 References

This relates to WCAG 11.3 and 13.1.

5.2.7 Image Maps

[IMAGE_MAPS] Do not use image maps unless you know the device supports them effectively.

5.2.7.1 What it means

Image maps allow fast navigation providing the requesting device can support the image involved and providing there is a means of navigating the map satisfactorily. Up, down, left, right and enter are available on most mobile devices, even if there is no pointing device. This is usually sufficient to allow navigation of the active regions of client-side image maps where they are defined as geometric shapes.

Many mobile devices lack a pointing device and server-side image maps cannot be used on such devices.

5.2.7.2 How to do it

If only small images can be displayed, break larger images up into smaller sections and deal with them separately.

For the Default Delivery Context, or if a satisfactory image map cannot be displayed, use a list of links with descriptive text instead.

5.2.7.3 What to test

IMAGE_MAPS Machine Test: Send a request to the site with a device that does not support client-side image maps and check the `map` element is not present.

5.2.7.4 References

This relates to WCAG 1.2 and 9.1.

5.2.8 Refreshing, Redirection and Spawned Windows

[POP_UPS] Do not cause pop-ups or other windows to appear and do not change the current window without informing the user.

[AUTO_REFRESH] Do not create periodically auto-refreshing pages, unless you have informed the user and provided a means of stopping it.

[REDIRECTION] Do not use markup to redirect pages automatically. Instead, configure the server to perform redirects by means of HTTP 3xx codes.

5.2.8.1 What it means

Each of these activities is likely to cause the user confusion, or add cost and delay to their interaction.

Some mobile devices use a separate window for input; this section does not refer to such windows.

Many mobile devices cannot support more than one window and consequently, attempting to open one will have unpredictable results.

Auto-refreshing pages are widely recognized as presenting accessibility problems. In a mobile environment they may expose the user to undue cost as a result of such a page being left open or put unnoticed into the background. If an auto-refreshing page is demanded by the application, always provide a means of ceasing the refresh and always inform the user that the page will refresh and may expose them to higher usage costs.

While redirection is a commonly employed mechanism, it must be remembered that redirection usually requires a round-trip to the browser. This adds to delay on slow links; so use a maximum of one redirect per page and limit the number of pages that are redirected.

5.2.8.2 What to test

POP_UPS Machine Test: Look for the `target` attribute on links and if present check to see if it has a value different from `_self`, `_parent` or `_top`.

AUTO_REFRESH Machine Test: Check whether `meta http-equiv="refresh" content="<the same URI>"` is used.

AUTO_REFRESH Human Test: If auto-refresh is used, check that options are provided to stop any page using auto-refresh.

REDIRECTION Machine Test: Check whether `meta http-equiv="refresh" content="<a different URI>"` is used.

5.2.8.3 References

This relates to WCAG 7.4, 7.5 and 10.1.

5.2.9 Externally Linked Resources

[EXTERNAL_RESOURCES] Keep the number of externally linked resources to a minimum.

5.2.9.1 What it means

Each linked resource (images, style sheets and other objects) requires a separate request across the network. This may add significantly to the load time of the page in the mobile context.

5.2.9.2 How to do it

Minimize the number of images on a page and consolidate style information into a single sheet per page (see also 5.4.9 Style Sheets).

5.2.9.3 What to test

Machine Test: Count the number of linked images, style sheets and other linked items.

Human Test: Review whether a similar effect could be obtained using fewer links.

5.3 Page Layout and Content

This section refers to the user's perception of the delivered content. It concentrates on design, the language used in its text and the spatial relationship between constituent components. It does not address the technical aspects of how the delivered content is constructed, which is discussed in 5.4 Page Definition.

5.3.1 Page Content

[SUITABLE] Ensure that content is suitable for use in a mobile context.

[CLARITY] Use clear and simple language.

[LIMITED] Limit content to what the user has requested.

5.3.1.1 What it means

Users in a mobile context are often looking for specific pieces of information, rather than browsing. Content providers should consider the likely context of use of information and, while providing the option to access all information, should offer appropriate information first. See also discussion under 2.4 User Goals and 3.1 One Web.

The general prescription to use clear language is of particular importance for mobile delivery, where brevity and directness are generally more desirable than a discursive style.

Writing content in the traditional journalistic "front loaded" style can assist users determining whether information is of interest to them and allow them to skip it more easily if it is not. Placing distinguishing information at the beginning of headings, paragraphs, lists, etc. can also help the user contextualize when using devices with limited screen area. See also 5.3.4 Navigation Bars etc. (Extraneous material) for a discussion of making sure that the subject matter of the page is near the top.

Mobile users often pay for bandwidth, so offering them content that is extraneous to their needs, especially advertising, costs them time and money and contributes to an unsatisfactory experience. In general, the user's consent should be sought before initiating the download of content.

5.3.1.2 What to test

Human Test: Examine content to determine if, given the subject matter, it is appropriate in a mobile context.

5.3.1.3 References

This relates to WCAG 13.8 and 14.1.

5.3.2 Page Size

[PAGE_SIZE_USABLE] Divide pages into usable but limited size portions.

[PAGE_SIZE_LIMIT] Ensure that the overall size of page is appropriate to the memory limitations of the device.

5.3.2.1 What it means

If pages are too big they may take an unduly long time to load. In addition, mobile devices typically have restrictions on the largest page they can accommodate.

On the other hand, if pages are too short then the user will be required to make multiple requests to read the relevant information. This can lead to an unnecessary delay, since each request typically takes a measurable time to complete.

The balance between pagination and scrolling is partly a matter of taste and partly a matter of necessity. Devices with severe memory restrictions can only have small pages delivered to them. Equally some devices offer a poor scrolling experience and a better page retrieval experience.

Some studies [MF] have been carried out in this area to test for user preferences. Some of these indicate that users prefer scrolling to click-throughs and some indicate the contrary. More research is likely to be needed in this area.

5.3.2.2 How to do it

For the Default Delivery Context assume the limits specified in 3.7 Default Delivery Context.

5.3.2.3 What to test

PAGE_SIZE_USABLE Machine Test: Measure the total size of the markup for a page; check that it does not exceed 10 kilobytes for the Default Delivery Context.

Human Test: Check that the page is still usable (e.g. not cut in the middle of a sentence, just before the end of a section, and so on).

PAGE_SIZE_LIMIT Machine Test: Measure the total size of markup and images for a page; check that it does not go over the allowed size for the device - 20 kilobytes for the Default Delivery Context.

5.3.2.4 References

This relates to WCAG 12.3.

5.3.3 Scrolling

[SCROLLING] Limit scrolling to one direction, unless secondary scrolling cannot be avoided.

5.3.3.1 What it means

The page should lay out so that simple repeated scrolling in the same direction (axis) allows the user to experience all its content. However some content (such as maps and other images) cannot be displayed without secondary scrolling.

If some element on the page requires secondary scrolling it must not cause the remainder of the page to require this. For example, if an object causes subsequent text to lay out with a significant margin to its left, then this text may not be visible once a user has scrolled past the object.

Equally, if the presence of such an object causes text to render beyond the right boundary of the page then the user will be required to scroll to read each line of text.

5.3.3.2 How to do it

If it is not possible to avoid presenting images that are larger than the screen size, then consider providing these images on a separate page with a link back to the main content.

In the Default Delivery Context assume a width of 120 pixels.

5.3.3.3 What to test

SCROLLING Machine Test: Check for `width` attributes and width style properties wider than the screen size - for the Default Delivery Context, 120 pixels.

Human Test: If it is wider than the screen size, check that the use case warrants it (e.g. maps).

Browse URIs within a site with a mobile device and observe that on pages with elements that require secondary scrolling only those elements require it, and the rest of the page requires only primary scrolling.

5.3.4 Navigation Bars etc. (Extraneous material)

[CENTRAL_MEANING] Ensure that material that is central to the meaning of the page precedes material that is not.

5.3.4.1 What it means

Many Web pages are designed with significant navigational and other elements at the top of or to the side of the page (e.g. Menu Bars, Breadcrumb Trails and Search Functions). This provides a convenient and well-understood navigational metaphor on large displays. However, on small displays this can result in the navigation appearing instead of the actual content of the page when the page is first retrieved.

Because it is important for the user to gain an idea of the content of the page on initial view, there should be a minimum amount of clutter preceding this - including navigation, decorative images, advertising and other material that is not central to the user's experience of the page. The user should not have to scroll significantly to find the primary content of the page.

See also 5.3.1 Page Content for a discussion of how writing style can help the user identify meaning.

5.3.4.2 How to do it

Menu selections can be placed away from the top of the page with a simple link to the selection at the top of the page. Alternatively, use meta navigation on top of the page with simple text links to major sections of the Web site.

5.3.4.3 What to test

Human test: Browse URIs within a site with a mobile device and observe that the most important/relevant information is conveyed first.

5.3.4.4 References

This relates to WCAG 13.5.

5.3.5 Graphics

[GRAPHICS_FOR_SPACING] Do not use graphics for spacing.

[LARGE_GRAPHICS] Do not use images that cannot be rendered by the device. Avoid large or high resolution images except where critical information would otherwise be lost.

5.3.5.1 What it means

The popular mechanism of using a 1 pixel graphic for absolute positioning does not work on a variety of screens.

Graphics that are larger than necessary, for example by having a higher resolution than is displayable on the device or by having too many colors, waste bandwidth.

5.3.5.2 What to test

GRAPHICS_FOR_SPACING Machine Test: Check for very small and/or transparent graphics.

LARGE_GRAPHICS Machine Test: Check dimensions of graphics.

5.3.6 Color

[USE_OF_COLOR] Ensure that information conveyed with color is also available without color.

[COLOR_CONTRAST] Ensure that foreground and background color combinations provide sufficient contrast.

5.3.6.1 What it means

Mobile devices often do not have good color contrast and are often used in less-than-ideal lighting conditions. Hence information highlighted in color may not be visible to users. If color is used to indicate a feature then that feature should generally also be indicated in a way that is not color dependent. In particular, do not use blue or purple text, as this may be confused with hyperlinks, especially on devices that do not underline links.

5.3.6.2 What to test

USE_OF_COLOR Human Test: Browse the page in a monochrome environment.

COLOR_CONTRAST Human Test: Browse the page under a strong light parallel to the screen.

Machine Test: There are automatic tools to test color contrast.

5.3.6.3 References

This relates to WCAG 2.1 and 2.2.

5.3.7 Background Images

[BACKGROUND_IMAGE_READABILITY] When using background images make sure that content remains readable on the device.

5.3.7.1 What it means

Images that are used indiscriminately can lead to content that is hard to view, particularly with the limited contrast often found on mobile devices and in the hostile viewing conditions in which mobile devices are frequently used.

Before using background images, consider carefully your objectives for doing so and try to use alternative techniques to achieve similar objectives. If you use a background image ensure that the content is readable with and without the background image for devices that do not support them.

5.3.7.2 What to test

Machine Test: Test for the presence of a background image.

Human Test: Test readability both on devices that support them and devices that do not.

5.4 Page Definition

5.4.1 Title

[PAGE_TITLE] Provide a short but descriptive page title.

5.4.1.1 What it means

Provide a descriptive title for the page to allow easy identification. Keep the title short to reduce page weight, and bear in mind that it may be truncated.

Many mobile browsers do not display the title of a page. Where the title is displayed the available space may be limited.

The device may use the page title as the default label for bookmarks. Again, space may be limited, so use it to help identify the content and not for other purposes.

5.4.1.2 What to test

Machine Test: Test for presence of the `title` element.

Human Test: Test that the title is descriptive of content.

5.4.2 Frames

[NO_FRAMES] Do not use frames.

5.4.2.1 What it means

Many mobile devices do not support frames. In addition, frames are recognized as being generally problematic.

5.4.2.2 What to test

Machine Test: Test for presence of frame related elements - check for `frameset` and `iframe` elements.

5.4.2.3 References

See http://www.w3.org/TR/xframes/#s_intro for a discussion of problems with frames.

5.4.3 Structural Elements

[STRUCTURE] Use features of the markup language to indicate logical document structure.

5.4.3.1 What it means

It is good practice for all but the simplest documents to indicate their structure through headings and sub-headings. Using structural markup, rather than formatting effects, allows easier adaptation of content where it needs to be divided into several pages, as well as potentially facilitating access to the sections of the document that a user is interested in.

Where headings are used they should be used in accordance with the specification, i.e. they should be properly nested according to their level.

Structural markup must not be used solely to create a font effect (see also 5.4.3 Structural Elements).

5.4.3.2 How to do it

Markup languages like HMTL contain many constructs to indicate structure.

5.4.4 Tables

[TABLES_SUPPORT] Do not use tables unless the device is known to support them.

[TABLES_NESTED] Do not use nested tables.

[TABLES_LAYOUT] Do not use tables for layout.

[TABLES_ALTERNATIVES] Where possible, use an alternative to tabular presentation.

5.4.4.1 What it means

Tables do not work well on limited size screens and may result in the user having to scroll horizontally to read them. Putting navigational links into tables may result in the user having both to scroll horizontally and vertically to see possible navigational choices.

5.4.4.2 What to test

TABLES_SUPPORT Machine Test: Send a request to the site with a device that does not support tables and check the `table` element is not present.

Machine Test: Check that there are no nested tables.

TABLES_LAYOUT Machine Test: Check that no column or row in a table is empty or contains only a 1x1 transparent GIF.

Machine Test: If there is a `table` element, check to see whether there is rendered content outside the element. If there is not then it is likely that the table is being used for layout.

5.4.4.3 References

This relates to WCAG 5.1, 5.2, 5.3, 5.5 and 5.6.

5.4.5 Non-Text Items

[NON-TEXT_ALTERNATIVES] Provide a text equivalent for every non-text element.

[OBJECTS_OR_SCRIPT] Do not rely on embedded objects or script.

5.4.5.1 What it means

A *non-text item* is defined by Non-text content in the WAI Glossary [WAIGlossary].

Downloading images to a mobiledevice adds to the time to display an image and the cost of displaying the page. Making the page readable in text-only mode can help the user assess its usefulness before images arrive.

Many mobile devices do not support embedded objects or script and in many cases it is not possible for users to load plug-ins to add support. Content must be designed with this in mind.

Even where a device does support scripting, do not use it unless there is no other way of accomplishing your objectives. Scripting increases power consumption and so decreases battery life.

5.4.5.2 How to do it

Design pages so that they are useful when rendered as text-only. See also 5.1.4 Testing

Design pages so that they are useful when rendered as text only. See also 5.1.4 Testing.

Always use features of the markup designed to support alternate rendering such as the `longdesc` and `alt` attributes in XHTML.

Use only features from the markup that are known to be supported by the device in question.

Avoid things like CSS image replacement and pictures of words.

If scripting is used, do not use `onmouse` and `onkey` triggers, use `onclick`.

5.4.5.3 What to test

NON-TEXT_ALTERNATIVES Machine Test: Test for presence of `alt` attribute on images and text content on objects.

Human Test: Check the relevance of the meaning of the content of `alt` attributes.

OBJECTS_OR_SCRIPT Machine Test: Test for the presence of `object` or `script` elements in content delivered to a device that does not support them and if present carry out the Human Test below.

Human Test: If present, test that the user experience is acceptable.

5.4.5.4 References

This relates to WCAG 1.1, 3.1, 6.2, 6.3, 6.5 and 9.2.

5.4.6 Image Size

[IMAGES_SPECIFY_SIZE] Specify the size of images in markup, if they have an intrinsic size.

[IMAGES_RESIZING] Resize images at the server, if they have an intrinsic size.

5.4.6.1 What it means

Images such as bitmaps have an intrinsic size. Telling the browser in advance what the size is avoids it having to re-flow the page when it receives it. Resizing images at the server reduces the amount of data transferred and the amount of processing the device has to carry out to scale the image.

Note that this recommendation contrasts with 5.4.8 Measures, which recommends using relative measures where possible.

5.4.6.2 What to test

IMAGES_SPECIFY_SIZE Machine Test: Test for presence of `width` and `height` attributes on `img` elements.

IMAGES_RESIZING Machine Test: Check `width` and `height` attributes are equal to image dimensions.

5.4.7 Valid Markup

[VALID_MARKUP] Create documents that validate to published formal grammars.

5.4.7.1 What it means

If the page markup is invalid this will result in unpredictable and possibly incomplete presentation.

5.4.7.2 What to test

Machine Test: Validate documents.

5.4.7.3 References

This relates to WCAG 3.2, 11.1 and 11.2.

See http://www.w3.org/QA/Tools/#validators.

5.4.8 Measures

[MEASURES] Do not use pixel measures and do not use absolute units in markup language attribute values and style sheet property values.

5.4.8.1 What it means

Avoiding pixel and absolute measures allows the browser to adapt content to fit the display. An exception to rule is where an image has been specifically sized for a particular display (see 5.4.6 Image Size). In this case references to the image in markup may specify the exact dimensions of the image in pixels, in order to help the browser to flow the page and avoid re-flowing it after the page has been retrieved. Devices may realize the intentions of authors more accurately if margins, borders and padding are specified in pixels.

5.4.8.2 How to do it

Use percentage and relative measures such as `em`, `ex`, `bolder`, `larger` and `thick`.

5.4.8.3 What to test