US011021867B2

(12) **United States Patent**
Brekke et al.

(10) **Patent No.: US 11,021,867 B2**
(45) **Date of Patent: Jun. 1, 2021**

(54) **HANGER FOR FIRE SEPARATION WALL**

(71) Applicant: **Columbia Insurance Company**, Omaha, NE (US)

(72) Inventors: **Steven Brekke**, Lakeville, MN (US); **Mark R. Rolf**, Fredericksburg, VA (US)

(73) Assignee: **Columbia Insurance Company**, Omaha, NE (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **16/433,799**

(22) Filed: **Jun. 6, 2019**

(65) **Prior Publication Data**

US 2019/0284794 A1 Sep. 19, 2019

Related U.S. Application Data

(63) Continuation of application No. 16/225,517, filed on Dec. 19, 2018, now Pat. No. 10,316,510, which is a continuation of application No. 15/675,409, filed on Aug. 11, 2017, now Pat. No. 10,184,242, which is a (Continued)

(51) **Int. Cl.**
E04B 1/26 (2006.01)

(52) **U.S. Cl.**
CPC ***E04B 1/2612*** (2013.01)

(58) **Field of Classification Search**
CPC E04B 1/2612; E04B 1/2608; E04B 1/2604; E04B 1/945; E04B 1/94; E04B 1/26; E04B 2001/2644; E04B 2001/2652; E04B 2001/2676; E04B 2001/2415; E04B 2001/2684; E04B 5/12; E04B 5/14; E04B 7/045; B21D 53/56; Y10T 403/4605;
(Continued)

(56) **References Cited**

U.S. PATENT DOCUMENTS

414,169 A * 10/1889 Reuschel E04B 1/2612 403/232.1
478,163 A * 7/1892 Lehman F16B 7/0446 403/190
(Continued)

FOREIGN PATENT DOCUMENTS

JP 0314482 Y2 3/1991
JP 05171718 A 7/1993
(Continued)

OTHER PUBLICATIONS


Complaint for Patent Infringement, Case No. 3:19-cv-04683, filed Aug. 12, 2019, pp. 6.
(Continued)

Primary Examiner — James M Ference
(74) *Attorney, Agent, or Firm* — Stinson LLP

(57) **ABSTRACT**

A hanger for connecting a structural component to a wall that can have sheathing mounted thereon either before or after the hanger is connected to the wall. The hanger includes a channel-shaped portion configured to receive the structural component. An extension portion extends from the channel-shaped portion and is configured to extend through the sheathing to engage the wall at a first location. A connection portion is configured for attachment to the wall at a second location spaced from the first location.

23 Claims, 43 Drawing Sheets



Simpson Strong-Tie Company Inc. EX1038
Simpson Strong-Tie Co. v. Columbia Insurance Co.
U.S. Patent No. 11,649,626

Related U.S. Application Data

continuation of application No. 14/555,049, filed on Nov. 26, 2014, now Pat. No. 10,024,049.

(60) Provisional application No. 61/922,531, filed on Dec. 31, 2013.

(58) **Field of Classification Search**
CPC Y10T 403/3921; Y10T 403/4602; Y10T 29/49623
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

537,504	A *	4/1895	Van Dorn	F16B 7/0446	403/190
546,147	A *	9/1895	Gregg	E04B 1/2612	403/232.1
598,135	A *	2/1898	Butz	E04B 1/2612	403/232.1
625,427	A *	5/1899	Stewart, Jr. et al.	F16B 7/0446	403/190
666,918	A *	1/1901	Butz	F16B 7/0446	403/190
717,316	A *	12/1902	Avery	A47C 23/062	403/190
753,053	A *	2/1904	Eberhardt	F16B 7/0446	403/190
770,050	A *	9/1904	Dreyer	F16B 7/0446	403/190
783,807	A *	2/1905	Tuteur	E04B 1/2612	403/232.1
796,433	A *	8/1905	Kahn	F16B 7/0446	403/190
804,451	A *	11/1905	Carlson	E04B 1/2612	52/702
828,488	A *	8/1906	Lanz	B21D 53/00	29/897.3
874,514	A *	12/1907	Lindow	F16B 7/0446	403/190
922,215	A *	5/1909	Tuteur	F16B 7/0446	403/190
924,842	A *	6/1909	Seipp	F16B 7/0446	403/190
943,847	A *	12/1909	Seipp	F16B 7/0446	403/190
1,406,723	A *	2/1922	Caldwell	E04B 1/2608	403/232.1
1,728,981	A *	9/1929	Ropp	E04B 1/2612	52/702
3,125,785	A *	3/1964	Conville	E04B 2/80	52/238.1
3,601,428	A	8/1971	Gilb		
3,633,950	A	1/1972	Gilb		
3,752,512	A	8/1973	Gilb		
3,907,445	A *	9/1975	Wendt	E04B 1/2612	403/191
3,945,741	A *	3/1976	Wendt	E04B 1/5818	403/191
3,972,169	A *	8/1976	Sheppard, Jr.	E04B 1/2608	52/702
4,005,942	A *	2/1977	Gilb	E04B 1/2612	403/189
4,198,175	A *	4/1980	Knepp	F16B 15/0046	403/191
4,223,866	A *	9/1980	Black	E04G 17/18	249/211
4,230,416	A *	10/1980	Gilb	E04B 1/2612	248/300
4,261,155	A *	4/1981	Gilb	E04B 1/2612	248/282.1
4,353,664	A *	10/1982	Gilb	E04B 1/2612	403/232.1
4,411,548	A *	10/1983	Tschan	E04B 1/2612	403/232.1
4,422,792	A *	12/1983	Gilb	E04B 1/2612	403/232.1
4,423,977	A	1/1984	Gilb		
4,472,916	A *	9/1984	Krebs	E04B 1/18	52/236.6
4,480,941	A	11/1984	Gilb et al.		
4,560,301	A *	12/1985	Gilb	B21D 53/38	403/232.1
4,584,813	A *	4/1986	Hudson	E04B 1/2612	248/214
4,594,017	A *	6/1986	Hills	E04B 1/2612	403/232.1
4,665,672	A *	5/1987	Commins	E04B 1/0007	403/190
4,709,527	A	12/1987	Cooley		
4,717,279	A	1/1988	Commins		
4,827,684	A	5/1989	Allan		
4,893,961	A	1/1990	O'Sullivan et al.		
4,920,725	A *	5/1990	Gore	E04B 1/2612	403/232.1
5,004,369	A	4/1991	Young		
5,104,252	A *	4/1992	Colonias	E04B 1/2612	403/230
5,111,632	A *	5/1992	Turner	E04B 1/2612	403/232.1
5,160,211	A *	11/1992	Gilb	E04F 11/181	256/65.02
5,217,317	A	6/1993	Young		
5,230,198	A *	7/1993	Callies	E04B 1/2608	403/232.1
5,249,404	A *	10/1993	Leek	E04B 1/0007	182/87
5,341,619	A *	8/1994	Dunagan	E04B 1/2612	248/300
5,423,156	A	6/1995	Nellessen, Jr.		
5,457,928	A *	10/1995	Sahnazarian	E04B 1/2612	403/232.1
5,555,694	A *	9/1996	Commins	E04B 1/2612	248/300
5,564,248	A *	10/1996	Callies	E04B 1/2612	403/232.1
5,603,580	A *	2/1997	Leek	E04B 1/2612	403/168
5,697,725	A *	12/1997	Ballash	E04B 1/2608	403/231
5,797,694	A *	8/1998	Breivik	E04B 1/2608	403/231
5,896,721	A *	4/1999	Sugiyama	E04B 1/2604	403/232.1
6,131,358	A *	10/2000	Wise	E04B 1/2612	52/289
6,230,466	B1 *	5/2001	Pryor	E04B 1/2612	403/231
6,463,711	B1 *	10/2002	Callies	E04B 1/2612	403/232.1
6,877,291	B2 *	4/2005	Shamroukh	E04B 7/022	403/232.1
7,316,098	B1 *	1/2008	Sackett	E04B 7/045	52/712
7,707,785	B2 *	5/2010	Lin	E04B 7/045	52/289
7,971,410	B2 *	7/2011	Jerke	E04H 9/14	52/702
8,387,333	B2	3/2013	Brekke		
8,677,718	B2 *	3/2014	Marshall	E04D 3/3608	52/655.1
8,720,155	B1 *	5/2014	Robell	E04B 1/2612	52/289
9,206,594	B1 *	12/2015	Grevious	F16B 5/0614	
2001/0054270	A1	12/2001	Rice		
2002/0078656	A1 *	6/2002	Leek	E04B 1/2612	52/702

(56) **References Cited**

U.S. PATENT DOCUMENTS

2004/0096269	A1*	5/2004	Shahnazarian	E04B 1/2612 403/232.1
2004/0129845	A1*	7/2004	Whale	E04B 1/2612 248/201
2005/0120669	A1*	6/2005	Harrison	E04B 1/2612 52/698
2005/0155307	A1*	7/2005	Timony	E04B 1/2612 52/506.01
2006/0081743	A1*	4/2006	Evans	E04C 3/125 248/226.11
2006/0156682	A1*	7/2006	McAndrew	E04B 5/14 52/837
2006/0191233	A1*	8/2006	Tamlyn	F16B 15/0023 52/702
2007/0011959	A1*	1/2007	DeBene	E04G 21/1891 52/105
2007/0119108	A1*	5/2007	Downard	E04B 1/2604 52/289
2007/0294979	A1*	12/2007	Lin	E04B 1/2612 52/702
2008/0101855	A1*	5/2008	Lin	E04B 1/2612 403/232.1
2008/0237421	A1*	10/2008	Szpotowski	E04B 5/12 248/222.51
2009/0113839	A1*	5/2009	Carr	E04B 1/2612 52/712
2010/0031601	A1*	2/2010	Lin	E04B 1/2612 52/712
2011/0146173	A1*	6/2011	Visser	E04B 1/26 52/268
2012/0222382	A1*	9/2012	Brekke	E04B 1/2612 52/702
2012/0297724	A1*	11/2012	Pope	E04B 1/2608 52/702
2013/0067850	A1*	3/2013	Sasanecki	E04B 1/2612 52/702
2013/0232758	A1*	9/2013	Pond	F16B 7/185 29/428
2014/0338282	A1*	11/2014	Sidhu	E04C 3/04 52/702
2015/0059259	A1*	3/2015	Hatzinikolas	E04B 1/941 52/98
2015/0167291	A1*	6/2015	Bundy	E04B 1/2612 52/702
2015/0184370	A1*	7/2015	Brekke	E04B 1/2612 52/708
2015/0218832	A1*	8/2015	Peters	E04B 5/12 269/46
2017/0321418	A1*	11/2017	Tremblay	A47K 1/14

FOREIGN PATENT DOCUMENTS

JP	H7-229225	8/1995
WO	2012060863 A2	5/2012
WO	2013126987 A1	9/2013

OTHER PUBLICATIONS

Plaintiffs' Notice of Motion and Motion for Preliminary Injunction; Memorandum of Points and Authorities in Support of Motion, Case No. 3:19-cv-04683, filed Aug. 12, 2019, pp. 20.

Installer's Pocket Guide, Simpson Strong-Tie Company, Inc. (2009), pp. 60.

Top-Flange Joist Hangers Installed on Walls Over Wood Structural Panel Sheathing or Drywall, Technical Bulletin, Simpson Strong-Tie Company, Inc. (2013), pp. 2.

S/LBV / S/B and S/BA Hangers, Simpson Strong-Tie Company, Inc. (2010), pp. 1.

Cold-Formed Steel Connectors for Residential and Mid-Rise Construction (C-CFS10), Simpson Strong-Tie Company, Inc. (2010) pp. 76.

Wood Construction Connectors Catalog 2013-2014 (C-2013), Simpson Strong-Tie Company, Inc. pp. 236.

Declaration of Dr. Reynaud Serrette, filed as Exhibit 2001 in Case No. PGR2019-00063 on Dec. 13, 2019, 124 pages.

Curriculum Vitae of Reynaud L. Serrette, Ph.D., filed as Exhibit 2002 in Case No. PGR2019-00063 on Dec. 13, 2019, 15 pages.

American Institute of Timber Construction, Timber Construction Manual, Fourth Edition, 1994, filed as Exhibit 2015 in Case No. PGR2019-00063 on Dec. 13, 2019, 17 pages.

International Code Council, International Building Code, 2012, filed as Exhibit 2016 in Case No. PGR2019-00063 on Dec. 13, 2019, 57 pages.

International Code Council, International Building Code, 2000, filed as Exhibit 2017 in Case No. PGR2019-00063 on Dec. 13, 2019, 60 pages.

MiTek, Fire Wall Hangers FWH Series, Structural Connectors Specification Sheet, 2019, tiled as Exhibit 2018 in Case No. PGR2019-00063 on Dec. 13, 2019, 2 pages.

Simpson Strong-Tie, DU/DHU/DHUTF Drywall Hangers Specification Sheet, filed as Exhibit 2019 in Case No. PGR2019-00063 on Dec. 13, 2019, 7 pages.

ICC-ES Evaluation Report, Mar. 2019, filed as Exhibit 2021 in Case No. PGR2019-00063 on Dec. 13, 2019, 18 pages.

Definition of From, The New Oxford American Dictionary, Second Edition, 2005, filed as Exhibit 2022 in Case No. PGR2019-00063 on Dec. 13, 2019, 4 pages.

Gypsum Association, Gypsum Panel Products Types, Uses, Sizes, and Standards, 2004, filed as Exhibit 2023 in Case No. PGR2019-00063 on Dec. 13, 2019, 2 pages.

PABCO Gypsum, for Those About to Rock PABCO Gypsum Products, filed as Exhibiti 2024 in Case No. PGR2019-00063 on Dec. 13, 2019, 8 pages.

Beall, C., "Fire Ratings of Masonry Walls," 1989, filed as Exhibit 2025 in Case No. PGR2019-00063 on Dec. 13, 2019, 3 pages.

Bilow, D. N., et al., "Fire and Concrete Structures," 2008, filed as Exhibit 2026 in Case No. PGR2019-00063 on Dec. 13, 2019, 10 pages.

Irish Concrete Federation, Comprehensive Fire Protection and Safety with Concrete, Dec. 2007, filed as Exhibit 2027 in Case No. PGR2019-00063 on Dec. 13, 2019, 33 pages.

MontgomeryTownship Department of Planning and Zoning, Basement Finish/Remodel Code, 2009, filed as Exhibit 2028 in Case No. PGR2019-00063 on Dec. 13, 2019, 5 pages.

Township of Hillsborough, Sample Guide for Finish Basement Requirements in Existing One and Two Family Dwellings, Jan. 30, 2012, filed as Exhibit 2029 in Case No. PGR2019-00063 on Dec. 13, 2019, 5 pages.

Lstiburek, J., "Understanding Basements," Building Science Digest 103, filed as Exhibit 2030 in Case No. PGR2019-00063 on Dec. 13, 2019, 18 pages.

Moisture Control in Buildings: The Key Factor in Mold Prevention, 2nd Edition, 2009, filed as Exhibit 2031 in Case No. PGR2019-00063 on Dec. 13, 2019, 67 pages.

U.S. Department of Agriculture, Forest Service, Wood-Frame House Construction, Agriculture Handbook No. 73, Apr. 1975, filed as Exhibit 2032 in Case No. PGR2019-00063 on Dec. 13, 2019, 12 pages.

CEL Consulting, Inc., Testing of Joist Hangers per AC13 "Acceptance Criteria for Joist Hangers and Similar Devices," filed as Exhibit 2033 in Case No. PGR2019-00063 on Dec. 13, 2019, 17 pages.

Patent Owner's Preliminary Response to the Petition for Post Grant Review filed in Case No. PGR2019-00063 on Dec. 13, 2019, 120 pages.

Petitioner Simpson Strong-Tie Company Inc.'s Reply to Patent Owner's Preliminary Response filed in Case No. PGR2019-00063 on Feb. 10, 2020, 9 pages.

Supplemental Declaration of W. Andrew Fennell in Support of Petitioner's Reply to Patent Owner's Preliminary Response filed in Case No. PGR2019-00063 on Feb. 10, 2020, 6 pages.

Minutes of Telephonic Meeting Held on Jan. 30, 2020, filed in Case No. PGR2019-00063 on Jan. 30, 2020, 29 pages.

(56) **References Cited**

OTHER PUBLICATIONS

Order Denying Plaintiffs' Motion for Preliminary Injunction, Case No. 3:19-w-04683, filed Oct. 4, 2019, pp. 20.
Reply in Support of Plaintiffs' Notice of Motion and Motion for Preliminary Injunction; Memorandum of Points and Authorities in Support of Motion, Case No. 3:19-cv-04683, filed Sep. 13, 2019, pp. 18.
Answer, Affirmative Defenses, and Counterclaim to Complaint for Patent Infringement, Case No. 3:19-cv-04683, filed Sep. 3, 2019, pp. 8.
Memorandum of Points and Authorities in Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, filed Sep. 5, 2019, pp. 31.
Declaration of W. Andrew Fennell in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, filed Sep. 5, 2019, pp. 91.
Declaration of Sam Hensen in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683 filed Sep. 5, 2019, pp. 8.
Investigation of U.S. Appl. No. 16/225,517, Exhibit A to Declaration of W. Andrew Fennell in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683,dated Jun. 3, 2019, pp. 68.
Declaration of Joseph V. Mauch in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, filed Sep. 5, 2019, pp. 4.
Invalidity Claim Chart, U.S. Pat. No. 10,316,510, Exhibit E to Declaration of Joseph V. Mauch in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, dated Sep. 2019, pp. 30.
Invalidity Claim Chart, U.S. Pat. No. 10,316,510, Exhibit F to Declaration of Joseph V. Mauch in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, dated Sep. 2019, pp. 30.
Invalidity Claim Chart, U.S. Pat. No. 10,316,510, Exhibit G to Declaration of Joseph V. Mauch in Support of apposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, dated Sep. 2019, pp. 32.
Invalidity Claim Chart, U.S. Pat. No. 10,316,510, Exhibit H to Declaration of Joseph V. Mauch in Support of Opposition to Motion for Preliminary Injunction, Case No. 3:19-cv-04683, dated Sep. 2019, pp. 32.
Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, filed Sep. 5, 2019, pp. 152.
Declaration of W. Andrew Fennell in Support of Petition for Post-Grant Review of U.S. Patent No. 10,316,510, Exhibit 1003 , dated Sep. 5, 2019, pp. 172.
Fire-Rated Assemblies in Commercial Construction, Exhibit 1016 to Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, dated May 2014, pp. 106.
Fire Resistance Design Manual Sound Control, Exhibit 1017 to Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, dated Jun. 2012, pp. 230.
International Building Code,Exhibit 1018 to Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, dated May 2011, pp. 12.
Stainless steel for durability, fire-resistance and safety, Exhibit 1030 to Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, pp. 8.
Infringement Claim Charts, Exhibit 1031 to Petition for Post-Grant Review of U.S. Pat. No. 10,316,510, dated Aug. 2019, pp. 20.
Decision Granting Institution of Post-Grant Review issued in Case No. PGR2019-00063 on Mar. 12, 2020, 63 pages.
Patent Owner's Sur-Reply filed in Case No. PGR2019-00063 on Feb. 20, 2020, 10 pages.
Patent Owner's Corrected Sur-Reply filed in Case No. PGR2019-00063 on Mar. 3, 2020, 9 pages.
Supplemental Declaration of W. Andrew Fennell in Support of Petitioner's Reply to Patent Owner's Preliminary Response filed as Exhibit 1036 in Case No. PGR2019-00063 on Feb. 10, 2020, 6 pages.
Supplemental Declaration of Dr. Reynaud Serrette, filed as Exhibit 2034 in Case No. PGR2019-00063 on Feb. 19, 2020, 5 pages.
Trimber, K. A., et al., "Measuring Moisture in Walls," Interface, Apr. 2012, filed as Exhibit 2035 in Case No. PGR2019-00063 on Feb. 19, 2020, 8 pages.
U.S. Department of Housing and Urban Development, Office of Policy Development and Research, Building Concrete Masonry Homes: Design and Construction Issues, filed as Exhibit 2036 in Case No. PGR2019-00063 on Feb. 19, 2020, 43 pages.
CGC Inc., The Gypsum Construction Handbook, Centennial Edition, 2005, filed as Exhibit 2037 in Case No. PGR2019-00063 on Feb. 19, 2020, 34 pages.
Clarkwestern Dietrich Building Systems LLC, Furring Channel/Hat Channel, filed as Exhibit 2038 in Case No. PGR2019-00063 on Feb. 19, 2020, 3 pages.
ASTM International, Standard Specification for Testing and Establishing Allowable Loads of Joist Hangers, Designation: D7147-11, filed as Exhibit 2039 in Case No. PGR2019-00063 on Feb. 19, 2020, 10 pages.
APA, Floor Construction, an Excerpt of the Engineered Wood Construction Guide, Dec. 2019, filed as Exhibit 2040 in Case No. PGR2019-00063 on Feb. 19, 2020, 16 pages.
International Code Council, 2012 International Building Code, 2011, filed as Exhibit 2041 in Case No. PGR2019-00063 on Feb. 19, 2020, 17 pages.
Supplemental Declaration of Dr. Reynaud Serrette, filed as Exhibit 2042 in Case No. PGR2019-00063 on Feb. 26, 2020, 5 pages.
Petitioner Simpson Strong Tie Company Incs Opposition to Patent Owners Contingent Motion to Amend, Case PGR2019-00063, U.S. Pat. No. 10,316,510, Aug. 27, 2020, pp. 1-30.
Petitioner Simpson Strong Tie Company Incs Reply to Patent Owners Response, Case PGR2019-00063, U.S. Pat. No. 10,316,510, Aug. 27, 2020, pp. 1-35.
Exhibit 1038 Serrette Deposition Transcript, Case PGR2019-00063, Jul. 29, 2020, pp. 1-272.
Exhibit 1039 Fennell Declaration, Case PGR2019-00063, U.S. Pat. No. 10,316,510, Aug. 27, 2020, pp. 1-28.
Exibit 1040 Definition, pp. 1-7.
Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 1044—Deposition of Dr. Reynaud Serrette, Dec. 22, 2020, 116 pages.
Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Petitioner's Sur-Reply to Patent Owner's Reply to Petitioner's Opposition to Patent Owner's Revised Contingent Motion to Amend, Dec. 31, 2020, 17 pages.
Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 2058—Patent Owner's Notice of Submission of Demonstrative Exhibits for Jan. 14, 2021 Oral Hearing, Jan. 11, 2021, 83 pages.
Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 1045—Petitioner's Demonstratives for Oral Argument, Jan. 14, 2021, 77 pages.
Patent Owner's Response to the Petition for Post Grant Review filed in Case No. PGR2019-00063 on Jun. 4, 2020, 115 pages.
Patent Owner's Contingent Motion to Amend Under 37 C.F.R. Section 42.221 filed in Case No. PGR2019-00063 on Jun. 4, 2020, 41 pages.
Videoconference Deposition of W. Andrew Fennell filed as Exhibit 2043 in Case No. PGR2019-00063 on Jun. 4, 2020, 61 pages.
Third Supplemental Declaration of Dr. Reynaud Serrette filed as Exhibit 2044 in Case No. PGR2019-00063 on Jun. 4, 2020, 44 pages.
International Code Council, 2012 International Building Code, 2011, filed as Exhibit 2045 in Case No. PGR2019-00063 on Jun. 4, 2020, 6 pages.
Buchanan, A. H., Structural Design for Fire Safety, 2001, filed as Exhibit 2046 in Case No. PGR2019-00063 on Jun. 4, 2020, 99 pages.
ASTIM International, Standard Test Methods for Fire Tests of Building Construction and Materials, E119-19, filed as Exhibit 2047 in Case No. PGR2019-00063 on Jun. 4, 2020, 37 pages.

(56) **References Cited**

OTHER PUBLICATIONS

American Wood Council, Calculating the Fire Resistance of Exposed Wood Members, Technical Report 10, American Forest & Paper Association, filed as Exhibit 2048 in Case No. PGR2019-00063 on Jun. 4, 2020, 55 pages.

New Oxford American Dictionary, Second Edition, Definition of "through," filed as Exhibit 2049 in Case No. PGR2019-00063 on Jun. 4, 2020, 2 pages.

McEntee, P., "What You Should Know About the New DGH Fire Wall Hanger Options," Feb. 2018, filed as Exhibit 2050 in Case No. PGR2019-00063 on Jun. 4, 2020, 3 pages.

Memorandum of Points and Authorities in Opposition to Motion for Preliminary Injunction filed as Exhibit 2051 in Case No. PGR2019-00063 on Jun. 4, 2020, 31 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Preliminary Guidance Patent Owner's Motion to Amend, Sep. 21, 2020, 12 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Patent Owner's Sur-Reply, Oct. 8, 2020, 37 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Revised Motion to Amend, Oct. 8, 2020, 43 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Petitioner Simpson Strong-Tie Company Inc.'s Opposition to Patent Owner's Revised Contingent Motion to Amend, Nov. 19, 2020, 31 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Patent Owner's Reply in Support of Its Revised Motion to Amend, Dec. 10, 2020, 21 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 1042—Declaration of W. Andrew Fennell in Support of Petitioner's Reply and Opposition to Patent Owner's Revised Contingent Motion to Amend, Nov. 19, 2020, 31 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 1043—Blank Rrendering of Tsukamoto Reference, 1 page.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 2054—Sheet Metal Stamping 101 Parts I-V, 39 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 2055—Declaration of Dr. Serrette in Support of the Revised Contingent Motion to Amend, Oct. 7, 2020, 12 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Exhibit 2056—ANSI/AISC 360-10 Specification for Structural Steel Buildings, Jun. 22, 2010, 35 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Declaration of Dr. Reynaud Serrette in Support of the Reply to the Opposition to the Revised Contingent Motion to Amend, Dec. 10, 2020, 57 pages.

Simpson Strong-Tie Company Inc. v. *Columbia Insurance Company* Case PGR2019-00063, Final Written Decision, Mar. 1, 2021, 143 pages.

* cited by examiner

FIG. 1



10
74
74
34
74
14
12
74
26
30
50
20
14
28
18
22
20
18
16
22
26
32
22
12
16
34

FIG. 2



74
76
42
26
40
76
66
68
76
48
60
74
68
48
66
46
46
54
38
54
54
52
54
44
54
54

FIG. 2A




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7



26
76
76
76
76
74
74
66
60
60
66
68
68
48
48
46
52
46
44

FIG. 8



26
44
46
46
48
60
60
48
68
68
66
66
74
74
76
76
76
76

FIG. 9




FIG. 10




34
78
74
78
30
FIG. 10A
48
74
78
78
48
74
46
48
46
52
48
28
54
48
46
44
46
52
46
54
26
44
32
34

FIG. 10A







FIG. 11

FIG. 12


74
78
74
34
30
78
78
74
74
48
46
52
48
28
26
12
46
14
26
20
56
18
22
44
56
34
16




FIG. 13

FIG. 13A




FIG. 14




FIG. 14A

FIG. 14A




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20





FIG. 21






FIG. 22




FIG. 23

FIG. 24




FIG. 25



174
178
178
30
174
174
178
178
174
14
166
22
126
50
28
20
126
166
18
14
156
20
18
156
156
32
22
156
22
12
16
34
16
12

FIG. 26



126
174
176
168
140
176
160
142
148
176
176
160b
174
168
146a
162
166
164
154
146b
138
154
154
154
152
154
144
154

FIG. 27



126
174
176
160a
160b
168
176
176
176
174
166
148
166
146
162
146
154
154
154
144

FIG. 28




FIG. 29




FIG. 30





FIG. 31





126
174
176
176
176
176
176
166
168
160b
146b
160a
168
174
166
152
148
144
146a

FIG. 32



176
174
176
166
168
146
160b
176
176
176
160a
168
166
174
176
144
148
146
126

FIG. 33

FIG. 34




FIG. 35
34
142
30
174
148
166
178
174
146
178
146
166
50
28
126
152
148
160
126
162
144
146
146
152
34
144
34

FIG. 35





34
34
34
34
174
178
160
146
152
178
160
174
148
146
30
174
178
160
146
152
178
160
174
148
146

FIG. 36

FIG. 37





FIG. 38






12
146
156
160
178
178
174
160
148
126
30
12
174
146
156
160
178
178
174
160
148
126
34
34

FIG. 39

FIG. 40



HANGER FOR FIRE SEPARATION WALL

CROSS-REFERENCE TO RELATED APPLICATION

This application is a continuation of U.S. application Ser. No. 16/225,517, filed Dec. 19, 2018, now U.S. Pat. No. 10,316,510, which is a continuation of U.S. application Ser. No. 15/675,409, filed Aug. 11, 2017, now U.S. Pat. No. 10,184,242, which is a continuation of U.S. application Ser. No. 14/555,049, filed Nov. 26, 2014, now U.S. Pat. No. 10,024,049, which claims priority to U.S. Provisional Application No. 61/922,531, filed Dec. 31, 2013, the entirety of which are incorporated herein by reference.

FIELD OF THE INVENTION

The present invention generally relates to connections for structures, and more specifically, a truss hanger for connecting a truss to a wall including fire retardant sheathing.

BACKGROUND

The use of fire separation walls in structures, such as in multifamily housing, is commonplace. Often, fire separation is required to be continuous along the walls between adjoining units to prevent fire from spreading between the adjoining units in a multifamily structure. For some types of construction, the building codes also require exterior walls to be fire rated. Typically, gypsum board is used as a fire retardant sheathing along these walls. Floor trusses or joists are attached to or hung from the walls including the gypsum board, but cannot be hung from the gypsum board itself. The trusses or joists must therefore be attached to the wall framing. A cutout for the entire cross section of the truss leaves a large discontinuity in the fire retardant sheathing. However, building codes require that the fire separation wall maintain a certain fire resistant rating. Thus, the integrity of the fire retardant sheathing should be maintained and interruptions of the sheathing kept to a minimum.

SUMMARY

In one aspect of the present invention, a hanger for connecting a structural component to a wall having sheathing mounted thereon includes a channel-shaped portion configured to receive the structural component. The channel shaped portion includes a bottom wall, side walls extending from opposite edges of the bottom wall and a back wall. The bottom wall, side walls and back wall are sized and arranged to receive an end of the structural component for supporting the end of the structural component. A connection portion includes a top flange extending away from the back wall of the channel-shaped portion in a direction opposite to the bottom wall of the channel-shaped portion. The top flange is configured for attachment to a top surface of a top plate of the wall. The connection portion further includes a back flange extending from an edge of the top flange in a direction toward the bottom wall of the channel-shaped portion. The back flange of the connection portion faces the back wall of the channel-shaped portion and the back flange and back wall define a space sized to receive the sheathing between the back flange and the back wall. An extension portion extends from the channel-shaped portion to the connection portion and interconnects the channel-shaped portion and the connection portion. The extension portion separates the back wall of the channel-shaped portion from the back flange of the connection portion to define the space sized to receive the sheathing.

In another aspect pf the present invention a hanger for connecting a structural component to a wall adapted to have sheathing mounted thereon generally comprises a channel-shaped portion configured to receive the structural component. An extension portion extends from the channel-shaped portion and is configured to extend through the sheathing to engage the wall at a first location. The extension portion includes extension flanges extending from the channel-shaped portion forming a bend between each extension flange and the channel-shaped portion. Each of the extension flanges is configured to extend through the sheathing. A connection portion is fixed in position relative to the channel-shaped portion such that that channel-shaped portion does not rotate relative to the connection portion. The connection portion is configured for attachment to the wall at a second location spaced from the first location. The extension flanges define planar surfaces disposed in opposed face-to-face relation between the connection portion and the channel-shaped portion.

In another aspect of the present invention, a truss hanger for connecting a truss to a wall adapted to have fire resistant sheathing mounted thereon generally comprises a channel-shaped portion configured to receive the truss. The channel-shaped portion includes a base sized and shaped for receiving a truss chord of the truss thereon, side panels extending upward from the base, and a back panel. The back panel extends orthogonally from one of the side panels. An extension portion extends from the channel-shaped portion and is configured to extend through the fire resistant sheathing. The extension portion includes extension flanges. Each of the extension flanges extends away from the base of the channel-shaped portion. A connection portion includes a top flange extending away from the back panel of the channel-shaped portion in a direction opposite to the base of the channel-shaped portion. The top flange is configured for attachment to a top surface of a top plate of the wall. The connection portion further includes a back flange extending from an edge of the top flange in a direction toward the base of the channel-shaped portion.

A hanger for connecting a structural component to a wall having sheathing mounted thereon generally comprises a channel-shaped portion configured to receive the structural component. An extension portion is configured to be disposed at least partially in the sheathing. A connection portion is configured for attachment to the wall.

Other objects and features will be in part apparent and in part pointed out hereinafter.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. **1** is a fragmentary perspective of adjacent floor trusses connected to a wall having fire retardant sheathing by truss hangers that extend through the sheathing;

FIG. **2** is a perspective of a truss hanger according to a first embodiment of the present invention;

FIG. **2**A is a rear perspective of the truss hanger;

FIG. **3** is a front elevation thereof;

FIG. **4** is a right side elevation thereof;

FIG. **5** is a left side elevation thereof;

FIG. **6** is a rear elevation thereof;

FIG. **7** is a top plan thereof;

FIG. **8** is a bottom plan thereof;

FIG. **9** is a perspective of a wall having fire retardant sheathing with a slot cut in the sheathing to receive the truss hanger;

FIG. **10** is the perspective of FIG. **9**, but showing two of the truss hangers mounted thereon;

FIG. **10**A is an enlarged fragmentary perspective of FIG. **10**;

FIG. **11** is a top plan of FIG. **10**, illustrating the truss hanger extending through the fire retardant sheathing;

FIG. **12** is a perspective similar to FIG. **10**, but showing a floor truss positioned for mounting in the truss hanger;

FIG. **13** is a side elevation of FIG. **12**;

FIG. **13**A is an enlarged fragmentary perspective of FIG. **13** with a portion of the fire retardant sheathing broken away;

FIG. **14** is the perspective of FIG. **10**, but showing floor trusses mounted in the truss hangers;

FIG. **14**A is an enlarged fragmentary perspective of FIG. **14**;

FIG. **15** is a top view of a stamped metal blank for forming a truss hanger according to the present invention;

FIG. **16** is a perspective of a slot template for use in cutting the slot in the sheathing to receive the truss hanger;

FIG. **17** is a rear perspective of the slot template;

FIG. **18** is a front elevation thereof;

FIG. **19** is a right side elevation thereof;

FIG. **20** is a left side elevation thereof;

FIG. **21** is a rear elevation thereof;

FIG. **22** is a top plan thereof;

FIG. **23** is a bottom plan thereof;

FIG. **24** is a front view of a stamped metal blank for forming the slot template;

FIG. **25** is a fragmentary perspective of adjacent floor trusses connected at an angle to a wall having fire retardant sheathing by truss hangers of a second embodiment that extend through the sheathing;

FIG. **26** is a perspective of one of the truss hangers of FIG. **25**;

FIG. **27** is a rear perspective thereof;

FIG. **28** is a front elevation thereof;

FIG. **29** is a right side elevation thereof;

FIG. **30** is a left side elevation thereof;

FIG. **31** is a rear elevation thereof;

FIG. **32** is a top plan thereof;

FIG. **33** is a bottom plan thereof;

FIG. **34** is a perspective of a wall and the two truss hangers mounted thereon with parts broken away;

FIG. **35** is an enlarged fragmentary perspective of FIG. **34**;

FIG. **36** is a top plan of FIG. **34**, illustrating the truss hangers extending through the fire retardant sheathing;

FIG. **37** is a side elevation of FIG. **34**;

FIG. **38** is an enlarged fragment of FIG. **37**;

FIG. **39** is a top plan similar to FIG. **36**, but showing a floor truss mounted in each truss hanger; and

FIG. **40** is a front view of a stamped metal blank for forming a truss hanger according to the present invention.

Corresponding reference characters indicate corresponding parts throughout the drawings.

DETAILED DESCRIPTION

Referring to FIG. **1**, a first embodiment of a connection system for a fire separation wall is shown generally at **10**. Floor trusses generally indicated at **12** each include truss members (broadly, "wooden structural members") including a top chord **14**, a bottom chord **16**, and web members **18** joining the top and bottom chords. Each floor truss also includes end members **20** at each end joining the top and bottom chords **14**, **16** (only one end of each truss is shown). The truss members can be joined by nail plates **22** or by any other suitable fastening structure. The number and orientations of the web members **18** and chords **14**, **16** may vary from the illustrated embodiment without departing from the scope of the invention, as a truss hanger **26** according to the present invention is readily applicable to other truss configurations (e.g. a roof truss). Moreover, the hanger **26** may be used to connect structural components other than trusses to a wall or other part of a structure. The hanger can be used to support other wood framing members such as solid sawn or structural composite lumber.

As seen in FIG. **1**, a wall **28** includes a top member or plate **30** and support members or studs **32** (only one stud may be seen in FIG. **1**). As illustrated, the top plate **30** is formed by two 2×4's in stacked relation. Fire retardant sheathing **34** is mounted on both sides of the wall **28**, as illustrated. In one embodiment, the fire retardant sheathing is gypsum board, such as two layers of ⅝" gypsum board mounted on each side of the wall **28** as illustrated, although other configurations of fire retardant sheathing are within the scope of the present invention. Other wall configurations, including different wall constructions and materials, are within the scope of the present invention. For example, the truss hangers **26** can be used with any wall assembly or fire-rated wall assembly, such as a 2-hour fire-resistive wall assembly. The floor trusses **12** are mounted on the wall **28** adjacent the fire retardant sheathing **34** by the truss hangers **26**. The truss hangers **26** extend through a narrow slot in the fire retardant sheathing **34** to maintain the integrity and fire retardant characteristics of the fire separation wall.

Referring to FIGS. **2-8**, the truss hanger **26** includes a channel-shaped portion **38**, an extension portion **40**, and a connection portion **42**. The channel-shaped portion **38** is configured to receive the floor truss **12**. The channel-shaped portion **38** includes a seat or base **44** and a pair of side panels **46** extending upward from the base. When installed, the base **44** is generally horizontal, and the side panels **46** extend generally vertical from the base. A back panel **48** extends from each of the side panels **46**. Each back panel **48** is generally perpendicular to both the side panels **46** and the base **44**. When installed, each back panel **48** extends generally parallel to an interior face **50** of the fire retardant sheathing **34**. The base **44**, side panels **46**, and back panels **48** form a channel **52** configured to receive the floor truss **12**.

As seen in FIGS. **1** and **12-14**A, the floor truss **12** is received in the channel **52** to attach the floor truss to the wall **28**. The bottom chord **16** of the floor truss **12** engages and rests upon (i.e., is supported by) the base **44**. The end member **20** of the floor truss **12** is positioned against the back panels **48** between the side panels **46**. The truss hanger **26** includes fastening structure for attaching the floor truss **12** to the truss hanger. Fastening structure can be of any type known in the art for attaching a connector to a wooden structural member, such as nailing teeth (not shown) struck from the material of the hanger. In the illustrated embodiment, the fastening structure comprises a hole to allow for insertion of a fastening member. More specifically, in one embodiment the fastening structure comprises nail holes **54** in the side panels **46** of the truss hanger **26**, and the fastening member comprises a nail **56** (see FIG. **12**). In the illustrated embodiment, nail holes **54** are positioned on each of the side panels **46** so that nails **56** can be inserted into both the bottom chord **16** and the end member **20** of the floor truss **12** to attach the hanger **26** to the floor truss **12**.

Referring again to FIGS. **2-8**, the extension portion **40** includes two extension flanges **60** configured to extend through the fire retardant sheathing **34**. Each flange **60** extends from one of the back panels **48**. The flanges **60** are positioned in opposed, face-to-face relation, and preferably engage each other along a juncture. Each flange **60** extends generally perpendicular from the corresponding back panel **48** and generally parallel to the side panels **46**. At a bottom edge, each flange **60** includes a driving point **62**. Each of the driving points **62** is generally triangular and includes a pointed tip **64**. As seen in FIGS. **3** and **6**, the tips **64** of the driving points **62** are vertically offset from each other. As illustrated, the tip **64***a* of one flange **60***a* extends vertically below the tip **64***b* of the other flange **60***b*. In one embodiment, the tips **64** are vertically offset from each other about ⅛", although other configurations are within the scope of the present invention, such as tips that are aligned or tips that are offset a smaller or larger amount.

A back flange **66** extends from each of the extension flanges **60**. Each back flange **66** extends generally perpendicular from the extension flange **60** and is oriented generally parallel to the back panels **48**. Referring to FIG. **13**A, the back flanges **66** engage the wall **28** at a first location L_1, which in the illustrated embodiment is a vertical face of the top plate **30** of the wall. The back panels **48**, extension flanges **60**, and back flanges **66** form a pair of sheathing channels **68**. Each sheathing channel **68** is configured to receive a portion of the fire retardant sheathing **34** to secure the sheathing between the hanger **26** and the wall **28**. As seen in FIG. **7**, the sheathing channels **68** extend generally perpendicular to the truss-receiving channel **52**.

As seen in FIGS. **10**A and **11**, the extension flanges **60** extend through a slot **72** in the fire retardant sheathing **34**. Preferably, the slot has an area less than or equal to 6 square inches, and the gap between the extension flanges **60** and the edge of the slot **72** is less than or equal to ⅛". The driving points **62** extend down into the sheathing **34** to further secure the sheathing between the hanger **26** and the wall **28**. A portion of the fire retardant sheathing **34** extends into each sheathing channel **68** and is secured between the back panels **48** and the back flanges **66**.

In one embodiment, the slot **72** in the fire retardant sheathing **34** can be made using a slot template **82** (FIGS. **16-24**). The slot template **82** includes a vertical panel **84** having a rear face **86** configured to engage the interior face **50** of the fire retardant sheathing **34** and a horizontal panel **88** having a bottom face **90** configured to engage a top face of the sheathing. The horizontal panel **88** extends generally perpendicular from the vertical panel **84**. The slot template **82** is configured to be quickly fixed in position on the sheathing **34** for use in cutting the slot **72** to receive the truss hanger **26**. Portions of the slot template **82** are configured to be pressed into the sheathing **34** to locate the template on the sheathing and retain the template in position for cutting the slot **72**. In the illustrated embodiment, the horizontal panel includes prongs **92** that are bent downward for insertion into the top face of the sheathing **34**. Bottom corners **94** of the vertical panel **84** are bent rearward for insertion into the interior face **50** of the sheathing **34**. The prongs **92** and the corners **94** are inserted into the sheathing **34** to retain the template **82** in position for cutting the slot **72**. In addition, the vertical panel **84** optionally includes dimples **96** extending toward the rear face **86** of the vertical panel **84**. The dimples **96** ensure the vertical panel **84** remains slightly spaced from the interior face **50** of the sheathing **34** so the template **82** can be easily removed from the sheathing after the slot **72** is cut.

The template **82** includes a guide slot **98** to guide a cutting tool in cutting the slot **72** in the sheathing **34**. The guide slot **98** extends from a top edge of the vertical panel **84** to a location spaced from a bottom edge of the vertical panel. As illustrated, the guide slot **98** includes a wide, rectangular portion **98***a* in the horizontal panel **88** to ease insertion of a cutting tool into the guide slot. A converging portion **98***b* of the slot **98** in the vertical panel **84** transitions from the wide portion **98***a* to a narrow lower portion **98***c* of the slot. This facilitates entry of the cutting tool into the narrow portion **98***c*. The narrow portion **98***c* of the guide slot **98** is dimensioned to facilitate cutting the slot **72** in the sheathing **34** to a size configured to receive the extension flanges **60** of the truss hanger **26**.

As seen in FIG. **24**, the template **82** described above can be formed as one piece from a metal blank **100** that is stamped from a sheet metal roll and bent into shape. In one embodiment, the template **82** is stamped from 16 gauge steel, although other thicknesses (e.g., 12-18 gauge) and other suitable materials are within the scope of the present invention.

In use, the template **82** is placed on the sheathing **34** in a selected location for a slot **72**. The template can be used to cut the slot **72** in the sheathing **34** either before or after the sheathing is mounted on the wall **28**. The prongs **92** and corners **94** are inserted into the sheathing **34** by tapping with a hand or striking with a hammer or other blunt instrument. Once the template **82** is secured in position on the sheathing **34**, a cutting tool (e.g., a drywall cutout tool) is inserted into the guide slot **98** to cut a slot **72** in the sheathing at the location of the guide slot. In one embodiment, a drywall cutout tool with a ⅛" or ¼" spiral bit is used to cut the slot **72**, although other cutting tools are within the scope of the present invention. After the slot **72** is cut in the sheathing **34**, the template **82** is removed from the sheathing. The sheathing **34** is then configured to receive the truss hanger **26**.

Referring again to FIGS. **2-8**, the connection portion of the hanger includes a pair of connector tabs **74** extending from the back flanges **66**. Each connector tab **74** extends generally perpendicular from one of the back flanges **66**. The connector tabs **74** are generally horizontal when the hanger **26** is installed. The connector tabs **74** are configured to engage an upper surface of the top plate **30** of the wall **28** at a second location L2 spaced from the first location L_1. The connector tabs **74** can be used to attach the truss hanger **26** to the wall, thereby hanging the floor trusses **12** from the wall. As seen in FIG. **1**, the connector tabs **74** extend over a portion of the top plate **30** of the wall **28**. Each connector tab **74** includes fastening structure, such as nail holes **76**, for insertion of a fastening member, such as nails **78** (see FIGS. **10** and **10**A), to attach the hanger **26** to the wall **28**. In the illustrated embodiment, each connector tab **74** includes three nail holes **76**. Other configurations are within the scope of the present invention, such as a different number of nail holes, or alternate fastening structure such as nailing teeth or other appropriate structure for fastening the hanger to the wall.

The base **44** and back flanges **66** of the truss hanger **26** cooperate to stabilize the truss hanger **26** and protect the fire retardant sheathing **34** under the loads transferred from the truss **12** to the wall **28** by way of the hanger. The channel **52** that receives an end portion of the truss **12** is spaced to the interior of the wall **28** and more particularly to the interior of the second location L2 where the connector tabs **74** are attached to an upper surface of the top plate **30**. The vertically downward load of the truss **12** applied to the base **44** of the truss hanger **26** urges the truss hanger **26** to pivot

so that the base would move toward the wall **28**, which could damage the fire retardant sheathing **34** and pry out the nails **78** connecting the connector tabs **74** to the upper surface of the top plate **30**. However, this motion is resisted by the engagement of the back flanges **66** with the interior vertical face of the top plate **30** at the first location L_1. Thus, there is a force couple between the base **44** of the hanger **26** carrying the vertical load of the truss **12** and the back panels **48** of the hanger (via engagement of the back flanges **66** with the top plate **30**) engaging the end face of the truss. Accordingly, the truss hanger **26** and truss **12** are stable with minimal disruption of the fire retardant sheathing **34**, even though the truss is held at a distance from the wall **28** by the truss hanger.

As seen in FIG. **15**, a truss hanger **26** as described above can be formed as one piece from a metal blank **80** that is stamped from a sheet metal roll and bent into shape. In one embodiment, the truss hanger **26** is stamped from 12-14 gauge steel, although other suitable materials are within the scope of the present invention. The configuration of the truss hanger **26** of the present invention allows a lighter gauge metal to be used.

In use, the truss hanger **26** is positioned in the slot **72** of the fire retardant sheathing **34** mounted on the wall **28**. As seen in FIGS. **9-14**A, one method of using the truss hanger **26** includes cutting the slot **72** in the fire retardant sheathing **34** (either before or after the sheathing is mounted on the wall). In one embodiment, the slot **72** can be cut using the slot template **82** (either before or after the sheathing **34** is mounted to the wall **28**). The slot can be any suitable length, and in one embodiment is about 10 inches long. The truss hanger **26** is then positioned against the fire retardant sheathing **34** so that the extension flanges **60** extend through the slot **72**. In one embodiment, the hanger **26** is slid downward into place so that the extension flanges **60** extend through the slot **72**, the back flanges **66** are positioned adjacent the wall **28**, and the fire retardant sheathing **34** is positioned in the sheathing channels **68** between the back flanges and the back panels **48**. The hanger connector tabs **74** are fastened to the top plate **30** of the wall **28** by any suitable means, such as by inserting nail **78** through the nail holes **76**. Then, a truss member, e.g. truss bottom chord **16**, is positioned in the truss channel **52** of the hanger **26** (see FIG. **1**), thereby securing the floor truss **12** to the wall **28**. The truss hanger **26** is then fastened to the truss **12** by any suitable means, such as by inserting nails **56** through the nail holes **54** in each side panel **46** of the hanger. The hanger **26** is thus secured to both the truss **12** and the wall **28**, with the fire retardant sheathing **34** secured between the hanger and the wall.

In another embodiment, the truss hangers **26** can be installed without pre-forming the slot **72** in the fire retardant sheathing **34**. More particularly, each hanger **26** can be driven into the sheathing **34**. The driving point **62** of the hanger **26** is positioned against a top edge of the fire retardant sheathing. The hanger **26** is then driven downward into the sheathing **34**, led by the pointed tip **64**. The hanger **26** continues to be driven into the gypsum boards until the connector tabs **74** engage the upper surface of the top plate **30**. In this way, the hanger **26** forms the slot in the sheathing **34**.

In still another embodiment, the truss hangers **26** can be installed on the wall **28** before the sheathing **34** is mounted on the wall. This simplifies construction by allowing the building to be completely framed and roofed before requiring the sheathing **34** to be installed. Trade workers (e.g., mechanical, electrical) therefore have complete access to the wall cavity to install components without interference from the sheathing **34**. The truss hanger **26** is positioned against the wall **28** such that the back flanges **66** engage the wall and the connector tabs **74** engage the top plate **30**. The connector tabs **74** are fastened to the top plate **30** of the wall by any suitable means, such as by inserting nails **78** through nail holes **76**. Then, a truss **12** is positioned in the truss channel **52** of the hanger **26**. The truss hanger is fastened to the truss **12** by any suitable means, such as by inserting nails **56** through the nail holes **54** in each side panel **46** of the hanger **26**. The floor truss **12** is thereby secured to the hanger **26** and the wall **28**, and access to the wall cavity remains unhindered by sheathing. Subsequently, the sheathing **34** can be mounted on the wall **28** by moving the sheathing upward into place so that the extension flanges **60** of the hanger **26** extend through the slot **72** of the sheathing and the sheathing is positioned in the sheathing channels **68** between the back flanges **66** and the back panels **48**.

Referring to FIGS. **25-40**, a second embodiment of a truss hanger **126** for use in mounting the floor truss **12** to the wall **28** is illustrated. The truss hanger **126** is similar to the truss hanger **26** described above, with differences as pointed out herein. Where the truss hanger **26** is configured for mounting the floor truss **12** generally orthogonal to the wall **28**, the truss hanger **126** is configured for mounting the floor truss **12** in a skewed position relative to the wall.

Referring to FIGS. **26-33**, the truss hanger **126** includes a channel-shaped portion **138**, an extension portion **140**, and a connection portion **142**. The channel-shaped portion **138** is configured to receive the floor truss **12**. The channel-shaped portion **138** is configured to support the floor truss **12** at a non-orthogonal angle relative to the wall **28**. In this skewed embodiment, the channel-shaped portion **138** is offset from the extension portion **140**. The channel-shaped portion **138** includes a seat or base **144** and a pair of side panels **146** extending upward from the base. When installed, the base **144** is generally horizontal, and the side panels **146** extend generally vertical from the base. A back panel **148** extends from one of the side panels **146***a* toward the opposing side panel **146***b*. The back panel **148** is generally perpendicular to both the side panels **146** and the base **144**. When installed, the back panel **148** extends at a non-orthogonal angle (e.g., about 45°) to the interior face **50** of the fire retardant sheathing **34**. The base **144**, side panels **146**, and back panel **148** form a channel **152** configured to receive the floor truss **12**. Other configurations are within the scope of the present invention. For example, the truss hanger **126** can be configured to support the floor truss **12** at a range of different angles with respect to the wall **28**.

As seen in FIGS. **25** and **39**, the floor truss **12** is received in the channel **152** to attach the floor truss to the wall **28** at a skewed angle. The bottom chord **16** of the floor truss **12** engages and rests upon (i.e., is supported by) the base **144**. The end member **20** of the floor truss **12** is positioned against the back panel **148** between the side panels **146**. The truss hanger **126** includes fastening structure for attaching the floor truss **12** to the truss hanger. Fastening structure can be of any type known in the art for attaching a connector to a wooden structural member, such as nailing teeth (not shown) struck from the material of the hanger. In the illustrated embodiment, the fastening structure comprises a hole to allow for insertion of a fastening member. More specifically, in one embodiment the fastening structure comprises nail holes **154** in the side panels **146** of the truss hanger **126** (see, FIG. **26**), and the fastening member comprises a nail **156** (see, FIG. **25**). In the illustrated embodiment, nail holes **154** are positioned on each of the side panels **146** so that nails

156 can be inserted into both the bottom chord 16 and the end member 20 of the floor truss 12 to attach the hanger 126 to the floor truss.

Referring again to FIGS. 26-33, the extension portion 140 includes two extension flanges 160 configured to extend through the fire retardant sheathing 34. One of the flanges 160*a* extends from the back panel 148. The other flange 160*b* extends from the side panel 146*b*. The flanges 160 are positioned in opposed, face-to-face relation, and preferably engage each other along a juncture. At a bottom edge, each flange 160 includes a driving point 162. Each of the driving points 162 is generally triangular and includes a pointed tip 164. As seen in FIG. 28, the tips 164 of the driving points 162 are vertically offset from each other. As illustrated, the tip 164*a* of one flange 160*a* extends vertically below the tip 164*b* of the other flange 160*b*. In one embodiment, the tips 164 are vertically offset from each other about ⅛", although other configurations are within the scope of the present invention, such as tips that are aligned or tips that are offset a smaller or larger amount.

A back flange 166 extends from the extension flange 160 generally perpendicular from the extension flange. Referring to FIG. 38, the back flange 166 engages the wall 28 at a first location L_{10}, which in the illustrated embodiment is a vertical face of the top plate 30 of the wall behind the fire retardant sheathing 34. The back flange 166 comprises a back flange portion 166*a* bent from the extension flange 160*a* and a back flange portion 166*b* bent from the extension flange 160*b*. The back panel 148, side panel 146*b*, extension flanges 160, and back flange 166 form a pair of sheathing channels 168 (see, FIG. 32). Each sheathing channel 168 is configured to receive a portion of the fire retardant sheathing 34.

As seen in FIGS. 34-36, the extension flanges 160 extend through the slot 72 in the fire retardant sheathing 34. Preferably, the slot has an area less than or equal to 6 square inches, and the gap between the extension flanges 60 and the edge of the slot 72 is less than or equal to ⅛". The driving points 162 extend down into the sheathing 34 to engage the sheathing and further secure the sheathing between the hanger 126 and the wall 28. A portion of the fire retardant sheathing 34 extends into each sheathing channel 168 and is secured against the back flange 166.

Referring again to FIGS. 26-33, the connection portion 142 of the hanger 126 includes a pair of connector tabs 174 extending from the back flange portions 166*a*, 166*b*. Each connector tab 174 extends generally perpendicular from a respective one of the back flanges 166*a*, 166*b*. The connector tabs 174 are generally horizontal when the hanger 126 is installed. The connector tabs 174 are configured to overlie and engage an upper surface of the top plate 30 of the wall 28 at a second location L_{20} spaced from the first location L_{10} (see, FIGS. 37 and 38). The connector tabs 174 can be used to attach the truss hanger 126 to the wall 28, thereby hanging the floor trusses 12 from the wall. As seen in FIG. 25, the connector tabs 174 extend over a portion of the top plate 30 of the wall 28. Each connector tab 174 includes fastening structure, such as nail holes 176, for insertion of a fastening member, such as nails 178 (see FIGS. 34 and 35), to attach the hanger 126 to the wall 28. In the illustrated embodiment, each connector tab 174 includes three nail holes 176. Other configurations are within the scope of the present invention, such as a different number of nail holes, or alternate fastening structure such as nailing teeth or other appropriate structure for fastening the hanger to the wall.

The base 144 and back flanges 166 cooperate to stabilize the truss hanger 126 and protect the fire retardant sheathing 34 from exposure to the loads transferred from the truss 12 to the wall 28 by way of the truss hanger 126. The channel 152 that receives an end portion of the truss 12 is spaced to the interior of the wall 28 and more particularly to the interior of the second location L_{20} where the connector tabs 174 are attached to an upper surface of the top plate 30 (see FIG. 38). The vertically downward load of the truss 126 applied to the base 144 of the truss hanger 126 urges the truss hanger to pivot so that the base would move toward the wall 28, which could damage the fire retardant sheathing 34 and pry out the nails 178 connecting the connector tabs 174 to the upper surface of the top plate 30. However, this motion is resisted by the engagement of the back flanges 166 with the interior vertical face of the top plate 30 at the first location L_{10}. Thus, there is a force couple between the base 144 and back panel 148 of the hanger 126 (via engagement of the back flanges 166 with the top plate 30) engaging the end fact of the truss. Accordingly, the truss hanger 126 and truss 12 are stable with minimal disruption of the fire retardant sheathing 34, even though the truss is held at a distance from the wall 28.

As seen in FIG. 40, a truss hanger 126 as described above can be formed as one piece from a metal blank 180 that is stamped from a sheet metal roll and bent into shape. Parts of the blank 180 are labelled with reference numerals corresponding to the various parts of the formed truss hanger 126. In one embodiment, the truss hanger 126 is stamped from 12-14 gauge steel, although other suitable materials are within the scope of the present invention. The configuration of the truss hanger 126 of the present invention allows a lighter gauge metal to be used.

The truss hanger 126 is used as described above with reference to the truss hanger 26. In use, the truss hanger 126 is positioned in the slot 72 of the fire retardant sheathing 34 mounted to the wall 28. One method of using the truss hanger 126 includes cutting the slot 72 in the fire retardant sheathing (either before or after the sheathing is mounted on the wall). In one embodiment, the slot 72 can be cut using the slot template 82 (either before or after the sheathing 34 is mounted to the wall 28). The slot 72 can be any suitable length, and in one embodiment is about 10 inches long. The truss hanger 126 is then positioned against the fire retardant sheathing 34 so that the extension flanges 160 extend through the slot 72. In one embodiment, the hanger 126 is slid downward into place so that the extension flanges 160 extend through the slot 72, the driving point 162 engages the fire retardant sheathing 34, the back flange 166 is positioned adjacent the wall 28, and the fire retardant sheathing is positioned in the sheathing channels 168 of the hanger. The hanger connector tabs 174 are fastened to the top plate 30 of the wall 28 by driving nails 178 through the nail holes 176 into the top plate 30. Then, a truss member, e.g. truss bottom chord 16 is positioned in the truss channel 152 of the hanger 126. Nails 156 are driven through holes 154 in the side panels 146 to secure the floor truss 12 to the wall 28. The hanger 126 is thus secured to both the truss 12 and the wall 28, with the fire retardant sheathing 34 between the hanger and the wall.

In another embodiment, the truss hangers 126 can be installed without pre-forming the slot 72 in the fire retardant sheathing 34. More particularly, each hanger 126 can be driven into the sheathing 34. The pointed tip 164 of the driving point 162 of the hanger 126 is positioned against a top edge of the fire retardant sheathing 34. The hanger 126 is then driven downward into the sheathing 34, led by the pointed tip 164. The hanger 126 continues to be driven into the gypsum boards until the connector tabs 174 engage the

upper surface of the top plate **30**. In this way, the hanger **126** forms the slot in the sheathing **34**.

In another embodiment, the truss hangers **126** can be installed on the wall **28** before the sheathing **34** is mounted on the wall. This simplifies construction by allowing the building to be completely framed and roofed before requiring the sheathing **34** to be installed. Trade workers (e.g., mechanical, electrical) therefore have complete access to the wall cavity to install components without interference from the sheathing **34**. The truss hanger **126** is positioned against the wall **28** such that the back flange **166** engages the wall and the connector tabs **174** engage the top plate **30**. The connector tabs **174** are fastened to the top plate **30** of the wall by any suitable means, such as by inserting nails **178** through nail holes **176**. Then, a truss **12** is positioned in the truss channel **152** of the hanger **126**. The truss hanger **126** is fastened to the truss **12** by any suitable means, such as by inserting nails **156** through the nail holes **154** in each side panel **146** of the hanger. The floor truss **12** is thereby secured to the hanger **126** and the wall **28**, and access to the wall cavity remains unhindered by sheathing. Subsequently, the sheathing **34** can be mounted on the wall **28** by moving the sheathing upward into place so that the extension flanges **160** of the hanger **126** extend through the slot **72** of the sheathing and the sheathing is positioned in the sheathing channels **168** of the hanger.

The truss hanger **26**, **126** permits a floor truss **12** to be secured to a wall **28** through fire retardant sheathing **34** with minimal interruption to the sheathing. Installation of the truss hanger minimally disrupts the continuity of the sheathing and therefore does not reduce the fire resistive rating of a fire rated assembly. The extension flanges **60**, **160** extend through the fire retardant sheathing **34** so that the sheathing is interrupted only by the slot **72** required to receive the flanges. The back flanges **66**, **166** engage the wall **28** behind the sheathing **34** to stabilize the hanger **26**, **126** and protect the sheathing. The truss hanger **26**, **126** can be mounted on a wall already having sheathing mounted thereon, or can be mounted on a wall before the sheathing (i.e., the sheathing does not have to be mounted on the wall before the truss hanger), thereby simplifying construction. The truss hanger **26**, **126** can be formed from a metal blank **80**, **180**, which reduces the number of parts required to hang the floor truss **12** and simplifies the manufacturing process.

In an independent test performed by an outside firm, the truss hanger was installed as part of a wall assembly including 2×6 wood studs, 24" on center, with two layers of ⅝" Type X gypsum attached to each side. The gypsum board included a slot to accommodate the hanger. The hanger was fixed to the top plate of the wall with six **10***d* common nails in the connector tabs. The cavities in the wall were filled with mineral wool insulation. The testing was performed per ASTM E814 which subjected the specimen to the time/temperature curve prescribed in ASTM E119 for a period of two hours, followed by a hose stream test. As a result of this testing, the outside firm reported that when installed on one side of a maximum 2 hour fire-rated wall assembly, the penetration of the truss hanger through the gypsum board will not reduce the fire resistive rating of the 2 hour fire resistive assembly.

Having described the invention in detail, it will be apparent that modifications and variations are possible without departing from the scope of the invention defined in the appended claims.

When introducing elements of the present invention or the preferred embodiments(s) thereof, the articles "a", "an", "the" and "said" are intended to mean that there are one or more of the elements. The terms "comprising", "including" and "having" are intended to be inclusive and mean that there may be additional elements other than the listed elements.

In view of the above, it will be seen that the several objects of the invention are achieved and other advantageous results attained.

As various changes could be made in the above products without departing from the scope of the invention, it is intended that all matter contained in the above description and shown in the accompanying drawings shall be interpreted as illustrative and not in a limiting sense.

What is claimed is:

1. A hanger for connecting a structural component to a wall adapted to have sheathing mounted thereon, the hanger comprising:

a channel-shaped portion configured to receive the structural component, the channel-shaped portion including a base configured to receive an end portion of the structural component thereon to support the structural component, the base having an upper surface configured to engage the structural component, the upper surface lying in a base plane;

a connection portion configured for attachment to the wall, the connection portion including a back flange having an upper edge, the back flange extending from the upper edge in a direction generally toward the base plane, the connection portion and channel-shaped portion being in a fixed, spaced apart relation relative to one another; and

an extension portion including first and second extension flanges extending from the channel-shaped portion to the connection portion, each extension flange being configured to extend through the sheathing, each extension flange lying in an extension flange plane, the extension flange planes being generally perpendicular to the base plane, the back flange and the channel-shaped portion defining a sheath space sized and shaped to receive the sheathing therein so that the channel-shaped portion is located on one side of the sheathing and the back flange is located on an opposite side of the sheathing when the hanger and sheathing are installed on the wall.

2. The hanger as set forth in claim **1**, wherein each of the first and second extension flanges are planar.

3. The hanger as set forth in claim **2**, wherein each of the first and second extension flanges include an edge, the first and second extension flanges arranged to extend edgewise through the sheathing.

4. The hanger as set forth in claim **2**, wherein the first and second extension flanges each include an upper free edge.

5. The hanger as set forth in claim **1**, wherein the first and second extension flanges are configured to extend through the sheathing while maintaining a 2 hour fire resistance rating of the sheathing.

6. The hanger as set forth in claim **1**, wherein a portion of the channel-shaped portion is in an opposed, spaced apart relation with the back flange.

7. The hanger as set forth in claim **1**, wherein the back flange has a front surface lying in a back flange plane and wherein the hanger further comprises a stop configured to engage the end of the structural component to space the end of the structural component from the back flange plane by a distance sized large enough to permit the sheathing to be received between the end of the structural component and the back flange plane.

8. The hanger as set forth in claim 7, wherein the stop is configured to space the end of the structural component from the back plane by a distance sized large enough to permit two layers of 5/8 inch thick sheathing to be received between the end of the structural component and the back flange plane.

9. The hanger as set forth in claim 7, wherein the stop comprises back panels extending toward each other.

10. The hanger as set forth in claim 1, wherein the first and second extension flanges are parallel to one another.

11. The hanger as set forth in claim 1, further comprising connections between the first and second extension flanges and the channel-shaped portion, locations of the connections being spaced apart from a lower end of the channel-shaped portion where the base of the channel-shaped is located.

12. The hanger as set forth in claim 1, wherein the back flange has a front surface lying in a back flange plane and the first and second extension flanges space the channel-shaped portion from the back flange plane by a distance sized large enough to permit two layers of 5/8 inch thick sheathing to be received between the channel-shaped portion and the back flange plane.

13. The hanger as set forth in claim 1, wherein the connection portion includes a top flange configured to attach to a top plate of the wall, the top flange extending from the back flange.

14. The hanger as set forth in claim 13, wherein the top flange is connected to the channel-shaped portion by way of the back flange and the extension portion.

15. The hanger as set forth in claim 1, wherein the wall is a frame wall having a top plate having a vertical dimension, and wherein the back flange has a vertical dimension greater than the vertical dimension of the top plate.

16. A hanger to connect a joist to a frame wall adapted to have sheathing mounted thereon so that an interior side of the sheathing faces the frame wall and an exterior side of the sheathing faces away from the frame wall, the frame wall including a wooden upper plate and wooden studs extending down from the upper plate, the hanger comprising:

a channel-shaped portion configured to receive the structural component, the channel-shaped portion including a base configured to receive an end portion of the structural component thereon to support the structural component and side panels extending upward from the base;

a connection portion configured for attachment to the frame wall, the connection portion including a back flange configured for engaging a vertical face of the upper plate of the frame wall, the connection portion and channel-shaped portion being in a fixed, spaced apart relation relative to one another; and

first and second extension flanges interconnecting the connection portion and the channel-shaped portion and holding the connection portion and channel-shaped portion in spaced apart relation to each other, the first and second extension flanges being configured to extend through an opening in the sheathing to the wall frame, the back flange, the first and second extension flanges and the channel-shaped portion defining a sheathing space sized and shaped to receive the sheathing therein so that the channel-shaped portion is located on one side of the sheathing and the back flange is located on an opposite side of the sheathing, the back flange being sized and arranged to at least partially block the opening in the sheathing to reduce the exposure of the wooden top plate and wooden studs to an exterior through the opening in the sheathing.

17. The hanger as set forth in claim 16, wherein the first and second extension flanges are configured to extend through the sheathing while maintaining a 2 hour fire resistance rating of the sheathing.

18. The hanger as set forth in claim 16, wherein the connection portion includes a top flange configured to overlie an upper surface of the top plate, the back flange extending down from the top flange.

19. The hanger as set forth in claim 18, wherein the top flange and back flange are connected to each other by a bend.

20. The hanger as set for thin claim 19, wherein the side panels have rearward edges lying in a rear edge plane, each of the first and second extension flanges lying in an extension flange plane, the extension flange planes being generally perpendicular to the rear edge plane.

21. The hanger as set forth in claim 16, wherein the back flange has a front surface lying in a back flange plane and wherein the hanger further comprises a stop configured to engage the end of the structural component to space the end of the structural component from the back flange plane by a distance sized large enough to permit the sheathing to be received between the end of the structural component and the back flange plane.

22. The hanger as set forth in claim 21, wherein the stop is configured to space the end of the structural component from the back plane by a distance sized large enough to permit two layers of 5/8 inch thick sheathing to be received between the end of the structural component and the back flange plane.

23. The hanger as set forth in claim 22, wherein the stop comprises back panels extending toward each other.

* * * * *

UNITED STATES PATENT AND TRADEMARK OFFICE

CERTIFICATE OF CORRECTION

PATENT NO. : 11,021,867 B2
APPLICATION NO. : 16/433799
DATED : June 1, 2021
INVENTOR(S) : Brekke

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

In the Claims

Column 12, Claim 5, Line 56:
Add --a wall assembly including the wall and-- after the phrase 'rating of';

Column 13, Claim 11, Line 15:
Add --portion-- after the term 'channel-shaped';

Column 13, Claim 16, Line 34:
Replace "joist" with --structural component--;

Column 14, Claim 17, Line 22:
Add --a wall assembly including the frame wall and-- after the phrase 'rating of'.

Signed and Sealed this
Twenty-eighth Day of December, 2021



Drew Hirshfeld
Performing the Functions and Duties of the
Under Secretary of Commerce for Intellectual Property and
Director of the United States Patent and Trademark Office