



US011857737B2

(12) **United States Patent**
Franklin et al.

(10) **Patent No.:** **US 11,857,737 B2**
(45) **Date of Patent:** **Jan. 2, 2024**

(54) **SYSTEM AND METHOD FOR
LOW-PROFILE OCCLUSION BALLOON
CATHETER**

(71) Applicant: **Prytime Medical Devices, Inc.**,
Boerne, TX (US)

(72) Inventors: **Curtis J. Franklin**, Lakewood, CO
(US); **David Spencer**, Boerne, TX
(US); **Todd J. Krummenacher**,
Lakewood, CO (US)

(73) Assignee: **Prytime Medical Devices, Inc.**,
Boerne, TX (US)

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 112 days.

(21) Appl. No.: **17/563,669**

(22) Filed: **Dec. 28, 2021**

(65) **Prior Publication Data**

US 2022/0118221 A1 Apr. 21, 2022

Related U.S. Application Data

(63) Continuation of application No. 16/133,193, filed on
Sep. 17, 2018, now Pat. No. 11,672,951, which is a
(Continued)

(51) **Int. Cl.**
A61M 25/00 (2006.01)
A61M 25/10 (2013.01)

(Continued)

(52) **U.S. Cl.**
CPC ... **A61M 25/0068** (2013.01); **A61B 17/12036**
(2013.01); **A61M 25/008** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC A61M 25/0068; A61M 25/0074; A61M
25/1002; A61M 25/1006; A61M
2025/1052; A61B 17/12036
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

2,156,289 A 5/1939 Hoy
3,585,983 A 6/1971 Kantrowitz et al.
(Continued)

FOREIGN PATENT DOCUMENTS

EP 1094861 B1 4/2005
EP 1658808 A1 5/2006
(Continued)

OTHER PUBLICATIONS

Holcomb et al., "Causes of death in US Special Operations Forces
in the global war on terrorism: 2001-2004," *Annals of Surgery*, vol.
245, No. 6, pp. 986-991 (2007).

(Continued)

Primary Examiner — Laura A Bouchelle


Assistant Examiner — John A Doubrava

(74) *Attorney, Agent, or Firm* — Panitch Schwarze
Belisario & Nadel LLP

(57) **ABSTRACT**

An occlusion catheter system includes a proximal hub
having an inflation connection port and an inflation pathway.
An inflation catheter member is connected to the proximal
hub and has an inflation lumen. A stiffener member defines
a longitudinal axis. The proximal end of the stiffener mem-
ber is connected to the proximal hub. The stiffener member
extends through a portion of the inflation lumen. An occlu-
sion balloon has a proximal balloon end and a distal balloon
end. A distal catheter member is positioned substantially on
the longitudinal axis and is connected to the distal end of the
stiffener member. An atraumatic tip is positioned on a distal
end of the distal catheter member. The atraumatic tip has a
substantially circular profile in a relaxed configuration. A
pressure sensor is connected to the occlusion catheter system
distally relative to the occlusion balloon and is connected to
a processor by electrical wiring.

10 Claims, 33 Drawing Sheets



Related U.S. Application Data

continuation of application No. 15/551,504, filed as application No. PCT/US2016/023223 on Mar. 18, 2016, now Pat. No. 10,149,962.

- (60) Provisional application No. 62/204,804, filed on Aug. 13, 2015, provisional application No. 62/136,571, filed on Mar. 22, 2015, provisional application No. 62/136,180, filed on Mar. 20, 2015, provisional application No. 62/136,370, filed on Mar. 20, 2015, provisional application No. 62/136,152, filed on Mar. 20, 2015, provisional application No. 62/136,123, filed on Mar. 20, 2015, provisional application No. 62/136,326, filed on Mar. 20, 2015, provisional application No. 62/136,390, filed on Mar. 20, 2015, provisional application No. 62/136,230, filed on Mar. 20, 2015, provisional application No. 62/135,576, filed on Mar. 19, 2015, provisional application No. 62/135,552, filed on Mar. 19, 2015, provisional application No. 62/135,609, filed on Mar. 19, 2015, provisional application No. 62/135,528, filed on Mar. 19, 2015, provisional application No. 62/135,603, filed on Mar. 19, 2015.

(51) **Int. Cl.**

A61B 17/12 (2006.01)

A61B 17/00 (2006.01)

(52) **U.S. Cl.**

CPC *A61M 25/0074* (2013.01); *A61M 25/1002* (2013.01); *A61M 25/104* (2013.01); *A61M 25/1006* (2013.01); *A61M 25/10182* (2013.11); *A61B 17/12045* (2013.01); *A61B 17/12109* (2013.01); *A61B 17/00017* (2013.01); *A61M 25/007* (2013.01); *A61M 2025/0002* (2013.01); *A61M 2025/1052* (2013.01); *A61M 2025/1059* (2013.01); *A61M 2025/1081* (2013.01); *A61M 2025/1084* (2013.01); *A61M 2025/1086* (2013.01); *A61M 2025/1093* (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

4,464,172 A 8/1984 Lichtenstein
4,713,888 A 12/1987 Broselow
4,777,951 A 10/1988 Cribier et al.
4,823,469 A 4/1989 Broselow
4,865,549 A 9/1989 Sonstebly
4,926,885 A 5/1990 Hinkle
4,983,166 A 1/1991 Yamawaki
5,047,045 A 9/1991 Arney et al.
5,087,246 A * 2/1992 Smith A61M 25/1002
604/103
5,135,494 A 8/1992 Engelson et al.
5,158,529 A 10/1992 Kanai
5,169,386 A 12/1992 Becker et al.
5,250,070 A 10/1993 Parodi
5,282,479 A 2/1994 Havran
5,295,995 A 3/1994 Kleiman
5,320,605 A 6/1994 Sahota
5,383,856 A 1/1995 Bersin
5,425,711 A 6/1995 Ressemann
5,447,503 A 9/1995 Miller
5,505,702 A 4/1996 Arney
5,522,400 A 6/1996 Williams
5,554,121 A 9/1996 Ainsworth
5,558,644 A 9/1996 Boyd et al.
5,571,093 A 11/1996 Cruz et al.
5,609,606 A 3/1997 O'Boyle
5,718,678 A 2/1998 Fleming, III
5,738,652 A 4/1998 Boyd et al.

5,911,702 A 6/1999 Romley et al.
6,007,517 A 12/1999 Anderson
6,011,988 A 1/2000 Lynch et al.
6,013,019 A 1/2000 Fischell et al.
6,013,055 A 1/2000 Bamos et al.
6,102,930 A 8/2000 Simmons, Jr.
6,113,579 A 9/2000 Eidenschink et al.
6,129,737 A * 10/2000 Hamilton A61M 25/1002
604/96.01
6,146,370 A 11/2000 Barbut
6,161,547 A 12/2000 Barbut
6,165,199 A 12/2000 Barbut
6,190,356 B1 2/2001 Bersin
6,231,572 B1 5/2001 Hart et al.
6,248,121 B1 6/2001 Nobles
6,280,434 B1 8/2001 Kinoshita et al.
6,423,031 B1 7/2002 Donlon
6,453,572 B2 9/2002 Cross et al.
6,575,932 B1 6/2003 O'Brien et al.
6,579,221 B1 6/2003 Peterson
6,602,270 B2 8/2003 Leschinsky et al.
6,656,153 B1 12/2003 Sakai et al.
6,666,814 B2 12/2003 Downey et al.
6,669,679 B1 12/2003 Savage et al.
6,679,860 B2 1/2004 Stiger
6,695,811 B2 2/2004 Samson et al.
6,719,270 B2 4/2004 Ozawa
6,719,720 B1 4/2004 Voelker et al.
6,733,513 B2 5/2004 Boyle et al.
6,735,532 B2 5/2004 Freed et al.
6,736,790 B2 5/2004 Barbut et al.
6,746,462 B1 6/2004 Selmon et al.
6,796,959 B2 9/2004 Davis et al.
6,936,056 B2 8/2005 Nash et al.
6,979,318 B1 12/2005 McDonald et al.
7,341,571 B1 3/2008 Harris et al.
7,434,326 B2 10/2008 Gifford
7,503,904 B2 3/2009 Choi
7,503,909 B2 3/2009 Kusu et al.
7,763,043 B2 7/2010 Goodin et al.
7,892,469 B2 2/2011 Lim et al.
7,909,810 B2 3/2011 Noone
7,951,186 B2 5/2011 Eidenschink et al.
7,951,819 B2 5/2011 Niculescu-Duvaz et al.
7,959,644 B2 6/2011 Shriver
8,021,330 B2 9/2011 McAndrew
8,088,103 B2 1/2012 Teeslink et al.
8,162,879 B2 4/2012 Hattangadi et al.
8,241,241 B2 8/2012 Evans et al.
8,262,611 B2 9/2012 Teeslink et al.
8,419,648 B2 4/2013 Corl et al.
8,430,899 B2 4/2013 Dae et al.
8,499,681 B2 8/2013 Kanner et al.
8,545,382 B2 10/2013 Suzuki et al.
8,655,798 B2 2/2014 Humphrey et al.
8,672,868 B2 3/2014 Simons
8,747,358 B2 6/2014 Trombley, III et al.
8,814,900 B2 8/2014 Fleming, III
8,900,214 B2 12/2014 Nance et al.
8,948,848 B2 2/2015 Merhi
8,951,565 B2 2/2015 McCarthy
9,131,874 B2 9/2015 Eliason et al.
9,211,396 B2 12/2015 Aboytes
D748,257 S 1/2016 Franklin
9,414,843 B2 8/2016 Pavcnik et al.
9,474,882 B2 10/2016 Franklin
9,687,333 B2 6/2017 Angel et al.
10,111,669 B2 10/2018 Eliason et al.
10,143,789 B2 12/2018 Frost
10,279,094 B2 5/2019 Williams et al.
10,368,872 B2 8/2019 Franklin et al.
10,449,337 B2 10/2019 Kassab et al.
2002/0007146 A1 1/2002 Omaleki et al.
2002/0062119 A1 5/2002 Zadno-Azizi
2002/0081406 A1 * 6/2002 Wang B32B 27/08
428/35.2
2002/0193735 A1 12/2002 Stiger
2003/0032974 A1 2/2003 Leschinsky et al.
2003/0083579 A1 5/2003 Aita et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

- | | | | | | |
|-------------------|---------|-----------------------------|-------------------|---------|------------------------------------|
| 2003/0083617 A1 | 5/2003 | St. Germain et al. | 2015/0012031 A1 | 1/2015 | Rago et al. |
| 2003/0167038 A1 | 9/2003 | Yozu et al. | 2015/0039012 A1 | 2/2015 | Solar et al. |
| 2004/0039332 A1 * | 2/2004 | Kantor A61M 25/0023 | 2015/0272732 A1 | 10/2015 | Tilson et al. |
| | | 604/528 | 2015/0367098 A1 | 12/2015 | Aggerholm et al. |
| 2004/0073162 A1 | 4/2004 | Bleam et al. | 2016/0000446 A1 | 1/2016 | Eliason et al. |
| 2004/0082935 A1 | 4/2004 | Lee et al. | 2016/0051386 A1 * | 2/2016 | Haarmann-Thiemann A61M 25/10 |
| 2004/0254528 A1 | 12/2004 | Adams et al. | | | 623/1.11 |
| 2005/0059931 A1 | 3/2005 | Garrison et al. | 2016/0375230 A1 | 12/2016 | Lee et al. |
| 2005/0148812 A1 | 7/2005 | Nigroni et al. | 2017/0296779 A1 | 10/2017 | Purdy et al. |
| 2005/0261725 A1 | 11/2005 | Crawford et al. | 2019/0366046 A1 * | 12/2019 | Klocke A61M 25/0105 |
| 2007/0043307 A1 | 2/2007 | Raulerson et al. | 2020/0022587 A1 | 1/2020 | Glover et al. |
| 2007/0043409 A1 | 2/2007 | Brian et al. | 2021/0290243 A1 | 9/2021 | Franklin et al. |
| 2007/0129466 A1 | 6/2007 | Kagawa et al. | 2022/0000486 A1 | 1/2022 | Williams et al. |
| 2007/0135830 A1 | 6/2007 | Schaeffer | | | |
| 2007/0219466 A1 | 9/2007 | Tremulis et al. | | | |
| 2007/0219488 A1 | 9/2007 | Francescatti | | | |
| 2008/0027356 A1 | 1/2008 | Chen et al. | | | |
| 2008/0082046 A1 | 4/2008 | Kato et al. | | | |
| 2008/0082119 A1 | 4/2008 | Vitullo | | | |
| 2008/0097300 A1 | 4/2008 | Eskaros et al. | | | |
| 2008/0243067 A1 | 10/2008 | Rottenberg et al. | | | |
| 2008/0243221 A1 | 10/2008 | Arcand | | | |
| 2008/0262477 A1 | 10/2008 | Djaladat | | | |
| 2008/0287786 A1 * | 11/2008 | Lentz A61M 25/104 | | | |
| | | 604/509 | | | |
| 2009/0018500 A1 * | 1/2009 | Carter A61M 25/10 | | | |
| | | 604/99.01 | | | |
| 2009/0026595 A1 | 1/2009 | Kadoi | | | |
| 2009/0062666 A1 | 3/2009 | Roteliuk | | | |
| 2009/0171272 A1 | 7/2009 | Tegg et al. | | | |
| 2009/0171293 A1 | 7/2009 | Yang et al. | | | |
| 2009/0265951 A1 | 10/2009 | Black | | | |
| 2009/0287079 A1 | 11/2009 | Shriver | | | |
| 2009/0312807 A1 | 12/2009 | Boudreault et al. | | | |
| 2010/0016735 A1 | 1/2010 | Harpas et al. | | | |
| 2010/0041984 A1 | 2/2010 | Shapland et al. | | | |
| 2010/0113939 A1 * | 5/2010 | Mashimo A61M 25/10187 | | | |
| | | 600/488 | | | |
| 2010/0204712 A1 * | 8/2010 | Mallaby A61B 17/22 | | | |
| | | 606/128 | | | |
| 2010/0234915 A1 | 9/2010 | Herlich et al. | | | |
| 2010/0262076 A1 | 10/2010 | Rowe et al. | | | |
| 2010/0268017 A1 | 10/2010 | Siess | | | |
| 2010/0280451 A1 | 11/2010 | Teeslink et al. | | | |
| 2011/0144742 A1 | 6/2011 | Madrid et al. | | | |
| 2011/0172696 A1 * | 7/2011 | Jeffrey A61M 25/1006 | | | |
| | | 29/428 | | | |
| 2011/0196412 A1 | 8/2011 | Levit et al. | | | |
| 2011/0295301 A1 | 12/2011 | Hoem et al. | | | |
| 2011/0295302 A1 | 12/2011 | Mohl | | | |
| 2011/0301630 A1 | 12/2011 | Hendriksen et al. | | | |
| 2012/0101413 A1 | 4/2012 | Beetel et al. | | | |
| 2012/0108979 A1 | 5/2012 | Franklin et al. | | | |
| 2012/0109057 A1 | 5/2012 | Krolik et al. | | | |
| 2012/0116352 A1 | 5/2012 | Rangi | | | |
| 2012/0130359 A1 | 5/2012 | Turovskiy | | | |
| 2012/0172911 A1 | 7/2012 | Welch | | | |
| 2012/0209176 A1 | 8/2012 | Anderson | | | |
| 2012/0215166 A1 | 8/2012 | Barki | | | |
| 2012/0271231 A1 | 10/2012 | Agrawal | | | |
| 2012/0302994 A1 | 11/2012 | Wilson et al. | | | |
| 2013/0102926 A1 | 4/2013 | Eliason et al. | | | |
| 2013/0102929 A1 | 4/2013 | Haight et al. | | | |
| 2013/0172786 A1 | 7/2013 | Olson et al. | | | |
| 2013/0190619 A1 | 7/2013 | Nudel | | | |
| 2013/0281869 A1 | 10/2013 | Barbut et al. | | | |
| 2013/0289607 A1 | 10/2013 | Pedersen et al. | | | |
| 2013/0338637 A1 | 12/2013 | Fischer, Jr. et al. | | | |
| 2014/0221898 A1 | 8/2014 | Kurrus et al. | | | |
| 2014/0243873 A1 | 8/2014 | Franklin | | | |
| 2014/0249504 A1 | 9/2014 | Franklin et al. | | | |
| 2014/0316012 A1 | 10/2014 | Freyman et al. | | | |
| 2014/0364835 A1 | 12/2014 | Allen et al. | | | |
| 2014/0378869 A1 | 12/2014 | Sela et al. | | | |

FOREIGN PATENT DOCUMENTS

- | | | |
|----|----------------|---------|
| EP | 1911484 A2 | 4/2008 |
| EP | 2389974 A1 | 11/2011 |
| EP | 2716323 A1 | 4/2014 |
| EP | 2837402 A2 | 2/2015 |
| GB | 2297259 A | 7/1996 |
| JP | H 03198868 A | 8/1991 |
| JP | H03280962 A | 12/1991 |
| JP | H 09-164208 A | 6/1997 |
| JP | H1080497 A | 3/1998 |
| JP | 2000217922 A | 8/2000 |
| JP | 2002505165 A | 2/2002 |
| JP | 2003535652 A | 12/2003 |
| JP | 200714820 A | 1/2007 |
| JP | 2008546471 A | 12/2008 |
| JP | 2011245300 A | 12/2011 |
| WO | 9220398 A1 | 11/1992 |
| WO | 9713542 A1 | 4/1997 |
| WO | 9725093 A1 | 7/1997 |
| WO | 9834670 A2 | 8/1998 |
| WO | 1999/24105 A2 | 5/1999 |
| WO | 9925417 A1 | 5/1999 |
| WO | 9944666 A2 | 9/1999 |
| WO | 0197743 A2 | 12/2001 |
| WO | 2004049970 A2 | 6/2004 |
| WO | 2006014631 A1 | 2/2006 |
| WO | 2006135853 A2 | 12/2006 |
| WO | 2007001701 A1 | 1/2007 |
| WO | 2007022592 A1 | 3/2007 |
| WO | 2008013441 A1 | 1/2008 |
| WO | 2010070685 A1 | 6/2010 |
| WO | 2011133736 A2 | 10/2011 |
| WO | 2014/003809 A1 | 1/2014 |
| WO | 2014134215 A1 | 9/2014 |
| WO | 2014152191 A1 | 9/2014 |
| WO | 2015/006828 A1 | 1/2015 |
| WO | 2015035393 A1 | 3/2015 |
| WO | 2015191685 A1 | 12/2015 |
| WO | 2016149653 A2 | 9/2016 |
| WO | 2017210584 A1 | 12/2017 |
| WO | 2019095049 A1 | 5/2019 |
| WO | 2020033372 A1 | 2/2020 |

OTHER PUBLICATIONS

- Sohn et al., "Demographics, Treatment, and Early Outcomes in Penetrating Vascular Combat Trauma," Arch Surg, vol. 143, No. 8, pp. 783-787 (2008).
- White et al., "The Epidemiology of Vascular Injury in the Wars in Iraq and Afghanistan," Annals of Surgery, vol. 253, No. 6, pp. 1184-1189 (2011).
- Fenton et al., "Comparing risks of alternative medical diagnosis using Bayesian arguments," J. Biomed. Inf., vol. 43, pp. 485-495 (2010).
- Patel et al., "Bayesian Designs for Device Clinical Trials," MDG Forum, Waltham, MA., Nov. 3, 2010, downloaded from web page: <http://www.cytel.com/pdfs/Patel_Bayes_Devices_Slides_11.18.10.pdf>.
- Guidance for the Use of Bayesian Statistics in Medical Device Clinical Trials, U.S. Department of Health and Human Services,

(56)

References Cited**OTHER PUBLICATIONS**

- Food and Drug Administration, Center for Devices and Radiological Health, Division of Biostatistics, Office of Surveillance and Biometrics, Feb. 5, 2010.
- Int'l Preliminary Report on Patentability dated Sep. 11, 2015 in Int'l Application No. PCT/US2014/018779.
- Int'l Search Report and Written Opinion dated Jun. 8, 2014 in Int'l Application No. PCT/US2014/018779.
- Int'l Search Report and Written Opinion dated Oct. 14, 2011 in Int'l Application No. PCT/US2011/033368.
- Sandgren et al., "The Diameter of the Common Femoral Artery in Healthy Human: Influence of Sex, Age, and Body Size," *Journal of Vascular Surgery*, vol. 29, No. 3, pp. 503-510 (1999).
- Sam II et al., "Blunt Traumatic Aortic Transection: Endoluminal Repair with Commercially Available Aortic Cuffs," *Journal of Vascular Surgery*, vol. 38, No. 5, pp. 1132-1135 (2003).
- Peterson et al., "Percutaneous endovascular repair of blunt thoracic aortic transection," *Journal of Trauma*, vol. 59, No. 5, pp. 1062-1065 (2005).
- Office Action dated Oct. 28, 2014 in U.S. Appl. No. 13/642,465, by Eliason.
- Office Action dated Apr. 6, 2015 in U.S. Appl. No. 13/642,465, by Eliason.
- Stannard et al., "Resuscitative Endovascular Balloon Occlusion of the Aorta (REBOA) as an Adjunct for Hemorrhagic Shock," *J. Trauma*, vol. 71, pp. 1869-1872 (2011).
- Ledgerwood et al., "The Role of Thoracic Aortic Occlusion for Massive Hemoperitoneum," *J Trauma*, vol. 16, No. 8, pp. 610-615 (1976).
- Detrano et al., "Bayesian Probability Analysis: a Prospective Demonstration of its Clinical Utility in Diagnosing Coronary Disease," *Circulation*, vol. 69, No. 3, pp. 541-547 (1984).
- Int'l Search Report and Written Opinion dated Jan. 28, 2015 in Int'l Application No. PCT/US2014/054802.
- Int'l Preliminary Report on Patentability dated Mar. 24, 2016 in Int'l Application No. PCT/US2014/054802.
- Int'l Preliminary Report on Patentability dated Nov. 1, 2012 in Int'l Application No. PCT/US2011/033368.
- Langewouters et al., "The static elastic properties of 45 human thoracic and 20 abdominal aortas in vitro and the parameters of a new model," *Journal of Biometrics*, vol. 17, No. 6, pp. 425-435 (1984).
- Hughes, "Use of an Intra-Aortic Balloon Catheter Tamponade for Controlling Intra-Abdominal Hemorrhage in Man," *Surgery*, vol. 36, pp. 65-68 (1954).
- Office Action dated Aug. 23, 2016 in AU Application No. 2015274743.
- Extended European Search Report dated Oct. 5, 2016 in Europe Application No. EP 14 75 6640.
- Supplemental Search Report dated Dec. 19, 2016 in EP Application No. 15806534.
- Int'l Preliminary Report dated Dec. 22, 2016 in Int'l Application No. PCT/US2015/035061.
- Int'l Search Report and Written Opinion dated Sep. 4, 2015 in Int'l Application No. PCT/US2014/035061.
- Extended Search Report dated Mar. 24, 2017 in EP Application No. 14842370.
- Int'l Search Report and Written Opinion dated Apr. 21, 2017 in Int'l Application No. PCT/US2016/023223.
- Extended Search Report dated Mar. 21, 2017 in EP Application No. 15806534.
- Office Action dated Apr. 11, 2017 in JP Application No. 2016-546035.
- Office Action dated Mar. 20, 2017 in CA Application No. 2,797,237.
- Extended European Search Report dated Jun. 26, 2017 in EP Application No. 14842370.
- Int'l Preliminary Report dated Jul. 17, 2017 in Int'l Application No. PCT/US2016/023223.
- Int'l Search Report and Written Opinion dated Sep. 28, 2017 in Int'l Application No. PCT/US2017/035729.
- Office Action dated Sep. 19, 2017 in JP Application No. 2015-559309.
- Office Action dated Sep. 12, 2017 in JP Application No. 2016-546035.
- Office Action dated Oct. 12, 2017 in CA Application No. 2,980,018.
- Chen et al., "The Renal Length Nomogram: A Multivariable Approach," *The Journal of Urology*, vol. 168, pp. 2149-2152 (Nov. 2002).
- Int'l Search Report and Written Opinion dated Oct. 18, 2019 in Int'l Application No. PCT/US19/45252.
- Office Action dated Jan. 9, 2023 in U.S. Appl. No. 16/133,193.
- Int'l Search Report and Written Opinion dated Jun. 8, 2022 in Int'l Application No. PCT/US2022/020704.
- European Search Report dated May 31, 2022 in European Application No. 19846055.2.
- M. Austin Johnson et al. (published on May 27, 2016). Partial Resuscitative Balloon Occlusion of the Aorta (P-REBOA): Clinical Technique and Rationale, *J Trauma Acute Care Surg*, 81(5) Suppl 1:S133-S137.
- Rachel M. Russo et al. (presented at the Military Surgical Symposium, Nashville, TN in Apr. 2015, published on Apr. 29, 2016). Partial Resuscitative Endovascular Balloon Occlusion of the Aorta in Swine Model of Hemorrhagic Shock, *J Am Coll Surg*, 223:359-368.
- Rachel M. Russo et al. (published on Dec. 14, 2015). Extending the Golden Hour: Partial Resuscitative Endovascular Balloon Occlusion of the Aorta in a Highly Lethal Swine Liver Injury Model, *J Trauma Acute Care Surg* (80)3:372-380.
- Extended Search Report dated May 10, 2023 in European Application No. 22743436.2.

* cited by examiner




FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 9A




FIG. 9B




FIG. 9C









FIG. 9D












FIG. 21




FIG. 22




FIG. 26




FIG. 27




FIG. 28




FIG. 28A




FIG. 31




FIG. 31A




FIG. 31B




FIG. 32A




FIG. 33




FIG. 34




FIG. 35A




FIG. 35B




FIG. 35C








FIG. 35D






FIG. 37




FIG. 37B




FIG. 37A




FIG. 37C




FIG. 38




FIG. 39




FIG. 39A




FIG. 39B




FIG. 40




FIG. 41




FIG. 41A




FIG. 42A




FIG. 42B




FIG. 43






FIG. 43A






FIG. 44




FIG. 45

1

SYSTEM AND METHOD FOR LOW-PROFILE OCCLUSION BALLOON CATHETER

CROSS-REFERENCE TO RELATED APPLICATIONS

The present application is a continuation of U.S. patent application Ser. No. 16/133,193, filed Sep. 17, 2018 and titled, "System and Method for Low-Profile Occlusion Balloon Catheter," which is a continuation of U.S. patent application Ser. No. 15/551,504, filed Aug. 16, 2017 and titled, "System and Method for Low-Profile Occlusion Balloon Catheter," and issued as U.S. Pat. No. 10,149,962 on Dec. 11, 2018, which is a Section 371 of International Patent Application No. PCT/US2016/023223, filed Mar. 18, 2016, which was published in English on Sep. 22, 2016 as International Publication No. WO 2016/149653 and claims the benefit of U.S. Provisional Patent Application Nos. 62/135,552, filed Mar. 19, 2015 and titled, "Anti-Hypertensive Vascular Occlusion Catheter and Method," 62/135,528, filed on Mar. 19, 2015 and titled, "Anti-Hypertensive Vascular Occlusion Catheter with Electromechanical Actuation and Method," 62/135,576, filed Mar. 19, 2015 and titled, "Anti-Hypertensive Vascular Occlusion Catheter and Method," 62/135,603, filed Mar. 19, 2015 and titled, "Anti-Hypotensive Vascular Occlusion Catheter with Electromechanical Actuation Method," 62/135,609, filed Mar. 19, 2015 and titled, "Control Processing System for Regulating Vascular Occlusion and Method," 62/136,123, filed Mar. 20, 2015 and titled, "System and Apparatus for Vascular Pre-Conditioning and Method," 62/136,152, filed Mar. 20, 2015 and titled, "Vascular Pre-Conditioning Occlusion Catheter and Method," 62/136,180, filed Mar. 20, 2015 and titled, "Vascular Occlusion Catheter with Infusion Capability and Method," 62/136,230, filed Mar. 20, 2015 and titled, "Vascular Occlusion-Perfusion Catheter and Method," 62/136,326, filed Mar. 20, 2015 and titled, "Vascular Occlusion Catheter with Variable Perfusion Flow and Method," 62/136,370, filed Mar. 20, 2015 and titled, "Vascular Occlusion-Perfusion Catheter with Plural Occlusion Members and Method," 62/136,390, filed Mar. 20, 2015 and titled, "Vascular Occlusion-Perfusion Catheter with Mechanically Actuated Variable Occlusion-Perfusion Properties and Method," 62/136,571, filed Mar. 22, 2015 and titled, "Low Profile Sensing Vascular Occlusion Catheter and Method of Vascular Occlusion," and 62/204,804, filed Aug. 13, 2015 and titled, "System and Method for Low-Profile Occlusion Balloon Catheter," the entire contents of each of which are incorporated by reference herein in their entireties.

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

This invention was made with government support under Contract No. W911QY-15-C-0099 and grant title "Resuscitative Endovascular Balloon Occlusion of the Aorta (REBOA) Research", awarded by U.S. Army Medical Materiel Agency. The government has certain rights in the invention.

BACKGROUND OF THE INVENTION

The present invention pertains generally to vascular occlusion catheters and methods of vascular pre-conditioning while controlling occlusion and perfusion during an occlusion procedure. Pre-conditioning is employed to mitigate ischemia before, during and/or after a vascular occlu-

2

sion procedure, as well as used to reduce or ameliorate the onset of hypertension during or reduce or ameliorate the onset of hypotension after a vascular occlusion procedure. Vascular occlusions may be indicated in either the venous system and/or the arterial system. Endoarterial occlusion is a procedure in which a blood vessel is at least partially occluded in order to restrict blood flow upstream or downstream the occlusion site for purposes of a vascular procedure or repair. It is known that transient hypertension is a risk factor in arterial occlusion, particularly aortic occlusion. Transient hypertension occurs when the blood pressure upstream the occlusion site rises to a potentially unsafe level during the time duration of the occlusion. Upon completion of a procedure requiring arterial occlusion, particularly aortic occlusion, care must be taken during the process of reestablishing blood flow to reduce or ameliorate the onset of hypotension. Thus, arterial occlusion carries with it two twin risks, hypertension during the occlusion and hypotension as the occlusion is withdrawn and blood flow restored, that must be managed.

Temporary aortic occlusion as an operative method to increase proximal or central perfusion to the heart and brain in the setting of shock due to major trauma is generally known. Despite potential advantages over thoracotomy with aortic clamping, resuscitative endovascular balloon occlusion of the aorta ("REBOA") for trauma has not been widely adopted.

Many attempts have been made at developing technologies to control non-compressible abdominal hemorrhage. For example, non-occlusive, abdominal tamponade procedures have been developed to address the problem of non-compressible hemorrhage, such as providing introducing an expandable biocompatible foam into the abdominal cavity to apply pressure to the abdominal organs and vasculature. Pharmacological efforts have also been developed to address the problem of non-compressible hemorrhage. Conventional REBOA procedures are typically performed in an operating room and with the aid of fluoroscopy of other imaging.

Devices that automate inflation and deflation of a balloon are known. Intra-aortic balloon counterpulsation catheters for blood pressure augmentation coordinated with electrocardiography signals are also known. Over inflation safety devices are also known, such as a pressure-relief valve coupled to an inflation lumen that opens when pressure within the inflation lumen exceeds a threshold pressure, but is still that relative pressure within the balloon necessary to maintain occlusion of the blood vessel.

It would be desirable to design, develop and implement a system that intermittently and automatically releases an occlusion by releasing apposition of an occlusive member against the vascular wall and allowing perfusion past the occlusion member in response to a physiological parameter, then re-establishing occlusion in response to potential changes in the physiological parameter, either during a vascular repair procedure to control hypertension or post-repair procedure to control hypotension.

BRIEF SUMMARY OF THE INVENTION

In accordance with a preferred embodiment of the present invention, there is provided an arterial occlusion catheter system including an occluding member carried at a distal aspect of a catheter, an atraumatic guiding tip forming a distal end of the catheter and a pressure accumulator communicating with the occluding member. The atraumatic guiding tip alleviates the need for a guide wire, and, there-

fore for initial guide wire placement, allowing the preferred arterial occlusion catheter to be used in field operations and without the necessity of fluoroscopy or other imaging modality.

In accordance with another preferred embodiment of the present invention, there is provided an arterial occlusion catheter system including an occluding member carried at a distal aspect of a catheter, an atraumatic guiding tip forming a distal end of the catheter, a pressure valve communicating with the occluding member that release expansive force applied to the occluding member to allow perfusion past the occluding member when hypertension is present, and a means for re-applying the expansive force to re-establish occlusion when the arterial pressure is normalized.

In accordance with still another preferred embodiment of the present invention, there is provided an arterial occlusion catheter system having a computer hardware and software control over the physiological parameter set points at which automatic computer controlled occlusion or release of occlusion occur, including, without limitation, set points for systolic and/or diastolic arterial blood pressure, heart rate, heart rhythm (including, without limitation, the P, Q, R, S, T and U peaks, their size, timing and duration), blood oxygenation, tissue oxygenation or the presence or absence of metabolic blood products.

In accordance with yet still another preferred embodiment of the present invention, there is provided an arterial occlusion catheter system having computer hardware and software control monitoring physiological parameter set points for systolic and/or diastolic arterial blood pressure, heart rate, heart rhythm (including, without limitation, the P, Q, R, S, T and U peaks, their size, timing and duration), blood oxygenation, tissue oxygenation or the presence or absence of metabolic blood products and which provides visual, auditory or tactile feedback to a medical practitioner as signals for the medical practitioner to take certain recommended actions based upon the monitored physiological parameter set points.

In accordance with still yet another preferred embodiment of the present invention, there is provided an arterial occlusion system and method in which fluids, such as blood, plasma, saline, blood products or blood substitutes, are infused proximal and/or distal the occlusion site.

In accordance with another preferred embodiment of the present invention, there is provided an arterial occlusion system and method in which the occlusion member has a geometric conformation such that at different degrees of deployment it assumes different transverse geometric profiles that yield different degrees of arterial occlusion and permit perfusion past the occlusion member. The occlusion member may have a torroidal shape when fully deployed and a fluted or corrugated shape with longitudinally oriented flutes or corrugations and valleys between adjacent flutes or corrugations when in its partially deployed state. Alternatively, the occlusion member may have a helical shape when either fully or partially deployed, such that fluid flow around the occlusion member is maintained while at least partially occluding the artery. Further, the occlusion member may have a torroidal shape with vanes, the vanes being either longitudinally oriented or helically oriented, the vanes being sufficiently pliant so that they deflect and fold against the occlusion member when the occlusion member is in full apposition with the vascular luminal wall surface, but pliantly recover to project from the occlusion member and define fluid flow pathways between adjacent vanes and past the occlusion member.

In accordance with yet another preferred embodiment of the present invention, there is provided an arterial occlusion system and method having a catheter with at least one occlusion member at a distal end thereof, a plurality of fluid flow ports communicating with a common fluid flow lumen within the catheter and an luminal occluding member that is movable within the common fluid flow lumen to open or close one or more of the plurality of fluid flow ports, thereby controlling the volume and rate of perfusion fluid flow past the at least one occlusion member.

While in all preferred embodiments of the present invention, the occluding member is preferably a balloon, the occluding member may also consist of a woven or non-woven shape memory metal membrane, a superelastic metal membrane, an elastic metal membrane, a woven or non-woven polymer material or a shape memory polymer and that the occluding member may or may not be supported by an expansive or reinforcing frame.

As noted above, arterial hypertension is a frequent result of arterial occlusion for any clinically significant period of time, particularly, in aortic occlusion situations. A need has been recognized to provide a catheter system in which clinically significant hypertension is alleviated automatically and without medical practitioner intervention or control, concurrently with the arterial pressure exceeding a pre-determined level upstream in the blood flow from the occlusion member.

The preferred present invention generally relates to endovascular arterial occlusion catheters that are particularly well suited to emergency or trauma use for REBOA procedures to occlude non-compressible hemorrhage either in the field, on the battlefield or in emergency room environments where guidance imaging is typically not available. More particularly, the preferred present invention pertains to an arterial occlusion catheter that has an atraumatic guiding tip made of a generally flexible material, elastic material, shape memory material or superelastic material. The atraumatic guiding tip may be formed at least in part of elastomeric polymer that permits guide wire and fluoroscopy free guidance of the arterial occlusion catheter to the site requiring occlusion. Still more particular, the present invention relates to a low profile aortic occlusion catheter having an atraumatic guiding tip formed of polymer, metal or polymer reinforced with an elastic, shape memory or superelastic material and having a lumen for introducing or withdrawing fluids from a body into which the catheter is placed and/or for introducing sensors, adjunctive medical devices or other diagnostic or therapeutic modalities, to determine and evaluate a condition within the body, such as arterial pressure or flow rate, to diagnose a condition in the body and/or to treat a condition in the body.

Balloon catheters generally comprise an elongated catheter shaft with a deflated balloon on the distal end of the shaft, and are used in a number of different medical procedures, including, for example, angioplasty, stent placement, occlusion, drug delivery, etc. The catheter is introduced through a percutaneous sheath and maneuvered into the patient's blood vessels until the balloon is properly positioned across the stenotic area to be dilated. Once properly in position, the balloon is inflated with liquid one or more times to a predetermined size and pressure to widen the coronary passageway and increase blood flow.

It is desirable for balloon catheters to attain very low profiles in order to facilitate passage of the balloon across severe and remote vascular obstructions. High strength materials are commonly required in the design of balloon catheter components to prevent shaft buckling when the

balloon is inflated. Additionally, high strength materials are required so that torque applied to the proximal end of the catheter results in rotation of the distal tip of the catheter. High flexibility materials are also commonly required in the design of balloon catheter components to maintain a low-profile and avoid trauma or perforation of the blood vessels while the catheter is maneuvered through the patient's tortuous vasculature.

However, conventional balloon catheters, particularly those designed for aortic occlusion, generally do not properly balance the need for proximal segment stiffness with the need for a low profile, flexible distal segment and trackability through the tortuous vascular pathway without entry into collateral vessels. A low profile balloon catheter with a high strength and relatively stiff proximal segment and a flexible distal segment with an atraumatic tip having a design that restricts tracking and entry into collateral vessels, which is employed by preferred embodiments of the present invention.

In one preferred embodiment, the devices comprise an elongate catheter having a proximal and a distal region. The catheter may also have a lumen extending between the proximal and distal regions. An expandable occlusion member, e.g., a balloon, a membrane with or without an expandable frame or an expandable section of the catheter itself, is carried at the distal region of the catheter. The catheter in certain preferred embodiments may include plural expandable occlusion members, i.e., second, third, fourth, etc. expandable occlusion members, at the distal region of the catheter, proximal and/or distal the first expandable occlusion member.

In certain preferred embodiments, the catheter will also include means for measuring physiological parameters distal and/or proximal one or more of the expandable occlusion members, including, for example blood pressure sensors, heart rate sensors, flow sensors, chemical sensors, temperature sensors, oxygenation sensors, ischemia sensors, biological sensors, imaging sensors or the like.

In use, the catheter having one expandable device is located in the descending aorta so that the expandable device is suprarenal or infrarenal. The expandable device is then expanded to partially or completely obstruct the descending aorta. Cerebral blood flow and cerebral blood pressure rises and is maintained at an increased level, as desired. Cephalic blood pressure and/or cerebral blood flow may be monitored, and the expandable device adjusted as needed. Therapeutic instruments may be deployed through the lumen (when present) of the occlusion catheter systems.

In another preferred embodiment, the occlusion member, when expanded, has a maximum periphery that conforms to the inner wall of the vessel, thereby providing a sealed contact between it and the vessel wall. The occlusion catheter system may have a blood flow or other fluid flow conduit allowing blood flow from a location upstream to a location downstream. The preferred devices further include a variable flow mechanism in operative association with the blood conduit, thereby allowing blood flow through the conduit to be adjusted and controlled. The preferred devices can optionally include a manometer and/or pressure limiter to provide feedback to the variable flow mechanism for precise control of the upstream and downstream blood pressure.

In certain preferred embodiments of the invention, the arterial occlusion catheter system includes an additional access lumen that allows access and passage of other medical devices or adjunctive therapies. Devices, such as flow wires, imaging catheters or devices, infusion, atherectomy,

angioplasty, hypothermia catheters or devices, or electrophysiologic study (EPS) catheters, can be introduced through the additional access lumen to access a position in the blood vessel to provide diagnostic or therapeutic interventions. Hypothermia is one example of an adjunctive therapy that may be delivered using the additional access lumen of the preferred arterial occlusion catheter. Where cerebral cooling is desired the additional access lumen may be used to introduce cooled blood or other cooled fluids, a cooling wire, or other type of heat exchanger, such as a cooling catheter.

In still another preferred embodiment, the occlusion member comprises a first balloon mounted to a distal end of the catheter, and a second balloon mounted on the distal end of the catheter and proximal the first balloon, with a region of the catheter being intermediate the first and the second balloons. The first balloon has a first balloon inflation chamber and the second balloon has a second balloon inflation chamber, the first balloon inflation chamber and the second balloon inflation chamber may communicate with a common inflation lumen or, alternatively, may communicate with separate inflation lumens, termed herein, first inflation lumen and second inflation lumen, such that the first and second balloons are either concurrently or separately inflatable. A perfusion lumen may also be provided in the catheter and communicates with perfusion openings passing through the wall of the catheter to permit fluids, including blood and blood products to be introduced through the catheter. The perfusion openings are preferably located distal the first balloon (first perfusion openings), proximal the first balloon and intermediate the first balloon and the second balloon (second perfusion openings), and/or proximal the second balloon (third perfusion openings), or in any combination thereof, such that fluid flow may be established either concurrently or selectively through all of or only some of the perfusion openings. Selective fluid flow through the perfusion openings may be accomplished in a number of alternative manners. For example, a plurality of perfusion lumens may be provided in the catheter. A first perfusion lumen communicating with the perfusion openings distal the first balloon, a second perfusion lumen communicating with the perfusion openings proximal the first balloon and intermediate the second balloon and the first balloon, and a third perfusion lumen communicating with the perfusion openings proximal the proximal balloon. Alternatively, a single common perfusion lumen may communicate with all of the perfusion openings, and a selector member is disposed within the perfusion lumen and movable within the perfusion lumen to selectively expose only those perfusion lumens in the catheter regions through which perfusion is desired. A non-limiting example of a selector member comprises a tubular hypotube having non-fenestrated wall surfaces that is longitudinally movable within the perfusion lumen to select either the first perfusion openings, the second perfusion openings or the third perfusion openings, or portions thereof. The hypotube may, itself, have fenestrations or openings passing through its wall surfaces, wherein rotational movement of the fenestrated hypotube within the perfusion lumen will align the hypotube fenestrations with one or more of the perfusion openings to permit fluid flow from the lumen of the hypotube and through the aligned fenestrations and perfusion openings and into the vascular structure.

It will be understood that there are many advantages in using the partial aortic occlusion devices and methods disclosed herein. For example, the devices can be used (1) to provide variable partial occlusion of a vessel; (2) to

augment and maintain cerebral perfusion in patients suffering from global or focal ischemia; (3) to condition the brain or spinal cord to secrete neuroprotective agents prior to a major surgery which will necessitate reduced cerebral or spinal perfusion; (4) to prolong the therapeutic window in global or focal ischemia; (5) to accommodate other medical devices, such as an atherectomy catheter; (6) prophylactically by an interventional radiologist, neuroradiologist, or cardiologist in an angiogram or fluoroscopy suite; (7) for prevention of cerebral ischemia in patients undergoing procedures, such as coronary catheterization or surgery, where cardiac output might fall as a result of arrhythmia, myocardial infarction or failure; (8) to treat shock, thereby eliminating or reducing the use of systemic vasoconstrictors; (9) to prevent hypotensive neurologic damage during carotid stenting, and (10) to rescue vasospasm induced by hemorrhage or interventional procedures.

Provided herein are systems, methods and compositions for an occlusion balloon catheter system comprising: a first catheter member having a first lumen extending longitudinally through the first catheter member and open at a distal end of the first catheter member; a second catheter member having a second lumen extending longitudinally through the second catheter member and open at a distal end of the second catheter member, the second catheter member is positioned over and in spaced apart relationship relative to a proximal section of the first catheter member forming an annular space between the second catheter member and the first catheter member, the proximal section of the first catheter member resides within the second lumen of the second catheter member and the first catheter member extends beyond the distal end of the second catheter member, a third catheter member that may comprised a proximal shaft of an atraumatic tip having a third lumen extending longitudinally and partially through the third catheter member; the third catheter member is positioned over a distal section of the first catheter member, the third catheter member having a distal section that extends distally from a distal end of the first catheter member such that the first lumen and the third lumen are in fluid flow communication, whereby the second and third catheter are spaced apart from each other along a longitudinal axis of the first catheter member with the first catheter member extending therebetween; an atraumatic tip member having a proximal section co-axially coupled to a distal end of the third catheter member; and a balloon coupled at its proximal end to the second catheter member and at its distal end to the third catheter member and in fluid flow communication with the second catheter member; the balloon being positioned such that the space between the second catheter member and the third catheter member is within the balloon.

REBOA is preferably performed, as follows:

Step 1: Arterial Access and Positioning of Initial Sheath

Access to the arterial circulation for REBOA for trauma is obtained through the femoral artery. After femoral artery access is obtained, a ten to fifteen centimeter (10-15 cm) long sheath is positioned in the femoral and external iliac artery. Access to the femoral artery can be obtained using several techniques, including: percutaneous, open exposure (i.e., cut down), or exchange over a guide wire from an existing femoral arterial line. Percutaneous access is commonly accomplished under ultrasound guidance. Ultrasound or direct surgical identification of the femoral artery lateral to the vein is preferred in the hypotensive patient without a palpable pulse. Once identified, the artery should be entered at a forty-five degree (45°) angle with a hollow eighteen gauge (18-gauge) needle through which a thirty-five thou-

sandths inch (0.035") wire or similarly sized wire can be passed. After the wire has been passed into the artery, the needle is removed and a small incision made at the interface of the wire and the skin. Next the sheath is placed over the wire into the artery. Any time a sheath is passed over a wire into the arterial system, the sheath's internal dilator is preferably firmly in place to allow a smooth reverse taper from the wire to the diameter of the sheath. Once the dilator and sheath have been advanced over the wire through the skin into the artery, the dilator is removed leaving the sheath as a working port through which other maneuvers can be accomplished.

Step 2: Selection and Positioning of the Balloon

Selection of a Balloon: A balloon inflated inside the aorta to occlude flow should be compliant and of large diameter. Stiff or noncompliant balloons pose a risk of arterial damage.

Positioning of the Balloon (Zones of the Aorta): Balloon selection should be made in view of the aortic zone to be occluded. Aortic zones can be considered I, II, and III spanning from cranial or proximal to caudal or distal. Zone I is preferably considered the descending thoracic aorta between the origin of the left subclavian and celiac arteries. Zone II preferably represents the para-visceral aorta between the celiac and the lowest renal artery and zone III preferably represents the infrarenal abdominal aorta between the lowest renal artery and the aortic bifurcation, depending on patient anatomy. In most instances of shock and pending cardiovascular collapse, the aim is to position the occlusive balloon to occlude zone I. In this case, a larger diameter balloon and a longer sheath are advanced into the thoracic aorta. REBOA in zone I typically requires a longer sheath, such as a sheath having a forty-five to sixty centimeter (45-60 cm) length, to be positioned in the descending thoracic aorta to support or hold the balloon against aortic pulsation once it is inflated. Inflation of a compliant balloon in aortic zone III may provide specific utility in cases of pelvic or junctional femoral hemorrhage. In this instance, a relatively smaller diameter balloon may be sufficient. Because the aortic bifurcation will support or hold the inflated balloon against pulsation, this maneuver can potentially be accomplished using a large diameter but shorter sheath, such as ten to fifteen centimeters (10-15 cm).

Wire Control and Positioning of the Large Sheath and Balloon: Positioning of the balloon in the aorta preferably takes place over a thirty-five thousands inch (0.035") wire, but is not so limited, and through an appropriately sized sheath that takes the place of the initial sheath previously described. Re-sheathing may be accomplished by inserting a two hundred sixty centimeter (260 cm) long, thirty-five thousands inch (0.035") stiff wire (e.g., Amplatz Stiff Wire Guide; Cook Medical) through the initial sheath in the femoral artery. The stiff wire is preferably advanced under fluoroscopic guidance or visualization such that the floppy tip is in the distal aortic arch. The extent of the wire outside of the sheath at this point should be noted and marked so that the wire is not advanced or withdrawn significantly, such as by more than five centimeters (>5 cm). Failure to maintain control of the wire's insertion depth during this and subsequent maneuvers may result in inadvertent injury to coronary or cerebral vessels if it is advanced too far or an inability to advance the balloon to the occlusion zone if it is withdrawn.

The initial sheath may be removed and backed off of the wire with pressure held proximally over the femoral artery for hemostasis. The larger sheath is then advanced over the wire, preferably lead by its internal dilator, through the skin

opening and into the femoral and iliac artery. In this manner, the wire acts as a rail over which the large sheath or balloon catheter can be advanced or withdrawn as the operator focuses on the fluoroscopic image.

To occlude zone I, the larger, longer sheath is preferably advanced over the stiff wire under fluoroscopic guidance into the thoracic aorta to the desired location of occlusion. Fluoroscopically, zone I can be estimated to exist above the twelfth (12th) rib and below the medial head of the clavicle. Next, the internal dilator is preferably removed from the sheath and the back end of the extended wire. The balloon is next preferably loaded on and advanced over the stationary wire into and through the sheath. Under fluoroscopic visualization, after the balloon advances from the end of the sheath, it is ready to be inflated. To occlude zone III typically requires a large diameter but shorter sheath, such as ten to twenty-five centimeters (10-25 cm), to allow passage of the balloon into the terminal aorta under fluoroscopic visualization. The concept in this scenario is that once the balloon is inflated, any aortic pulsation will push the balloon to the terminal aorta and its bifurcation.

Step 3: Inflation of the Balloon and Securing of the Apparatus

Balloon Inflation: Similar to step 2, inflation of the balloon is preferably accomplished under fluoroscopic guidance. A large-volume syringe, usually thirty to sixty milliliters (30-60 mL) is filled with a half and half solution of sterile saline and iodinated contrast. This mixture allows visualization of the balloon inflation as well as more rapid inflation and deflation times by reducing viscosity. Preferably with fluoroscopy, the balloon is inflated until the outer edges of the balloon change from convex to parallel as the balloon takes on the contour of the aortic wall. One may notice that during systole, the balloon changes shape and creates a "mushroom cap" as it is pulsed inferiorly. In zone I occlusion, the previously positioned long sheath can then support the balloon and maintain its position within the aorta. When inflation appears adequate to gain aortic wall apposition and augment central blood pressure, the three-way stopcock on shaft of the balloon should be turned off toward the balloon to maintain inflation and occlusion while other maneuvers are undertaken.

Securing the Inflated Balloon, Sheath, and Wire Apparatus: It is next preferred to hold the balloon, sheath, and wire securely so that none generally change position as the central aortic pressure returns pushing the balloon caudal. Although the balloon, sheath, and wire can be secured with sutures or an occlusive dressing that pin the apparatus to the patient, these are preferably observed continuously to limit downward or caudal migration.

Step 4: Deflation of the Balloon

Once a decision to attempt deflation is made, care is preferably taken to deflate the balloon slowly as this step can be anticipated to result in a decrease in afterload and hypotension. After prolonged balloon inflation or in situations where incomplete resuscitation has occurred, deflation of the balloon can potentially result in reperfusion, washout of metabolic byproducts, and acidosis. As such, intermittent balloon inflation and deflation is preferred until some hemodynamic stability is restored.

Step 5: Removal of the Balloon and Sheath

After REBOA is no longer required, the deflated balloon and wire are preferably removed from the large sheath which is preferably flushed with heparinized saline, such as one hundred milliliters (100 mL) of saline or one thousand (1,000) units of heparin. The relatively large diameter sheaths used to deploy currently available compliant bal-

loons are best removed with open surgical exposure of the femoral artery. This can be accomplished using a longitudinal or transverse groin incision with dissection through the soft tissues overlying the femoral sheath. The femoral artery proximal and distal to the sheath entry site should be exposed to allow control. Proximally, this often requires dissection for two to three centimeters (2-3 cm) underneath the inguinal ligament as an assistant uses a narrow handheld retractor (e.g., short Wylie renal vein retractor) to lift the inguinal ligament off of the femoral sheath. During this maneuver, the surgeon preferably considers the circumflex iliac veins, which course over the top of the distal external iliac and proximal common femoral artery. Exposure distal to the sheath entry site preferably includes identification and control of both the superficial and profunda femoris arteries.

Once proximal and distal exposure and control have been accomplished, the sheath may be removed. The resulting arteriotomy should be closely examined and closed. Restoration of flow through the arterial segment is preferably confirmed using manual palpation for pulses and use of continuous wave Doppler of both the artery and more distal extremity. Closure of the femoral artery exposure is preferably accomplished in layers using absorbable suture in the soft tissues and skin.

REBOA can be considered in the following five steps, each with specific procedural considerations: 1. Arterial access, 2. Balloon selection and positioning, 3. Balloon inflation, 4. Balloon deflation, and 5. Sheath removal. REBOA procedures may be conducted under fluoroscopy or other suitable imaging modality.

There is a need for a device that permits medical practitioners to conduct REBOA procedures without the conventional necessity of using fluoroscopy or other imaging modality together with the suitability of using the device and techniques for field applications outside the hospital or in hospital emergency room settings. In trauma situations where a patient is undergoing severe central torso hemorrhaging, particularly when not in a hospital setting, such as on a battlefield or on a public street or highway, imaging capability is simply not available to emergency responders or field medical practitioners. In such situations, it is preferred to temporarily occlude a central torso hemorrhage so that the patient may be stabilized in the field and transported to a hospital or other facility in which repair of the traumatic injury may be conducted.

Injuries in modern warfare are often caused by explosion and related high-velocity penetrating shrapnel leading to non-compressible bleeding. Non-compressible bleeding accounts for approximately eighty-five percent (85%) of preventable deaths on the battlefield, eighty percent (80%) of which include acute hemorrhage within the abdomen/torso. Abdominal hemorrhage involves injury to the spleen, liver, or retroperitoneal vasculature, and is typically non-compressible, meaning that it cannot be treated by external compression or the application of tourniquets or topical dressings.

Emergency surgical intervention is currently the only available method for treating non-compressible abdominal hemorrhage. Battlefield or other major trauma generally occurs in an austere, resource constrained environment, often with extended evacuation time due to persisting tactical threats or environmental constraints. Transport time to reach a hospital where surgery can take place varies, but is estimated to average one hour (1 hr). The majority of preventable deaths due to abdominal hemorrhage is nearly fifty percent (50%) and can be attributed to delays in

11

hemorrhage control during transportation, highlighting the need for rapid, far-forward hemorrhage treatments.

Systems, methods and compositions for an occlusion balloon catheter system comprising: a first catheter member having a first and second lumens extending along a longitudinal axis thereof that forms a proximal section of the catheter system, a second catheter member having a third lumen forming a distal section of the catheter system and coupled to a distal end of the first catheter member, an inflatable balloon coupled at its proximal end to a distal end of the first catheter member and at its distal end to a proximal end of the second catheter member, a first lumen of the first catheter member terminating within the inflatable balloon to communicate an inflation fluid to an area within the inflatable balloon and a second lumen of the first catheter member being in fluid flow communication with the third lumen of the second catheter member; an atraumatic guiding tip coupled to a distal end of the third lumen of the second catheter member; and a third catheter member having at least one lumen passing longitudinally therethrough, the third catheter member being disposed within each of the second lumen of the first catheter member and the third lumen of the second catheter member and passing there-through.

Preferred embodiments of the present invention have been actively conceptualized, modeled, iterated and working prototypes produced of multiple REBOA related devices. The concepts are responses to the following lists of clinical needs, including (1) Pushing back the ischemic injury envelope, (2) Reperfusion mitigation/prevention, (3) Ischemia mitigation/prevention, (4) Hypertension mitigation/prevention, (5) Traumatic brain injury ("TBI") mitigation/prevention, (6) Pre-hospital use, (7) Rapid deployment, (8) Field specific packaging, (9) Easier to use, and (10) Lower profile

Preferred embodiments of the present invention may also include:

Infusion Catheter

The infusion catheter or occlusion catheter system is a preferably multi-purpose, low profile, such as approximately five French (5 Fr) catheter, although the preferred system is not limited to catheters having this size. The preferred systems may be used independently or in conjunction with a REBOA catheter from the contralateral leg to administer fluids (i.e. reperfusion mitigation/ischemia prevention) or gas/fluid angiography below the REBOA occlusion balloon. The combination of the P-tip and hybrid shaft design preferably allow for proper placement in large vessels without needing to be inserted over a guidewire. The infusion catheter of the preferred embodiments may be compatible with power injection.

Smart REBOA

Smart REBOA is a REBOA accessory that can preferably be connected to and used with any REBOA catheter. Smart REBOA preferably controls the occlusion balloon inflation volume and inflation/deflation rate, using the patient's own vital signs as feedback. A validated algorithm is capable of using feedback from a variety of vital signs (i.e. heart rate, respiration rate, pulse oxygenation, blood pressure, etc.) to modulate the inflation volume of the balloon for an optimized REBOA procedure.

Decision Support REBOA (DS REBOA)

DS REBOA builds upon the preferred Smart REBOA concept. DS REBOA preferably combines the real time

12

monitoring and feedback of the Smart REBOA device with a historical and constantly updated database of known REBOA cases and outcomes to provide forward looking possible diagnoses and other decision support information (collectively called 'prognostics') through sophisticated statistical means. The DS REBOA also preferably provides a patient specific, real time step through clinical practice guide and other decision support mechanisms to assist the clinician.

Power Injection Capable REBOA (PIC REBOA)

PIC REBOA is preferably a REBOA Catheter that is approximately seven French (7 Fr) compatible and offers the same or similar features as the ER-REBOA Catheter (balloon occlusion, built-in arterial line, guidewire and fluoroscopy-free), but preferably adds the ability to perform power injections. The PIC REBOA is not limited to being seven French (7 Fr) compatible.

REBOA with Above & Below Balloon Lumens (ABBL REBOA)

ABBL REBOA is a REBOA Catheter that preferably offers the same or similar features as the ER-REBOA Catheter, but contains an additional lumen below the balloon for fluid/gas injections/sampling. ABBL REBOA is preferably compatible with power injectors for either above or below the balloon angiography.

REBOA with a Partial Occlusion Balloon (POB REBOA)

POB REBOA is a REBOA Catheter that preferably provides the clinician the ability to selectively control the degree of occlusion. Balloon design preferably permits minimal occlusion, such as ten percent (10%), up to total or near total occlusion, such as one hundred percent (100%).

REBOA with Large Bore Lumen for High Flow Rate Infusions (LBL REBOA)

LBL REBOA is a REBOA Catheter that preferably includes the same or similar features as the ER-REBOA Catheter (balloon occlusion, built-in arterial line, guidewire and fluoroscopy-free), but has a larger diameter central lumen that provides the ability to perform high flow rate infusions (i.e. selective aortic arch perfusion (SAAP)).

ECMO/Cryogenic/CRRT Adjuncts

Extra Corporeal Membrane Oxygenation ("ECMO") continues to become more clinically widespread. ECMO is preferably used in cases where the patient's lungs have been damaged or temporarily compromised, by bypassing the patient's lungs through the use of catheters to shunt the blood away from the damaged organs and through an ECMO device instead. Recent advances have reduced the size, weight and cost of ECMO, while improving its efficacy. Combining the REBOA technology with various ECMO catheters to provide a "one stop" solution for patients with lung or other major organ compromise in the setting of hemorrhage may become a clinically preferred method. Similar combinations with existing and proposed cryogenic devices and Continuous Renal Replacement Therapy (CRRT) systems also are contemplated.

13

REBOA with Anti-Hypertension Feature
(A-HYPER REBOA)

A-HYPER REBOA is a REBOA accessory that uses the patient's own supra-occlusion blood pressure to control the inflation/deflation of the REBOA balloon is contemplated. Should the patient's supra occlusion blood pressure rise dangerously high, potentially increasing the risk of hemorrhagic stroke, the system preferably automatically and temporarily deflates the REBOA balloon until the blood pressure drops to a safer level.

REBOA with Anti-Hypotension Feature (A-HYPO
REBOA)

A-HYPO REBOA is a REBOA accessory that uses the patient's own blood pressure to control balloon deflation during the removal of the REBOA balloon is contemplated. If the patient's blood pressure should drop dangerously low during the deflation of the REBOA balloon, the system may automatically re-inflate the balloon to restore adequate pressure to the vital organs. The system will then preferably begin a pre-programmed cycle of deflation/repeat inflations until the patient can be weaned completely off occlusion.

Inflation Safety Device (ISD)

The ISD is a REBOA accessory that can preferably be used with the ER-REBOA Catheter to decrease the risk of over-inflating the balloon during fluoroscopy-free balloon inflation (i.e. field use). The ISD is preferably connected in line between the ER-REBOA Catheter and the inflation syringe. The user advances the syringe plunger, pausing occasionally to read the pressure gauge. When the pressure gauge needle comes to rest in the 'blue zone' or a preferred marked zone of the pressure gauge, proper occlusion has generally been achieved.

Infection Control Sleeve (ICS)

The infection control sleeve ("ICS") is a REBOA accessory that is preferably pre-loaded on the ER-REBOA Catheter to minimize the risk of infection when the device is deployed in austere environments. The ER-REBOA Catheter with the ICS preferably remains compatible with seven French 7 Fr components and has the same or similar features (balloon occlusion, built-in arterial line, guidewire and fluoroscopy-free) to other preferred REBOA systems and catheters.

Ruggedized, Low Volume (Cube) Packaging
(REBOA w/LV PKG)

REBOA w/LV PKG is a modified ER-REBOA Catheter and redesigned, ruggedized, low volume package (approximately twenty-five percent (25%) of the current ER-REBOA package volume) specific configured for field use. The ER-REBOA Catheter preferably remains compatible with seven French (7 Fr) components and has the same or similar features (balloon occlusion, built-in arterial line, guidewire and fluoroscopy-free) to other preferred REBOA systems.

Zone 3 REBOA (Z3 REBOA)

The Z3 REBOA is a REBOA Catheter preferably designed for Zone 3 placement relative to the aorta. The Z3 REBOA is preferably six French (6 Fr) compatible that has

14

a shorter shaft length and an optimized balloon for generally less cumbersome Zone 3 placements.

Ultra-Low Profile REBOA (ULP REBOA)

The ULP REBOA is a preferred REBOA system that is compatible with six French or less (≤ 6 Fr) components. The ULP REBOA is preferably designed and configured for faster placement and improved ease-of-use. The balloon is filled with carbon dioxide (CO_2), preferably using a pressure regulated system that preferably inflates the balloon to a set pressure, regardless of the diameter of the aorta. The use of the carbon dioxide (CO_2) also enables the catheter shaft to be ultra-low profile, such as less than or equal to six French (≤ 6 Fr) compatible. An electronic, catheter-based pressure sensor typically requires no priming/flushing, so arterial line measurements can preferably be taken as soon as the device is inserted.

REBOA Gas Balloon Inflator (GBI)

The GBI is a REBOA accessory that is preferably used with the ER-REBOA Catheter to provide rapid balloon inflation/deflation. The GBI preferably fills the balloon with carbon dioxide (CO_2) gas to a set pressure, regardless of the vessel diameter, preferably making pre-hospital balloon inflation less technique dependent.

Guidewire Compatible REBOA (GWC REBOA)

The GWC REBOA is a preferred REBOA Catheter that can be used with a guidewire but doesn't require one and is preferably compatible with seven French (7 Fr) components. The preferred GWC REBOA allows the user to leave behind a guidewire when finished with REBOA for additional procedures. The GWC REBOA Catheter preferably, but not necessarily, remains seven French (7 Fr) compatible and has the same or similar features (balloon occlusion, built-in arterial line, guidewire and fluoroscopy-free) to other preferred REBOA systems.

When a fluid is used as the pressure source to activate the occlusion member, such as to fill an occlusion balloon, that fluid may be a liquid, including water, saline, contrast medium or any combination thereof, or may be a gas, including carbon dioxide, helium, air or oxygen.

It would be desirable to develop a system that intermittently and automatically releases an occlusion by releasing apposition of an occlusive member against the vascular wall and allowing perfusion past the occlusion member in response to a physiological parameter, then reestablishing occlusion in response to the same physiological parameter.

The methods, systems, and apparatus are set forth in part in the description which follows or can be learned by practice of the methods, apparatus, and systems. The advantages of the methods, apparatus, and systems will be realized and attained by means of the elements and combinations particularly pointed out in the appended claims and the below description. It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory only and are not restrictive of the methods, apparatus, and systems, as claimed or described.

BRIEF DESCRIPTION OF SEVERAL VIEWS OF
THE DRAWINGS

The foregoing summary, as well as the following detailed description of the invention, will be better understood when

15

read in conjunction with the appended drawings. For the purpose of illustrating the invention, there are shown in the drawings embodiments which are presently preferred. It should be understood, however, that the invention is not limited to the precise arrangements and instrumentalities shown. In the drawings:

FIG. 1 is a top perspective view of a first preferred embodiment of an occlusion catheter system in accordance with the present invention;

FIG. 2 is an enlarged perspective view of the occlusion catheter system of FIG. 1 taken from within circle 2 of FIG. 1 with a transparent occlusion balloon;

FIG. 3 is a cross-sectional view the occlusion catheter system of FIG. 1, taken along line 2-2 of FIG. 2.

FIG. 4 is an enlarged perspective view of the occlusion catheter system of FIG. 1, taken from within circle 4 of FIG. 1 with a transparent occlusion balloon;

FIG. 5 is a cross-sectional view the occlusion catheter system of FIG. 1, taken along line 5-5 of FIG. 2 directly into the page of FIG. 2;

FIG. 6 is a cross-sectional view of the occlusion catheter system of FIG. 1, taken along line 6-6 of FIG. 1;

FIG. 7 is a combination partial cross-sectional view of the occlusion catheter system taken along line 7-7 of FIG. 1 and a magnified top perspective view of the occlusion catheter system near a proximal end of the occlusion balloon of the occlusion catheter system of FIG. 1;

FIG. 8 is a cross-sectional view of the occlusion catheter system of FIG. 1, taken along line 8-8 of FIG. 1;

FIG. 9 is a magnified top perspective view of a portion of a second preferred embodiment of the occlusion catheter system proximate a occlusion balloon of the second preferred occlusion catheter system of the present invention;

FIG. 9A is a cross-sectional view of the occlusion catheter system of FIG. 9, taken along line 9A-9A of FIG. 9.

FIG. 9B a combination partial cross-sectional view of the occlusion catheter system taken along line 9B-9B of FIG. 9 and a magnified top perspective view of the occlusion catheter system near a proximal end of the occlusion balloon of the occlusion catheter system of FIG. 9;

FIG. 9C is a cross-sectional view of the occlusion catheter system of FIG. 9, taken along line 9C-9C of FIG. 9;

FIG. 9D is a cross-sectional view of the occlusion catheter system of FIG. 9, taken along line 9D-9D of FIG. 9, wherein the lumens and catheters are sized differently than the embodiment of FIG. 9C;

FIG. 10 is a magnified top perspective view of an alternative embodiment of a distal portion of the occlusion catheter system of FIG. 9;

FIG. 11 is a magnified top perspective view an atraumatic tip of the occlusion catheter system of FIG. 10, taken from within shape 11 of FIG. 10;

FIG. 12 is a top perspective view of a third preferred embodiment of an occlusion catheter system of the preferred present invention;

FIG. 13 is an enlarged top perspective view of the occlusion catheter system of FIG. 12, taken from within shape 13 of FIG. 12;

FIG. 14 is a cross-sectional view of the occlusion catheter system of FIG. 13, taken along line 14-14 of FIG. 13;

FIG. 15 is a top perspective view of the occlusion catheter system of FIG. 12, taken from within shape 15 of FIG. 1;

FIG. 16 is a cross-sectional view of the occlusion catheter of FIG. 12, taken along line 16-16 of FIG. 12;

FIG. 17 is a cross-sectional view of the occlusion catheter system of FIG. 12, taken along line 17-17 of FIG. 12;

16

FIG. 18 is a cross-sectional view of the occlusion catheter system of FIG. 12, taken along line 18-18 of FIG. 12;

FIG. 19 is a diagrammatic rendering of a first preferred pressure regulation system for automatically releasing occlusion by any of the occlusion catheter systems of the first, second and third preferred embodiments of FIGS. 1-18;

FIG. 20 is a diagrammatic rendering of a second preferred pressure regulation system for controlling the occlusion balloon of any of the occlusion catheter system of the first, second and third preferred embodiments of FIGS. 1-18;

FIG. 21 is a diagrammatic rendering of a third preferred pressure regulation system for controlling the occlusion balloon of any of the occlusion catheter system of the first, second and third preferred embodiments of FIGS. 1-18;

FIG. 22 is a diagrammatic rendering of a fourth preferred pressure regulation for controlling the occlusion balloon of any of the occlusion catheter system of the first, second and third preferred embodiments of FIGS. 1-18;

FIG. 23 is a top perspective view of a first preferred embodiment of an alternative occlusion perfusion balloon system that may be utilized with any of the occlusion catheter systems of the first, second and third preferred embodiments of the occlusion catheter system of FIGS. 1-18, wherein the occlusion perfusion balloon is in a minimal inflation configuration;

FIG. 24 is a rear elevational view of the occlusion perfusion balloon system of FIG. 23;

FIG. 25 is a top plan view of the occlusion perfusion balloon system of FIG. 23;

FIG. 26 is a top perspective view of the occlusion perfusion balloon system of FIG. 23, wherein the occlusion perfusion balloon is in a low inflation volume configuration;

FIG. 27 is a top perspective view occlusion perfusion balloon system of FIG. 23, wherein the occlusion perfusion balloon is in a medium inflation configuration;

FIG. 28 is a top perspective view of the occlusion perfusion balloon system of FIG. 23, wherein the occlusion perfusion balloon is in a full inflation configuration;

FIG. 28A is a cross-sectional view of the occlusion perfusion balloon system of FIG. 23, taken along line 28A-28A of FIG. 28;

FIG. 29A is side perspective view of a second preferred embodiment of an alternative occlusion perfusion balloon system that may be utilized with any of the occlusion catheter systems of the preferred embodiments described herein, wherein the occlusion perfusion balloon is in an inflated configuration;

FIG. 29B is a cross-sectional view taken along line 29B-29B of FIG. 29A;

FIG. 30A is a side perspective view of a third preferred embodiment of an alternative occlusion perfusion balloon system that may be utilized with any of the occlusion catheter systems of the preferred embodiments of the occlusion catheter system described herein, wherein the occlusion perfusion balloon is in an inflated configuration;

FIG. 30B is a cross-sectional view taken along line 30B-30B of FIG. 30A;

FIG. 31 is a side elevational view of fourth and fifth preferred embodiments of an alternative occlusion perfusion balloon system that may be utilized with any of the occlusion catheter systems of the preferred embodiments of the occlusion catheter systems described herein, wherein the occlusion perfusion balloon is in an inflated configuration;

FIG. 31A is a cross-sectional view of the occlusion perfusion balloon system of FIG. 31, taken along line 31A-31A of FIG. 31 in accordance with the fourth preferred embodiment;

17

FIG. 31B is a cross-sectional view of the occlusion perfusion balloon system of FIG. 31, taken along line 31A-31A of FIG. 31, wherein a restraining filament is incorporated into the occlusion perfusion balloon in accordance with the fifth preferred embodiment;

FIG. 32 is a top perspective view of a sixth preferred embodiment of an occlusion perfusion balloon system comprised of an occlusion perfusion balloon assembly that may be utilized with any of the preferred occlusion catheter systems described herein, wherein the occlusion perfusion balloon assembly is in an inflated configuration;

FIG. 32A is a cross-sectional view of the occlusion perfusion balloon system of FIG. 32, taken along line 32A-32A of FIG. 32;

FIG. 33 is a top perspective view of a seventh preferred embodiment of an occlusion perfusion balloon system that may be utilized with any of the preferred occlusion catheter systems described herein, wherein the occlusion perfusion balloon is in an inflated configuration;

FIG. 34 is a top perspective view of an eighth preferred embodiment of an occlusion perfusion balloon system that may be utilized with any of the preferred occlusion catheter systems of described herein, wherein the occlusion perfusion balloon is in an inflated configuration;

FIG. 35A is a side perspective view of a ninth preferred embodiment of an occlusion/perfusion balloon system that may be utilized with any of the occlusion catheter systems described herein, wherein the occlusion/perfusion balloon is in a partially inflated configuration within a vessel;

FIG. 35B is a side elevational view of the occlusion/perfusion balloon system of FIG. 35A, wherein the balloon is in the partially inflated configuration;

FIG. 35C is a side elevational view of the occlusion/perfusion balloon system of FIG. 35A, wherein the balloon is in a fully inflated configuration;

FIG. 35D is a side perspective view of an occlusion/perfusion balloon system in accordance with a tenth preferred embodiment that may be utilized with any of the occlusion catheter systems described herein;

FIG. 36 is a top perspective view of an occlusion catheter system in accordance with a fourth preferred embodiment of the present invention;

FIG. 36A is a cross-sectional view of the occlusion catheter system of FIG. 36, taken along line 36A-36A of FIG. 36;

FIG. 36B is a cross-sectional view of the occlusion catheter system of FIG. 36, taken along line 36B-36B of FIG. 36;

FIG. 36C is a cross-sectional view of the occlusion catheter system of FIG. 36, taken along line 36C-36C of FIG. 36;

FIG. 37 is a top perspective view of an occlusion catheter system in accordance with a fifth preferred embodiment of the present invention;

FIG. 37A is a cross-sectional view of the occlusion catheter system of FIG. 37, taken along line 37A-37A of FIG. 37;

FIG. 37B is a cross-sectional view of the occlusion catheter system of FIG. 37, taken along line 37B-37B of FIG. 37;

FIG. 37C is a cross-sectional view of the occlusion catheter system of FIG. 37, taken along line 37C-37C of FIG. 37;

FIG. 38 is a top perspective view of a catheter system in accordance with a sixth preferred embodiment of the present invention, wherein the system is particularly adaptable for use as a hemorrhage exclusion system;

18

FIG. 39 is a top perspective view of a catheter system in accordance with a seventh preferred embodiment of the present invention, wherein the system is also particularly adaptable for use as a hemorrhage exclusion system;

FIG. 39A is a cross-sectional view of the catheter system of FIG. 39, taken along line 39A-39A of FIG. 39;

FIG. 39B is a magnified top perspective view of the catheter system of FIG. 38, taken from within shape 39B of FIG. 39;

FIG. 40 is a top perspective view of a first preferred inflation control system that may be utilized with any of the occlusion catheter systems of the first, second and third preferred embodiments of the occlusion catheter system of FIGS. 1-18;

FIG. 41 is a top perspective view of a second preferred inflation control system that may be utilized with any of the occlusion catheter systems of the first, second and third preferred embodiments of the occlusion catheter system of FIGS. 1-18;

FIG. 41A is a cross-sectional view of a third preferred inflation control system that may be utilized with any of the occlusion catheter systems of the first, second and third preferred embodiments of the occlusion catheter system of FIGS. 1-18;

FIG. 42A is a side perspective view of a first preferred infection/contamination control system that may be utilized with any of the occlusion catheter systems of the first, second and third preferred embodiments of the occlusion catheter system of FIGS. 1-18;

FIG. 42B is a magnified top perspective view of the infection/contamination control system of FIG. 42A, taken from within shape 42B of FIG. 42A;

FIG. 43 is side perspective view of a catheter system in accordance with a eighth preferred embodiment of the present invention, wherein the system is adaptable for use with a guidewire;

FIG. 43A is cross-sectional view of the catheter system of FIG. 43, taken along line 43A-43A of FIG. 43;

FIG. 43B is a side perspective view of an alternative preferred catheter system in accordance with the eighty preferred embodiment of the present invention;

FIG. 43C is a cross-sectional view of the alternative preferred catheter system of FIG. 43B, taken along line 43C-43C of FIG. 43B;

FIG. 44 is bottom perspective view of an occlusion catheter system in accordance with a ninth preferred embodiment of the present invention, wherein the system is adaptable for use as a power injection compatible vascular occlusion balloon catheter; and

FIG. 45 is side elevational view of an occlusion catheter system in accordance with a tenth preferred embodiment of the present invention, wherein the system is also adaptable for use as an infusion catheter.

DETAILED DESCRIPTION OF THE INVENTION

The foregoing and other features and advantages of the invention will become more apparent from the following detailed description of exemplary embodiments, read in conjunction with the accompanying drawings. The detailed description and drawings are merely illustrative of the invention rather than limiting, the scope of the invention being defined by the appended claims and equivalents thereof.

Certain terminology is used in the following description for convenience only and is not limiting. Unless specifically

set forth herein, the terms “a,” “an” and “the” are not limited to one element but instead should be read as meaning “at least one”. The words “right”, “left”, “lower” and “upper” designate directions in the drawings to which reference is made. The words “inwardly” or “distally” and “outwardly” or “proximally” refer to directions toward and away from, respectively, the patient’s body, or the geometric center of the preferred occlusion balloon catheter and related parts thereof. The words, “anterior”, “posterior”, “superior,” “inferior”, “lateral” and related words and/or phrases designate preferred positions, directions and/or orientations in the human body to which reference is made and are not meant to be limiting. The terminology includes the above-listed words, derivatives thereof and words of similar import.

It should also be understood that the terms “about,” “approximately,” “generally,” “substantially” and like terms, used herein when referring to a dimension or characteristic of a component of the invention, indicate that the described dimension/characteristic is not a strict boundary or parameter and does not exclude minor variations therefrom that are functionally the same or similar, as would be understood by one having ordinary skill in the art. At a minimum, such references that include a numerical parameter would include variations that, using mathematical and industrial principles accepted in the art (e.g., rounding, measurement or other systematic errors, manufacturing tolerances, etc.), would not vary the least significant digit.

While the invention has been described in connection with various embodiments, it will be understood that the invention is capable of further modifications. This application is intended to cover any variations, uses or adaptations of the invention following, in general, the principles of the invention, and including such departures from the present disclosure as, within the known and customary practice within the art to which the invention pertains.

Certain terminology is used in the following description for convenience only and is not limiting. The words “lower,” “bottom,” “upper” and “top” designate directions in the drawings to which reference is made. The words “inwardly,” “outwardly,” “upwardly” and “downwardly” refer to directions toward and away from, respectively, the geometric center of the vascular occlusion catheter system, and designated parts thereof, in accordance with the present disclosure. Unless specifically set forth herein, the terms “a,” “an” and “the” are not limited to one element, but instead should be read as meaning “at least one.” The terminology includes the words noted above, derivatives thereof and words of similar import.

It should also be understood that the terms “about,” “approximately,” “generally,” “substantially” and like terms, used herein when referring to a dimension or characteristic of a component of the invention, indicate that the described dimension/characteristic is not a strict boundary or parameter and does not exclude minor variations therefrom that are functionally similar. At a minimum, such references that include a numerical parameter would include variations that, using mathematical and industrial principles accepted in the art (e.g., rounding, measurement or other systematic errors, manufacturing tolerances, etc.), would not vary the least significant digit.

Vascular Occlusion Systems

Furthermore, while the invention is described as a balloon catheter occlusion system, it will be understood that the described variants of the preferred balloon catheter system

may be used clinically for a variety of different therapeutic or diagnostic indications involving vascular interventions, including, for example and without limitation, arterial occlusion, angioplasty, stent delivery, atherectomy, drug delivery, imaging or the like. In accordance with an exemplary and preferred embodiment, the preferred balloon catheter system is well suited for use as an arterial occlusion balloon catheter, and in particular an aortic occlusion balloon catheter. Applications making advantageous use of embodiments of the invention may use any suitable access site for vascular intervention. For example, applications of the catheter system may involve access at the femoral artery, the brachial artery, the subclavian artery, or any other blood vessel suitable for use as an access site for catheterization, including venous vessels.

Moreover, it will be understood that while a balloon is referred to herein as an example of occlusion member, other types of occlusion members are contemplated as being expressly within the scope of the present invention. In addition to balloons, the occlusion members may include stents, coils, grafts, sheaths, cages, plugs, supported or unsupported membranes, or the like. The occlusion member, including the occlusion balloons, may be fabricated of biocompatible polymer or biocompatible metal, or combinations thereof, and may be woven or non-woven in structure. Biocompatible metals include, but are not limited to, stainless steel, titanium, nitinol, cobalt, vanadium, aluminum, nickel, tantalum, zirconium, chromium, silver, gold, silicon, magnesium, niobium, scandium, platinum, cobalt, palladium, manganese, molybdenum and alloys thereof, such as cobalt-chromium-molybdenum or zirconium-titanium-tantalum alloys. The metals and/or the polymers may be elastic, shape memory or superelastic. More recent advanced materials may also be used, including carbon fibers, carbon nanotubes or carbon composites, such as carbon/polyetheretherketone (PEEK). In the present application, when the term “balloon” is used it is intended to mean a fluid fillable member capable of expanding from a first smaller diameter to a second larger diameter under the influence of fluid introduced into the balloon. Unless otherwise stated, a balloon is not limited in size, shape, geometry, material or construction. When used in this application, the term “occlusion member” is intended to be inclusive of balloons and other structures, including stents, coils, grafts, sheaths, cages, plugs or supported or unsupported membranes.

In one aspect of the invention, a pressure relief apparatus for a balloon catheter is provided. The balloon catheter includes a shaft having a balloon attached to the distal end of the shaft, an inflation/deflation lumen for inflating and deflating the balloon and a pressure relief port. The pressure relief port may alternatively be formed through the wall of the inflation/deflation lumen, through the wall of the proximal hub, or may be part of the fluid pathway that couples to the proximal hub. A pressure relief member is secured either across or within the pressure relief port to form a fluid tight seal. The fluid tight seal is configured to open or fail (e.g. open, burst, rupture, tear or leak) at a predetermined pressure to release pressure from the inflation/deflation lumen through the pressure relief port. The predetermined pressure may be less than or equal to the rated burst pressure of the balloon.

In one variation, the pressure relief port comprises a first outwardly opening passage and a second passage in fluid communication with the first passage. The second passage extends inwardly from the first passage and opens into the inflation/deflation lumen. In this variation, the cross-section

21

tional area of the first passage may be larger than the cross-sectional area of the second passage.

In one embodiment, a wall extends radially between an inside end of the first passage of the pressure relief port and an outside end of the second passage of the pressure relief port. The pressure relief member may be disposed adjacent the wall and across the outside end of the second passage of the pressure relief port to block the pressure relief port and form a fluid tight seal. The pressure relief member may be a plastic film, a thin metallic film, a pop-off valve or other similar biased valve. The bias of the pressure relief member is less than or equal to a predetermined pressure known to protect the device from overpressure and burst and to protect the patent from injury.

In another aspect, a pressure relief apparatus for a balloon catheter having a balloon with a rated burst pressure includes a proximal hub adapted for connection to a proximal end portion of a balloon catheter shaft wherein a pressure relief port is formed in the proximal hub. In one embodiment, the proximal hub may comprise a plastic body that defines an inflation/deflation lumen and a may or may not include guide wire lumen or a working lumen.

The proximal hub may be formed from a substantially rigid material and includes a wall defining the inflation/deflation lumen for directing a fluid into and from an inflation/deflation lumen of the catheter shaft. In this alternative embodiment, the proximal hub includes a pressure relief port formed through the wall of the hub and a pressure relief member disposed across or in the pressure relief port, forming a fluid tight seal across the pressure relief port. The pressure relief member is configured to open or fail, (e.g. open, rupture, tear, burst or leak), at a predetermined pressure to release pressure from the inflation/deflation lumen through the pressure relief port.

In the case of an occlusion balloon, it is preferable that the balloon be of a compliant or partially compliant balloon material and typically formed relatively distensible plastic or polymer material. The balloons may also be constructed of substantially compliant or partially compliant polymeric, biocompatible materials, such as PBAX or other related polymers. The balloon may alternatively be constructed of a non-compliant material, which will typically expand less than about ten percent (10%), and more typically less than about five percent (5%), when pressurized from their rated operating pressure to the balloon's rated burst pressure.

Where an occlusion balloon is the occlusion member, the proximal and distal ends of the balloon may be attached to the catheter shaft using techniques known in the art, for example, with an adhesive such as a medical grade epoxy adhesive or may be refloxed to become an integral part of the catheter shaft wall.

In the following description, when reference is made to the terms "proximal" or "proximally" it is intended to mean a portion or component of the preferred vascular occlusion catheter system that is oriented away from the body into which the system is or is intended to be placed. Conversely, when reference is made to the terms "distal" or "distally" it is intended to mean a portion or component of the preferred balloon catheter system that is oriented toward the body into which the system is or is intended to be placed. Thus, for example, the guiding atraumatic tip described hereinafter is located at a distal end of the balloon catheter system, while the proximal hub is located at a proximal end of the balloon catheter system.

As shown in the accompanying figures, the vascular occlusion catheter system 100 generally includes a catheter assembly having a first catheter member 130 having a first

22

lumen 230, a second catheter member 110 having a second lumen 210, a third catheter member 120 having a third lumen 220, an occlusion member 140, a proximal hub 190 and a guiding atraumatic tip 150. The first lumen 230 of the first catheter member 130 extends longitudinally through the first catheter member and is coupled at its proximal end to the proximal hub 190 and at its distal end to a proximal section of the third catheter member 120 and in communication with the third lumen 220 of the third catheter member. The second lumen 210 of the second catheter member 110 also extends longitudinally through the second catheter member 110, and terminates in a first port 160 distal to a proximal end of and within a space 142 at least partially bounded by the occlusion member 140, best seen in FIGS. 9 and 9A. Where the occlusion member 140 is a balloon, the second lumen 210 is in communication with the space 142 bounded by the balloon 140 and conveys inflation fluid to and from the balloon 140 from a source external to the balloon catheter system 100. The third catheter member 120 is coupled at a proximal end thereof to a distal end of the first catheter member 130 such that the third lumen 220 of the third catheter member 120 is in communication with the first lumen 230 of the first catheter member 130. As best seen in FIG. 1, the second catheter member 110 and the third catheter member 120 are positioned in longitudinal co-axial spaced apart relationship from one and other along a longitudinal axis 131 of the first catheter member 130 thereby defining an intermediate region 115 of the first catheter member 130 within the space 142 that is not covered by either the second catheter member 110 or the third catheter member 120.

When a balloon is the occlusion member 140, balloon 140 is attached, at its proximal end 144 to a distal end of the second catheter member 110 and at its distal end 146 to a proximal end of the third catheter member 120. Referring to FIGS. 2-5, a proximal radio opaque marker 158 may be affixed to the first catheter member 130 at or near the first port 160, which is near the attachment position of the inflatable balloon at the proximal end 144 of the balloon 140. A distal radio opaque marker 159 may be affixed to the first catheter member 130 near the attachment position on the distal end 146 of the balloon 140. The proximal and distal radio opaque markers 158, 159 may be implemented as bands made of a radio opaque material. In one example, the radio opaque material is a metal that is radio opaque such as stainless steel, or an alloy, such as a platinum iridium alloy. In another example, the proximal and distal radio opaque markers 158, 159 may be sections of the catheters that have been impregnated with radio opaque material such as for example stainless steel or a suitable alloy. In another example, the proximal and distal radio opaque markers 158, 159 may be implemented as bands or sections of plastic or a polymer such as PEBAX that has been mixed with barium sulfate. The implementation of the proximal and distal radio opaque markers 158, 159 on the catheter system would aid in visualization of the balloon position within the vasculature using fluoroscopy or x-ray.

When a balloon is used as the occlusion member 140, in operation, balloon 140 is inflated by introducing an inflation fluid, such as saline, from an external source, such as a syringe, coupled to the proximal hub 190, into and through the second lumen 210, out of the first port 160 and into the space 142 within the balloon 140. As is known in the art, the inflation fluid is introduced until the balloon 140 is inflated to a desired diameter or a desired fluid pressure of the inflation fluid is achieved, or both. Deflation of the balloon 140 is simply the reverse process of withdrawing the infla-

23

tion fluid from the space 142 of the inflation balloon 140. In its deflated or collapsed state, the inflation balloon 140 will be positioned either within or adjacent to the intermediate region 115 of the first catheter member 130, thereby providing a lower profile to the entire balloon catheter system 100.

When a fluid is used as the pressure source to activate the occlusion member, such as to fill an occlusion balloon, that fluid may be a liquid, including water, saline, contrast medium or any combination thereof, or may be a gas, including carbon dioxide, helium, air or oxygen. Catheter balloons may be inflated with gas, rather than liquid, because the balloon can be inflated and deflated more quickly than a comparable volume of saline or other liquid inflation media. Although air is relatively easy to load into an inflation device, air is not an ideal inflation medium, because air does not rapidly dissolve in blood. In the event that the balloon bursts or leaks, bubbles could be formed in the arterial blood, impeding blood flow. In addition, as nitrogen is a chief component of air, nitrogen has thrombogenic properties that may present clinical risks in the event the balloon bursts. Accordingly, it is desirable to use a gas other than air and to prevent air contamination of the gas used. A preferable gas used for balloon inflation is either carbon dioxide or helium.

As will be described in more detail hereinafter, with exemplary reference to FIGS. 19-22, the present invention also includes alternative embodiments of occlusion control systems that regulate the position of the occlusion member 140 and the apposition of the occlusion member 140 against a vascular wall surface. It is understood that when the occlusion member 140 is at least partially in non-apposition with the vascular wall surface, that fluid flow or perfusion past the occlusion member may or will occur. This fluid flow or perfusion may be of circulatory blood, or may be of fluids introduced through the preferred vascular occlusion catheter system, or through another fluid introduction system, such as a catheter.

The third catheter member 120 is depicted more particularly in FIGS. 4-5. The third catheter member 120 is coupled at its proximal end concentrically about a distal end of the first catheter member 130. A plurality of side ports 170 pass through a side wall of the third catheter member 120 and provides fluid communication between the third lumen 220 and external environments proximate the external surface of the third catheter member 130, such as the inside of the patient's major vessel when inserted into the patient. The distal end of the first catheter member 130 is preferably positioned within the third lumen 220 and does not occlude the plurality of side ports 170, but terminates proximal to the plurality of side ports 170 such that fluid may be freely communicated between the first lumen 230, the third lumen 220 and the plurality of side ports 170 to either introduce fluid or withdraw fluid through the plurality of side ports 170. The plurality of side ports 170 may also be utilized for power injection of a contrast medium into the major vessel of the patient distally relative to the occlusion member 140, as will be described in further detail herein. It will also be understood by those skilled in the art that maintaining fluid communication between the first lumen 230, the second lumen 220 and the plurality of side ports 170 also permits introduction of tethered sensors, such as flow sensing wires, pressure sensing wires, ischemia sensors or the like to the distal end of the balloon catheter system 100.

Finally, a guiding atraumatic tip 150 is coupled to a distal end section of the third catheter member 120. The guiding atraumatic tip 150 may be made of an elastic, shape memory

24

and/or superelastic material, such as a metal or polymer. A reinforcing member 152 (depicted in phantom) may optionally be included either within the guiding atraumatic tip 150 or wound about an external surface of the guiding atraumatic tip 150 to offer additional reinforcement to the tip 150. A proximal end of the guiding atraumatic tip 150 is coupled to a distal end of the third lumen 220 of the third catheter member 120 and a distal end of the guiding atraumatic tip 150 projects distally from the third catheter member 120 and preferably has a generally circular profile when viewed from the side in a relaxed configuration. The atraumatic tip 150 preferably curves proximally from the longitudinal axis 131 upwardly and then back toward the central longitudinal axis 131 of the balloon catheter system 100, but leaves an unconnected end 161 of the distal end of the guiding atraumatic tip 150 as it returns to a position proximate the longitudinal axis 131. The atraumatic tip 150 is designed and configured to permit the tip 150 to assume a linear or delivery configuration co-axial with the central longitudinal axis 131 of the balloon catheter system 100 for delivery and introduction into the patient's vessel through a catheter. Once the atraumatic tip 150 is introduced into the vessel and emerges from the introduction catheter, the atraumatic tip 150 preferably returns to the relaxed configuration to inhibit introduction of the catheter system 100 into smaller vessels as it moves into the patient.

In the first embodiment of the preferred balloon catheter system 100 illustrated in FIGS. 1-8, the balloon catheter system 100, when the inflatable balloon 140 is in an uninflated condition, is of sufficiently small cross-segmental dimension to pass through a 6 to 8 French (2-2.67 mm)-percutaneous sheath, such as, for example 7 French (2.33 mm). Thus, the balloon catheter system 100 has a greatest outer diameter, when the inflatable balloon 140 is uninflated, of less than 2-2.67 mm. It will be understood by those skilled in the art that the balloon catheter system 100 is not limited to a dimension sufficient to pass through a 2-2.67 mm (6 to 8 French) percutaneous sheath, but that such lower profile or smaller is generally considered desirable to enable passage of a balloon catheter system 100 through tortuous vasculature and to a desired position within the body for purposes of arterial occlusion. The balloon catheter system 100 is, therefore, not intended to be limited to this dimensional size, but may be made of smaller or larger dimension as desired or needed.

In one embodiment of the invention, the first catheter member 130 is formed of stainless steel metal and is radio opaque, in accordance with another embodiment of the invention, it is constructed of nitinol and in accordance with still another embodiment of the invention it is formed of biocompatible polymers. The first catheter member 130 lends columnar strength to the balloon catheter system 100 and provides a functional backbone for carrying the second catheter member 110, the third catheter member 120 and the inflatable balloon.

The outer diameter of the first catheter member 130 is smaller than the inner diameter of the second lumen 210 of the second catheter member 110, thereby forming an annular space 212 between the outer surface of the first catheter member 130 and the inner surface of the second catheter member 110, as best shown in FIG. 7.

In one embodiment of the invention, the distal end of the second catheter member 110 may have a tapering or narrowing diameter of the outside surface and/or the second lumen 210 diameter. Preferably, there is a minimal amount of narrowing on the second catheter member 110 and the proximal lumen 210 to allow the annular space 212 to

25

remain sufficiently large down the length of the second catheter member **110** to permit adequate flow of the inflation fluid through the annular space **212**.

Turning now to FIGS. 4-5, the distal portion of the balloon catheter system **100** is illustrated. The first lumen **230** of the first catheter member **130** may be used as a pressure monitoring line, such as by using a fluid column therein to sense pressures through the plurality of side ports **170**. The first lumen **230** may alternatively be used to introduce or withdraw fluids, such as drugs, contrast media or blood through the plurality of side ports **170**. Referring to FIG. 5, the outer surface of the first catheter member **130** is coupled to at least a portion of the inner surface of the distal lumen **220**, such that there is no annular space between the outer surface of the first catheter member **130** and the inner surface of the second lumen **220**. In one embodiment, the portion of the inner surface of the distal lumen **220** may be the length of the second lumen **220**. Referring now to FIG. 4, the third catheter member **120** or the proximal shaft of the atraumatic tip **150** may include a plurality of segments of distally decreasing durometer polymer to provide a step-down transition to the guiding atraumatic tip **150**. The number of step down durometer segments may be between one (1) and six (6) and may step down in decreasing fashion by regular or irregular increments, such, for example 75D, 63D, 55D, 40D, etc. Alternatively, the third catheter member **120** may be made of a single durometer polymer, but having distally tapering wall thicknesses to impart a flexibility gradient to the third catheter member **120**. The plurality of segments of decreasing durometer plastic may be abutted and be bonded together or may be manufactured from a single extrusion including decreasing durometer hardness.

Referring now to FIG. 5, the guiding atraumatic tip **150** is shown in its unstrained and undeformed state as it would assume when in the body. The guiding atraumatic tip **150** is used to minimize trauma to or perforation of the vasculature as the balloon catheter system **100** is advanced through the patient's tortuous anatomy, and to prevent departure from an intended vessel path, such as diversion into an undesired branch vessel. The size, shape and material of the distal section of the tip **150** are such that it will not pass into collateral vessels during delivery. The guiding atraumatic tip **150** has a constrained state when passing through an introducer sheath in which the distal section of the tip **150** is substantially linear and co-axial with the longitudinal axis **131** of the balloon catheter system **100**, and a relaxed state, as depicted, which is assumed upon exiting the introducer sheath and entering a blood vessel. In one embodiment, the guiding atraumatic tip **150** may be formed of an elastomeric, shape memory or superelastic material, including metals and polymer. In another embodiment, the guiding atraumatic tip **150** may have a reinforcing elastic, shape memory or superelastic core **152** which aids in transition between the unstressed state and the stressed state of the guiding atraumatic tip **150**. In accordance with an exemplary embodiment of the tip **150**, the outer diameter of the guiding atraumatic tip **150** (in the relaxed state) may be between 1-7 mm, preferably between 2-6 mm and most preferably between 4-6 mm.

Turning now to FIG. 6, the proximal portion of the balloon catheter system **100** is illustrated. The second catheter member **110** is coupled to the proximal hub **190** and the distal end of the first catheter member **130** may be operably coupled to the proximal hub **190** at a proximal bonding site using an adhesive **180** to bond an inner wall surface of the proximal hub **190** to an outer wall surface of the first catheter member **130**. As illustrated, the proximal hub **190** has two

26

fluid pathways **192** and **194**. A first fluid pathway **192** communicates with the first lumen **230** of the first catheter member and a second fluid pathway **194** communicates with the second lumen **210** of the second catheter member **120**. It will be understood that the proximal hub **190** may be configured to have more than two fluid pathways, with each fluid pathway communicating with a different lumen in the balloon catheter system **100**. The first fluid pathway **192** of the proximal hub **190** may be connected to an external pressure sensor, which would transduce pressure from a fluid column within the first lumen **230** and through the plurality of side port **170** (FIG. 5).

Referring to FIGS. 1-5, in the first preferred embodiment, the balloon catheter system or occlusion catheter system **100** also includes the plurality of side ports **170** positioned between the occlusion member **140** and the atraumatic tip **150** in the third catheter member **120**, the proximal shaft of the atraumatic tip **150** and/or the first catheter member **130**. The plurality of side ports **170** preferably facilitates power injection of a contrast medium into the patient's major vessel distally relative to the occlusion member **140** during use. Such power injection may be utilized for procedures such as angiography or arteriography. In the first preferred embodiment, the plurality of side ports **170** include a first side port **170a**, a second side port **170b**, a third side port **170c**, a fourth side port **170d**, a fifth side port **170e** and a sixth side port **170f**. The plurality of side ports **170** is not limited to including six (6) side ports **170a**, **170b**, **170c**, **170d**, **170e**, **170f** and the occlusion catheter system **100** may include more or less side ports **170a**, **170b**, **170c**, **170d**, **170e**, **170f** and the plurality of side ports **170** may be sized and configured in nearly any manner desired by the designer and/or medical technician for pressure sensing, power injection or other related procedures utilizing the plurality of side ports **170**.

Turning now to FIGS. 9 and 9A-9D, an alternative or second preferred embodiment of the balloon catheter system **300** is illustrated. The balloon catheter system **300** includes generally a catheter assembly including a first catheter member **310** having at least two lumens **210**, **330** passing longitudinally through the first catheter member **310**, a second catheter member **320** having a single lumen **230** passing longitudinally through the second catheter member **320** and an inflatable balloon **140**. The first catheter member **310** is coupled at its proximal end to a proximal hub **190** (not shown) and at a distal end thereof to a proximal end of the inflatable balloon **140**. The second catheter member **320** is coupled at its distal end to a proximal end of the first catheter member **310** such that one of the first lumen **210** or the second lumen **330** is in fluid flow communication with the second catheter member **320**. The other of the first lumen **210** or the second lumen **230** terminates at the distal end of the first catheter member **310**. For purposes of illustration only and for clarity in the following description, it will be assumed that second lumen **330** terminates at the distal end of the first catheter member **310** and has a distal port opening **160**, it will also be assumed that the first lumen **210** is in fluid flow communication with the second catheter member **320**. As with the first embodiment of the balloon catheter system **100** described above, the second embodiment of the balloon catheter system **300**, when the inflation balloon **140** is in an uninflated condition, is of a sufficiently small cross-sectional diameter to pass through a 6-8 French (2-2.67 mm)-percutaneous sheath, such as, for example, 7 French (2.33 mm). Thus, the balloon catheter system **300** has a greatest outer diameter, when the inflatable balloon **140** is uninflated, that is less than 2-2.67 mm. It will be

27

understood by those skilled in the art that the balloon catheter system **100** is not limited to a dimension sufficient to pass through a 2-2.67 mm (6 to 8 French) percutaneous sheath, but that such lower profile or smaller is generally considered desirable to enable passage of a balloon catheter system **300** through tortuous vasculature and to a desired position within the body for purposes of arterial occlusion. The balloon catheter system **300** is, therefore, not intended to be limited to this dimensional size, but may be made of smaller or larger dimension as desired or needed.

Referring now to FIG. 9A, the first catheter member **310** includes first lumen **330** and a second lumen **210**. The second catheter member **320** includes a first lumen **220**. The first catheter member **310** terminates at its distal end within the space defined under the balloon **140**, where it is both coupled to the second catheter member **320** and terminates with an open port **160** in fluid communication with lumen **330**, permitting fluid to be delivered to and from the balloon **140** for inflation and/or deflation. In accordance with an alternative embodiment, the distal end of the first catheter member **310** may, optionally, be tapered, such as by narrowing the wall thickness of the catheter member **310** or by crimping the first catheter member **310** to a smaller diameter, thereby compressing and reducing the open area of the first lumen **330** and the second lumen **210**. If the first catheter member **310** is crimped to a tapered diameter, it is preferable that the extent of the crimping does not compress the open area of the first lumen **330** and the second lumen **210** in a manner that significantly reduces fluid flow there through of fluid flow pressures therein, particularly with the second lumen **330** when it is used for the inflation fluid for the inflation balloon **140**.

The third catheter member **130** is positioned within one of the first lumen **210** or the second lumen **330** of the first catheter member **310**. As depicted in the figures, this arrangement is illustrated with the third catheter member **130** being positioned within the first lumen **210** of the first catheter member **310** and also within the first lumen **220** of the second catheter member **320**. The outer diameter of the third catheter member **130** is less than the inner diameter of the first lumen **210** of the first catheter member **310** as well as smaller than the inner diameter of the first lumen **210** of the second catheter member **320**, such that an annular space **212** is formed therebetween as depicted in FIG. 9C. In the more distal region of the first catheter member **310**, within the region of the distal taper discussed above, the annular space **212** is compressed and either closes or is substantially closed to fluid flow, thereby effectively sealing the distal end of the first lumen **210** near the transition to the proximal attachment point of the inflatable balloon **140**, as depicted in FIG. 9A.

The third catheter member **130** passes longitudinally into the first lumen **230** of the second catheter member **320** and has a first lumen **230** passing longitudinally through the third catheter member **130**. As with the first catheter member **130** of the first alternative embodiment described above, the first lumen **230** of the third catheter member **130** permits monitoring of conditions within the body, such as arterial pressure monitoring by hydrostatic pressure within a fluid column within the first lumen **230**, or allows for the introduction of tethered sensors, such as flow sensing wires, pressure sensing wires or the like to the distal end of the balloon catheter system **300**. First lumen **230** may also be used to deliver drugs, contrast media, or permit the introduction or withdrawal of fluids to and from the body.

As with the alternative embodiment discussed above with reference to FIGS. 1-8, the embodiment depicted in FIGS.

28

9-9D may, optionally, include the second catheter member **320** being constructed of plural segments having distally increasing flexibility, such as by making the segments of distally decreasing durometer polymer or fashioning the second catheter member **320** to have a distally tapering wall thickness. The second catheter member **320** may be formed of discrete segments abutted and coupled together to form an elongated second catheter member **320** with either distally decreasing durometer or distally tapering wall thicknesses. Alternatively, the second catheter member **320** may be made by extrusion or molding polymers of distally decreasing durometer or distally tapering wall thicknesses.

As with the alternative embodiment of the balloon catheter system **100**, the second catheter member **320** includes an open port **170** that is in fluid flow communication with the first lumen **230** of the third catheter member. Similarly, as with the balloon catheter system **100**, the balloon catheter system **300** of the second preferred embodiment includes a guiding atraumatic tip (not shown in FIGS. 9-9D) as described above with reference to guiding atraumatic tip **150** of the first preferred embodiment, which is coupled to a distal end of the second catheter member **320**.

With reference to FIGS. 10 and 11, there is depicted an alternative embodiment of the guiding atraumatic tip **450**. It will be understood that guiding atraumatic tip **450** may be employed with any of the foregoing embodiments of the preferred balloon catheter system **100** or of the second preferred balloon catheter system **300**. The guiding atraumatic tip **450** is comprised generally of a polymeric cylindrical or tubular member **452** that has a distal section **454** that has been formed into a generally flattened cylinder having two generally planar opposing surfaces **455**, **457** and two generally curved opposing surfaces **458**, **459**. The two generally planar opposing surfaces **455**, **457** include an inner planar surface **455** and an outer planar surface **457**. The distal section **454** has a distally extending section **453** that projects distally and a curved section **456** continuous with the distally extending section that curves away from the central longitudinal axis **131** of the balloon catheter system **100**, **300** then proximally toward the occlusion balloon **140** and subtends a generally circular arc toward the central longitudinal axis **131** of the balloon catheter system **100**, **300**. The angle of the curve may be between about one hundred eighty degrees (180°) and three hundred fifty-five degrees (355°), more preferably between about two hundred seventy degrees (270°) and three hundred fifty degrees (350°) and even more preferably between about three hundred degrees (300°) and three hundred fifty degrees (350°) such that a gap is provided between the terminal end of the generally cylindrical flattened distal section **454** and the more proximal surface of the distal section **454**. It will also be understood that the distally extending section **453** and curved section **456** may be formed as a generally in-plane circular shape or may be formed as an out-of-plane generally helical shape, where a terminal end of the curved section **456** is laterally displaced from the central longitudinal axis **131** of the balloon catheter system **100** or balloon catheter system **300**. In this manner, the generally flattened distal section **454** is characterized by a generally circular profile. The atraumatic tip **550** preferably operates in a manner similar to the guiding atraumatic tips **150**, **350** of the previously described preferred embodiments, but is made of a polymer material without the need for a reinforcing member **152**, as described above.

In the preferred embodiment, a tip thickness T_t is defined between the inner planar surface **455** and the outer planar surface **457** and tip width W_t is defined between the oppos-

ing curved lateral surfaces **458**, **459**. The tip width W_t is preferably greater than the tip thickness T_t such that the atraumatic tip **450** is readily flexible about a central tip axis **450a**. The atraumatic tip **450** is preferably flexible about the central tip axis **450a** from the substantially circular profile in the relaxed configuration to the introduction configuration, wherein the atraumatic tip **450** is relatively straight or positioned on the longitudinal central axis **431**. In the preferred embodiment, the tip thickness T_t is less than the tip width W_t . The relatively smaller tip thickness T_t in comparison to the tip width W_t facilitates the flexing of the atraumatic tip **450** from the relaxed configuration with the substantially circular profile to the introduction configuration, wherein the atraumatic tip **450** is substantially straight and is positioned on the longitudinal central axis **431** and renders bending of the atraumatic tip **450** laterally more difficult.

A tapered transition section **451** may, optionally, be provided between the polymeric cylindrical or tubular member **452** and the generally flattened cylindrical distal section **454**. Guiding atraumatic tip **450** may be integral with the third catheter member **120** of balloon catheter system **100** or the second catheter member **320** of balloon catheter system **300**. Alternatively, guiding atraumatic tip **450** may be fabricated as a discrete member and joined to the third catheter member **120** of balloon catheter system **100** or the second catheter member **320** of balloon catheter system **300**.

The guiding atraumatic tip **450**, which may be made of polyether block amide (PBAX, Arkema, Paris France) having a durometer of forty (40D), or a similar polymer, such as polyurethane or polyethylene, that is compatible with the catheter shaft and balloon to make bonding easier and more secure. As discussed above, the guiding atraumatic tip **450** may be either cylindrical or tubular, or have a solid cylindrical section and a tubular section. The curve of the guiding atraumatic tip **450** may be made by any of a wide number of processes, including, for example, injection molding, round extrusion, flattening and post-processing into the curved distal section **456**, a flat extrusion bonded to a round extrusion, or an extrusion that is pressed into a hot die having a shape of the desired curved distal section **450**.

The atraumatic tip **450** may include a radio opaque tip marker **460**. The radio opaque tip marker **460** may be implemented as a band surrounding the tip **450** or as a two-dimensional planar material on one or both of the planar opposing surfaces **455**. Alternatively, the radio opaque tip marker **460** may be located at the most distal point of the atraumatic tip **450** indicated at **460'** in FIG. 11. The band or the planar material may be composed of any suitable radio opaque material, such as for example, stainless steel or a suitable alloy such as platinum iridium. In another example embodiment, the tip **450** may be made of a plastic or polymer, such as for example, PEBAX that is impregnated with a radio opaque material. In another example embodiment, the plastic or polymer composition forming the tip **450** may be mixed with a radio opaque compound such as for example barium sulfate sufficient to permit visualization of the tip **450** using x-ray or fluoroscopy.

In an alternative embodiment described herein with reference to FIGS. 12-18, a balloon catheter system **500** generally includes a catheter assembly having a stiffener member **530**, which is preferably comprised of a solid wire, an inflation catheter member **510** having an inflation lumen **610**, a distal catheter member **520**, an inflatable balloon **540**, a proximal hub **590** and a guiding atraumatic tip **550**. The stiffener member **530** is secured to the proximal hub **590** and extends longitudinally through the inflation catheter member

510 along the longitudinal axis **531** of the stiffener member **530**, which substantially comprises the longitudinal axis **531** of the catheter system **500**. The stiffener member **530** includes a proximal end **530b**, a distal end **530c** and defines the longitudinal axis **531**. The stiffener member **530** is coupled at the proximal end **530b** to the proximal hub **590** and at the distal end **530c** to a proximal section of the distal catheter member **520**. The proximal hub **590** includes an inflation connection port **590a** with an inflation fluid pathway **594** therein. The inflation lumen **610** of the inflation catheter member **510** is in fluid communication with the inflation fluid pathway **594** and extends longitudinally through the inflation catheter member **510**. The inflation lumen **610** preferably terminates at a first port **560** distal to a proximal balloon end **544** of and within a space **542** defined by the inflatable balloon **540**, such that the inflation lumen **610** is in fluid flow communication with the space **542** within the inflatable balloon **540** to convey an inflation fluid to and from the inflatable balloon **540** from a source external the balloon catheter system **500** that is preferably connected to the inflation connection port **590a**. The distal catheter member **520** is coupled at a proximal end thereof to a distal end of the stiffener member **530**. The inflation catheter member **510** and the distal catheter member **520** are positioned in longitudinal co-axial spaced apart relationship from one and other along a longitudinal axis **531** of the stiffener member **530**, thereby defining an intermediate region **530a** of the stiffener member **530** within the space **542** within the inflatable balloon **540** that is not covered by either the inflation catheter member **510** or the distal catheter member **520**.

In this preferred embodiment of the balloon catheter system **500**, when the occlusion balloon **540** is in an uninflated condition, the catheter system **500** is of sufficiently small cross-segmental dimension to pass through a five to six (5-6) French (1.67-2 mm) percutaneous sheath, such as, for example six (6) French (2 mm) introduction sheath. Thus, the balloon catheter system **500** has a greatest outer diameter, when the occlusion balloon **540** is uninflated, of less than 1.67-2 mm. The balloon catheter system **500** of the preferred embodiment of FIGS. 12-18 preferably has a smaller greatest outer diameter when the occlusion balloon **540** is uninflated than the above-described preferred catheter system **100** because of the solid stiffener member **530**, which replaces the first catheter **130** with the first lumen **230** therein. It will be understood by those skilled in the art that the balloon catheter system **500** is not limited to a dimension sufficient to pass through a five to six (5-6) French percutaneous sheath, but that such lower profile or smaller maximum diameter when the occlusion balloon **540** is uninflated is generally considered desirable to enable passage of a balloon catheter system **500** through tortuous vasculature and to a desired position within the body for purposes of arterial occlusion. In addition, the reduced maximum diameter limits the size of the percutaneous introduction puncture in the patient's skin and may limit the clinical requirements for the medical professionals performing the procedure. The balloon catheter system **500** is, therefore, not intended to be limited to this dimensional size, but may be made of smaller or larger dimension as desired or needed.

In general, the alternative embodiment described herein with reference to FIGS. 12-18 includes the stiffener member **530**, preferably the solid wire, instead of a tube with a lumen. The solid stiffener member **530** may be implemented as a solid flexible wire made of any suitable material that may be formed into a wire-like component. Examples of materials that may be used include polymeric materials,

biocompatible metals, nitinol and stainless steel. The stiffener member 530 of this preferred embodiment may be constructed of a solid nitinol hypotube. The nitinol hypotube stiffener member 530 provides flexibility and sufficient stiffness along the longitudinal axis 531 and is generally a small diameter tube or wire. The stiffener member 530 implementation without a lumen removes the fluid communication with a third lumen. The stiffener member 530 does, however, allow for the implementation of a catheter system having a lower profile than the first embodiment of the catheter system 100.

In the alternative embodiment of FIGS. 12-18, the catheter system 500 preferably includes a pressure sensor 533 mounted distally of the occlusion balloon 540 or on a surface of the occlusion balloon 540 proximate its distal balloon end 546. The pressure sensor 533 preferably communicates with a processor 501 that may be wired to the pressure sensor 533 or may receive pressure readings from the pressure sensor 533 through wireless communication techniques. In the preferred embodiment, the pressure sensor 533 is wired to and in communication with the processor 501 by an electrical wire 533a that carries pressure signals from the pressure sensor 533 to the processor 501. The electrical wire 533a of the preferred embodiment extends at least partially through the inflation lumen 610 and is in electrical contact with the pressure sensor 533 and the processor 501. The preferred pressure sensor 533 is mounted to an external surface of the distal catheter member 520 to sample and detect pressures at the distal side of the inflatable balloon 540. For example, the pressure sensor 533 may sample pressure near the distal balloon end 546 of the inflatable balloon 540 during use and transmit the pressure readings to the processor 501 for review by an operator, medical technician or physician. The pressure sensor 533 may also be utilized to provide pressure measurements at predetermined intervals to the processor 501. The processor 501 may adjust the inflation of the occlusion balloon 540 to permit limited flow through the vessel to the distal balloon end 546 of the occlusion balloon 540. The processor 501 may be controlled to maintain a range of pressures at the distal balloon end 546 or a minimum pressure based on inflation and deflation of the occlusion balloon 540.

Referring to FIGS. 12-18, the inflatable balloon 540 is attached at its proximal balloon end 544 to a distal end of the inflation catheter member 510 and at its distal balloon end 546 to a proximal end of the distal catheter member 520. In operation, the inflatable balloon 540 is inflated by introducing an inflation fluid, such as saline, from an external source, such as a syringe, coupled to the proximal hub 590, into and through the inflation lumen 610, out of the first port 560 and into the space 542 within the inflatable balloon 540. Inflation and deflation of the inflatable balloon 540 in FIGS. 1-8 is performed as described above with reference to FIGS. 1-8.

Referring to FIGS. 15 and 16, the distal catheter member 520 is fixedly coupled at its proximal end concentrically about a distal end of the stiffener member or solid wire 530. In the preferred example shown in FIG. 16, the distal catheter member 520 has a lumen 620 extending longitudinally through the distal catheter member 520 and coupled concentrically about a proximal end of the atraumatic tip 550. The distal catheter member 520 is not limited to including the lumen 620 and may be configured as substantially solid between its proximal and distal end or integrally formed with or fixed to the atraumatic tip 550. The guiding atraumatic tip 550 may be constructed of an elastic, shape memory and/or superelastic material, such as a metal or polymer. A reinforcing member 552 (depicted in phantom)

may optionally be included either within the guiding atraumatic tip 550 or wound about an external surface of the guiding atraumatic tip 550 to offer additional reinforcement to the tip 550. The guiding atraumatic tip 550 projects distally from the distal catheter member 520 and preferably has a generally flattened configuration, curving proximally and then toward the central longitudinal axis 531 of the balloon catheter system 500, but leaving a unconnected end 561 at the distal end of the guiding atraumatic tip 550. The atraumatic tip 550 is preferably designed and configured such that the atraumatic tip 550 is able to unfold from a relaxed configuration (FIG. 16) and assume a linear configuration co-axial with the central longitudinal axis 531 of the balloon catheter system 500 for delivery. During introduction, the atraumatic tip 550 is preferably straightened along the longitudinal axis 531 in an introduction configuration such that the atraumatic tip may be positioned within a catheter for introduction and returns to the substantially circular-shape in the relaxed configuration when the atraumatic tip 550 emerges from the catheter in the patient's vessel. Specifically, the atraumatic tip 550 preferably has sufficient flexibility such that the substantially circular curve of the atraumatic tip 550, in the relaxed configuration, may be straightened coaxially with the longitudinal axis 531 for introduction of the catheter system 500 into the patient's vessel through an introduction catheter.

The atraumatic tip 550 of the preferred embodiment has a smaller thickness between the inner and outer planar surfaces 555, 557 than the lateral outer opposing surfaces 558, 559 of the atraumatic tip 550. This flattened shape of the atraumatic tip 550 facilitates the folding or flexing of the atraumatic tip along the longitudinal axis 531. The shape and configuration of the preferred atraumatic tip 550 preferably limits bending and folding of the atraumatic tip 550 laterally relative to the longitudinal axis 531. In addition, the relatively flattened atraumatic tip 550 provides manufacturing advantages when the atraumatic tip is constructed of a polymeric material compared to the substantially cylindrical atraumatic tip 150 shown in the first preferred embodiment. In the preferred embodiment, the lateral outer surfaces 558, 559 are substantially arcuate, but are not so limited and may be relatively planar or otherwise configured.

In the preferred embodiment, a tip thickness T_t is defined between the inner planar surface 555 and the outer planar surface 557 and tip width W_t is defined between the opposing curved lateral surfaces 558, 559. The tip width W_t is preferably greater than the tip thickness T_t such that the atraumatic tip 550 is readily flexible about a central tip axis 550a. The atraumatic tip 550 is preferably flexible about the central tip axis 550a from the substantially circular profile in the relaxed configuration to the introduction configuration, wherein the atraumatic tip 550 is relatively straight or positioned on the longitudinal central axis 531. In the preferred embodiment, the tip thickness T_t is less than the tip width W_t . The relatively smaller tip thickness T_t in comparison to the tip width W_t facilitates the flexing of the atraumatic tip 550 from the relaxed configuration with the substantially circular profile to the introduction configuration, wherein the atraumatic tip 550 is substantially straight and is positioned on the longitudinal central axis 431 and renders bending of the atraumatic tip 550 laterally more difficult.

The atraumatic tip 550 of the alternative preferred embodiment of the catheter system 500 is preferably configured and functions similar to the above-described atraumatic tip 450 of the preferred embodiment of FIGS. 10 and 11. The atraumatic tip 550 is preferably formed into the

generally flattened frusta-cylinder having the two generally planar opposing inner and outer surfaces 555, 557 and two generally curved opposing lateral surfaces 558, 559. The atraumatic tip 550 has a distally extending section 553 that projects distally and a curved section 556 continuous with the distally extending section 553 that curves away from the central longitudinal axis 531 of the balloon catheter system 500 then proximally toward the occlusion balloon 540 and subtends a generally circular arc toward the central longitudinal axis 531 of the balloon catheter system 500. In the relaxed configuration, the atraumatic tip 550 preferably has a substantially circular profile when viewed from the side, but is not so limited and may have nearly any sized and shaped profile that limits introduction of the atraumatic tip 550 into an alternative or smaller vessel path than desired by the physician or medical professional. The angle of the curvature may be between about one hundred eighty degrees (180°) and three hundred fifty-five degrees (355°), more preferably between about two hundred seventy degrees (270°) and three hundred fifty degrees (350°) and even more preferably between about three hundred degrees (300°) and three hundred fifty degrees (350°) such that a gap 561a is provided between the unconnected end 561 of the generally cylindrical flattened distal section 554 and the more proximal surface of the distal section 554. The generally flattened section 554 provides manufacturing and functional advantage when compared to a cylindrical atraumatic tip, such as the atraumatic tip 150 described in FIGS. 4 and 5. The flattened atraumatic tip 550 of this alternative preferred embodiment permits flexibility of the atraumatic tip 550 about a plane or axis extending substantially laterally through the atraumatic tip 550, generally perpendicular to the longitudinal axis 531 to accommodate straightening of the atraumatic tip 550 coaxially with the longitudinal axis 531 for introduction. In addition, the greater lateral thickness of the atraumatic tip 550 laterally relative to the longitudinal axis 531 provides stiffness to the atraumatic tip 550 such that the tip 550 is more difficult to bend or flex out of its preferred shape laterally relative to the longitudinal axis 531 during placement of the balloon 540 and movement of the catheter system 550 through the major vessels of the patient.

A tapered transition section 551 is preferably provided between a substantially cylindrical portion of the distal catheter member 520 and the generally flattened distal section 554. The preferred guiding atraumatic tip 550 is integral with the distal catheter member 520 of balloon catheter system 500. Alternatively, the guiding atraumatic tip 550 may be fabricated as a discrete member and joined to the distal catheter member 520 of balloon catheter system 500.

The guiding atraumatic tip 550 is preferably constructed of a polyether block amide (PBAX, Arkema, Paris France) having a durometer of forty (40D), or a similar polymer, such as polyurethane or polyethylene, that is compatible with the distal catheter member 520 and the balloon 540 to make bonding easier and more secure. As discussed above, the guiding atraumatic tip 550 may be generally flattened, cylindrical or tubular, or have a solid cylindrical section and a tubular section. The curve of the guiding atraumatic tip 550 may be made by any of a wide number of processes, including, for example, injection molding, round extrusion, flattening and post-processing into the curved distal section 556, a flat extrusion bonded to a round extrusion, or an extrusion that is pressed into a hot die having a shape of the desired curved distal section 550.

The atraumatic tip 550 may include a radio opaque tip marker 560a at the unconnected end 561. The radio opaque

tip marker 560a may be implemented as a band surrounding the tip or unconnected end 561 or as a two-dimensional planar material on one or both of the planar opposing surfaces 555, 557. The radio opaque marker 560a may be constructed of any suitable radio opaque material, such as for example, stainless steel or a suitable alloy such as platinum iridium. In another example embodiment, the tip 550 may be constructed of a plastic or polymer, such as for example, PEBAX that is impregnated with a radio opaque material to define the radio opaque tip marker 560a. In another example embodiment, the plastic or polymer composition forming the atraumatic tip 550 may be mixed with a radio opaque compound such as for example barium sulfate sufficient to permit visualization of the tip 550 using x-ray or fluoroscopy to define the radio opaque tip marker 560a.

As noted above in the description of the first preferred embodiment of the balloon catheter system 100 illustrated in FIGS. 1-8, the balloon catheter system 100, when the inflatable balloon 140 is in an uninflated condition, is of sufficiently small cross-segmental dimension to pass through a 6 to 8 French (2-2.67 mm) percutaneous sheath, such as, for example, 7 French (2.33 mm). Thus, the balloon catheter system 100 has a greatest outer diameter, when the inflatable balloon 140 is uninflated, of less than 2-2.67 mm. It will be understood by those skilled in the art that example implementations of the alternative embodiment of the balloon catheter system 500 described herein with reference to FIGS. 12-18 may have an even smaller cross-sectional dimension due to the use of the stiffener member or solid wire 530 instead of a catheter with a lumen. The diameter of the stiffener member 530 is smaller than the inner diameter of the inflation lumen 610 of the inflation catheter member 510, thereby forming an annular space 612 between the outer surface of the solid stiffener member 530 and the inner surface of the inflation catheter member 510. The dimensions of the inner diameter of the inflation lumen 610 and the diameter of the stiffener member 530 may be specified in example implementations to provide optimal inflation fluid flow as well as a reduced profile that may further ease deployment.

Turning now to FIGS. 14-16, the distal portion of the balloon catheter system 500 is illustrated. As shown in FIG. 16, the outer surface of the stiffener member 530 is coupled to at least a portion of the inner surface of the second lumen 620, such that there is no annular space between the outer surface of the stiffener member 530 and the inner surface of the second lumen 620. Referring now to FIG. 15, the distal catheter member 520 may include a plurality of segments of distally decreasing durometer polymer to provide a step-down transition to the guiding atraumatic tip 150. The number of step down durometer segments may be between one (1) and six (6) and may step down in decreasing fashion by regular or irregular increments, such, for example 75D, 63D, 55D, 40D, etc. Alternatively, the distal catheter member 520 may be made of a single durometer polymer, but having distally tapering wall thicknesses to impart a flexibility gradient to the third catheter member 520. The plurality of segments of decreasing durometer plastic may be abutted and be bonded together or may be manufactured from a single extrusion including decreasing durometer hardness.

In an alternative embodiment, the stiffener member 530 may extend completely into the space shown for the second lumen 620 such that the distal catheter member 520 com-

35

pletely covers the distal end of the stiffener member 530. The atraumatic tip 550 may be formed as an extension of the second catheter body 520.

Turning now to FIG. 17, the proximal portion of the balloon catheter system 500 is illustrated. The inflation catheter member 510 is coupled to the proximal hub 590 and the proximal end of the stiffener member or solid wire 530 is fixedly coupled to the proximal hub 590 at a proximal bonding site, preferably using an adhesive 580, to bond an inner wall surface of the proximal hub 590 to an outer wall surface of the solid stiffener member 530. The amount of adhesive 580 used is preferably sufficient to fixedly couple the solid stiffener member 530 to the proximal hub 590. As shown in FIG. 17, the adhesive 580 may fill the entire portion 592 of the proximal hub 590 that holds the stiffener member 530. The proximal end of the stiffener member 530 is not limited to being adhesively bonded to the proximal hub 590 and may be otherwise fastened, secured or fixed to the proximal hub 590, as long as the stiffener member 530 is substantially secured to the proximal hub 590 such that the stiffener member 530 provides stiffness for the balloon catheter system 500, the stiffener member 530 is substantially secured relative to the inflation catheter member 510 and the occlusion balloon 540, the assembly is able to withstand the normal operating conditions of the catheter system 500 and securement results in a structure able to perform the preferred functions of the catheter system 500, as is described herein. Since the solid stiffener member 530 has no lumen, no fluid pathway is needed in the portion 592 that holds the stiffener member 530 and the stiffener member 530 can have a relatively small diameter, thereby reducing the overall diameter of the catheter system 500. As illustrated, the proximal hub 590 has an inflation fluid pathway 594. The inflation fluid pathway 594 communicates with the inflation lumen 610 of the inflation catheter member 520. In this alternative preferred embodiment, the inflation lumen 610 is defined between the outer surface of the stiffener member 530 and an inner surface of the inflation catheter member 510. It will be understood that the proximal hub 590 may be configured to have more than the inflation fluid pathway 594, with each fluid pathway communicating with a different one of any additional lumens in the balloon catheter system 500.

It will be understood that when reference is made to coupling two or more component sections, members or pieces of the balloon catheter system, that conventional catheter material bonding modalities are intended to be encompassed and employed. For example, a wide variety of biocompatible adhesives useful in catheter manufacture are known, similarly, thermobonding techniques used in catheter manufacture are also known. Thus, for example, where it is described that the guiding atraumatic tip is coupled to the third catheter member or to the distal catheter member, it is contemplated that such coupling may be made using thermobonding, biocompatible adhesives or other methods of fixedly bonding two components in medical devices.

It will also be understood by those skilled in the art that it is well known to manufacture catheters of a variety of medical grade, biocompatible polymers, such as, for example and without limitation, silicone, nylon, polyurethane, PETE, latex, thermoplastic elastomers, polyether block amides (PBAX, Arkema, Paris, France). Alternatively, it is known to manufacture catheters of metals, such as nitinol or stainless steel. Similarly, it is known to manufacture catheters of metal-reinforced polymer, such as, for example and without limitation, stainless steel braiding over polyurethane, stainless steel helical windings over silicone

36

or nitinol reinforced polymer. Thus, any or all of the first catheter member, the second catheter member, the inflation catheter member, the distal catheter member, or the third catheter member in any of the foregoing embodiments may be fabricated of biocompatible polymers, biocompatible metals or metal-reinforced polymers, as is known in the art.

It will also be understood by those skilled in the art that while the implementation of radio opaque markers are described in the context of embodiments described with reference to FIGS. 1-8, it may be desirable to include radio opaque marker bands positioned at the proximal and distal ends of the balloon in implementations of embodiments described above with reference to FIGS. 9-11, and embodiments described above with reference to FIGS. 12-18. It is also desirable to include length markers on the outer catheter shaft to indicate to the physician the insertion depth of the balloon catheter system 100, the balloon catheter system 300, or the balloon catheter system 500. The length markers may be printed or laser etched onto the outside of the catheter shaft.

In each of the foregoing described embodiments of the vascular occlusion systems depicted in FIGS. 1-18, the catheter may also include sensors, transmitters, receivers, interrogators or other means for measuring physical and/or physiological parameters distal and/or proximal one or more of the expandable occlusion members, including, for example blood pressure sensors, heart rate sensors, flow sensors, chemical sensors, temperature sensors, oxygenation sensors, biological sensors, imaging sensors or the like.

The preferred catheters, sheaths, guide wires, balloons or other occlusion members, or other components that are introduced into the vasculature may be coated with a variety of coatings, including without limitation, antibacterial, antimicrobial, lubricants, anticoagulant and/or antifouling coatings. Thus, any or all components of any of the preferred systems described herein may further include one or more biocompatible coatings.

Occlusion Control System

Control over the apposition of the occlusion member against the vessel walls is preferably accomplished by controlling the inflation of the preferred balloons, selection of the size of the occlusion member, placement of the occlusion member or other methods and techniques that provide control to users of the preferred systems. Aortic occlusion may result in arterial hypertension upstream of an occlusion site as pressure builds against the occlusion member. If the arterial pressure reaches a deleterious hypertensive state, vascular rupture, stroke or other undesirable events may occur that could potentially injure the patient. Conversely, after the vascular occlusion is complete and blood flow is restored, there is a potential for concomitant drop in arterial blood pressure potentially leading to a hypotensive event that could result in a dangerously low blood pressure and, in extreme cases, cardiac arrest.

The preferred control systems are not limited to their utility with the preferred vascular occlusion catheter systems 100, 300, 500 of the present invention, but may be used virtually with any type of vascular occlusion system. Thus, in FIG. 19, there is shown a generic type of vascular occlusion system 700, while in FIGS. 20-22, the vascular occlusion catheter system is generically shown schematically and is designated by box 710, to denote a non-specific vascular occlusion catheter system, including, for all of FIGS. 19-22, without limitation, the first, second and third preferred vascular occlusion catheter systems 100, 300, 500

described above. Other vascular occlusion catheter systems that rely upon a pressure being applied to an occlusion member to urge the occlusion member into apposition with a vascular wall, thereby at least partially occluding the blood vessel are expressly included within the scope of occlusion control system of the present invention, such as the additional occlusion/perfusion systems described herein.

In each of the preferred embodiments of the occlusion control systems, the pressure sources are denominated schematically by a generic box or oval to denote that a wide variety of pressure sources are intended to be included within the preferred embodiments of the invention. The pressure source may be a syringe or syringe-like inflation device, an endoflator device, a pump or other similar means of applying a pressure to the occlusion member in the vascular occlusion catheter 710. As noted above, when a fluid is used as the pressure medium to activate the occlusion member, such as to fill an occlusion balloon, that fluid may be a liquid, including water, saline, contrast medium or any combination thereof, or may be a gas, including carbon dioxide, helium, air or oxygen. The fluid source may, in the instance of a liquid, be a liquid reservoir, a pre-measured volume of liquid in a vessel that is removably engageable with the pressure source or other similar container for holding and dispensing liquid from the fluid source to the pressure source. In the instance of a gas, the fluid source may be a gas reservoir or a pre-measured volume of pressurized gas in a canister that is removably engagement with the pressure source to deliver the pre-measured volume of gas to the pressure source. A canister with a pre-measured gas volume at a known pressure is also contemplated, for example, a carbon dioxide cartridges that are commercially available in a wide variety of mass of pressurized gas, including without limitation eight, twelve, sixteen, twenty-five or thirty-three grams (8 g, 12 g, 16 g, 25 g, 33 g). Converting mass to volume of a gas at standard temperature and pressure (STP) typically entails resolving the gas constant equation, as follows: $V=nRT/P$ wherein V is volume, n is mass, R is the molar volume of the gas, T is temperature (Kelvin) and P is pressure (atm). The volume of gas needed to inflate a specific occlusion member to a given inflation volume and inflation pressure may be calculated utilizing this preferred formula.

Referring to FIG. 19, a first embodiment of the occlusion control system 700 includes a vascular occlusion catheter 711 has a proximal hub 790 that includes at least one pressure line port 794. The pressure line port 794 communicates with a pressure conduit or lumen 712 in the vascular occlusion catheter 711. The pressure conduit 712 may be a lumen within the vascular occlusion catheter 711 or may be a tubular conduit placed within a lumen in the vascular occlusion catheter 711. A pressure accumulator or reservoir 730 communicates with the pressure line port 794 via pressure line 732 that is, in turn, coupled to a connecting conduit 720 associated with pressure line port 794. An actuator 744, such as a fluid pump, is coupled to the pressure accumulator 730 and to a fluid source ("FS") 742. The actuator 744 is also operably coupled to a controller or central processing unit ("CPU") 750. The controller 750 operates as a computer control and may have an interface, not shown, that permits programming of computer control software that monitors and controls activation of the actuator 744 to regulate pressure in the occlusion member 740 and to collect data from sensors associated with the occlusion control system 700.

In accordance the preferred embodiment of occlusion control system 700, the occlusion member 740 has a first

pressure Pmax, which is below the failure pressure of the occlusion member 740. The pressure accumulator 730 is preferably pressurized, such as with a fluid, to an accumulator pressure Pa, where the accumulator pressure $P_a < P_{max}$, and where the accumulator pressure Pa is less than a predetermined maximum safe blood pressure Pbp within the vascular system being occluded, such that $P_a < P_{bp} < P_{max}$. When the occlusion member 740 is in apposition with the vascular wall and the vessel is substantially occluded, the pressure exerted at the occlusion member 740 may be considered the apposition pressure Papp, wherein the apposition pressure Papp is substantially equal to the pressure in the accumulator 730 or the accumulator pressure Pa. In this preferred embodiment, when during occlusion the blood pressure Pbp against the occlusion member 740 exceeds the apposition pressure Papp, the accumulator pressure Pa in the accumulator 730 and in the occlusion member 740 is exceeded and the occlusion member 740 may yield to the blood pressure Pbp and release apposition against the vascular wall surface and allow fluid flow past the occlusion site. Since the apposition pressure Papp within the occlusion member 740 and the accumulator pressure Pa within the accumulator 730 is preferably a closed system, the pressure in the accumulator 730, such as the accumulator pressure Pa, will rise and when blood pressure reduces to be less than the accumulator pressure Pa in the accumulator 730 and the apposition pressure Papp within the occlusion member 740, the occlusion member 740 will preferably reestablish occlusion.

This effect of automatically adjusting apposition pressure Papp in response to an elevation in blood pressure Pbp, causing a release of apposition against the vascular wall and, therefore, releasing the occlusion and permitting fluid flow past the occlusion site, in turn lowers the blood pressure head against the occlusion member 740. When the blood pressure Pbp upstream of the occlusion member 740 has downwardly adjusted to below the accumulator pressure Pa and the apposition pressure Papp, the occlusion member 740, under the influence of the elevated pressure in the accumulator 740, reestablishes apposition and, therefore, occlusion is reestablished. This cycle may be likened to "burping" as a pressure release.

One further aspect of the occlusion control system 700 illustrated in FIG. 19, is that the preferred computer controller 750 preferably monitors the accumulator pressure Pa, the blood pressure Pbp and the apposition pressure Papp and, when required, either automatically or after providing audible or visual notification to a medical practitioner and input from the medical practitioner, actuates the actuator 744 to draw fluid from fluid source 742 and communicates the drawn fluid to the occlusion member 740 to increase the apposition pressure Papp. Conversely, where apposition pressure Papp is determined by the computer controller 750 or by the medical practitioner to be too high, the actuator 744 may be controlled to withdraw fluid from the occlusion member 740, lowering apposition pressure Papp and moving fluid from the occlusion member 740 to the fluid source 742.

The occlusion control system 700 is preferably a bidirectional system capable of increasing the occlusion pressure or apposition pressure Papp or decreasing the occlusion pressure or apposition pressure Papp under either manual control or under control of the computer processor 750. Moreover, the preferred occlusion control system 700 is operable to automatically release the apposition when the blood pressure Pbp impinging on the occlusion member 740 is above a pre-determined level (typically that regarded as safe for the patient). Accordingly, the occlusion control system 700

preferably includes a pressure sensor that is able to sense blood pressure on the proximal or distal side of the balloon 740 to measure the blood pressure Pbp impinging on the occlusion member 740 and to adjust inflation pressure or apposition pressure Papp of the occlusion member 740 to at least partially control the blood pressure Pbp in the vessel.

An alternative or second preferred embodiment of occlusion control system 751 is depicted in FIG. 20. In alternative or second preferred embodiment of the occlusion control system 751, the occlusion catheter 710 is under control of a pressure source ("I") 752, which in the case of a fluid is coupled to a fluid source ("FS") 751. Similar to the first preferred occlusion control system 700, the pressure source 752 may be under manual control, under automatic control of a computer processor 753, or under manual control interfacing with the computer processor 753. A pressure conduit 754 preferably bifurcates into a free line 756 and a regulated line 758. A check valve 760 is preferably positioned in-line in the regulated line 758. An actuable valve 762 is preferably interposed in both the free line 756 and the regulated line 758, and is operable to select the free line 756, the regulated line 758 or both the free line 756 and the regulated line 758. A fluid conduit 766 leads from the actuable valve 762 to the occlusion catheter 710. A pressure sensor 764 may be interposed within fluid conduit 766 to monitor pressure during operation of the second preferred occlusion control system 751 and may alternatively be positioned in the occlusion control system 751 to detect pressure at various locations relative to the system 751, such as within an occlusion balloon or at proximal and/or distal ends of the occlusion balloon. The pressure sensor 764 may be a pressure gauge, electronic pressure sensor or pressure sensor that provides visual signal to the medical practitioner directly or may feed a pressure signal to the computer processor 753 that controls the occlusion control system 751, in turn, upon the pressure signal and/or displays pressure data to the medical practitioner.

Referring to FIG. 21, there is shown yet another alternative or third preferred embodiment of an occlusion control system 800. Unlike the occlusion control system 751 of the second preferred embodiment, the preferred occlusion control system 800 preferably has a single pressure conduit communicating between the occlusion catheter 710, which is utilized herein as a generic occlusion catheter 710, and a pressure source ("I") 752, which, in the case of a fluid, is coupled to a fluid source ("FS") 801. Similar to the occlusion control system 700 of the first preferred embodiment, the pressure source ("I") 802 of the third preferred embodiment may be under manual control, under automatic control of a computer processor 803, or under manual control interfacing with the computer processor ("CPU") 803. A pressure conduit 804 preferably provides fluid communication between the pressure source 802 and the occlusion catheter 710. A check valve 806 is preferably in-line with the pressure conduit 804. The check valve 806 may be any type of manual or automatically actuable valves that operate both to prevent back-flow of an inflation fluid and as a pressure relief if there is an overpressure in the occlusion catheter 710. A fluid conduit 866 leads from the check valve 806 to the occlusion catheter 710. A pressure sensor 808 may be interposed within the fluid conduit 804, 866 to monitor pressure during operation of the occlusion control system 800. The pressure sensor 808 may be a pressure gauge that provides visual signal to the medical practitioner directly or may output a pressure signal to computer control 803 that controls the occlusion control system 800, in turn, upon the pressure signal and/or displays pressure data to the medical

practitioner. An additional feature of the occlusion control system 800 may be the addition of a timer 810. The timer 810 is preferably incorporated into the computer processor 803 or may be positioned in-line with the fluid conduit 804, 866. The timer 810 preferably communicates a time signal to the check valve 806, to the computer control 803 and/or to the pressure source 802, as indicated by dashed lines in FIG. 21. The time signal may be a regular, consistent signal representative of the timer status, or may be a single time elapse signal that activates the check valve 806, the pressure source 802 and/or the CPU 803 to withdraw pressure communicated to the occlusion catheter 710. Similarly, the timer 810 may issue a series of time signals according to a pre-programmed routine stored in the CPU 803 or in the timer 810 itself, to control cycling of the pressure source 802 and/or opening and closing cycles of the check valve 806.

In a fourth preferred embodiment of the occlusion control system 820, the pressure source 802 is again in communication with the occlusion catheter 710 via a pressure conduit 826. An actuable valve 828 is preferably in-line in the pressure conduit 826 and operates under the influence of a controller 822. The controller 822 is preferably operably coupled, such as by electrical, mechanical or electromechanical coupling, to both the actuable valve 828 and to the pressure source 802. The controller 822 may also communicate with a computer control or CPU 803. In this preferred embodiment, the actuable valve 828 is operable under the control of the controller 822 to open or close to allow pressure from the pressure source 802 to be applied to the occlusion catheter 710 or to withdraw pressure from the occlusion catheter 710, depending upon the pressure state at the occlusion member 740 of the preferred occlusion catheter 710. Again, similar to the above-described embodiments the pressure source 802 is operable to increase pressure or decrease pressure applied to the occlusion catheter 710, such as by drawing fluid from fluid source 801 and supplying the fluid to the occlusion catheter 710 to inflate the occlusion balloon 740. In the reverse, the pressure source 802 is operable to decrease pressure by drawing fluid from the occlusion balloon 740, thereby deflating the occlusion balloon 740, releasing apposition and occlusion at the vascular wall and permitting perfusion past the occlusion member 740 when the occlusion member 740 is positioned in the vessel.

Pressure sensors 764, 808 may be positioned external the occlusion catheter 710, as shown in the second and third preferred embodiments of FIGS. 20 and 21, or may be incorporated in the occlusion catheter 710 itself and be positioned distal the occlusion member 740 with either an electrical connection at the proximal hub 790, may be wireless or may be comprised of pressure sensors positioned both distal and proximate relative to the occlusion member 740 and external relative to the occlusion catheter 710 to sense pressure both distal relative to the occlusion member 740, proximal the occlusion member 740, within the occlusion member 740 and within the pressure line 804, 866, 826, 766 proximal the occlusion member 740.

In each of the foregoing described preferred embodiments of the occlusion control systems 700, 751, 800, 820 depicted and described with reference to FIGS. 19-22, the systems may also include sensors, transmitters, receivers, interrogators or other means for measuring physical and/or physiological parameters distal and/or proximal one or more of the expandable occlusion members, including, for example blood pressure sensors, heart rate sensors, flow sensors,

chemical sensors, temperature sensors, oxygenation sensors, ischemia sensors, biological sensors, imaging sensors or the like.

Occlusion/Perfusion Systems

The preferred occlusion control systems **700**, **751**, **800**, **820** described above function to control the apposition of the occlusion member **140**, **540**, **740** against the vascular wall of the patient's vessel by regulating the pressure applied to the occlusion member **140**, **540**, **740**. These preferred systems **700**, **751**, **800**, **820** regulate and mitigate both hypertension and hypotension, by controlling the relative degree of occlusion and perfusion, such as during and after a vascular repair procedure. The occlusion catheter system **100**, **300**, **500**, **700**, itself, can also be configured to regulate the degree of occlusion and perfusion. Referring to FIGS. 23-34, there are provided alternative preferred occlusion balloon geometries that at least partially occlude the vascular lumen of the patient's vessel, thereby permitting at least a partial perfusion flow of blood past the occlusion site, if desired by the physician or medical technician performing a procedure with the preferred systems.

A first preferred embodiment of the occlusion/perfusion balloon system **1200** is depicted in FIGS. 23-28A, a second preferred embodiment of the occlusion/perfusion balloon **1220** is depicted in FIGS. 29A and 29B, a third preferred embodiment of the occlusion/perfusion balloon **1230** is depicted in FIGS. 30A and 30B, a fourth and fifth preferred embodiment of the occlusion/perfusion balloon system **1240** is depicted in FIGS. 31-31B, a sixth preferred embodiment of an occlusion/perfusion balloon system **1260** is depicted in FIGS. 32 and 32A, a seventh preferred embodiment of the occlusion/perfusion balloon system **1270** is depicted in FIG. 33, an eighth preferred embodiment of the occlusion/perfusion balloon system **1280** is depicted in FIG. 34, a ninth preferred embodiment of the occlusion/perfusion balloon system **2000** is depicted in FIGS. 35A and 35B and a tenth preferred embodiment of the occlusion/perfusion balloon system **2100** is depicted in FIG. 35D.

Referring to FIGS. 23-28A, a balloon **1201** of the occlusion/perfusion balloon system **1200** of the first preferred embodiment is fabricated of a substantially compliant biocompatible material, which may be a polymer, metal or composite material. The balloon **1201** of the occlusion/perfusion balloon system **1200** may alternatively be constructed of a substantially compliant material such that the balloon has a substantially defined shape in a fully inflated configuration that facilitates at least partial flow of fluid through channels **1206a**. The term "substantially non-compliant" is intended to mean a compliance range of about zero to fifteen percent (0-15%) of its expanded diameter when inflated to its rated pressure. The balloon **1201** of the occlusion/perfusion balloon **1200** is preferably constructed of polymeric balloon materials, including, but not limited to, polyethylene terephthalate ("PET"), nylon, polyethylene, polyether block amides, such as PEBAX, polyurethane and polyvinyl chloride. Highly compliant polymer materials may be made substantially non-compliant by incorporation of composite materials, such as carbon fibers or other substantially non-elastic materials, into or on the polymer material of the preferred balloon **1201**. Similarly, a compliant balloon material may be constrained by a substantially non-compliant material, including polymer, metal or composite.

While the first preferred balloon **1201** is depicted in the accompanying figures in an elliptical-shape, it may have a

different geometric shape than elliptical, including, without limitation, spherical, elliptical, conical, square, rectangular, dog-boned, tapered, stepped, or combinations thereof, such as, for example, conical/square or conical/spherical.

The first preferred occlusion/perfusion balloon system **1200** has a plurality of radially projecting members **1204** on the balloon **1201** when the occlusion/perfusion balloon system **1200** is in a partially-inflated to nearly fully-inflated configuration. The projecting members **1204** preferably project outwardly relative to a central longitudinal axis **1200a** of the balloon **1201**. Landing areas **1206** and channels **1206a** are preferably defined between adjacent pairs of the projecting members **1204** when the balloon **1201** is partially-inflated to nearly fully-inflated. The balloon **1201** has a proximal end **1208** and a distal end **1212** that engage with and are joined to a proximal catheter member **1200b** and a distal catheter member **1200c**. The proximal catheter member **1200b** includes an inflation lumen **1210** therein that facilitates inflation of the balloon. The balloon **1201** may be utilized with any of the preferred occlusion catheter systems **100**, **300**, **500**, **700**, **800**, **1300**, **1350** described herein by mounting the proximal and distal ends **1208**, **1212** to the associated catheters. The first preferred balloon **1201** defines an open envelope within the balloon **1201**, which receives an inflation fluid or gas to expand the balloon **1201** from a collapsed configuration (not shown), wherein the balloon **1201** is folded to have substantially the same diameter as the proximal and/or distal catheters **1200b**, **1200c** for introduction into a patient's vessel, to its fully expanded state or inflated configuration (FIGS. 28 and 28A). In the inflated configuration, the projecting members **1204** and landing areas **1206** are nearly, visually imperceptible from each other, as the balloon **1201** has a substantially smooth, continuous outer surface shape in the inflated configuration. In contrast, in partially inflated configurations (FIGS. 23-27), the projecting members **1204** and the landing areas **1206** or channels **1206a** are visually identifiable with the projecting members **1204** typically positioned further from the central longitudinal axis **1200a** than the associated landing areas **1206**, with the channels **1206a** defined in the spaces between the projecting members **1204**.

In this first preferred embodiment of the occlusion/perfusion balloon system **1200**, the channels **1206a** of the balloon **1201** permit flow of fluid and blood past the balloon **1201**, substantially parallel or along the longitudinal axis **1200a** when the system **1200** is inserted into a patient's vessel. The balloon **1201** of the first preferred occlusion/perfusion system **1200** may take on numerous shapes, each with channels **1206a** depending on the level of inflation. For example, in a minimal inflation configuration (FIGS. 23-25), the balloon **1201** has relatively deep and large channels **1206a** to accommodate relatively significant blood and fluid flow, in a low inflation configuration (FIG. 26), the balloon **1201** has comparatively smaller channels **1206a**, in a medium inflation configuration (FIG. 27), the balloon **1201** has again comparatively smaller channels **1206a** and, in a full inflation configuration (FIG. 28), the balloon **1201** does not include perceptible channels, such that the vessel may be completely occluded when the balloon **1201** is inflated to the fully inflated configuration.

The plurality of radially projecting members **1204** and landing areas **1206** preferably extend along or substantially parallel to the central longitudinal axis **1200a** of the balloon **1201**. The radially projecting members **1204** may be oriented substantially parallel to the longitudinal axis **1200a** of the balloon **1201** or may extend at an angle relative to the longitudinal axis **1200a** of the balloon system **1201**. For

example, the projecting members **1204** may spiral in a curved manner along an outside surface **1200d** of the balloon **1201**, such that the channels **1206a** extend in a substantially spiral or arcuate orientation relative to the longitudinal axis **1200a**. The angular orientation of the projecting members **1204** and landing areas **1206** are preferably sufficient to channel blood or fluid flow along the length of the balloon **1201** within the vessel and to generally not impede flow or contribute substantially to highly disrupted blood flow that may result in thrombosis. A preferred angular offset of the projecting members **1204** and landing areas **1206** may be between zero and forty-five degrees (0-45°) relative to the longitudinal axis **1200a** the balloon **1201**. The radially projecting members **1204** may have either a generally linearly extending orientation, as is shown in the first preferred embodiment, a curvilinear orientation or nearly any other orientation that permits formation of the landing areas **1206** between the projecting members **1206** such that blood and fluid may flow through the landing areas **1206** when the balloon **1201** is inserted in the vessel and is at least partially inflated.

In the first preferred embodiment, the occlusion/perfusion balloon system **1200** includes four (4) regularly arrayed radially projecting members **1204** on or incorporated into the balloon **1201**. The balloon **1201** is not limited to including four (4) regularly arrayed radially projecting members **1204** and associated landing areas **1206** and the number of radially projecting members **1204** may be any number greater than two (2) that permit blood and fluid to flow through the landing areas **1206** when the balloon **1201** is in one of its partially inflated configuration. In the first preferred embodiment, there is sufficient surface area on the radially projecting members **1204** to seat in apposition with a vascular wall surface of the patient's vessel and that there is sufficient surface area in the landing areas **1206** to channel fluid or blood flow along a length of the balloon **1201** when the balloon **1201** is in one of its partially inflated configurations, such as the partially inflated configurations of FIGS. 23-27.

In the first preferred embodiment of the occlusion/perfusion balloon system **1200**, each of the plurality of radially projecting members **1204** has a generally circular or arcuate transverse profile, as depicted in FIG. 27, on an upper aspect **1205** thereof, and a stem portion **1207** that extends from the landing area **1206**. The stem portion **1207** connects with the upper aspect **1205** of each radially projecting member **1204** such that the stem portions **1207** have a smaller stem width than an upper aspect width (See FIG. 24). In the first preferred embodiment, the projecting members **1204** each have an apex **1218** that is preferably located intermediate a length of each radially projecting member **1204** or centrally between the proximal end **1208** and distal end **1212** of the preferred balloon **1201**. The projecting members **1204** of the first preferred embodiment also preferably include a proximal, generally flattened or planar area **1214** and a distal, generally flattened or planar area **1216** on an outermost surface of each radially projecting member **1204** relative to the central longitudinal axis **1200a**. The proximal and distal generally flattened or planar areas **1214**, **1216** preferably extend proximally and distally, respectively, from the apexes **1218**. As will be seen from the series of FIGS. 23-28, representing a sequence of the balloon **1201** of the first preferred occlusion/perfusion balloon system **1200** with increasing degrees of inflation, the apex **1218** forms the outermost equatorial circumference at the longitudinal midpoint of the balloon **1201** along the longitudinal axis **1200a**. The proximal and distal generally flattened or planar areas

1214, **1216** facilitate diametric expansion and transition to the preferred fully elliptical-like shape of the fully expanded balloon **1201** in its full inflation configuration (See FIG. 28).

The first preferred embodiment of the occlusion/perfusion balloon system **1200** may be constructed by forming the balloon **1201** of two or more materials having differing hardness or moduli of elasticity. In the first preferred embodiment, as depicted in FIG. 28A, the balloon **1201** may be formed such that the plurality of projecting members **1204** are made of a higher durometer material, while the landing areas **1206** are made of a relatively lower durometer material. These materials may be co-extruded or molded to define the preferred balloon **1201**. In addition, the occlusion/perfusion balloon **1201** may be alternatively designed and configured with different materials that are able to take on the general size and shape of the occlusion/perfusion balloon **1201**, particularly the minimal inflation, low inflation, medium inflation and full inflation configurations and related inflation configurations between these configurations shown in the drawings, and withstand the normal operating conditions of the occlusion/perfusion balloon **1201**.

The size, shape and configuration of the plurality of projecting members **1204** of the first preferred balloon **1201** is but one exemplary embodiment and may take on other various sizes, shapes and configurations. As described above, the plurality of projecting members **1204** are preferably an integral part of the balloon **1201** itself, and form the wall surfaces of the balloon **1201**. Alternatively, the projecting members **1204** may be elongate filaments, tubes, cylinders or other members that are either joined to or integrally formed with an outer wall surface of the occlusion/perfusion balloon **1201**. For example, the projecting members **1204** may be constructed of a high durometer polytetrafluoroethylene (PTFE), fluorinated ethylene propylene (FEP), polyether block amide (PBAX) or other similar biocompatible material, formed in solid or tubular members having a circular, elliptical, quadrilateral, polygonal or other suitable transverse cross-sectional shape. These alternative projecting members **1204** may also be separately connected to the balloon **1201** and separately inflatable and deflatable to control the inflation configuration of the occlusion/perfusion balloon **1201**. The preferred projecting members **1204** may be configured in nearly any shape, size and configuration such that the occlusion/perfusion balloon **1201** is able to selectively permit flow of fluid and blood past the projecting members **1204**, at least in certain inflation configurations, along the longitudinal axis **1200a**. In addition, the occlusion/perfusion balloon **1201** may be configured such that the channels **1206** are comprised of flow channels or holes (not shown) that are surrounded by the material of the occlusion/perfusion balloon **1201** to permit flow of blood and fluid through or around the occlusion/perfusion balloon **1201** generally parallel or along the longitudinal axis **1200a**.

Referring to FIGS. 29A and 29B, an occlusion balloon system **1220** in accordance with a second preferred embodiment includes a balloon **1222** with a plurality of projecting members **1224** projecting from an outer wall surface **1223** of the balloon **1222**. The balloon **1222** is connected to a proximal catheter member **1220b** and a distal catheter member **1220c**, which may be incorporated into any of the preferred occlusion catheter systems **100**, **300**, **500**, **700**, **1700**, **1800**, described herein. The proximal catheter member **1220b** includes an inflation lumen therein that facilitates inflation of the balloon **1222**. The projecting members **1224** preferably extend substantially radially away from the outer surface **1223** of the balloon **1222** and extend along the outer surface **1223** substantially longitudinally relative to the

longitudinal axis **1220a**. The preferred projecting members **1224** preferably extend along an entire length of a substantially tubular section **1223a** of the balloon **1222**, which tapers to the proximal and distal catheters **1220b**, **1220c** in a substantially funnel-shape at its ends. The outer surface **1223** of the balloon **1222** preferably has a constant diameter in the tubular section **1223a**. The projecting members **1224** are not limited to extending substantially longitudinally along the entire length of the tubular section **1223a** and the tubular section **1223a** is not limited to having a substantially constant diameter and the balloon **1222** may be otherwise designed and configured such that the balloon **1222** is able to partially and fully occlude a vessel and withstand the normal operating conditions of the preferred occlusion balloon system **1220**.

The projecting members **1224** preferably define channels **1224a** between the projecting members **1224** or adjacent the projecting members **1224** that permit flow of blood and fluid substantially parallel to the longitudinal axis **1220a** when the occlusion balloon system **1220** is positioned within a vessel. The balloon of the system **1220** may be inflated to various levels to enhance or reduce the channels **1224a**, depending on the preferred procedure, preferences of the medical technician or conditions encountered or detected within the vessel.

Referring to FIGS. **30A** and **30B**, an occlusion/perfusion balloon system **1230** in accordance with a third preferred embodiment includes a balloon **1232** and a plurality of vanes **1234** that project from an outer wall surface **1233** of the balloon **1232**. In this third preferred embodiment of the occlusion/perfusion balloon system **1230**, the vanes **1234** are preferably resilient in nature and are capable of deforming or folding over against an outer wall surface **1233** of the balloon **1232**, as depicted by phantom lines **1238** (FIG. **30B**), when the balloon **1232** is in apposition against a vascular wall surface and occluding the vessel or partially occluding the vessel. The vanes **1234** of the third preferred embodiment also preferably extend substantially radially away from the outer surface **1233** and extend along the outer surface **1233** substantially longitudinally relative to the longitudinal axis **1230a**. The vanes **1234** preferably extend along an entire length of a substantially tubular section **1233a**, which tapers to the proximal and distal catheters **1230b**, **1230c**. The proximal catheter **1230b** includes an inflation lumen therein that facilitates inflation and deflation of the balloon **1232**. The outer surface **1233** preferably has a constant diameter in the tubular section **1233a**. The vanes **1234** preferably extend to tips **1234a** that are spaced at a greater distance from the outer surface **1233** when compared to the similar projecting members **1224** of the second preferred embodiment. The outer surface **1233** of the balloon **1232** preferably has a constant diameter in the tubular section **1233a**. The projecting members **1234** are not limited to extending substantially longitudinally along the entire length of the tubular section **1233a** and the tubular section **1233a** is not limited to having a substantially constant diameter and the balloon **1232** may be otherwise designed and configured such that the balloon **1232** is able to partially and fully occlude a vessel and withstand the normal operating conditions of the preferred occlusion balloon system **1220**.

In this third preferred embodiment of the system **1230**, the vanes **1234** preferably define channels **1234b** therebetween and with the walls of the vessel that permit flow of blood and fluid through the vessel along or substantially parallel to the longitudinal axis **1230a**. The channels **1234b** may be manipulated or controlled by the user or designer by the

inflation of the balloon **1232**, the stiffness of the vanes **1234**, the height of the vanes **1234**, the separation of the vanes **1234** and related other factors that may increase or decrease the size of the channels **1234b** that facilitate flow of fluid through the vessel when the balloon **1232** is inflated.

Referring to FIGS. **31-31B**, fourth and fifth preferred embodiments of the occlusion/perfusion system **1240** includes a compliant occlusion balloon **1242** and at least one restraining filament **1250** connected to proximal and distal catheters **1240b**, **1240c** with the restraining filament **1250** positioned on an outside of an outer surface **1243** of the balloon **1242**. The proximal catheter **1240b** includes an inflation lumen therein that carries fluid or gas to and from the balloon **1242** to facilitate inflation and deflation of the balloon **1242**, respectively. The restraining filament **1250** deforms at least one section of the occlusion balloon **1242** radially inward toward a longitudinal axis **1240a** of the balloon **1242** and away from the vascular wall or allows an adjacent portion of the balloon **1242** to extend further away from the longitudinal axis **1240a** than the portion proximate the filament **1240**. The inclusion of the restraining filament **1250** preferably creates a reverse curvature in the balloon **1242** and permits fluid to flow past the balloon **1242**, substantially parallel to the longitudinal axis **1240a** when the balloon **1242** is positioned within the vessel. When a desired time elapses, a desired arterial blood pressure is achieved, or when other indicators suggest, the tension on the restraining filament **1250** may be released, the reverse curvature will expand and the balloon **1242** and the balloon **1242** will return to its occlusion position in apposition with the vessel wall.

In the occlusion/perfusion system **1240** of the fourth preferred embodiment, the catheters **1240b**, **1240c** preferably accommodate the at least one restraining filament **1250** within the catheter **1240b**, **1240c**, such that the filament **1250** exits the catheter **1240b**, **1240c** proximate the balloon **1242**, overlay the balloon **1250** along a portion of the length of the balloon **1250** and is configured to provide tension against the outer surface **1243** of the balloon **1250** to define channels or flow paths along the balloon **1250**, preferably substantially parallel to or along the direction of the longitudinal axis **1240a**. In order to accommodate this arrangement, the catheter **1240b**, **1240c** of the fourth preferred embodiment is provided with a distal port **1246** passing through the outer wall of the distal catheter **1240c** and a proximal port **1248** also passing through the outer wall of the proximal catheter **1240b**. The restraining filament **1250** is preferably lead from the proximal end of the proximal catheter **1240b**, where it is accessible to the medical practitioner for tensioning, is passed through a lumen in the proximal catheter **1240b** (not shown), exits the proximal port **1248**, passes over the balloon **1242** and adjacent the outer surface **1243** of the balloon **1242**, and anchor or is attached at the distal port **1246** to the distal catheter **1240c**. In this manner, tensioning the at least one filament **1250** at the proximal end of the proximal catheter **1240b** preferably causes the filament **1250** to tension against the balloon **1242** or block expansion of the balloon **1242** proximate the filament **1250**. When the balloon **1242** is inflated, the portions of the balloon **1242** spaced from the filament **1250** expand away from the longitudinal axis **1240a**, while the portions of the balloon **1242** adjacent and beneath the filament **1250** are blocked from expansion by the filament **1250**. Accordingly, the outer surface **1243** of the balloon **1242** forms or defines channels **1254** extending substantially parallel to the longitudinal axis **1240a** or along the length of the filament **1250** between the expanded portions of the

balloon 1242 between the filament 1250 that permit fluid flow in the channels 1254 created between the vessel wall 1252 (shown in phantom in FIG. 31A) and the reverse curve of the outer surface 1243 of the balloon 1242.

Referring specifically to FIG. 31B, the fifth preferred occlusion/perfusion balloon system 1240 entails running the at least one restraining filament 1250 within the interior space or within the material defined by the balloon 1242 and joining the at least one filament 1250 to the inner wall surface of the balloon 1242. This joining between the at least one restraining filament 1250 and the inner wall surface of the balloon 1242 may be accomplished by adhesives, thermobonding or reflowing. Alternatively, one or more lumens may be co-extruded with the inner wall surface of the balloon 1242 or tubular members joined to the inner wall surface of the balloon 1242, and the at least restraining filament 1250 run within this at least one lumen or tubular member and anchored therein. The balloon 1242 may alternatively be formed from different materials, with the filament 1250 being constructed of a stiffer material than the remainder of the balloon 1242, such that the portion of the balloon 1242 with the filament 1240 therein does not expand at the same rate or to the same extent as the remainder of the balloon 1242. In this fifth preferred embodiment, occlusion/perfusion balloon system 1240 does not necessarily include the proximal port 1248 and the distal port 1246, as the filament 1250 may be positioned within the catheters 1240b, 1240c or within a lumen of the catheters 1240b, 1240c. The filament 1250 would, therefore, typically not be exposed to the blood vessel or blood flow in such a configuration, as the filament 1250 would be encased within the balloon 1242 and the catheters 1240b, 1240c, where the filament 1250 would not typically be exposed to fluid and blood flow during use.

Referring to FIGS. 32 and 32A, a sixth preferred embodiment of an occlusion/perfusion balloon system 1260 includes a plurality of balloons 1264 carried commonly on a catheter 1262. The plurality of balloons 1264 may be incorporated with any of the preferred occlusion catheter systems 100, 300, 500, 700, 1700, 1800, described herein. The plurality of balloons 1264 are preferably independently expandable though inflation lumens or an inflation lumen 1265 in the catheter 1262. The inflation lumen 1265 preferably communicates independently with each one of the plurality of balloons 1264. The catheter 1262 preferably includes a seal member 1266 movably mounted therein and a plurality of openings 1268 that pass through the outer wall of catheter 1262 and communicate with the fluid flow lumen 1265. The seal member 1266 is reciprocally movable within the fluid lumen 1265 and selectively occludes or opens one or more of the plurality of openings 1268 in the outer wall of the catheter 1262, thereby permitting fluid flow through the fluid flow lumen 1265 and independently or concurrently into each of the plurality of balloons 1264. In this manner, the volume and rate of fluid flow into the plurality of occluding balloons 1264 may be adjusted by the relative position of the seal member 1266 within the fluid flow lumen 1265.

Referring to FIGS. 33 and 34, a seventh preferred embodiment of an occlusion/perfusion balloon system 1270 preferably does not rely upon an occlusion balloon or upon a fluid pressure to activate an occlusion balloon. Rather, in this seventh preferred embodiment, the occlusion member consists of a supporting cage structure 1272 formed of a plurality of structural members, which may be longitudinally oriented struts 1276 that taper distally, connect to a distal catheter member 1274 and taper proximally where the struts 1276 connect to a proximal catheter member 1275. An

occluding membrane 1278 is preferably coupled to the supporting cage structure and may consist of a partial covering on the supporting cage structure 1272 or may be comprised of a full covering (on the supporting cage structure 1272, as illustrated in FIG. 34 with reference to occlusion/perfusion system 1280 of the eighth preferred embodiment).

The struts of the supporting cage structure 1272 are preferably, fixedly coupled at their distal ends to the distal catheter member 1274 and at their proximal end are preferably, fixedly coupled to the proximal catheter sleeve member 1275. The proximal catheter sleeve member 1275 is reciprocally movable relative to the distal catheter 1274. The relative movement of the proximal catheter sleeve member 1275 relative to the distal catheter 1274 preferably causes deformation of the supporting cage structure 1272 and allows the cage structure 1272 to diametrically expand or diametrically contract under the influence of such relative movement. Such diametric expansion preferably brings the supporting cage structure 1272 and the occluding membrane 1278 into an occlusive position within the lumen of a blood vessel, while diametric contraction preferably reduces the diametric profile of the supporting cage structure 1272 and the occluding membrane 1278, thereby allowing for fluid and blood flow past the occlusion site or past the cage structure 1272.

The supporting cage structure 1272 of the seventh and eighth preferred embodiments, like a balloon, may assume a wide variety of geometries, including, without limitation, spherical, elliptical, conical, square, rectangular, dog boned, tapered, stepped, or combinations thereof, such as, for example, conical/square or conical/spherical. The supporting cage structure 1272 and its struts 1276 may be made of any suitable biocompatible material, including polymers, metals and/or composites or combinations thereof. The biocompatible material may be an elastic, superelastic, shape memory material and is preferably able to take on the general size and shape of the cage structure 1272, perform the functions of the preferred cage structure 1272 and withstand the normal operating conditions of the cage structure 1272.

The occluding membrane 1278 preferably covers at least a portion of the supporting cage structure 1272 in order to at least partially occlude the blood vessel into which the occlusion/perfusion systems 1270, 1280 are placed. The occluding membrane 1278 may cover a proximal portion of the supporting cage 1272, a distal portion of the supporting cage 1272, the entire cage 1272, such as is shown in the eighth preferred embodiment (FIG. 34), or it may cover only portions of the cage 1272 to permit partial or partially occluded flow through the vessel. The supporting cage 1272 may facilitate pre-conditioning systems that infuse fluid into the vessel to pre-emptively and prophylactically mitigate possible ischemia during occlusion. The catheters 1272, 1275, 1284, 1285 may include infusion holes 1284a therein that facilitate infusion of fluid into the vessel and the infusion holes 1284 may extend along all or a portion of the longitudinal length of the catheters 1272, 1275, 1284, 1285. Furthermore, the occluding membrane 1278 may have an opening 1279 in a proximal end to allow fluid flow there-through to facilitate partial occlusion and perfusion.

The occluding membrane 1278 is preferably constructed of a woven or non-woven biocompatible material, such as polymers, metals, composites and combinations thereof, and may be elastic, superelastic or shape memory. The occluding membrane 1278 may cover the outer surface of the supporting cage 1272, the inner surface of the supporting cage 1272,

or both. The occluding membrane **1278** may be joined to the supporting cage **1278** by sutures, biocompatible adhesive, by reflow, by thermal welding, or by joining to another layer of occluding membrane **1278** on the opposing surface of the supporting cage **1272** such that the struts of the supporting cage **1278** are at least partially encapsulated by the occluding membrane **1278**. Methods and materials for joining the occluding membrane **1278** to supporting cage **1272** may include adhesive bonding, fastening, clamping, co-molding and other related engagement techniques.

Referring to FIGS. **35A-35C**, in a ninth preferred embodiment, an occlusion balloon system **2000** includes a balloon or inflatable occlusion member **2001** with a plurality of projecting members **2002** projecting from an outer wall surface **2003** of the balloon **2001**. The balloon **2001** is connected to a proximal catheter member **2004** and a distal catheter member **2005**, which may be incorporated into any of the preferred occlusion catheter systems **100**, **300**, **500**, **700**, **1700**, **1800**, described herein. The proximal catheter member **2004** includes an inflation lumen therein that facilitates inflation of the balloon **2001**. The projecting members **2002** preferably extend substantially radially away from a central longitudinal axis **2006** of the balloon **2001** and extend along the outer surface **2003** substantially laterally or circumferentially around the longitudinal axis **2006**. The preferred projecting members **2002** preferably extend around an entire circumference of the balloon **2001**, but are not so limited and may extend partially around the outer surface **2003**, may extend at angles relative to the longitudinal axis **2006**, may be comprised of various pockets on the surface **2003** or may be otherwise configured to create spacing between a vessel **2008** and the outer surface **2003**, at least when the balloon **2001** is partially inflated. The balloon **2001** of the ninth preferred embodiment includes four projecting members **2002** longitudinally spaced along the length of the balloon **2001**. The end projecting members **2002** taper in an arcuate shape to connections with the proximal and distal catheters **2004**, **2005**. The outer surface **2003** of the balloon **1222** preferably has a constant diameter at the peaks of the projecting members **2002**, but is not so limited and may have tapered or variable spacing relative to the longitudinal axis **2006**. Lateral channels **2007** are preferably defined between the projecting members **2002** when the balloon **2001** is at least partially inflated and are comprised of circumferentially extending voids wherein the vessel **2008** is out of contact with the outer surface **2003** in the channels **2007**. In contrast, when the balloon **2001** is fully inflated or is in an inflated configuration, the balloon **2001** expands such that the outer surface **2003** is substantially consistent and channels **2007** are not formed. In this fully inflated configuration or at least close to the fully inflated configuration, the outer surface **2003** is in direct contact with the vessel **2008** and fluid and blood flow are substantially occluded in the vessel **2008**. The projecting members **2001** defined in at least the partially inflated configuration are not limited to extending substantially laterally or circumferentially around the longitudinal axis **2006** and the projecting members **2002** are not limited to having a substantially constant diameter. The balloon **2001** may be otherwise designed and configured such that the balloon **2001** is able to partially and fully occlude the vessel **2008** and withstand the normal operating conditions of the preferred occlusion balloon system **2000**.

The projecting members **2002** in the partially inflated configuration of the balloon **2001** preferably permit at least partial flow of blood and fluid substantially parallel to the longitudinal axis **2006** when the occlusion balloon system

2000 is positioned within the vessel **2008**. The balloon **2001** of the system **2000** may be inflated to various levels to enhance or reduce the channels **2007** and the position of the projecting members **2002** relative to the inner wall of the vessel **2008**, depending on the preferred procedure, preferences of the medical technician or conditions encountered or detected within the vessel. Generally, as the pressure is increased within the balloon **2001**, the projecting members **2002** come into closer positioning relative to the inner surface of the vessel **2008** and, therefore, limit flow of fluid and blood through the vessel **2008**.

Referring to FIG. **35D**, in a tenth preferred embodiment, an occlusion/perfusion balloon system **2100** includes a balloon or inflatable occlusion member **2101** with a spiral-shape projecting from a longitudinal axis **2106** of the tenth preferred occlusion/perfusion balloon system **2100**. The inflatable occlusion/perfusion balloon **2101** includes channels **2107** defined between projecting portions **2102** of the spiral-shaped balloon **2101** that permit flow of blood past the balloon **2101** when inserted into the vessel and at least partially inflated. Similar to the ninth preferred occlusion balloon system **2000**, the tenth preferred occlusion/perfusion balloon system **2100** may be fully inflated within the vessel and substantially or completely occlude the vessel. The tenth preferred occlusion/perfusion system **2100** also includes a proximal catheter **2104** and a distal catheter **2105** connected to proximal and distal balloon ends of the balloon **2101**, which may be incorporated into any of the preferred occlusion catheter systems and other preferred systems having inflatable balloons or occlusion members described herein.

In each of the foregoing described embodiments of the occlusion/perfusion balloon systems depicted and described with reference to FIGS. **23-35C**, the systems may also include sensors, transmitters, receivers, interrogators or other means for measuring physical and/or physiological parameters distal and/or proximal one or more of the expandable occlusion members, including, for example blood pressure sensors, heart rate sensors, flow sensors, chemical sensors, temperature sensors, oxygenation sensors, ischemia sensors, biological sensors, imaging sensors or the like. Data collection of the readings from the sensors may be utilized with a controller or processor to control inflation of the balloons or occlusion members of the preferred systems to facilitate partial flow of fluid and blood through the vessel **2008** when desired or to fully occlude the vessel **2008**, as desired by the medical technician.

Pre-Conditioning Systems

Referring to FIGS. **36-37C**, pharmacologically active agents, such as pressors, anticoagulants, anti-inflammatory agents, anti-hypertensive agents, anti-hypotensive agents, anti-arrhythmic agents, or any other indicated agent may be delivered using a fourth preferred embodiment of an occlusion catheter system **1300** or a pre-conditioning system **1300**. Larger volume infusions are also deliverable using the pre-conditioning system or the fourth preferred embodiment of the occlusion catheter system **1300**, including blood, blood products, extracorporeal membrane oxygenation adjuncts, hypothermia adjuncts, saline, contrast or other therapeutic or diagnostic agents.

A four preferred occlusion catheter system or pre-conditioning system **1300** generally comprises a balloon catheter that has a plurality of proximal side ports **1308** positioned proximal an occlusion member or balloon **1304** and a plurality of distal side ports **1310** positioned distally relative to the occlusion member or balloon **1304**. The plurality of

51

proximal side ports **1308** and the plurality of distal ports **1310** are operable independently of each other to deliver fluids from the forth preferred occlusion catheter system **1300** to the blood vessel into which the forth preferred system **130** is introduced. The pre-conditioning system **1300**, synonymously termed "infusion system," includes a second catheter member **1302** that is connected to a proximal hub **1301** attached to a proximal end of the second catheter member **1302**. The occlusion member **1304** is coupled toward a distal end of the second catheter member **1302**. The occlusion member **1304**, while depicted in FIG. **43** as a balloon, may be any type of member capable of vascular occlusion, such as those other embodiments of occlusion members disclosed herein or as are known in the art.

The second catheter member **1302** has a second lumen **1303** passing along a substantial longitudinal length of the second catheter member **1302**. The second catheter member **1302** also has at least one, but preferably the plurality of proximal side ports **1308** passing through an outer wall of the second catheter member **1302**. The plurality of proximal side ports **1308** is preferably in fluid flow communication with the second lumen **1303**. The plurality proximal side ports **1308** may be in a regular or irregular pattern and may be positioned about the circumference of the second catheter member **1302** or may have only a single orientation relative to the central longitudinal axis **1331** of the infusion catheter system **1300**.

A third catheter member **1320** of the fourth preferred occlusion catheter system **1300** extends distally relative to the occlusion member **1304** and terminates in an atraumatic tip **1306** or forms a proximal shaft or portion of the atraumatic tip **1306**. The third catheter member **1320** has a third lumen **1322** passing along a substantial longitudinal length of the third catheter member **1302**, preferably along and coaxially with the longitudinal axis **1331** near the distal end of the infusion catheter system **1300**. The atraumatic tip **1306** is described above in greater detail with reference to the embodiments of the occlusion catheter **100**, **300**, **500**, and serves to guide the catheter system **1300** as it traverses the vasculature and prevents the fourth preferred catheter system **1300** from tracking into collateral vessels, while preferably eliminating the need for a guide wire for placement of the occlusion catheter system **1300**. The occlusion catheter system **1300** may also incorporate the atraumatic tip **450**, **550** of the second the third preferred embodiments of the occlusion catheter system **300**, **500**, as is described herein.

At least one of and preferably all of the plurality of distal side ports **1310** pass through the outer wall of the third catheter member **1320** and communicate with the third lumen **1322** to communicate fluid distally relative to the occlusion member **1304**. The plurality of distal side ports **1310** may be in a regular or irregular pattern and may be positioned about the circumference of the third catheter member **1320** or may have only a single orientation relative to the central longitudinal axis **1331** of the infusion catheter system **1300**.

In the fourth preferred embodiment of occlusion catheter system **1300** where the occlusion member **1304** is a balloon, three lumens are preferred to service inflation of the occlusion member **1304** and fluid delivery to or sample collection from both of the plurality of proximal side ports **1308** and the plurality of distal side ports **1308**. At least one hypotube or second catheter member **1312** is disposed within the second lumen **1303**. Where the second catheter member or hypotube **1312** is employed, the second catheter member

52

1312 preferably has at least a first hypotube lumen **1314** and a second hypotube lumen **1316**, with the first hypotube lumen **1314** configured to communicate an inflation fluid to the occlusion balloon **1304** and the second hypotube lumen **1316** configured to communicate fluid to the third catheter member **1320** and the plurality of distal side ports **1310** through the third lumen **1322**, such that the third lumen **1322** is in fluid communication with the second hypotube lumen **1316**. The second lumen **1303**, between the second catheter member **1312** and the first catheter member **1302**, preferably communicates fluid from the proximal hub **1301** to the plurality of proximal side ports **1308**.

The at least one hypotube or second catheter member **1312** is preferably constructed of a material having different material properties than the first catheter member **1302** or the third catheter member **1320**, such that the first lumen **1312** increases the column strength, pushability and pullability of the occlusion/infusion catheter system **1300** within the vasculature. In accordance with the fourth preferred embodiment of the occlusion catheter system **1300**, the second catheter member **1312** is constructed of a relatively strong metal, preferably stainless steel or nitinol. The second catheter member **1312** may alternatively be constructed of a polymer, preferably a polymer having a higher hardness than that of either the first catheter member **1302** or the third catheter member **1320**, but is not so limited. The first catheter member **1302**, second catheter member **1312** and third catheter member **1320** may also be combined in construction and configuration to have a transitioning stiffness, to include a separate stiffening member, such as a nitinol wire or braided shaft, to have sufficient pushability to have the appropriate amount of column strength.

Referring to FIGS. **37-37C**, a fifth preferred embodiment of the occlusion/infusion system **1350** is generally similar to the infusion system or occlusion catheter system **1300** of the fourth preferred embodiment. The occlusion/infusion system or occlusion catheter system **1350** of the fifth preferred embodiment employs a first hypotube **1362** and a second hypotube **1364** within a second lumen **1353** of a second catheter member **1352**. The second hypotube **1364** extends from the proximal end of the second catheter member **1352** and terminates in communication with the occlusion balloon **1354**. Inflation fluid is communicated through a second hypotube lumen **1365** of the second hypotube **1364**, through an inflation port **1357** in the second catheter member **1352** that is positioned within a space **1355** defined within the balloon **1354** and fills the space **1355** to inflate the balloon **1354**. A seal **1349** is positioned within the second catheter member **1352** distal to the inflation port **1357** to seal the second lumen **1353** distally of the seal **1349** and permit the inflation fluid to flow through the inflation port **1357** and into the balloon **1354**, but not distally of a distal end of the balloon **1354** in the second lumen **1353**. The first hypotube **1362** extends within the second lumen **1353** of the second catheter member **1352**, extends beyond the seal **1349** and terminates within the third lumen **1368** in the distal portion of the second catheter member **1352** or a proximal portion of the atraumatic tip (not shown) to communicate with a plurality of distal side ports **1360**. In this manner, fluid introduced into the first hypotube **1362** is communicated through the first hypotube lumen **1363** to the plurality of distal side ports **1360** for release through the plurality of distal side ports **1360** distal to the occlusion balloon **1354**.

It will be appreciated, therefore, that fluids may be infused through either the plurality of proximal side ports **1358** or the plurality of distal side ports **1360**, independently, or through both, concurrently. The same or different infusion

fluids may be infused through the plurality of proximal side ports **1358** and the plurality of distal side ports **1360**, as well. The size, shape and position of the plurality of proximal side ports **1358** and that of the plurality of distal side ports **1360** may be configured to be the same or different and may be configured depending upon the type of fluid being infused. Furthermore, the plurality of proximal side ports **1358**, the plurality of distal side ports **1360**, the first hypotube **1362** and the second hypotube **1364** may be constructed of materials and tolerances suitable for powered injection at higher pressures and flow rates.

Alternatively, an adjunctive or secondary infusion catheter, such as those that are known in the art, that comprises a low-profile catheter shaft, a fluid connector at a proximal end of the catheter shaft and a plurality of fluid openings at a distal end of the catheter shaft, may be engaged to pass within the second lumen **1353**, down the length of the second catheter member **1352** and out of a port distal to the occlusion member **1354**. In this manner, the fourth and fifth preferred occlusion catheter systems **1300**, **1350** may or may not have the plurality of proximal and distal side ports **1308**, **1310**, **1358**, **1360**, but may simply employ a secondary infusion catheter that is inserted into the second lumen **1303**, **1353** of the second catheter member **1302**, **1352**, or, where the preferred occlusion catheter systems **1300**, **1350** include the plurality of proximal and distal side ports **1308**, **1310**, **1358**, **1360**, the secondary infusion catheter may be inserted into a lumen, for instance the second hypotube lumen **1316**, such that it will be able to extend a substantial longitudinal length of second catheter member **1302**, **1352** and deliver fluid through the plurality of distal side ports **1310**, **1360**.

Finally, it will be understood by those in the art, that the terminus of the third lumens **1322**, **1368** may be configured to laterally guide a guiding tip of a guide wire or catheter out of either the plurality of distal side ports **1310**, **1360** or out of a dedicated skive (not shown) formed in the distal wall surface of third catheter member **1320**, **1370**.

An alternative configuration of the fourth and fifth preferred occlusion catheter systems **1300**, **1350** may employ a secondary or adjunctive infusion catheter that is utilized for the primary occlusion, then as infusion is required, to endoluminally deliver the secondary infusion catheter laterally to the already placed occlusion catheter, diametrically collapse the occlusion member to permit luminal space for the infusion catheter to pass the occlusion member, then reestablish occlusion when the infusion catheter is positioned distal to the occlusion member, thereby forming occlusion around the infusion catheter.

In each of the foregoing described embodiments of the pre-conditioning systems or the fourth and fifth preferred embodiments of the occlusion catheter systems **1300**, **1350** depicted and described with reference to FIGS. **35-36C**, the systems **1300**, **1350** may also include sensors, transmitters, receivers, interrogators or other means for measuring physical and/or physiological parameters distal and/or proximal one or more of the expandable occlusion members **1304**, **1354**, including, for example blood pressure sensors, heart rate sensors, flow sensors, chemical sensors, temperature sensors, oxygenation sensors, ischemia sensors, biological sensors, imaging sensors or the like.

Hemorrhage Exclusion and Flow Restoration Systems

The foregoing described embodiments of the vascular occlusion catheter system operate by creating a luminal obstruction to blood flow to the hemorrhage site to at least

partially stem the outflow of blood and permit vascular repair of the hemorrhage site while preserving blood flow to the patient's brain and other vital organs. Alternative embodiments of the present invention operate to create an obstruction and occlude the hemorrhage site within the vascular wall. Moreover, rather than create luminal obstruction to blood flow, typically superior to the hemorrhage site, these alternative embodiments, restore patency of the blood vessel at the hemorrhage site and permit blood flow past the hemorrhage site while obstructing and occluding the trauma or injury to the vessel wall itself.

FIG. **38** illustrates a first preferred embodiment a hemorrhage exclusion system **1400** in accordance with the present invention. The preferred hemorrhage exclusion system **1400** is conceptually similar to occlusion/perfusion system **1270** depicted in FIG. **33**. In the first preferred hemorrhage exclusion system **1400**, an elongate support structure **1412** is formed of a plurality of structural support members, and is connected to a longitudinally extending catheter or catheter sleeve **1406**. The structural support members, which may be longitudinally oriented struts, form a distal cage section **1408** and a proximal cage section **1402**. The distal cage section **1408** is preferably, immovably coupled to a distal end of the catheter **1406** and, when an atraumatic guiding tip **1404** is provided, proximal to the atraumatic guiding tip **1404**. The proximal cage section **1410** is coupled to the catheter sleeve member **1406**. An intermediate cage section **1416** extends between the proximal cage section **1410** and the distal cage section **1408**. The hemorrhage exclusion system **1400** also includes an elongate support structure in the intermediate cage section **1416** that is preferably comprised of a continuation of the structural support members of the proximal and distal cage sections **1410**, **1408** with a large open volume within the support structure. The open volume between the structural support members of the proximal cage section **1410** and distal cage section **1408** facilitates blood flow longitudinally through the elongate support structure along the outside of the catheter sleeve **1406**. The elongate support structure—may be constructed of any appropriate biocompatible material, including polymers, metals, composite materials or combinations thereof, as discussed above with reference to the occlusion members.

An exclusion member **1414** is carried on the intermediate cage section **1416** by the structural support members. The exclusion member **1414** extends along at least a substantial extent of the intermediate cage section **1416**. The exclusion member **1414** may be fabricated of any appropriate woven or non-woven biocompatible material, including polymers, metals, composite materials or combinations thereof, as discussed above in reference to the occlusion members. The exclusion member **1414** may be plastically deformable, elastically deformable, or have shape memory or superelastic properties. The exclusion member **1414** is preferably, generally tubular and may be porous, non-porous or bioabsorbable. The exclusion member **1414** may be coupled to either the outer or inner surface of the elongate support structure **1412**, or both. Coupling between the exclusion member **1414** may be in accordance with any methods and materials for joining biomaterials to support structures, including, without limitation, sutures, biocompatible adhesive, by reflow, by thermal welding, or by joining to another layer of exclusion member **1414** on the opposing surface of the support structure **1412** such that the struts of the support structure **1412** are at least partially encapsulated by the joined layers of the exclusion member **1414**.

55

The catheter sleeve or catheter **1406** is preferably comprised of proximal and distal sections that are movably coupled to each other such that relative movement of the proximal and distal catheter sleeve members **1406** translates to diametric expansion or contraction of the elongate support structure **1412** and the exclusion member **1414**. The proximal and distal portions of the catheter sleeve member **1406** are preferably comprised of a tubular structure with a lumen through which an opposing catheter passes. The catheter sleeve **1406** is not so limited and may be constructed of nearly any assembly or construction that permits collapse and expansion of the elongate support structure **1412**, wherein the elongate support structure **1412** has a similar diameter to the catheter sleeve **1406** in the collapsed configuration and has an expanded (FIG. **38**) diameter that allows blood flow through the intermediate cage section **1416** in the expanded configuration.

The elongate support structure **1412**, may assume a wide variety of geometries, provided that the exclusion member **1414** supported on the elongate support structure defines a fluid flow pathway to restore patency to the vessel and allow blood to flow past the hemorrhage site.

In use, the hemorrhage exclusion system **1400** is advanced to a hemorrhage site. Contrast may be injected through the catheter **1406** and out of a port **1403** near the distal end of the catheter **1406** to image the hemorrhage, determine its position in the vessel wall and preferably estimate its relative size. The exclusion member **1414** is preferably positioned in such a manner as to span the hemorrhage site and extend both proximal and distal relative to the hemorrhage site. The support structure **1412** and the exclusion member **1414** are diametrically expanded into apposition with the vascular luminal wall surface, by relative movement of the proximal and distal portions of the catheter sleeve **1406**. The exclusion member **1414** preferably blocks flow of blood out of the hemorrhage site and allows blood to continue to flow through the vessel and, preferably, preventing flow of blood out of the hemorrhage. Further imaging using injected contrast may be employed to verify successful positioning of the exclusion member **1414** and coverage of the hemorrhage site to stem the outflow of blood from the vessel trauma or injury. Alternatively or additionally blood pressure and/or blood flow data may be obtained by pressure and/or flow sensors operably associated with the hemorrhage exclusion system **1400**, to also verify successful placement of the exclusion member **1414** and restoration of vascular patency and blood flow through the lumen of the exclusion member **1414**, through the elongate support structure **1412** and through the vessel. The exclusion member **1414** is preferably maintained in place blocking the hemorrhage site at least until the medical practitioner is able to develop a plan to repair the hemorrhage.

An alternative preferred embodiment of the occlusion catheter system, which is similar to the foregoing hemorrhage exclusion system **1400** of the first preferred embodiment, involves eliminating the central catheter sleeve member **1406** and affixing the proximal cage section **1402** to a more proximal section of the catheter **1406**. A constraining sheath (not shown) is then placed over the catheter **1406**, the elongate structural support **1412** and the exclusion member **1414**, constraining the structural support **1412** and exclusion member **1414** in a reduced diametric state until the constraining sheath is withdrawn. This configuration is particularly well suited where the elongate structural support **1412** is made of an elastic, shape memory or super elastic material. This alternate preferred embodiment is conceptually

56

similar to the manner in which self-expanding or shape memory stents are endovascularly delivered and placed.

Referring to FIGS. **39-39B**, another or second preferred embodiment of the occlusion catheter system or hemorrhage exclusion system **1450** does not employ an elongate support structure **1414**, as is utilized in the first preferred embodiment of the hemorrhage exclusion system **1400**. The second preferred system **1450** includes a catheter **1452** having a relatively larger diametric profile which carries within a lumen in the catheter **1452** a furled or rolled sheet of an exclusion material **1456**. An elongate spindle member **1453** carrying a rolled sheet of exclusion material **1456** is preferably positioned within a lumen of the catheter **1452**. The catheter **1452** has an elongated slot **1455** passing through a wall surface of the catheter **1452**. The exclusion material **1456** preferably has a leading edge that projects out of an elongate slot **1455** and, when the elongate spindle member **1453** is rotationally moved within the lumen of catheter **1452**, the exclusion material **1456** unfurls or unrolls out of the elongated slot **1455**. As the exclusion material **1456** fully unrolls from within the catheter lumen, the exclusion material **1456** preferably forms a diametrically enlarged generally tubular structure with at least one region of overlap of the exclusion material **1456**, such that a first winding of the exclusion material **1456** forms an outer layer **1459** of the tubular structure and a second winding of the exclusion material **1456** forms an inner layer of the tubular structure. The tubular structure so formed defines a central lumen **1460** that allow blood flow through the tubular structure while the exclusion member **1456** is deployed in its diametrically expanded state.

In use, the hemorrhage exclusion system **1450** of the second preferred embodiment is endoluminally delivered to a hemorrhage site. Similar to the hemorrhage exclusion system **1400** of the first preferred embodiment, the hemorrhage site may be imaged by contrast injection to position the exclusion system **1450** relative to the hemorrhage site. Once properly positioned, the elongate spindle **1453** is rotatably actuated to unfurl or unroll the exclusion member **1456** through the elongate slot **1455** until it assumes its enlarged tubular shape and defines the blood flow central lumen **1460** and is preferably in apposition with the vascular wall surface and excludes or bypasses the hemorrhage site. Exclusion or bypass of the hemorrhage may be verified by contrast imaging or by blood pressure and/or blood flow data obtained from the patient or from blood pressure and/or blood flow sensors operably associated with, preferably attached to the exclusion system **1450**.

In each of the foregoing preferred embodiments of the hemorrhage exclusion systems **1400**, **1450** depicted and described with reference to FIGS. **38-39B**, the systems **1400**, **1450** may also include sensors, transmitters, receivers, interrogators or other means for measuring physical and/or physiological parameters distal and/or proximal one or more of the expandable occlusion members, including, for example blood pressure sensors, heart rate sensors, flow sensors, chemical sensors, temperature sensors, oxygenation sensors, ischemia sensors, biological sensors, imaging sensors or the like. The sensors may communicate with a controller, which may control various aspects of the operation of the systems **140**, **1450**, such as unfurling the exclusion member **1456** or collapsing the exclusion member **1456**.

Inflation Control Systems

Referring to FIG. **40**, a first preferred of an inflation control system **1500** may be utilized with any of the pre-

57

ferred occlusion catheter systems and other preferred systems having inflatable balloons or occlusion members described herein. In the first preferred embodiment, the inflation control system **1500** is preferably connected in-line between an inflation device (i.e. pressure source) and the balloon catheter, such as the first preferred occlusion catheter system **100**. The inflation control system **1500** preferably helps to prevent the user from overinflating the balloon, such as the occlusion member **140** and damaging the blood vessel into which the occlusion member or balloon **140** is inserted. The inflation control system **1500** preferably includes a pressure source **1502**, such as a syringe, which may be manually actuated or may be coupled to any of a large number of known automated injectors or pressure systems. The pressure source **1502** has a fluid source contained within the syringe, and is coupled to a bifurcated pressure conduit **1506**, that in turn communicates with a free line and a regulated line. A one-way check valve **1508** is interposed in the regulated line to prevent both backpressure and backflow to the syringe **1502**. A selectable flow valve **1504** is interposed in the free line and communicates with the regulated line. The selectable flow valve **1504** is operable to select the free line, the regulated line or both the free line and the regulated line. A fluid conduit leads from the selectable flow valve **1504** to a pressure sensor **1510**. A coupling **1512**, preferably a luer lock fitting, is provided to couple the occlusion catheter (not shown) to the pressure sensor **1510**. While an analog pressure gauge is shown in FIG. **55**, the analog pressure gauge is not limiting and a wide variety of analog or digital pressure sensors **1510** are capable of being used to provide the medical practitioner with information concerning the pressure in the inflation control system **1500**.

In use, the inflation control system **1500** allows the practitioner to apply fluid pressure to the occlusion catheter, e.g., by advancing the syringe plunger, to inflate the occlusion balloon, while simultaneously preventing both backpressure and backflow. When the selector valve **1504** is positioned to open the regulated line and close the free line, fluid is free to flow through the check valve **1506** to the occlusion catheter and ultimately to the balloon. Pausing during inflation will not result in deflation of the balloon because when force is no longer applied to the syringe plunger, the fluid no longer advances through the check valve **1508** and the backpressure from the elastic balloon causes the fluid to try to exit the balloon/catheter, thereby causing the check valve **1508** to close.

The pressure sensor **1510** preferably senses the applied pressure at the pressure source **1502**, but not necessarily at the occlusion balloon. Namely, because of the length of the occlusion catheter and the high resistance of the fluid passing through the narrow annular space of the catheter shaft, the pressure at the pressure gauge **1510** may be higher than the actual pressure in the balloon, but allowances and compensation may be calculated to predict or measure the pressure within the balloon with the gauge **1510**. A dwell time typically exists between the time pressure is applied at the pressure source **1502** and when the pressure equilibrates at the occlusion balloon, but the pressure in the system between the check valve **1508** and the balloon quickly equalizes and the pressure sensor **1510** accurately reads the true pressure in the balloon. Excluding backpressure and backflow via the check valve **1508** creates a closed system in which the pressure can be allowed to equilibrate, as represented by a constant pressure readout on the pressure sensor **1510**, which will then represent the pressure at the

58

occlusion balloon. Additional fluid pressure may then be applied at the pressure source **1502**.

As should be understood, the pressure sensor **1510** may have a "target occlusion pressure" identified thereon (i.e. such as a blue zone of the gauge **1510**) that the practitioner knows to keep inflating until the needle comes a rest in the blue zone. This would indicate occlusion but not over inflation. Therefore, since this system is based on pressure and not volume, it is not necessary to know the vessel diameter before inflating the balloon. Rather, the practitioner need only fill the balloon until the needle of the pressure gauge **1510** comes to a rest in the "blue zone".

Pressure may be withdrawn from the occlusion balloon by means of the selector flow valve **1504** being switched to open the free line, by-passing the check valve **1508**, and releasing pressure back to the pressure source **1502** from the occlusion balloon. The syringe plunger is preferably retracted and the fluid is drained from the balloon back into the syringe **1502**.

Referring to FIG. **41**, a preferred second embodiment of an inflation control system **1550** is useful in the preferred inflation method of the present invention. A conventional balloon inflation device **1562** is illustrated in FIG. **41** (such as a QL Inflation Device, Atrion Medical, Arab, Alabama). The inflation device **1562** has a fluid chamber and a plunger **1564**. The plunger **1564** is preferably threaded to allow for rotation of the plunger **1564** relative to the fluid chamber and controlled depression of the plunger **1564** within the fluid chamber. A fluid conduit **1563** communicates with an outlet **1561** in the inflation device **1562** to communicate the inflation fluid to the occlusion catheter (not shown), such as the occlusion catheter system **100** of the first preferred embodiment or any of the other preferred occlusion systems described herein, that is coupled to the inflation device **1550** via a coupling **1561**. A pressure sensor **1560** is preferably provided in the outlet line of the inflation device **1550**. A lock **1566** is preferably provided that engages the threaded plunger **1564** during pressurization and disengages from the threaded plunger **1564** during depressurization. The lock **1566** acts, essentially, to isolate the pressure within the occlusion balloon, catheter and fluid conduit **1563** and resists transmitting backpressure or fluid backflow to the plunger **1564**. Essentially, the lock **1566** functions in a manner similar to the check valve **1508** in the preceding first preferred embodiment of the inflation control system **1500**.

The method of inflating the occlusion balloon (not shown) using the inflation device **1562** entails the practitioner filling the fluid chamber with an inflation fluid by withdrawing the plunger **1564** to fill the fluid conduit **1563** and the fluid chamber. Expelling any air present in the fluid chamber and fluid conduit and connecting the inflation device **1550** to the occlusion catheter (not shown). To inflate the occlusion balloon, the plunger **1564** is actuated either by linear force or by rotating the plunger **1564** to engage the threads for a controlled pressurization. The lock **1566** should be engaged with the plunger **1564** to resist backpressure as the balloon occlusion member inflates. The pressure sensor **1560** will sense the applied pressure at the inflation device **1550**, but not necessarily at the occlusion balloon. Because of the length of the occlusion catheter, a dwell time exists between the time pressure is applied at the inflation device **1550** and when the pressure equilibrates at the occlusion balloon. By excluding backpressure and backflow, the lock **1566** serves to create a closed system in which the pressure can be allowed to equilibrate, as represented by a constant pressure readout on the pressure sensor **1560**. When the pressure indicated on the pressure sensor **1560** is stable, this will then

59

represent the pressure at the occlusion balloon. Additional fluid pressure may then be applied or pressure may be withdrawn from the occlusion balloon by either reversing the rotation of the plunger, essentially unthreading the plunger **1564**, and depressurizing the balloon, or by means of releasing the lock **1566** and withdrawing the plunger **1564**.

The second preferred inflation device **1550** is not limited to the specific arrangement described and shown herein and further mechanisms may be employed to prevent the user/practitioner from overinflating the balloon and damaging the blood vessel or the balloon. For example, as shown in FIG. **41A**, any of the preferred vascular occlusion catheter systems, such as the first, second or third preferred occlusion catheter systems **100**, **300**, **500**, may include a spring biased valve **1501** positioned within the catheter, proximal the atraumatic guiding tip **150**, **450**, **550**, including a plunger **1501a** sealingly engaging the catheter lumen and occluding a port **1503** located distally therefrom. The spring **1501b** biases the piston **1501a** into the position occluding the port **1503** and may define a spring constant configured to be overcome by a counteracting force corresponding to a pressure equal to or less than the cracking pressure of the vessel. Therefore, prior to overinflating the balloon and damaging the vessel, the pressure within the catheter overcomes the spring **1501b** bias and pushes the plunger **1501a** distally to expose the port **1503** and permit pressure release therethrough. The spring **1501b** will push the plunger **1501a** back into the position occluding port **1503** once sufficient pressure is released.

Infection/Contamination Control System

Rapid endovascular occlusion or exclusion of a traumatic hemorrhagic injury while on the battlefield or on the street involves not only a non-sterile environment, but an environment that is may be highly contaminated and prone to a wide variety of sources of bacterial or viral infections. It is desirable to design, construct and deploy a device that facilitates vascular access and endovascular delivery of a vascular occlusion catheter while minimizing infections resulting from contamination when used in austere environments, i.e., on the battlefield or on the street, rather than in a hospital or other sterile or controlled environment.

Referring to FIGS. **42A** and **42B**, a first preferred infection control catheter sleeve system **1600** provides a substantially sterile field for the occlusion catheter **1602** and the occlusion balloon **1608** during access and endovascular delivery and through the vascular occlusion procedure. The occlusion catheter preferably includes an inflation catheter **1602a** positioned proximate the balloon **1608** and a distal catheter member **1602b** positioned distally relative to the balloon **1608**. The inflation catheter member **1602a** preferably has an inflation lumen similar to the inflation lumens described herein with respect to the preferred occlusion catheter members that has a port opening into an inner area of the occlusion balloon **1608** to permit inflation and deflation of the occlusion balloon **1608**. The catheter sleeve system **1600** generally comprises a sleeve **1610** that is preferably comprised of an elongate tubular structure fabricated of a highly resilient material capable of being sterilized. The catheter sleeve **1610** is preferably a thin walled, elastic in inelastic polymer material that is capable of being longitudinally collapsed in an accordion-like fashion to ease insertion of the catheter **1602** into the sterile lumen of the elongate tubular structure **1610** and thereafter elongated in an accordion-like fashion as needed to cover substantially

60

the entire shaft of the catheter **1602** in a covered configuration. The catheter sleeve **1610** preferably has hub members **1604**, **1606** at respective proximal sleeve and distal sleeve ends **1610a**, **1610b** of the catheter sleeve tubular structure **1610** that permit the catheter **1602** to extend into and through the catheter sleeve **1600** while generally maintaining hemostasis and a sterile field within the catheter sleeve **1600**. The preferred system **1600** includes proximal and distal hub members **1604**, **1606** that may be constructed and configured as any type of hemostatic valve that permits the catheter **1602** to pass through the valve, such as, for example, without limitation, a Tuohy Borst valve.

The distal hub member **1606** may also include surfaces, such as flanges, wings, or other projections from the distal hub member **1606** that facilitate close approximation with the patient's skin and application of a shield dressing or other adhesive dressing to retain the distal hub member **1606**, catheter sleeve **1600** and catheter **1602** positioned on the patient after the occlusion catheter has been delivered.

In use, as the distal tip of the catheter **1602** is inserted into an introducer sheath or the patient's body with the atraumatic tip **1605** substantially straightened along the longitudinal axis **1601** and the distal hub member **1606** of the catheter sleeve **1600** preferably remains mated to the introducer sheath during insertion of the catheter **1602**. The preferred thin polymer of the catheter sleeve **1610** collapses in an accordion-like manner as the catheter **1602** is advanced into the body. Therefore, if something non-sterile comes into contact with the outside of the catheter sleeve **1610**, it generally does not contaminate the catheter shaft **1602** that is inserted into the body. In addition, as the catheter **1602** is withdrawn from the patient, the sleeve **1610** is able to expand from its working configuration to the covered configuration such that materials, such as blood, from the vessel of the patient is substantially maintained within the sleeve **1610** or is swiped from the catheter **1602** by the distal hub **1606**.

Guide Wire Compatibility

As indicated above, the vascular occlusion catheter systems, such as, for example, without limitation, the first, second and third preferred vascular occlusion catheter systems or occlusion catheter systems **100**, **300**, **500**, are preferably capable of use without the need for a guide wire **1700**. Guide wires **1700** are typically designed to navigate vessels to reach a desired vessel segment. Once the guide wire **1700** arrives at the destination in the vessel, the guide wire **1700** acts as a guide that facilitates delivery of the catheter system to the destination vessel segment. The atraumatic tip described above in detail with reference to the preferred embodiments of the occlusion catheter system **100**, **300**, **500**, serves to guide the catheter as it traverses the vasculature and typically prevents the catheter from tracking into collateral vessels, while preferably eliminating the need for a guide wire for catheter placement.

Practitioners, may desire for the preferred vascular occlusion catheter systems described herein to include guide wire capability for familiarity purposes. Accordingly, as shown in FIGS. **43** and **43A**, an eighth preferred vascular occlusion catheter system **1701** is provided with guide wire capability, while not requiring the guide wire **1700** for use. In this preferred embodiment, the spiral or substantially circular shape of the atraumatic tip **1706**, which is preferably configured in the same manner as the atraumatic tips **450**, **550** of the second and third preferred embodiments, is positioned proximate an exit port **1702** of the catheter system **1701**. The

atraumatic tip **1706** may alternatively be removed and replaced with a distal end defining a substantially straight, compliant end and having the exit port **1702**. The exit port **1702** is in communication with a guide lumen **1703** defined in a tip shaft **1705** of the atraumatic tip **1706**. The guide lumen **1703** is preferably positioned coaxially or substantially parallel and proximate a longitudinal axis **1707** of the catheter system **1701**. The catheter system **1701** preferably includes multiple lumens therein for inflation of an occlusion balloon **1708** and sliding receipt of the guide wire **1700**.

In the preferred embodiment, the guide wire **1700** may be comprised of an eighteen thousandths of an inch (0.018") to an approximately twenty-five thousandths of an inch (0.025") or thirty-five thousandths (0.035") diameter guide wire **1700**. The guide lumen **1703** and other lumens in the catheter system **1701** are designed and configured to accept sliding acceptance of the guide wire **1700**. The guide wire **1700** may be slidably inserted and extend through the catheter system **1701**, preferably coaxially or proximate and substantially parallel to the longitudinal axis **1707**, and extend out of the distal end of the system **1701** through the exit port **1702**. Accordingly, after the guide wire **1700** is inserted into a patient's body, the catheter system **1701** is capable of advancing over the guide wire **1700** to reach the desired vascular destination and the guide wire **1700** may subsequently be removed from the patient while retaining the system **1701**, particularly the occlusion balloon **1708** therein.

The preferred catheter system **1701** includes a proximal hub (not shown) that is the same or similar to the proximal hub of the herein described preferred embodiments. The proximal hub is connected to an inflation catheter member **1709** that is positioned at a proximal end of the occlusion member or occlusion balloon **1708**. The inflation catheter member **1709** has an inflation lumen **1709a** therein that opens into an internal space of the occlusion balloon **1708** at a first port **1709b**. The inflation lumen **1709a** and inflation catheter member **1709** are preferably positioned on or along the longitudinal axis **1707**. The occlusion balloon **1708** preferably has a proximal end **1708a** and a distal end **1708b**, wherein the proximal end is connected to the inflation catheter member **1709**. A distal catheter member **1705**, which may be comprised of the tip shaft **1705** or may be a separate catheter member is positioned substantially on the longitudinal axis **1707** and is connected to the distal end **1708b** of the balloon **1708**.

The atraumatic tip **1706** is connected to or formed integrally with the distal catheter member or tip shaft **1705**. The guide lumen **1703** is formed within the distal catheter member or tip shaft **1705** for slidable receipt of the guide wire **1700**, preferably substantially along the longitudinal axis **1707**.

In the preferred embodiment, the catheter system **1701** may maintain the generally spiral or substantially circular shaped atraumatic tip **1706** during insertion and the guide wire **1700** exits the catheter system **1701** through the exit port **1702** below the atraumatic tip **1706** such that the guide wire **1700** may be initially inserted into the patient and the system **1701** is guided into position along the guide wire **1700**. The lumens of the preferred system **1701**, including the guide lumen **1703** are in communication with the exit port **1702** and are appropriately dimensioned to accommodate the desired diameter guide wire **1700**. In the preferred embodiment, the exit port **1702** is positioned on a lower side of the atraumatic tip **1706**, opposite the circular profile, such that the circular profile is preferably oriented in its relaxed configuration after insertion into the patient's vessel and

during the guiding movement into the appropriate location for the procedure in the vessel.

The catheter system **1701** of the eighth preferred embodiment may also be configured such that the exit port **1702** is located on an opposite side of the atraumatic tip **1706** in the tip shaft **1705**. Referring to FIGS. **43B** and **43C**, the alternative eighth preferred embodiment of the catheter system **1701'** has similar features when compared to the preferred catheter system **1701** and like reference numerals are utilized to identify and describe like features with a prime symbol (') utilized to distinguish the eighth preferred embodiment from the alternative preferred embodiment. In the alternative preferred embodiment, the exit port **1702'** is positioned proximate an inner tip surface **1709'** of the atraumatic tip **1706'** such that the guide wire **1700** would extend out of the alternative preferred system **1701'** into the inner surface **1709'** of the atraumatic tip **1706'**. The guide wire **1700** is preferably sufficiently flexible to deflect out of the way of the atraumatic tip **1706'** as it extends out of the exit port **1702'** to guide the catheter system **1701'** to the appropriate location in the vessel and position the occlusion member (not shown) in the appropriate zone, such as zone I, II or III, as is described above in the Summary of the Invention section. The alternative eighth preferred embodiment otherwise operates substantially the same as the eighth preferred embodiment of the system **1701** with the guide wire **1700**.

Power Injection Capability

Injecting contrast media into a patient's vasculature enables increased visualization using fluoroscopy. Contrast delivery is most effective and efficient using a medical device called a "power injector" that can be programmed to deliver specific amounts of contrast agent at specific flow rates.

Referring to FIG. **44**, in a ninth preferred embodiment, an occlusion catheter system **1800** includes multiple or a plurality of side ports **1809** to distribute contrast medium in the vasculature rapidly and evenly, preferably distally relative to an occlusion member **1808**. At least one side port **1809** (multiple side ports in the illustrated embodiment) is in fluid communication with a lumen, e.g., the first, second and/or third lumen as described above with respect to the preferred catheter systems **100**, **300**, **500**, **1300**, **1350**, accessible from the proximal hub (not shown), such as, for example, without limitation, the proximal hubs **190**, **590**, **790**. Accordingly, contrast medium pumped into the catheter **1800** from the proximal hub is dispensed from the plurality of side ports **1809** and into the surrounding vasculature.

The catheter **1800** is preferably configured in a similar manner to the occlusion catheter system **100** with the first catheter member **130** having the first lumen **230**, the second catheter member **110** having the second lumen **210** and the atraumatic tip **150** with a proximal portion comprised of the third catheter member **120** with the third lumen **220**. The multiple side ports **1809** are preferably formed in the proximal portion of the atraumatic tip **150**, the third catheter member **120** or the first catheter member **130** and may also be formed in each of these components of the catheter **1800**. The plurality of side ports **1809** are in fluid communication with the first lumen **230** through the first catheter member **130**, which is preferably in fluid communication with a power injection mechanism (not shown) through the first fluid pathway **192** in the proximal hub **190**. The space within the occlusion member **1808** is preferably in fluid communication with an injection mechanism, such as the inflation

control system **1500** through the second fluid pathway **194** and the second lumen **210**, which introduces pressurized fluid or gas into the occlusion member **1808** through the distal port opening **160**.

In the illustrated embodiment, the side ports **1809** are located distally from the occlusion member **1808**. The side ports **1809**, however, may be located proximally and/or distally of the occlusion member **1808** and the number of side ports **1809** may be determined according to the desired dispensing rate. The plurality of side ports **1809** may also be located in a single plane or in a circumferential manner around the catheter shaft. The plurality of side ports **1809** may also be utilized to withdraw fluids from the patient's vasculature, such as, for example, for blood sampling.

The lumen in fluid communication with the side ports **1809** may be a hypotube constructed of a metal (e.g., nitinol), a polymer, a reinforced polymer (e.g., braided), or a composite material in order to withstand power injection pressures. The catheter hub, extension lines, and connectors are also constructed of the appropriate polymer/composite material in order to withstand power injection pressures. For example, extension lines may be braid reinforced or otherwise reinforced to withstand the power injection pressures. The catheter **1800** is, therefore, capable of being used safely with a power injector for contrast injections. The catheter **1800** may also be used for visualization of hemorrhage using fluoroscopy by injecting visualization agent into the patient and visualizing flow and, particularly hemorrhage.

Infusion Catheter

Referring to FIG. 45, an infusion catheter or occlusion catheter system **1900** in accordance with a tenth preferred embodiment (not including an occlusion member) can be utilized to infuse and withdraw fluids from a patient's vascular system. Similarly to the occlusion catheter **100**, **300**, **500**, the infusion catheter **1900** includes a distal, curled/spiral, polymeric atraumatic tip **1906** to assist the catheter **1900** to track up a blood vessel and remain in the central lumen of the vasculature. The catheter shaft **1910** is configured to have an appropriate stiffness to be pushable without kinking, while also being sufficiently flexible to not damage blood vessels. The catheter shaft **1910** may be constructed of a polymeric material, a metallic material, or a combination of plastic, metal, and composite materials (e.g., fiberglass, carbon fiber, nylon, etc.) to achieve the appropriate stiffness. The catheter shaft **1910** may be approximately five French (5 Fr) or five and twenty-four hundredths millimeters (5.24 mm), but may alternatively be constructed in other sizes as necessary. Similarly, the diameter of the generally circular profile of the atraumatic tip **1906** (discussed below) may also be sized appropriately according to the destination vessel size. The atraumatic tip **1906** is preferably designed and configured similar to the atraumatic tips **450**, **550** of the second and third preferred embodiments of the occlusion catheter system **300**, **500**, as is described above.

Similarly to the occlusion catheter systems **100**, **300**, **500** of the first, second and third preferred embodiments, the infusion catheter **1900** of the tenth preferred embodiment is intended to be used without a guide wire for rapid insertion. The combination of the atraumatic tip **1906** and catheter shaft **1910** substantially negates the need for a separate guide wire, as is typically utilized in procedures introducing catheters, stents, screws or other devices into the patient. The infusion catheter **1900** preferably has a single lumen **1912** connected to a hub (not shown), e.g., with a standard

luer lock fitting (not shown) at the proximal end of the occlusion catheter system **1900**. The occlusion catheter system **1900** may alternatively be connected with a hub via any of numerous different connectors/fittings, that are currently known or that later become known.

The catheter shaft **1910** of the tenth preferred embodiment includes a plurality of side ports **1909** (a plurality of ports **1909** in the illustrated embodiment) proximal relative to the atraumatic tip **1906**. The plurality of side ports **1909** is in fluid communication with the lumen **1912**. A fluid may be injected at the catheter hub and exit into the vasculature at the plurality of side ports **1909**. The plurality of side ports **1909** preferably assist in distributing the fluid evenly to prevent the fluid stream from causing damage to the blood vessel. The plurality of side ports **1909** may be positioned in a single plane or spiral around the catheter shaft **1910** or may otherwise be arranged and configured to facilitate injection in a manner desired by the medical professional or designer.

As explained above, the catheter shaft **1910** is preferably constructed of a material capable of withstanding the pressures and flow rates of power injection for contrast visualization. The catheter shaft **1910** could be braided or non-braided. The catheter **1900** may also be used for blood pressure monitoring via an external pressure sensor or to withdraw fluids (i.e. blood sampling, blood filtration/oxygenation (extracorporeal membrane oxygenation ("ECMO"), etc.).

The infusion catheter **1900** may be used in combination with an occlusion catheter system, but is not so limited. For example, an occlusion catheter system could be placed in the right femoral artery and advanced to the aorta and the occlusion member inflated to occlude the vessel. The infusion catheter **1900** could be inserted via the left femoral artery and used to infuse fluids (i.e. blood products, hyper-oxygenated perfusate, crystalloids, etc.). The infusion catheter **1900** could also be used with a power/hand injector to inject radiopaque contrast (CO₂, Isovue, etc.) to visualize the hemorrhage.

The infusion catheter **1900** may be packaged with a pre-installed "peel-away sheath" that is used to straighten the atraumatic tip **1906** for insertion into the valve of the introducer sheath or directly into the blood vessel. The peel-away sheath is advanced distally to capture and straighten the atraumatic tip **1906** and then can be retracted proximally toward the catheter hub and peeled off the catheter shaft **1910** if necessary.

Decision Support Systems

Intelligent systems are becoming widely accepted and are finding their way into acceptance in medical diagnostics and in the performance and predictive analysis of medical device clinical trials. Articles and presentations have been given related to this subject matter.

An approach based on Bayesian statistics is an approach for learning from evidence as it accumulates. In clinical trials, traditional statistical methods may use information from previous studies only at the design stage. Then, at the data analysis stage, the information from these studies is considered as a complement to, but not part of, the formal analysis. In contrast, the Bayesian approach uses Bayes' Theorem to formally combine prior information with current information on a quantity of interest. The Bayesian idea is to consider the prior information and the trial results as part of a continual data stream, in which inferences are being updated each time new data become available.

The Bayes theorem may be used to calculate the probability of coronary artery disease based upon clinical data and non-invasive test results. Pre-test probabilities of disease are assigned based on clinical data and the equation is used to calculate post-test probabilities after multiple sequential tests. When good prior information on clinical use of a device exists, the Bayesian approach enables this information to be incorporated into the statistical analysis of a given decisional matrix.

Good prior information is often available for medical devices because of their mechanism of action and evolutionary development. The mechanism of action of medical devices is typically physical. As a result, device effects are typically local, not systemic. Local effects can sometimes be predictable from prior information on the previous generations of a device when modifications to the device are minor. Good prior information can also be available from studies of the device overseas.

Bayesian methods are usually less controversial when the prior information is based on empirical evidence such as data from clinical trials. Bayesian methods can, however, be controversial when the prior information is based mainly on personal opinion.

Bayesian analyses are often computationally intense. Recent breakthroughs in computational algorithms and computing speed have, however, made it possible to carry out calculations for very complex and realistic Bayesian models. These advances have resulted in an increase in the popularity of Bayesian methods. A basic computational tool is a method called Markov Chain Monte Carlo ("MCMC") sampling, which is a method for simulating from the distributions of random quantities.

As the Bayesian predictive modeling scheme has become well known, it is useful in conjunction with the various control systems of the present invention, as described above, as predictive analysis profiling during a vascular occlusion procedure.

In connection with the present invention, the various preferred embodiments of the occlusion catheter systems and related components and devices described herein, and the occlusion or the occlusion/perfusion control over the vascular occlusion devices, is well suited to oversight and control using intelligent systems, such as those in which Bayesian probability analysis is applied. In each of the above-described embodiments, including without limitation, the vascular occlusion devices, the occlusion catheter systems, the control systems for controlling apposition of the occlusion member against the vessel wall or for excluding the hemorrhage site, the pre-conditioning systems or the occlusion/perfusion systems, both physical and/or physiological data is either acquired or is capable of being acquired. Acquisition of real-time physical and/or physiological data during an occlusion procedure or during a vascular repair involving a vascular occlusion includes, without limitation, blood pressure, heart rate, flow, chemistry, temperature, oxygenation, imaging or the like. In combination with prior data obtained from clinical practice guides, standard of care protocols, process flowcharts, and other data acquired during prior procedures, intelligent predictive analysis may be applied in software or firmware resident at the computer controllers, e.g., controllers **750**, **753**, **803**, to either automatically control the preferred systems described herein or to output intelligently processed information to the medical practitioner to aid in decision making during the occlusion procedure.

It will be appreciated by those skilled in the art that changes could be made to the embodiments described above

without departing from the broad inventive concept thereof. For example, nearly any of the individual components of the various embodiments may be incorporated with other preferred embodiments without departing from the spirit and scope of the preferred inventions. The plurality of proximal and distal side ports may be incorporated in nearly any of the preferred occlusion catheter systems, the atraumatic tips may be mixed and matched with the various embodiments of the occlusion catheter systems, nearly any of the preferred occlusion members, such as the first preferred occlusion balloon system **1200** with the projecting members **1204** may be incorporated with any of the preferred occlusion catheter systems and other similar arrangement of the disclosed features of the preferred systems may be employed without departing from the spirit and scope of the disclosed preferred inventions. It is understood, therefore, that the invention is not limited to the particular embodiments disclosed, but it is intended to cover modifications within the spirit and scope of the present invention, as defined by the appended claims.

We claim:

1. An occlusion catheter system comprising:

- a proximal hub;
- a flow valve configured to selectively fluidly communicate the proximal hub with an inflation device;
- a proximal catheter section in fluid communication with the proximal hub;
- a distal catheter section distally terminating with an atraumatic tip;
- an intervening occlusion balloon connecting the proximal catheter section with the distal catheter section, the occlusion balloon being compliant;
- at least one length marking on an exterior of the proximal catheter section to indicate an insertion depth of the occlusion catheter system;
- a lumen extending from the proximal hub through the proximal catheter section and into fluid communication with the occlusion balloon;
- a solid wire, secured at a proximal-most end thereof within the proximal hub, and extending within the proximal catheter section, the occlusion balloon and into the distal catheter section; and
- the proximal catheter section, the occlusion balloon and the distal catheter section having a greatest outer diameter of less than 6 Fr in an uninflated configuration.

2. The occlusion catheter system of claim 1, wherein the occlusion balloon is asymmetrical.

3. The occlusion catheter system of claim 1, wherein the occlusion balloon comprises a conically shaped portion facing a spherically shaped portion.

4. The occlusion catheter system of claim 1, wherein the occlusion balloon comprises a conically shaped portion facing another conically shaped portion.

5. The occlusion catheter system of claim 1, wherein the occlusion balloon comprises a first conically shaped portion, a second conically shaped portion and an intervening generally cylindrical portion.

6. The occlusion catheter system of claim 1, wherein the solid wire is constructed of a metal.

7. The occlusion catheter system of claim 1, wherein the solid wire is constructed of a stainless steel.

8. The occlusion catheter system of claim 1, further comprising a proximal radio opaque marker proximate a proximal end of the occlusion balloon and a distal radio opaque marker proximate a distal end of the occlusion balloon.

67

9. The occlusion catheter system of claim 1, wherein the occlusion balloon comprises at least two oppositely oriented frustoconical portions.

10. An inflation control system kit comprising:
the occlusion catheter system of claim 1; and
a syringe containing a fluid, the syringe being configured
to fluidly connect with an inlet of the proximal hub.

* * * * *

68