

**UNITED STATES PATENT AND TRADEMARK OFFICE
PATENT TRIAL AND APPEAL BOARD**

Camel Manufacturing Company, LLC

Petitioner,

v.

DLX Enterprises, LLC,

Patent Owner.

Case No. PGR2024-00033
U.S. Patent No. 11,732,496

EXHIBIT 1010

U.S. PATENT APPLICATION NO. 16/861,012



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	ISSUE DATE	PATENT NO.	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	03/22/2022	11280107	9693-012A-CIP	8204

4678 7590 03/02/2022
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

ISSUE NOTIFICATION

The projected patent number and issue date are specified above.

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b) (application filed on or after May 29, 2000)

The Patent Term Adjustment is 0 day(s). Any patent to issue from the above-identified application will include an indication of the adjustment on the front page.

If a Continued Prosecution Application (CPA) was filed in the above-identified application, the filing date that determines Patent Term Adjustment is the filing date of the most recent CPA.

Applicant will be able to obtain more detailed information by accessing the Patent Application Information Retrieval (PAIR) WEB site (<http://pair.uspto.gov>).

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Application Assistance Unit (AAU) of the Office of Data Management (ODM) at (571)-272-4200.

INVENTOR(s) (Please see PAIR WEB site <http://pair.uspto.gov> for additional inventors):

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

APPLICANT(s) (Please see PAIR WEB site <http://pair.uspto.gov> for additional applicants):

DLX Enterprises, LLC, Eugene, OR;

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The USA offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to encourage and facilitate business investment. To learn more about why the USA is the best country in the world to develop technology, manufacture products, and grow your business, visit SelectUSA.gov.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2:

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Inventor Information:

Inventor 1				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Jonathan		Urhausen	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 2				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Adam		Barr	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 3				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Donald		Bierman	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Residence Information (Select One)		☒ US Residency	☐ Non US Residency	☐ Active US Military Service	
City	Eugene	State/Province	OR	Country of Residence ⁱ	US
Mailing Address of Inventor:					
Address 1		245 Jackson Street			
Address 2					
City	Eugene	State/Province	OR		
Postal Code	97402	Country ⁱ	US		
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.					

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).			
☐ An Address is being provided for the correspondence information of this application.			
Customer Number	4678		
Email Address	docketing@maccordmason.com	<input type="button" value="Add Email"/>	<input type="button" value="Remove Email"/>

Application Information:

Title of the Invention	SHELTER AND HUB SYSTEM		
Attorney Docket Number	9693-012A-CON1	Small Entity Status Claimed	☒
Application Type			
Subject Matter			
Total Number of Drawing Sheets (if any)	30	Suggested Figure for Publication (if any)	

Filing By Reference:

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Publication Information:

☐	Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☒	Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)		
Customer Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					

Additional Representative Information blocks may be generated within this form by selecting the **Add** button.

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing benefit claim information in the Application Data Sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.
When referring to the current application, please leave the "Application Number" field blank.

Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
	Continuation of	16/431322	2019-06-04

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Prior Application Status		Patented	Remove		
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
16431322	Continuation of	15/639261	2017-06-30	10309093	2019-06-04

Prior Application Status		Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)	
15639261	Claims benefit of provisional	62/356793	2016-06-30	

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the **Add** button.

Foreign Priority Information:

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Application Number	Country ¹	Filing Date (YYYY-MM-DD)	Access Code ² (if applicable)

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013.

☐ NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant **must opt-out** of the authorization by checking the corresponding box A or B or both in subsection 2 below.

NOTE: This section of the Application Data Sheet is **ONLY** reviewed and processed with the **INITIAL** filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

A. Priority Document Exchange (PDX) - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h)(1).

B. Search Results from U.S. Application to EPO - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

☐ A. Applicant **DOES NOT** authorize the USPTO to permit a participating foreign IP office access to the instant application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.

☐ B. Applicant **DOES NOT** authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

NOTE: Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Applicant 1

If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.

Clear

- ☒ Assignee ☐ Legal Representative under 35 U.S.C. 117 ☐ Joint Inventor
- ☐ Person to whom the inventor is obligated to assign. ☐ Person who shows sufficient proprietary interest

If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:

Name of the Deceased or Legally Incapacitated Inventor:

If the Applicant is an Organization check here. ☒

Organization Name DLX Enterprises, LLC

Mailing Address Information For Applicant:

Address 1 ~~245 Jackson Street~~ 1075 Arrowsmith Rd.

Address 2

City Eugene State/Province OR

Country¹ US Postal Code 97402

Phone Number Fax Number

Email Address

Additional Applicant Data may be generated within this form by selecting the Add button.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Assignee 1						
Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.						
If the Assignee or Non-Applicant Assignee is an Organization check here. ☒						
Organization Name	DLX Enterprises, LLC					
Mailing Address Information For Assignee including Non-Applicant Assignee:						
Address 1	245 Jackson Street 1075 Arrowsmith Rd.					
Address 2						
City	Eugene	State/Province	OR			
Country i	US	Postal Code	97402			
Phone Number		Fax Number				
Email Address						
Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.						

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Signature:

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). **However, if this Application Data Sheet is submitted with the INITIAL filing of the application and either box A or B is not checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).**

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Kelly B. Robinson/			Date (YYYY-MM-DD)	<u>2022-02-16</u>
First Name	Kelly B.	Last Name	Robinson	Registration Number	72960
Additional Signature may be generated within this form by selecting the Add button.					

Electronic Acknowledgement Receipt

EFS ID:	45008685
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CIP
Receipt Date:	16-FEB-2022
Filing Date:	28-APR-2020
Time Stamp:	11:52:08
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Request for Corrected Filing Receipt	9693-012A-CIP_Updated_ADS.pdf	1145904 5a6ebcbef16b48c18b20df5f044c4ca1c64896a3	no	8

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:	
Total Files Size (in bytes):	1145904
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>	

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via EFS-Web.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

4678 7590 11/15/2021
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via EFS-Web or by facsimile to (571) 273-2885, on the date below.

(Typed or printed name)
(Signature)
(Date)

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CJP	8204

TITLE OF INVENTION: SHELTER AND HUB SYSTEM

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	\$600	\$0.00	\$0.00	\$600	02/15/2022

EXAMINER	ART UNIT	CLASS-SUBCLASS
CANFIELD, ROBERT	3636	135-145000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

☐ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.

☐ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-09 or more recent) attached. Use of a Customer Number is required.

2. For printing on the patent front page, list

(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,

(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

1 MacCord Mason PLLC

2

3

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE

(B) RESIDENCE: (CITY and STATE OR COUNTRY)

DLX Enterprises, LLC

Eugene, Oregon

Please check the appropriate assignee category or categories (will not be printed on the patent): ☐ Individual ☒ Corporation or other private group entity ☐ Government

4a. Fees submitted: ☐ Issue Fee ☐ Publication Fee (if required) ☐ Advance Order - # of Copies _____

4b. Method of Payment: (Please first reapply any previously paid fee shown above)

☒ Electronic Payment via EFS-Web ☐ Enclosed check ☐ Non-electronic payment by credit card (Attach form PTO-2038)

☒ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. 50-1923

5. Change in Entity Status (from status indicated above)

☐ Applicant certifying micro entity status. See 37 CFR 1.29

☐ Applicant asserting small entity status. See 37 CFR 1.27

☐ Applicant changing to regular undiscounted fee status.

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.

NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.

NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature /Kelly B. Robinson/

Date February 7, 2022

Typed or printed name Kelly B. Robinson

Registration No. 72,960

Electronic Patent Application Fee Transmittal				
Application Number:		16861012		
Filing Date:		28-Apr-2020		
Title of Invention:		SHELTER AND HUB SYSTEM		
First Named Inventor/Applicant Name:		Jonathan Urhausen		
Filer:		Kelly B. Robinson/Nichol Neal		
Attorney Docket Number:		9693-012A-CIP		
Filed as Small Entity				
Filing Fees for Utility under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
UTILITY APPL ISSUE FEE	2501	1	600	600

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Extension-of-Time:				
Miscellaneous:				
Total in USD (\$)				600

Electronic Acknowledgement Receipt

EFS ID:	44927416
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CIP
Receipt Date:	07-FEB-2022
Filing Date:	28-APR-2020
Time Stamp:	09:19:33
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	CARD
Payment was successfully received in RAM	\$600
RAM confirmation Number	E202227020463164
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Issue Fee Payment (PTO-85B)	9693-012A- CIP_Issue_fee_transmittal.pdf	1834755	no	1
			a048efed9173729ef208b90dbcb6c3182757f3bd		
Warnings:					
Information:					
2	Fee Worksheet (SB06)	fee-info.pdf	37928	no	2
			dade7ac9bda86bd6554081d37c4d19615639240		
Warnings:					
Information:					
Total Files Size (in bytes):			1872683		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					



United States Patent and Trademark Office

Office of the Chief Financial Officer

Document Code:WFEE

User :72233

Sale Accounting Date:01/27/2022

Sale Item Reference Number
16861012

Effective Date
11/04/2021

Document Number	Fee Code	Fee Code Description	Amount Paid	Payment Method
I20221QC20090728	2251	EXTENSION FOR RESPONSE WITHIN 1ST MONTH	\$110.00	Deposit Account



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204
4678	7590	12/06/2021		
MACCORD MASON PLLC 2733 Horse Pen Creek Road, Suite 101 GREENSBORO, NC 27410			EXAMINER CANFIELD, ROBERT	
			ART UNIT 3636	PAPER NUMBER
			MAIL DATE 12/06/2021	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

Application No. : 16861012
Applicant : Urhausen
Filing Date : 04/28/2020
Date Mailed : 12/06/2021

NOTICE TO FILE CORRECTED APPLICATION PAPERS

Notice of Allowance Mailed

This application has been accorded an Allowance Date and is being prepared for issuance. The application, however, is incomplete for the reasons below.

Applicant is given two (2) months from the mail date of this Notice within which to respond. This time period for reply is extendable under 37 CFR 1.136(a) for only TWO additional MONTHS.

The informalities requiring correction are indicated in the attachment(s). If the informality pertains to the abstract, specification (including claims) or drawings, the informality must be corrected with an amendment in compliance with 37 CFR 1.121 (or, if the application is a reissue application, 37 CFR 1.173). Such an amendment may be filed after payment of the issue fee if limited to correction of informalities noted herein. See Waiver of 37 CFR 1.312 for Documents Required by the Office of Patent Publication, 1280 Off. Gaz. Patent Office 918 (March 23, 2004). In addition, if the informality is not corrected until after payment of the issue fee, for purposes of 35 U.S.C. 154(b)(1)(iv), “all outstanding requirements” will be considered to have been satisfied when the informality has been corrected. A failure to respond within the above-identified time period will result in the application being ABANDONED.

See attachment(s).

*A copy of this notice **MUST** be returned with the reply. Please address response to
“Mail Stop Issue Fee, Commissioner for Patents,
P.O. Box 1450, Alexandria, VA 22313-1450”.*

/Kam Sin/
Publication Branch
Office of Data Management
(571) 272-4200

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

IDENTIFICATION OF DRAWING DEFICIENCIES

- ☐ There is a hole or the image thereof within the illustration. FIG(s)
- ☐ The illustration is penetrated or traversed by a solid or broken line that is not intended to be part of the drawing, such as a dark line caused by a flaw in the copying process. FIG(s)
- ☐ An ink stamp or the image thereof obscures part of the illustration. FIG(s)
- ☐ The drawing is marred by black smudges, obliterations, or fax/copier marks (for example, speckles or dots in a substantial portion of the drawing). FIG(s)
- ☐ Figure numbers are duplicated or missing. FIG(s)
- ☐ Drawing sheet or figure is missing. FIG(s)
- ☐ Numbers, letters, or reference characters in the drawing have been crossed out or are illegibly handwritten. FIG(s)
- ☐ The character of the lines, numbers, and letters is poor. FIG(s)
- ☐ The drawing's background shows that the original drawing was made on graph paper or other paper with a pattern or decoration. FIG(s)
- ☐ The FIG. number label is placed in a location that causes the drawing to be read upside down. FIG(s)
- ☒ Data, a reference number, or part of the drawing is truncated or missing, or a lead line has no reference number. FIG(s) 4, 7
- ☐ The drawing and/or the FIG. label contain(s) foreign language. FIG(s)
- ☐ This utility application contains a photograph of a view that is capable of being illustrated as a line drawing. FIG(s)
- ☐ A petition under 37 CFR 1.84(a)(2) to accept color drawings has been granted, but the brief description of the drawings in the specification does not contain (or has not been amended to contain) the paragraph required by 37 CFR 1.84(a)(2)(iii).
- ☐ This reissue application contains added and/or amended drawings that are not labeled as "New" or "Amended" or "Canceled" as required by 37 CFR 1.173(b)(3). FIG(s)
- ☐ This Design reissue application contains a drawing that is labeled as "Canceled" but is not surrounded by brackets, or a drawing that is surrounded by brackets but is not labeled as "Canceled." See 37 CFR 1.173(b)(3). FIG(s)
- ☐ OTHER:
- ☐ COMMENTS:

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC
Serial No.: 16/861,012
Filed: April 28, 2020
Confirmation No.: 8204

Examiner: R. Canfield
Art Unit: 3636

For: SHELTER AND HUB SYSTEM

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

Response to Notice to File Corrected Papers

In response to the Notice mailed December 6, 2021, requiring correction of informality in Figures 4 and 7, please find filed herewith annotated and replacement drawings providing the call out number identified in each of Figures 4 and 7.

The Commissioner is authorized to charge Deposit Account 50-1923 if any Extension of Time, or any additional fees for the accompanying response are required, and Applicant requests that this be considered a Petition therefor.

Respectfully submitted,

/Kelly B. Robinson/

Kelly B. Robinson
Registration No. 72,960
MacCord Mason PLLC
2733 Horse Pen Creek Road, Suite 101
Greensboro, North Carolina 27410
(336) 273-4422

Date: December 9, 2021
File No.: 9693-012A-CIP





FIG. 4






FIG. 4
Call out number 12
inadvertently missing from
drawing now added




FIG. 7

Electronic Acknowledgement Receipt

EFS ID:	44483282
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CIP
Receipt Date:	10-DEC-2021
Filing Date:	28-APR-2020
Time Stamp:	10:05:15
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Miscellaneous Incoming Letter	Notice_to_File_Corrected_Application_Papers.pdf	114051 e42ef5c49cfb4acc0e997795d8db314899b4e71d	no	3

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:					
2	Transmittal Letter accompanying New/ Add'l Drawings	9693-012A-CIP_Response.pdf	75095	no	1
			dea60ddb580cd8c375c83da4859a6404a67d5115		
Warnings:					
Information:					
3	Drawings-only black and white line drawings	Replacement_Drawings.pdf	1327692	no	2
			b3de4d3c7f7d077e93fd2c0c3f68c7f532a1cd5115		
Warnings:					
Information:					
4	Drawings-only black and white line drawings	Annotated_Drawings.pdf	1444848	no	2
			8d89c927ee7ea1d731570cb3f7b8d9dcb7a1c15a3		
Warnings:					
Information:					
Total Files Size (in bytes):			2961686		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204
4678	7590	12/06/2021		
MACCORD MASON PLLC 2733 Horse Pen Creek Road, Suite 101 GREENSBORO, NC 27410			EXAMINER CANFIELD, ROBERT	
			ART UNIT 3636	PAPER NUMBER
			MAIL DATE 12/06/2021	DELIVERY MODE PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.



UNITED STATES PATENT AND TRADEMARK OFFICE

Commissioner for Patents
United States Patent and Trademark Office
P.O. Box 1450
Alexandria, VA 22313-1450
www.uspto.gov

Application No. : 16861012
Applicant : Urhausen
Filing Date : 04/28/2020
Date Mailed : 12/06/2021

NOTICE TO FILE CORRECTED APPLICATION PAPERS

Notice of Allowance Mailed

This application has been accorded an Allowance Date and is being prepared for issuance. The application, however, is incomplete for the reasons below.

Applicant is given two (2) months from the mail date of this Notice within which to respond. This time period for reply is extendable under 37 CFR 1.136(a) for only TWO additional MONTHS.

The informalities requiring correction are indicated in the attachment(s). If the informality pertains to the abstract, specification (including claims) or drawings, the informality must be corrected with an amendment in compliance with 37 CFR 1.121 (or, if the application is a reissue application, 37 CFR 1.173). Such an amendment may be filed after payment of the issue fee if limited to correction of informalities noted herein. See Waiver of 37 CFR 1.312 for Documents Required by the Office of Patent Publication, 1280 Off. Gaz. Patent Office 918 (March 23, 2004). In addition, if the informality is not corrected until after payment of the issue fee, for purposes of 35 U.S.C. 154(b)(1)(iv), “all outstanding requirements” will be considered to have been satisfied when the informality has been corrected. A failure to respond within the above-identified time period will result in the application being ABANDONED.

See attachment(s).

*A copy of this notice **MUST** be returned with the reply. Please address response to
“Mail Stop Issue Fee, Commissioner for Patents,
P.O. Box 1450, Alexandria, VA 22313-1450”.*

/Kam Sin/
Publication Branch
Office of Data Management
(571) 272-4200

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

IDENTIFICATION OF DRAWING DEFICIENCIES

- ☐ There is a hole or the image thereof within the illustration. FIG(s)
- ☐ The illustration is penetrated or traversed by a solid or broken line that is not intended to be part of the drawing, such as a dark line caused by a flaw in the copying process. FIG(s)
- ☐ An ink stamp or the image thereof obscures part of the illustration. FIG(s)
- ☐ The drawing is marred by black smudges, obliterations, or fax/copier marks (for example, speckles or dots in a substantial portion of the drawing). FIG(s)
- ☐ Figure numbers are duplicated or missing. FIG(s)
- ☐ Drawing sheet or figure is missing. FIG(s)
- ☐ Numbers, letters, or reference characters in the drawing have been crossed out or are illegibly handwritten. FIG(s)
- ☐ The character of the lines, numbers, and letters is poor. FIG(s)
- ☐ The drawing's background shows that the original drawing was made on graph paper or other paper with a pattern or decoration. FIG(s)
- ☐ The FIG. number label is placed in a location that causes the drawing to be read upside down. FIG(s)
- ☒ Data, a reference number, or part of the drawing is truncated or missing, or a lead line has no reference number. FIG(s) 4, 7
- ☐ The drawing and/or the FIG. label contain(s) foreign language. FIG(s)
- ☐ This utility application contains a photograph of a view that is capable of being illustrated as a line drawing. FIG(s)
- ☐ A petition under 37 CFR 1.84(a)(2) to accept color drawings has been granted, but the brief description of the drawings in the specification does not contain (or has not been amended to contain) the paragraph required by 37 CFR 1.84(a)(2)(iii).
- ☐ This reissue application contains added and/or amended drawings that are not labeled as "New" or "Amended" or "Canceled" as required by 37 CFR 1.173(b)(3). FIG(s)
- ☐ This Design reissue application contains a drawing that is labeled as "Canceled" but is not surrounded by brackets, or a drawing that is surrounded by brackets but is not labeled as "Canceled." See 37 CFR 1.173(b)(3). FIG(s)
- ☐ OTHER:
- ☐ COMMENTS:



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

NOTICE OF ALLOWANCE AND FEE(S) DUE

4678 7590 11/15/2021
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

EXAMINER

CANFIELD, ROBERT

ART UNIT

PAPER NUMBER

3636

DATE MAILED: 11/15/2021

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204

TITLE OF INVENTION: SHELTER AND HUB SYSTEM

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	\$600	\$0.00	\$0.00	\$600	02/15/2022

THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED. THIS NOTICE OF ALLOWANCE IS NOT A GRANT OF PATENT RIGHTS. THIS APPLICATION IS SUBJECT TO WITHDRAWAL FROM ISSUE AT THE INITIATIVE OF THE OFFICE OR UPON PETITION BY THE APPLICANT. SEE 37 CFR 1.313 AND MPEP 1308.

THE ISSUE FEE AND PUBLICATION FEE (IF REQUIRED) MUST BE PAID WITHIN THREE MONTHS FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. THIS STATUTORY PERIOD CANNOT BE EXTENDED. SEE 35 U.S.C. 151. THE ISSUE FEE DUE INDICATED ABOVE DOES NOT REFLECT A CREDIT FOR ANY PREVIOUSLY PAID ISSUE FEE IN THIS APPLICATION. IF AN ISSUE FEE HAS PREVIOUSLY BEEN PAID IN THIS APPLICATION (AS SHOWN ABOVE), THE RETURN OF PART B OF THIS FORM WILL BE CONSIDERED A REQUEST TO REAPPLY THE PREVIOUSLY PAID ISSUE FEE TOWARD THE ISSUE FEE NOW DUE.

HOW TO REPLY TO THIS NOTICE:

I. Review the ENTITY STATUS shown above. If the ENTITY STATUS is shown as SMALL or MICRO, verify whether entitlement to that entity status still applies.

If the ENTITY STATUS is the same as shown above, pay the TOTAL FEE(S) DUE shown above.

If the ENTITY STATUS is changed from that shown above, on PART B - FEE(S) TRANSMITTAL, complete section number 5 titled "Change in Entity Status (from status indicated above)".

For purposes of this notice, small entity fees are 1/2 the amount of undiscounted fees, and micro entity fees are 1/2 the amount of small entity fees.

II. PART B - FEE(S) TRANSMITTAL, or its equivalent, must be completed and returned to the United States Patent and Trademark Office (USPTO) with your ISSUE FEE and PUBLICATION FEE (if required). If you are charging the fee(s) to your deposit account, section "4b" of Part B - Fee(s) Transmittal should be completed and an extra copy of the form should be submitted. If an equivalent of Part B is filed, a request to reapply a previously paid issue fee must be clearly made, and delays in processing may occur due to the difficulty in recognizing the paper as an equivalent of Part B.

III. All communications regarding this application must give the application number. Please direct all communications prior to issuance to Mail Stop ISSUE FEE unless advised to the contrary.

IMPORTANT REMINDER: Maintenance fees are due in utility patents issuing on applications filed on or after Dec. 12, 1980. It is patentee's responsibility to ensure timely payment of maintenance fees when due. More information is available at www.uspto.gov/PatentMaintenanceFees.

PART B - FEE(S) TRANSMITTAL

Complete and send this form, together with applicable fee(s), by mail or fax, or via EFS-Web.

By mail, send to: Mail Stop ISSUE FEE
Commissioner for Patents
P.O. Box 1450
Alexandria, Virginia 22313-1450

By fax, send to: (571)-273-2885

INSTRUCTIONS: This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

Certificate of Mailing or Transmission

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via EFS-Web or by facsimile to (571) 273-2885, on the date below.

	(Typed or printed name)
	(Signature)
	(Date)

4678 7590 11/15/2021
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861.012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204

TITLE OF INVENTION: SHELTER AND HUB SYSTEM

APPLN. TYPE	ENTITY STATUS	ISSUE FEE DUE	PUBLICATION FEE DUE	PREV. PAID ISSUE FEE	TOTAL FEE(S) DUE	DATE DUE
nonprovisional	SMALL	\$600	\$0.00	\$0.00	\$600	02/15/2022

EXAMINER	ART UNIT	CLASS-SUBCLASS
CANFIELD, ROBERT	3636	135-145000

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

☐ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.

☐ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-09 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list

(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,

1 _____

(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

2 _____

3 _____

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE

(B) RESIDENCE: (CITY and STATE OR COUNTRY)

Please check the appropriate assignee category or categories (will not be printed on the patent) : ☐ Individual ☐ Corporation or other private group entity ☐ Government

4a. Fees submitted: ☐ Issue Fee ☐ Publication Fee (if required) ☐ Advance Order - # of Copies _____

4b. Method of Payment: (Please first reapply any previously paid fee shown above)

☐ Electronic Payment via EFS-Web ☐ Enclosed check ☐ Non-electronic payment by credit card (Attach form PTO-2038)

☐ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. _____

5. **Change in Entity Status** (from status indicated above)

☐ Applicant certifying micro entity status. See 37 CFR 1.29

☐ Applicant asserting small entity status. See 37 CFR 1.27

☐ Applicant changing to regular undiscounted fee status.

NOTE: Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.

NOTE: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.

NOTE: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

NOTE: This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature _____

Date _____

Typed or printed name _____

Registration No. _____



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204
4678	7590	11/15/2021	EXAMINER	
MACCORD MASON PLLC			CANFIELD, ROBERT	
2733 Horse Pen Creek Road, Suite 101			ART UNIT	
GREENSBORO, NC 27410			PAPER NUMBER	
			3636	
DATE MAILED: 11/15/2021				

Determination of Patent Term Adjustment under 35 U.S.C. 154 (b) (Applications filed on or after May 29, 2000)

The Office has discontinued providing a Patent Term Adjustment (PTA) calculation with the Notice of Allowance.

Section 1(h)(2) of the AIA Technical Corrections Act amended 35 U.S.C. 154(b)(3)(B)(i) to eliminate the requirement that the Office provide a patent term adjustment determination with the notice of allowance. See Revisions to Patent Term Adjustment, 78 Fed. Reg. 19416, 19417 (Apr. 1, 2013). Therefore, the Office is no longer providing an initial patent term adjustment determination with the notice of allowance. The Office will continue to provide a patent term adjustment determination with the Issue Notification Letter that is mailed to applicant approximately three weeks prior to the issue date of the patent, and will include the patent term adjustment on the patent. Any request for reconsideration of the patent term adjustment determination (or reinstatement of patent term adjustment) should follow the process outlined in 37 CFR 1.705.

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Customer Service Center of the Office of Patent Publication at 1-(888)-786-0101 or (571)-272-4200.

OMB Clearance and PRA Burden Statement for PTOL-85 Part B

The Paperwork Reduction Act (PRA) of 1995 requires Federal agencies to obtain Office of Management and Budget approval before requesting most types of information from the public. When OMB approves an agency request to collect information from the public, OMB (i) provides a valid OMB Control Number and expiration date for the agency to display on the instrument that will be used to collect the information and (ii) requires the agency to inform the public about the OMB Control Number's legal significance in accordance with 5 CFR 1320.5(b).

The information collected by PTOL-85 Part B is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450. Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a federal, state, or local law enforcement agency, if the USPTO becomes aware of a violation of a federal, state, or local law or regulation.

Notice of Allowability	Application No. 16/861,012	Applicant(s) Urhausen et al.	
	Examiner ROBERT CANFIELD	Art Unit 3636	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address--

All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. **THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS.** This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.

1. ☒ This communication is responsive to 11/04/21 interview.
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on _____.

2. ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on _____; the restriction requirement and election have been incorporated into this action.

3. ☒ The allowed claim(s) is/are 1-7,9-13 and 15-19. As a result of the allowed claim(s), you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to PPHfeedback@uspto.gov.

4. ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

a) ☐ All b) ☐ Some* c) ☐ None of the:

1. ☐ Certified copies of the priority documents have been received.

2. ☐ Certified copies of the priority documents have been received in Application No. _____.

3. ☐ Copies of the certified copies of the priority documents have been received in this national stage application from the International Bureau (PCT Rule 17.2(a)).

* Certified copies not received: _____.

Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file a reply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.
THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.

5. ☐ CORRECTED DRAWINGS (as "replacement sheets") must be submitted.
☐ including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date _____.

Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).

6. ☐ DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.

Attachment(s)

1. ☒ Notice of References Cited (PTO-892)	5. ☒ Examiner's Amendment/Comment
2. ☐ Information Disclosure Statements (PTO/SB/08), Paper No./Mail Date _____.	6. ☐ Examiner's Statement of Reasons for Allowance
3. ☐ Examiner's Comment Regarding Requirement for Deposit of Biological Material _____.	7. ☒ Other <u>PTO-2323</u> .
4. ☒ Interview Summary (PTO-413), Paper No./Mail Date. _____.	

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

Notice of Pre-AIA or AIA Status

1. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.
2. The amendment filed 10/26/21 after final rejection has been entered however further amendments are made below.
3. The drawings filed 5/29/0 are approved.
4. An extension of time under 37 CFR 1.136(a) is required in order to make an examiner's amendment that places this application in condition for allowance. During a conversation conducted on 11/04/21, Kelly Robinson requested an extension of time for ONE MONTH(S) and authorized the Director to charge Deposit Account No. 501923 the required fee of \$ 110.00 for this extension and authorized the following examiner's amendment. Should the changes and/or additions be unacceptable to applicant, an amendment may be filed as provided by 37 CFR 1.312. To ensure consideration of such an amendment, it MUST be submitted no later than the payment of the issue fee.
5. The application has been amended as follows:

Claim 1. (Currently Amended) A rapid-deployment shelter system, said shelter system comprising:

a shelter including a frame and a cover, wherein [[a]] the frame system is configured to alternate between a first extended angular opened position and a second retracted position;

the frame including ~~more than one set~~ sets of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;

the frame in the angular opened position including: frame poles that are joined in pairs serving as leg poles, frame poles that are joined in pairs serving as ceiling poles, the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;

wherein the joined leg poles and ceiling poles form an exterior frame opening configured to mate with an exterior frame opening of another shelter or a shelter attachment device; ~~the shelter including a door end along each side of said shelter.~~ and

wherein each side of the frame forms one said exterior frame opening.

Claim 15. (Currently Amended) A rapid-deployment shelter system, the shelter system comprising:

an articulating frame system, said articulating frame system including a plurality of interconnected frame poles forming a frame, said articulating frame system configured to alternate between a first extended angular opened position and a second retracted position;

the frame including sets ~~more than one set~~ of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;

the frame in the angular opened position including:
frame poles that are joined in pairs serving as leg poles,
frame poles that are joined in pairs serving as ceiling poles,
the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;

a cover configured to fit with the frame to form a shelter, wherein the shelter is a hub shelter ~~including a door end along each side of said shelter,~~ and wherein each side ~~the frame at the exterior~~ of the articulating frame system is configured to fit with a frame of a second shelter to form a shared interior space through an angular mated opening.

Claim 17

Line 2, insert "items" after "connect".

6. Claims 1-7, 9-13 and 15-19 are allowed.

7. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

8. Any inquiry concerning this communication or earlier communications from the examiner should be directed to ROBERT CANFIELD whose telephone number is (571)272-6840. The examiner can normally be reached M-F 10-6, some Saturdays.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Dunn can be reached on 571-272-6670. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of published or unpublished applications may be obtained from Patent Center. Unpublished application information in Patent Center is available to registered users. To file and manage patent submissions in Patent Center, visit: <https://patentcenter.uspto.gov>. Visit <https://www.uspto.gov/patents/apply/patent-center> for more information about Patent Center and <https://www.uspto.gov/patents/docx> for information about filing in DOCX format. For additional questions, contact the Electronic Business Center (EBC) at 866-217-9197

Application/Control Number: 16/861,012
Art Unit: 3636

Page 5

(toll-free). If you would like assistance from a USPTO Customer Service

Representative, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

ROBERT CANFIELD
Primary Examiner
Art Unit 3635

/Robert Canfield/
Primary Examiner, Art Unit 3636

<i>Examiner-Initiated Interview Summary</i>	Application No. 16/861,012	Applicant(s) Urhausen et al.		
	Examiner ROBERT CANFIELD	Art Unit 3636	AIA (First Inventor to File) Status Yes	Page 1 of 1

All Participants (applicant, applicants representative, PTO personnel)	Title	Type
ROBERT CANFIELD	Primary Examiner	Telephonic
Kelly Robinson	Attorney of Record	

Date of Interview: 04 November 2021

Issues Discussed:

Proposed Amendment(s)

Discussed the after final amendment filed 10/26/21 and agreed to the further changes noted on the attached Examiner's Amendment to place in condition for allowance.

/Robert Canfield/ Primary Examiner, Art Unit 3636	
<p>Applicant is reminded that a complete written statement as to the substance of the interview must be made of record in the application file. It is the applicants responsibility to provide the written statement, unless the interview was initiated by the Examiner and the Examiner has indicated that a written summary will be provided. See MPEP 713.04</p> <p>Please further see: MPEP 713.04 Title 37 Code of Federal Regulations (CFR) § 1.133 Interviews, paragraph (b) 37 CFR § 1.2 Business to be transacted in writing</p>	

Applicant recordation instructions: It is not necessary for applicant to provide a separate record of the substance of interview.

Examiner recordation instructions: Examiners must summarize the substance of any interview of record. A complete and proper recordation of the substance of an interview should include the items listed in MPEP 713.04 for complete and proper recordation including the identification of the general thrust of each argument or issue discussed, a general indication of any other pertinent matters discussed regarding patentability and the general results or outcome of the interview, to include an indication as to whether or not agreement was reached on the issues raised.

<i>Notice of References Cited</i>	Application/Control No. 16/861,012		Applicant(s)/Patent Under Reexamination Urhausen et al.	
	Examiner ROBERT CANFIELD		Art Unit 3636	Page 1 of 1

U.S. PATENT DOCUMENTS						
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20200190844-A1	06-2020	Ribner; Thad B.	E04H15/50	1/1
	B					
	C					
	D					
	E					
	F					
	G					
	H					
	I					
	J					
	K					
	L					
	M					

FOREIGN PATENT DOCUMENTS						
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS		
*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

AFCP 2.0 Decision

Application No.

16/861,012

Applicant(s)

Urhausen et al.

Examiner

ROBERT CANFIELD

Art Unit

3636

AIA (FITF) Status

Yes

This is in response to the After Final Consideration Pilot request filed 26 October 2021.

1. **Improper Request** – The AFCP 2.0 request is improper for the following reason(s) and the after final amendment submitted with the request will be treated under pre-pilot procedure.

- ☐ An AFCP 2.0 request form PTO/SB/434 (or equivalent document) was not submitted.
- ☐ A non-broadening amendment to at least one independent claim was not submitted.
- ☐ The request is not the first proper AFCP 2.0 request submitted in response to the most recent final rejection.
- ☐ Other: _____

2. **Proper Request**

- A. After final amendment submitted with the request will not be treated under AFCP 2.0.

The after final amendment cannot be reviewed and a search conducted within the guidelines of the pilot program.

- ☐ The after final amendment will be treated under pre-pilot procedure.

- B. Updated search and/or completed additional consideration.

The examiner performed an updated search and/or completed additional consideration of the after final amendment within the time authorized for the pilot program. The result(s) of the updated search and/or completed additional consideration are:

- ☐ 1. All of the rejections in the most recent final Office action are overcome and a Notice of Allowance is issued herewith.
- ☐ 2. The after final amendment would not overcome all of the rejections in the most recent final Office action. See attached interview summary for further details.
- ☐ 3. The after final amendment was reviewed, and it raises a new issue(s). See attached interview summary for further details.
- ☐ 4. The after final amendment raises new issues, but would overcome all of the rejections in the most recent final Office action. A decision on determining allowability could not be made within the guidelines of the pilot. See attached interview summary for further details, including any newly discovered prior art.
- ☒ 5. Other: See Continuation Sheet

Examiner Note: Please attach an interview summary when necessary as described above.

Continuation of Proper Request- B. 5. Other: The after final has been entered and further amendments have been made by Examiner's Amendment to place the application in condition for allowance.

Issue Classification 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

CPC						
Symbol					Type	Version
E04H	/	15	/	18	F	2013-01-01
E04B	/	1	/	1903	I	2013-01-01
E04H	/	15	/	50	I	2013-01-01
E04H	/	15	/	36	I	2013-01-01
E04H	/	15	/	44	I	2013-01-01
E04B	/	2001	/	1957	A	2013-01-01
E04B	/	2001	/	1927	A	2013-01-01

CPC Combination Sets				
Symbol	Type	Set	Ranking	Version
/				

NONE		Total Claims Allowed:	
(Assistant Examiner)	(Date)	17	
/Robert Canfield/ Primary Examiner, Art Unit 3636 (Primary Examiner)	04 November 2021 (Date)	O.G. Print Claim(s) 1	O.G. Print Figure 16B & 20B

<i>Issue Classification</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

INTERNATIONAL CLASSIFICATION					
CLAIMED					
E04H	/	15	/	18	
E04H	/	15	/	36	
E04H	/	15	/	46	
E04B	/	1	/	19	
NON-CLAIMED					
	/		/		

US ORIGINAL CLASSIFICATION	
CLASS	SUBCLASS

CROSS REFERENCES(S)						
CLASS	SUBCLASS (ONE SUBCLASS PER BLOCK)					

NONE		Total Claims Allowed:	
(Assistant Examiner)		17	
(Date)			
/Robert Canfield/		04 November 2021	
Primary Examiner, Art Unit 3636		O.G. Print Claim(s)	O.G. Print Figure
(Primary Examiner)		1	16B & 20B
(Date)			

Issue Classification 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

☒ Claims renumbered in the same order as presented by applicant ☐ CPA ☐ T.D. ☐ R.1.47															
CLAIMS															
Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original	Final	Original

NONE	Total Claims Allowed:	
(Assistant Examiner)	(Date)	17
/Robert Canfield/ Primary Examiner, Art Unit 3636 (Primary Examiner)	04 November 2021 (Date)	O.G. Print Claim(s) 1 O.G. Print Figure 16B & 20B

<i>Search Notes</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

CPC - Searched*		
Symbol	Date	Examiner
E04H15/18, 36, 44	01/01/2021	RC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner
135	97	01/01/2021	RC
52	79.9		
52	79.5, 79.7, 79.8, 79.12, 86	07/23/2021	RC
135	97, 124, 128, 131, 906, 908		

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
EAST classification/text/name/citation search - history attached	01/01/2021	RC
reviewed both parent file histories and checked for double patenting		
updated search - history attached and checked for double patenting issues again	07/23/2021	RC
update - attached	11/04/2021	RC

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

<i>Search Notes</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner
	see attached text queries	11/04/2021	

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

PE2E SEARCH - Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
L1	1	("10309093").PN.	(USPAT)	OR	ON	ON	2020/08/13 01:29 PM
L2	2	((("4945936") or ("9243423")).PN.	(USPAT)	OR	OFF	OFF	2020/08/13 01:43 PM
L3	19	("20060260666" "20130008478" "20140182643" "4706696" "4846204" "4945936" "5069572" "5634483" "5666986" "6553698" "6772780" "6802329" "7131236" "7556054" "8925565" "9243423" "9243424" "9631393" "D454609").PN. OR ("10309093").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:40 PM
L4	36	("1124420" "1666757" "2357056" "3000386" "3044477" "3794054" "3929146" "4033366" "4750509" "4865066").PN. OR ("4945936").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:42 PM
L5	58	("20030037812" "2665171" "2812769" "3208083" "3391409" "4473986" "4512097" "4522008" "4561618" "4579066" "4637180" "4675923" "4689932" "4707953" "4747239" "4761929" "4800597" "4800663" "4838003" "4934396" "4970841" "5216763" "5230196" "5274980" "5375275" "5444946" "5446930" "5469587" "5542730" "5651228" "5794640" "5934301" "5943837" "6035877" "6141934" "6192633" "6237860" "6244011" "6725873" "6779538" "RE33710").PN. OR ("7131236").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:45 PM
L6	50	("1484231" "1873178" "3899843" "3968808" "4268000").PN. OR ("4512097").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:46 PM

L7	20	("3381923" "4512097" "4658560" "4663899" "4809471").PN. OR ("4995212").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:50 PM
L8	97	("0014655" "0058283" "0379274" "1078069" "20030005953" "20070051399" "20070215192" "2113118" "2306706" "2336116" "2448895" "2530765" "2555220" "2731972" "2948287" "2953145" "2962034" "2984249" "3054413" "3177882" "3333373" "3738378" "3810482" "3929146" "4077417" "4148332" "4201237" "4280521" "4285354" "4627210" "4637748" "4750509" "4787182" "4819680" "4838003" "4941499" "4971090" "5195551" "5293890" "5328286" "5333634" "5361794" "5423341" "5617681" "5628338" "5634483" "5666986" "5732726" "5797695" "5884646" "5943837" "6021795" "6032430" "6167898" "6286530" "6296415" "6516823" "6591571" "6604844" "6666223" "6772780" "6776179" "6854476" "6868858" "6874519" "6892744" "7025075" "7040585" "7059094" "7311113" "7481235" "7546845" "D544941" "RE40544").PN. OR ("9243424").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 01:54 PM
L9	2467	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/09/01 02:45 PM
L12	23	("3507526").URPN.	(USPAT)	OR	ON	ON	2020/09/01 05:03 PM
L13	54	("1203267" "1291388" "1388657" "1403309" "4097168" "4172678" "4337937" "4449843" "4509381" "4657428" "4769897").PN. OR ("4904108").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 05:08 PM

L14	2467	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/09/01 05:16 PM
L15	1140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/09/01 05:16 PM
L16	1073	L15 not L14	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:18 PM
L17	1	("9605441").PN.	(USPAT)	OR	ON	ON	2020/09/01 05:37 PM
L18	112	("0014655" "0058283" "0379274" "1061547" "1129194" "1347107" "20010050098" "20030005953" "20070051399" "20070215192" "20120318316" "20130014794" "20140076372" "20140109945" "20140261601" "20140290710" "20150083177" "20150275541" "2113118" "2306706" "2448895" "2530765" "2555220" "2716993" "2731972" "2948287" "2962034" "2984249" "3054413" "3333373" "3738378" "3766932" "3810482" "3929146" "4077417" "4148332" "4201237" "4280521" "4285354" "4627210" "4637748" "4750509" "4787182" "4819680" "4838003" "4941499" "4944321" "4971090" "4998552" "5263507" "5293890" "5328286" "5333634" "5361794" "5423341" "5617681" "5628338" "5634483" "5666986" "5732726" "5771654" "5797695" "5884646" "5943837" "6021795" "6032430" "6167898" "6283136" "6286530" "6296415" "6463948" "6516823" "6591571" "6604844" "6666223" "6772780")	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 05:37 PM

		"6776179" "6854476" "6868858" "6874519" "6892744" "7025075" "7040585" "7059094" "7311113" "7316239" "7481235" "7546845" "8156952" "8186369" "8910648" "D544941" "D705884" "RE40544").PN. OR ("9605441").URPN.					
L19	3650	L12 L13 L14 L15 L16 L17 L18	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:45 PM
L20	2298	y10t403/342,347.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:45 PM
L21	2112	L20 not L19	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:46 PM
L22	3722	y10t403/4949,4966.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:51 PM
L23	5762	L19 L21	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:51 PM
L24	3694	L22 not L23	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:51 PM
L25	1458	L22 not L23	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:51 PM
L26	22	(US-20060260666-\$ or US-20070051399-\$ or US-20150167343-\$ or US-20150240513- \$).did. or (US-3507526- \$ or US-3968808-\$ or US-4512097-\$ or US- 4838003-\$ or US- 4945936-\$ or US- 4986016-\$ or US- 4995212-\$ or US- 6223482-\$ or US- 6553698-\$ or US- 7131236-\$ or US- 8360085-\$ or US- 8496019-\$ or US- 9243424-\$ or US-	(US-PGPUB; USPAT; DERWENT)	OR	ON	ON	2020/09/01 05:54 PM

L27	7223	9605441-\$).did. or (CN-201129060-\$ or CN-201169953-\$ or CN-201798187-\$ or US-20150167343-\$).did. L23 L25 L26	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:55 PM
L28	0	e04b1/1903,3441.cpc	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:56 PM
L29	4303	e04b1/1903,3441.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:56 PM
L30	3682	L29 not L27	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:56 PM
L31	1310	L29 not L27	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:56 PM
L32	3757	e04h15/34,44,48,50.cpc .	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:57 PM
L33	3148	L32 not L27	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:57 PM
L34	3148	L32 not L27	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:57 PM
L35	3148	L32 not L27	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/09/01 05:58 PM
L36	29	("3529508" "4571111" "4638133").PN. OR ("5017068").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/09/01 06:02 PM
L37	23	("3507526").URPN.	(USPAT)	OR	ON	ON	2020/09/01 06:12 PM
L38	19	("2003/0074845").URP N.	(USPAT)	OR	ON	ON	2020/09/01 06:26 PM
L39	484	(135/28).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/09/01 06:38 PM
L40	1	("8448656").PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/09/02 05:07 PM
L41	1	("8360085").PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/09/02 05:07 PM
L42	4	((("10309093") or ("9243423") or	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/09/02 05:20 PM

L43	2	("4945936") or ("5666986").PN. ("20150240513").PN.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/09/02 06:04 PM
L44	1	("4995212").PN.	(USPAT)	OR	OFF	OFF	2020/11/24 01:48 PM
L45	4	((("4995212") or ("20150167343") or ("9243423") or ("6223482")).PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/11/24 01:51 PM
L46	3	((("10309093") or ("9243424") or ("20150240513")).PN.	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/16 04:25 PM
L47	5	((("10309093") or ("9243424") or ("4995212") or ("6223482") or ("20150240513")).PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/12/16 04:26 PM
L48	6	((("10309093") or ("9243424") or ("9243423") or ("4995212") or ("6223482") or ("20150240513")).PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2020/12/16 04:27 PM
L49	2	((("9243423") or ("20150240513")).PN.	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/16 04:43 PM
L50	20	("2003/0074845").URP N.	(USPAT)	OR	ON	ON	2020/12/17 02:45 PM
L51	42	("20020066239" "20030074845" "20030164185" "3968808" "4026313" "4156433" "4193414" "4280521" "4290244" "4334660" "4437275" "4473986" "4512097" "4522008" "4561618" "4579066" "4637180" "4666102" "4689932" "4747239" "4761929" "4800663" "4838003" "4970841" "5230196" "5274980" "5444946" "5651228" "5943837" "6141934" "6196242" "6401735" "6941704" "RE33710").PN. OR ("7712261").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/12/17 02:48 PM
L52	40	("2659618" "3381923" "3507526" "3563580" "3710806" "3810482" "3830031" "3888056" "3914063" "4111574" "4241746" "4393887"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2020/12/17 02:49 PM

L53	2467	"4512097" "4809471").PN. OR ("4986016").URPN. ((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/12/17 02:50 PM
L54	1140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/12/17 02:51 PM
L55	2316	y10t403/342,347.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:51 PM
L56	3791	y10t403/4949,4966.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:51 PM
L57	0	e04b1/1903,3441.cpc	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:51 PM
L58	4350	e04b1/1903,3441.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:51 PM
L59	484	(135/28).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2020/12/17 02:51 PM
L60	9499	(E04B1/1903 or E04H15/44 or E04H15/50 or E04H15/36 or E04B2001/1957 or E04B2001/1927).cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:52 PM
L61	19318	L53 L54 L55 L56 L58 L59 L60	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:53 PM
L62	82	L61 and @pd>"20200902"	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:53 PM
L63	1	((("DLX") near3 ("ENTERPRISES") near3 ("LLC"))).AS,AANM.	(USPAT)	OR	ON	ON	2020/12/17 02:54 PM
L64	15	((("URHAUSEN") near3 ("Jonathan")) OR (("BARR") near3 ("Adam")) OR (("BIERMAN") near3 ("Donald")) OR (("TILLER") near3	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT)	OR	ON	ON	2020/12/17 02:54 PM

L65	26135	("Matt"))).INV. 135/\$.ccls.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:57 PM
L66	242614	52/\$.ccls.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:57 PM
L67	266593	L65 L66	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:57 PM
L68	1508	L67 and (hub node).clm.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:57 PM
L69	965	L68 and (frame framing framework)	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:58 PM
L70	1060	L68 and (frame framing framework pole)	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 02:58 PM
L71	701	L70 and (expand expanded deploy deployed fold folded folding collapse collapsed collapsible)	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 03:00 PM
L72	6	("4689932" "8082938"). PN.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2020/12/17 03:16 PM
L73	2	(US-7712261-\$ or US- 8082938-\$).did.	(USPAT)	OR	ON	ON	2020/12/17 03:17 PM
L79	2	(US-7712261-\$ or US- 8082938-\$).did.	(USPAT)	OR	ON	ON	2020/12/17 04:41 PM
L81	38	("10309093" "20060260 666" "20070051399" "2 0130008478" "2014018 2643" "20150167343" " 20150240513" "201801 55952" "3929146" "465 8560" "4706696" "4846 204" "4945936" "49952 12" "5017068" "506957 2" "5634483" "5666986" "5943837" "6223482" " 6553698" "6553699" "6 758354" "6772780" "68 02329" "7131236" "755 6054" "8360085" "8448 656" "8496019" "89255	(US-PGPUB; USPAT)	OR	ON	ON	2021/01/01 01:27 PM

L82	32	65" "9163425" "9243423" "9243424" "9605441" "9631393" "D454609" "D544941").PN. (US-20060260666-\$ or US-20070051399-\$ or US-20150167343-\$ or US-20150240513-\$ or US-20030074845-\$ or US-20080017233-\$).did. or (US-4945936-\$ or US-7131236-\$ or US-4512097-\$ or US-3968808-\$ or US-4995212-\$ or US-6223482-\$ or US-6553698-\$ or US-9243424-\$ or US-3507526-\$ or US-8496019-\$ or US-9605441-\$ or US-8360085-\$ or US-5017068-\$ or US-7533498-\$ or US-7712261-\$ or US-8448656-\$ or US-8082938-\$).did. or (US-3507526-\$ or US-3559353-\$).did. or (CN-201129060-\$ or CN-201169953-\$ or CN-201798187-\$ or US-20150167343-\$ or EP-222437-\$ or CN-104314360-\$ or US-20110017249-\$).did.	(US-PGPUB; USPAT; USOCR; DERWENT)	OR	ON	ON	2021/01/01 02:19 PM
L83	17	L82 not L81	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 02:19 PM
L84	423	(135/97).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/01/01 02:21 PM
L85	1	("4063566").PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2021/01/01 02:22 PM
L86	35	("2263867" "3397710" "3699986" "3874396").PN. OR ("4063566").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:22 PM
L87	10	("20060283103" "3374797" "3533202" "3773061" "4063566" "5159948" "6357462" "8001987").PN. OR ("10858856").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:22 PM
L88	84	("1420671" "2508679"	(US-PGPUB; USPAT;	OR	ON	ON	2021/01/01

		"3017893" "3222067" "3802133" "3925942" "3965915" "4011880" "4063566" "4886084").PN. OR ("5222513").URPN.	USOCR)				02:23 PM
L89	40	("0426112" "0634759" "1111040" "1214928" "1691411" "2032693" "2061510" "2372187").PN. OR ("3802133").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:24 PM
L90	110	("3397710" "3699986" "3802133" "3874396" "3955328" "4063566" "4078572" "4815490" "4886084" "4979532" "5078096" "5222513").PN. OR ("5394897").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:24 PM
L91	33	("2841832" "3468083" "3566554" "3618273" "3690077" "3769766" "3790657" "3813835").PN. OR ("3955328").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:24 PM
L92	45	("2255837" "2787321" "2808065" "2875824" "3834400" "3925828" "3968809" "4065166" "4102353" "4145855" "4285354" "4398376" "4561227" "4637748" "4979532" "5058340" "5170811" "5226264" "5394897" "5457922").PN. OR ("6145525").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:26 PM
L93	80	("1728356" "20020134415" "20040238021" "20050100400" "20050189009" "20060060235" "20080083443" "20080210283" "20090084420" "20100200038" "20110168221" "20130074894" "20130306121" "3368575" "3550601" "3699986" "3709237" "3810482" "3847170" "3941140" "3958289" "3965915" "4026312"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:28 PM

		"4063566" "4067346" "4077417" "4239247" "4285355" "4526391" "4632138" "4730569" "4819680" "4858635" "4917217" "4941499" "4979532" "5050526" "5159948" "5222513" "5251921" "5382111" "5394897" "5402596" "5575490" "5592961" "5593061" "5620396" "5628338" "5820189" "5906217" "6014833" "6098335" "6145525" "6192633" "6360761" "6565139" "6701948" "6782905" "6854476" "7040335" "7185666" "7614415" "7743781" "7958904" "8915258" "9085914" "9103137" "9163425" "9238924" "9470010" "D313061" "D339842").PN. OR ("9752345").URPN.					
L94	36	("2910994" "3261659" "3345996" "3501213" "3766844" "4304224" "4348777" "4442162" "4675923" "4707953" "4800597" "4858256" "5090972" "5326211" "5331991" "5394897" "5537784" "5551102" "5562539" "6021794").PN. OR ("6390110").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:30 PM
L95	27	("20070039639" "3421188" "3503101" "4369356" "4649947" "4838294" "4862563" "5008987" "5076288" "5222513" "5289619" "5394897" "5535928" "5819474" "5894642" "5970541" "6041454" "6049953" "6568981" "7273061" "7350244" "9103137" "9303426" "9470010").PN. OR ("9714523").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:32 PM
L96	67	("1666757" "1884449" "20020104561" "20040238021" "20050189009" "20050205124"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:34 PM

		"20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "3699986" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "6273114" "6357462" "6666223" "7588045" "8001987" "8132584" "8316508" "8763621" "8776815" "9470010" "D692083" "D779611").PN. OR ("9869110").URPN.					
L97	37	("4078572" "4979532" "5222513" "6273114" "6554013" "D351011" "D369638" "D382621" "D382622").PN. OR ("D652885").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/01/01 02:36 PM
L98	2282	e04h15/18.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 02:44 PM
L99	2167	L98 not L84	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 02:44 PM
L100	2590	L99 L84	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 03:05 PM
L101	1	((("DLX") near3 ("ENTERPRISES") near3 ("LLC"))).AS,AANM.	(USPAT)	OR	ON	ON	2021/01/01 03:05 PM
L102	15	((("URHAUSEN") near3 ("Jonathan")) OR (("BARR") near3 ("Adam")) OR (("BIERMAN") near3 ("Donald"))).INV.	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT)	OR	ON	ON	2021/01/01 03:06 PM

L103	2475	e04h15/36,44.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 03:06 PM
L104	2160	L103 not L100	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 03:06 PM
L105	4	("2007/0125410").URP N.	(USPAT)	OR	ON	ON	2021/01/01 03:12 PM
L106	4327	L99 L104	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 03:16 PM
L107	533	(52/79.9).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/01/01 03:16 PM
L108	532	L107 not L106	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/01 03:16 PM
L109	8	("2010/0170162").URP N.	(USPAT)	OR	ON	ON	2021/01/01 03:18 PM
L110	40	(US-20080017233-\$ or US-20060283103-\$ or US-20050189009-\$ or US-20070039639-\$ or US-20080264462-\$ or US-20120090455-\$ or US-20070125410-\$ or US-20100170162- \$).did. or (US-7533498- \$ or US-4063566-\$ or US-10858856-\$ or US- 5159948-\$ or US- 5222513-\$ or US- 3802133-\$ or US- 5394897-\$ or US- 3955328-\$ or US- 4886084-\$ or US- 6145525-\$ or US- 9752345-\$ or US- 6390110-\$ or US- 8381454-\$ or US- 9103137-\$ or US- 9714523-\$ or US- 4649947-\$ or US- 9869110-\$ or US- D652885-\$ or US- 4064663-\$ or US- 2691291-\$).did. or (US- 3559353-\$).did. or (CA- 2837116-\$ or DE- 29510827-\$ or DE- 29517290-\$ or DE-	(US-PGPUB; USPAT; USOCR; FPRS; DERWENT)	OR	ON	ON	2021/01/01 03:21 PM

L112	1301	29716289-\$ or FR-2207225-\$ or FR-2705718-\$).did. or (CA-2890530-\$ or FR-2997984-\$).did. (shelter tent) with hub	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/02 01:21 PM
L113	79	L112 same door	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/01/02 01:22 PM
L114	1	("9470010").PN.	(US-PGPUB; USPAT)	OR	OFF	OFF	2021/01/02 02:20 PM
L115	32	(US-20080017233-\$ or US-20060283103-\$ or US-20050189009-\$ or US-20070039639-\$ or US-20080264462-\$ or US-20120090455-\$ or US-20070125410-\$ or US-20100170162-\$).did. or (US-7533498-\$ or US-10858856-\$ or US-5159948-\$ or US-5394897-\$ or US-3955328-\$ or US-4886084-\$ or US-6145525-\$ or US-9752345-\$ or US-8381454-\$ or US-9103137-\$ or US-9714523-\$ or US-4649947-\$ or US-9869110-\$ or US-D652885-\$ or US-9470010-\$).did. or (US-3559353-\$).did. or (CA-2837116-\$ or DE-29510827-\$ or DE-29517290-\$ or DE-29716289-\$ or FR-2705718-\$).did. or (FR-2997984-\$).did.	(US-PGPUB; USPAT; USOCR; FPRS; DERWENT)	OR	ON	ON	2021/01/02 02:30 PM
L116	1	("9988823").PN.	(USPAT)	OR	OFF	OFF	2021/01/02 04:53 PM
L117	1	("3559353").PN.	(USPAT)	OR	OFF	OFF	2021/04/15 12:08 PM
L118	1	("9714523").PN.	(USPAT)	OR	OFF	OFF	2021/04/15 12:13 PM
L119	1	("9752345").PN.	(USPAT)	OR	OFF	OFF	2021/04/15 12:15 PM
L120	3	((("3559353") or ("9714523") or	(USPAT)	OR	OFF	OFF	2021/07/23 01:01 PM

L121	2	("9752345").PN. (("10941559") or ("10309093")).PN.	(USPAT)	OR	OFF	OFF	2021/07/23 01:19 PM
L122	2469	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/07/23 02:15 PM
L123	1140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/07/23 02:15 PM
L124	2317	y10t403/342,347.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:15 PM
L125	3798	y10t403/4949,4966.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:15 PM
L126	4436	e04b1/1903,3441.cpc.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:15 PM
L127	3956	e04h15/34,44,48,50.cpc .	(US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:15 PM
L128	485	(135/28).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/07/23 02:15 PM
L129	423	(135/97).CCLS.	(US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT)	OR	OFF	OFF	2021/07/23 02:16 PM
L130	17373	L120 L121 L122 L123 L124 L125 L126 L127 L128 L129	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:16 PM
L131	255	L130 and @pd>"20210101"	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:16 PM
L132	29	("20050194032" "20050204680" "20050204681" "20050262779" "20060101631" "20060157100" "20080016817" "20080017232" "20080017233" "20080017234" "20120298162" "20170175414" "20170247906" "4689932" "5230196" "5274980" "5444946"	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/07/23 02:21 PM

		"5651228" "6141934" "7357238" "7455164" "7481235" "7533498" "7556054" "7712261" "7832170" "8082938" "9631393" "RE33710").PN. OR ("10995516").URPN.					
L133	2618	52/79.5,79.7,9.8,79.12, 86.ccls.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:24 PM
L134	1928	135/97,124,128,131,90 6,908.ccls.	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:45 PM
L135	1800	L134 not L133	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 02:45 PM
L136	1	("10060151").PN.	(USPAT)	OR	OFF	OFF	2021/07/23 03:32 PM
L137	55	("1666757" "1884449" "20020104561" "20040238021" "20050189009" "20050205124" "20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "3699986" "3756649" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "5641192" "6273114" "6357462" "6666223" "7040333" "7588045" "8001987" "8132584" "8316508" "8763621" "8776815" "9470010" "D470560" "D652885" "D692083" "D779611").PN. OR	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/07/23 03:32 PM

L138	1	("10060151").URPN. ("10364588").PN.	(USPAT)	OR	OFF	OFF	2021/07/23 03:34 PM
L139	65	("1666757" "1884449" "1927387" "20020104561" "20040238021" "20050189009" "20050205124" "20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "2935074" "3316508" "3699986" "3756649" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "5641192" "5669655" "6273114" "6357462" "6666223" "7040333" "7588045" "8001987" "8132584" "8763621" "8776815" "9470010" "D224850" "D369638" "D470560" "D624623" "D652885" "D692083" "D779611").PN. OR ("10364588").URPN.	(US-PGPUB; USPAT; USOCR)	OR	ON	ON	2021/07/23 03:34 PM
L140	11	L139 not L137	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/07/23 03:34 PM
L141	55	((FR-2207225-A1 OR CA-2837116-A1 OR DE-29510827-U1 OR DE-29517290-U1 OR DE-29716289-U1 OR FR-2705718-A1).did. AND FPRS.dbnm.) OR ((US-9714523-B2 OR US-4649947-A OR US- 9869110-B2 OR US- D652885-S OR US-	(USPAT; US-PGPUB; FPRS; USOCR; IBM_TDB; EPO; JPO; DERWENT; FIT (AU, AP, AT, BE, BG, BR, BY, CA, CH, CN, CS, CU, CZ, DD, DE, DK, EA, EE, EP, ES, FI, FR, GB, HR, HU, ID, IE, IL, IS, IT, JP, KR, LT, LU, LV, MA, OA, RU, SU,	OR	ON	ON	2021/11/02 04:43 PM

		DE-29716289-U1 OR FR-2705718-A1).did. AND FPRS.dbnm.) OR ((US-9714523-B2 OR US-4649947-A OR US- 9869110-B2 OR US- D652885-S OR US- 9103137-B2 OR US- 4064663-A OR US- 2691291-A OR US- 3802133-A OR US- 7533498-B2 OR US- 4063566-A OR US- 10858856-B1 OR US- 5159948-A OR US- 5222513-A OR US- 5394897-A OR US- 3955328-A OR US- 4886084-A OR US- 6145525-A OR US- 9752345-B1 OR US- 6390110-B1 OR US- 8381454-B1 OR US- 9470010-B2 OR US- 10364588-B2 OR US- 10060151-B2 OR US- 4953329-A OR US- 4373305-A OR US- 8082938-B2 OR US- 6141934-A OR US- 4689932-A OR US- 10995516-B2).did. AND USPT.dbnm.) OR ((US- 20070039639-A1 OR US-20080264462-A1 OR US-20120090455- A1 OR US- 20070125410-A1 OR US-20100170162-A1 OR US-20060283103- A1 OR US- 20080017233-A1 OR US-20050189009-A1 OR US-20070084493- A1 OR US- 20170247906-A1 OR US-20080017232-A1 OR US-20050204681- A1 OR US- 20050204680-A1).did. AND PGPB.dbnm.) OR ((FR-2997984-A1 OR CA-2890530-A1 OR US-20200190844-A1 OR US-20180100326- A1 OR US- 20040173252-A1 OR AT-8701724-A).did.	GB, JP, KR, OA, RU, SU, WO); FPRS; EPO; JPO; DERWENT; IBM_TDB)				
--	--	---	---	--	--	--	--

L143	156	AND DWPI.dbnm.) OR ((US-3559353-A).did. AND USOC.dbnm.) L130 AND @pd>"20210723"	(US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB)	OR	ON	ON	2021/11/03 02:25 PM
L144	2	((US-20200190844-A1 OR US-20080017232- A1).did. AND PGPB.dbnm.)	(US-PGPUB)	OR	ON	ON	2021/11/03 02:39 PM

PE2E SEARCH - Search History (Interference)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	British Equivalents	Time Stamp
N74	106200	(hub node) with (frame framing framework pole)	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 03:05 PM
N75	8164	(hub node) with (frame framing framework pole) with (shelter structure canopy tent arch)	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 03:05 PM
N76	673	N75 same (expand expanded deploy deployed fold folded folding collapse collapsed collapsible)	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 03:06 PM
N77	11	N75 with (attach attached attachment attaching) with projection	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 03:07 PM
N78	4	(US-20080017232-\$ or US-20200190844-\$).did. or (US-4986016-\$ or US-RE33710-\$).did.	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 03:17 PM
N80	4	(US-20080017232-\$ or US-20200190844-\$).did. or (US-4986016-\$ or US-RE33710-\$).did.	(US-PGPUB; USPAT)	OR	ON	ON	2020/12/17 04:41 PM
N111	5	(US-20080017232-\$ or US-20200190844-\$).did. or (US-4986016-\$ or US-4838003-\$ or US-RE33710-\$).did.	(US-PGPUB; USPAT)	OR	ON	ON	2021/01/01 02:19 PM
N112	529	(shelter tent) WITH hub	(US-PGPUB; USPAT)	OR	ON	ON	2021/11/03 02:28 PM
N113	190	N112 WITH frame	(US-PGPUB; USPAT)	OR	ON	ON	2021/11/03 02:29 PM

OK TO ENTER: /RC/

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC

Serial No.: 16/861,012

Filed: April 28, 2020

Confirmation No.: 8204

Examiner: R. Canfield

Art Unit: 3636

For: SHELTER AND HUB SYSTEM

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

AMENDMENT UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM

In response to the Office Action mailed July 26, 2021, please consider the following amendments and arguments supporting allowance of the claimed subject matter.

The Commissioner is authorized to charge Deposit Account 501923 if any Extension of Time, or any additional fees for the accompanying response are required, and Applicant requests that this be considered a Petition therefor.

Amendment to the Claims begin on Page 2.

Remarks begin on Page 6.

Bibliographic Data

Application No: 16/861,012

Foreign Priority claimed: ☐ Yes ☒ No

35 USC 119 (a-d) conditions met: ☐ Yes ☐ No ☐ Met After Allowance

Verified and Acknowledged:

Examiner's Signature

Initials

Title:

FILING or 371(c) DATE	CLASS	GROUP ART UNIT	ATTORNEY DOCKET NO.
04/28/2020	135	3636	9693-012A-CIP
RULE			

APPLICANTS

DLX Enterprises, LLC, Eugene, OR, UNITED STATES

INVENTORS

Jonathan Urhausen, Eugene, OR, UNITED STATES

Adam Barr, Eugene, OR, UNITED STATES

Donald Bierman, Eugene, OR, UNITED STATES

CONTINUING DATA

This application is a CIP of 16431322 06/04/2019 PAT 10941559

16431322 is a CON of 15639261 06/30/2017 PAT 10309093

15639261 has PRO of 62356793 06/30/2016

FOREIGN APPLICATIONS

IF REQUIRED, FOREIGN LICENSE GRANTED**

05/04/2020

**** SMALL ENTITY ****

STATE OR COUNTRY

UNITED STATES

ADDRESS

MACCORD MASON PLLC

2733 Horse Pen Creek Road, Suite 101

GREENSBORO, NC 27410

UNITED STATES

FILING FEE RECEIVED

\$865



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	865	9693-012A-CIP	20	2

4678
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

CONFIRMATION NO. 8204
CORRECTED FILING RECEIPT



Date Mailed: 10/28/2021

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, Eugene, OR;

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CIP of 16/431,322 06/04/2019 PAT 10941559
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 05/04/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/861,012**

Projected Publication Date: Request for Non-Publication Acknowledged

Non-Publication Request: Yes

Early Publication Request: No

**** SMALL ENTITY ****

Title

SHELTER AND HUB SYSTEM

Preliminary Class

135

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative,

page 2 of 4

this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC

Serial No.: 16/861,012

Filed: April 28, 2020

Confirmation No.: 8204

Examiner: R. Canfield

Art Unit: 3636

For: SHELTER AND HUB SYSTEM

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

AMENDMENT UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM

In response to the Office Action mailed July 26, 2021, please consider the following amendments and arguments supporting allowance of the claimed subject matter.

The Commissioner is authorized to charge Deposit Account 501923 if any Extension of Time, or any additional fees for the accompanying response are required, and Applicant requests that this be considered a Petition therefor.

Amendment to the Claims begin on Page 2.

Remarks begin on Page 6.

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

We Claim:

1. **(Currently Amended)** A rapid-deployment shelter system, said shelter system comprising:

a shelter including a frame and a cover, wherein ~~a the~~ frame system is configured to alternate between a first extended angular opened position and a second retracted position;

the frame including more than one set of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;

the frame in the angular opened position including:

frame poles that are joined in pairs serving as leg poles,

frame poles that are joined in pairs serving as ceiling poles,

the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;

wherein the joined leg poles and ceiling poles form an exterior frame opening configured to mate with an exterior frame opening of another shelter;

the shelter including a door end along each side of said shelter

~~the frame including an exterior frame opening along each side of the frame.~~

2. **(Currently Amended)** The shelter system of claim 1, wherein ~~said~~ the frame includes at least four exterior frame openings.
3. **(Previously Amended)** The shelter system of claim 1, wherein the shelter is a hub shelter.

4. (Previously Amended) The shelter system of claim 3, wherein the hub shelter is adapted to mate with a second shelter.
5. (Previously Amended) The shelter system of claim 4, wherein the hub shelter and the second shelter adjoin one with another to form a continuous interior space in a shelter complex.
6. (Previously Amended) The shelter system of claim 5, wherein the exterior frame openings include a set of upper angles and a set of lower angles.
7. (Original) The shelter system of claim 6, wherein the set of upper angles are each greater than the angles of each lower angle in the set of lower angles.
8. Cancelled
9. (Original) The shelter system of claim 3 wherein said hub shelter includes a shelter door end along each side of the shelter.
10. (Previously Amended) The shelter system of claim 1 wherein the frame at an exterior of the frame system is configured to fit with a frame of a second shelter to form a shared interior space through an angular mated opening.
11. **(Currently Amended)** The shelter system of claim 10 wherein each shelter includes a door end ~~is an door end~~.
12. (Previously Amended) The shelter system of claim 10 including a shelter attachment device that fits along the face of the angular mated opening to form a connection between the adjoining shelters to avoid water penetration.

13. (Previously Amended) The shelter system of claim 12 wherein said shelter attachment is a geometric replica of the dimensions of the angular mated opening.

14. Cancelled

15. **(Currently Amended)** A rapid-deployment shelter system, the shelter system comprising:

an articulating frame system, said articulating frame system including a plurality of interconnected frame poles forming a frame, said articulating frame system configured to alternate between a first extended angular opened position and a second retracted position;

the frame including more than one set of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;

the frame in the angular opened position including:

frame poles that are joined in pairs serving as leg poles,

frame poles that are joined in pairs serving as ceiling poles,

the leg poles each adjoining to ceiling poles and the ceiling poles

adjoining with each other to form an upper angle at a peak;

a cover configured to fit with the frame to form a shelter, **wherein the shelter is a hub shelter including a door end along each side of said shelter, and**

wherein the frame at the exterior of the articulating frame system is configured to fit with a frame of a second shelter to form a shared interior space through an angular mated opening.

16. **(Currently Amended)** The shelter system of claim 15 wherein the frame and the frame of a the second shelter form a shelter complex with a shared interior space.

17. **(Currently Amended)** The shelter system of claim 16 including a hub ~~in each of the shelters~~ that serves to connect ~~items~~ in the interior of the shelter ~~and the second shelter in the shared interior space to one of either the frame or frame of the second shelter.~~
18. **(Currently Amended)** The shelter system of claim 16 wherein the frame and the ~~second~~ frame **of the second shelter** include door ends.
19. (Original) The shelter system of claim 18 including a shelter attachment that fits with the door ends of the shelter and second shelter.
20. Cancelled

Remarks

The Office Action mailed July 26, 2021 has been carefully considered. After such consideration, various claims have been amended toward indicated allowance, to adjust for proper antecedent basis, and to advance prosecution.

Specifically, Claim 20 was indicated as objected to as being dependent upon a rejected base claim but allowable if rewritten in independent form. Claim 20 has been cancelled and the limitation incorporated into claim 15 and is therefore believed to be in condition for allowance.

Claims 1-14 were indicated as allowable if rewritten or amended to overcome the §112 rejections. Consistent with these findings amendment has been made to overcome the §112 rejections and Claims 1-14 are also believed to be in condition for allowance. The wording from the drawing objection has either been removed, amended or the claim cancelled.

Claims 8, 14, and 20 have been cancelled. It is believed that all remaining claims are in condition for allowance and/or depend now from a claim indicated as allowable.

The priority as noted had a typographical error in the corrected ADS which has now been corrected. It is believed all remaining claims are in condition for allowance, consistent with the indicated allowable subject matter of the previous office action. If any matters remain unresolved, Applicant's attorney requests a phone call to address such matters.

Drawings

The wording "frame opening along each side" has been removed and replaced with the clearer, supported wording "the shelter including a door end along each side of said shelter." Claims 8 and 14 have been cancelled. Claim 17 language has been amended removing the "hub in each of the shelters" language. With these amendments, it is believed the drawing objection has been overcome and reconsideration is requested.

Objections

Claim 20 was objected to as being dependent upon a rejected base claim but allowable if rewritten in independent form including any intervening claims. Claim 20 has been cancelled and the Claim 20 limitation incorporated into claim 15 and Claim 15 is therefore believed to be in

condition for allowance. Claims 16-19 depend from Claim 15 and are therefore also believed to be in condition for allowance.

35 USC §112

The language of Claims 1 and 10 referring to “the frame system” has been amended for proper antecedent basis.

In Claim 2, “said” has been removed from “said the frame” clarifying the claim language.

In Claim 11, the repeated phrase has been removed for clarity.

Claim 17 has been amended to the language as suggested for clarity.

In Claim 18, the language has been amended and proper antecedent basis has been provided.

By these amendments, all outstanding §112 issues have been addressed and it is believed overcome.

Conclusion

Accordingly, the claims, as amended, patentably distinguish over the cited references and allowance is respectfully requested. Applicants note that because Applicants have addressed certain concerns of the Office does not mean that Applicants concede other comments of the Office. Furthermore, in the interest of clarity and brevity, the fact that Applicants have made arguments for the patentability of some claims does not necessarily suggest that there are not additional supportive grounds for the patentability of those or other claims.

The Applicants submit that by this amendment, he/she has placed the case in condition for immediate allowance and such action is respectfully requested. However, if any issue remains unresolved, Applicants’ attorney would welcome the opportunity for a telephone interview to expedite allowance and issue.

Respectfully submitted,

/Kelly B. Robinson/

Kelly B. Robinson
Registration No. 72,960
MacCord Mason PLLC
2733 Horse Pen Creek Road, Suite 101
Greensboro, North Carolina 27410
(336) 273-4422

Date: October 26, 2021
File No.: 9693-012A-CIP

CERTIFICATION AND REQUEST FOR CONSIDERATION UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM 2.0		
Practitioner Docket No.: 9693-012A-CIP	Application No.: 16/861,012	Filing Date: April 28, 2020
First Named Inventor: Jonathan Urhausen	Title: SHELTER AND HUB SYSTEM	
<p>APPLICANT HEREBY CERTIFIES THE FOLLOWING AND REQUESTS CONSIDERATION UNDER THE AFTER FINAL CONSIDERATION PILOT PROGRAM 2.0 (AFCP 2.0) OF THE ACCOMPANYING RESPONSE UNDER 37 CFR 1.116.</p> <ol style="list-style-type: none"> 1. The above-identified application is (i) an original utility, plant, or design nonprovisional application filed under 35 U.S.C. 111(a) [a continuing application (<i>e.g.</i>, a continuation or divisional application) is filed under 35 U.S.C. 111(a) and is eligible under (i)], or (ii) an international application that has entered the national stage in compliance with 35 U.S.C. 371(c). 2. The above-identified application contains an outstanding final rejection. 3. Submitted herewith is a response under 37 CFR 1.116 to the outstanding final rejection. The response includes an amendment to at least one independent claim, and the amendment does not broaden the scope of the independent claim in any aspect. 4. This certification and request for consideration under AFCP 2.0 is the only AFCP 2.0 certification and request filed in response to the outstanding final rejection. 5. Applicant is willing and available to participate in any interview requested by the examiner concerning the present response. 6. This certification and request is being filed electronically using the Office's electronic filing system (EFS-Web). 7. Any fees that would be necessary consistent with current practice concerning responses after final rejection under 37 CFR 1.116, <i>e.g.</i>, extension of time fees, are being concurrently filed herewith. [There is no additional fee required to request consideration under AFCP 2.0.] 8. By filing this certification and request, applicant acknowledges the following: <ul style="list-style-type: none"> • Reissue applications and reexamination proceedings are not eligible to participate in AFCP 2.0. • The examiner will verify that the AFCP 2.0 submission is compliant, <i>i.e.</i>, that the requirements of the program have been met (see items 1 to 7 above). For compliant submissions: <ul style="list-style-type: none"> ○ The examiner will review the response under 37 CFR 1.116 to determine if additional search and/or consideration (i) is necessitated by the amendment and (ii) could be completed within the time allotted under AFCP 2.0. If additional search and/or consideration is required but cannot be completed within the allotted time, the examiner will process the submission consistent with current practice concerning responses after final rejection under 37 CFR 1.116, <i>e.g.</i>, by mailing an advisory action. ○ If the examiner determines that the amendment does not necessitate additional search and/or consideration, or if the examiner determines that additional search and/or consideration is required and could be completed within the allotted time, then the examiner will consider whether the amendment places the application in condition for allowance (after completing the additional search and/or consideration, if required). If the examiner determines that the amendment does not place the application in condition for allowance, then the examiner will contact the applicant and request an interview. <ul style="list-style-type: none"> ▪ The interview will be conducted by the examiner, and if the examiner does not have negotiation authority, a primary examiner and/or supervisory patent examiner will also participate. ▪ If the applicant declines the interview, or if the interview cannot be scheduled within ten (10) calendar days from the date that the examiner first contacts the applicant, then the examiner will proceed consistent with current practice concerning responses after final rejection under 37 CFR 1.116. 		
Signature /Kelly B. Robinson/	Date October 26, 2021	Practitioner Registration No. 72960
Name (Print/Typed) Kelly B. Robinson	Telephone Number 336-273-4422	
Note: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. Submit multiple forms if more than one signature is required, see below*.		
☒ * Total of <u>1</u> forms are submitted.		

Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Acknowledgement Receipt

EFS ID:	44122457
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CIP
Receipt Date:	26-OCT-2021
Filing Date:	28-APR-2020
Time Stamp:	15:22:02
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1		9693-012A-CIP_Response.pdf	109198	yes	8
			9a50d424c9ed3eace33bb941557553b9605b82f6		

Multipart Description/PDF files in .zip description					
Document Description			Start	End	
Response After Final Action			1	1	
Claims			2	5	
Applicant Arguments/Remarks Made in an Amendment			6	8	
Warnings:					
Information:					
2	After Final Consideration Program Request	9693-012A-CIP_AFCP.pdf	223975	no	2
			0e38c58f9e8c3181bd1b0606414708c47fc8adc9		
Warnings:					
Information:					
Total Files Size (in bytes):			333173		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875	Application or Docket Number 16/861,012	Filing Date 04/28/2020	☐ To be Mailed
---	--	---------------------------	---------------------------------------

ENTITY: ☐ LARGE ☒ SMALL ☐ MICRO

APPLICATION AS FILED - PART I

FOR	(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA	RATE (\$)	FEE (\$)
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A	
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))	N/A	N/A	N/A	
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A	
TOTAL CLAIMS (37 CFR 1.16(i))	minus 20 = *		x \$50 =	
INDEPENDENT CLAIMS (37 CFR 1.16(h))	minus 3 = *		x \$230 =	
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).			
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))				
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL	

APPLICATION AS AMENDED - PART II

		(Column 1)		(Column 2)	(Column 3)	RATE (\$)	ADDITIONAL FEE (\$)	
AMENDMENT	10/26/2021	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA			
	Total (37 CFR 1.16(i))	* 17	Minus	** 20	= 0	x \$50 =	0	
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0	x \$240 =	0	
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
						TOTAL ADD'L FEE	0	
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE (\$)	ADDITIONAL FEE (\$)	
	Total (37 CFR 1.16(i))	*	Minus	**	=	x \$0 =		
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x \$0 =		
	☐ Application Size Fee (37 CFR 1.16(s))							
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							
						TOTAL ADD'L FEE		
* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.						LIE		
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".						/TARA A WASHINGTON/		
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".								
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.								

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Jonathan Urhausen et al.
Serial No.: 16/861,012
Filing Date: April 28, 2020
Confirmation No.: 8204
For: SHELTER AND HUB SYSTEM

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

Sir:

REQUEST FOR CORRECTED FILING RECEIPT

Applicant has attached a corrected Application Data Sheet and requests that this application be updated to reflect the correct Domestic Priority Data. The correct priority data should read as follows:

This application is a CIP of 16/431,322 06/04/2019 PAT 10941559
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Applicant requests that an Updated Filing Receipt be issued.

The Commissioner is hereby authorized to charge any fees which may be required to
Deposit Account No. 501923.

Respectfully submitted,

/Kelly B. Robinson/

Kelly B. Robinson
Registration No. 72,960
MacCord Mason PLLC
2733 Horse Pen Creek Road, Suite 101
Greensboro, NC 27410
(336) 273-4422

Date: October 26, 2021
File No.: 9693-012A-CIP

CORRECTED ADS FORM

Application Number	16861012
Title of Invention	SHELTER AND HUB SYSTEM

Inventor Information

****If no data is shown, no data has been corrected****

	Data of Record	Updated Data
Order Number		
Name		

Residence Information

Residency		
City		
State		
Country of Residence		

Mailing Address of Inventor

Address 1		
Address 2		
City,State/Province, Postal Code		
Country		



Application Information

	Data of Record	Updated Data
Title of Invention	SHELTER AND HUB SYSTEM	
Attorney Docket Number	9693-012A-CON1	
Entity Type	Small	

Domestic Benefit/National Stage Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121,365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S. C. 119(e) or 120, and 37 CFR 1.78(a).

	Data of Record	Updated Data
Prior Application Status	patented	
Application Number	16861012	
Continuity Type	CON	<u>CIP</u>
Prior Application Number	16431322	
Filing Date (YYYY-MM-DD)	2019-06-04	
Patent Number	10941559	
Issue Date (YYYY-MM-DD)	2021-03-09	

		Data of Record	Updated Data
	Prior Application Status	patented	
	Application Number	16431322	
	Continuity Type	CON	<u>CON</u>
	Prior Application Number	15639261	
	Filing Date (YYYY-MM-DD)	2017-06-30	
	Patent Number	10309093	
	Issue Date (YYYY-MM-DD)	2019-06-04	

		Data of Record	Updated Data
	Prior Application Status	pending	
	Application Number	15639261	
	Continuity Type	PRO	
	Prior Application Number	62356793	
	Filing Date (YYYY-MM-DD)	2016-06-30	
	Patent Number		
	Issue Date (YYYY-MM-DD)	0001-01-01	

Foreign Priority Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

		Data of Record	Updated Data
	Application Number		
	Country		
	Filing Date		
	Access Code		

Applicant Information

****If no data is shown, no data has been corrected****

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

	Data of Record	Updated Data
Applicant Type		
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is		
Name of the Deceased or Legally Incapacitated Inventor		
Applicant is an Organization		
Name		
Organization Name		
Address 1		
Address 2		
City,State/Province,Postal Code		
Country		
Phone Number		
Fax Number		

Email Address		
---------------	--	--

Assignee Information including Non-Applicant Assignee Information

****If no data is shown, no data has been corrected****
Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office

	Data of Record	Updated Data
Order		
Applicant is an Organization		
Name		
Organization Name		

Mailing Address

Address 1		
Address 2		
City,State/Province,Postal Code		
Country		
Phone Number		
Fax Number		
Email Address		

Signature

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b).

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, all joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of all joint inventor-applicants.

Signature	/Kelly B. Robinson/	Registration Number	72960
First Name	Kelly	Last Name	Robinson

Electronic Acknowledgement Receipt

EFS ID:	44122312
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CIP
Receipt Date:	26-OCT-2021
Filing Date:	28-APR-2020
Time Stamp:	11:19:00
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Request for Corrected Filing Receipt	9693-012A-CIP_Request_for_Corrected_Filing_Receipt.pdf	75300 2f6085f7a5fa5418955b7e2743cbbf54d3c22c12	no	1

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:					
2	Application Data Sheet	9693-012A-CIP_Corrected_ADS.pdf	3188787	no	6
			7104b9ccc6869a8af9492ce8040d340689cd3a26		
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
Total Files Size (in bytes):				3264087	
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CIP	8204
4678	7590	07/26/2021		
MACCORD MASON PLLC 2733 Horse Pen Creek Road, Suite 101 GREENSBORO, NC 27410			EXAMINER CANFIELD, ROBERT	
			ART UNIT	PAPER NUMBER
			3636	
			MAIL DATE	DELIVERY MODE
			07/26/2021	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 16/861,012	Applicant(s) Urhausen et al.	
	Examiner ROBERT CANFIELD	Art Unit 3636	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 5/05/21.
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on ____.
- 2a) ☒ This action is **FINAL**. 2b) ☐ This action is non-final.
- 3) ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on ____; the restriction requirement and election have been incorporated into this action.
- 4) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

- 5) ☒ Claim(s) 1-20 is/are pending in the application.
5a) Of the above claim(s) ____ is/are withdrawn from consideration.
- 6) ☐ Claim(s) ____ is/are allowed.
- 7) ☒ Claim(s) 1-19 is/are rejected.
- 8) ☒ Claim(s) 20 is/are objected to.
- 9) ☐ Claim(s) ____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to PPHfeedback@uspto.gov.

Application Papers

- 10) ☐ The specification is objected to by the Examiner.
- 11) ☒ The drawing(s) filed on 5/29/20 is/are: a) ☐ accepted or b) ☒ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

- a) ☐ All b) ☐ Some** c) ☐ None of the:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. ____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☐ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b)
Paper No(s)/Mail Date ____.
- 3) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date ____.
- 4) ☐ Other: ____.

Notice of Pre-AIA or AIA Status

1. This office action is in response to the amendment filed 5/05/21. Claims 1-20 are pending. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.
2. While corrected ADS correctly reflects that the instant application is a CIP of application serial number 16/431,322 it is not clear why the continuity type CON has been deleted ("~~CON~~") for serial number 16/431,322 with respect to serial number 15/639,261? As "corrected" there is no continuity type listed between applications 16/431,322 and 15/639,261.
3. The text of those sections of Title 35, U.S. Code not included in this action can be found in a prior Office action.
4. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, a frame opening ***along each side*** as now called for in claim 1, the top upper angle greater than the other upper angles [cl. 8], the hook and loop configuration [cl. 14] and a hub in each of the shelters [cl.17] must be shown or the feature(s) canceled from the claim(s). No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate

prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as “amended.” If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either “Replacement Sheet” or “New Sheet” pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

5. Claims 1-14 and 17-19 are rejected under 35 U.S.C. 112(b) or 35 U.S.C. 112 (pre-AIA), second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which the inventor or a joint inventor (or for applications subject to pre-AIA 35 U.S.C. 112, the applicant), regards as the invention.

In claims 1 and 10, “the frame system” lacks antecedent basis.

In claim 2, “said the frame” is unclear.

In claim 11, “includes a door end is an door end” is unclear.

Claim 17 is completely unclear and does not appear to claim what is disclosed.

As best understood each shelter does not include a hub. The examiner suggests the following:


17. (Currently Amended) The shelter system of claim 16 including a hub-in each of the shelters that serves to connect items in the interior of the shelter and the second shelter in the shared interior space to one of either the frame or frame of the second shelter.

In claim 18, "the second frame" lacks antecedent basis. The examiner suggests amending to "the frame of the second shelter".


6. Claims 15-19 are rejected under 35 U.S.C. 102(a)(1) as being anticipated by U.S. Patent 3,559,353 to Partridge.

Partridge provides a shelter system which can be "easily erected and collapsed" [col. 1, Ins. 24-26] which is considered to meet "rapid-deployment". The system comprised of arched frame units 10 comprised of a plurality of interconnected frame poles 11. The configured to alternate between a first extended angular open position [Fig.3] and second retracted or "collapsed" position.

Each unit 10 which may be joined end to end with another unit [col. 2, Ins. 43-45]. Covering 9 is it over the framework. Each open end of figure 4 is considered a "door end". Any or the units 10 may be considered "a hub shelter" as they are configured to mate to an adjacent unit at each end. With respect to claim 19, col. 2 line 46 recites that the ends of members 1 may be socketed together which is considered to meet the limitation of "a shelter attachment".




Alternately:



7. Claims 15-19 are rejected under 35 U.S.C. 102(a)(1) as being anticipated by U.S. Patent 9,752,345 to LaHood .

LaHood provides a shelter system comprised of first and second shelters 12 and 12' or 12" and 12". Each shelter comprised a frame comprised of a plurality of interconnected frame poles 52 and a cover 54. A hub 50 is provided in each shelter. LaHood further teaches removing at least one side wall panel 14a (which suggests more than one) and securing adjacent shelters together using attachment devices 60/160 by way of hook and loop [col.8, ln. 47] to form a continuous interior space without narrowing. Any side may be considered "a door end". Any one of the shelters may be considered a "hub shelter".



8. Claim 20 is objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

9. Claims 1-14 would be allowable if rewritten or amended to overcome the rejection(s) under 35 U.S.C. 112(b) or 35 U.S.C. 112 (pre-AIA), 2nd paragraph, set forth in this Office action.

10. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

11. Applicant's arguments filed 5/05/21 have been considered but they are not found fully persuasive.

The corrected ADS corrected one issue and created another. As noted above there is now no continuity type listed between applications 16/431,322 and 15/639,261.

The claim amendments have not resolved the drawing objections as alleged. The drawings are objected for not showing claimed subject matter as outlined above.

The examiner agrees that Lilly fails to provide the claimed articulated paired pole structures.

The examiner disagrees that LaHood and Partridge fail to provide articulated leg poles and ceiling poles however neither frame of LaHood or Partridge includes a frame opening ***along each side*** as now called for in claim 1. This feature is not required of claim 15. Partridge only has openings at two ends which is why it still meets claim 15 as noted above. LaHood teaches removing at least one wall panel but wouldn't work if all sides were removed.

12. Applicant's amendment necessitated the new ground(s) of rejection presented in this Office action. Accordingly, **THIS ACTION IS MADE FINAL**. See MPEP § 706.07(a). Applicant is reminded of the extension of time policy as set forth in 37 CFR 1.136(a).

A shortened statutory period for reply to this final action is set to expire THREE MONTHS from the mailing date of this action. In the event a first reply is filed within TWO MONTHS of the mailing date of this final action and the advisory action is not mailed until after the end of the THREE-MONTH shortened statutory period, then the

shortened statutory period will expire on the date the advisory action is mailed, and any extension fee pursuant to 37 CFR 1.136(a) will be calculated from the mailing date of the advisory action. In no event, however, will the statutory period for reply expire later than SIX MONTHS from the date of this final action.

13. Any inquiry concerning this communication or earlier communications from the examiner should be directed to ROBERT CANFIELD whose telephone number is (571)272-6840. The examiner can normally be reached on M-F 10-6, some Saturdays.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Dunn can be reached on 571-272-6670. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <https://ppair-my.uspto.gov/pair/PrivatePair>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access

to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

ROBERT CANFIELD
Primary Examiner
Art Unit 3635

/Robert Canfield/
Primary Examiner, Art Unit 3636

<i>Notice of References Cited</i>	Application/Control No. 16/861,012		Applicant(s)/Patent Under Reexamination Urhausen et al.	
	Examiner ROBERT CANFIELD		Art Unit 3636	Page 1 of 1

U.S. PATENT DOCUMENTS						
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20170247906-A1	08-2017	Zeigler; Theodore R.	E04H15/50	1/1
*	B	US-20080017232-A1	01-2008	Zeigler; Theodore R.	E04H15/50	135/131
*	C	US-20070084493-A1	04-2007	Prusmack; A. Jon	E04H15/18	135/135
*	D	US-20050204681-A1	09-2005	Zeigler; Theodore R.	E04H15/50	52/646
*	E	US-20050204680-A1	09-2005	Zeigler; Theodore R.	E04H15/50	52/646
*	F	US-10995516-B2	05-2021	Ribner; Thad B.	E04H15/50	1/1
*	G	US-8082938-B2	12-2011	Prusmack; A. Jon	E04B1/3441	135/135
*	H	US-6141934-A	11-2000	Zeigler; Theodore R.	E04H15/50	135/121
*	I	US-4953329-A	09-1990	Frantl; Erich	E04B1/3205	52/80.1
*	J	US-4689932-A	09-1987	Zeigler; Theodore R.	E04B1/3211	52/653.1
*	K	US-4373305-A	02-1983	Russell; Leslie T.	E04B1/32	52/64
*	L	US-20040173252-A1	09-2004	Bouchard, Georges	E04H15/50	135/131
*	M	US-10060151-B2	08-2018	Krenzel; Ronald L.	E04H15/40	1/1

FOREIGN PATENT DOCUMENTS					
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	CPC Classification
	N				
	O				
	P				
	Q				
	R				
	S				
	T				

NON-PATENT DOCUMENTS		
*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
 Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

<i>Search Notes</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

CPC - Searched*		
Symbol	Date	Examiner
E04H15/18, 36, 44	01/01/2021	RC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner
135	97	01/01/2021	RC
52	79.9		
52	79.5, 79.7, 79.8, 79.12, 86	07/23/2021	RC
135	97, 124, 128, 131, 906, 908		

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
EAST classification/text/name/citation search - history attached	01/01/2021	RC
reviewed both parent file histories and checked for double patenting		
updated search - history attached and checked for double patenting issues again	07/23/2021	RC

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

<i>Search Notes</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	3	((("3559353") or ("9714523") or ("9752345")).PN.	USPAT	OR	OFF	2021/07/23 13:01
L2	2	((("10941559") or ("10309093")).PN.	USPAT	OR	OFF	2021/07/23 13:19
L5	2,469	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/07/23 14:15
L6	1,140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/07/23 14:15
L7	2,317	y10t403/342,347.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:15
L8	3,798	y10t403/4949,4966.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:15
L9	4,436	e04b1/1903,3441.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:15
L10	3,956	e04h15/34,44,48,50.cpc.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:15

L11	485	(135/28).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/07/23 14:15
L12	423	(135/97).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/07/23 14:16
L13	17,373	1 2 5 6 7 8 9 10 11 12	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:16
L14	255	13 and @pd>"20210101"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:16
L15	29	("20050194032" "20050204680" "20050204681" "20050262779" "20060101631" "20060157100" "20080016817" "20080017232" "20080017233" "20080017234" "20120298162" "20170175414" "20170247906" "4689932" "5230196" "5274980" "5444946" "5651228" "6141934" "7357238" "7455164" "7481235" "7533498" "7556054" "7712261" "7832170" "8082938" "9631393" "RE33710").PN. OR ("10995516").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/07/23 14:21
L16	2,618	52/79.5,79.7,9.8,79.12,86.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:24
L17	1,928	135/97,124,128,131,906,908.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO;	OR	ON	2021/07/23 14:45

			DERWENT; IBM_TDB			
L18	1,800	17 not 16	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 14:45
L19	1	("10060151").PN.	USPAT	OR	OFF	2021/07/23 15:32
L20	55	("1666757" "1884449" "20020104561" "20040238021" "20050189009" "20050205124" "20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "3699986" "3756649" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "5641192" "6273114" "6357462" "6666223" "7040333" "7588045" "8001987" "8132584" "8316508" "8763621" "8776815" "9470010" "D470560" "D652885" "D692083" "D779611").PN. OR ("10060151").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/07/23 15:32
L21	1	("10364588").PN.	USPAT	OR	OFF	2021/07/23 15:34
L22	65	("1666757" "1884449" "1927387" "20020104561" "20040238021" "20050189009" "20050205124" "20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "2935074" "3316508" "3699986" "3756649" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "5641192" "5669655" "6273114" "6357462" "6666223" "7040333" "7588045" "8001987" "8132584"	US-PGPUB; USPAT; USOCR	OR	ON	2021/07/23 15:34

		"8763621" "8776815" "9470010" "D224850" "D369638" "D470560" "D624623" "D652885" "D692083" "D779611").PN. OR ("10364588").URPN.				
L23	11	22 not 20	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 15:34
L24	62	("20180155952" "4658560" "4995212" "6772780" "9163425" "9631393" "D454609" "20050189009" "20060283103" "3955328" "4649947" "6145525" "4706696" "8360085" "9243424" "10858856" "4886084" "9752345" "9869110" "3929146" "5017068" "5634483" "D544941" "5666986" "20080017233" "10309093" "20070051399" "4945936" "6553699" "6802329" "8925565" "20070039639" "20080264462" "20100170162" "3559353" "9714523" "20060260666" "4846204" "5069572" "6758354" "7533498" "9103137" "20130008478" "20140182643" "6223482" "6553698" "7131236" "8496019" "9243423" "9605441" "20120090455" "5159948" "8381454" "D652885" "20150167343" "20150240513" "5943837" "7556054" "8448656" "20070125410" "5394897" "9470010").PN.	US-PGPUB; USPAT	OR	ON	2021/07/23 15:42
L25	16	(US-20080017233-\$ or US-20050204681-\$ or US-20050204680-\$ or US- 20080017232-\$ or US-20170247906-\$ or US-20070084493-\$).did. or (US- 10995516-\$ or US-4689932-\$ or US- 6141934-\$ or US-8082938-\$ or US- 4373305-\$ or US-4953329-\$).did. or (US- 20200190844-\$ or AT-8701724-\$ or US- 20040173252-\$ or US-20180100326-\$).did.	US-PGPUB; USPAT; DERWENT	OR	ON	2021/07/23 15:42
L26	15	25 not 24	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/07/23 15:42

L27	1	("4689932").PN.	USPAT	OR	OFF	2021/07/23 16:26
-----	---	-----------------	-------	----	-----	---------------------

7/23/2021 4:46:22 PM

C:\Users\rcafield\Documents\EAST\Workspaces\16861012.wsp



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	865	9693-012A-CON1	20	2

4678
MACCORD MASON PLLC
2733 Horse Pen Creek Road, Suite 101
GREENSBORO, NC 27410

CONFIRMATION NO. 8204
CORRECTED FILING RECEIPT



Date Mailed: 05/06/2021

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, Eugene, OR;

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CIP of 16/431,322 06/04/2019 PAT 10941559
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 05/04/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/861,012**

Projected Publication Date: Request for Non-Publication Acknowledged

Non-Publication Request: Yes

Early Publication Request: No

**** SMALL ENTITY ****

Title

SHELTER AND HUB SYSTEM

Preliminary Class

135

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative,

page 2 of 4

this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

CORRECTED ADS FORM

Application Number	16861012
Title of Invention	SHELTER AND HUB SYSTEM

Inventor Information

****If no data is shown, no data has been corrected****


	Data of Record	Updated Data
Order Number		
Name		

Residence Information

Residency		
City		
State		
Country of Residence		

Mailing Address of Inventor

Address 1		
Address 2		
City,State/Province, Postal Code		
Country		



Application Information

	Data of Record	Updated Data
Title of Invention	SHELTER AND HUB SYSTEM	
Attorney Docket Number	9693-012A-CON1	
Entity Type	Small	

Domestic Benefit/National Stage Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121,365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S. C. 119(e) or 120, and 37 CFR 1.78(a).

	Data of Record	Updated Data
Prior Application Status	patented	
Application Number	16861012	
Continuity Type	CON	<u>CIP</u>
Prior Application Number	16431322	
Filing Date (YYYY-MM-DD)	2019-06-04	
Patent Number	10941559	
Issue Date (YYYY-MM-DD)	2021-03-09	

		Data of Record	Updated Data
	Prior Application Status	patented	
	Application Number	16431322	
	Continuity Type	CON	
	Prior Application Number	15639261	
	Filing Date (YYYY-MM-DD)	2017-06-30	
	Patent Number	10309093	
	Issue Date (YYYY-MM-DD)	2019-06-04	
		Data of Record	Updated Data
	Prior Application Status	pending	
	Application Number	15639261	
	Continuity Type	PRO	
	Prior Application Number	62356793	
	Filing Date (YYYY-MM-DD)	2016-06-30	
	Patent Number		
	Issue Date (YYYY-MM-DD)	0001-01-01	

Foreign Priority Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

		Data of Record	Updated Data
	Application Number		
	Country		
	Filing Date		
	Access Code		

Applicant Information

****If no data is shown, no data has been corrected****
Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

	Data of Record	Updated Data
Applicant Type		
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is		
Name of the Deceased or Legally Incapacitated Inventor		
Applicant is an Organization		
Name		
Organization Name		
Address 1		
Address 2		
City,State/Province,Postal Code		
Country		
Phone Number		
Fax Number		

Email Address		
---------------	--	--

Assignee Information including Non-Applicant Assignee Information

****If no data is shown, no data has been corrected****
Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office

	Data of Record	Updated Data
Order		
Applicant is an Organization		
Name		
Organization Name		

Mailing Address

Address 1		
Address 2		
City,State/Province,Postal Code		
Country		
Phone Number		
Fax Number		
Email Address		

Signature

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b).

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Kelly B. Robinson/	Registration Number	72960
First Name	Kelly	Last Name	Robinson

Electronic Acknowledgement Receipt

EFS ID:	42643888
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	
Customer Number:	4678
Filer:	Kelly B. Robinson/Christian Carter
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	05-MAY-2021
Filing Date:	28-APR-2020
Time Stamp:	14:19:42
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet to update/ correct info	CorrectedADS.pdf	76631	no	6
			de28241d4332b48f98a162b25d21b5e534a40ec3		

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:	
Total Files Size (in bytes):	76631
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>	

Electronic Patent Application Fee Transmittal				
Application Number:		16861012		
Filing Date:		28-Apr-2020		
Title of Invention:		SHELTER AND HUB SYSTEM		
First Named Inventor/Applicant Name:		Jonathan Urhausen		
Filer:		Kelly B. Robinson/Christian Carter		
Attorney Docket Number:		9693-012A-CON1		
Filed as Small Entity				
Filing Fees for Utility under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Extension - 1 month with \$0 paid	2251	1	110	110
Miscellaneous:				
Total in USD (\$)				110

Electronic Acknowledgement Receipt

EFS ID:	42643800
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Christian Carter
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	05-MAY-2021
Filing Date:	28-APR-2020
Time Stamp:	14:09:07
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	DA
Payment was successfully received in RAM	\$ 110
RAM confirmation Number	E202155E09220183
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Amendment/Req. Reconsideration-After Non-Final Reject	Amendment_and_EOT.pdf	132450	no	9
			58a1f0e9ad678459f79b34ebeb6a63f71f431 be5f		
Warnings:					
Information:					
2	Fee Worksheet (SB06)	fee-info.pdf	30558	no	2
			bfe99e57defb32ae1086f5fa77024a3c3c828 276		
Warnings:					
Information:					
Total Files Size (in bytes):			163008		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC

Serial No.: 16/861,012

Filed: April 28, 2020

Confirmation No.: 8204

Examiner: R. Canfield

Art Unit: 3636

For: SHELTER AND HUB SYSTEM

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

AMENDMENT AND REQUEST FOR EXTENSION OF TIME

In response to the Office Action mailed January 5, 2021, please consider the following amendments and arguments supporting allowance of the claimed subject matter.

The Commissioner is authorized to charge Deposit Account 501923 for one Extension of Time, or any additional fees for the accompanying response if required, and Applicant requests that this be considered a Petition therefor.

Amendment to the Specification begins on Page 2.

Amendment to the Claims begin on Page 3.

Remarks begin on Page 7.

Amendments to the Specification:

Please replace the first paragraph on page 1 at line 1-6 with the following amended paragraph below:

This application is a continuation-in-part of Application Serial No. 16/431,322, filed June 4, 2019, which is a continuation of Application Serial No. 15/639261, filed June 30, 2017, now Patent No. 10,309,093, which claims benefit of provisional 62/356,793, filed June 30, 2016.

Amendments to the Claims:

This listing of claims will replace all prior versions, and listings, of claims in the application:

We Claim:

1. **(Currently Amended)** A rapid-deployment shelter system, said shelter system comprising:

~~a first shelter including a door end~~ **frame and a cover, wherein the frame system is configured to alternate between a first extended angular opened position and a second retracted position;**

the frame including more than one set of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;

the frame in the angular opened position including:

frame poles that are joined in pairs serving as leg poles,

frame poles that are joined in pairs serving as ceiling poles,

the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;

wherein the joined leg poles and ceiling poles form an exterior frame opening configured to mate with an exterior frame opening of another shelter;

the frame including an exterior frame opening along each side of the frame.

~~a second shelter including a door end, and~~

~~wherein each door end is configured to mate directly one with the other and form a shelter complex having an interior space without a narrowing between the door ends.~~

2. (Currently Amended) The shelter system of claim 1, wherein said ~~first shelter door end~~ and said ~~second shelter door end~~ are ~~arched door ends~~ **the frame includes at least four exterior frame openings.**
3. (Currently Amended) The shelter system of claim 1, wherein the ~~first~~ shelter is a hub shelter.
4. (Currently Amended) The shelter system of claim 3, wherein the hub shelter ~~door end~~ and the ~~second shelter door end~~ are ~~arched door ends~~ **is adapted to mate with a second shelter.**
5. (Currently Amended) The shelter system of claim 4, wherein the hub shelter and the second shelter adjoin one with another to form a continuous interior space in ~~a~~ **the** shelter complex.
6. (Currently Amended) The shelter system of claim 5, wherein the **exterior frame openings** ~~arched door ends~~ include a set of upper angles and a set of lower angles.
7. (Original) The shelter system of claim 6, wherein the set of upper angles are each greater than the angles of each lower angle in the set of lower angles.
8. (Currently Amended) The shelter system of claim 7 wherein ~~the~~ **a** top upper angle is greater than the other upper angles **of the set of upper angles.**
9. (Original) The shelter system of claim 3 wherein said hub shelter includes a shelter door end along each side of the shelter.
10. (Currently Amended) The shelter system of claim ~~1~~ 9 wherein **the frame at an exterior of the frame system is configured to fit with a frame of a second shelter to form a shared interior space through an angular mated opening** ~~each shelter door end is~~

~~configured to mate with an additional shelter to form a consistent interior space within each adjoining shelter and the shelter hub.~~

11. **(Currently Amended)** The shelter system of claim 10 wherein each shelter **includes** a door end is an ~~arched~~ door end.
12. **(Currently Amended)** The shelter system of claim 10 including a shelter attachment device that fits along the ~~mated~~ face of the **angular mated opening** ~~adjoined shelter door ends~~ to form a connection between the adjoining shelters to avoid water penetration.
13. **(Currently Amended)** The shelter system of claim 12 wherein said shelter attachment **is a geometric replica** ~~mimies~~ **of** the dimensions of the **angular mated opening** ~~arched door ends~~.
14. (Original) The shelter system of claim 13 wherein said shelter attachment is secured to the adjoining shelters by way of a hook and loop configuration.
15. **(Currently Amended)** A rapid-deployment shelter system, the shelter system comprising:
 - an a articulating** frame **system**, said **articulating** frame **system** including a plurality of interconnected frame poles **forming a frame**, ~~and~~ said **articulating** frame **system** configured to alternate between a first extended **angular opened** position and a second retracted position;
 - the frame including more than one set of frame poles that are joined in pairs about an axis A at a connected point, the frame poles that are joined in pairs are configured to articulate relative to one another;**
 - the frame in the angular opened position including:**
 - frame poles that are joined in pairs serving as leg poles,**
 - frame poles that are joined in pairs serving as ceiling poles,**

the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;

~~a second frame, said second frame including a plurality of interconnected frame poles and said second frame configured to alternate between a first extended position and a second retracted position independent of the frame;~~

~~a cover configured to fit with the frame to form a shelter;~~

~~a cover configured to fit with the second frame to form a second shelter; and~~

~~wherein said frame and said second frame include matched door end configurations able to adjoin with one another without a narrowing space being formed between the two matched door end configurations.~~

wherein the frame at the exterior of the articulating frame system is configured to fit with a frame of a second shelter to form a shared interior space through an angular mated opening.

16. **(Currently Amended)** The shelter system of claim 15 wherein the frame and **the frame of** a second **shelter** ~~frame~~ form a shelter complex with a shared interior space.
17. **(Currently Amended)** The shelter system of claim 16 including a hub in each of the shelters that serves to connect items in the interior of the shelter and the second shelter in the shared interior space to one of either the frame or second **frame of the second shelter**.
18. **(Currently Amended)** The shelter system of claim 16 wherein the frame and the second frame include ~~arched~~ door ends.
19. (Original) The shelter system of claim 18 including a shelter attachment that fits with the door ends of the shelter and second shelter.
20. (Original) The shelter system of claim 15 wherein said shelter is a hub shelter including a door end along each side of said shelter.

Remarks

The Office Action mailed January 5, 2021 has been carefully considered. After such consideration, various claims have been amended to address typographical errors and antecedent basis and claims 1 and 15 have been amended for clarity and to advance prosecution.

Interview of August 13, 2020

Applicant would first like to thank Examiner Canfield for the interview discussion of April 15, 2021. Applicant agrees with the Interview Summary of 4/16/2021 as to topics discussed, and amendment has been made herein consistent with those discussions.

It is believed that in view of Applicant's amendments and responses included herein, the case is condition for allowance, **if, however, the Examiner finds the application not yet ready for allowance, the Examiner is respectfully requested to phone Applicant's representative to discuss the application further.**

Objections

The objection as to the priority claim language has been amended as requested.

Amendment has been made that eliminates the objected to wording relating to the figures and by this amendment it is believed the objection to the drawings has been addressed and overcome.

35 USC §112

The language objected to in claim 8 and claim 13 has been amended to provide for antecedent basis and further clarification and by these amendments it is believed the objection has been addressed and overcome.

Claim Rejections 35 USC §102 and 35 USC §103

Claims 1-20 were rejected under combinations of US Pat. No. 3,559,353 to Partridge in view of and to combinations of Lilly (US Pat. No. 9,714,523) and/or LaHood (US Pat. No. 9,752,345). Claims 1 and 15 distinguish over each of these references individually and collectively for at least each of the reasons below:

- Applicant claims a different frame structure, and none of the references disclose or suggest a **frame including more than one set of frame poles that are joined in pairs**

about an axis A at a connected point, the frame poles that are joined in pairs configured to articulate relative to one another.

- Also, the references collectively or individually fail to provide a shelter where
the frame in the angular opened position including:
frame poles that are joined in pairs serving as leg poles,
frame poles that are joined in pairs serving as ceiling poles,
the leg poles each adjoining to ceiling poles and the ceiling poles adjoining with each other to form an upper angle at a peak;
- Further, the references do not disclose or suggest **joined leg poles and ceiling poles forming an exterior frame opening configured to mate with an exterior frame opening of another shelter.**
- The references also fail to teach or suggest a frame structure as claimed where the frame **includes an exterior frame opening along each side of the frame.**
- Specifically Lilly nor LaHood teach or suggest Applicant's articulating paired pole structure. Partridge teaches a lattice work unit (10) with a collapsing framework that is attached to and supported by both purlins (1) and curved end stays (5), a very different configuration and structure than is claimed by Applicant.

All references fail to provide or suggest any of the deficiencies described above, either alone or in combination. All of the remaining claims depend from either claim 1 or 15 and are therefore also believed to be in condition for allowance. No new matter has been added and the amendments are supported at least throughout the figures, Pg. 13, lns. 4-19, and Pg. 15, Lns. 20-Pg. 16, Lns. 6. It is believed that the claims distinguish over the cited references and reconsideration and allowance is respectfully requested.

Conclusion

Accordingly, the claims, as amended, patentably distinguish over the cited references and allowance is respectfully requested. Applicants note that because Applicants have addressed certain concerns of the Office does not mean that Applicants concede other comments of the Office. Furthermore, in the interest of clarity and brevity, the fact that Applicants have made

arguments for the patentability of some claims does not necessarily suggest that there are not additional supportive grounds for the patentability of those or other claims.

The Applicants submit that by this amendment, he/she has placed the case in condition for immediate allowance and such action is respectfully requested. However, if any issue remains unresolved, Applicants' attorney would welcome the opportunity for a telephone interview to expedite allowance and issue.

Respectfully submitted,
/Kelly B. Robinson/

Kelly B. Robinson
Registration No. 72,960
MacCord Mason PLLC
P. O. Box 2974
Greensboro, North Carolina 27402
(336) 273-4422

Date: May 5, 2021
File No.: 9693-012A-CON1

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

PATENT APPLICATION FEE DETERMINATION RECORD				Application or Docket Number 16/861,012		Filing Date 04/28/2020		☐ To be Mailed		
Substitute for Form PTO-875										
ENTITY: ☐ LARGE ☒ SMALL ☐ MICRO										
APPLICATION AS FILED - PART I										
FOR		(Column 1) NUMBER FILED	(Column 2) NUMBER EXTRA	RATE (\$)		FEE (\$)				
☐ BASIC FEE (37 CFR 1.16(a), (b), or (c))		N/A	N/A	N/A						
☐ SEARCH FEE (37 CFR 1.16(k), (i), or (m))		N/A	N/A	N/A						
☐ EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))		N/A	N/A	N/A						
TOTAL CLAIMS (37 CFR 1.16(i))		minus 20 = *		x \$50 =						
INDEPENDENT CLAIMS (37 CFR 1.16(h))		minus 3 = *		x \$230 =						
☐ APPLICATION SIZE FEE (37 CFR 1.16(s))		If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).								
☐ MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))										
* If the difference in column 1 is less than zero, enter "0" in column 2.				TOTAL						
APPLICATION AS AMENDED - PART II										
AMENDMENT	05/05/2021	CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE (\$)		ADDITIONAL FEE (\$)		
	Total (37 CFR 1.16(i))	* 20	Minus	** 20	= 0	x \$50 =		0		
	Independent (37 CFR 1.16(h))	* 2	Minus	*** 3	= 0	x \$240 =		0		
	☐ Application Size Fee (37 CFR 1.16(s))									
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))									
						TOTAL ADD'L FEE		0		
AMENDMENT		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE (\$)		ADDITIONAL FEE (\$)		
	Total (37 CFR 1.16(i))	*	Minus	**	=	x \$0 =				
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x \$0 =				
	☐ Application Size Fee (37 CFR 1.16(s))									
	☐ FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))									
						TOTAL ADD'L FEE				
* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.						SLIE				
** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".						/TIMOTHY COLE/				
*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".										
The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.										

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CON1	8204
4678	7590	04/16/2021		
MACCORD MASON PLLC 2733 Horse Pen Creek Road, Suite 101 GREENSBORO, NC 27410			EXAMINER CANFIELD, ROBERT	
			ART UNIT	PAPER NUMBER
			3636	
			MAIL DATE	DELIVERY MODE
			04/16/2021	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

<i>Applicant-Initiated Interview Summary</i>	Application No. 16/861,012	Applicant(s) Urhausen et al.		
	Examiner ROBERT CANFIELD	Art Unit 3636	AIA (First Inventor to File) Status Yes	Page 1 of 1

All Participants (applicant, applicants representative, PTO personnel)	Title	Type
ROBERT CANFIELD	Primary Examiner	Telephonic
Kelly Robinson	Attorney of Record	

Date of Interview: 15 April 2021

Issues Discussed:

Proposed Amendment(s)

Discussed attached proposed claim 1. The examiner noted there appears to be some nomenclature issues. Discussed that frame having a cover there over which includes including ends 59. The examiner indicated he fails to find support for the ends 59 being able to retract to provide an unencumbered passageway and requested support be shown. Also noted that in the proposed claim 1 "the angular entryway of the second shelter" lacked antecedent basis as no second shelter is defined. Examiner acknowledged Lilly fails to provide the articulated frame but Partridge and LaHood both do and would read on proposed claim 1. No agreements were reached.

☒ Attachment

/Robert Canfield/ Primary Examiner, Art Unit 3636	
<p>Applicant is reminded that a complete written statement as to the substance of the interview must be made of record in the application file. It is the applicants responsibility to provide the written statement, unless the interview was initiated by the Examiner and the Examiner has indicated that a written summary will be provided. See MPEP 713.04</p> <p>Please further see: MPEP 713.04 Title 37 Code of Federal Regulations (CFR) § 1.133 Interviews, paragraph (b) 37 CFR § 1.2 Business to be transacted in writing</p>	

Applicant recordation instructions: The formal written reply to the last Office action must include the substance of the interview. (See MPEP section 713.04). If a reply to the last Office action has already been filed, applicant is given a non-extendable period of the longer of one month or thirty days from this interview date, or the mailing date of this interview summary form, whichever is later, to file a statement of the substance of the interview.

Examiner recordation instructions: Examiners must summarize the substance of any interview of record. A complete and proper recordation of the substance of an interview should include the items listed in MPEP 713.04 for complete and proper recordation including the identification of the general thrust of each argument or issue discussed, a general indication of any other pertinent matters discussed regarding patentability and the general results or outcome of the interview, to include an indication as to whether or not agreement was reached on the issues raised.

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC

Serial No.: 16/861,012

Filed: April 28, 2020

Confirmation No.: 8204

Examiner: R. Canfield

Art Unit: 3636

For: SHELTER AND HUB SYSTEM

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

PROPOSED POINTS FOR DISCUSSION AND PROPOSED AMENDMENTS

DO NOT ENTER

1. A rapid-deployment shelter system, said shelter system comprising:

a first shelter including ~~a door end;~~

an articulating frame system of articulating poles, the articulating frame system including a plurality of interconnecting poles forming an angular entryway,

a cover fitting with the articulating frame system, the cover including at least two door ends, said door ends configured to retract to allow the angular entryway of the first shelter to mate with the angular entryway of a second shelter,

~~a second shelter including a door end, and~~

wherein ~~each door end is configured to mate directly one with the other~~ **an interior space is formed at the angular entryway between the first shelter and the second shelter adapted to and** form a shelter complex having an interior space without a **doorway** narrowing between the door ends, **the angular entryway being unincumbered.**

Reference Figures shown below:




FIG. 2




FIG. 20A




FIG. 20C

It is believed the proposed claims address the issues raised by the office and distinguish over the cited references. Applicant welcomes any further suggestions or wording proposed by the office.

Regards,

Kelly



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NO.	FILING DATE	FIRST NAMED INVENTOR	ATTORNEY DOCKET NO.	CONFIRMATION NO.
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CON1	8204
4678	7590	01/05/2021		
MACCORD MASON PLLC 2733 Horse Pen Creek Road, Suite 101 GREENSBORO, NC 27410			EXAMINER CANFIELD, ROBERT	
			ART UNIT	PAPER NUMBER
			3636	
			MAIL DATE	DELIVERY MODE
			01/05/2021	PAPER

Please find below and/or attached an Office communication concerning this application or proceeding.

The time period for reply, if any, is set in the attached communication.

Office Action Summary	Application No. 16/861,012	Applicant(s) Urhausen et al.	
	Examiner ROBERT CANFIELD	Art Unit 3636	AIA (FITF) Status Yes

-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --

Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
- If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
- Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133). Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

Status

- 1) ☒ Responsive to communication(s) filed on 4/28/20.
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on ____.
- 2a) ☐ This action is **FINAL**. 2b) ☒ This action is non-final.
- 3) ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on ____; the restriction requirement and election have been incorporated into this action.
- 4) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

Disposition of Claims*

- 5) ☒ Claim(s) 1-20 is/are pending in the application.
5a) Of the above claim(s) ____ is/are withdrawn from consideration.
- 6) ☐ Claim(s) ____ is/are allowed.
- 7) ☒ Claim(s) 1-20 is/are rejected.
- 8) ☐ Claim(s) ____ is/are objected to.
- 9) ☐ Claim(s) ____ are subject to restriction and/or election requirement

* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see http://www.uspto.gov/patents/init_events/pph/index.jsp or send an inquiry to PPHfeedback@uspto.gov.

Application Papers

- 10) ☒ The specification is objected to by the Examiner.
- 11) ☒ The drawing(s) filed on 5/29/20 is/are: a) ☐ accepted or b) ☒ objected to by the Examiner.
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

Certified copies:

- a) ☐ All b) ☐ Some** c) ☐ None of the:
1. ☐ Certified copies of the priority documents have been received.
2. ☐ Certified copies of the priority documents have been received in Application No. ____.
3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

** See the attached detailed Office action for a list of the certified copies not received.

Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☒ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b)
Paper No(s)/Mail Date 11/04/20.
- 3) ☐ Interview Summary (PTO-413)
Paper No(s)/Mail Date ____.
- 4) ☐ Other: ____.

Notice of Pre-AIA or AIA Status

1. This is a first office action on the merits for application serial number 16/861,012 filed 4/28/20. Claims 1-20 are pending. The present application, filed on or after March 16, 2013, is being examined under the first inventor to file provisions of the AIA.
2. The specification and application data sheet indicate that this application is a continuation of application serial number 16/431,322 filed 6/04/19 which was a continuation of application serial number 15/639,261 filed 6/30/17, which claimed priority to provisional application serial number 62/356,793 filed 6/30/16. While this application repeats a substantial portion of the prior applications, it adds disclosure not presented in the prior applications. Namely, none of Figures 16A-20D and their respective descriptions are disclosed until the filing of the instant application on 4/28/20. Because this application names at least one joint inventor named in the prior application, it appears to constitute a continuation-in-part of the prior application. The first sentence of the specification should be amended accordingly and a corrected application data sheet (ADS) should be filed.
3. The disclosure is objected to because of the following informalities: the first sentence of the specification incorrectly identifies this application as a continuation of application serial number 16/431,322. As noted above, the application is a continuation-in-part because it adds disclosure not found in application serial number 16/431,322

Appropriate correction is required.

4. The information disclosure statement (IDS) submitted on 11/04/20 is in compliance with the provisions of 37 CFR 1.97. Accordingly, the information disclosure statement is being considered by the examiner.
5. The drawings are objected to under 37 CFR 1.83(a). The drawings must show every feature of the invention specified in the claims. Therefore, each door end is configured to mate directly one with the other and form a shelter complex having an interior space without a narrowing between the door ends [cl.1], the top upper angle greater than the other upper angles [cl. 8] and the hook and loop [cl. 14] must be shown or the feature(s) canceled from the claim(s). The door ends in Fig. 18 appear to include a door within a wall so they are not without a narrowing. Fig. 19 shows one shelter end without a narrowing but the other shelter end is not shown. The mating ends are not shown in Fig. 20A, 20B and 20D. In Fig. 20C the ends appear open without a narrowing but they are not mated directly to one another. No new matter should be entered.

Corrected drawing sheets in compliance with 37 CFR 1.121(d) are required in reply to the Office action to avoid abandonment of the application. Any amended replacement drawing sheet should include all of the figures appearing on the immediate prior version of the sheet, even if only one figure is being amended. The figure or figure number of an amended drawing should not be labeled as "amended." If a drawing figure is to be canceled, the appropriate figure must be removed from the replacement sheet, and where necessary, the remaining figures must be renumbered and appropriate changes made to the brief description of the several views of the drawings for consistency. Additional replacement sheets may be necessary to show the renumbering

of the remaining figures. Each drawing sheet submitted after the filing date of an application must be labeled in the top margin as either "Replacement Sheet" or "New Sheet" pursuant to 37 CFR 1.121(d). If the changes are not accepted by the examiner, the applicant will be notified and informed of any required corrective action in the next Office action. The objection to the drawings will not be held in abeyance.

6. The following is a quotation of 35 U.S.C. 112(b):
(b) CONCLUSION.—The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the inventor or a joint inventor regards as the invention.

The following is a quotation of 35 U.S.C. 112 (pre-AIA), second paragraph:
The specification shall conclude with one or more claims particularly pointing out and distinctly claiming the subject matter which the applicant regards as his invention.

7. Claims 8 and 13 are rejected under 35 U.S.C. 112(b) or 35 U.S.C. 112 (pre-AIA), second paragraph, as being indefinite for failing to particularly point out and distinctly claim the subject matter which the inventor or a joint inventor (or for applications subject to pre-AIA 35 U.S.C. 112, the applicant), regards as the invention.

In claim 8, "the top upper angle" and "the other upper angles" lack antecedent basis.

In claim 13, it is not clear what the metes and bounds are of "mimics" dimensions?

8. The following is a quotation of the appropriate paragraphs of 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(a)(1) the claimed invention was patented, described in a printed publication, or in public use, on sale, or otherwise available to the public before the effective filing date of the claimed invention.

9. Claims 1-6, 15, 16 and 18 are rejected under 35 U.S.C. 102(a)(1) as being anticipated by U.S. Patent 3,559,353 to Partridge.

Partridge provides a shelter system which can be “easily erected and collapsed” [col. 1, Ins. 24-26] which is considered to meet “rapid-deployment”. The system comprised of arched frame units 10 comprised of a plurality of interconnected frame pole 11. Each unit 10 which may be joined end to end with another unit [col. 2, Ins. 43-45]. Covering 9 is it over the framework. Each open end of figure 4 is considered a “door end” which is configured to mate to another unit 10 without narrowing. Any or the units 10 may be considered a hub shelter” as they are configured to mate to an adjacent unit at each end. With respect to claim 19, col. 2 line 46 recites that the ends of members 1 may be socketed together.

10. Claims 1-9 are rejected under 35 U.S.C. 102a)(1) as being anticipated by U.S. Patent 9,714,523 to Lilly, II et al.

Lilly provides a shelter system of securing first 30 and second 40 shelters end to end using a hook end loop configuration 50 (Fig. 2). As discussed at column 5, lines 35-36, any of number of shelters can be joined. As discussed at column 10, Ins. 36-44 the end panels may be removed to create a full width opening between connected shelters (Fig. 7). Any one of the shelters may be considered a “hub shelter”. With respect to claim 9, Fig 10 shows a door on each side.

11. Claims 1-6 and 9-20 are rejected under 35 U.S.C. 102(a)(1) as being anticipated by U.S. Patent 9,752,345 to LaHood .

LaHood provides a shelter system comprised of first and second shelters 12 and 12' or 12" and 12''' . Each shelter comprised a frame comprised of a plurality of interconnected frame poles 52 and a cover 54. A hub 50 is provided in each shelter. LaHood further teaches removing at least one side wall panel 14a (which suggests more than one) and securing adjacent shelters together using attachment devices 60/160 by way of hook and loop [col.8, ln. 47] to form a continuous interior space without narrowing. Any one of the shelters may be considered a "hub shelter".

12. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

U.S. 2007/0039639 to Duncan provides plural shelters 12 which may be connected in series [0011] and Fig. 3, each comprised of arched frames 22 and covers 18. It is not clear if the mated ends have an open space without narrowing.

Note figures 8-11 of U.S. 2007/0125410 to Williams.

U.S. 2008/0017233 to Zeigler provides arched frame shelters capable of being mated end to end without a narrowing.

U.S. Patent 4,649,947 to Tury et al. provides in figures 47-49 how a plurality of shelters 10 comprised on arched frame may be connected end to end using a connector 202. While connector 202 is open at its ends without narrowing, the respective shelters 10 appear to have end walls with doors therein.

U.S. Patent 5,159,948 to Moreau et al. teaches a central or hub tent 1 connected to three tents 2-4 on arched "door ends".

CA 2,837,116 to World Shelters Inc. provides mated shelters each including a collapsible arch frame Fig. 2 similar to that disclosed in the instant application. Figures 1A and 1B show door ends of hub shelters mated to door ends of other shelters. However, there is no description or clear showing in the figures that there is no narrowing.

Note hub shelter 4 of DE 29517290 to Umarex.

13. Any inquiry concerning this communication or earlier communications from the examiner should be directed to ROBERT CANFIELD whose telephone number is (571)272-6840. The examiner can normally be reached on M-F 10-6, some Saturdays.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Dunn can be reached on 571-272-6670. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only.

For more information about the PAIR system, see <https://ppair-my.uspto.gov/pair/PrivatePair>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

ROBERT CANFIELD
Primary Examiner
Art Unit 3635

/Robert Canfield/
Primary Examiner, Art Unit 3636

<i>Notice of References Cited</i>	Application/Control No. 16/861,012		Applicant(s)/Patent Under Reexamination Urhausen et al.	
	Examiner ROBERT CANFIELD		Art Unit 3636	Page 1 of 2

U.S. PATENT DOCUMENTS						
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-20120090455-A1	04-2012	Duncan; David	E04H15/18	89/36.07
*	B	US-20100170162-A1	07-2010	Pfeiffer; Heinz	E04H15/008	52/2.24
*	C	US-20080264462-A1	10-2008	Rottmann; Andrew A.	E04H15/18	135/123
*	D	US-20080017233-A1	01-2008	Zeigler; Theodore R.	E04H15/50	135/145
*	E	US-20070125410-A1	06-2007	Williams; Marty L.	E04H15/36	135/136
*	F	US-20070039639-A1	02-2007	Duncan; David	E04H9/10	135/97
*	G	US-20060283103-A1	12-2006	Chen; Lian-Shun	E04H15/18	52/63
*	H	US-20050189009-A1	09-2005	Walter, Thomas A.	E04H15/32	135/97
*	I	US-10858856-B1	12-2020	Dusek; Jacob	E04H15/36	1/1
*	J	US-9869110-B2	01-2018	Krenzel; Ronald L.	E04H15/50	1/1
*	K	US-9752345-B1	09-2017	LaHood; John Matthew	E04H15/30	1/1
*	L	US-9714523-B2	07-2017	Lilly, II; Curtis G.	E04H15/64	1/1
*	M	US-9470010-B2	10-2016	Youn; Keong Woong	E04H15/18	1/1

FOREIGN PATENT DOCUMENTS						
*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N	CA-2837116-A1	11-2012	CA	ZEIGLER THEODORE R	E04H15/18
	O	DE-29716289-U1	10-1997	DE	MEHLER	E04H15/18
	P	DE-29517290-U1	12-1995	DE	UMAREX	E04H15/36
	Q	DE-29510827-U1	09-1995	DE	ROYALBEACH	E04H15/18
	R	FR-2705718-A1	12-1994	FR	ARNAULD THERY	E04H15/18
	S	FR-2997984-A1	05-2014	FR	LAFoux	E04H15/18
	T					

NON-PATENT DOCUMENTS		
*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
 Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

<i>Notice of References Cited</i>	Application/Control No. 16/861,012		Applicant(s)/Patent Under Reexamination Urhausen et al.	
	Examiner ROBERT CANFIELD		Art Unit 3636	Page 2 of 2

U.S. PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Name	CPC Classification	US Classification
*	A	US-9103137-B2	08-2015	Williams; Marty	E04H15/06	1/1
*	B	US-8381454-B1	02-2013	Robinson; Markus R.	E04H1/1211	52/79.5
*	C	US-D652885-S	01-2012	Frey; Pascal		D21/834
*	D	US-7533498-B2	05-2009	Zeigler; Theodore R.	E04B1/3205	135/128
*	E	US-6145525-A	11-2000	Mooney; David Allan	E04H5/02	135/119
*	F	US-5394897-A	03-1995	Ritchey; Michael T.	E04H15/18	135/117
*	G	US-5159948-A	11-1992	Moreau; Alain	E04H15/18	135/125
*	H	US-4886084-A	12-1989	Lawrence; George W.	E04H15/18	135/124
*	I	US-4649947-A	03-1987	Tury; Keith A.	E04H15/18	135/117
*	J	US-3955328-A	05-1976	Lindsay; Jeffrey	E04B1/34846	52/73
*	K	US-3559353-A	02-1971	Partridge	E04B1/3441	135/131
	L					
	M					

FOREIGN PATENT DOCUMENTS

*		Document Number Country Code-Number-Kind Code	Date MM-YYYY	Country	Name	CPC Classification
	N					
	O					
	P					
	Q					
	R					
	S					
	T					

NON-PATENT DOCUMENTS

*		Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages)
	U	
	V	
	W	
	X	

*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

<i>Search Notes</i> 	Application/Control No. 16/861,012	Applicant(s)/Patent Under Reexamination Urhausen et al.
	Examiner ROBERT CANFIELD	Art Unit 3636

CPC - Searched*		
Symbol	Date	Examiner
E04H15/18, 36, 44	01/01/2021	RC

CPC Combination Sets - Searched*		
Symbol	Date	Examiner

US Classification - Searched*			
Class	Subclass	Date	Examiner
135	97	01/01/2021	RC
52	79.9		

* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

Search Notes		
Search Notes	Date	Examiner
EAST classification/text/name/citation search - history attached	01/01/2021	RC
reviewed both parent file histories and checked for double patenting		

Interference Search			
US Class/CPC Symbol	US Subclass/CPC Group	Date	Examiner

/Robert Canfield/ Primary Examiner, Art Unit 3636	
--	--

①⑨ RÉPUBLIQUE FRANÇAISE
INSTITUT NATIONAL
DE LA PROPRIÉTÉ INDUSTRIELLE
PARIS

①① N° de publication :
(à n'utiliser que pour les
commandes de reproduction)

2 705 718

②① N° d'enregistrement national :

93 06616

⑤① Int Cl⁵ : E 04 H 15/18 , 15/36 , 15/54

⑫

DEMANDE DE BREVET D'INVENTION

A1

②② Date de dépôt : 27.05.93.

③③ Priorité :

④③ Date de la mise à disposition du public de la
demande : 02.12.94 Bulletin 94/48.

⑤⑥ Liste des documents cités dans le rapport de
recherche préliminaire : *Se reporter à la fin du
présent fascicule.*

⑥① Références à d'autres documents nationaux
apparentés :

⑦① Demandeur(s) : COMPAX (S.A.) — FR.

⑦② Inventeur(s) : Thery Amauld.

⑦③ Titulaire(s) :

⑦④ Mandataire : Cabinet Beau de Loménie.


⑤④ Installation à structure tubulaire en arceaux couverte par au moins une bâche à câbles et bâche à câbles correspondante.

⑤⑦ L'installation est constituée d'une structure en arceaux, recouverte au moins en toiture d'au moins une bâche à câbles.

Selon l'invention, la structure en arceaux est tubulaire et la bâche comporte un tissu enduit dont les bords opposés sont solidaires de câbles de mise sous tension.

La bâche à câbles pour la couverture d'une installation de l'invention avec structure tubulaire en arceaux comporte des câbles qui sont fixés le long d'au moins deux de ses bords opposés pour être jantés par dessus les arceaux.

De manière caractéristique, elle est réalisée dans un premier tissu (8) enduit double face; chaque câble (11) est logé coulissant dans un second tissu replié, formant manchon (10) de recouvrement de l'arceau (5), qui est fixé le long d'un bord (9) dudit premier tissu (8); le second tissu a une structure apte à absorber la déformation occasionnée par le jantage entre les deux bords du manchon (10).



FR 2 705 718 - A1



INSTALLATION A STRUCTURE TUBULAIRE EN ARCEAUX
COUVERTE PAR AU MOINS UNE BACHE A CABLES ET BACHE A
CABLES CORRESPONDANTE

La présente invention concerne une installation qui est constituée d'une
5 structure en arceaux recouverte , au moins en toiture , d'une bâche à
câbles, c'est-à-dire d'une bâche dont les bords opposés sont munis de
câbles destinés à réaliser la mise en tension de la bâche. Elle concerne
plus particulièrement une installation dont la structure en arceaux est
10 tubulaire, ainsi qu'une bâche à câbles spécialement conçue pour une telle
installation.

On connaît par le document FR.2.673.657 un hangar qui comporte
une ossature métallique qui est constituée d'arcs, reliés par des entretoises,
recouverts d'une bâche à câbles. Les arcs en question sont formés dans
des poutres en I cintrées , qui sont boulonnées au sol par l'intermédiaire de
15 platines soudées à leurs extrémités. Comme cela apparaît clairement à
l'examen de la figure 2 du document FR.2.673.657, la bâche est bordée le
long de chacun de ses bords frontaux par un ourlet qui est destiné au
passage du câble ; de plus les poutres en I sont cintrées dans le plan de
leur âme , la cavité formée par l'âme et les deux demi ailes constituant,
20 pour chacun des arcs d'extrémité , le logement d'un câble passé dans
chacun des ourlets. La mise en tension du câble entraîne à la fois la
tension de la bâche et son blocage dans le logement.

Selon le demandeur, l'installation précitée présente comme premier
inconvenient que , lors de sa mise en tension le long de la poutre en I, il se
25 produit un léger coulisement de la bâche selon l'arête de l'aile du I qui
forme le bord extérieur du logement. Un tel coulisement, notamment s'il est
amené à être répété, risque de couper ou de détériorer la bâche. Ceci
serait d'autant plus vrai dans le cas d'une bâche comportant, comme
élément de couverture , un tissu présentant une enduction en contact avec
30 l'arête. Il se produirait une dégradation de l'enduction au niveau de l'arête
génératrice de frottement.

Le but que s'est fixé le demandeur est de proposer une installation qui pallie l'inconvénient précité.

Ce but est parfaitement atteint par l'installation selon l'invention qui est constituée d'une structure en arceaux, recouverte au moins en toiture
5 au moins d'une bâche à câbles. De manière caractéristique la structure en arceaux est tubulaire et la bâche comporte un tissu enduit dont les bords opposés sont solidaires de câbles de mise sous tension.

Ainsi lors de la mise en tension des câbles, le contact entre la bâche et les arceaux s'effectue selon des arcs de cercle, sans arête ni
10 discontinuité comme c'est le cas lorsque l'arceau est une poutre en I. Il n'y a donc pas de risque de dégradation du fait d'un frottement selon une arête.

De préférence la structure en arceaux comporte des pieds qui sont arrimés au sol et les arceaux sont constitués de tubes creux cintrés qui sont emboîtés dans les pieds. Selon ce mode particulier de réalisation, une fois
15 que les pieds sont arrimés au sol, le montage de la structure en arceaux s'effectue par simple emboîtement des tubes creux sur les pieds. De plus la solidarisation de l'installation est obtenue uniquement grâce à la mise en tension des différents câbles. La tension mise en jeu est particulièrement importante.

20 S'agissant d'une bâche réalisée à partir d'un tissu enduit double face, compte-tenu des tensions exercées, il peut se produire un certain allongement de la bâche. Pour pallier cet inconvénient, de préférence le tissu enduit double face comporte des éléments longitudinaux de renfort consistant en des bandes qui sont rapportées sur le tissu enduit et qui sont
25 eux-mêmes réalisés dans un tissu technique à forte résistance et à faible allongement.

L'autre inconvénient de l'installation décrite dans le document FR.2.673.657 réside dans le fait que la bâche est tendue entre les deux arcs d'extrémité. Ceci est une limitation importante compte-tenu du poids
30 de la bâche. Les dimensions de l'installation devront tenir compte de cette contrainte ou bien se posent des difficultés pour le placement de la bâche

au-dessus de la structure métallique.

C'est un autre objet de l'invention que de proposer une installation qui pallie l'inconvénient précité. Cette installation est constituée d'une structure tubulaire en arceaux recouverte d'une bâche à câbles qui de manière caractéristique est constituée d'au moins deux modules 5 comprenant chacun le même nombre d'arceaux recouverts par une bâche modulaire, de longueur prédéterminée, tendue par dessus lesdits arceaux; d'autre part ladite installation comprend au moins une bâche à câbles de liaison, de faible longueur, tendue par dessus deux arceaux adjacents 10 rapprochés de chacun des modules.

La solution précitée de l'invention permet de réaliser des installations de grande longueur à partir de bâches modulaires. La bâche inter-modules de liaison permet de réaliser un jantage simple entre les modules comme cela apparaîtra plus clairement à la lecture de la 15 description qui sera faite ci-après. Pour un certain nombre d'utilisations, s'agissant d'une installation portable pour stockage ou pour réception, il peut être nécessaire que, en dehors de la couverture, l'installation soit fermée par des pignons.

C'est un autre objet de l'invention que de proposer une installation 20 ayant des pignons frontaux, comportant des bâches à câbles, tendues sur les arceaux tubulaires d'extrémités.

Selon une variante préférée, au moins un pignon frontal comporte:

- a) deux barres de traverse fixées entre les deux montants opposés d'un même arceau d'extrémité, la première traverse au niveau du sol et la 25 seconde à une hauteur déterminée,
- b) une première bâche à câbles en forme de segment circulaire dont le câble est fixé le long du bord en arc de cercle, des moyens de mise sous tension du câble de cette première bâche qui sont fixés à l'arceau au niveau de la seconde traverse et des moyens d'accrochage de ladite 30 première bâche à ladite seconde traverse, et
- c) au moins une seconde bâche à câbles ayant sensiblement la forme d'un

trapèze rectangle dont le côté oblique est en arc de cercle et muni d'un câble apte à être tendu le long de l'arceau entre la première et la deuxième traverses, et des moyens d'accrochage de ladite deuxième bâche à la première et à la deuxième traverses selon les deux côtés parallèles du

5 trapèze.

La partie du pignon frontal qui ne comprend pas les deux bâches précitées fait office d'ouverture de passage. Cette ouverture peut elle-même être fermée à l'aide d'une bâche à câbles du même type que la seconde bâche précitée et d'une porte formée dans une bâche et qui est montée

10 coulissante entre la première et la seconde traverses.

Pour faciliter le montage et le démontage des bâches et compléter la mise en tension obtenue grâce aux câbles, il peut être avantageux de disposer d'un système spécialement adapté de fixation. Selon l'invention, dans ce cas, la bâche à câbles comporte, le long d'un bord non câblé, un

15 ourlet ou manchon , apte à permettre l'introduction par coulissement d'une tige, et des encoches par lesquelles est accessible la tige introduite dans l'ourlet ou le manchon et l'installation comporte des éléments flexibles de fixation, chaque élément , par exemple lanière ou sangle, passant dans une encoche et enserrant à la fois ladite tige et une traverse fixée entre deux

20 arceaux.

Ceci peut être mis en oeuvre pour les bâches de pignon pour leur accrochage sur la première ou la seconde traverse précitée, ainsi que pour les bâches de toiture pour l'accrochage de leurs bords longitudinaux aux traverses fixées longitudinalement entre les arceaux.

Le demandeur a constaté que lorsque la bâche est réalisée à l'aide d'un tissu enduit double face, il se forme , lors de la mise en tension, des plis dans la bâche à proximité du câble et que ces plis provoquent à la longue des cassures préjudiciables. C'est un autre objet de la présente invention que de proposer une bâche à câbles qui pallie l'inconvénient

25

30 précité.

Ce but est parfaitement atteint grâce à la bâche à câble pour

couverture de structure tubulaire en arceaux, selon l'installation de l'invention. De manière connue cette bâche comporte des câbles qui sont fixés le long d'au moins deux bords opposés de la bâche pour être jantés par dessus les arceaux correspondants. De manière caractéristique la

5 bâche est réalisée dans un premier tissu enduit double face ; chaque câble est logé coulissant dans un second tissu replié , formant manchon de recouvrement de l'arceau, qui est fixé le long d'un bord dudit premier tissu; le second tissu a une structure apte à absorber la déformation occasionnée par le jantage entre les deux bords du manchon.

10 Dans la suite du présent texte on dénommera sous le terme jantage l'opération qui consiste à réaliser la mise en tension d'une bâche entre deux arceaux tubulaires, grâce à des dispositifs de tension qui sont fixés au sol et solidaires des extrémités libres du câble.

Cette mise en tension est réalisée alors que l'élément de couverture

15 est disposé au-dessus des différents montants de la structure tubulaire et que chacun des bords munis d'un câble enveloppe partiellement la surface supérieure et latérale d'un montant extrême de ladite structure tubulaire. Cette enveloppement doit être suffisant pour éviter que le câble ne puisse passer au-dessus du montant tubulaire et donc déjanter, par exemple en

20 cas de grand vent.

Ainsi , selon l'invention, les parties de la bâche, le long de chacun des bords opposés, qui sont déformées lors de la mise sous tension des câbles sont constituées par des manchons indépendants, à déformabilité améliorée , de manière à éviter le phénomène de cassure observé

25 précédemment.

S'agissant d'une structure tubulaire en arceaux dont la hauteur maximale est de l'ordre de 3 à 4 mètres, la déformation occasionnée par le jantage entre les deux bords du manchon est comprise entre 5 et 10%. Cette déformation correspond à l'écart de longueur existant entre les deux

30 bords du manchon du fait que chacun des bords se trouve à un niveau de hauteur différent par rapport à l'arceau correspondant.

Comme second tissu constitutif du manchon de recouvrement, il est possible d'utiliser un tissu enduit simple face. Le fait que l'enduction ne soit que sur l'une des faces et non sur les deux faces comme c'est le cas pour le premier tissu donne plus de souplesse au manchon, le tissu étant moins
5 bloqué par l'enduction.

De préférence, dans ce cas, la matière formant l'enduction du premier et du second tissus est la même et la face enduite du manchon est tournée vers l'intérieur de celui-ci, la fixation du manchon sur le premier tissu étant réalisée par soudage à l'aide de l'enduction.

10 Cette disposition particulière trouve son intérêt dans la simplicité de fabrication de la bâche à câbles.

Selon une version préférée de l'invention, la bâche à câbles est constituée avec un premier tissu en polyester enduit sur les deux faces de PVC, faisant de l'ordre de 500 à 650g/m² et constituée de fils de l'ordre
15 de 1100 dtex; le second tissu, constitutif du manchon, est un tissu polyester enduit sur une face de PVC, faisant de l'ordre de 650 à 750g/m² avec d'une part des fils de l'ordre de 1100 dtex et d'autre part des fils de l'ordre de 2200 dtex.

S'agissant d'un manchon de recouvrement dont la surface intérieure
20 comporte une enduction PVC, avantageusement le câble de mise sous tension est un câble qui ne comporte pas d'enduction PVC. En effet la demanderesse a constaté que si le câble était lui-même gainé de PVC il se produisait un accrochage entre le manchon et le câble empêchant un bon coulissement lors de l'introduction du câble dans le manchon et sa mise
25 sous tension. Par exemple le câble pourra être un câble d'acier, monotoron, recouvert d'une gaine de polyéthylène. Le glissement d'un tel câble, gainé polyéthylène, à l'intérieur du manchon enduit PVC est supérieur à celui qu'aurait un câble gainé PVC.

Une autre difficulté est apparue lors de la mise en oeuvre d'une
30 bâche à câbles constituée d'un tissu enduit double face, sans manchon indépendant de recouvrement. En effet lors du jantage, il se produit un

accrochage entre la surface enduite de la bâche et les arceaux de jantage. Cet accrochage peut occasionner des plis.

Avantageusement, pour pallier cet inconvénient, le pli du manchon qui est tourné vers l'arceau à recouvrir est un tissu dont la face extérieure
5 est non-enduite, ledit pli ayant une longueur telle que l'arceau n'est en contact qu'avec ladite face non-enduite.

La présente invention sera mieux comprise à la lecture de la description qui va être faite d'un mode préféré de réalisation d'une installation modulaire comportant une structure tubulaire en arceaux
10 recouverte par des bâches à câbles à manchon de recouvrement, illustré par le dessin annexé dans lequel :

La figure 1 est une vue partielle en coupe d'une bâche à câbles jantée sur un arceau,

La figure 2 est une vue schématique en perspective d'une installation
15 modulaire, et ,

La figure 3 est une vue en coupe d'une bâche de liaison, inter-modules, et une vue partielle des deux bâches modulaires correspondantes,

La figure 4 est une vue partielle de face d'un pignon, depuis l'intérieur de l'installation,

20 La figure 5 est une vue partielle d'un système d'accrochage d'une bâche.

L'installation 1 montrée à la figure 2 peut servir comme bâtiment d'élevage, de stockage, de réception. Elle est constituée d'une structure tubulaire recouverte de bâche à câbles. Plus particulièrement la structure tubulaire de cette installation 1 comporte deux modules identiques 2 et 3
25 reliés par une bâche de liaison 4.

Dans chaque module les montants tubulaires en arceaux 5 sont emboîtés à leurs deux extrémités dans des pieds qui sont arrimés dans le sol et sont recouverts d'une bâche à câbles 6 ayant une longueur prédéterminée L.

30 Dans un exemple concret de réalisation, mais non limitatif, chaque module 2,3 comportait quatre arceaux 5 régulièrement disposés et fixés au

sol. Sur les quatre arceaux était tendue une bâche à câbles 6 ayant une longueur L de 5mètres. On désigne dans le présent texte comme étant la longueur L la distance séparant les deux arceaux extrêmes 5 d'un même module, dans le sens longitudinal de l'installation 1. La largeur au sol de
5 l'installation 1, prise entre les pieds de chaque arceau, était de 8,50mètres.

Les deux modules 2,3 de l'installation 1 sont disposés dans le prolongement l'un de l'autre, de sorte que deux arceaux extrêmes, respectivement 5a pour le premier arceau du premier module 2 et 5b pour le premier arceau du second module 3 sont espacés d'une distance d, qui
10 est de l'ordre de quelques dizaines de centimètres. Les deux modules 2,3 sont reliés entre eux par une bâche à câbles 7 de liaison inter-modules. Sur la figure 1 on a représenté partiellement une bâche à câbles 6 selon l'invention, jantée sur un arceau 5.

La bâche à câbles 6 est constituée d'un tissu enduit double face 8
15 qui est l'élément principal de couverture. Ce tissu enduit double face 8 est muni, le long de chacun des deux bords 9 selon lesquels va être réalisé le jantage, d'un manchon 10 destiné à servir de logement au câble 11.

Le manchon 10 est réalisé à partir d'un tissu qui est replié en deux plis 12,13 dont les extrémités libres 12', 13' sont fixées au bord 9 du tissu
20 enduit double face 8.

De préférence le tissu constitutif du manchon 10 est un tissu enduit sur une face, l'enduction étant réalisée dans la même matière que celle du tissu enduit double face 8. La fixation des extrémités libres 12' et 13' sur le bord 9 est réalisée par soudage. Ceci peut être fait soit par compression
25 à chaud soit par compression combinée avec l'action de hautes fréquences. On comprend que la face enduite du tissu constitutif du manchon 10 est la face qui est tournée vers l'intérieur du manchon.

Dans un exemple précis de réalisation, mais non limitativement, le tissu enduit double face 8 était une toile de polyester, réalisée à partir de
30 fils de 1100dtex. Cette toile était enduite double face avec une enduction PVC (polychlorure de vinyle). Son poids au mètre carré était de 575 g, avec

une résistance à la rupture comprise entre 250 et 270daN pour une éprouvette de 5cm de large. Le tissu enduit simple face, constitutif du manchon 10 était une toile polyester réalisée à partir de fils de 1100dtx et de fils de 2200dtx. Cette toile était enduite de PVC. Son poids au
5 mètre carré était de 700g avec une résistance à la rupture de 400 à 420daN pour une éprouvette de 5cm de large.

Comme on peut le remarquer sur la figure 1, la longueur de chacun des deux plis 12,13, ainsi que la zone de fixation de l'extrémité 13' sur la toile enduite double face 8 sont telles que l'arceau 5, après jantage, est en
10 contact uniquement avec le manchon 10. Etant donné que la face 13a du pli 13 du manchon 10 qui est en contact avec l'arceau 5 est une face non enduite, on obtient un glissement optimal du manchon sur l'arceau 5 lors du positionnement de la bâche 6 et de la mise en tension du câble 11 lors de l'opération de jantage.

15 Du fait de l'existence du manchon 10 et du choix de sa structure, on ne remarque aucun pli ni cassure préjudiciable malgré la déformation qui est due à la différence de longueur existant sur le manchon d'une part au niveau du bord 9 et d'autre part au niveau du câble 11, du fait de la courbure de l'arceau 5.

20 Cette déformation peut être comprise entre 5 et 10%, dans l'exemple précité.

Sur la figure 3 on a représenté les deux arceaux extrêmes 5a et 5b sur lesquels sont jantées d'une part la bâche de liaison 7 et d'autre part les deux bâches 6a pour le premier module et 6b pour le second module.

25 On dispose d'abord sur les deux arceaux 5a et 5b la bâche de liaison 7, dans un état relativement détendu. Pour ce faire les deux câbles 14 et 15 de ladite bâche de liaison 7 sont fixés au sol à l'aide d'un dispositif de fixation et de tension, à vis, non représenté, mais sans que soit exercée une tension importante.

30 La bâche de liaison 7 a la même structure que les deux bâches modulaires 6a et 6b. Elle ne diffère que par la longueur réduite de la toile

16 enduite double face. Ses deux bords opposés 17,18 sont eux aussi fixés à deux manchons 19 et 20, à l'intérieur desquels coulissent les deux câbles 14 et 15.

Une fois que la bâche de liaison 7 a été disposée par dessus les
5 deux arceaux 5a et 5b, les manchons 19 et 20 recouvrant partiellement chacun des arceaux 5a et 5b, et la toile enduite double face 16 étant à l'état relativement détendu, on peut placer une première bâche modulaire 6a pour que celle-ci soit jantée sur le premier arceau 5a. Pour ce faire il suffit de disposer le manchon 10a par dessus la toile enduite double face 16
10 recouvrant l'arceau 5a jusqu'à ce que le câble 11a vienne en position de jantage, comme cela est représenté à la figure 3. Cette opération réalisée, il suffit de faire de même pour la seconde bâche modulaire 6b, jusqu'à jantage de celle-ci sur l'arceau 5b.

Le positionnement optimum est montré à la figure 3, selon lequel
15 les deux bâches modulaires 6a et 6b sont parfaitement jantées respectivement sur les arceaux 5a et 5b et la toile enduite double face 16 de la bâche de liaison 7 est tendue entre les deux câbles 11a et 11b.

On obtient une parfaite étanchéité au niveau de cette liaison intermodulaire, qui de plus fait office de gouttière d'évacuation des eaux de
20 pluie.

Cette présentation en modules permet d'éviter la confection de bâches de grande dimension qui non seulement est très coûteuse mais également très lourde à poser, ce qui pourrait limiter la longueur des installations.

25 De préférence chaque bâche comporte des éléments de renfort 21, représentés schématiquement sur la figure 2, qui sont destinés à bloquer dimensionnellement la toile enduite double face qui constitue la bâche à proprement parler. Ces éléments de renfort sont situés longitudinalement par rapport à l'installation. Il s'agit par exemple d'un tissu technique de
30 haute résistance mécanique et de faible allongement et qui est rapporté, de manière à lui être solidaire, sur le tissu enduit. En particulier le tissu

technique servant de renfort longitudinal est réalisé à partir du tissu enduit simple face, constitutif du manchon de recouvrement. L'application de cette bande de renfort 21 sur le tissu enduit double face peut être obtenue par thermosoudage, la face enduite de la bande de renfort 21 étant en contact
5 avec le tissu enduit double face constituant la bâche.

La fermeture de l'installation, à chacune de ses extrémités peut être obtenue à l'aide de pignons 22, dont une représentation schématique montrée à la figure 4.

Ce pignon 22 est constituée , dans l'exemple ainsi illustré, de trois
10 bâches à câbles 23,24,25 et de deux barres de traverse 26,27.

La première barre de traverse 26 est fixée, au niveau du sol, entre les parties basses 28,29 des deux montants opposés du même arceau 30 d'extrémité, correspondant audit pignon 22. La seconde barre de traverse 27 est fixée également entre les deux montants opposés de l'arceau 30
15 mais à une hauteur H, suffisante pour permettre le passage d'une personne et éventuellement des produits à stocker à l'intérieur de l'installation.

La première bâche à câbles 23 est destinée à être jantée sur la partie supérieure de l'arceau 30 et fixée à la seconde traverse 27. Pour cela des moyens de mise sous tension 31 sont fixés à l'arceau 30 au
20 niveau de la seconde traverse. De plus des moyens d'accrochage 32 sont prévus pour solidariser cette première bâche 23 de pignon avec la seconde traverse 27.

On comprend que cette première bâche 23 de pignon a la forme d'un segment circulaire avec le câble qui est fixé le long du bord en arc de
25 cercle du segment. Selon un mode de réalisation, le bord 33 correspondant à la corde du segment circulaire est pourvu soit d'un ourlet soit d'un manchon rapporté 38, permettant l'introduction par coulissement d'une tige 39, par exemple d'un jonc composite. De plus , de manière espacée, ladite bâche 23 comporte, de manière espacée et à proximité dudit bord 33 , des
30 encoches 40 par lesquelles est accessible la tige 39 introduite dans l'ourlet ou le manchon 38. Ainsi les moyens d'accrochage consistent dans

des lanières 41 qui sont placées au niveau des encoches 40 à la fois autour de la seconde barre de traverse 27 et de la tige 39.

Les deuxième et troisième bâches de pignon 24,25 ont la même structure, étant symétriques par rapport au plan longitudinal de l'installation.

5 Chacune de ces deux bâches 24,25 a une forme qui est sensiblement celle d'un trapèze rectangle. Comme cela apparaît sur la figure 4, les deux côtés parallèles 34,35 sont destinés à être fixés respectivement sur la seconde et la première barres de traverse 27,26 ; le côté 36, perpendiculaire aux deux premiers 34,35, a une hauteur H ; le
10 quatrième côté 37, oblique, a en réalité une forme courbe, étant destiné à être janté sur la portion de l'arceau 30 entre la première et la seconde traverses 26,27. Pour cela la bâche à câbles 24 est munie d'un câble, le long du quatrième bord 37 ; de plus l'installation comporte des moyens de mise sous tension dudit câble, situés au niveau de la première et de la
15 seconde traverses. Enfin il est prévu des moyens d'accrochage permettant de solidariser l'adite seconde bâche 24 avec les deux barres de traverse 26,27. Ces moyens d'accrochage peuvent être identiques à ceux prévus pour la première bâche 23.

Dans l'exemple illustré à la figure 4, la seconde et la troisième
20 bâche de pignon 24,25 délimitent, avec la première bâche 23, un espace 38, faisant office de porte de passage. Cet espace 38 peut lui-même être fermé à l'aide d'une quatrième bâche , non représentée, par exemple montée coulissante par des moyens appropriés entre la première et la seconde barres de traverse 26,27.

25 Comme on peut le comprendre, si l'on veut une meilleure tenue des deuxième et troisième bâches 24,25, il est possible de disposer entre la première et la seconde barres de traverse 26,27 des montants verticaux sur lesquels pourront être accrochées les bâches latérales 24,25 grâce aux moyens d'accrochage précités.

30 Le mode de réalisation, décrit ci-dessus, des moyens d'accrochage n'est pas limité au pignon. La mise en tension d'une bâche de toiture peut

être avantageusement complétée grâce à un système similaire. Dans ce cas chaque bord longitudinal 42 de ladite bâche comporte d'une part un ourlet ou un manchon rapporté 43, dans lequel est introduit par coulisement une tige 44, par exemple un jonc en matériau composite et

5 d'autre part, de manière espacée, des encoches 45 par lesquelles est accessible ladite tige 44. L'accrochage de la bâche et sa mise en tension sont obtenus grâce à une sangle 46 passant dans l'encoche 45 et enserrant à la fois la tige 44 et une traverse longitudinale 48 disposée entre les pieds

10 de deux arceaux successifs, quasiment au ras du sol, avec un espace suffisant pour le passage de ladite sangle. Cette disposition rend particulièrement aisés le montage et le démontage des bâches.

REVENDICATIONS

1. Installation constituée d'une structure en arceaux, recouverte au moins en toiture d'au moins une bâche à câbles, caractérisée en ce que la structure en arceaux est tubulaire et en ce que la bâche comporte un tissu
5 enduit dont les bords opposés sont solidaires de câbles de mise sous tension.
2. Installation selon la revendication 1 caractérisée en ce que la structure en arceaux comporte des pieds qui sont arrimés au sol et les arceaux sont constitués de tubes creux cintrés qui sont emboîtés dans les pieds.
- 10 3. Installation selon la revendication 1 ou la revendication 2 ,caractérisée en ce que la bâche est réalisée à partir d'un tissu enduit double face et comporte des éléments longitudinaux de renfort consistant en des bandes (21) qui sont rapprochées sur le tissu enduit et qui sont eux-mêmes réalisés dans un tissu technique à forte résistance et à faible allongement.
- 15 4. Installation selon les revendications 1 à 3 caractérisée en ce qu'elle est constituée d'au moins deux modules (2,3) comprenant chacun le même nombre d'arceaux (5) recouverts par une bâche modulaire, de longueur prédéterminée , tendue par dessus lesdits arceaux et en ce qu'elle comprend au moins une bâche à câbles de liaison (4), de faible longueur,
20 tendue par dessus deux arceaux adjacents (5a, 5b) rapprochés de chacun des modules (2,3).
5. Installation selon les revendications 1 à 4 caractérisée en ce qu'elle comporte des pignons frontaux , comportant des bâches à câbles, tendues sur les arceaux tubulaires d'extrémités.
- 25 6. Installation selon la revendication 5 caractérisée en ce qu'au moins un pignon frontal comporte :
 - a) deux barres de traverse (26,27) fixées entre les deux montants opposés d'un même arceau (30) d'extrémité, la première (26) traverse au niveau du sol et la seconde (27) à une hauteur déterminée (H),
 - 30 b) une première bâche à câbles (23) en forme de segment circulaire dont le câble est fixé le long du bord en arc de cercle , des moyens (31) de mise

- sous tension du câble de cette première bâche (23) qui sont fixés à l'arceau (30) au niveau de la seconde traverse (27) et des moyens d'accrochage (33) de ladite première bâche (23) à ladite seconde traverse, et
- c) au moins une seconde bâche à câbles (24,25) ayant sensiblement la
- 5 forme d'un trapèze rectangle dont le côté oblique (37) est en arc de cercle et muni d'un câble apte à être tendu le long de l'arceau (30) entre la première (26) et la deuxième (27) traverses, et des moyens d'accrochage de ladite deuxième bâche à la première et à la deuxième traverses selon les deux côtés (34,35) parallèles du trapèze.
- 10 7. Installation selon l'une des revendications 1 ou 6 caractérisée en ce que la bâche à câble (6,23) comporte, le long d'un bord non câblé (33,42), un ourlet ou manchon (38,43), apte à permettre l'introduction par coulisement d'une tige (39,44) et des encoches (40,45) par lesquelles est accessible la tige (39,44) introduite dans l'ourlet ou le manchon (38,43) et en ce qu'elle
- 15 comporte des éléments flexibles (41,46) de fixation, chaque élément passant dans une encoche (40,45) et enserrant à la fois ladite tige (39,44) et une traverse (27,48) fixée entre deux arceaux.
8. Bâche à câbles pour couverture d'installation avec structure tubulaire en arceaux selon l'une des revendications 1 à 7, comportant des câbles qui
- 20 sont fixés le long d'au moins deux de ses bords opposés pour être jantés par dessus les arceaux caractérisée en ce qu'elle est réalisée dans un premier tissu (8) enduit double face, en ce que chaque câble (11) est logé coulissant dans un second tissu replié, formant manchon (10) de recouvrement de l'arceau (5), qui est fixé le long d'un bord (9) dudit
- 25 premier tissu (8), et en ce que le second tissu a une structure apte à absorber la déformation occasionnée par le jantage entre les deux bords du manchon (10).
9. Bâche à câbles selon la revendication 8 caractérisée en ce que le second tissu a une structure apte à absorber une déformation comprise
- 30 entre 5 et 10%.
10. Bâche à câbles selon l'une des revendications 8 ou 9 caractérisée en

ce que le second tissu constitutif du manchon (10) de recouvrement est un tissu enduit simple face.

11. Bâche à câbles selon la revendication 10 caractérisée en ce que la matière formant l'enduction du premier et du second tissus est la même et
5 la face enduite du manchon (10) est tournée vers l'intérieur de celui-ci, la fixation du manchon sur le premier tissu étant réalisée par soudage à l'aide de l'enduction.

12. Bâche à câbles selon la revendication 11 caractérisée en ce qu'elle est constituée d'un premier tissu en polyester enduit sur les deux faces de
10 PVC, faisant de l'ordre de 500 à 650g/m² et constituée de fils de l'ordre de 1100 dtex ; d'un second tissu, pour manchon (10), en polyester enduit sur une face de PVC, faisant de l'ordre de 650 à 750g/m² avec d'une part des fils de l'ordre de 1100 dtex et d'autre part des fils de l'ordre de 2200dtex.

13. Bâche à câbles selon l'une des revendications 11 ou 12 caractérisée en ce que le câble (10) de mise sous tension est un câble qui ne comporte pas d'enduction PVC.

14. Bâche à câbles selon la revendication 13 caractérisée en ce que le câble est un câble d'acier , monotoron, recouvert d'une gaine de
20 polyéthylène.

15. Bâche à câbles selon les revendications 8 à 14 caractérisée en ce que le pli du manchon qui est tourné vers l'arceau (5) à recouvrir est un tissu dont la face extérieure (13a) est non-enduite, ledit pli ayant une longueur telle que l'arceau n'est en contact qu'avec ladite face non-enduite,
25 après jantage.

FIG. 3




FIG. 4





FIG. 5



DOCUMENTS CONSIDERES COMME PERTINENTS		Revendications concernées de la demande examinée
Catégorie	Citation du document avec indication, en cas de besoin, des parties pertinentes	
A	FR-A-2 643 934 (BERANGER FENOUILLET) * abrégé; figure 1 * ----	1,2
A	EP-A-0 267 590 (THEIS) * abrégé; figure 2 * ----	1
A	EP-A-0 056 561 (SCHMID) * abrégé; figures 1-3 * ----	1,4,5
A	DE-A-23 45 220 (FA. FILCLAIR) * le document en entier * ----	1,4
A	DE-A-29 03 169 (LANG) * revendication 1; figures 1-5 * ----	1
A,D	FR-A-2 673 657 (PETIARD) ----	
A	US-A-2 856 941 (O'NEAL) -----	
		DOMAINES TECHNIQUES RECHERCHES (Int.Cl.5)
		E04H
Date d'achèvement de la recherche		Examineur
11 Mai 1994		Clasing, M
CATEGORIE DES DOCUMENTS CITES X : particulièrement pertinent à lui seul Y : particulièrement pertinent en combinaison avec un autre document de la même catégorie A : pertinent à l'encontre d'au moins une revendication ou arrière-plan technologique général O : divulgation non-écrite P : document intercalaire T : théorie ou principe à la base de l'invention E : document de brevet bénéficiant d'une date antérieure à la date de dépôt et qui n'a été publié qu'à cette date de dépôt ou qu'à une date postérieure. D : cité dans la demande L : cité pour d'autres raisons & : membre de la même famille, document correspondant		

1

EPO FORM 1503 03.82 (P04C13)

PUB-NO: FR002705718A1
DOCUMENT- FR 2705718 A1
IDENTIFIER:
TITLE: Installation having an arched tubular structure
covered with at least one tarpaulin with
incorporated cables and corresponding tarpaulin
with incorporated cables
PUBN-DATE: December 2, 1994
PATENT- 9447694
FAMILY-ID:

INVENTOR-INFORMATION:
NAME COUNTRY
ARNAULD THERY

APPLICANT:
NAME COUNTRY
COMPAX SA FR

APPL-NO: FR 9306616 A
APPL-DATE: May 27, 1993

PRIORITY-DATA:
PRIORITY-NO PRIORITY-APPL-DATE
FR 9306616 A 19930527

CPC-CURRENT:
TYPE CPC DATE
CPCI E04H15/18 20130101
CPCI E04H15/36 20130101

INT-CL-CURRENT:
TYPE IPC DATE
IPCP E04H15/18 20060101
IPCS E04H15/36 20060101

REF-CITED:

PHASE-COUNTRY/NUMBER/KIND/DATE-NPL-INFO

SER US 2856941 A 19581021
SER FR 2673657 A1 19920911
SER DE 2903169 A1 19800731
SER DE 2345220 A1 19740328
SER EP 0056561 A1 19820728
SER EP 0267590 A1 19880518
SER FR 2643934 A1 19900907

ABSTRACT:

The invention consists of an arched structure covered, at least as regards the roofing, with at least one tarpaulin with incorporated cables. According to the invention, the arched structure is tubular and the tarpaulin comprises a coated fabric whose opposite edges are fastened to tensioning cables. The tarpaulin with incorporated cables, for covering an installation of the invention with an arched tubular structure comprises cables which are fixed along at least two of its opposite edges in order to be rimmed over the top of the arches. Characteristically, the tarpaulin is made from a first fabric (8) coated on both sides; each cable (11) is housed so as to be able to slide in a second, folded-over fabric that forms a sleeve (10) for covering the arch (5) and is fixed along an edge (9) of the said first fabric (8); the second fabric has a structure suitable for absorbing the deformation arising from the rimming between the two edges of the sleeve (10).

①⑨ RÉPUBLIQUE FRANÇAISE
INSTITUT NATIONAL
DE LA PROPRIÉTÉ INDUSTRIELLE
PARIS

①⑪ N° de publication :
(à n'utiliser que pour les
commandes de reproduction)

2 997 984

①⑫ N° d'enregistrement national : **12 60857**

⑤① Int Cl⁸ : **E 04 H 15/18 (2013.01)**

①⑫ **DEMANDE DE BREVET D'INVENTION**

A1

②② Date de dépôt : 15.11.12.

③⑦ Priorité :

⑦① Demandeur(s) : DECATHLON Société anonyme —
FR.

④③ Date de mise à la disposition du public de la
demande : 16.05.14 Bulletin 14/20.

⑤⑥ Liste des documents cités dans le rapport de
recherche préliminaire : *Se reporter à la fin du
présent fascicule*

⑥⑦ Références à d'autres documents nationaux
apparentés :

⑦② Inventeur(s) : LAFOUX BENJAMIN et SIMON BEN-
JAMIN.

⑦③ Titulaire(s) : DECATHLON Société anonyme.


⑦④ Mandataire(s) : CABINET BEAU DE LOMENIE
Société civile.

⑤④ **SYSTEME DE TENTE MODULAIRE.**

⑤⑦ L'invention porte sur un système de tente modulaire
comprenant un module de tente central (100) qui comporte :

○ une toile de tente (104) dans laquelle est ménagée au
moins une ouverture (106a, 106b), ladite ouverture étant
munie d'un premier moyen de fixation (112a, 112b) et
s'étendant dans une première surface (P1) inclinée par rap-
port à un plan vertical;

○ au moins une casquette (116, 118) s'étendant autour
de l'ouverture (106a, 106b) tout en faisant saillie depuis la
toile de tente vers l'extérieur du module de tente central, la
casquette présentant un bord périphérique (116c) muni d'un
deuxième moyen de fixation (120) et s'étendant dans une
seconde surface (P2) inclinée par rapport au plan vertical (V1),
la seconde surface présentant, par rapport au plan
vertical, une inclinaison opposée à celle de la première sur-
face.



FR 2 997 984 - A1



Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Arrière-plan de l'invention

La présente invention porte sur le domaine des tentes. Il concerne plus particulièrement les tentes modulaires, à savoir les tentes constituées de modules qui peuvent être assemblés les uns aux autres selon les besoins de l'utilisateur.

Un tel système modulaire est notamment décrit dans le document US 6 273 114. Il comporte un module de tente central 4 et une pluralité de modules de tente complémentaires 6 fixés au module de tente central 4.

Le module de tente central abrite une pièce de vie principale, tandis que les modules de tente complémentaires forment des chambres annexes.

Dans cet art antérieur, les modules de tente complémentaire sont identiques et, de surcroît, ils sont conformés pour être fixés uniquement sur deux faces latérales opposées du module de tente central.

En d'autres termes, le système modulaire de l'art antérieur, ne propose qu'une seule configuration.

Objet et résumé de l'invention

Un but de la présente invention est de proposer un système de tente modulaire qui présente une plus grande modularité en permettant davantage de combinaisons ou de configurations d'assemblage.

A cet effet, l'invention porte tout d'abord sur un module de tente central comportant :

- une toile de tente dans laquelle est ménagée au moins une ouverture, ladite première ouverture étant munie d'un premier moyen de fixation et s'étendant dans une première surface inclinée par rapport à un plan vertical ;
- au moins une casquette s'étendant autour de la première ouverture tout en faisant saillie depuis la toile de tente vers l'extérieur du module de tente central, la casquette présentant un bord périphérique muni d'un deuxième moyen de fixation et s'étendant dans une seconde surface inclinée par rapport au plan vertical, la seconde surface présentant, par rapport au plan vertical, une inclinaison opposée à celle de la première surface.

Par casquette, on entend une extension, rigide ou souple, faisant saillie depuis la toile de tente vers l'extérieur de manière à former un auvent.

5 Le premier moyen de fixation s'étend préférentiellement selon une première courbe en forme d'arche qui s'étend dans la première surface inclinée. De même, le deuxième moyen de fixation s'étend préférentiellement selon une deuxième courbe en forme d'arche qui s'étend dans la deuxième surface inclinée. De préférence, les première et deuxième surfaces inclinées sont planes ou légèrement incurvées.

10 De préférence, la première surface est inclinée de sorte qu'elle s'étend depuis la base vers le sommet du module de tente central. La seconde surface est quant à elle inclinée de manière opposée de sorte qu'elle s'étend de la base vers une direction opposée au sommet du module de tente central.

15 Le module de tente central selon l'invention est configuré pour être attaché à différents types de modules de tente complémentaires qui peuvent être reliés par l'intermédiaire du premier moyen de fixation, ou du deuxième moyen de fixation.

20 De préférence, le module de tente central comporte plusieurs ouvertures munies de premiers moyens de fixation, et, encore de préférence, il est prévu une ouverture dans chacune des faces latérales du module de tente central. Ainsi, lorsque le module de tente central présente une base rectangulaire et quatre pans de toile définissant quatre faces latérales, le module de tente central peut être pourvu de quatre
25 ouvertures, grâce à quoi il est possible d'y connecter directement jusqu'à quatre modules de tente complémentaires.

Encore de préférence, chaque ouverture est munie d'une casquette faisant saillie depuis la toile de tente et ayant un deuxième moyen de fixation. Un intérêt est de pouvoir monter des modules de tente
30 complémentaires de types différents au module de tente central. On comprend en effet que certains modules de tente complémentaires ont des moyens de fixation compatibles avec le ou les premiers moyens de fixation de ou des ouvertures, tandis que d'autres modules de tente complémentaires ont des moyens de fixation compatibles avec le ou les
35 deuxièmes moyens de fixation de la ou des casquettes.

En outre, comme il sera décrit plus en détail ci-après, les modules de tente complémentaires peuvent être assemblés entre eux, grâce à quoi l'invention permet de concevoir des systèmes modulaires variés.

5 De façon avantageuse, le module de tente central comporte en outre un pan de porte dont le pourtour comprend un organe de fixation arrangé pour coopérer avec le premier moyen de fixation de l'ouverture ou bien avec le deuxième moyen de fixation. Ce pan de porte est avantageusement utilisé pour obturer l'ouverture, notamment lorsque cette dernière n'est pas reliée à un module de tente complémentaire.

10 De manière avantageuse, les premier et deuxième moyens de fixation présentent la même longueur.

En conséquence, les moyens de fixation des modules de tente complémentaires présentent également la même longueur. Un intérêt, qui sera développé plus en détail ci-après, est notamment de pouvoir fixer
15 ensemble deux modules de tente complémentaires afin de constituer des unités autonomes et autoportées.

Selon une variante, les premier et deuxième moyens de fixation sont des fermetures à glissières. Ces fermetures à glissières s'étendent le long des première et deuxième boucles précitées.

20 Selon une autre variante, les premier et deuxième moyens de fixation sont constitués de boucles de fixation. Ces boucles de fixation s'étendent également le long des première et deuxième boucles précitées.

Selon un mode de réalisation avantageux, les première et seconde surfaces sont sensiblement symétriques par rapport au plan vertical.

25 De préférence, l'angle entre le plan vertical et l'une ou l'autre des première et seconde surfaces est compris entre 10° et 40°.

De manière préférentielle, le bord périphérique de la casquette comporte en outre un rabat d'étanchéité recouvrant le deuxième moyen de fixation de la casquette. Ce rabat d'étanchéité permet d'assurer
30 l'étanchéité, en cas de pluie, de la jonction entre le module de tente central et le module de tente complémentaire fixé au deuxième moyen de fixation.

On comprend par ailleurs que la casquette, qui s'étend autour de l'ouverture et donc autour du premier moyen de fixation, permet quant à
35 elle d'assurer l'étanchéité de la jonction entre le module de tente central et le module de tente complémentaire fixé au premier moyen de fixation.

La présente invention porte en outre sur un abri modulaire qui comporte un module de tente central selon l'invention et au moins un module de tente complémentaire configuré pour être attaché au module de tente central et/ou à un autre module de tente complémentaire.

5 Ledit au moins un module de tente complémentaire est configuré pour être attaché au module de tente central par l'intermédiaire du premier moyen de fixation ou du deuxième moyen de fixation.

De préférence, l'abri modulaire comporte plusieurs types de modules de tente complémentaires, certains pouvant être attachés au
10 module de tente central par l'intermédiaire du premier moyen de fixation, alors que d'autres peuvent être attachés au module de tente central par l'intermédiaire du deuxième moyen de fixation.

Le moyen de fixation d'un module de tente complémentaire est donc configuré pour être attaché à l'un ou l'autre des premier et deuxième
15 moyens de fixation du module de tente central. Par conséquent, le moyen de fixation du module de tente complémentaire qui est configuré pour être attaché avec le premier moyen de fixation du module de tente central pourra être attaché à un autre module de tente complémentaire par l'intermédiaire du moyen de fixation du module de tente complémentaire
20 qui est configuré pour être attaché avec le deuxième de moyen de fixation du module de tente central. Il est ainsi possible, de manière particulièrement avantageuse, d'attacher ensemble deux modules de tente complémentaires.

Selon un premier mode de réalisation, l'abri modulaire comporte au
25 moins un module de tente complémentaire d'un premier type configuré pour être attaché au module de tente central ou à un module de tente complémentaire d'un autre type ; le module de tente complémentaire du premier type comporte une face d'entrée présentant un contour périphérique muni d'un dispositif de fixation, le contour périphérique
30 s'étendant dans une surface qui est inclinée par rapport à un plan vertical ; la surface dans laquelle s'étend le contour périphérique du module de tente complémentaire du premier type présente la même inclinaison que la seconde surface dans laquelle s'étend le bord périphérique de la casquette du module de tente central, et lorsque le
35 module de tente complémentaire du premier type est attaché au module de tente central, le dispositif de fixation du module de tente

complémentaire du premier type est assemblé au deuxième moyen de fixation du module de tente central.

On entend par face d'entrée la face du module de tente complémentaire du premier type par laquelle l'utilisateur entre dans ledit module.

Ce module de tente complémentaire du premier type présente de préférence, mais pas nécessairement, une chambre intérieure munie d'une entrée débouchant dans la face d'entrée.

De manière avantageuse, le dispositif de fixation du module de tente complémentaire du premier type est de même longueur que le deuxième moyen de fixation du module de tente central.

De préférence, le dispositif de fixation du module de tente complémentaire du premier type et le deuxième moyen de fixation du module de tente central sont des fermetures à glissières.

Selon une variante, le dispositif de fixation du module de tente complémentaire du premier type et le deuxième moyen de fixation du module de tente central sont constitués de boucles d'attaches. Ces boucles sont par exemples constituées d'éléments mâles venant s'emboîter avec des éléments femelles. D'autres types de fixation pourront être envisagés.

Avantageusement, le module de tente complémentaire du premier type comporte un boudin formant arceau qui entoure la face d'entrée, le dispositif de fixation étant disposé au-dessus du boudin. De préférence, il s'agit d'un boudin gonflable. Ce boudin permet de donner la forme d'arceau ou d'arche à la face d'entrée. Il permet également de rigidifier la jonction entre la casquette et le module de tente complémentaire du premier type.

Selon un deuxième mode de réalisation, l'abri modulaire selon l'invention comporte au moins un module de tente complémentaire d'un deuxième type, différent du premier type, configuré pour être attaché au module de tente central ou à un module de tente complémentaire d'un autre type ; le module de tente complémentaire du deuxième type comporte une face d'entrée présentant un contour périphérique muni d'un dispositif de fixation, le contour périphérique s'étendant dans une surface qui présente la même inclinaison que la première surface dans laquelle s'étend le premier moyen de fixation du module de tente central, et

lorsque le module de tente complémentaire du deuxième type est attaché au module de tente central, le dispositif de fixation est assemblé au premier moyen de fixation, et le contour périphérique vient se loger en dessous de la casquette.

5 Sans sortir du cadre de la présente invention, l'abri modulaire peut comprendre à la fois au moins un module de tente complémentaire du premier type et au moins un module de tente complémentaire du deuxième type.

Par ailleurs, le module de tente complémentaire du premier type
10 peut être attaché au module de tente complémentaire du deuxième type. Pour ce faire, on assemble le dispositif de fixation du module de tente complémentaire du premier type avec le dispositif de fixation du module de tente complémentaire du deuxième type. Cela permet de former une unité indépendante du module de tente central. Le cas échéant, le module
15 de tente complémentaire du premier type et/ou le module de tente complémentaire du deuxième type pourront comprendre une porte d'entrée afin d'accéder à cette unité autonome.

Avantageusement, le dispositif de fixation du module de tente complémentaire du deuxième type est de même longueur que le premier
20 moyen de fixation du module de tente central.

De préférence, le dispositif de fixation du module de tente complémentaire du deuxième type et le premier moyen de fixation du module de tente central sont des fermetures à glissières.

Selon une variante, le dispositif de fixation du module de tente
25 complémentaire du deuxième type et le premier moyen de fixation du module de tente central sont constitués de boucles d'attaches, de préférence du même type que celles décrites plus haut.

Là-encore, on entend par face d'entrée la face du module de tente complémentaire du deuxième type par laquelle l'utilisateur entre dans ledit
30 module.

Ce module de tente complémentaire du deuxième type présente de préférence, mais pas nécessairement, une chambre intérieure munie d'une entrée débouchant dans la face d'entrée.

Selon un troisième mode de réalisation, l'abri modulaire comporte
35 au moins un module de tente complémentaire d'un troisième type, distinct des modules de tente complémentaires des premier et deuxième types,

configuré pour être attaché au module de tente central et/ou à un module de tente complémentaire d'un autre type ; le module de tente complémentaire du troisième type comporte une première face d'entrée présentant un premier contour périphérique muni d'un premier dispositif de fixation, le premier contour périphérique s'étendant dans une troisième surface inclinée par rapport à un plan vertical et qui présente la même inclinaison que la première surface du module de tente central ; le premier dispositif de fixation peut être assemblé de manière démontable au premier moyen de fixation du module de tente central ; le module de tente complémentaire du troisième type comporte en outre une seconde face d'entrée, opposée à la première entrée, présentant un second contour périphérique muni d'un second dispositif de fixation, le second contour périphérique s'étendant dans une quatrième surface qui est parallèle à la troisième surface; le second dispositif de fixation peut être assemblé de manière démontable au deuxième moyen de fixation, grâce à quoi le module de tente complémentaire du troisième type peut être attaché au module de tente central et/ou à un module de tente complémentaire d'un autre type par l'intermédiaire de son premier dispositif de fixation ou de son second dispositif de fixation.

Ce module de tente complémentaire du troisième type présente de préférence, mais pas nécessairement, une chambre intérieure munie d'une entrée débouchant dans la première et/ou la seconde face d'entrée.

L'abri modulaire selon l'invention peut comprendre à la fois au moins un module de tente complémentaire du premier type, au moins un module de tente complémentaire du deuxième type, et au moins un module de module de tente complémentaire du troisième type, ou bien uniquement un ou plusieurs desdits modules de tente complémentaires.

Par ailleurs, le module de tente complémentaire du premier type peut être attaché au module de tente complémentaire du troisième type.

Pour ce faire, on assemble le dispositif de fixation du module de tente complémentaire du premier type avec le premier dispositif de fixation du module de tente complémentaire du troisième type.

L'unité constituée de l'assemblage du module de tente complémentaire du premier type avec le module de tente complémentaire du troisième type peut être avantageusement attachée au module de tente central en assemblant le second dispositif de fixation du module de

tente complémentaire du troisième type avec le deuxième moyen de fixation du module de tente central.

En outre, le module de tente complémentaire du deuxième type peut être attaché au module de tente complémentaire du troisième type.

- 5 Pour ce faire, on assemble le dispositif de fixation du module de tente complémentaire du deuxième type avec le second dispositif de fixation du module de tente complémentaire du troisième type.

- 10 L'unité constituée de l'assemblage du module de tente complémentaire du deuxième type avec le module de tente complémentaire du troisième type peut être avantageusement attachée au module de tente central en assemblant le premier dispositif de fixation du module de tente complémentaire du troisième type avec le premier moyen de fixation du module de tente central.

- 15 L'invention permet également de former une unité autoportée indépendante du module de tente central. Le cas échéant, le module de tente complémentaire du premier type et le module de tente complémentaire du deuxième type sont assemblés au module de tente complémentaire du troisième type.

- 20 Avantageusement, les premier et second dispositifs de fixation du module de tente complémentaire du troisième type présentent respectivement la même longueur que les premier et deuxième moyens de fixation du module de tente central.

De préférence, les premier et second dispositifs de fixation sont des fermetures à glissières.

- 25 Selon une variante, les premier et second dispositifs de fixation sont constitués de boucles d'attaches, de préférence similaires aux boucles d'attache précitées.

- 30 Avantageusement, le module de tente complémentaire du troisième type comporte un boudin formant arceau qui entoure la seconde face d'entrée, et le deuxième dispositif de fixation est disposé au-dessus dudit boudin. Ce boudin est de préférence gonflable afin de faciliter le montage du module de tente complémentaire du troisième type. Il permet en outre de former la structure en arche de la seconde face d'entrée.

- 35 Selon un quatrième mode de réalisation, l'abri modulaire comporte deux modules de tente centraux reliés l'un à l'autre par le biais d'un module de tente complémentaire du troisième type.

Pour ce faire, le premier module de tente central est attaché à la première face d'entrée du module de tente complémentaire du troisième type, tandis que le second module de tente central est attaché à la seconde face d'entrée du module de tente complémentaire du troisième type.

Le module de tente complémentaire du troisième type permet donc de relier ensemble deux modules de tente centraux, ce qui permet d'agrandir significativement le volume de l'abri.

Selon un cinquième mode de réalisation, l'abri modulaire comporte un module de tente complémentaire du premier type et un module de tente complémentaire du deuxième type, les modules de tente complémentaires des premier et deuxième types étant attachés l'un à l'autre sans module de tente central. L'unité constituée de l'assemblage d'un module de tente complémentaire du premier type et d'un module de tente complémentaire du deuxième type est donc indépendante du module de tente central de l'abri modulaire.

Selon une variante, déjà mentionnée plus haut, l'abri modulaire comporte en outre un module de tente complémentaire du troisième type disposé entre le module de tente complémentaire du premier type et le module de tente complémentaire du deuxième type. L'invention vise également à couvrir chacun des modules de tente complémentaire décrits ci-dessus.

A cet effet, l'invention concerne en outre un module de tente complémentaire d'un premier type configuré pour être attaché au module de tente central selon l'invention ou à un module de tente complémentaire d'un autre type ; ledit module de tente complémentaire du premier type comporte une face d'entrée présentant un contour périphérique muni d'un dispositif de fixation, le contour périphérique s'étendant dans une surface qui est inclinée par rapport à un plan vertical, la surface dans laquelle s'étend le contour périphérique du module de tente complémentaire du premier type présente la même inclinaison que la seconde surface dans laquelle s'étend le bord périphérique de la casquette du module de tente central, et lorsque le module de tente complémentaire du premier type est attaché au module de tente central, le dispositif de fixation du module de tente complémentaire du premier type est assemblé au deuxième moyen de fixation du module de tente central.

L'invention concerne en outre un module de tente complémentaire d'un deuxième type configuré pour être attaché au module de tente central selon l'invention, ou à un module de tente complémentaire d'un autre type ; le module de tente complémentaire du deuxième type

5 comporte une face d'entrée présentant un contour périphérique muni d'un dispositif de fixation, le contour périphérique s'étendant dans une surface inclinée qui présente la même inclinaison que la première surface dans laquelle s'étend le premier moyen de fixation du module de tente central, et, lorsque le module de tente complémentaire du deuxième type est

10 attaché au module de tente central, le dispositif de fixation est assemblé au premier moyen de fixation, et le contour périphérique vient se loger en dessous de la casquette.

L'invention concerne en outre un module de tente complémentaire d'un troisième type configuré pour être attaché au module de tente central selon l'invention, et/ou à un module de tente complémentaire d'un autre type ; le module de tente complémentaire du troisième type

15 comporte une première face d'entrée présentant un premier contour périphérique muni d'un premier dispositif de fixation, le premier contour périphérique s'étendant dans une troisième surface inclinée par rapport à un plan vertical et qui présente la même inclinaison que la première

20 surface du module de tente central ; le premier dispositif de fixation peut être assemblé de manière démontable au premier moyen de fixation du module de tente central, le module de tente complémentaire du troisième type comporte en outre une seconde face d'entrée, opposée à la première

25 face d'entrée, présentant un second contour périphérique muni d'un second dispositif de fixation, le second contour périphérique s'étendant dans une quatrième surface qui est parallèle à la troisième surface ; le second dispositif de fixation peut être assemblé de manière démontable au deuxième moyen de fixation, grâce à quoi le module de tente

30 complémentaire du troisième type peut être attaché au module de tente central et/ou à un module de tente complémentaire d'un autre type par l'intermédiaire de son premier dispositif de fixation ou de son second dispositif de fixation.

L'invention concerne enfin un ensemble modulaire comportant un

35 module de tente complémentaire du premier type selon l'invention et un module de tente complémentaire du deuxième type selon l'invention, le

module de tente complémentaire du premier type étant attaché au module de tente complémentaire du deuxième type.

Avantageusement, l'abri modulaire comporte en outre un module de tente complémentaire du troisième type reliant le module de tente
5 complémentaire du premier type au module de tente complémentaire du deuxième type.

Brève description des dessins

- 10 L'invention sera mieux comprise à la lecture de la description qui suit de modes de réalisation de l'invention donnés à titre d'exemples non limitatifs, en référence aux dessins annexés, sur lesquels :
- la figure **1** illustre un module de tente central conforme à la présente invention ;
 - 15 - les figures **2A** et **2B** illustrent un module de tente complémentaire du premier type, en perspective et en vue de face ;
 - les figures **3A** et **3B** illustrent un module de tente complémentaire du deuxième type, en perspective et en vue de face,
 - 20 - la figure **4** est une vue en perspective d'un module de tente complémentaire du troisième type ;
 - la figure **5** illustre un abri modulaire selon l'invention avant assemblage qui comporte un module de tente central, et des modules de tente complémentaires des premier, deuxième et
 - 25 - la figure **6** illustre l'abri modulaire de la figure **5** une fois assemblé ;
 - la figure **7** illustre un mode de réalisation de l'abri modulaire selon l'invention comprenant un module de tente central, un
 - 30 - la figure **8** illustre un autre mode de réalisation de l'abri modulaire selon l'invention comprenant un module de tente central, un module de tente complémentaire du premier type,
 - 35

deux modules de tente complémentaires du troisième type, et un module de tente complémentaire du deuxième type ;

- 5 - la figure **9** illustre un autre mode de réalisation de l'abri modulaire selon l'invention comprenant deux modules de tente centraux reliées l'un à l'autre par l'intermédiaire d'un module de tente complémentaire du troisième type, ainsi qu'un module de tente complémentaire du premier type, un autre module de tente complémentaire du troisième type et un module de tente complémentaire du deuxième type ; et
- 10 - la figure **10** illustre un mode de réalisation de l'abri modulaire dépourvu de module de tente central et comportant un module de tente complémentaire du troisième type assemblé à un module de tente complémentaire du premier type et à un module de tente complémentaire du deuxième type.

15

Description détaillée de l'invention

L'invention porte sur un système de tentes modulaires qui permet à l'utilisateur de concevoir l'abri qui lui convient en assemblant des modules les uns aux autres.

- 20 Le premier module, appelé module de tente central **100**, est illustré en figure **1**.

Le module de tente central **100** comprend une toile de tente portée par une paire d'arceaux croisés **102**.

- 25 Dans cet exemple, la toile de tente **104** est constituée d'une pluralité de pans attachés les uns aux autres afin de former la toile extérieure du module de tente central **100**.

- 30 Le module de tente central **100** présente dans cet exemple quatre faces latérales s'étendant depuis la base **108** du module de tente central **100**. Sur la figure **1**, ne sont visibles que les faces **106a** et **106b** qui sont sensiblement perpendiculaires l'une à l'autre.

Dans cet exemple, chacune des faces latérales est munie d'une ouverture **110a**, **110b**.

Sans sortir du cadre de l'invention, une seule des faces latérales ou bien certaines d'entre elles pourraient être munie d'une ouverture.

Chacune des ouvertures **110a**, **110b** est munie d'un premier moyen de fixation **112a**, **112b** qui, dans cet exemple, s'étend selon le pourtour de ladite ouverture.

5 Selon le mode de réalisation de la figure **1**, l'ouverture **110a** est obturée par un pan de porte **114** rapporté dont le pourtour comprend un organe de fixation **114a** qui coopère avec le premier moyen de fixation **112a** de l'ouverture **110a**.

10 Dans cet exemple, les premiers moyens de fixation **112a**, **112b** ainsi que l'organe de fixation **114a** du pan de porte **114** sont des fermetures à glissières.

Bien entendu, un pan de porte **114** similaire pourrait être monté sur la seconde face latérale **106b** afin d'obturer l'ouverture **110b**.

15 Pour chacune des ouvertures **110a**, **110b**, le premier moyen de fixation **112a**, **112b** s'étend selon une courbe qui présente sensiblement la forme d'une arche.

Cette arche s'étend dans une première surface **P1** qui est inclinée par rapport à un plan vertical.

20 La première surface **P1**, dans laquelle s'étend le premier moyen de fixation **112a**, est inclinée de sorte que le sommet de l'arche le long duquel s'étend le premier moyen de fixation est plus proche du centre de la base **108** du module de tente central **100** que ne l'est la base de ladite arche.

25 En d'autres termes, considérée depuis sa base vers le sommet du module de tente central, la première surface **P1** est inclinée vers l'intérieur du module de tente central.

Cette inclinaison est mieux visible sur la figure **5** qui montre notamment le module de tente central **100** en vue de côté.

30 Sur cette figure, on constate que le premier moyen de fixation **112a** s'étend selon une première surface **P1** qui est inclinée par rapport au plan vertical **V1**, l'angle d'inclinaison étant référencé α .

35 Dans l'exemple de la figure **5**, la première surface **P1** est une surface plane. Cependant, sans sortir du cadre de la présente invention, la première surface pourrait être légèrement incurvée ou bombée. Dans ce cas, le plan **P1** peut être vu comme celui qui contient le bord d'extrémité inférieur et le sommet de l'arche dans lequel s'étend le premier moyen de fixation.

Dans cet exemple non limitatif, l'angle α est de l'ordre de 20°.

En se référant à nouveau à la figure **1**, on constate que la toile de tente **104** comporte une première casquette **116** qui s'étend autour de la première ouverture **110a** tout en faisant saillie depuis la toile de tente **104** vers l'extérieur du module de tente central **100**.

Dans cet exemple, la casquette **116** est souple bien qu'elle pourrait tout à faire être constituée d'un matériau rigide.

La casquette **116** est constituée d'une portion supérieure **116a** qui s'étend dans un plan sensiblement horizontal et de portions latérales **116b**, **116c** qui flanquent l'ouverture **110a**.

On constate par ailleurs que le module de tente central **100** comporte une deuxième casquette **118** qui s'étend autour de la seconde ouverture **110b**, en faisant également saillie depuis la toile de tente **104** vers l'extérieur du module de tente central **100**.

Dans cet exemple, les casquettes **116** et **118** sont identiques de sorte qu'on ne s'intéressera dorénavant qu'à la première casquette **116**.

La première casquette **116** comporte en outre un bord périphérique **116c** qui s'étend autour de l'ouverture **110a**, ce bord périphérique **116c** étant muni d'un deuxième moyen de fixation **120**, en l'espèce une fermeture à glissières.

Ce second moyen de fixation **120**, tout comme le bord périphérique **116c**, s'étend également selon une courbe en forme d'arche. Cette courbe s'étend dans une seconde surface qui est inclinée par rapport au plan vertical précité.

Conformément à l'invention, l'inclinaison de la seconde surface est opposée à celle de la première surface. En d'autres termes, considérée depuis la base vers le sommet de l'arche, la seconde surface **P2** s'étend vers l'extérieur du module de tente central.

Sur la figure **5**, la seconde surface **P2** est plane. Sans sortir du cadre de la présente invention, elle pourrait toutefois être légèrement incurvée ou bombée. Dans ce cas, la référence **P2** correspondrait au plan moyen qui contient la base et le sommet de l'arche le long duquel s'étend le second moyen de fixation **120**.

Dans cet exemple, le premier moyen de fixation **112a** de la première face latérale **106a** présente la même longueur que le deuxième moyen de fixation **120**. Il s'agit ici d'une fermeture à glissière ;

alternativement, on pourrait prévoir des boucles de fixation montées le long du bord périphérique **116c** et du pourtour de l'ouverture.

En se référant à nouveau à la figure **5**, on constate que les première et seconde surfaces **P1**, **P2** sont sensiblement symétriques par rapport au plan vertical **V1**. Dans cet exemple, l'angle α entre le plan vertical **V1** et la surface **P1** est égal à l'angle β défini entre le plan vertical **V1** et la seconde surface **P2**.

Conformément à l'invention, le module de tente central **100** est configuré pour être attaché à au moins un module de tente complémentaire, quand bien même que le module de tente central pourrait être utilisé de manière autonome.

Sur les figures **5** et **6**, on a illustré un mode de réalisation de l'abri modulaire selon l'invention, dans lequel le module de tente central **100** est attaché à un module complémentaire d'un premier type **200**, à un module complémentaire d'un deuxième type **300**, et à un module complémentaire d'un troisième type **400**, qui vont être successivement décrits plus en détail ci-dessous.

La figure **6** illustre les modules une fois assemblés les uns aux autres afin de constituer l'abri modulaire **AM1**.

Dans l'exemple de la figure **6**, les modules de tente complémentaires sont attachés à deux faces latérales opposées du module de tente central **100**. Bien entendu, cet exemple n'est pas limitatif, les modules complémentaires pouvant coopérer avec l'une ou l'autre des faces latérales du module de tente central **100**.

On va maintenant décrire plus en détail le module de tente complémentaire du premier type **200**, à l'aide des figures **2A** et **2B**.

Le module complémentaire du premier type **200** comporte une toile de tente **202** qui est reliée à un boudin gonflable **204** présentant la forme d'un arceau. Le boudin formant arceau **204** délimite une ouverture **206** ménagée dans la face d'entrée **208** du module de tente complémentaire du premier type **200**. La face d'entrée **208** présente un contour périphérique **208a** qui est muni d'un dispositif de fixation **210**.

Dans cet exemple, le dispositif de fixation **210** est une fermeture à glissière.

Comme on le constate sur la figure **2B**, le dispositif de fixation **210** est disposé au dessus du boudin **204**. Le contour périphérique **208a** de la

face d'entrée **208** présente la forme d'une arche le long de laquelle s'étend la fermeture à glissière **210**.

5 En se référant à la figure **5**, on constate que le contour périphérique **208a** s'étend dans une surface **P3** qui est inclinée par rapport à un plan vertical **V2**.

Conformément à l'invention, la surface **P3** dans laquelle s'étend le contour périphérique **208a** présente la même inclinaison α que la seconde surface **P2** dans laquelle s'étend le bord périphérique **116c** de la casquette **116** du module de tente central **100**.

10 En d'autres termes, le dispositif de fixation **210** s'étend dans la surface **P3** qui présente la même inclinaison que la seconde surface **P2** du module de tente central **100**.

Comme on l'a représenté sur la figure **6**, lorsque le module de tente complémentaire du premier type **200** est attaché au module de tente central **100**, le dispositif de fixation **210** du module de tente complémentaire du premier type **200** est assemblé au deuxième moyen de fixation **120** du module de tente central **100**.

On comprend en effet que la surface dans laquelle s'étend le contour périphérique du premier module de tente complémentaire est parallèle à la seconde surface **P2** dans laquelle s'étend le bord périphérique de la casquette. Lorsque le module de tente complémentaire du premier type est attaché au module de tente central **100**, la surface **P3** dans laquelle s'étend le dispositif de fixation **210** se retrouve sensiblement confondue avec la surface **P2** dans laquelle s'étend le second dispositif de fixation **120** du module de tente central **100**, grâce à quoi le dispositif de fixation **210** et le deuxième moyen de fixation **120** peuvent être assemblés l'un à l'autre afin de connecter ensemble le module de tente du premier type et le module de tente central.

Dans cet exemple, la surface **P3** est donc inclinée d'un angle α par rapport au plan vertical **V2** de sorte que, considérée depuis la base vers le sommet du boudin **204**, la surface **P3** est inclinée vers l'intérieur du module de tente complémentaire du premier type **200**, étant rappelé que la seconde surface **P2** est quant à elle inclinée vers l'extérieur du module de tente central **100**.

35 On comprend par ailleurs que le dispositif de fixation **210** du module de tente complémentaire du premier type **200** est de même

longueur que le deuxième moyen de fixation **120** du module de tente central **100**.

5 Aussi, le module de tente complémentaire du premier type peut être notamment assemblé à n'importe laquelle des casquettes du module de tente central **100**.

En se référant maintenant aux figures **3A** et **3B**, on va décrire plus en détail le module de tente complémentaire du deuxième type **300**.

10 Ce module de tente complémentaire du deuxième type **300** est également configuré pour être attaché directement au module de tente central **100** ou à un module de tente complémentaire d'un autre type.

15 Le module de tente complémentaire du deuxième type **300** comporte également une toile de tente **302** mise en volume par le biais d'arceaux **304**, **306**, l'un des arceaux présentant une forme d'arche délimitant une face d'entrée **306** du module de tente complémentaire du deuxième type **300**.

20 Le module de tente complémentaire du deuxième type **300** est également pourvu d'une chambre intérieure **308** dont l'un des pans **308a** coïncide sensiblement avec la face d'entrée **306**. Ce pan **308a** est muni d'une ouverture **310** constituant une entrée du module de tente complémentaire du deuxième type **300**.

La face d'entrée **306** présente par ailleurs un contour périphérique **306a** qui est muni d'un dispositif de fixation **310**. Dans cet exemple, le dispositif de fixation **310** est une fermeture à glissière.

25 Ce contour périphérique **306a** ainsi que la fermeture à glissière **310** s'étendent dans une surface **P4** qui, comme on le constate sur la figure **5**, est inclinée et présente la même inclinaison α que la première surface **P1** dans laquelle s'étend le premier moyen de fixation **112a** du module de tente central **100**.

30 Comme on le voit sur la figure **6**, lorsque le module de tente complémentaire du deuxième type **300** est attaché au module de tente central **100**, la surface **P4** dans laquelle s'étend le dispositif de fixation **310** est parallèle à la première surface **P1** du module de tente central de manière à pouvoir assembler le dispositif de fixation **310** au premier moyen de fixation **112a**. La fixation directe du module de tente
35 complémentaire du deuxième type **300** au module de tente central **100** est illustrée en figures **7** et **9**.

On constate que le contour périphérique vient se loger en dessous de la casquette du module de tente central **100**.

Par ailleurs, le dispositif de fixation **310** du module de tente complémentaire du deuxième type **300**, en l'espèce une fermeture à glissière, est de même longueur que la fermeture à glissière constituant le premier moyen de fixation **112a** du module de tente central **100**. On pourrait bien entendu remplacer les fermetures à glissières par des boucles d'attache sans sortir du cadre de la présente invention.

On va maintenant décrire plus en détail, le module de tente complémentaire du troisième type **400** à l'aide des figures **4**, **5**, **6**.

Comme on le constate notamment sur les figures **5** et **6**, le module de tente complémentaire du troisième type **400** illustré sur la figure **4** est configuré pour être attaché au module de tente central **100** ou à un module de tente complémentaire d'un autre type. Le module de tente complémentaire du troisième type **400** comporte une toile de tente **402** mise en volume par un premier arceau **404** qui délimite une première face d'entrée **406**. Cette première face d'entrée **406** présente un premier contour périphérique **406a** qui s'étend dans une troisième surface **P5**, laquelle est inclinée par rapport à un plan vertical **V4**, la troisième surface **P5** présentant la même inclinaison α que la première surface **P1** du module de tente central **100**.

Le premier dispositif de fixation **310** peut être assemblé de manière démontable au premier moyen de fixation **112a** du module de tente central. En conséquence, le premier dispositif de fixation **310** présente la même longueur que le premier moyen de fixation du module de tente central. En l'espèce, le premier dispositif de fixation du module de tente complémentaire du troisième type et le premier moyen de fixation du module de tente central sont des fermetures à glissières.

En se référant à nouveau à la figure **4**, on constate que le module de tente complémentaire du troisième type **400** comporte en outre une seconde face d'entrée **408** qui est opposée à la première face d'entrée **406**. Le module complémentaire du troisième type **400** comporte un boudin **410** formant arceau qui entoure la seconde face d'entrée **408**.

Le boudin **410** s'étend selon un second contour périphérique **408a** qui est muni d'un second dispositif de fixation **420**. Le second contour périphérique **408a** s'étend dans une quatrième surface **P6**, mieux visible

sur la figure **5**, qui est inclinée et parallèle à la troisième surface **P5**. Cette quatrième surface **P6** est donc inclinée d'un angle α par rapport au plan vertical **V5**.

En se référant à la figure **5**, on constate que la quatrième surface **P6**, considérée depuis la base vers le sommet du boudin **409**, s'étend vers l'intérieur du module de tente central du troisième type, tandis que la troisième surface **P5** s'étend vers l'extérieur dudit module.

En conséquence, le second dispositif de fixation **420** peut être assemblé de manière démontable au deuxième moyen de fixation **120** de la casquette du module de tente central **100**, grâce à quoi le module de tente complémentaire du troisième type **400** peut être attaché au module de tente central **100**.

On comprend également que le module de tente complémentaire du troisième type **400** peut être attaché au module de tente complémentaire du deuxième type **300** dans la mesure où la surface **P4** du module de tente complémentaire du deuxième type présente la même inclinaison que la quatrième surface inclinée du module de tente complémentaire du troisième type.

Cet agencement est notamment visible sur la figure **5**.

Les figures **7** à **10** présentent différents modes de réalisation de l'abri modulaire conforme à la présente invention.

L'abri modulaire **AM2** de la figure **7** comprend un module de tente central **100**, attaché directement par une première face latérale à un module de tente complémentaire du deuxième type et par une deuxième face latérale à un module complémentaire du premier type.

L'abri modulaire **AM3** du mode de réalisation de la figure **8** diffère du mode de réalisation de la figure **7** en ce qu'un premier module de tente complémentaire du troisième type **400** est inséré entre le module de tente complémentaire du deuxième type **300** et le module de tente central **100** ; et un second module de tente complémentaire du troisième type **400'** est inséré entre le module de tente central **100** et le module de tente complémentaire du premier type **200**.

L'abri modulaire **AM4** de la figure **9** comporte deux modules de tente centraux **100**, **100'** reliés l'un à l'autre par le biais d'un module de tente complémentaire du troisième type **400**. L'un des deux modules de tente centraux **100** est attaché à un module de tente central du deuxième

type **300**, tandis que l'autre des deux modules de tente centraux **100'** est attaché directement à un second module de tente complémentaire du troisième type **400'**, qui est lui-même attaché à un module de tente complémentaire du premier type **200**.

- 5 Dans le mode de réalisation **AM5** de la figure **10**, l'abri modulaire **AM5** comporte un module de tente complémentaire du premier type **200** et un module de tente complémentaire du deuxième type **300**, les modules de tente complémentaires des premier et deuxième types étant attachés l'un à l'autre sans module de tente central mais par le biais d'un
- 10 module de tente complémentaire du troisième type **400**.

REVENDECATIONS

1. Module de tente central (100) comportant :
 - 5 ○ une toile de tente (104) dans laquelle est ménagée au moins une ouverture (106a, 106b), ladite ouverture étant munie d'un premier moyen de fixation (112a, 112b) et s'étendant dans une première surface (P1) inclinée par rapport à un plan vertical ;
 - 10 ○ au moins une casquette (116, 118) s'étendant autour de l'ouverture (106a, 106b) tout en faisant saillie depuis la toile de tente vers l'extérieur du module de tente central, la casquette présentant un bord périphérique (116c) muni d'un deuxième moyen de fixation (120) et s'étendant dans une seconde surface (P2) inclinée par rapport au plan vertical (V1), la seconde surface présentant, par rapport au plan vertical, une inclinaison opposée à celle de la première surface.
 - 15
- 20 2. Module de tente central selon la revendication 1, caractérisé en ce qu'il comporte en outre un pan de porte (114) dont le pourtour comprend un organe de fixation (114a) arrangé pour coopérer avec le premier moyen de fixation (112a) de l'ouverture (110a) ou bien avec le deuxième moyen de fixation.
- 25 3. Module de tente central selon la revendication 1 ou 2, caractérisé en ce que les premier (112a) et deuxième (120) moyens de fixation présentent la même longueur.
- 30 4. Module de tente central selon l'une quelconque des revendications 1 à 3, caractérisé en ce que les premier (112a) et deuxième (120) moyens de fixation sont des fermetures à glissières.
- 35 5. Module de tente central selon l'une quelconque des revendications 1 à 3, caractérisé en ce que les premier (112a) et deuxième (120) moyens de fixation sont constitués de boucles de fixation.

- 5 6. Module de tente central selon l'une quelconque des revendications 1 à 5, caractérisé en ce que les première et seconde surfaces (P1, P2) sont sensiblement symétriques par rapport au plan vertical (V1).
- 10 7. Module de tente central selon l'une quelconque des revendications 1 à 6, caractérisé en ce que le bord périphérique de la casquette comporte en outre un rabat d'étanchéité recouvrant le deuxième moyen de fixation de la casquette.
- 15 8. Abri modulaire comportant au moins un module de tente central selon l'une quelconque des revendications 1 à 7, et au moins un module de tente complémentaire (200, 300, 400) configuré pour être attaché au module de tente central et/ou à un autre module de tente complémentaire (200, 300, 400).
- 20 9. Abri modulaire selon la revendication 8, caractérisé en ce qu'il comporte au moins un module de tente complémentaire d'un premier type (200) configuré pour être attaché au module de tente central (100) ou à un module de tente complémentaire d'un autre type (300, 400), en ce que le module de tente complémentaire du premier type comporte une face d'entrée (208) présentant un contour périphérique (208a) muni d'un dispositif de fixation (210), le contour périphérique s'étendant dans une surface (P3) qui est
- 25 inclinée par rapport à un plan vertical (V2), en ce que la surface dans laquelle s'étend le contour périphérique du module de tente complémentaire du premier type présente la même inclinaison (α) que la seconde surface (P2) dans laquelle s'étend le bord périphérique (116c) de la casquette (116) du module de tente central (100), et en ce que, lorsque le module de tente complémentaire du premier type (200) est attaché au module de
- 30 tente central (100), le dispositif de fixation (210) du module de tente complémentaire du premier type (200) est assemblé au deuxième moyen de fixation (120) du module de tente central (100).
- 35

10. Abri modulaire selon la revendication 9, caractérisé en ce que le dispositif de fixation (210) du module de tente complémentaire du premier type (200) est de même longueur que le deuxième moyen de fixation (120) du module de tente central (100).
- 5
11. Abri modulaire selon la revendication 9 ou 10, caractérisé en ce que le dispositif de fixation du module de tente complémentaire du premier type (200) et le deuxième moyen de fixation du module de tente central (100) sont des fermetures à glissières.
- 10
12. Abri modulaire selon la revendication 9 ou 10, caractérisé en ce que le dispositif de fixation du module de tente complémentaire du premier type (200) et le deuxième moyen de fixation du module de tente central (100) sont constitués de boucles d'attaches.
- 15
13. Abri modulaire selon l'une quelconque des revendications 9 à 12, caractérisé en ce que le module de tente complémentaire du premier type comporte un boudin formant arceau (204) qui entoure la face d'entrée (208), le dispositif de fixation (210) étant disposé
- 20
14. Abri modulaire selon l'une quelconque des revendications 9 à 13, caractérisé en ce qu'il comporte au moins un module de tente complémentaire d'un deuxième type (300) configuré pour être attaché au module de tente central (100) ou à un module de tente complémentaire d'un autre type (200, 400), en ce que le module de tente complémentaire du deuxième type comporte une face d'entrée (306) présentant un contour périphérique (306a) muni d'un dispositif de fixation (310), le contour périphérique s'étendant
- 25
- 30
- 35
- dans une surface (P4) qui présente la même inclinaison (α) que la première surface (P1) dans laquelle s'étend le premier moyen de fixation (112a) du module de tente central (100), et en ce que, lorsque le module de tente complémentaire du deuxième type (300) est attaché au module de tente central (100), le dispositif de fixation (310) est assemblé au premier moyen de fixation (112a), et

le contour périphérique (306a) vient se loger en dessous de la casquette (116).

- 5 15. Abri modulaire selon la revendication 14, caractérisé en ce que le dispositif de fixation (310) du module de tente complémentaire du deuxième type (300) est de même longueur que le premier moyen de fixation du module de tente central (100).
- 10 16. Abri modulaire selon la revendication 14 ou 15, caractérisé en ce que le dispositif de fixation du module de tente complémentaire du deuxième type (300) et le premier moyen de fixation du module de tente central (100) sont des fermetures à glissières.
- 15 17. Abri modulaire selon la revendication 14 ou 15, caractérisé en ce que le dispositif de fixation du module de tente complémentaire du deuxième type (300) et le premier moyen de fixation du module de tente central (100) sont constitués de boucles d'attaches.
- 20 18. Abri modulaire selon l'une quelconque des revendications 8 à 17, caractérisé en ce qu'il comporte au moins un module de tente complémentaire d'un troisième type (400) configuré pour être attaché au module de tente central et/ou à un module de tente complémentaire d'un autre type (200, 300), en ce que le module de tente complémentaire du troisième type comporte une première
- 25 face d'entrée (406) présentant un premier contour périphérique muni d'un premier dispositif de fixation, le premier contour périphérique s'étendant dans une troisième surface inclinée par rapport à un plan vertical et qui présente la même inclinaison (α) que la première surface (P1) du module de tente central (100), en
- 30 ce que le premier dispositif de fixation (410) peut être assemblé de manière démontable au premier moyen de fixation (112a) du module de tente central (100), en ce que le module de tente complémentaire du troisième type (400) comporte en outre une
- 35 seconde face d'entrée (407), opposée à la première face d'entrée (406), présentant un second contour périphérique (408a) muni d'un second dispositif de fixation (420), le second contour périphérique

- 5 (408a) s'étendant dans une quatrième surface qui est parallèle à la troisième surface, en ce que le second dispositif de fixation (420) peut être assemblé de manière démontable au deuxième moyen de fixation (120), grâce à quoi le module de tente complémentaire du troisième type (400) peut être attaché au module de tente central (100) et/ou à un module de tente complémentaire d'un autre type par l'intermédiaire de son premier dispositif de fixation ou de son second dispositif de fixation.
- 10 19. Abri modulaire selon la revendication 18, caractérisé en ce que les premier (410) et second (420) dispositifs de fixation présentent respectivement la même longueur que les premier (112a) et deuxième (120) moyens de fixation du module de tente central.
- 15 20. Abri modulaire selon la revendication 18 ou 19, caractérisé en ce que les premier et second dispositifs de fixation sont des fermetures à glissières.
- 20 21. Abri modulaire selon la revendication 18 ou 19, caractérisé en ce que les premier et second dispositifs de fixation sont constitués de boucles d'attaches.
- 25 22. Abri modulaire selon l'une quelconque des revendications 18 à 21, caractérisé en ce que le module de tente complémentaire du troisième type (400) comporte un boudin formant arceau (409) qui entoure la seconde face d'entrée (408), et en ce que le deuxième dispositif de fixation est disposé au-dessus dudit boudin.
- 30 23. Abri modulaire (AM4) selon l'une quelconque des revendications 18 à 22, caractérisé en ce qu'il comporte deux modules de tente centraux (100, 100') reliés l'un à l'autre par le biais d'un module de tente complémentaire du troisième type (400).
- 35 24. Abri modulaire (AM5) selon les revendications 9 et 14, caractérisé en ce qu'il comporte un module de tente complémentaire du premier type (200) et un module de tente complémentaire du deuxième type (300), les modules de tente complémentaires des

premier et deuxième types étant attachés l'un à l'autre sans module de tente central.

- 5 25. Abri modulaire (AM5) selon les revendications 18 et 24, caractérisé en ce qu'il comporte en outre un module de tente complémentaire du troisième type (400) disposé entre le module de tente complémentaire du premier type et le module de tente complémentaire du deuxième type.
- 10 26. Module de tente complémentaire d'un premier type (200) configuré pour être attaché à un module de tente central (100) selon l'une quelconque des revendications 1 à 7 ou à un module de tente complémentaire d'un autre type (300, 400), caractérisé en ce que
- 15 ledit module de tente complémentaire du premier type comporte une face d'entrée (208) présentant un contour périphérique (208a) muni d'un dispositif de fixation (210), le contour périphérique s'étendant dans une surface (P3) qui est inclinée par rapport à un
- 20 plan vertical (V2), en ce que la surface dans laquelle s'étend le contour périphérique du module de tente complémentaire du premier type présente la même inclinaison (α) que la seconde surface (P2) dans laquelle s'étend le bord périphérique (116c) de la
- 25 casquette (116) du module de tente central (100), et en ce que, lorsque le module de tente complémentaire du premier type (200) est attaché au module de tente central (100), le dispositif de
- fixation (210) du module de tente complémentaire du premier type (200) est assemblé au deuxième moyen de fixation (120) du module de tente central (100).
- 30 27. Module de tente complémentaire d'un deuxième type (300) configuré pour être attaché à un module de tente central (100) selon l'une quelconque des revendications 1 à 7, ou à un module de tente complémentaire d'un autre type (200, 400), caractérisé en ce que le module de tente complémentaire du deuxième type
- 35 comporte une face d'entrée (306) présentant un contour périphérique (306a) muni d'un dispositif de fixation (310), le contour périphérique s'étendant dans une surface inclinée (P4) qui

5 présente la même inclinaison (α) que la première surface (P1) dans laquelle s'étend le premier moyen de fixation (112a) du module de tente central (100), et en ce que, lorsque le module de tente complémentaire du deuxième type (300) est attaché au module de tente central (100), le dispositif de fixation (310) est assemblé au premier moyen de fixation (112a), et le contour périphérique (306a) vient se loger en dessous de la casquette (116).

10 28. Module de tente complémentaire d'un troisième type (400) configuré pour être attaché à un module de tente central selon l'une quelconque des revendications 1 à 7, et/ou à un module de tente complémentaire d'un autre type (200, 300), caractérisé en ce que le module de tente complémentaire du troisième type

15 comporte une première face d'entrée (406) présentant un premier contour périphérique muni d'un premier dispositif de fixation, le premier contour périphérique s'étendant dans une troisième surface inclinée par rapport à un plan vertical et qui présente la même inclinaison (α) que la première surface (P1) du module de tente central (100), en ce que le premier dispositif de fixation (410) peut

20 être assemblé de manière démontable au premier moyen de fixation (112a) du module de tente central (100), en ce que le module de tente complémentaire du troisième type (400) comporte en outre une seconde face d'entrée (407), opposée à la première face d'entrée (406), présentant un second contour périphérique

25 (408a) muni d'un second dispositif de fixation (420), le second contour périphérique (408a) s'étendant dans une quatrième surface qui est parallèle à la troisième surface, en ce que le second dispositif de fixation (420) peut être assemblé de manière démontable au deuxième moyen de fixation (120), grâce à quoi le

30 module de tente complémentaire du troisième type (400) peut être attaché au module de tente central (100) et/ou à un module de tente complémentaire d'un autre type par l'intermédiaire de son premier dispositif de fixation ou de son second dispositif de fixation.






35 29. Ensemble modulaire (AM5) comportant un module de tente complémentaire du premier type (200) selon la revendication 26 et

un module de tente complémentaire du deuxième type (300) selon la revendication 27, le module de tente complémentaire du premier type étant attaché au module de tente complémentaire du deuxième type.

5

30.Ensemble modulaire (AM5) selon la revendication 29, caractérisé en ce qu'il comporte en outre un module de tente complémentaire du troisième type (400) selon la revendication 28 reliant le module de tente complémentaire du premier type au module de tente complémentaire du deuxième type.

10






FIG. 5




FIG. 4








FIG. 6



**RAPPORT DE RECHERCHE
PRÉLIMINAIRE**établi sur la base des dernières revendications
déposées avant le commencement de la rechercheN° d'enregistrement
nationalFA 775157
FR 1260857

DOCUMENTS CONSIDÉRÉS COMME PERTINENTS		Revendication(s) concernée(s)	Classement attribué à l'invention par l'INPI
Catégorie	Citation du document avec indication, en cas de besoin, des parties pertinentes		
A	US 2004/238021 A1 (HOLUB TIMOTHY M [US] ET AL) 2 décembre 2004 (2004-12-02) * alinéas [0002], [0006], [0008], [0034], [0045], [0047], [0049], [0054] - [0060]; figures 2,4,8-10 *	1-30	E04H15/18
A	US 5 394 897 A (RITCHEY MICHAEL T [US] ET AL) 7 mars 1995 (1995-03-07) * figures 1-6 *	1-30	
A	WO 2011/018664 A1 (TOLAND DUSTIN [GB]) 17 février 2011 (2011-02-17) * figures 1,9,10,11 *	1-30	
			DOMAINES TECHNIQUES RECHERCHÉS (IPC)
			E04H
Date d'achèvement de la recherche		Examineur	
29 juillet 2013		Decker, Robert	
CATÉGORIE DES DOCUMENTS CITÉS X : particulièrement pertinent à lui seul Y : particulièrement pertinent en combinaison avec un autre document de la même catégorie A : arrière-plan technologique O : divulgation non-écrite P : document intercalaire T : théorie ou principe à la base de l'invention E : document de brevet bénéficiant d'une date antérieure à la date de dépôt et qui n'a été publié qu'à cette date de dépôt ou qu'à une date postérieure. D : cité dans la demande L : cité pour d'autres raisons & : membre de la même famille, document correspondant			

ANNEXE AU RAPPORT DE RECHERCHE PRÉLIMINAIRE
RELATIF A LA DEMANDE DE BREVET FRANÇAIS NO. FR 1260857 FA 775157

La présente annexe indique les membres de la famille de brevets relatifs aux documents brevets cités dans le rapport de recherche préliminaire visé ci-dessus.
Les dits membres sont contenus au fichier informatique de l'Office européen des brevets à la date du **29-07-2013**
Les renseignements fournis sont donnés à titre indicatif et n'engagent pas la responsabilité de l'Office européen des brevets, ni de l'Administration française

Document brevet cité au rapport de recherche		Date de publication	Membre(s) de la famille de brevet(s)		Date de publication
US 2004238021	A1	02-12-2004	US	2004238021 A1	02-12-2004
			US	2007295377 A1	27-12-2007

US 5394897	A	07-03-1995	AUCUN		

WO 2011018664	A1	17-02-2011	EP	2464803 A1	20-06-2012
			WO	2011018664 A1	17-02-2011

EPO FORM P0465

Pour tout renseignement concernant cette annexe : voir Journal Officiel de l'Office européen des brevets, No.12/82

DERWENT- 2014-J30345
ACC-NO:
DERWENT- 201676
WEEK:

Copyright ©2021 Thomson Reuters

TITLE: Central tent module for use in modular shelter of modular assembly, has cover including peripheral edge provided with fixing unit and extending over surface inclined relative to vertical plane in opposite direction to another surface

INVENTOR: LAFOUX B; SIMON B

PATENT-ASSIGNEE: DECATHLON[DECA] , DECATHLON SA[DECA] ,
PROMILES[PROMN]

PRIORITY-DATA: 2012FR-060857 (November 15, 2012)

PATENT-FAMILY:

PUB-NO	PUB-DATE	LANGUAG E
FR 2997984 A1	May 16, 2014	FR
WO 2014076384 A1	May 22, 2014	FR
FR 2997984 B1	January 16, 2015	FR
CN 104781487 A	July 15, 2015	ZH
EP 2920386 A1	September 23, 2015	FR
RU 2602855 C1	November 20, 2016	RU

DESIGNATED-STATES: AE AG AL AM AO AT AU AZ BA BB BG BH BN BR BW BY
BZ CA CH CL CN CO CR CU CZ DE DK DM DO DZ EC EE
EG ES FI GB GD GE GH GM GT HN HR HU ID IL IN IR
IS JP KE KG KN KP KR KZ LA LC LK LR LS LT LU LY
MA MD ME MG MK MN MW MX MY MZ NA NG NI NO NZ OM
PA PE PG PH PL PT QA RO RS RU RW SA SC SD SE SG
SK SL SM ST SV SY TH TJ TM TN TR TT TZ UA UG US
UZ VC VN ZA ZM ZW AL AT BE BG CH CY CZ DE DK EE

ES FI FR GB GR HR HU IE IS IT LI LT LU LV MC MK
MT NL NO PL PT RO RS SE SI SK SM TR BA ME

APPLICATION-DATA:

PUB-NO	APPL- DESCRIPTOR	APPL-NO	APPL-DATE
FR 2997984A1	N/A	2012FR-060857	November 15, 2012
FR 2997984B1	N/A	2012FR-060857	November 15, 2012
CN 104781487A	N/A	2013CN- 80059839	October 25, 2013
EP 2920386A1	N/A	2013EP-815013	October 25, 2013
WO2014076384A1	N/A	2013WO- FR052549	October 25, 2013
CN 104781487A	PCT Application	2013WO- FR052549	October 25, 2013
EP 2920386A1	PCT Application	2013WO- FR052549	October 25, 2013
RU 2602855C1	PCT Application	2013WO- FR052549	October 25, 2013
RU 2602855C1	Based on	2015RU-122486	October 25, 2013

CPC-CURRENT:

CPC-INVENTIVE:

TYPE	CPC	DATE
CPCI	E04H15/18	20130101
CPCI	E04H15/40	20130101

INT-CL-CURRENT:

TYPE	IPC	DATE
CIPP	E04H15/18	20060101
CIPS	E04H15/40	20060101

ABSTRACTED-PUB-NO: FR 2997984 A1

BASIC-ABSTRACT:

NOVELTY - The module (100) has a tent canvas, in which openings are formed. The openings are provided with fixing units e.g. fixing loops, and extend over a surface (P1) i.e. flat surface, inclined relative to a vertical plane (V1). Covers (116, 118) extend around the openings and project from the canvas towards outside of the module. One of the covers (116) has a peripheral edge provided with another fixing unit (120) and extending over another surface (P2) i.e. planar surface, inclined relative to the vertical plane in an opposite direction to the former surface.

DESCRIPTION - An INDEPENDENT CLAIM is also included for a modular shelter.

USE - Central tent module for use in a modular shelter of a modular assembly (all claimed).

ADVANTAGE - The module provides the module assembly with a high modularity by providing large combinations or configurations of the assembly.

DESCRIPTION OF DRAWING(S) - The drawing shows a perspective view of a modular shelter including a central tent module and complementary tent modules of three types before assembly.

Surfaces (P1, P2)

Vertical plane (V1)

Central tent module (100)

Cross arches (102)

Covers (116, 118)

Fixing unit (120)

CHOSEN- Dwg.5/10
DRAWING:

TITLE- CENTRAL TENT MODULE SHELTER ASSEMBLE COVER
TERMS: PERIPHERAL EDGE FIX UNIT EXTEND SURFACE INCLINE
RELATIVE VERTICAL PLANE OPPOSED DIRECTION

DERWENT-CLASS: Q46

Doc code: IDS

PTO/SB/08a (01-10)

Doc description: Information Disclosure Statement (IDS) Filed

Approved for use through 07/31/2012. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

U.S.PATENTS						Remove
Examiner Initial*	Cite No	Patent Number	Kind Code ¹	Issue Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear
	1	6772780		2004-08-10	Roy Justin Price	
	2	7556054		2009-07-07	Theodore R. Zeigler	
	3	4945936		1990-08-07	Dennis C. Surrendi	
	4	7131236		2006-11-07	Chad Sample	
	5	4846204		1989-07-11	Bae Sok Kyu	
	6	5666986		1997-09-16	Clifford Royston Fox	
	7	6553699		2003-04-29	Mathias D. Kemeny	
	8	8925565		2015-01-06	Kwan Jun Choi	

/Robert Canfield/ (12/31/2020)

12/31/2020

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number		16861012
Filing Date		2020-04-28
First Named Inventor	Jonathan Urhausen	
Art Unit		3636
Examiner Name	Robert Canfield	
Attorney Docket Number		9693-012A-CON1

9	9243423		2016-01-26	Ki Ho Jin	
10	9243424		2016-01-26	Ki Ho Jin	
11	9631393		2017-04-25	Theodore R. Zeigler	
12	D454609		2002-03-19	Meyerhoffer et al	
13	5069572		1991-12-03	Niksic	
14	4706696		1987-11-17	Gillis	
15	6802329		2004-10-12	Chen	
16	5634483		1997-06-03	Gwin	
17	4995212		1991-02-26	James N. Morgan	
18	6223482		2001-05-01	Herman Zahar	
19	6553698		2003-04-29	Mathias D Kemeny	

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

20	8496019	2013-07-30	Nanqing Zhou
21	9605441	2017-03-28	Kwan Jun Choi
22	8360085	2013-01-29	Sunghee Lee
23	5017068	1991-05-21	James D. Cooksey
24	8448656	2013-05-28	Kwan Jun Choi
25	4658560	1987-04-21	Bryan J. Beaulieu
26	5943837	1999-08-31	Richard A. Esser
27	D544941	2007-06-19	Thomas Edward Rogers
28	3929146	1975-12-30	Francis H. Maiken
29	9163425	2015-10-20	Ryan L. Kubica
30	6758354	2004-07-06	Ottavio Carletti

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

	31	10309093	2019-06-04	Urhausen et al	
--	----	----------	------------	----------------	--

If you wish to add additional U.S. Patent citation information please click the Add button.

Add

U.S.PATENT APPLICATION PUBLICATIONS

Remove

Examiner Initial*	Cite No	Publication Number	Kind Code ¹	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear
	1	20130008478		2013-01-10	Alejandro Prieto Estebanez	
	2	20140182643		2014-07-03	Baoqing Yang	
	3	20060260666		2006-11-23	Choi	
	4	20070051399		2007-03-08	In-Young Jung	
	5	20150167343		2015-06-18	Miao Sheng Fang	
	6	20150240513		2015-08-27	Miao Sheng Fang	
	7	20180155952		2018-06-07	Jay Robert	

If you wish to add additional U.S. Published Application citation information please click the Add button.

Add

FOREIGN PATENT DOCUMENTS

Remove

/Robert Canfield/ (12/31/2020)

12/31/2020

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

Examiner Initial*	Cite No	Foreign Document Number ³	Country Code ²	Kind Code ⁴	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear	T ⁵
	1							

If you wish to add additional Foreign Patent Document citation information please click the Add button

NON-PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T ⁵
	1		

If you wish to add additional non-patent literature document citation information please click the Add button

EXAMINER SIGNATURE

Examiner Signature	/Robert Canfield/ (12/31/2020)	Date Considered	12/31/2020
--------------------	--------------------------------	-----------------	------------

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

¹ See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. ² Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). ³ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁴ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁵ Applicant is to place a check mark here if English language translation is attached.



19 BUNDESREPUBLIK
DEUTSCHLAND



DEUTSCHES
PATENTAMT

12 Gebrauchsmuster
10 DE 295 10 827 U 1

51 Int. Cl.⁸:
E 04 H 15/18
E 04 H 15/54
E 04 H 15/58

11 Aktenzeichen:	295 10 827.4
22 Anmeldetag:	4. 7. 95
47 Eintragungstag:	14. 9. 95
43 Bekanntmachung im Patentblatt:	26. 10. 95

DE 295 10 827 U 1

73 Inhaber:
Royalbeach Spiel und Sportartikel Vertriebs GmbH,
83417 Kirchanschöring, DE

74 Vertreter:
Haft, von Puttkamer, Berngruber, Czybulka, 81669
München

54 Zelt

DE 295 10 827 U 1

04.07.95

1

Royalbeach Spiel- und
Sportartikelvertriebs GmbH

03.07.1995
14264

83417 Kirchanschöring

Z E L T

Die Erfindung bezieht sich auf ein selbsttragendes Zelt.

Selbsttragende Zelte bestehen meist aus einer mit einer Bodenwanne versehenen kuppelförmigen Zelthülle, die an sich kreuzenden bogenförmigen Stangen aufgespannt ist. Die Stangen, die meistens aus ineinander steckbaren Rohrelementen gebildet sind, werden in Hülsen oder Stifte gesteckt, die an der Kuppelbasis der Zelthülle vorgesehen sind.

Die bekannten selbsttragenden Zelte sind für eine bestimmte Anzahl von Personen ausgelegt, beispielsweise zwei, vier oder sechs. Der Platz zum Kochen oder für das Gepäck, ist wenn überhaupt vorhanden, meist sehr beengt, jedenfalls bei Trekking-, Bergsport und dergleichen Zelte, bei denen es auf ein geringes Gewicht ankommt.

Aufgabe der Erfindung ist es, ein selbsttragendes Zelt bereitzustellen, das bezüglich der Zahl der aufnehmbaren Personen äußerst variabel ist und zudem ausreichend Platz zum Kochen und für das Gepäck bietet.

Dies wird erfindungsgemäß mit dem im Anspruch 1 gekennzeichneten Zelt erreicht. In den Unteransprüchen sind vorteilhafte Ausgestaltungen des erfindungsgemäßen Zeltes wiedergegeben.

295108 27

04.07.95

2

Das erfindungsgemäße Zelt besteht im einfachsten Fall aus zwei selbsttragenden Zeltteilen. Die Zelthülle jedes Zeltteils ist dabei mit einer zu einem Bogen aufspannbaren Öffnung versehen. Ferner ist eine Verbindungsvorrichtung vorgesehen, mit der die Zelthüllen der beiden Zeltteile an den zu einem Bogen aufgespannten Öffnungen unter Bildung eines Durchgangs zusammenfügbar sind.

Das eine Zeltteil kann dabei den Schlafplatz darstellen und das andere Zeltteil den Platz für das Gepäck, zum Kochen und dergleichen. Auch können beide Zeltteile als Schlafplatz ausgelegt sein, oder ein Zeltteil als Schlafplatz und das andere teilweise als Schlafplatz und zum Teil als Gepäck- oder Kochplatz.

Das erfindungsgemäße Zelt kann jedoch auch aus drei oder noch mehr Zeltteilen bestehen. In diesem Fall bildet ein Zeltteil ein zentrales Zeltteil, an das die anderen Zeltteile flügel förmig angeschlossen sind. D.h. die Zelthülle des zentralen Zeltteils ist mit einer der Anzahl der Flügelzeltteile entsprechenden jeweils zu einem Bogen aufspannbaren Öffnungen versehen. Die Zelthülle jedes Flügelzeltteils weist ihrerseits jeweils eine zu einem Bogen aufspannbare Öffnung auf, die mit der Zelthülle des zentralen Zeltteils an einer der Öffnungen des zentralen Zeltteils mit einer Verbindungsvorrichtung zusammenfügbar ist.

Die Verbindungsvorrichtung zum Zusammenfügen der Zeltteile an den bogenförmigen Öffnungen wird vorzugsweise durch einen Reißverschluß gebildet. Sie kann jedoch auch durch einen Klettverschluß, durch Schnüre oder dergleichen gebildet sein.

Um die miteinander verbundenen Zelthüllen im Bereich der Durchgangsöffnung zu einem Bogen aufzuspannen ist vorzugsweise eine bogenförmige Stange vorgesehen, die im wesent-

295108 27

04.07.95

3

lichen parallel zur bogenförmigen Durchgangsöffnung verläuft.

Die Stange wird an einer der beiden Zelthüllen im Bereich der Durchgangsöffnung fixiert. Zur Fixierung können beispielsweise an der Zelthülle im Bereich der Öffnung Schlaufen oder dergleichen vorgesehen sein, durch die die Stange gesteckt wird. Die Stange erstreckt sich also vorzugsweise außen über die Zelthülle, wobei die Zelthülle an der Stange aufgehängt wird.

Die Stange kann aus biegsamen Rohrelementen zusammensteckt sein, beispielsweise aus faserverstärkten, Kunststoff oder Leichtmetall. Nach dem Zusammenstecken der Stange, wird sie durch die Schlaufen gesteckt und dabei entsprechend gebogen. Die beiden Enden der Stange werden in Ösen oder Stifte gesteckt, die an den gegenüberliegenden Seiten am Boden der Zelthülle vorgesehen sind.

Die Zeltteile des erfindungsgemäßen Zeltes, also das zentrale Zeltteil sowie die daran angeschlossenen Zeltflügelteile werden vorzugsweise jeweils durch eine kuppelförmige Zelthülle gebildet, die an sich kreuzenden bogenförmigen Stangen aufgespannt wird.

Die Stangen sind vorzugsweise in gleicher Weise aufgebaut, wie die vorstehend erwähnte Stange zum Aufspannen der Durchgangsöffnung, d.h. sie bestehen vorzugsweise aus zusammensteckbaren Rohrelementen, aus faserverstärktem Kunststoff oder Leichtmetall und sind mit ihren Enden in Ösen oder durch Stifte fixiert, die an der Kuppelbasis der Zelthülle des jeweiligen Zeltteils befestigt sind.

Die Stangen kreuzen sich im allgemeinen im Scheitelpunkt der kuppelförmigen Zelthülle. Es können zwei sich kreuzende Stangen vorgesehen sein. Der Winkel, mit dem sich die beiden Stangen kreuzen, kann dabei unterschiedlich sein.

295108 27

04.07.95

4

Vorzugsweise ist es beim zentralen Zeltteil ein rechter Winkel, wodurch sich eine Kuppel mit annähernd quadratischer Basisfläche ergibt. Hingegen kann bei den Flügelzeltteilen ein anderer Winkel erwünscht sein, um eine rechteckige Basisfläche mit unterschiedlichen langen Seiten zu erhalten.

Statt zwei sich kreuzenden Stangen können auch drei oder noch mehr sich im Scheitelpunkt kreuzende Stangen zum Aufspannen einer entsprechend ausgebildeten Zelthülle vorgesehen sein. Dies gilt insbesondere für das zentrale Zeltteil.

Bei einer kuppelförmigen Zelthülle sind die zu einem Bogen aufspannbaren Durchgangsöffnungen in den Wölbsegmenten der Kuppel vorgesehen. Gleiches gilt für etwaige zusätzliche Eingänge.

So kann das zentrale Zeltteil mit einem oder mehreren Eingangsöffnungen versehen sein, die jeweils in einem der Wölbsegmente der kuppelförmigen Zelthülle vorgesehen sind. Damit sind die Flügelzeltteile über das zentrale Zeltteil zugänglich.

Statt oder zusätzlich zu dem Eingang in dem zentralen Zeltteil können jedoch auch die Flügelzeltteile separate Eingänge aufweisen, beispielsweise an der von dem zentralen Zeltteil abgewandten Seite.

Die Zeltteile können eine unterschiedliche Höhe besitzen. So ist es vorteilhaft eines, insbesondere das zentrale Zeltteil mit einer größeren Höhe auszubilden, um einen bequemen Aufenthaltsplatz zu erhalten, z.B. um darin zu stehen.

Nachstehend ist eine Ausführungsform des erfindungsgemäßen Zeltes anhand der Zeichnung näher erläutert.

295 108 27

04.07.95

5

Darin zeigen jeweils schematisch:

Fig. 1 und Fig. 2 eine perspektivische Ansicht des Zeltes von der einen bzw. anderen Seite; und

Fig.3 einen Schnitt durch zwei im Bereich einer Durchgangsöffnung zusammengefügte Zeltteile in etwa natürlicher Größe.

Gemäß Fig. 1 und Fig. 2 besteht das Zelt aus drei Zeltteilen 1, 2 und 3. Das Zeltteil 1 stellt das zentrale Zeltteil dar, die Zeltteile 2 und 3 bilden Flügel, die an das zentrale Zeltteil 1 angeschlossen sind.

Das zentrale Zeltteil 1 besteht aus einer kuppelförmigen Zelthülle 4 aus vier Wölbsegmenten 5 bis 8. Die Zelthülle 4 ist an den Kanten der Kuppel mit zwei bogenförmigen Stangen 9, 10 aufgespannt, die sich im Kuppelscheitel im rechten Winkel kreuzen.

Die Stange 9, 10 sind durch nicht dargestellte Schlaufen oder dergleichen Einhängenvorrichtungen geführt, die an den Kuppelkanten der Zelthülle 4 angenäht sind. Mit ihren Enden sind die Stangen 9, 10 in nicht dargestellte Ösen oder Stifte gesteckt, die an der Basis der kuppelförmigen Zelthülle 4 befestigt sind.

Wie aus Fig. 2 ersichtlich, weist die Zelthülle 4 des zentralen Zeltteil 1 an den beiden benachbarten Wölbsegmenten 7, 8 je einen Eingang 11, 12 auf.

Die beiden Flügelzeltteile 2, 3 sind gleich ausgebildet, so daß nachstehend nur das Zeltteil 2 näher beschrieben wird.

Das Zeltteil 2 besteht aus einer kuppelförmigen Zelthülle 13 aus vier Wölbsegmenten 14 bis 17. Mit ihren Kanten ist

295 108 27

04.07.95

6

die Zelthülle 13 an zwei bogenförmigen Stangen 18, 19 aufgespannt, die sich im Kuppelscheitel kreuzen. Die Stangen 18, 19 sind durch nicht dargestellte Schlaufen oder dergleichen Einhängenvorrichtungen geführt.

Das vom zentralen Zeltteil 1 abgewandeten Segment 15 und das dem zentralen Zeltteil 1 zugewandte Segment 16 sind tunnelförmig ausgebildet. Das Wölbsegment 15 erstreckt sich dabei von den beiden Wölbkanten an den Stangen 18, 19 zu einer weiteren bogenförmigen Stange 20. Von der bogenförmigen Stange 20 verläuft ein keilförmiger Abschnitt 21 der Zelthülle 13 nach unten, wobei die eine Keilfläche 22 mit einem Eingang versehen sein kann.

Die Kuppelsegmente 16 der Zelthülle 13 der beiden Flügelzeltteile 2 und 3 sind mit einer zu einem Bogen aufspannbaren Öffnung versehen; desgleichen die den Kuppelsegmenten 16 der beiden Flügelzeltteile 2 und 3 zugewandeten benachbarten Wölbsegmente 5 und 6 der Zelthülle 4 des zentralen Zeltteil 1.

Die Segmente 5 und 6 der Zelthülle 4 des zentralen Zeltteil 1 sind mit den Segmenten 16 der Zelthülle 13 der Flügelzeltteile 2 und 3 an den aufgespannten beiden Öffnungen unter Bildung eines Durchgangs mit einem Reißverschluß zusammenfügbar.

Dazu ist, wie in Fig. 3 gezeigt, an jedem Segment 6, 16 die Schließkette 23, 24 des Reißverschlusses angenäht. Der Reißverschluß erstreckt sich also über den gesamten Bogen der Durchgangsöffnung. Die Verbindung des Segments 5 des zentralen Zeltteils mit dem benachbarten Segment 16 des Flügelzeltteils 3 erfolgt in gleicher Weise.

Gemäß Fig. 1 und 2 ist zum Aufspannen der bogenförmigen Durchgangsöffnung eine bogenförmige Stange 25 vorgesehen. Gemäß Fig. 3 ist die bogenförmige Stange 25 in einer

295108 27

04.07.95

7

Schlaufe 26 geführt, die an dem Segment 6 der Hülle 4 des zentralen Zeltteils 1 angenäht ist.

Die bogenförmige Stange 25 ist im wesentlichen senkrecht angeordnet. Dazu ist das Wölbsegment 16 der Zelthülle 13 der Flügelzeltteile 2 und 3 durch ein gewölbtes Dreieck gebildet, dessen eine Kante entlang dem Bogen 25 und dessen beide andere Kanten entlang den bogenförmigen Stangen 18, 19 verlaufen. Desgleichen bilden die Wölbsegmente 5 und 6 der Zelthülle 4 des zentralen Zeltteils 1 gewölbte Dreiecke, wobei jedes der Dreiecke mit einer Kante entlang dem Bogen 25 und mit seinen beiden anderen Kanten entlang den bogenförmigen Stangen 9 und 10 verläuft.

Gemäß Fig. 1 und 2 ist das zentrale Zeltteil 1 höher ausgebildet als die Flügelzeltteile 2 und 3.

Die Flügelzeltteile 2 und 3 können mit Abspannleinen 27 versehen sein. Die Zelthüllen 4, 13 sind normalerweise mit angenähten Bodenwannen versehen. Insbesondere bei der Zelthülle 4 des zentralen Zeltteils 1 kann jedoch auf einen Boden verzichtet werden. Für die Flügelzeltteile 2 und 3 und gegebenenfalls für das zentrale Zeltteil 1 kann ein Überzelt vorgesehen sein.

295 108 27

04-07-95

1

SCHUTZANSPRÜCHE

1. Selbsttragendes Zelt, dadurch gekennzeichnet, daß es aus wenigstens zwei selbsttragenden Zeltteilen (1, 2, 3) besteht, deren Zelthülle (4, 13) jeweils mit mindestens einer zu einem Bogen aufspannbaren Öffnung versehen ist, und eine Verbindungsvorrichtung vorgesehen ist, mit der die Zelthüllen (4, 13) der beiden Zeltteile (1, 2, 3) an den aufgespannten beiden Öffnungen unter Bildung eines Durchgangs zusammenfügbar sind.
2. Zelt nach Anspruch 1, dadurch gekennzeichnet, daß die Zelteile (1, 2, 3) eine unterschiedliche Höhe aufweisen.
3. Zelt nach Anspruch 1, dadurch gekennzeichnet, daß das eine Zeltteil (1) ein zentrales Zeltteil bildet, dessen Zelthülle (4) wenigstens zwei jeweils zu einem Bogen aufspannbare Öffnungen aufweist und wenigstens zwei weitere Zellteile (2, 3) vorgesehen sind, deren Hüllen (13) jeweils wenigstens eine zu einem Bogen aufspannbare Öffnung besitzen, und eine Verbindungsvorrichtung vorgesehen ist, mit der die Zelthülle (4) des zentralen Zeltteils (1) mit der Zelthülle (13) der weiteren Zeltteile (2, 3) an den aufgespannten, einander zugewandten Öffnungen zusammenfügbar ist.

295 108 27

04.07.95


2

4. Zelt nach Anspruch 3, dadurch gekennzeichnet, daß das zentrale Zeltteil (1) wenigstens eine Eingangsöffnung (11, 12) aufweist.
5. Zelt nach Anspruch 3 oder 4, dadurch gekennzeichnet, daß das zentrale Zeltteil (1) höher ist als die weiteren Zeltteile (2, 3).
6. Zelt nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß zum Aufspannen der Durchgangsöffnungen eine bogenförmige Stange (25) vorgesehen ist, an der wenigstens eine der beiden durch die Verbindungsvorrichtung miteinander verbundenen Zelthüllen (4, 13) fixiert ist.
7. Zelt nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Zeltteile (1, 2, 3) durch eine kuppelförmige Zelthülle (4, 13) gebildet sind, die an sich kreuzenden bogenförmigen Stangen (9, 10; 18, 19) aufgespannt ist.
8. Zelt nach Anspruch 7, dadurch gekennzeichnet, daß die zu einem Bogen aufspannbaren Öffnungen an einem der Wölbsegmente (5, 6, 16) der kuppelförmigen Zelthülle (4, 13) der Zeltteile (1, 2, 3) vorgesehen sind.
9. Zelt nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die Bögen der aufgespannten Öffnungen der Zelthülle (4, 13) der Zeltteile (1, 2, 3) senkrecht angeordnet sind.
10. Zelt nach einem der vorstehenden Ansprüche, dadurch gekennzeichnet, daß die zum Zusammenfügen der Zelthüllen (4, 13) an den aufgespannten bogenförmigen Öffnungen vorgesehene Verbindungsvorrichtung durch eine Reißverschluß (23, 24) gebildet wird.

295108 27

04.07.95

FIG. 1



295 108 27

04.07.95

FIG. 2





FIG. 3

295 108 27

PUB-NO: DE029510827U1
DOCUMENT-IDENTIFIER: DE 29510827 U1
TITLE: Zelt
PUBN-DATE: September 14, 1995
PATENT-FAMILY-ID: 8010121

APPLICANT:

NAME	COUNTRY
ROYALBEACH SPIEL UND SPORTARTI	DE

APPL-NO: DE 29510827 U
APPL-DATE: July 4, 1995

PRIORITY-DATA:

PRIORITY-NO	PRIORITY-APPL-DATE
DE 29510827 U	19950704

CPC-CURRENT:

TYPE	CPC	DATE
CPCI	E04H15/18	20130101

INT-CL-CURRENT:

TYPE	IPC	DATE
IPCP	E04H15/18	20060101

EAST Search History

EAST Search History (Prior Art)

Ref #	Hits	Search Query	DBs	Default Operator	Plurals	Time Stamp
L1	1,301	(shelter tent) with hub	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/02 13:21
L2	79	1 same door	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/02 13:22
L4	1	("9470010").PN.	US-PGPUB; USPAT	OR	OFF	2021/01/02 14:20
L5	32	(US-20080017233-\$ or US-20060283103-\$ or US-20050189009-\$ or US-20070039639-\$ or US-20080264462-\$ or US-20120090455-\$ or US-20070125410-\$ or US-20100170162-\$).did. or (US-7533498-\$ or US-10858856-\$ or US-5159948-\$ or US-5394897-\$ or US-3955328-\$ or US-4886084-\$ or US-6145525-\$ or US-9752345-\$ or US-8381454-\$ or US-9103137-\$ or US-9714523-\$ or US-4649947-\$ or US-9869110-\$ or US-D652885-\$ or US-9470010-\$).did. or (US-3559353-\$).did. or (CA-2837116-\$ or DE-29510827-\$ or DE-29517290-\$ or DE-29716289-\$ or FR-2705718-\$).did. or (FR-2997984-\$).did.	US-PGPUB; USPAT; USOCR; FPRS; DERWENT	OR	ON	2021/01/02 14:30
S1	1	("10309093").PN.	USPAT	OR	OFF	2020/08/13 13:29
S2	2	((("4945936") or ("9243423"))).PN.	USPAT	OR	OFF	2020/08/13 13:43
S3	19	("20060260666" "20130008478" "20140182643" "4706696" "4846204" "4945936" "5069572" "5634483" "5666986" "6553698" "6772780" "6802329" "7131236" "7556054" "8925565" "9243423"	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:40

		"9243424" "9631393" "D454609").PN. OR ("10309093").URPN.				
S4	36	("1124420" "1666757" "2357056" "3000386" "3044477" "3794054" "3929146" "4033366" "4750509" "4865066").PN. OR ("4945936").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:42
S5	58	("20030037812" "2665171" "2812769" "3208083" "3391409" "4473986" "4512097" "4522008" "4561618" "4579066" "4637180" "4675923" "4689932" "4707953" "4747239" "4761929" "4800597" "4800663" "4838003" "4934396" "4970841" "5216763" "5230196" "5274980" "5375275" "5444946" "5446930" "5469587" "5542730" "5651228" "5794640" "5934301" "5943837" "6035877" "6141934" "6192633" "6237860" "6244011" "6725873" "6779538" "RE33710").PN. OR ("7131236").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:45
S6	50	("1484231" "1873178" "3899843" "3968808" "4268000").PN. OR ("4512097").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:46
S7	20	("3381923" "4512097" "4658560" "4663899" "4809471").PN. OR ("4995212").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:50
S8	97	("0014655" "0058283" "0379274" "1078069" "20030005953" "20070051399" "20070215192" "2113118" "2306706" "2336116" "2448895" "2530765" "2555220" "2731972" "2948287" "2953145" "2962034" "2984249" "3054413" "3177882" "3333373" "3738378" "3810482" "3929146" "4077417" "4148332" "4201237" "4280521" "4285354" "4627210" "4637748" "4750509" "4787182" "4819680" "4838003" "4941499" "4971090" "5195551" "5293890" "5328286" "5333634" "5361794" "5423341" "5617681" "5628338" "5634483" "5666986" "5732726" "5797695" "5884646" "5943837" "6021795" "6032430" "6167898" "6286530" "6296415" "6516823" "6591571" "6604844" "6666223" "6772780" "6776179" "6854476" "6868858"	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 13:54

		"6874519" "6892744" "7025075" "7040585" "7059094" "7311113" "7481235" "7546845" "D544941" "RE40544").PN. OR ("9243424").URPN.				
S9	2,467	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/09/01 14:45
S12	23	("3507526").URPN.	USPAT	OR	ON	2020/09/01 17:03
S13	54	("1203267" "1291388" "1388657" "1403309" "4097168" "4172678" "4337937" "4449843" "4509381" "4657428" "4769897").PN. OR ("4904108").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 17:08
S14	2,467	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/09/01 17:16
S15	1,140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/09/01 17:16
S16	1,073	S15 not S14	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:18
S17	1	("9605441").PN.	USPAT	OR	OFF	2020/09/01 17:37
S18	112	("0014655" "0058283" "0379274" "1061547" "1129194" "1347107" "20010050098" "20030005953" "20070051399" "20070215192" "20120318316" "20130014794" "20140076372" "20140109945" "20140261601" "20140290710" "20150083177" "20150275541" "2113118" "2306706" "2448895" "2530765" "2555220" "2716993" "2731972" "2948287" "2962034" "2984249" "3054413" "3333373" "3738378" "3766932" "3810482"	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 17:37

		"3929146" "4077417" "4148332" "4201237" "4280521" "4285354" "4627210" "4637748" "4750509" "4787182" "4819680" "4838003" "4941499" "4944321" "4971090" "4998552" "5263507" "5293890" "5328286" "5333634" "5361794" "5423341" "5617681" "5628338" "5634483" "5666986" "5732726" "5771654" "5797695" "5884646" "5943837" "6021795" "6032430" "6167898" "6283136" "6286530" "6296415" "6463948" "6516823" "6591571" "6604844" "6666223" "6772780" "6776179" "6854476" "6868858" "6874519" "6892744" "7025075" "7040585" "7059094" "7311113" "7316239" "7481235" "7546845" "8156952" "8186369" "8910648" "D544941" "D705884" "RE40544").PN. OR ("9605441").URPN.				
S19	3,650	S12 S13 S14 S15 S16 S17 S18	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:45
S20	2,298	y10t403/342,347.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:45
S21	2,112	S20 not S19	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:46
S22	3,722	y10t403/4949,4966.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:51

S23	5,762	S19 S21	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:51
S24	3,694	S22 not S23	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:51
S25	1,458	S22 not S23	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:51
S26	22	(US-20060260666-\$ or US-20070051399-\$ or US-20150167343-\$ or US-20150240513-\$).did. or (US-3507526-\$ or US-3968808-\$ or US-4512097-\$ or US-4838003-\$ or US-4945936-\$ or US-4986016-\$ or US-4995212-\$ or US-6223482-\$ or US-6553698-\$ or US-7131236-\$ or US-8360085-\$ or US-8496019-\$ or US-9243424-\$ or US-9605441-\$).did. or (CN-201129060-\$ or CN-201169953-\$ or CN-201798187-\$ or US-20150167343-\$).did.	US-PGPUB; USPAT; DERWENT	OR	ON	2020/09/01 17:54
S27	7,223	S23 S25 S26	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:55
S28	0	e04b1/1903,3441.cpc	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:56
S29	4,303	e04b1/1903,3441.cpc.	US-PGPUB; USPAT; USOCR;	OR	ON	2020/09/01 17:56

			FPRS; EPO; JPO; DERWENT; IBM_TDB			
S30	3,682	S29 not S27	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:56
S31	1,310	S29 not S27	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:56
S32	3,757	e04h15/34,44,48,50.cpc.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:57
S33	3,148	S32 not S27	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:57
S34	3,148	S32 not S27	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:57
S35	3,148	S32 not S27	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/09/01 17:58
S36	29	("3529508" "4571111" "4638133").PN. OR ("5017068").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/09/01 18:02
S37	23	("3507526").URPN.	USPAT	OR	ON	2020/09/01 18:12
S38	19	("2003/0074845").URPN.	USPAT	OR	ON	2020/09/01 18:26

S39	484	(135/28).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/09/01 18:38
S40	1	("8448656").PN.	US-PGPUB; USPAT	OR	OFF	2020/09/02 17:07
S41	1	("8360085").PN.	US-PGPUB; USPAT	OR	OFF	2020/09/02 17:07
S42	4	((("10309093") or ("9243423") or ("4945936") or ("5666986"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/09/02 17:20
S43	2	("20150240513").PN.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/09/02 18:04
S44	1	("4995212").PN.	USPAT	OR	OFF	2020/11/24 13:48
S45	4	((("4995212") or ("20150167343") or ("9243423") or ("6223482"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/11/24 13:51
S46	3	((("10309093") or ("9243424") or ("20150240513"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/12/16 16:25
S47	5	((("10309093") or ("9243424") or ("4995212") or ("6223482") or ("20150240513"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/12/16 16:26
S48	6	((("10309093") or ("9243424") or ("9243423") or ("4995212") or ("6223482") or ("20150240513"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/12/16 16:27
S49	2	((("9243423") or ("20150240513"))).PN.	US-PGPUB; USPAT	OR	OFF	2020/12/16 16:43
S50	20	("2003/0074845").URPN.	USPAT	OR	ON	2020/12/17 14:45
S51	42	("20020066239" "20030074845" "20030164185" "3968808" "4026313" "4156433" "4193414" "4280521" "4290244" "4334660" "4437275" "4473986" "4512097" "4522008" "4561618" "4579066" "4637180" "4666102" "4689932" "4747239" "4761929" "4800663" "4838003" "4970841" "5230196" "5274980" "5444946" "5651228" "5943837" "6141934" "6196242" "6401735" "6941704" "RE33710").PN. OR ("7712261").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/12/17 14:48

S52	40	("2659618" "3381923" "3507526" "3563580" "3710806" "3810482" "3830031" "3888056" "3914063" "4111574" "4241746" "4393887" "4512097" "4809471").PN. OR ("4986016").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2020/12/17 14:49
S53	2,467	((52/81.3) or (52/646) or (52/655.1) or (52/655.2)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/12/17 14:50
S54	1,140	((135/909) or (135/120.3) or (135/159) or (135/147) or (135/135)).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/12/17 14:51
S55	2,316	y10t403/342,347.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:51
S56	3,791	y10t403/4949,4966.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:51
S57	0	e04b1/1903,3441.cpc	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:51
S58	4,350	e04b1/1903,3441.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:51
S59	484	(135/28).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2020/12/17 14:51

S60	9,499	(E04B1/1903 or E04H15/44 or E04H15/50 or E04H15/36 or E04B2001/1957 or E04B2001/1927).cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:52
S61	19,318	S53 S54 S55 S56 S58 S59 S60	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:53
S62	82	S61 and @pd>"20200902"	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:53
S63	1	((("DLX") near3 ("ENTERPRISES") near3 ("LLC"))).AS,AANM.	USPAT	OR	ON	2020/12/17 14:54
S64	15	((("URHAUSEN") near3 ("Jonathan")) OR ((("BARR") near3 ("Adam"))) OR ((("BIERMAN") near3 ("Donald"))) OR ((("TILLER") near3 ("Matt")))).INV.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2020/12/17 14:54
S65	26,135	135/\$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:57
S66	242,614	52/\$.ccls.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:57
S67	266,593	S65 S66	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:57

S68	1,508	S67 and (hub node).clm.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:57
S69	965	S68 and (frame framing framework)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:58
S70	1,060	S68 and (frame framing framework pole)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 14:58
S71	701	S70 and (expand expanded deploy deployed fold folded folding collapse collapsed collapsible)	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 15:00
S72	6	("4689932" "8082938").PN.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2020/12/17 15:16
S73	2	(US-7712261-\$ or US-8082938-\$).did.	USPAT	OR	ON	2020/12/17 15:17
S79	2	(US-7712261-\$ or US-8082938-\$).did.	USPAT	OR	ON	2020/12/17 16:41
S81	38	("10309093" "20060260666" "20070051399" "20130008478" "20140182643" "20150167343" "20150240513" "20180155952" "3929146" "4658560" "4706696" "4846204" "4945936" "4995212" "5017068" "5069572" "5634483" "5666986" "5943837" "6223482" "6553698" "6553699" "6758354" "6772780" "6802329" "7131236" "7556054" "8360085" "8448656"	US-PGPUB; USPAT	OR	ON	2021/01/01 13:27

		"8496019" "8925565" "9163425" "9243423" "9243424" "9605441" "9631393" "D454609" "D544941").PN.				
S82	32	(US-20060260666-\$ or US- 20070051399-\$ or US-20150167343-\$ or US-20150240513-\$ or US- 20030074845-\$ or US-20080017233-\$).did. or (US-4945936-\$ or US- 7131236-\$ or US-4512097-\$ or US- 3968808-\$ or US-4995212-\$ or US- 6223482-\$ or US-6553698-\$ or US- 9243424-\$ or US-3507526-\$ or US- 8496019-\$ or US-9605441-\$ or US- 8360085-\$ or US-5017068-\$ or US- 7533498-\$ or US-7712261-\$ or US- 8448656-\$ or US-8082938-\$).did. or (US-3507526-\$ or US-3559353-\$).did. or (CN-201129060-\$ or CN- 201169953-\$ or CN-201798187-\$ or US-20150167343-\$ or EP-222437-\$ or CN-104314360-\$ or US-20110017249-\$).did.	US-PGPUB; USPAT; USOCR; DERWENT	OR	ON	2021/01/01 14:19
S83	17	S82 not S81	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 14:19
S84	423	(135/97).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/01/01 14:21
S85	1	("4063566").PN.	US-PGPUB; USPAT	OR	OFF	2021/01/01 14:22
S86	35	("2263867" "3397710" "3699986" "3874396").PN. OR ("4063566").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:22
S87	10	("20060283103" "3374797" "3533202" "3773061" "4063566" "5159948" "6357462" "8001987").PN. OR ("10858856").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:22
S88	84	("1420671" "2508679" "3017893" "3222067" "3802133" "3925942" "3965915" "4011880" "4063566" "4886084").PN. OR ("5222513").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:23

S89	40	("0426112" "0634759" "1111040" "1214928" "1691411" "2032693" "2061510" "2372187").PN. OR ("3802133").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:24
S90	110	("3397710" "3699986" "3802133" "3874396" "3955328" "4063566" "4078572" "4815490" "4886084" "4979532" "5078096" "5222513").PN. OR ("5394897").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:24
S91	33	("2841832" "3468083" "3566554" "3618273" "3690077" "3769766" "3790657" "3813835").PN. OR ("3955328").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:24
S92	45	("2255837" "2787321" "2808065" "2875824" "3834400" "3925828" "3968809" "4065166" "4102353" "4145855" "4285354" "4398376" "4561227" "4637748" "4979532" "5058340" "5170811" "5226264" "5394897" "5457922").PN. OR ("6145525").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:26
S93	80	("1728356" "20020134415" "20040238021" "20050100400" "20050189009" "20060060235" "20080083443" "20080210283" "20090084420" "20100200038" "20110168221" "20130074894" "20130306121" "3368575" "3550601" "3699986" "3709237" "3810482" "3847170" "3941140" "3958289" "3965915" "4026312" "4063566" "4067346" "4077417" "4239247" "4285355" "4526391" "4632138" "4730569" "4819680" "4858635" "4917217" "4941499" "4979532" "5050526" "5159948" "5222513" "5251921" "5382111" "5394897" "5402596" "5575490" "5592961" "5593061" "5620396" "5628338" "5820189" "5906217" "6014833" "6098335" "6145525" "6192633" "6360761" "6565139" "6701948" "6782905" "6854476" "7040335" "7185666" "7614415" "7743781" "7958904" "8915258" "9085914" "9103137" "9163425" "9238924" "9470010" "D313061" "D339842").PN. OR ("9752345").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:28

S94	36	("2910994" "3261659" "3345996" "3501213" "3766844" "4304224" "4348777" "4442162" "4675923" "4707953" "4800597" "4858256" "5090972" "5326211" "5331991" "5394897" "5537784" "5551102" "5562539" "6021794").PN. OR ("6390110").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:30
S95	27	("20070039639" "3421188" "3503101" "4369356" "4649947" "4838294" "4862563" "5008987" "5076288" "5222513" "5289619" "5394897" "5535928" "5819474" "5894642" "5970541" "6041454" "6049953" "6568981" "7273061" "7350244" "9103137" "9303426" "9470010").PN. OR ("9714523").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:32
S96	67	("1666757" "1884449" "20020104561" "20040238021" "20050189009" "20050205124" "20060096631" "20060118155" "20070251562" "20090056781" "20090065037" "20090250089" "20100180923" "20110048483" "20110232712" "20120211041" "20130061896" "20150337557" "2137625" "2513729" "2928403" "3699986" "3874396" "4102352" "4641676" "4793371" "4941500" "4947884" "5117853" "5394897" "5441069" "5490532" "5634483" "6273114" "6357462" "6666223" "7588045" "8001987" "8132584" "8316508" "8763621" "8776815" "9470010" "D692083" "D779611").PN. OR ("9869110").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:34
S97	37	("4078572" "4979532" "5222513" "6273114" "6554013" "D351011" "D369638" "D382621" "D382622").PN. OR ("D652885").URPN.	US-PGPUB; USPAT; USOCR	OR	ON	2021/01/01 14:36
S98	2,282	e04h15/18.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 14:44
S99	2,167	S98 not S84	US-PGPUB; USPAT;	OR	ON	2021/01/01 14:44

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S100	2,590	S99 S84	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 15:05
S101	1	((("DLX") near3 ("ENTERPRISES") near3 ("LLC"))).AS,AANM.	USPAT	OR	ON	2021/01/01 15:05
S102	15	((("URHAUSEN") near3 ("Jonathan")) OR ((("BARR") near3 ("Adam"))) OR ((("BIERMAN") near3 ("Donald")))).INV.	US-PGPUB; USPAT; USOCR; EPO; JPO; DERWENT	OR	ON	2021/01/01 15:06
S103	2,475	e04h15/36,44.cpc.	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 15:06
S104	2,160	S103 not S100	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 15:06
S105	4	("2007/0125410").URPN.	USPAT	OR	ON	2021/01/01 15:12
S106	4,327	S99 S104	US-PGPUB; USPAT; USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB	OR	ON	2021/01/01 15:16
S107	533	(52/79.9).CCLS.	US-PGPUB; USPAT; FPRS; EPO; JPO; DERWENT	OR	OFF	2021/01/01 15:16
S108	532	S107 not S106	US-PGPUB; USPAT;	OR	ON	2021/01/01 15:16

			USOCR; FPRS; EPO; JPO; DERWENT; IBM_TDB			
S109	8	("2010/0170162").URPN.	USPAT	OR	ON	2021/01/01 15:18
S110	40	(US-20080017233-\$ or US-20060283103-\$ or US-20050189009-\$ or US-20070039639-\$ or US-20080264462-\$ or US-20120090455-\$ or US-20070125410-\$ or US-20100170162-\$).did. or (US-7533498-\$ or US-4063566-\$ or US-10858856-\$ or US-5159948-\$ or US-5222513-\$ or US-3802133-\$ or US-5394897-\$ or US-3955328-\$ or US-4886084-\$ or US-6145525-\$ or US-9752345-\$ or US-6390110-\$ or US-8381454-\$ or US-9103137-\$ or US-9714523-\$ or US-4649947-\$ or US-9869110-\$ or US-D652885-\$ or US-4064663-\$ or US-2691291-\$).did. or (US-3559353-\$).did. or (CA-2837116-\$ or DE-29510827-\$ or DE-29517290-\$ or DE-29716289-\$ or FR-2207225-\$ or FR-2705718-\$).did. or (CA-2890530-\$ or FR-2997984-\$).did.	US-PGPUB; USPAT; USOCR; FPRS; DERWENT	OR	ON	2021/01/01 15:21

1/2/2021 4:44:44 PM

C:\Users\rcanfield\Documents\EAST\Workspaces\16861012.wsp



19 BUNDESREPUBLIK
DEUTSCHLAND



DEUTSCHES
PATENTAMT

12 **Gebrauchsmuster**
10 **DE 297 16 289 U 1**

51 Int. Cl.⁶:
E 04 H 15/06
E 04 H 15/18
E 04 H 15/54
B 60 P 3/37

21	Aktenzeichen:	297 16 289.6
22	Anmeldetag:	10. 9. 97
47	Eintragungstag:	30. 10. 97
43	Bekanntmachung im Patentblatt:	11. 12. 97

DE 297 16 289 U 1

73	Inhaber:	Mehler AG, 36043 Fulda, DE
74	Vertreter:	HOFFMANN · EITLE, 81925 München

54 Vorzelt für Wohnwagen und Tunnelmodul zur Erweiterung solcher Vorzelte

DE 297 16 289 U 1

10.09.97

71 287 p/p7/gw/bn

Mehler AG
Edelzellerstr. 44
D-36043 Fulda

Vorzelt für Wohnwagen und Tunnelmodul
zur Erweiterung solcher Vorzelte

Technisches Gebiet

Die vorliegende Erfindung betrifft Vorzelte für Wohnwagen, Campingwagen oder ähnliches, die eine eigene Stützkonstruktion, zumindest einen heraustrennbaren Vorderwandteil und/oder zumindest einen heraustrennbaren Seitenwandteil aufweisen. Die Erfindung betrifft ferner ein Tunnelmodul, das zur Erweiterung gattungsgemäßer Vorzelte dient.

Stand der Technik

Es sind viele unterschiedliche gattungsgemäße Vorzelte bekannt. Im allgemeinen weisen diese Vorzelte eine im wesentlichen kubische Grundgestalt auf, wobei eine Wand des Kubusses weggelassen ist, damit das Vorzelt mit dieser Seite an einen Wohnwagen oder ähnliches angebaut werden kann. Typischerweise beinhalten derartige Vorzelte eine eigene Stützkonstruktion, in der Regel durch zusammensteckbare Rohrstücke und Winkелеlemente gebildet.

Es ist ebenfalls bekannt, derartige Vorzelte mit Seiten- bzw. Vorderwänden auszurüsten, die ganz oder zum Teil aus dem

10.09.97

2

Vorzelt heraustrennbar sind. Das Heraustrennen der Wände bzw. Wandteile dient einerseits dazu, dem Bedarf der Zeltbenutzer an Frischluft Rechnung zu tragen, andererseits dazu, den Benutzern ein Zelt zur Verfügung zu stellen, was eine variable Größe aufweist. Zur Erweiterung des Vorzeltvolumens wurden bisher erkerähnliche Erweiterungselemente angeboten, die an der Naht, die sich nach Heraustrennen der Wände bzw. Wandteile ergibt, befestigt werden können. Nach Heraustrennen der Wand bzw. der Wandteile müssen diese dann im Vorzelt, Wohnwagen oder ähnlichem verstaut werden, was unter Umständen einen erheblichen Platzbedarf erfordert.

Aus dem entfernt liegenden technischen Gebiet der Steilwandzelte, an deren Konstruktion allerdings andere Anforderungen gestellt werden, als an die von Vorzelten, sind erweiterungsfähige Zelte bekannt. So ist beispielsweise in der DE 295 17 290 U1 ein Zelt in Modulbauweise offenbart, wobei die Module aus einzelnen Bauelementen gebildet sind. Das bekannte Steilwandzelt ermöglicht es dem Benutzer, das Zelt je nach Bedarf in unterschiedlichen Varianten zu erweitern oder zu vergrößern oder auch mehrere Zelte zu einer Baueinheit zu kombinieren. So ist dieses Zelt mit Bauelementen in Form einer Apsis und Bauelementen mit teilzylindrischer Form und halbkreisförmigem oder annähernd halbkreisförmigem Querschnitt ausgerüstet. Die stirnseitige bogenförmige Nahtlinie des apsisförmigen Bauelements ist ebenso wie der stirnseitige Bereich des teilzylindrischen Bauelements mit einem Reißverschluß versehen, wodurch diese beiden Bauteile miteinander verbindbar sind.

Unter Berücksichtigung des Standes der Technik ist es Aufgabe der vorliegenden Erfindung, ein Vorzelt für Wohnwagen, Campingwagen oder ähnliches bereitzustellen, das mit einfachen Mitteln schnell erweiterbar ist und ein Tunnelmodul für derartige Vorzelte bereitzustellen, mit dem Vorzelte einfach und schnell erweiterbar sind.

Darstellung der Erfindung

Erfindungsgemäß wird daher ein Vorzelt für Wohnwagen oder ähnliches bereitgestellt, mit einer eigenen Stützkonstruktion, zumindest einem heraustrennbaren Vorderwandteil und/oder zumindest einem heraustrennbaren Seitenwandteil, das dadurch gekennzeichnet ist, daß die Schnittstellen zu heraustrennbaren Vorderwandteilen und Vorzelts einerseits und heraustrennbaren Seitenwandteilen und Vorzelts andererseits identisch ausgebildet und angeordnet sind, an den Schnittstellen zur Erweiterung des Vorzelts ein im wesentlichen kubisches Tunnelmodul anbaubar ist und sowohl die heraustrennbaren Vorderwandteile, als auch die heraustrennbaren Seitenwandteile als Abschluß des erweiterten Vorzelts verwendbar sind.

Gleichermaßen wird erfindungsgemäß ein Tunnelmodul zur Erweiterung von Vorzelten von Wohnwagen oder ähnlichem bereitgestellt, von im wesentlichen kubischer Form und mit einer eigenen Stützkonstruktion, Aufnahmeelementen für diese Stützkonstruktion, ersten Befestigungselementen in einem ersten Randbereich des Tunnelmoduls, zweiten Befestigungselementen in einem zweiten Randbereich des Tunnelmoduls, wobei erste und zweite Befestigungselemente als miteinander in Eingriff bringbare Gegenstücke ausgebildet und angeordnet sind.

Die identische Anordnung und Ausbildung der Schnittstellen des erfindungsgemäßen Vorzelts gewährleistet, daß dessen Raumaufteilung veränderbar ist. Beispielsweise läßt sich der Eingangsbereich von der Vorderwand zu einer Seitenwand verlegen. Ferner ermöglicht es die Tatsache, daß erfindungsgemäß an den Schnittstellen des Zelts zur Erweiterung ein im wesentlichen kubisches Modul anbaubar ist, daß der Benutzer des Vorzelts bei eventueller Erweiterung desselben diese Erweiterung an einer beliebigen Seite vorsehen kann. Das erfindungsgemäße Tunnelmodul ermöglicht es

erstmalig durch Ausbildung und Anordnung von ersten und zweiten Befestigungselementen als miteinander in Eingriff bringbare Gegenstücke, daß das Tunnelmodul mit den ersten Befestigungselementen in einem ersten Randbereich an einem Vorzelt befestigbar ist und daß der zum Zweck der Erweiterung herausgetrennte Wandteil des Vorzelts an zweiten Befestigungselementen im zweiten Randbereich des Tunnelmoduls dort als Abschluß der Erweiterung anbringbar ist. Erweiterte Vorzelte sind folglich wetterdicht, die Erweiterung läßt sich platzsparend durchführen und ist kostengünstig. Die kubische Formgebung des Tunnelmoduls stellt sicher, daß Vorzelt und Tunnelmodul ein einheitliches Erscheinungsbild aufweisen und der ästhetische Gesamteindruck nicht getrübt wird. Durch das Bereitstellen einer eigenen Stützkonstruktion ist das Tunnelmodul mit einer ausreichenden Stabilität versehen, so daß die Erweiterung eines Vorzelts nicht dazu führt, daß das Vorzelt bezüglich seiner Festigkeit übermäßig beansprucht wird. Sowohl Vorzelt als auch Tunnelmodul weisen folglich eine ausreichend hohe Eigenfestigkeit auf. Bei entsprechender Gestaltung des Tunnelmoduls ist erfindungsgemäß der Vorteil gegeben, auch konventionelle Vorzelte mit dem neuartigen Tunnelmodul erweitern zu können.

Um sicherzustellen, daß einerseits das erfindungsgemäße Vorzelt nach Erweiterung im gesamten Bereich gleichwertig nutzbaren Raum bietet und andererseits das erfindungsgemäße Tunnelmodul eine Erweiterung bietet, die gleichermaßen nutzbar ist, wie das zu erweiternde Vorzelt, ist einerseits vorgesehen, daß die heraustrennbaren Vorderwandteile und die heraustrennbaren Seitenwandteile des Vorzelts eine Höhe aufweisen, die im wesentlichen der Eingangshöhe des Vorzelts entspricht und andererseits, daß das Tunnelmodul eine Höhe aufweist, die im wesentlichen der eines üblichen Vorzelts entspricht.

Um die Festigkeit eines erweiterten erfindungsgemäßen Vorzelts sicherzustellen, ist an die Stützkonstruktion des

10.09.97

5

Vorzelts eine eigene Stützkonstruktion des Tunnelmoduls anbringbar.

Diese eigene Stützkonstruktion des Tunnelmoduls weist vorteilhafterweise einen Giebel mit einem Winkel von ca. 165° auf. Der Giebelwinkel ist vorgesehen, um den Ablauf von Regenwasser sicherzustellen, wobei sich ein Winkel von 165° als idealer Kompromiß zwischen geringem Windfang und guten Ablaufbedingungen herausgestellt hat. Um diesen Kompromiß weiterhin zu verbessern, ist erfindungsgemäß ebenfalls vorgesehen, daß der Scheitel des Giebelwinkels außermittig zum Tunnelelement angeordnet ist, vorzugsweise in Richtung des Vorzelts. Gemäß einer vorteilhaften Weiterbildung ist das erfindungsgemäße Tunnelmodul mit ersten Befestigungselementen versehen, die durch eine erste Reißverschlußhälfte, ein Kederband oder ein Klettband gebildet sind und mit zweiten Befestigungselementen versehen, die entsprechend durch eine zweite Reißverschlußhälfte, eine Kederschiene oder ein Klettflausch gebildet sind. Durch eine derartige Ausgestaltung der Befestigungselemente wird die Forderung nach einer einfachen und schnellen aber gleichzeitig sicheren und wetterfesten Befestigung unter geringen Kosten noch besser erfüllt.

Damit die Festigkeit des Tunnelmoduls weiter verbessert ist, sind verschiedenartige Aufnahmeelemente zur Aufnahme von Verspannungs- bzw. Abspanneinrichtungen und einer Stützkonstruktion vorgesehen, die Ösen, verstärkte Ösen, Hohlsäume, verschließbare Hohlsäume und/oder Ankerhaken umfassen.

Um das erfindungsgemäße Tunnelmodul bezüglich der Wetterfestigkeit vorteilhaft weiterzubilden ist einerseits vorgesehen, es einstückig auszubilden, andererseits vorgesehen, das Dach und die Seitenteile bzw. die Seitenteile und den Boden durch Kappnähte derart miteinander zu verbinden, daß die Nahtgestaltung in Abflußrichtung des

Regenwassers keine Sicken oder Vertiefungen aufweist, die ein Eindringen des Wassers ins Zeltinnere begünstigen würden.

Kurze Beschreibung der Zeichnungen

Weitere Merkmale und Vorteile der vorliegenden Erfindung ergeben sich aus der detaillierten Beschreibung von Ausführungsbeispielen, die zur weiteren Erläuterung und zum besseren Verständnis der Erfindung unter Bezugnahme auf die beigefügten Zeichnungen folgt, in denen:

- Fig. 1 eine perspektivische Ansicht eines erfindungsgemäßen Vorzelts und erfindungsgemäßer Tunnelmodule,
- Fig.2-7 die einzelnen Elemente, aus denen das dargestellte Ausführungsbeispiel eines erfindungsgemäßen Tunnelmoduls aufgebaut ist,
- Fig. 8 schematisch ein Tunnelmodul im teilmontierten Zustand und
- Fig. 9 die Stützkonstruktion des ausgeführten Tunnelmoduls zeigt.

Beschreibung von Ausführungsbeispielen

Im folgenden wird ein Ausführungsbeispiel eines erfindungsgemäßen Vorzelts und ein Ausführungsbeispiel eines erfindungsgemäßen Tunnelmoduls unter Bezugnahme auf die Zeichnungen näher erläutert.

Aus Fig. 1 geht, schematisch dargestellt, der Aufbau eines teilweise durch Tunnelmodule 20 erweiterten Vorzelts 10 hervor. Es ist ersichtlich, daß das Vorzelt eine Vorderwand mit zwei Vorderwandteilen 11, 12 umfaßt. Eines dieser Vorderwandteile 11 befindet sich im Vorzelt, ein zweites

Vorderwandteil 12 ist zur Erweiterung des Vorzelts aus der Vorderwand herausgetrennt und als Abschluß des Tunnelmoduls 20 in dieses eingesetzt. Gleichmaßen ist eine Seitenwand 13 des Vorzelts 10 aus diesem herausgetrennt und als Abschluß an ein Tunnelmodul angebracht, das das Vorzelt seitlich erweitert. Sämtliche Befestigungen zwischen Wand- bzw. Wandteilen 11, 12, 13 und Vorzelt 10 bzw. zwischen Wand- bzw. Wandteilen 11, 12, 13 und Tunnelmodulen 20 sowie die Befestigungen zwischen Tunnelmodulen 20 und Vorzelt 10 sind in den dargestellten Ausführungsbeispielen durch Reißverschlüsse 18 gebildet. Die Tunnelmodule 20 sind von einer Stützkonstruktion getragen, von der von außen lediglich Dorne 16 sichtbar sind, die außen nach oben über die Tunnelmodule 20 vorstehen und relativ zu diesen durch Dichtelemente (nicht dargestellt), wie z.B. Gummilippen oder Aufsatzstücke, abgedichtet sind. Bodenseitig sind Vorzelt 10 und Tunnelmodule 20 durch Faulstreifen 17 abgeschlossen. Die Faulstreifen gewährleisten einen idealen Wasserablauf und gewährleisten durch ihre Befestigung mittels Ankern oder ähnlichem im Boden, daß auch ein winddichter Abschluß gegeben ist.

Die Fig. 2 bis 7 zeigen Einzelteile, aus denen ein Tunnelmodul vorzugsweise aufgebaut ist und verdeutlichen qualitativ die Größenverhältnisse zwischen ihnen.

So zeigt Fig. 2 ein Dachteil 22 und Fig. 3 eine Dachblende 23. Fig. 4 gibt ein geschlossenes Seitenteil 24 des Tunnelmoduls wieder, Fig. 5 ein Seitenteil 26, das mit einem Fenster 14 versehen ist. Fig. 6 illustriert einen Faulstreifen 17 und Fig. 7 einen Hohlraum 28. Alle in den Fig. 2 bis 7 dargestellten Bauteile sind im Grundriß vor dem Vernähen dargestellt, mit Ausnahme des Seitenteils 26, in das bereits das Fenster 14 eingenäht ist.

Aus Fig. 7 ergibt sich der Aufbau eines Hohlraums im einzelnen, der prinzipiell aus einem rechteckigen Textilstück

gefertigt wird. Auf dieses Textilstück werden in einem Randbereich ein Klettband 32, im anderen Randbereich von der Rückseite ein Klettflausch 34 befestigt, typischerweise durch Nähen oder Kleben. Diese beiden Klettbefestigungselemente werden miteinander verbinden, nachdem sie um die Stützkonstruktion geschlungen wurden. Im Mittelbereich des Hohlsaums befindet sich eine Markierung 30 für die Naht, an der Hohlraum 28 und Tunnelelement 20 miteinander vernäht werden. Durch eine derartige Befestigung des Tunnelelements an der Stützkonstruktion ist somit eine eindeutige Lagefixierung und ein sicherer Halt gewährleistet.

Fig. 8 zeigt ein Tunnelmodul 20 kurz vor der Fertigstellung. Das Tunnelmodul 20 ist im Grundriß dargestellt, d.h. in „aufgeklappter“ Position. In der Figur sind von oben nach unten folgende Elemente erkennbar: Faulstreifen 17, Seitenteil 26 mit Fenster 14, Dachteil 22 mit Dachblende 23, geschlossenes Seitenteil 24 und ein weiterer Faulstreifen 17. Die Orientierung des Tunnelmoduls 20 in der Figur ist dergestalt, daß die rechts dargestellte Seite zur späteren Befestigung an dem Vorzelt dient, die linke Seite die später vom Vorzelt abgewandte Seite darstellt.

Die aufgezählten Bauteile sind dabei vorzugsweise derart miteinander verbunden, daß sich die Überlappung in der Zeichnungsebene von der Mitte nach oben bzw. unten aus der Zeichnungsebene hinaus aufeinanderliegend ergibt; d.h. das in der Mitte dargestellte Dachteil 22 liegt zuunterst, die Seitenteile 26, 24 darauf und die Faulstreifen 17 auf den jeweiligen Seitenteilen. Bei in endgültig kubische Form geklapptem Tunnelmodul 20 stellt dies sicher, daß keine Sicken, Falze oder ähnliches gebildet werden, durch die ein Wassereintritt im Stoß- beziehungsweise Nahtbereich begünstigt würde. In der Fig. 8 sind ebenfalls die Kappnähte 36 als unterstützende Maßnahme zur Vermeidung von Wassereintritt im Nahtbereich schematisch dargestellt, mit denen Dachteil 22 und Seitenteile 24, 26 verbunden sind.

Dachteil 22 und Seitenteile 24, 26 sind entsprechend der Abbildung derart miteinander vernäht, daß das Dachteil 22 in Ablaufrichtung des Wassers die Seitenteile umgreift.

Wie bereits erwähnt, erfolgt die Befestigung des Tunnelmoduls 20 an Vorzelten mit geeigneten Befestigungsmitteln, in dem dargestellten Ausführungsbeispiel durch Reißverschlüsse 18. In der Fig. 8 ist das Tunnelmodul vor Befestigung der Reißverschlüsse 18 an ihm abgebildet. Rechtsseitig des Dachs 22 und der Seitenteile 24, 26 sind die Reißverschlüsse geschlossen dargestellt. Zur Befestigung werden die Reißverschlüsse getrennt, ein erstes Teil wird an der später dem Zelt benachbarten Seite befestigt, vorzugsweise durch Annähen, das Gegenstück 18' auf der anderen Seite. Das Gegenstück 18' ist symbolisch in der Fig. 8 linksseitig des Dachs 22 bzw. der Seitenteile 24, 26 abgebildet. Bei der Befestigung der Reißverschlußhälften 18, 18' ist darauf zu achten, daß der Reißverschluß, der im Dachbereich befestigt werden soll, in seinen Längenabmessungen die entsprechende Abmessung des Dachteils geringfügig unterschreitet und die Reißverschlüsse, die an den Seitenteilen befestigt werden sollen, in ihren Längenabmessungen die der Seitenteile geringfügig überschreiten. Bei Abstimmung der Längen und der endseitigen Befestigungspunkte der jeweiligen Reißverschlüsse ist darauf zu achten, daß dem Reiter des Reißverschlusses ausreichend Raum zur Verfügung gestellt wird, so daß er nicht mit dem angrenzenden Reißverschluß oder dessen Reiter kollidiert.

Zur Aufnahme der Stützkonstruktion sind an dem Tunnelmodul 20 verschiedene Klettverschlüsse 38, Hohlsäume 28 und Dornöffnungen 19 vorgesehen. Vorzeltseitig sind die Befestigungselemente unmittelbar im Randbereich des Tunnelmoduls angeordnet, an der dem Vorzelt entfernt liegenden Seite geringfügig vom Rand beabstandet. Zusätzlich zu diesen Vorkehrungen befinden sich in den Faulstreifen 17 Ankerhaken zur Aufnahme von Abspannelementen. Im Dachbereich

werden Tunnelmodul 20 und Stützkonstruktion durch die Hohlsäume in bereits erwähnter Art befestigt, zusätzlich reichen Dorne 16 der Stützkonstruktion durch das Tunnelmodul, genauer durch die Dornöffnungen 19 hindurch. Die Dornöffnungen oder Ösen sind dabei vorzugsweise mit einer Verstärkung und einem Dichtelement ausgestattet. Im gleichen Randbereich ist im Dachteil 22 des Tunnelmoduls eine Dachblende 23 übergestept.

Fig. 9 zeigt ein Beispiel einer Stützkonstruktion, die bei dem beschriebenen Tunnelmodul zur Anwendung kommt. In der Figur sind die vorzugsweise gleich zu gestaltenden Bauteile mit gleichen Bezugszeichen versehen. Die Stützkonstruktion ist eine steckbare Rohrkonstruktion, wobei zusätzlich Eckmodule und Giebelmodule G, von denen in der Figur nur eines dargestellt ist, vorgesehen sind. Die Stützkonstruktion wird mit den Rohrmodulen a im Boden abgestützt. Die Rohrmodule a sind in Zwischenteile g bzw. b eingesetzt, wobei durch Vorsehen von Knebelschrauben in letzteren Bauteilen eine Höheneinstellung der Stützkonstruktion gewährleistet ist. Eine Breitereinstellung ist in vergleichbarer Art vorgesehen, indem sowohl vorzeltseitig als auch an der dem Vorzelt entfernt liegenden Seite zwischen den Rohrmodulen b und e eine entsprechende Verstellmöglichkeit vorgesehen ist. In der Zeichnung ebenfalls dargestellt sind die Dorne 16, die bereits zuvor erwähnt wurden, und über ihnen Aufsatzstücke, mit denen die durch die Dornöffnungen gebildeten Öffnungen abgedichtet werden. Das Giebelelement G weist vorteilhafterweise einen Giebelwinkel γ von ca. 165° auf. Je nach Abmessungen des Tunnelmoduls werden unterschiedlich viele Giebelelemente eingesetzt. Diese werden mit der Stützkonstruktion vorteilhafterweise durch Schellen verbunden, und in ihnen ist ebenfalls in bereits geschilderter Weise eine Längeneinstellung vorgesehen.

Weitere Ausführungsformen und Vorteile der Erfindung ergeben sich aus den folgenden Ansprüchen.

S c h u t z a n s p r ü c h e

1. Vorzelt (10) für Wohnwagen oder ähnliches, mit
 - einer eigenen Stützkonstruktion,
 - zumindest einem heraustrennbaren Vorderwandteil (11, 12) und/oder
 - zumindest einem heraustrennbaren Seitenwandteil (13),**dadurch gekennzeichnet, daß**
 - die Schnittstellen (18) zwischen heraustrennbaren Vorderwandteilen und Vorzelt einerseits und heraustrennbaren Seitenwandteilen und Vorzelt andererseits identisch ausgebildet und angeordnet sind,
 - an den Schnittstellen zur Erweiterung des Vorzelts ein im wesentlichen kubisches Tunnelmodul (20) anbaubar ist und
 - sowohl die heraustrennbaren Vorderwandteile (12) als auch die heraustrennbaren Seitenwandteile (13) als Abschluß des erweiterten Vorzelts verwendbar sind.
2. Vorzelt nach Anspruch 1, **dadurch gekennzeichnet, daß** die heraustrennbaren Vorderwandteile und die heraustrennbaren Seitenwandteile eine Höhe aufweisen, die im wesentlichen der Höhe des Vorzelts entspricht.
3. Vorzelt nach mindestens einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** die Schnittstellen durch Reißverschlüsse (18), eine Kederband-Kederschienenverbindung oder eine Klettband-Klettflauschverbindung gebildet sind.
4. Vorzelt nach mindestens einem der vorhergehenden Ansprüche, **dadurch gekennzeichnet, daß** an die

10.09.97

12

Stützkonstruktion des Vorzelts eine eigene Stützkonstruktion des Tunnelmoduls anbringbar ist.

5. Tunnelmodul (20) zur Erweiterung von Vorzelten von Wohnwagen oder ähnlichem,
 - von im wesentlichen kubischer Form und mit
 - einer eigenen Stützkonstruktion,
 - Aufnahmeelementen (19, 28) für diese Stützkonstruktion,
 - ersten Befestigungselementen (18) in einem ersten Randbereich des Tunnelmoduls,
 - zweiten Befestigungselementen (18') in einem zweiten Randbereich des Tunnelmoduls, wobei
 - erste und zweite Befestigungselemente als miteinander in Eingriff bringbare Gegenstücke ausgebildet und angeordnet sind.
6. Tunnelmodul nach Anspruch 5, **dadurch gekennzeichnet, daß** die Stützkonstruktion einen Giebelwinkel (γ) von ca. 165° aufweist.
7. Tunnelmodul nach Anspruch 6, **dadurch gekennzeichnet, daß** der Scheitel des Giebelwinkels außermittig zum Tunnelelement angeordnet ist.
8. Tunnelmodul nach mindestens einem der Ansprüche 5 bis 7, **dadurch gekennzeichnet, daß** die ersten Befestigungselemente durch
 - eine erste Reißverschlußhälfte,
 - ein Kederband oder
 - ein Klettbandund die zweiten Befestigungselemente entsprechend durch
 - eine zweite Reißverschlußhälfte,
 - eine Kederschiene oder
 - ein Klettflausch gebildet sind.

9. Tunnelmodul nach mindestens einem der Ansprüche 5 bis 8, **dadurch gekennzeichnet, daß** die Aufnahmeelemente im ersten Randbereich diesem unmittelbar benachbart und die Aufnahmeelemente im zweiten Randbereich von diesem beabstandet angeordnet sind.
10. Tunnelmodul nach mindestens einem der Ansprüche 5 bis 9, **dadurch gekennzeichnet, daß** die Aufnahmeelemente
- Ösen,
 - verstärkte Ösen,
 - Hohlsäume,
 - verschließbare Hohlsäume und/oder
 - Ankerhaken
- umfassen.
11. Tunnelmodul nach mindestens einem der Ansprüche 5 bis 10, **dadurch gekennzeichnet, daß** das Tunnelmodul aus einem Dach (22) und zwei Seitenteilen (24, 26) gebildet wird.
12. Tunnelmodul nach Anspruch 11, **dadurch gekennzeichnet, daß** das Tunnelmodul weiterhin einen Boden aufweist.
13. Tunnelmodul nach mindestens einem der Ansprüche 5 bis 11, **dadurch gekennzeichnet, daß** das Tunnelmodul einstückig ausgebildet ist.
14. Tunnelmodul nach Anspruch 12, **dadurch gekennzeichnet, daß** das Tunnelmodul einstückig oder mit nur einer Nahtstelle ausgebildet ist.
15. Tunnelmodul nach Anspruch 11 oder 12, **dadurch gekennzeichnet, daß** das Dach und die Seitenteile durch Kappnähte (36) derart miteinander verbunden sind, daß das Dach um die Kanten zwischen dem Dach und den Seitenteilen gelegt ist.

10:09:47


14

16. Tunnelmodul nach Anspruch 12, **dadurch gekennzeichnet, daß** der Boden und die Seitenteile durch Kappnähte derart miteinander verbunden sind, daß die Seitenteile um die Kanten zwischen Seitenteilen und Boden gelegt sind.
17. Tunnelmodul, nach mindestens einem der Ansprüche 5 bis 16, **dadurch gekennzeichnet, daß** das Tunnelmodul eine Höhe aufweist, die im wesentlichen der eines üblichen Vorzelts entspricht.

29.09.97

1/4

FIG. 1



29.09.97

FIG. 2

2/4




FIG. 3




FIG. 4




FIG. 5







FIG. 6



29.09.97

3/4


FIG. 8



29.09.97

4/4

FIG. 9



PUB-NO: DE029716289U1
DOCUMENT- DE 29716289 U1
IDENTIFIER:
TITLE: Vorzelt f?r Wohnwagen und Tunnelmodul zur
Erweiterung solcher Vorzelte
PUBN-DATE: October 30, 1997
PATENT-FAMILY- 8045824
ID:

APPLICANT:
NAME COUNTRY
MEHLER AG DE

APPL-NO: DE 29716289 U
APPL-DATE: September 10, 1997

PRIORITY-DATA:
PRIORITY-NO PRIORITY-APPL-DATE
DE 29716289 U 19970910

CPC-CURRENT:
TYPE CPC DATE
CPCI E04H15/18 20130101
CPCI E04H15/08 20130101

INT-CL-CURRENT:
TYPE IPC DATE
IPCP E04H15/08 20060101
IPCS E04H15/18 20060101



(86) Date de dépôt PCT/PCT Filing Date: 2012/05/11
(87) Date publication PCT/PCT Publication Date: 2012/11/29
(85) Entrée phase nationale/National Entry: 2013/11/21
(86) N° demande PCT/PCT Application No.: US 2012/037407
(87) N° publication PCT/PCT Publication No.: 2012/161983
(30) Priorité/Priority: 2011/05/23 (US13/113,704)

(51) Cl.Int./Int.Cl. *E04H 15/34* (2006.01)
(71) Demandeur/Applicant:
WORLD SHELTERS, INC., US
(72) Inventeur/Inventor:
ZEIGLER, THEODORE R., US
(74) Agent: NORTON ROSE FULBRIGHT CANADA
LLP/S.E.N.C.R.L., S.R.L.

(54) Titre : MODULE STRUCTUREL A BUTEE, STRUCTURE REPLIABLE ET PROCEDE POUR ERIGER UNE
STRUCTURE REPLIABLE
(54) Title: STRUCTURAL MODULE WITH STOP, COLLAPSIBLE STRUCTURE, AND METHOD OF ERECTING A
COLLAPSIBLE STRUCTURE




FIG. 2

(57) Abrégé/Abstract:

A structural module includes a first strut pair including a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point, a second strut pair including a third strut and a fourth strut pivotably connected to each other

(57) **Abrégé(suite)/Abstract(continued):**

at a second strut pair pivotable connection point, a first hUQ, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub, a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub, and a stop arrangement attached to at least one of the first hub, the first strut, and the third strut, the stop arrangement including an abutment end.

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau(10) International Publication Number
WO 2012/161983 A1(43) International Publication Date
29 November 2012 (29.11.2012)

WIPO | PCT

(51) International Patent Classification:
E04H 15/34 (2006.01)(21) International Application Number:
PCT/US2012/037407(22) International Filing Date:
11 May 2012 (11.05.2012)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
13/113,704 23 May 2011 (23.05.2011) US(71) Applicant (for all designated States except US): **WORLD SHELTERS, INC.** [US/US]; 2401 Nordok Place, Alexandria, VA 22306 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **ZEIGLER, Theodore R.** [US/US]; 2401 Nordok Place, Alexandria, VA 22306 (US).(74) Agent: **BROWN, Harold R., III**; WRB-IP LLP, 801 N. Pitt Street, Suite 123, Alexandria, VA 22314 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO,

DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, IIR, IU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:


— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

— as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))

Published:

— with international search report (Art. 21(3))

(54) Title: STRUCTURAL MODULE WITH STOP, COLLAPSIBLE STRUCTURE, AND METHOD OF ERECTING A COLLAPSIBLE STRUCTURE

**FIG. 2**

(57) Abstract: A structural module includes a first strut pair including a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point, a second strut pair including a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point, a first hUQ, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub, a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub, and a stop arrangement attached to at least one of the first hub, the first strut, and the third strut, the stop arrangement including an abutment end.

STRUCTURAL MODULE WITH STOP, COLLAPSIBLE STRUCTURE,
AND METHOD OF ERECTING A COLLAPSIBLE STRUCTURE

BACKGROUND AND SUMMARY

[0001] The present invention relates to collapsible structures and, more particularly, to such structures including pivotable strut pairs that include stops for limiting pivotable movement of the struts.

[0002] A variety of types of collapsible structures (also often referred to as folding frame systems) are known. My U.S. Patent No. 7,712,261, and my U.S. Patent No. 7,556,054, which are incorporated by reference, disclose folding frame systems which can be locked in place by what can be referred to as a “tension lock”. In this tension lock arrangement, the frame is locked in an open position by pivotably connected strut members that are foldable from a parallel folded condition in which the struts lie substantially against each other, through a parallel open condition in which the struts are disposed substantially end-to-end, to an open locked condition slightly beyond the latter parallel condition beyond which the struts are prevented from pivoting. In this open locked condition, when a tension member is connected between points on the two struts removed from the pivot points, the tension member will prevent the struts from passing back to the parallel open or parallel folded positions unless the tension member is released or the struts are somehow deformed.

[0003] My U.S. Patent No. 5,230,196, U.S. Patent No. 5,444,946, and U.S. Patent No. 6,141,934, which are incorporated by reference, disclose embodiments of folding frame systems with what can be referred to as “manual locks”. In these systems, strut pairs are arranged in

scissor fashion, and, when the scissors are unfolded to open the system from a closed condition, ends of the struts are connected by hub portions that are manually locked together.

[0004] To simplify the construction of and erection and break-down of folding frame systems, it is desirable to provide a folding frame system that does not require a tension lock or a manual lock.

[0005] A structural module according to an aspect of the present invention comprises a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point, a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point, a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub, a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub, and a stop comprising a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define an abutment end of the stop, the first stop strut being pivotably connected at a second end thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut. The structural module is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and an open position in which the abutment end of the stop contacts the second hub.

[0006] A collapsible structure according to an aspect of the present invention comprises a plurality of strut pairs, each strut pair comprising a front strut and a rear strut pivotably connected to each other at a strut pair pivotable connection point, a plurality of hub pairs, each hub pair comprising an outer hub and an inner hub, at least one first hub pair of the plurality of hub pairs being connected to at least a first and a second strut pair of the plurality of strut pairs so

that an outer hub of the at least one first hub pair is pivotably connected to front struts of the first and second strut pair and an inner hub of the at least one first hub pair is pivotably connected to rear struts of the first and second strut pair, and a stop associated with at the at least one first hub pair, the stop comprising a first and a second stop strut pivotably connected to each other proximate first ends thereof, the first and the second stop strut being pivotably connected at second ends thereof to one of the front strut and the rear strut of the first and second strut pair, respectively.

[0007] A structural module according to another aspect of the present invention comprises a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point, a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point, a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub, a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub, and a stop arrangement attached to at least one of the first hub, the first strut, and the third strut, the stop arrangement including an abutment end. The structural module is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and an open position in which the abutment end of the stop contacts the second hub.

[0008] A method of erecting a collapsible structure according to an aspect of the present invention is also provided. The method involves use of a collapsible structure comprising a plurality of strut pairs, each strut pair comprising a front strut and a rear strut pivotably connected to each other at a strut pair pivotable connection point, a plurality of hub pairs, each hub pair comprising an outer hub and an inner hub, at least one first hub pair of the plurality of

hub pairs being connected to at least a first and a second strut pair of the plurality of strut pairs to form a series of strut pairs so that an outer hub of the at least one first hub pair is pivotably connected to front struts of the first and second strut pair and an inner hub of the at least one first hub pair is pivotably connected to rear struts of the first and second strut pair, and a stop associated with at the at least one first hub pair, the stop comprising a first and a second stop strut pivotably connected to each other proximate first ends thereof, the first and the second stop strut being pivotably connected at second ends thereof to one of the front strut and the rear strut of the first and second strut pair, respectively. The method comprises moving each strut pair from a collapsed position in which the front and rear strut of each strut pair are substantially parallel to each other and hubs of the first hub pair are at a greatest possible distance from each other to an open position in which the stop prevents hubs of the first hub pair from moving closer to each other and after each strut pair is in an open position, restraining relative movement of the strut pairs of the series of strut pairs without locking inner and outer hubs to each other.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The features and advantages of the present invention are well understood by reading the following detailed description in conjunction with the drawings in which like numerals indicate similar elements and in which:

[0010] FIGS. 1A and 1B are perspective views of embodiments of collapsible shelters according to aspects of the present invention;

[0011] FIG. 2 is a front view of a collapsible structure according to an aspect of the present invention;

[0012] FIG. 3 is a perspective view of a portion of a collapsible structure according to an aspect of the present invention;

[0013] FIG. 4A is a side view of a portion of a collapsible structure according to an aspect of the present invention, and FIGS. 4B and 4C are views of the collapsible structure of FIG. 4A taken at sections 4B-4B and 4C-4C, respectively;

[0014] FIGS. 5A-5D show steps in the erection of a collapsible structure in a method according to an aspect of the present invention;

[0015] FIG. 6 is a schematic view of a top of a portion of a collapsible structure according to an aspect of the present invention;

[0016] FIG. 7 is a perspective view of hubs of a hub pair according to an aspect of the present invention;

[0017] FIGS. 8A and 8B are side views of a portion of a collapsible structure according to an aspect of the present invention in an open and a folded condition;

[0018] FIGS. 9A and 9B are side views of a portion of a collapsible structure according to an another aspect of the present invention in an open and a folded condition; and

[0019] FIG. 10 is a side view of a portion of a collapsible structure according to another aspect of the present invention.

DETAILED DESCRIPTION

[0020] FIGS. 1A and 1B show embodiments of collapsible shelters 1A and 1B according to aspects of the present invention. The shelters 1A and 1B are shown with covers 2 attached. The shelters include collapsible structures 21 according to a further aspect of the present invention, an aspect of one of which is shown in FIG 2. The collapsible structures 21 facilitate construction

of collapsible shelters such as are shown for purposes of illustration and not limitation in FIGS. 1A and 1B. A substantially infinite number of configurations of collapsible shelters can be provided using the collapsible structures 21 and/or structural modules 23 of which they are made up.

[0021] The structure 21 comprises one or more structural modules 23, certain components of which are disposed within the area denoted by a dotted line in FIG. 2. Details of portions of structural modules are shown in FIGS. 3 and 4A-4C. A structural module 23 according to an aspect of the present invention comprises a first strut pair 25 comprising a first strut 27 and a second strut 29 pivotably connected to each other at a first strut pair pivotable connection point 31. The structural module 23 further comprises a second strut pair 33 comprising a third strut 35 and a fourth strut 37 pivotably connected to each other at a second strut pair pivotable connection point 39. The pivotable connection points 31 and 39 will ordinarily be formed by pins.

[0022] The structural module 23 further comprises a first hub 41 and a second hub 43. A first end 271 of the first strut 27 and a first end 351 of the third strut 35 are pivotably connected to the first hub 41, and a first end 291 of the second strut 29 and a first end 371 of the fourth strut 37 are pivotably connected to the second hub 43.

[0023] A stop 45 is provided and can, in one embodiment, comprise a first and a second stop strut 47 and 49, respectively. As seen in FIG. 3, the first and second stop strut 47 and 49 can be pivotably connected to each other proximate first ends 471 and 491 thereof to at least partially define an abutment end 51 of the stop. The first stop strut 47 can be pivotably connected at a second end 472 thereof to the first strut 27 and the second stop strut 49 can be pivotably connected at a second end 492 thereof to the third strut 35.

[0024] The structural module 23 is movable between a closed position (FIG. 5A and view “C” in FIG. 2) in which longitudinal axes of struts 27, 29 and 35, 37 of the first strut pair and the second strut pair 25 and 33 are substantially parallel to one another and an open position (FIG. 5D and view “O” in FIG. 2) in which the abutment end 51 of the stop 45 contacts the second hub 43. The abutment end 51 is not designed to be and does not need to be locked to the second hub 43, which facilitates erecting and folding the structure 21 and reduces the number of parts that can be damaged but, if desired, a locking connection (not shown) may be provided.

[0025] The structural module 23 is retained in an erected condition by means for limiting movement of the first and second strut pair pivotable connection points 31 and 39 relative to each other. The movement limiting means may take any number of forms but ordinarily includes at least some structure for holding distal ends 53 of a string 55 of two or more strut pairs 25, 33, 25', 33' in a fixed position relative to each other or for preventing the distal ends from moving away from each other. As seen, for example, in FIG. 5D, after a structure 21 comprising the string 55 of strut pairs is unfolded from the closed position (FIG. 5A), spread out (FIG. 5B) in a substantially flat condition, and raised from the flat, spread out condition to substantially a desired height (FIG. 5C) in which the abutment ends 51 of the stops 45 between each hub pair in the string contacts a corresponding hub, the distal ends 53 of the string 55 are fixed or prevented from moving apart, such as by securing them to the ground with stakes 57 extending through some suitable rigid or flexible attachment at the distal end of the string and thereby fixing the position of the distal ends relative to each other, by attaching a floor 59 or other tension member(s) such as cables between the distal ends to at least prevent them from moving apart, or by some combination of such illustrative measures. A floor 59 may be a rigid structure or, more typically, a flexible fabric structure that can be placed in tension. Fixing the distal ends 53 of the

string 55 in this condition prevents the structure from automatically collapsing and functions as an alternative to, e.g., locking each strut pair in an open position. When it is desired to collapse the structure, this can be conveniently done by removing the structure for holding the distal ends of the string in the fixed position. Typically, hubs such as are used to connect two strut pairs are provided at the distal ends 53 of a string 55 of struts. A stop may be provided to limit movement of hubs of a pair of hubs at the distal ends 53 of the string 55 toward each other but, ordinarily, it is sufficient to hold the distal ends in a fixed position by, e.g., stakes, floors, and/or cables. A scissor-type stop such as can be used between two pairs of strut pairs is less useful at the distal ends 53 of the string 55 and, if a stop is provided, it is presently preferred to provide a stop such as a strut that extends from one hub to contact another hub of a hub pair at the distal end.

[0026] An outer cover 2 (FIGS. 1A and 1B) is ordinarily pre-attached to the string 55 at outer hubs along the string and functions as a tension member to assist in preventing the strut pairs of the string from opening beyond the point at which the abutment ends 51 of the stops 45 contact corresponding hubs. In addition, tension cables T (FIGS. 2 and FIGS. 4A-4C) are typically provided and extend diagonally between hubs at diagonally opposite corners of squares defined by strut pairs on adjacent strings 55 of strut pairs and transverse strut pairs 75 between the adjacent strings of strut pairs. An inner cover (not shown) is ordinarily attached to inner hubs along the string at the time of erecting the structure 21 and also functions as a tension member to assist in preventing the strut pairs of the string from opening beyond the point at which the abutment ends 51 of the stops 45 contact corresponding hubs. While the inner cover and floor or cables attached to distal ends 53 of the string 55 can be preattached to the string 55, it is presently preferred to attach these components in the field to facilitate access to the struts and hubs forming the string 55 when erecting and collapsing the structure. The first and second hubs

41 and 43 are ordinarily provided with a centrally located hole for receiving a fastener for fastening an outer or inner cover to the hub, and with additional holes for receiving fasteners for securing the tension cables T.

[0027] As seen in a schematic top view of a string 55 of strut pairs as shown in FIG. 6, a first and a second pivot axis A1 and A2 extend through the first and the second strut pair 25 and 33 pivotable connection points 31 and 39, respectively, and a first and a second plane P1 and P2 perpendicular to the first and the second pivot axis, respectively, are parallel, or substantially so. Preferably, the struts of the strut pairs in a string 55 of strut pairs will have a certain amount of flexibility and will bend slightly so that the hubs of the hub pairs will be substantially aligned along radii r (FIG. 2) of the structure as seen in the top view of FIG. 4B which shows the first hub 41 completely obscuring the second hub (not seen in FIG. 4B) beneath it, as opposed to being offset by the thickness of the struts as shown in FIG. 6.

[0028] As seen, for example, in FIG. 2, in a given string 55 of strut pairs, the first strut pair 25 pivotable connection point 31 is ordinarily disposed along a middle half of each of the first and second struts 27 and 29, and the second strut pair 33 pivotable connection point 39 is also ordinarily disposed along a middle half of each of the third and fourth struts 35 and 37. If the pivotable connection points 31 and 39 are disposed at the midpoints of the struts 27, 29, 35, and 37, and the struts of a given strut pair are of equal length, the ends of the strut pairs will define corners of a rectangular shape when the strut pairs are in open positions. By offsetting the pivotable connection points 31 and 39 from the mid-points of the struts 27, 29, 35, and 37, when the strut pairs 25 and 33 are in an open position, the ends of the strut pairs can define corners of, for example, an isosceles trapezoidal shape as seen in FIG. 2, which facilitates forming an arch out of a string of strut pairs.

[0029] FIG. 3 shows a hub pair with struts 27, 29, 35, and 37 attached to hubs 41 and 43 of the pair via pins 63 that extend through holes 65 (FIG. 7) in legs 67 of the hubs. Each hub of a hub pair 61 can be identical to the other hub of the pair as seen, for example, in FIG. 7. Ordinarily, each hub in each hub pair in a string of strut pairs is identical to every other hub in the string. As seen in FIGS. 3 and 7, transverse legs 69 of the hubs 41 and 43, which may be identical to the legs 65, are likewise provided with holes 71. Ends of transverse struts 73 of transverse strut pairs 75 can be pivotably attached to the transverse legs 69 via pins 77 (FIG. 3). The transverse struts 73 will ordinarily be scissor struts attached to each other by pins (not shown) like the struts of the strut pairs 25 and 33, and will ordinarily, but not necessarily, be joined to each other at midpoints of the struts so that the strut pairs form a rectangular shape when in an open position. It is also possible to omit any structure that joins the transverse struts 73, i.e., they need not be pinned together. Ordinarily, no stop struts are attached to the transverse struts 73, and the extent to which the transverse strut pair 75 can be opened will ordinarily be limited by the extent to which non-transverse strut pairs with stops 45 attached thereto permit.

[0030] FIGS. 8A and 8B show a hub pair connecting two strut pairs 25 and 33 that are both in the form of isosceles trapezoids when in the open position (FIG. 8A). The second end 472 of the first stop strut 47 is connected to the first strut 27 and the second end 492 of the second stop strut 49 is connected to the third strut 35 at the same distance from the first hub 41. The first and second stop struts 47 and 49 are both the same length. When the strut pairs are folded to a collapsed position in which the struts are all substantially parallel, as shown in FIG. 8B, the abutment end 51 of the stop 45 is disposed evenly between the first and third struts 27 and 35, facilitating closing of the structure.

[0031] A somewhat different structure has been found to be useful when connecting two strut pairs that have different shapes when in an open position, such as different isosceles trapezoids or isosceles trapezoids attached to rectangles. FIGS. 9A and 9B show a hub pair connecting two strut pairs wherein one strut pair 25 is in the form of an isosceles trapezoid in the open position and the other strut pair 33' is in the form of a rectangle in the open position. In this arrangement, the second end 472 of the first stop strut 47 is connected to the first strut 27 and the second end 492' of the second stop strut 49' is connected to the third strut 35' at different distances from the first hub, and the first and second stop struts are different lengths. By appropriate selection of the distances, the abutment end 51' of the stop 45' can be disposed evenly between the first and third struts 27 and 35', facilitating proper closing of the structure. If some suitable measure such as altering the length of the stop struts and the point of connection of the second ends of the stop struts to the first and third struts were not taken, the stop might interfere with proper closure of the strut pairs.

[0032] As seen, for example, in FIGS. 3 and 6, the second end 472 of the first stop strut 47 can be pivotably attached to what may be denominated as a front side of the first strut 27 (to the left in FIG. 3 and to the right in FIG. 6, and the second end 492 of the second stop strut 492 can be pivotably attached to what can be denominated as a rear side of the third strut 35 (to the right in FIG. 3 and to the left in FIG. 6). It will be appreciated that which side of the strut is denominated as the "front" and which is denominated as the "rear" need not be essential to the invention and the terms are used merely to provide a frame of reference. As seen in FIG. 3, the stop 45 can comprise a spacer 79 disposed between the first ends 471 and 491 of the first and second stop strut 47 and 49. The spacer 51 can at least partially define the abutment end 51 of the stop and can contact the second hub 43 when the structural module is in the open position.

[0033] In the embodiment of the structure 21 and structural module 23 shown in, e.g., FIGS. 2 and 3, the first and second stop strut 47 and 49 and the first and third strut 27 and 35 define a convex quadrilateral shape (e.g., a diamond) when the structural module is in the open position. Other stop structures can be provided, however, as illustrated by the stop 45' shown in the structural module 23' in FIG. 10, in which the first and second stop strut 47' and 49' and the first and third strut 27' and 35' (in the position of the second and fourth strut 29 and 37 of the embodiment of FIGS. 2 and 3) define a concave quadrilateral shape when the structural module is in the open position and the abutment surface 51' of the stop contacts the second hub 43' (in the position of the first hub 41 of the embodiment of FIGS. 2 and 3).

[0034] While a scissor-type stop such as the stop 45 shown in, e.g., FIGS. 2 and 3 or the stop 45' shown in FIG. 10 is presently preferred, other stop structures can also be provided. A stop according other aspects of the invention can be in the form of, for example, a post extending from a center of one hub of a hub pair that is intended to abut in, preferably, a non-locking fashion with the other hub of the hub pair to limit the extent to which the hubs of the hub pair can move toward each other, and thus limit the extent to which the ends of the struts of the associated strut pairs attached to the hubs of the hub pair can move toward each other. The use of the illustrated scissor structures 45 and 45', however, is believed to be useful to ensure that the abutment surface 51 and 51' of the stops contacts the associated second hub 43

[0035] While the invention has been primarily described in connection with structures 21 in the form of arches of two or more strut pairs arranged substantially in a row, other structures can be provided in which strings of two or more strut pairs comprising stops arranged between each strut pair are joined end-to-end at angles to each other, which can facilitate construction of shelters having more complex shapes than simple arches. At the intersection of the strings,

different stop arrangements may be appropriate depending upon the particular structure sought to be constructed. Where, for example, a scissor-type stop such as is shown in FIG. 2 is not possible, a stop may be in the form of a rigid member that extends from one hub to contact another hub of a hub pair at the intersection of the strings.

[0036] A method of erecting a collapsible structure is shown in FIGS. 5A-5D and described in connection with the collapsible structure 21 of the type shown in FIG. 2. The collapsible structure 21 comprises a plurality of strut pairs 25, 33, 25', 33'. Each strut pair 25, 33, 25', 33' comprises a front strut and a rear strut pivotably connected to each other at a strut pair pivotable connection point. The structure 21 further includes a plurality of hub pairs, each hub pair comprising an outer hub 41 (FIG. 2) and an inner hub 43 (FIG. 2), at least one first hub pair of the plurality of hub pairs being connected to at least a first and a second strut pair of the plurality of strut pairs to form a series or string 55 of strut pairs so that an outer hub of the at least one first hub pair is pivotably connected to front struts of the first and second strut pair and an inner hub of the at least one first hub pair is pivotably connected to rear struts of the first and second strut pair. The structure 21 further includes a stop 45 associated with at the at least one first hub pair, the stop comprising a first and a second stop strut 47, 49 (FIG. 2) pivotably connected to each other proximate first ends thereof, the first and the second stop strut being pivotably connected at second ends thereof to one of the front strut and the rear strut of the first and second strut pair, respectively.

[0037] According to the method, each strut pair 25, 33, 25', 33' is moved from a collapsed position as seen in FIG. 5A in which the front and rear strut of each strut pair are substantially parallel to each other and hubs of the first hub pair are at a greatest possible distance from each other to an open position shown in FIGS. 5C and 5D in which the stop prevents hubs of the first

hub pair from moving closer to each other. From the collapsed position shown in FIG. 5A, the string 55 is unfolded as shown in FIG. 5B so that the hubs of each hub pair move closer to each other, and the struts of the strut pairs are moved from being substantially parallel through a position in which they are perpendicular and toward a position in which they would again be parallel. After each strut pair 25, 33, 25', 33' is in an open position as seen in FIG. 5C, relative movement of the strut pairs of the series 55 of strut pairs is restrained without locking inner and outer hubs to each other, such as by securing distal ends 53 of the string in a fixed position relative to each other, such as by means of stakes 57, and/or by preventing movement of the distal ends away from each other, such as by means of cables and/or floors 59.

[0038] In the present application, the use of terms such as “including” is open-ended and is intended to have the same meaning as terms such as “comprising” and not preclude the presence of other structure, material, or acts. Similarly, though the use of terms such as “can” or “may” is intended to be open-ended and to reflect that structure, material, or acts are not necessary, the failure to use such terms is not intended to reflect that structure, material, or acts are essential. To the extent that structure, material, or acts are presently considered to be essential, they are identified as such.

[0039] While this invention has been illustrated and described in accordance with a preferred embodiment, it is recognized that variations and changes may be made therein without departing from the invention as set forth in the claims.

Patent

Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

WHAT IS CLAIMED IS

1. A structural module, comprising:

a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point disposed in a middle half of each of the first strut and the second strut;

a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point disposed in a middle half of each of the third strut and the fourth strut;

a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub;

a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub; and

a stop having a first end that at least partially defines an abutment end of the stop, and a second end pivotably connected to the first strut and to the third strut,

wherein the structural module is movable between a closed position in which the abutment end of the stop is spaced from the second hub and an open position in which the abutment end of the stop contacts the second hub.

2. The structural module as set forth in claim 1, comprising means for limiting movement of the first and second strut pair pivotable connection points relative to each other.

3. The structural module as set forth in claim 2, wherein the movement limiting means comprises at least one of stakes for pinning distal ends of a string of strut pairs comprising the

first and second strut pair in fixed positions relative to each other and tension members arranged between distal ends of the string of strut pairs to prevent the distal ends from moving away from each other.

4. The structural module as set forth in claim 1, wherein a first and a second pivot axis extends through the first and the second strut pair pivotable connection points, respectively, and a first and a second plane perpendicular to the first and the second pivot axis, respectively, are parallel.

5. A structural module, comprising:

a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point;

a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point;

a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub;

a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub; and

a stop comprising a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define an abutment end of the stop, the first stop strut being pivotably connected at a second end thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut,

wherein the structural module is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one

Patent

Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

another and an open position in which the abutment end of the stop contacts the second hub, and wherein the second end of the first stop strut is connected to the first strut and the second end of the second stop strut is connected to the third strut at different distances from the first hub.

6. The structural module as set forth in claim 5, wherein the first stop strut and the second stop strut are of different length.

7. A structural module, comprising:

- a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point;

- a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point;

- a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub;

- a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub; and

- a stop comprising a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define an abutment end of the stop, the first stop strut being pivotably connected at a second end thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut,

wherein the structural module is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one

Patent
Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

another and an open position in which the abutment end of the stop contacts the second hub, and wherein the first stop strut and the second stop strut are of different length.

8. The structural module as set forth in claim 1, wherein the stop comprises a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define the abutment end of the stop, the first stop strut being pivotably connected at a second end thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut, wherein the structural module is movable between the closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and the open position in which the abutment end of the stop contacts the second hub, and wherein the second end of the first stop strut is pivotably attached to a front side of the first strut and the second end of the second stop strut is pivotably attached to a rear side of the third strut.

9. The structural module as set forth in claim 8, wherein the stop comprises a spacer disposed between the first ends of the first and second stop strut.

10. The structural module as set forth in claim 9, wherein the spacer contacts the second hub when the structural module is in the open position.

11. The structural module as set forth in claim 1, wherein the stop comprises a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define the abutment end of the stop, the first stop strut being pivotably connected at a second end

Patent

Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut, wherein the structural module is movable between the closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and the open position in which the abutment end of the stop contacts the second hub, and wherein the first and second stop strut and the first and third strut define a convex quadrilateral shape when the structural module is in the open position.

12. The structural module as set forth in claim 1, wherein the stop comprises a first and a second stop strut pivotably connected to each other proximate first ends thereof to at least partially define the abutment end of the stop, the first stop strut being pivotably connected at a second end thereof to the first strut and the second stop strut being pivotably connected at a second end thereof to the third strut, wherein the structural module is movable between the closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and the open position in which the abutment end of the stop contacts the second hub, and wherein the first and second stop strut and the first and third strut define a concave quadrilateral shape when the structural module is in the open position.

13. A collapsible structure, comprising:

a plurality of strut pairs, each strut pair comprising a front strut and a rear strut pivotably connected to each other at a strut pair pivotable connection point disposed in a middle half of each of the front strut and the rear strut;

a plurality of hub pairs, each hub pair comprising an outer hub and an inner hub;

at least one first hub pair of the plurality of hub pairs being connected to at least a first and a second strut pair of the plurality of strut pairs so that an outer hub of the at least one first hub pair is pivotably connected to front struts of the first and second strut pair and an inner hub of the at least one first hub pair is pivotably connected to rear struts of the first and second strut pair; and

a stop associated with at the at least one first hub pair, the stop comprising a first end pivotably connected to one of either the front struts of the first and second strut pair or to the rear struts of the first and second strut pair, and a second end at least partially defining an abutment end of the stop, the collapsible structure being movable to an open position in which the abutment end of the stop contacts one of the inner and outer hub of the at least one first hub pair.

14. The collapsible structure as set forth in claim 13, wherein the stop comprises a first and a second stop strut pivotably connected to each other proximate first ends thereof, the first ends of the first and second stop strut at least partially defining the abutment end of the stop, and the collapsible structure is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and the open position in which the abutment end of the stop contacts the one of the inner and outer hub of the at least one first hub pair.

15. The collapsible structure as set forth in claim 13, comprising at least two second hub pairs of the plurality of hub pairs each connected to a respective one of the first and the second strut pair at opposite ends of the first and second strut pair from the first hub pair, an inner hub of each of the at least two second hub pairs being pivotably connected to a rear strut of the respective one of

Patent

Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

the first and second strut pair and an outer hub of each of the at least two second hub pairs being pivotably connected to a respective front strut of the respective one of the first and second strut pair.

16. The collapsible structure as set forth in claim 15, comprising a stop associated with a respective one of each of the first and second hub pairs.

17. The collapsible structure as set forth in claim 13, comprising means for limiting movement of strut pair pivotable connection points relative to each other.

18. A structural module, comprising:

a first strut pair comprising a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point disposed in a middle half of each of the first strut and the second strut;

a second strut pair comprising a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point disposed in a middle half of each of the first strut and the second strut;

a first hub, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub;

a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub; and

a stop arrangement attached to at least one of the first hub, the first strut, and the third strut, the stop arrangement including an abutment end,

wherein the structural module is movable between a closed position in which longitudinal axes of struts of the first strut pair and the second strut pair are substantially parallel to one another and an open position in which the abutment end of the stop contacts the second hub.

19. A method of erecting a collapsible structure, the collapsible structure comprising a plurality of strut pairs, each strut pair comprising a front strut and a rear strut pivotably connected to each other at a strut pair pivotable connection point disposed in a middle half of each of the first strut and the second strut, a plurality of hub pairs, each hub pair comprising an outer hub and an inner hub, at least one first hub pair of the plurality of hub pairs being connected to at least a first and a second strut pair of the plurality of strut pairs to form a series of strut pairs so that an outer hub of the at least one first hub pair is pivotably connected to front struts of the first and second strut pair and an inner hub of the at least one first hub pair is pivotably connected to rear struts of the first and second strut pair, and a stop associated with at the at least one first hub pair, the stop comprising a first end pivotably connected to one of either the front struts of the first and second strut pair or to the rear struts of the first and second strut pair and a second end at least partially defining an abutment end of the stop, the collapsible structure being movable to an open position in which the abutment end of the stop contacts one of the inner and outer hub of the at least one first hub pair, the method comprising:

moving each strut pair from a collapsed position in which the front and rear strut of each strut pair are substantially parallel to each other and hubs of the first hub pair are at a greatest possible distance from each other to an open position in which the stop prevents hubs of the first hub pair from moving closer to each other; and

Patent

Application No. PCT/US2012/037407
Attorney's Docket No. 000002-092WO

after each strut pair is in an open position, restraining relative movement of the strut pairs
of the series of strut pairs without locking inner and outer hubs to each other.

1/10








FIG. 2




3/10

**FIG. 3**


4/10

**FIG. 4B****FIG. 4A****FIG. 4C**



5/10

**FIG. 5A****FIG. 5B****FIG. 5C****FIG. 5D**



6/10

**FIG. 6**



7/10

**FIG. 7**


8/10

**FIG. 8A****FIG. 9A**

9/10

**FIG. 8B****FIG. 9B**

10/10

**FIG. 10**

PUB-NO: CA002837116A1
DOCUMENT-IDENTIFIER: CA 2837116 A1
TITLE: STRUCTURAL MODULE WITH STOP, COLLAPSIBLE
STRUCTURE, AND METHOD OF ERECTING A
COLLAPSIBLE STRUCTURE
PUBN-DATE: November 29, 2012
PATENT-FAMILY-ID: 47217613

INVENTOR-INFORMATION:

NAME	COUNTRY
ZEIGLER THEODORE R	US

APPLICANT:

NAME	COUNTRY
WORLD SHELTERS INC	US

APPL-NO: CA 2837116 A
APPL-DATE: May 11, 2012

PRIORITY-DATA:

PRIORITY-NO	PRIORITY-APPL-DATE
US 2012037407 W	20120511
US 201113113704 A	20110523

CPC-CURRENT:

TYPE	CPC	DATE
CPCI	E04H15/18	20130101
CPCI	E04H15/06	20130101
CPCI	E04H15/50	20130101
CPCI	E04H15/405	20130101
CPCI	E04H15/505	20130101
CPCI	E04H15/54	20130101
CPCI	E04H1/005	20130101

INT-CL-CURRENT:

TYPE IPC

DATE

IPCP E04H15/34 20060101

ABSTRACT:

A structural module includes a first strut pair including a first strut and a second strut pivotably connected to each other at a first strut pair pivotable connection point, a second strut pair including a third strut and a fourth strut pivotably connected to each other at a second strut pair pivotable connection point, a first hUQ, a first end of the first strut and a first end of the third strut being pivotably connected to the first hub, a second hub, a first end of the second strut and a first end of the fourth strut being pivotably connected to the second hub, and a stop arrangement attached to at least one of the first hub, the first strut, and the third strut, the stop arrangement including an abutment end.



19 BUNDESREPUBLIK
DEUTSCHLAND



DEUTSCHES
PATENTAMT

12 Gebrauchsmuster
10 DE 295 17 290 U 1

51 Int. Cl.⁶:
E 04 H 15/18
E 04 H 15/54

11	Aktenzeichen:	295 17 290.8
22	Anmeldetag:	2. 11. 95
47	Eintragungstag:	21. 12. 95
43	Bekanntmachung im Patentblatt:	8. 2. 96

DE 295 17 290 U 1

73 Inhaber:
UMAREX Sportwaffen GmbH & Co KG, 59757
Arnsberg, DE

74 Vertreter:
H. Fritz und Kollegen, 59759 Arnsberg

54 Zelt in Modulbauweise

DE 295 17 290 U 1

- 1 Die vorliegende Erfindung betrifft ein aus einzelnen
Bauelementen in Modulbauweise aufgebautes Zelt. Aufgabe der
vorliegenden Erfindung ist es, dem Benutzer ein System zur
Verfügung zu stellen, mittels dessen er ein Zelt je nach
5 Bedarf in unterschiedlichen Varianten erweitern und
vergrößern kann oder auch mehrere Zelte so zu einer
Baueinheit kombinieren kann, daß diese dicht,
witterungsbeständig und stabil ist.
- 10 Die Lösung dieser Aufgabe liefert ein aus einzelnen
Bauelementen in Modulbauweise aufgebautes Zelt mit den
kennzeichnenden Merkmalen des Schutzanspruchs 1.
Erfindungsgemäß umfaßt das System wenigstens ein Bauelement
mit teilzylindrischer Form und halbkreisförmigem oder
15 annähernd halbkreisförmigem Querschnitt, an dem im
stirnseitigen Bereich entlang der bogenförmigen Nahtlinien
jeweils Reißverschlüsse vorgesehen sind und wenigstens ein
Bauelement in Form einer Apsis, dessen stirnseitige
bogenförmige Nahtlinie ebenfalls mit einem Reißverschluß
20 versehen ist, der der Nahtlinie des teilzylindrischen
Bauelements entspricht und mit diesem verbindbar ist.
- Erfindungsgemäß ist es möglich, mehrere Bauelemente mit
teilzylindrischer Form in axialer Richtung, über die an den
25 Reißverschlüssen vorgesehenen bogenförmigen Nahtlinien,
miteinander zu einem längeren Zelt zu verbinden und an einer
oder an beiden Stirnseiten der halbkreisförmigen Bauelemente
weitere Bauelemente in Form einer Apsis anzuschließen, die
ebenfalls über Reißverschlüsse mit den erstgenannten
30 Bauelementen verbunden werden. Dies ist problemlos möglich,
da die bogenförmigen Nahtlinien der halbkreisförmigen
Bauelemente und die bogenförmigen Nahtlinien der
apsisförmigen Bauelemente und die entsprechenden
Reißverschlüsse zusammenpassen.
- 35 Vorzugsweise ist gemäß einer Weiterbildung der Erfindung
vorgesehen, weitere etwa igluförmige Bauelemente zu
verwenden, die annähernd die Grundform einer quadratischen

001195

1 Pyramide haben, mit einem quadratischen Grundriß, aber
gekrümmten Seitenflächen. Dabei haben wenigstens zwei der
gekrümmten Seitenflächen, die einander gegenüber liegen,
ebenfalls bogenförmige Nahtlinien mit Reißverschlüssen, die
5 in der Umrißform den Nahtlinien der halbzyklindrischen
Bauelemente (tunnelförmige Bauelemente) und den Nahtlinien
der apsisförmigen Bauelemente entsprechen. Dadurch kann man
an die igluförmigen Bauelemente über Reißverschlüsse entweder
apsisförmige Bauelemente anschließen, um so ein Vorzelt zu
10 schaffen, das als Stauraum dient und an dieser Seite einen
Abschluß für die Baueinheit bildet. Man kann aber auch
igluförmige Bauelemente an die tunnelförmigen
halbzyklindrischen Bauelemente anbauen. Dadurch ist es möglich
zwei igluförmige Bauelemente, die eine größere Bauhöhe
15 aufweisen können als die tunnelförmigen Bauelemente, über
tunnelförmige Bauelemente miteinander zu verbinden. Es ist
aber auch möglich zwei igluförmige Bauelemente entlang ihrer
bogenförmigen, mit Reißverschluß versehenen, Nahtlinien
direkt miteinander zu verbinden. Das System bietet also
20 vielfältige Kombinationsmöglichkeiten. Beispielsweise können
unterschiedliche Personen jeweils mit igluförmigen,
tunnelförmigen und apsisförmigen Bauelementen reisen, die in
sich eine geschlossene Einheit bilden und bei Bedarf könnte
man diese mit anderen Bauelementen der gleichen Bauart, die
25 andere Reisende mit sich führen, kombinieren, so daß sich aus
mehreren Einzelzelten Zeltgruppen oder ganze Zeltstädte
aufbauen lassen, die in sich geschlossene und
witterungsbeständige Baueinheiten bilden. Vorzugsweise weisen
die igluförmigen und/oder die halbzyklindrischen
30 (tunnelförmigen) Bauelemente jeweils Innenzelte auf, die
als Schlafkabinen dienen.

Die genannten Bauelemente kann man mit weiteren Bauelementen
kombinieren, die ebenfalls eine Igluform aufweisen, aber als
35 Eckmodule dienen, wobei diese an zwei benachbarten Seiten
jeweils bogenförmige Nahtlinien mit Reißverschlüssen
aufweisen, die in der Umrißform den Nahtlinien der anderen
Bauelemente entsprechen. Unter Zuhilfenahme dieser Eckmodule

295172 90

00.11.95

1 ist es dann möglich, weitere Bauelemente anzuschließen und
Kombinationen von Zeltbaueinheiten zu schaffen, deren Achsen
im rechten Winkel zueinander stehen.

5 Gemäß einer bevorzugten Weiterbildung der Erfindung weisen
insbesondere die teilzylindrischen (tunnelförmigen)
Bauelemente in Achsrichtung ein bestimmtes Rastermaß auf,
bzw. ihre Länge beträgt in Achsrichtung ein ganzzahliges
Vielfaches dieses Rastermaßes. Wenn diese Bauelemente als
10 Schlafkabinen mit Innenzelt dienen, ergibt sich dann eine
Einerschlafkabine, wenn die Länge in Achsrichtung dem
Rastermaß entspricht, eine Zweierschlafkabine hat dann das
doppelte Rastermaß usw.

15

20

25

30

35

295172 90

1 Im folgenden wird die vorliegende Erfindung anhand von
Ausführungsbeispielen näher beschrieben. Dabei zeigen

5 Fig. 1 eine Ansicht eines ersten Zeltbauelements in Form
einer Apsis

Fig. 2 eine Ansicht eines zweiten Zeltbauelements in Form
eines Tunnels

10 Fig. 3 eine Ansicht eines dritten Zeltbauelements in Form
eines Iglus

Fig. 4 eine Ansicht eines vierten Zeltbauelements in Form
eines Eckiglus

15 Fig. 5 eine Ansicht einer Kombination aus verschiedenen
Zeltbauelementen der oben genannten Art zu einer
Baueinheit

20 Fig. 6 eine Ansicht einer Kombination aus verschiedenen
Zeltbauelementen der oben genannten Art zu einer
Baueinheit gemäß einer alternativen Variante

25 Fig. 7 ein weiteres Bauelement für Zelte gemäß einer
alternativen Ausführungsform der Erfindung

Fig. 8 eine Ansicht eines weiteren Zeltbauelements gemäß
einer alternativen Ausführungsform der Erfindung

30 Fig. 9 eine Ansicht eines weiteren Zeltbauelements in
Tunnelform gemäß einer alternativen Variante

Fig. 10 eine Ansicht eines weiteren Zeltbauelements

35 Fig. 11 eine Ansicht eines weiteren Zeltbauelements

Fig. 12 eine Kombination mehrerer Bauelemente der oben
genannten Art zu einer Baueinheit

001195

1 Zunächst wird auf die Fig. 1-6 Bezug genommen, in denen
Bauelemente für Zelte dargestellt sind, die zu einem System
gehören und in einer modularen Bauweise zu verschiedensten
Baueinheiten in zügiger und einfacher Montage zusammensetzbar
5 sind und auch entsprechend einfach demontierbar sind. Dabei
zeigt Fig. 1 ein Bauelement 1, das die Form einer Apsis hat
und bei einer größeren Zeltbaueinheit als Endstück dient. An
der einen Seite hat dieses Bauelement 1 eine halbkreisförmige
Nahtlinie 1a, die mit einem Reißverschluß 1b versehen ist, so
10 daß hier ein Anschluß an verschiedene andere Bauelemente
möglich ist, worauf nachfolgend noch näher eingegangen wird.

Fig. 2 zeigt ein weiteres Bauelement 2, das eine Tunnelform
hat, das heißt also etwa die Form eines Teilzylinders, wobei
15 rechts und links jeweils Nahtlinien 2a, 2b bestehen, die etwa
eine Halbkreisform haben und in der Form einer Nahtlinie 1a
eines Bauelements 1 in Apsisform entsprechen. Damit kann an
ein Bauelement 2 in Tunnelform sowohl rechts als auch links
bei Bedarf jeweils ein Bauelement 1 in Form einer Apsis
20 angeschlossen werden. Entsprechend sind an dem
Tunnelbauelement 2 entlang beider Nahtlinien 2a, 2b jeweils
Reißverschlüsse 2c, 2d vorhanden.

Das Bauelement 3 gemäß Fig. 3 hat etwa die Form eines Iglus,
25 dabei sind rechts und links jeweils halbkreisbogenförmige
Nahtlinien 3a, 3b vorhanden, die im Umriß den Nahtlinien 2a,
2b der Bauelemente 2 in Tunnelform und auch den Nahtlinien 1a
der Bauelemente 1 in Apsisform entsprechen. Damit ist es
möglich an ein Bauelement 3 in Igluform entweder rechts oder
30 links oder auch rechts und links ein abschließendes
Bauelement 1 in Apsisform anzubauen. Ebenso gut ist es
möglich, an ein Bauelement 3 in Igluform zur Verlängerung
oder zum Bau einer größeren Baueinheit rechts und/oder links
ein Bauelement 2 in Tunnelform anzubauen. Ebenso gut können
35 Kombinationen geschaffen werden, bei denen an ein Bauelement
3 in Igluform rechts ein Bauelement 1 in Apsisform angebaut
wird und links ein Bauelement 2 in Tunnelform oder
umgekehrt. Ebenso gut können auch an ein igluförmiges

295172 90

001195

1 Bauelement 3 an beiden Seiten Bauelemente 2 in Tunnelform
angeschlossen werden und dann in Verlängerung dieser wieder
weitere Bauelemente 3 in Igluform angebaut werden, die dann,
je nach Bedarf, endseitig durch Bauelemente 1 in Apsisform
5 abgeschlossen werden. Dieses System ist dabei in
Längsrichtung beliebig verlängerbar. Das Bauelement 3 in
Igluform hat an beiden Seiten im Bereich der Nahtlinien 3a,
3b entsprechende Reißverschlüsse 3c, 3d wie die übrigen
Bauelemente.

10 Eine mögliche Kombination von Bauelementen 1, 2, 3 der
vorgenannten Art ist in Fig. 5 schematisch dargestellt. Wie
man sieht, besteht die Baueinheit aus einem zentralen
Bauelement 3 in Igluform, das ein Innenzelt 30 mit Boden
15 enthält und somit als Schlafzelt dient. An der Vorder- und an
der Rückseite des igluförmigen Bauelements 3 ist jeweils ein
zu öffnender Reißverschluß, so daß man von beiden Seiten her
in das Zelt in Längsrichtung und somit in Achsrichtung der in
Fig. 5 dargestellten Baueinheit gelangen kann. Dagegen ist
20 das igluförmige Bauelement 3 in Richtung senkrecht zu dieser
Längsachsenrichtung geschlossen. Es ergeben sich also zwei
Eingänge vorn und hinten an dem igluförmigen Bauelement 3,
wobei an den einen Eingang das tunnelförmige Bauelement 2
angeschlossen ist und an den anderen Eingang das apsisförmige
25 Bauelement 1 angeschlossen ist. Das apsisförmige Bauelement 1
an der einen Seite dient somit als überdachter Stauraum und
Vorzelt. Das an der anderen Seite angeschlossene
tunnelförmige Bauelement 2 bildet ein weiteres, etwas
größeres teilzylindrisches Vorzelt, das zwar im allgemeinen
30 keinen Zeltboden aufweist, aber als weiterer Aufenthaltsraum
dient. Dabei kann das tunnelförmige Bauelement 2 mit weiteren
Reißverschlüssen versehen sein, so daß ein Öffnen der
Reißverschlüsse und Hochziehen der Zeltplane möglich ist und
sich zur Seite hin ein Fenster 2e ergibt, wie in Fig. 5
35 dargestellt ist.

Weiter in Längsrichtung ist anschließend an das tunnelförmige
Bauelement 2 ein Bauelement 1 in Form einer Apsis vorgesehen,

295172 90

02.11.95

1 das zu dieser Seite hin den Abschluß der Baueinheit bildet
und das tunnelförmige Bauelement 2 in Längsachsenrichtung der
gesamten Baueinheit verlängert und damit weiteren Stauraum
schafft. Auch dieses Bauelement 1 in Form einer Apsis hat ein
5 Fenster 1c bzw. eine Tür, wobei seitlich entlang der
Nahtlinie 1d an beiden Seiten jeweils ein Reißverschluß
vorgesehen ist, so daß man dort den Reißverschluß hochziehen
und die Zeltbahn aufrollen kann. Diese stirnseitige Öffnung,
die durch die Tür 1c gegeben ist, kann als Eingang für die
10 gesamte Zeltbaueinheit dienen. Ebenso gut kann man aber auch
das entsprechende als Apsis ausgebildete Bauelement 1 auf der
gegenüberliegenden Stirnseite als Eingang benutzen. Wahlweise
könnte man auch das Fenster 2e an der Seite des Bauelements 2
in Tunnelform als Eingang benutzen.

15 Ein weiteres Bauelement 4 in Igluform, das als Eckmodul
dient, ist in Fig. 4 dargestellt. Wie man sieht, ist die
Grundform dieses Bauelements 4 ähnlich derjenigen des
ebenfalls igluförmigen Bauelements 3, jedoch hat das
20 igluförmige Eckmodul-Bauelement 4 nicht an zwei Seiten, die
gegenüber liegen, sondern an zwei benachbarten Seiten jeweils
eine bogenförmige Öffnung 4a mit Reißverschlüssen 4b. Dadurch
ist es möglich, das Eckmodul 4 jeweils über Eck, also in
einem 90°-Winkel über Reißverschlüsse mit je einem
25 tunnelförmigen Bauelement 2 zu kombinieren, um dann
gegebenenfalls wiederum weitere Bauelemente z.B. in Igluform
anzuschließen. Das Eckmodul 4 hat dann zwei freibleibende
Seiten, an die kein tunnelförmiges Bauelement angeschlossen
ist und die mit Reißverschlüssen versehen sein können, so daß
30 sie dort das Öffnen ermöglichen und sich so eine weitere
Einstiegsöffnung 4c ergibt.

Fig. 6 zeigt eine beispielhafte Kombination verschiedener
Bauelemente unter Verwendung auch der igluförmigen Eckmodule
35 4. Wie man sieht ist die Baueinheit über Eck im rechten
Winkel gebaut, wobei als zentrales Bauelement das igluförmige
Eckmodul 4 dient. An dieses schließt sich in der Zeichnung
nach rechts hin ein tunnelförmiges Bauelement 2 an. An dieses

295172 90

02.11.93

1 tunnelförmige Bauelement 2 schließt sich wiederum ein
apsisförmiges Bauelement 1 an, wobei durch Öffnen dessen
stirnseitiger Reißverschlüsse hier endseitig ein Eingang für
die gesamte Baueinheit gegeben ist. Rechtwinklig zu dem
5 tunnelförmigen Bauelement 2 schließt sich an das Eckmodul 4
an der anderen Seite ein igluförmiges Bauelement 3 an, mit
einem Innenzelt, das als Schlafkabine dient. Stirnseitig ist
dieses igluförmige Bauelement 3 dann wiederum durch ein
apsisförmiges Bauelement 1 abgeschlossen, das eine durch
10 Reißverschluß zu öffnende Tür 1c hat, die als Eingang dient,
wobei der Benutzer ebensogut die Apsis 1 am anderen Ende als
Eingang benutzen kann.

Ein weiteres erfindungsgemäßes System von modularen
15 Bauelementen für Zelte wird nachfolgend unter Bezugnahme auf
die Fig. 7-12 näher beschrieben. Ähnlich wie bei dem
vorbeschriebenen System gemäß den Fig. 1-6 ist auch hier
wiederum ein Bauelement 7 in Form einer Apsis vorgesehen, das
in Fig. 7 für sich dargestellt ist. Dieses apsisförmige
20 Bauelement 7 dient als stirnseitiger Abschluß für eine
Baueinheit von Zelten. Diese Apsis hat zum einen zwei
Reißverschlüsse, die hochgezogen werden können, so daß sich
eine Türöffnung ergibt, die als Einstieg für die gesamte
Zeltbaueinheit dient. Zum anderen ist an der bogenförmigen
25 Nahtlinie, der Tür gegenüberliegend, ein Reißverschluß für
den Anschluß z.B. an ein tunnelförmiges Bauelement 9 gegeben.
Die bogenförmige Nahtlinie der Apsis 7 entspricht in ihrem
Verlauf und ihren Abmessungen aber nicht nur der Nahtlinie
des tunnelförmigen Bauelements 9 sondern auch derjenigen der
30 Schlafkabine 8, die in Fig. 8 gezeigt ist. Diese Schlafkabine
8 hat etwa die Form eines Halbzylinders, so daß sich an
beiden stirnseitigen Enden jeweils bogenförmige Nahtlinien
mit Reißverschlüssen ergeben, die den Anschluß eines
apsisförmigen Bauelements 7 oder eines tunnelförmigen
35 Bauelements 9 ermöglichen. Die Schlafkabine 8 hat
Befestigungsmöglichkeiten für ein Innenzelt mit Boden,
während tunnelförmiges Bauelement 9 und apsisförmiges

295172 90

02.11.95

1 Bauelement 7 in der Regel nur als Überdachung für Stauraum
dienen und keinen Zeltboden aufweisen.

5 Wie man aus der Darstellung gemäß Fig. 10 erkennt, gibt es
auch Schlafkabinen 10, die in der Form ebenfalls
halbzylinderförmig sind, wie die Schlafkabinen 8, jedoch eine
größere Breite aufweisen. Die Breiten der Schlafkabinen 8, 10
in Achsrichtung werden vorzugsweise so gewählt, daß sie ein
10 Vielfaches eines Rastermaßes betragen, so daß sich dann
Schlafkabinen für eine Person, zwei Personen, drei Personen
etc. ergeben. Die in Fig. 8 dargestellte Schlafkabine 8
eignet sich zum Beispiel für zwei Personen, die in Fig. 10
dargestellte Schlafkabine 10 für drei Personen.

15 Ebenso sind von den Tunnelmodulen 9 auch in Achsrichtung
verschieden lange Bauelemente vorgesehen. Figur 9 zeigt ein
längeres tunnelförmiges Bauelement 9, wohingegen Fig. 11 ein
kürzeres tunnelförmiges Bauelement 11 zeigt. Alle
tunnelförmigen Bauelemente 9, 11 sind an ihren beiden
20 Stirnseiten entlang dem Verlauf der bogenförmigen Nahtlinie
jeweils mit Reißverschlüssen versehen, so daß die Kombination
mit apsisförmigen Bauelementen 7 oder Schlafkabinen 8, 10
möglich ist. Es können aber auch mehrere tunnelförmige
Bauelemente 9, 11 bei Bedarf in Längsrichtung hintereinander
25 geschaltet werden. Die tunnelförmigen Bauelemente 9 können
weitere Reißverschlüsse aufweisen an der Seite, so daß die
Zeltbahn dort geöffnet und aufgerollt werden kann für eine
seitliche Einstiegsöffnung oder ein Fenster. Man kann auch
anstatt die Zeltbahn aufzurollen zwei Stangen verwenden, die
30 man senkrecht aufstellt und an denen man die Enden der
geöffneten Zeltbahn einhängt, so daß diese Zeltbahn dann ein
waagerechtes Vordach bildet, unter dem man sich gegen Regen
geschützt aufhalten kann. Bei der in den Fig. 7-12
dargestellten Variante der Erfindung weisen jeweils die
35 tunnelförmigen Bauelemente 9, 11 und die Schlafkabinen 8, 10
und die apsisförmigen Bauelemente 7 eine gleiche Höhe auf, so
daß die durch Kombinieren sich ergebenden länglichen
Zeltbaueinheiten insgesamt immer etwa gleiche Höhe aufweisen.

295172 90

02.11.95

Fig. 12 zeigt eine solche Kombination mehrerer Bauelemente 7, 11, 8, 9, 7 als Beispiel. Es bieten sich beliebige Variations- und Erweiterungsmöglichkeiten. Bei dieser Variante der Erfindung haben die Schlafkabinen 8, 10 und tunnelförmigen Bauelemente 9, 11 immer eine halbzyklindrische oder teilzyklindrische Form. Im Gegensatz dazu ist bei der Variante gemäß den Fig. 1-6 das igluförmige Bauelement 3 und auch das Eckmodul 4 etwa pyramidal, wobei es sich um Pyramiden mit gekrümmten und nicht ebenen Seitenflächen handelt. Die hier ebenfalls halbzyklindrischen oder teilzyklindrischen tunnelförmigen Bauelemente 2 haben daher, wie man aus Fig. 5 erkennt, eine Firstlinie, die niedriger liegt als die Spitze eines igluförmigen Bauelements 3 oder eines Eckmoduls 4. Die Nahtlinie des igluförmigen Bauelements 3 für den Anbau z.B. eines tunnelförmigen Bauelements 2 oder eines apsisförmigen Bauelements 1 entspricht in ihrem höchsten Punkt der Firstlinie des tunnelförmigen Bauelements 2, und liegt damit unter der Spitze des igluförmigen Bauelements 3, dadurch ergeben sich durch Kombination, wie man in den Fig. 5 und 6 erkennen kann, Baueinheiten, die im Bereich der tunnelförmigen Bauelemente 2 niedriger und im Bereich der igluförmigen Bauelemente 3 und der Eckmodule 4 in der Spitze höher sind und die tunnelförmigen Bauelemente 2 überragen.

295172 90

00.11.95

1

Schutzansprüche:

1. Aus einzelnen Bauelementen in Modulbauweise aufgebautes Zelt, dadurch gekennzeichnet, daß dieses wenigstens ein Bauelement (2, 8, 9, 10, 11) mit teilzylindrischer Form und halbkreisförmigem oder annähernd halbkreisförmigem Querschnitt umfaßt, an dem im stirnseitigen Bereich entlang der bogenförmigen Nahtlinien jeweils Reißverschlüsse (2c, 2d) vorgesehen sind und wenigstens ein Bauelement (1, 7) in Form einer Apsis, dessen stirnseitige bogenförmige Nahtlinie (1a) ebenfalls mit einem Reißverschluß (1b) versehen ist, der der Nahtlinie (2a, 2b) des teilzylindrischen Bauelements (2, 8, 9, 10, 11) entspricht und mit diesem verbindbar ist.
2. Aus einzelnen Bauelementen in Modulbauweise aufgebautes Zelt nach Anspruch 1, dadurch gekennzeichnet, daß das Bauelement (1) in Apsisform stirnseitig eine halbkreisförmige oder annähernd halbkreisförmige Nahtlinie, einen trapezförmigen Grundriß und die Zeltplane im geschlossenen Zustand eine entsprechende Polyedermantelform aufweist oder daß das Bauelement (7) in Apsisform stirnseitig eine halbkreisförmige oder annähernd halbkreisförmige Nahtlinie, einen bogenförmigen Grundriß und die Zeltplane im geschlossenen Zustand eine Teilkugelschalenform aufweist.
3. Aus einzelnen Bauelementen in Modulbauweise aufgebautes Zelt, dadurch gekennzeichnet, daß dieses wenigstens ein Bauelement (3) in Igluform aufweist mit annähernd der Grundform einer quadratischen Pyramide mit gekrümmten Seitenflächen, wobei wenigstens zwei der gekrümmten Seitenflächen entlang jeweils bogenförmiger Nahtlinien (3a, 3b) Reißverschlüsse (3c, 3d) aufweisen, die in der Umrißform den Nahtlinien (2a, 2b) der Bauelemente (2) in Tunnelform und auch den Nahtlinien (1a) der Bauelemente (1) in Apsisform entsprechen, so daß die igluförmigen Bauelemente (3) mittels der Reißverschlüsse (3c, 3d) mit

295172 00

02.11.95

- 1 den apsisförmigen Bauelementen (1) und/oder mit den
teilzylinderförmigen Bauelementen (2) verbindbar sind.
4. Aus einzelnen Bauelementen in Modulbauweise aufgebautes
5 Zelt nach einem der Ansprüche 1-3, dadurch
gekennzeichnet, daß weitere Bauelemente (4) in Igluform
vorgesehen sind, die als Eckmodule dienen, mit einer von
der quadratischen Pyramide abgeleiteten Form mit vier
gekrümmten Seitenflächen und etwa quadratischem
10 Grundriss, wobei das Bauelement (4) an wenigstens zwei
benachbarten Seiten entlang einer bogenförmigen Nahtlinie
jeweils Reißverschlüsse (4b) aufweist, und diese
Nahtlinie in der Umrißform derjenigen der Nahtlinien (2a,
2b) der teilzylindrischen Bauelemente (2) und/oder der
15 Nahtlinien (1a) der apsisförmigen Bauelemente (1)
entspricht, so daß das igluförmige Bauelement (4) über
Eck etwa im rechten Winkel mittels der Reißverschlüsse
mit apsisförmigen Bauelementen (1) und/oder
halbzylinderförmigen Bauelementen (2) und/oder
20 igluförmigen Bauelementen (3) verbindbar ist.
5. Aus einzelnen Bauelementen in Modulbauweise aufgebautes
Zelt nach einem der Ansprüche 1-4, dadurch
gekennzeichnet, daß teilzylindrische Bauelemente (8, 10)
25 mit Innenzelt und Boden vorgesehen sind, die als
Schlafkabine dienen und teilzylindrische Bauelemente (2,
9, 11), die tunnelförmig sind ohne Boden.
6. Aus einzelnen Bauelementen in Modulbauweise aufgebautes
30 Zelt nach einem der Ansprüche 1-5, dadurch
gekennzeichnet, daß die Länge der teilzylindrischen
Bauelemente (2, 8, 9, 10, 11) in Achsrichtung einem
bestimmten Rastermaß entspricht oder ein Mehrfaches
dieses Rastermaßes beträgt.
35

295172 90

00.11.95

Fig.1




Fig. 2




Fig. 3






Fig. 4




295172 90

Fig. 5



02.11.95

Fig. 6



295 172 90

00.11.95

Fig. 7




Fig. 8





Fig. 9



295172 90

02.11.95

Fig.10






Fig.11



295172 90

02.11.93

Fig.12



295172 90

PUB-NO: DE029517290U1
DOCUMENT-IDENTIFIER: DE 29517290 U1
TITLE: Zelt in Modulbauweise
PUBN-DATE: December 21, 1995
PATENT-FAMILY-ID: 8014856

APPLICANT:

NAME	COUNTRY
UMAREX GMBH & CO KG	DE

APPL-NO: DE 29517290 U
APPL-DATE: November 2, 1995

PRIORITY-DATA:

PRIORITY-NO	PRIORITY-APPL-DATE
DE 29517290 U	19951102

CPC-CURRENT:

TYPE	CPC	DATE
CPCI	E04H15/36	20130101
CPCI	E04H15/18	20130101

INT-CL-CURRENT:

TYPE	IPC	DATE
IPCP	E04H15/18	20060101
IPCS	E04H15/36	20060101

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		16861012
	Filing Date		2020-04-28
	First Named Inventor	Jonathan Urhausen	
	Art Unit	3636	
	Examiner Name	Robert Canfield	
	Attorney Docket Number	9693-012A-CON1	

U.S.PATENTS						Remove
Examiner Initial*	Cite No	Patent Number	Kind Code ¹	Issue Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	6772780		2004-08-10	Roy Justin Price	
	2	7556054		2009-07-07	Theodore R. Zeigler	
	3	4945936		1990-08-07	Dennis C. Surrendi	
	4	7131236		2006-11-07	Chad Sample	
	5	4846204		1989-07-11	Bae Sok Kyu	
	6	5666986		1997-09-16	Clifford Royston Fox	
	7	6553699		2003-04-29	Mathias D. Kemeny	
	8	8925565		2015-01-06	Kwan Jun Choi	

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number		16861012
Filing Date		2020-04-28
First Named Inventor	Jonathan Urhausen	
Art Unit	3636	
Examiner Name	Robert Canfield	
Attorney Docket Number	9693-012A-CON1	

9	9243423		2016-01-26	Ki Ho Jin	
10	9243424		2016-01-26	Ki Ho Jin	
11	9631393		2017-04-25	Theodore R. Zeigler	
12	D454609		2002-03-19	Meyerhoffer et al	
13	5069572		1991-12-03	Niksic	
14	4706696		1987-11-17	Gillis	
15	6802329		2004-10-12	Chen	
16	5634483		1997-06-03	Gwin	
17	4995212		1991-02-26	James N. Morgan	
18	6223482		2001-05-01	Herman Zahar	
19	6553698		2003-04-29	Mathias D Kemeny	

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number		16861012
Filing Date		2020-04-28
First Named Inventor	Jonathan Urhausen	
Art Unit		3636
Examiner Name	Robert Canfield	
Attorney Docket Number		9693-012A-CON1

20	8496019		2013-07-30	Nanqing Zhou	
21	9605441		2017-03-28	Kwan Jun Choi	
22	8360085		2013-01-29	Sunghee Lee	
23	5017068		1991-05-21	James D. Cooksey	
24	8448656		2013-05-28	Kwan Jun Choi	
25	4658560		1987-04-21	Bryan J. Beaulieu	
26	5943837		1999-08-31	Richard A. Esser	
27	D544941		2007-06-19	Thomas Edward Rogers	
28	3929146		1975-12-30	Francis H. Maiken	
29	9163425		2015-10-20	Ryan L. Kubica	
30	6758354		2004-07-06	Ottavio Carletti	

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

31	10309093	2019-06-04	Urhausen et al
----	----------	------------	----------------

If you wish to add additional U.S. Patent citation information please click the Add button.

Add

U.S.PATENT APPLICATION PUBLICATIONS

Remove

Examiner Initial*	Cite No	Publication Number	Kind Code ¹	Publication Date	Name of Patentee or Applicant of cited Document	Pages,Columns,Lines where Relevant Passages or Relevant Figures Appear
	1	20130008478		2013-01-10	Alejandro Prieto Estebanez	
	2	20140182643		2014-07-03	Baoqing Yang	
	3	20060260666		2006-11-23	Choi	
	4	20070051399		2007-03-08	In-Young Jung	
	5	20150167343		2015-06-18	Miao Sheng Fang	
	6	20150240513		2015-08-27	Miao Sheng Fang	
	7	20180155952		2018-06-07	Jay Robert	

If you wish to add additional U.S. Published Application citation information please click the Add button.

Add

FOREIGN PATENT DOCUMENTS

Remove

INFORMATION DISCLOSURE STATEMENT BY APPLICANT (Not for submission under 37 CFR 1.99)	Application Number		16861012	
	Filing Date		2020-04-28	
	First Named Inventor	Jonathan Urhausen		
	Art Unit	3636		
	Examiner Name	Robert Canfield		
	Attorney Docket Number	9693-012A-CON1		

Examiner Initial*	Cite No	Foreign Document Number ³	Country Code ² i	Kind Code ⁴	Publication Date	Name of Patentee or Applicant of cited Document	Pages, Columns, Lines where Relevant Passages or Relevant Figures Appear	T ⁵
	1							

If you wish to add additional Foreign Patent Document citation information please click the Add button

NON-PATENT LITERATURE DOCUMENTS

Examiner Initials*	Cite No	Include name of the author (in CAPITAL LETTERS), title of the article (when appropriate), title of the item (book, magazine, journal, serial, symposium, catalog, etc), date, pages(s), volume-issue number(s), publisher, city and/or country where published.	T ⁵
	1		

If you wish to add additional non-patent literature document citation information please click the Add button

EXAMINER SIGNATURE

Examiner Signature		Date Considered	
--------------------	--	-----------------	--

*EXAMINER: Initial if reference considered, whether or not citation is in conformance with MPEP 609. Draw line through a citation if not in conformance and not considered. Include copy of this form with next communication to applicant.

¹ See Kind Codes of USPTO Patent Documents at www.USPTO.GOV or MPEP 901.04. ² Enter office that issued the document, by the two-letter code (WIPO Standard ST.3). ³ For Japanese patent documents, the indication of the year of the reign of the Emperor must precede the serial number of the patent document. ⁴ Kind of document by the appropriate symbols as indicated on the document under WIPO Standard ST.16 if possible. ⁵ Applicant is to place a check mark here if English language translation is attached.

**INFORMATION DISCLOSURE
STATEMENT BY APPLICANT**
(Not for submission under 37 CFR 1.99)

Application Number	16861012
Filing Date	2020-04-28
First Named Inventor	Jonathan Urhausen
Art Unit	3636
Examiner Name	Robert Canfield
Attorney Docket Number	9693-012A-CON1

CERTIFICATION STATEMENT

Please see 37 CFR 1.97 and 1.98 to make the appropriate selection(s):

That each item of information contained in the information disclosure statement was first cited in any communication from a foreign patent office in a counterpart foreign application not more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(1).

OR

☐ That no item of information contained in the information disclosure statement was cited in a communication from a foreign patent office in a counterpart foreign application, and, to the knowledge of the person signing the certification after making reasonable inquiry, no item of information contained in the information disclosure statement was known to any individual designated in 37 CFR 1.56(c) more than three months prior to the filing of the information disclosure statement. See 37 CFR 1.97(e)(2).

See attached certification statement.

The fee set forth in 37 CFR 1.17 (p) has been submitted herewith.

☒ A certification statement is not submitted herewith.

SIGNATURE

A signature of the applicant or representative is required in accordance with CFR 1.33, 10.18. Please see CFR 1.4(d) for the form of the signature.

Signature	/Kelly B. Robinson/	Date (YYYY-MM-DD)	2020-11-04
Name/Print	Kelly B. Robinson	Registration Number	72960

This collection of information is required by 37 CFR 1.97 and 1.98. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 1 hour to complete, including gathering, preparing and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

Electronic Acknowledgement Receipt

EFS ID:	41031297
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	04-NOV-2020
Filing Date:	28-APR-2020
Time Stamp:	11:47:24
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Transmittal Letter	9693-012A- CON1_IDS_Transmittal.pdf	69735 44fb07ce609cb68d3fe0a7f5cfcb73ae94bc943f	no	1

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:					
2	Information Disclosure Statement (IDS) Form (SB08)	9693-012A-CON1_SB-08.pdf	613504	no	7
			5897637234d77086f2d21e5781896516527 edc1a		
Warnings:					
Information:					
Total Files Size (in bytes):			683239		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					

THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re Application: DLX Enterprises, LLC

Serial No.: 16/861,012

Filed: April 28, 2020

Art Unit: 3636

Confirmation No.: 8204

For: SHELTER AND HUB SYSTEM

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

INFORMATION DISCLOSURE STATEMENT

In accordance with 37 C.F.R. 1.56, counsel wishes to make of record the items of information on the PTO/SB/08a for the Examiner's consideration in connection with this application. Inclusion herein of any particular item of information is not to be construed as an admission that same is prior art.

Respectfully submitted,

/Kelly B. Robinson/

Kelly B. Robinson

Reg. No. 72,960

MacCord Mason PLLC

P.O. Box 2974

Greensboro, NC 27402

Date: November 4, 2020

File No.: 9693-012A-CON1

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875						Application or Docket Number 16/861,012				
APPLICATION AS FILED - PART I										
(Column 1)		(Column 2)		SMALL ENTITY		OR OTHER THAN SMALL ENTITY				
FOR	NUMBER FILED	NUMBER EXTRA	RATE(\$)	FEE(\$)		RATE(\$)	FEE(\$)			
BASIC FEE <small>(37 CFR 1.16(a), (b), or (c))</small>	N/A	N/A	N/A	75		N/A				
SEARCH FEE <small>(37 CFR 1.16(k), (l), or (m))</small>	N/A	N/A	N/A	330		N/A				
EXAMINATION FEE <small>(37 CFR 1.16(o), (p), or (q))</small>	N/A	N/A	N/A	380		N/A				
TOTAL CLAIMS <small>(37 CFR 1.16(j))</small>	20	minus 20 = *	x 50 =	0.00	OR					
INDEPENDENT CLAIMS <small>(37 CFR 1.16(h))</small>	2	minus 3 = *	x 230 =	0.00						
APPLICATION SIZE FEE <small>(37 CFR 1.16(s))</small>	If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).			0.00						
MULTIPLE DEPENDENT CLAIM PRESENT <small>(37 CFR 1.16(j))</small>				0.00						
			TOTAL	785		TOTAL				
* If the difference in column 1 is less than zero, enter "0" in column 2.										
APPLICATION AS AMENDED - PART II										
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY		OR OTHER THAN SMALL ENTITY		
AMENDMENT A		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)		RATE(\$)	ADDITIONAL FEE(\$)
	Total <small>(37 CFR 1.16(i))</small>	*	Minus	**	=	x	=	OR	x	=
	Independent <small>(37 CFR 1.16(h))</small>	*	Minus	***	=	x	=	OR	x	=
	Application Size Fee <small>(37 CFR 1.16(s))</small>							OR		
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM <small>(37 CFR 1.16(j))</small>							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY		OR OTHER THAN SMALL ENTITY		
AMENDMENT B		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)		RATE(\$)	ADDITIONAL FEE(\$)
	Total <small>(37 CFR 1.16(i))</small>	*	Minus	**	=	x	=	OR	x	=
	Independent <small>(37 CFR 1.16(h))</small>	*	Minus	***	=	x	=	OR	x	=
	Application Size Fee <small>(37 CFR 1.16(s))</small>							OR		
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM <small>(37 CFR 1.16(j))</small>							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	
* If the entry in column 1 is less than the entry in column 2, write "0" in column 3. ** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20". *** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3". The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1.										



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	865	9693-012A-CON1	20	2

CONFIRMATION NO. 8204

UPDATED FILING RECEIPT

4678
MACCORD MASON PLLC
300 N. GREENE STREET, SUITE 1600
P. O. BOX 2974
GREENSBORO, NC 27402



Date Mailed: 06/03/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, Eugene, OR;

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CON of 16/431,322 06/04/2019
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 05/04/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/861,012**

Projected Publication Date: Request for Non-Publication Acknowledged

Non-Publication Request: Yes

Early Publication Request: No

**** SMALL ENTITY ****

Title

SHELTER AND HUB SYSTEM

Preliminary Class

135

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative,

page 2 of 4

this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

CORRECTED ADS FORM

Application Number	16861012
Title of Invention	SHELTER AND HUB SYSTEM

Inventor Information

****If no data is shown, no data has been corrected****

	Data of Record	Updated Data
Order Number		
Name		

Residence Information

Residency		
City		
State		
Country of Residence		

Mailing Address of Inventor

Address 1		
Address 2		
City,State/Province, Postal Code		
Country		

Application Information

	Data of Record	Updated Data
Title of Invention	SHELTER AND HUB SYSTEM	
Attorney Docket Number	9693-012A-CON1	
Entity Type	Small	

Domestic Benefit/National Stage Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121,365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S. C. 119(e) or 120, and 37 CFR 1.78(a).

	Data of Record	Updated Data
Prior Application Status		
Application Number		
Continuity Type		
Prior Application Number		
Filing Date (YYYY-MM-DD)		
Patent Number		
Issue Date (YYYY-MM-DD)		

Foreign Priority Information

****If no data is shown, no data has been corrected****

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

		Data of Record	Updated Data
	Application Number		
	Country		
	Filing Date		
	Access Code		

Applicant Information

****If no data is shown, no data has been corrected****

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

	Data of Record	Updated Data
Applicant Type	ASG	
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is		
Name of the Deceased or Legally Incapacitated Inventor		
Applicant is an Organization	Yes	
Name		
Organization Name	DLX Enterprises, LLC	
Address 1		520 S. Bertelsen Road
Address 2		

City,State/Province,Postal Code	Eugene OR 97402	
Country	US	
Phone Number		
Fax Number		
Email Address		

Assignee Information including Non-Applicant Assignee Information

****If no data is shown, no data has been corrected****
Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office

	Data of Record	Updated Data
Order	1	
Applicant is an Organization	Yes	
Name		
Organization Name	DLX Enterprises, LLC	

Mailing Address

Address 1		<u>520 S. Bertelsen Road</u>
Address 2		
City,State/Province,Postal Code	Eugene OR	
Country	US	
Phone Number		
Fax Number		
Email Address		

Signature

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b).

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Kelly B. Robinson/	Registration Number	72960
First Name	Kelly B.	Last Name	Robinson

Electronic Acknowledgement Receipt

EFS ID:	39601449
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	02-JUN-2020
Filing Date:	28-APR-2020
Time Stamp:	14:37:21
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----


File Listing:


Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet to update/ correct info	CorrectedADS.pdf	65696	no	5
			80166cb69959adb4056eada75336fcd6dc9 f7e4c		

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:	
Total Files Size (in bytes):	65696
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>	








FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7






FIG. 8








FIG. 11




FIG. 12




FIG. 13





FIG. 14






FIG. 15B




FIG. 15C




FIG. 15D




FIG. 15E




FIG. 15F





FIG. 15G






FIG. 16B




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C





FIG. 20D

REPLACED WITH CLEAN, FORMAL FIGURE



REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 2

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 3

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 4

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 5

REPLACED WITH CLEAN, FORMAL FIGURE





FIG. 6

REPLACED WITH CLEAN, FORMAL FIGURE



REPLACED WITH CLEAN, FORMAL FIGURE






FIG. 8

REPLACED WITH CLEAN, FORMAL FIGURE



REPLACED WITH CLEAN, FORMAL FIGURE



REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 11

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 12

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 13

REPLACED WITH CLEAN, FORMAL FIGURE





FIG. 14

REPLACED WITH CLEAN, FORMAL FIGURE



REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 15B

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 15C

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 15D

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 15E

REPLACED WITH CLEAN, FORMAL FIGURE




FIG. 15F

REPLACED WITH CLEAN, FORMAL FIGURE





FIG. 15G



REPLACED WITH CLEAN, FORMAL FIGURE




Figure 168

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 17

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 19

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 20A

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 20B

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 20C

REPLACED WITH CLEAN, FORMAL FIGURE




Figure 20D

Electronic Patent Application Fee Transmittal

Application Number:	16861012			
Filing Date:	28-Apr-2020			
Title of Invention:	SHELTER AND HUB SYSTEM			
First Named Inventor/Applicant Name:	Jonathan Urhausen			
Filer:	Kelly B. Robinson/Nichol Neal			
Attorney Docket Number:	9693-012A-CON1			
Filed as Small Entity				
Filing Fees for Utility under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
UTILITY FILING FEE (ELECTRONIC FILING)	4011	1	75	75
UTILITY SEARCH FEE	2111	1	330	330
UTILITY EXAMINATION FEE	2311	1	380	380
Pages:				
Claims:				
Miscellaneous-Filing:				
LATE FILING FEE FOR OATH OR DECLARATION	2051	1	80	80
Petition:				

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Patent-Appeals-and-Interference:				
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				
Miscellaneous:				
Total in USD (\$)				865

Electronic Acknowledgement Receipt

EFS ID:	39571804
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	29-MAY-2020
Filing Date:	28-APR-2020
Time Stamp:	11:00:39
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	yes
Payment Type	DA
Payment was successfully received in RAM	\$865
RAM confirmation Number	E20205SB00535426
Deposit Account	
Authorized User	

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

File Listing:					
Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Drawings-only black and white line drawings	Replacement_Sheets.pdf	529262	no	30
			4b87b02785f2b3a99f3b13155a742230bfd d963c		
Warnings:					
The page size in the PDF is too large. The pages should be 8.5 x 11 or A4. If this PDF is submitted, the pages will be resized upon entry into the Image File Wrapper and may affect subsequent processing					
Information:					
2	Drawings-only black and white line drawings	Annotated_Sheets.pdf	25882575	no	30
			3864b7b204e1325b1e169d70262156ab81 4ca1a8		
Warnings:					
The page size in the PDF is too large. The pages should be 8.5 x 11 or A4. If this PDF is submitted, the pages will be resized upon entry into the Image File Wrapper and may affect subsequent processing					
Information:					
3	Fee Worksheet (SB06)	fee-info.pdf	37269	no	2
			bfaed7f902f073936df551cf5e63e3875142f aac		
Warnings:					
Information:					
Total Files Size (in bytes):			26449106		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111

If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	0.00	9693-012A-CON1	20	2

CONFIRMATION NO. 8204
CORRECTED FILING RECEIPT

4678
MACCORD MASON PLLC
300 N. GREENE STREET, SUITE 1600
P. O. BOX 2974
GREENSBORO, NC 27402



Date Mailed: 05/29/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, Eugene, OR;

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CON of 16/431,322 06/04/2019
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 05/04/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/861,012**

Projected Publication Date: Request for Non-Publication Acknowledged

Non-Publication Request: Yes

Early Publication Request: No

**** SMALL ENTITY ****

Title

SHELTER AND HUB SYSTEM

Preliminary Class

135

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative,

page 2 of 4

this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Jonathan Urhausen et al.

Serial No.: 16/861,012

Filing Date: April 28, 2020

Confirmation No.: 8204

For: **SHELTER AND HUB SYSTEM**

Commissioner for Patents

P.O. Box 1450

Alexandria, VA 22313-1450

Sir:

REQUEST FOR CORRECTED FILING RECEIPT

Applicant requests that the Filing Receipt mailed on May 4, 2020, be updated to reflect the correct Applicant's address. The Applicant's city ~~Eugen~~ should read Eugene.

Applicant has attached a copy of the Application Data Sheet as filed on April 28, 2020, as well as a copy of the Filing Receipt showing this correction. Applicant requests that a Corrected Filing Receipt be issued.

The Commissioner is hereby authorized to charge any fees which may be required to Deposit Account No. 501923.

Respectfully submitted,

/Kelly B. Robinson/

Kelly B. Robinson
Registration No. 72960
MacCord Mason PLLC
P. O. Box 2974
Greensboro, NC 27402
(336) 273-4422

Date: May 28, 2020

File No.: 9693-012A-CON1



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	0.00	9693-012A-CON1	20	2

CONFIRMATION NO. 8204

FILING RECEIPT

4678
MACCORD MASON PLLC
300 N. GREENE STREET, SUITE 1600
P. O. BOX 2974
GREENSBORO, NC 27402



Date Mailed: 05/04/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, ~~Eugene~~, OR; Eugene

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CON of 16/431,322 06/04/2019
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2:

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Inventor Information:

Inventor 1				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Jonathan		Urhausen	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 2				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Adam		Barr	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 3				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Donald		Bierman	

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Residence Information (Select One)		☒ US Residency	☐ Non US Residency	☐ Active US Military Service	
City	Eugene	State/Province	OR	Country of Residence ⁱ	US
Mailing Address of Inventor:					
Address 1		245 Jackson Street			
Address 2					
City	Eugene	State/Province	OR		
Postal Code	97402	Country ⁱ	US		
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.					

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).			
☐ An Address is being provided for the correspondence information of this application.			
Customer Number	4678		
Email Address	docketing@maccordmason.com	<input type="button" value="Add Email"/>	<input type="button" value="Remove Email"/>

Application Information:

Title of the Invention	SHELTER AND HUB SYSTEM		
Attorney Docket Number	9693-012A-CON1	Small Entity Status Claimed	☒
Application Type			
Subject Matter			
Total Number of Drawing Sheets (if any)	30	Suggested Figure for Publication (if any)	

Filing By Reference:

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Publication Information:

☐	Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☒	Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)		
Customer Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					

Additional Representative Information blocks may be generated within this form by selecting the **Add** button.

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing benefit claim information in the Application Data Sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.
When referring to the current application, please leave the "Application Number" field blank.

Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
	Continuation of	16/431322	2019-06-04

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Prior Application Status		Patented	Remove		
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
16431322	Continuation of	15/639261	2017-06-30	10309093	2019-06-04

Prior Application Status		Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)	
15639261	Claims benefit of provisional	62/356793	2016-06-30	

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the **Add** button.

Foreign Priority Information:

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Application Number	Country ¹	Filing Date (YYYY-MM-DD)	Access Code ² (if applicable)

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013.

☐ NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant **must opt-out** of the authorization by checking the corresponding box A or B or both in subsection 2 below.

NOTE: This section of the Application Data Sheet is **ONLY** reviewed and processed with the **INITIAL** filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

A. Priority Document Exchange (PDX) - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h)(1).

B. Search Results from U.S. Application to EPO - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

☐ A. Applicant **DOES NOT** authorize the USPTO to permit a participating foreign IP office access to the instant application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.

☐ B. Applicant **DOES NOT** authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

NOTE: Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Applicant 1

If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.

Clear

- ☒ Assignee ☐ Legal Representative under 35 U.S.C. 117 ☐ Joint Inventor
- ☐ Person to whom the inventor is obligated to assign. ☐ Person who shows sufficient proprietary interest

If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:

Name of the Deceased or Legally Incapacitated Inventor:

If the Applicant is an Organization check here. ☒

Organization Name DLX Enterprises, LLC

Mailing Address Information For Applicant:

Address 1 245 Jackson Street

Address 2

City Eugene

State/Province

OR

Country¹ US

Postal Code

97402

Phone Number

Fax Number

Email Address

Additional Applicant Data may be generated within this form by selecting the Add button.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Assignee 1						
Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.						
If the Assignee or Non-Applicant Assignee is an Organization check here.			☒			
Organization Name	DLX Enterprises, LLC					
Mailing Address Information For Assignee including Non-Applicant Assignee:						
Address 1		245 Jackson Street				
Address 2						
City	Eugene	State/Province	OR			
Country i	US	Postal Code	97402			
Phone Number		Fax Number				
Email Address						
Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.						

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Signature:

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). **However, if this Application Data Sheet is submitted with the INITIAL filing of the application and either box A or B is not checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).**

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Kelly B. Robinson/			Date (YYYY-MM-DD)	
First Name	Kelly B.	Last Name	Robinson	Registration Number	72960
Additional Signature may be generated within this form by selecting the Add button.					

Electronic Acknowledgement Receipt

EFS ID:	39557917
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	28-MAY-2020
Filing Date:	28-APR-2020
Time Stamp:	09:46:26
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Request for Corrected Filing Receipt	9693-012A- CON1_Request_for_Corrected_ Filing_Receipt.pdf	145819 05eac52cb0bde7202b72e92b4348f24c4176f2f3	no	2

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:					
2	Application Data Sheet	9693-012A-CON1_ADS.pdf	480098	no	8
			e8b49303b035424107d4320927c0f1925d5524fc		
Warnings:					
Information:					
This is not an USPTO supplied ADS fillable form					
Total Files Size (in bytes):				625917	
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					

PATENT APPLICATION FEE DETERMINATION RECORD Substitute for Form PTO-875						Application or Docket Number 16/861,012				
APPLICATION AS FILED - PART I										
(Column 1)		(Column 2)		SMALL ENTITY		OR OTHER THAN SMALL ENTITY				
FOR	NUMBER FILED	NUMBER EXTRA	RATE(\$)	FEE(\$)		RATE(\$)	FEE(\$)			
BASIC FEE (37 CFR 1.16(a), (b), or (c))	N/A	N/A	N/A	75		N/A				
SEARCH FEE (37 CFR 1.16(k), (l), or (m))	N/A	N/A	N/A	330		N/A				
EXAMINATION FEE (37 CFR 1.16(o), (p), or (q))	N/A	N/A	N/A	380		N/A				
TOTAL CLAIMS (37 CFR 1.16(j))	20	minus 20 = *	x 50 =	0.00	OR					
INDEPENDENT CLAIMS (37 CFR 1.16(h))	2	minus 3 = *	x 230 =	0.00						
APPLICATION SIZE FEE (37 CFR 1.16(s))	If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s).			0.00						
MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))				0.00						
* If the difference in column 1 is less than zero, enter "0" in column 2.			TOTAL	785		TOTAL				
APPLICATION AS AMENDED - PART II										
(Column 1)		(Column 2)		(Column 3)		SMALL ENTITY		OR OTHER THAN SMALL ENTITY		
AMENDMENT A		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)		RATE(\$)	ADDITIONAL FEE(\$)
	Total (37 CFR 1.16(i))	*	Minus	**	=	x	=	OR	x	=
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x	=	OR	x	=
	Application Size Fee (37 CFR 1.16(s))							OR		
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	
AMENDMENT B		CLAIMS REMAINING AFTER AMENDMENT		HIGHEST NUMBER PREVIOUSLY PAID FOR	PRESENT EXTRA	RATE(\$)	ADDITIONAL FEE(\$)		RATE(\$)	ADDITIONAL FEE(\$)
	Total (37 CFR 1.16(i))	*	Minus	**	=	x	=	OR	x	=
	Independent (37 CFR 1.16(h))	*	Minus	***	=	x	=	OR	x	=
	Application Size Fee (37 CFR 1.16(s))							OR		
	FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j))							OR		
						TOTAL ADD'L FEE		OR	TOTAL ADD'L FEE	
* If the entry in column 1 is less than the entry in column 2, write "0" in column 3. ** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20". *** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3". The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1.										



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING OR 371(C) DATE	FIRST NAMED APPLICANT	ATTY. DOCKET NO./TITLE
16/861,012	04/28/2020	Jonathan Urhausen	9693-012A-CON1

CONFIRMATION NO. 8204

FORMALITIES LETTER



OC000000116736011

4678
MACCORD MASON PLLC
300 N. GREENE STREET, SUITE 1600
P. O. BOX 2974
GREENSBORO, NC 27402

Date Mailed: 05/04/2020

NOTICE TO FILE MISSING PARTS OF NONPROVISIONAL APPLICATION

FILED UNDER 37 CFR 1.53(b)

Filing Date Granted

Items Required To Avoid Abandonment:

An application number and filing date have been accorded to this application. The item(s) indicated below, however, are missing. Applicant is given **TWO MONTHS** from the date of this Notice within which to file all required items below to avoid abandonment. Extensions of time may be obtained by filing a petition accompanied by the extension fee under the provisions of 37 CFR 1.136(a).

The application is informal since it does not comply with the regulations for the reason(s) indicated below.

The required item(s) identified below must be timely submitted to avoid abandonment:

- Replacement drawings in compliance with 37 CFR 1.84 and 37 CFR 1.121(d) are required. The drawings submitted are not acceptable because:
 - The drawings must be reasonably free from erasures and must be free from alterations, overwriting, interlineations, folds, and copy marks. See Figure(s) 3, 4, 12.

Applicant is cautioned that correction of the above items may cause the specification and drawings page count to exceed 100 pages. If the specification and drawings exceed 100 pages, applicant will need to submit the required application size fee.

- The statutory basic filing fee is missing.
- The application search fee must be submitted.
- The application examination fee must be submitted.
- Surcharge as set forth in 37 CFR 1.16(f) must be submitted.

The surcharge is due for any one of:

- late submission of the basic filing fee, search fee, or examination fee,
- late submission of inventor's oath or declaration,
- filing an application that does not contain at least one claim on filing, or
- submission of an application filed by reference to a previously filed application.

SUMMARY OF FEES DUE:

The fee(s) required within **TWO MONTHS** from the date of this Notice to avoid abandonment is/are itemized below. Small entity discount is in effect. If applicant is qualified for micro entity status, an acceptable Certification

of Micro Entity Status must be submitted to establish micro entity status. (See 37 CFR 1.29 and forms PTO/SB/15A and 15B.)

- **\$ 75** basic filing fee.
- **\$ 80** surcharge.
- **\$ 330** search fee.
- **\$ 380** examination fee.
- **\$(0) previous unapplied payment amount.**
- **\$ 865** TOTAL FEE BALANCE DUE.

Replies must be received in the USPTO within the set time period or must include a proper Certificate of Mailing or Transmission under 37 CFR 1.8 with a mailing or transmission date within the set time period. For more information and a suggested format, see Form PTO/SB/92 and MPEP 512.

Replies should be mailed to:

Mail Stop Missing Parts
Commissioner for Patents
P.O. Box 1450
Alexandria VA 22313-1450

Registered users of EFS-Web may alternatively submit their reply to this notice via EFS-Web, including a copy of this Notice and selecting the document description "Applicant response to Pre-Exam Formalities Notice".
<https://portal.uspto.gov/authenticate/AuthenticateUserLocalEPF.html>

For more information about EFS-Web please call the USPTO Electronic Business Center at 1-866-217-9197 or visit our website at <http://www.uspto.gov/ebc>.

If you are not using EFS-Web to submit your reply, you must include a copy of this notice.

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at **(571) 272-4000** or **(571) 272-4200** or **1-888-786-0101**.

/tnguyen/



UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE
United States Patent and Trademark Office
Address: COMMISSIONER FOR PATENTS
P.O. Box 1450
Alexandria, Virginia 22313-1450
www.uspto.gov

APPLICATION NUMBER	FILING or 371(c) DATE	GRP ART UNIT	FIL FEE REC'D	ATTY. DOCKET NO	TOT CLAIMS	IND CLAIMS
16/861,012	04/28/2020	3636	0.00	9693-012A-CON1	20	2

CONFIRMATION NO. 8204

FILING RECEIPT

4678
MACCORD MASON PLLC
300 N. GREENE STREET, SUITE 1600
P. O. BOX 2974
GREENSBORO, NC 27402



Date Mailed: 05/04/2020

Receipt is acknowledged of this non-provisional utility patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF FIRST INVENTOR, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection.

Please verify the accuracy of the data presented on this receipt. If an error is noted on this Filing Receipt, please submit a written request for a corrected Filing Receipt, including a properly marked-up ADS showing the changes with strike-through for deletions and underlining for additions. If you received a "Notice to File Missing Parts" or other Notice requiring a response for this application, please submit any request for correction to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections provided that the request is grantable.

Inventor(s)

Jonathan Urhausen, Eugene, OR;
Adam Barr, Eugene, OR;
Donald Bierman, Eugene, OR;

Applicant(s)

DLX Enterprises, LLC, Eugen, OR;

Assignment For Published Patent Application

DLX Enterprises, LLC, Eugene, OR

Power of Attorney: The patent practitioners associated with Customer Number 04678

Domestic Priority data as claimed by applicant

This application is a CON of 16/431,322 06/04/2019
which is a CON of 15/639,261 06/30/2017 PAT 10309093
which claims benefit of 62/356,793 06/30/2016

Foreign Applications for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.

Permission to Access Application via Priority Document Exchange: Yes

Permission to Access Search Results: Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

If Required, Foreign Filing License Granted: 05/04/2020

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 16/861,012**

Projected Publication Date: Request for Non-Publication Acknowledged

Non-Publication Request: Yes

Early Publication Request: No

**** SMALL ENTITY ****

Title

SHELTER AND HUB SYSTEM

Preliminary Class

135

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications: No

PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative,

page 2 of 4

this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

LICENSE FOR FOREIGN FILING UNDER
Title 35, United States Code, Section 184
Title 37, Code of Federal Regulations, 5.11 & 5.15

GRANTED

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

NOT GRANTED

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

SelectUSA

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

IN THE UNITED STATES PATENT AND TRADEMARK OFFICE

In re application of: Urhausen *et. al*
Serial No. 15/639261
Filing Date: June 30, 2017
Confirmation No. 1068
For: **SHELTER AND HUB SYSTEM**
Customer No. 04678

Commissioner for Patents
P.O. Box 1450
Alexandria, VA 22313-1450

POWER OF ATTORNEY

Sir:

The undersigned, assignee of the entire interest in and to an application of Urhausen et al. for U.S. Letters Patent for **SHELTER AND HUB SYSTEM** filed June 30, 2017, Application Serial No. 15/639261, by an assignment document recorded with the Patent and Trademark Office, hereby appoints the firm of MacCord Mason PLLC, comprising Edward W. Rilee, Reg. No. 31,869, Howard A. MacCord, Jr., Reg. No. 28,639, James L. Lester, Reg. No. 38,721, Jason T. Condrasky, Reg. No. 62,699, Carla L. Gannon, Reg. No. 56,358, Kelly B. Robinson, Reg. No. 72,960, and Douglas C. Tsao, Reg. No. 72,349, as my attorneys and/or agents with full power of substitution and revocation, to prosecute this application, to make alterations and amendments therein, to receive the patent, and to transact all business in the Patent and Trademark Office connected therewith. All of the above-identified attorneys are associated with Customer Number 04678.


Furthermore, in accordance with 37 CFR 3.73(b), the undersigned hereby states that the

documentary evidence of a chain of title from the original owner to the assignee, i.e. assignment document referenced above, has been reviewed and the undersigned certifies that, to the best of assignee's knowledge and belief, title is in assignee who seeks to prosecute this application.

The undersigned (whose title is supplied below), is authorized to act on behalf of the applicant/assignee.

PLEASE ADDRESS ALL COMMUNICATIONS AND TELEPHONE CALLS TO:
MACCORD MASON PLLC, P. O. BOX 2974, GREENSBORO, NORTH CAROLINA
27402, (336) 273-4422. Our Customer Number is 04678.

DLX Enterprises LLC

x 
Jonathan Urhausen
Managing Member

Date: x 09/14/17

SHELTER AND HUB SYSTEM

This application is a continuation of Application Serial No. 16/431,322, filed June 4, 2019, which is a continuation of Application Serial No. 15/639261, filed June 30, 2017, now Patent No. 10,309,093, which claims benefit of provisional 62/356,793, filed June 30, 2016.

Field of the Technology

The present disclosure relates generally to shelters and hub systems for shelters, and more particularly to an improved hub system, apparatus, kit and methods, for example, for deployable shelter assemblies.

Background

Deployable shelters, tents, rapid-deployment shelters, forts and the like typically include sheets of fabric, or other materials, secured to a frame. Often these units are free-standing or are similarly semi-attached to a ground surface or tangential fixture. In some instances, guy ropes help anchor the unit to a ground surface once the shelter is assembled. Rapid deployment and assembly of such a shelter is often a difficult and demanding task, particularly during emergency situations and in uncertain environmental conditions.

For instance, rapid tactical shelters are used in a variety of demanding on-site scenarios including fire, incident command, communication areas, crime scene investigation, flu vaccination, military deployment, temporary hospital, and other on-site emergency response spots in a variety of challenging terrains, and environmental conditions. Rapid deployment, with quick and easy set-up and take-down of such units is often beneficial, if not necessary. Deployment situations may be, for example, in extreme heat or cold, during on-going emergencies and in remote locations, making ease of assembly extremely important and transportation of weighted items impractical. Durability of items in such terrain and environmental situations can also be a challenge.

Incremental changes to weight, cost, ease of assembly and durability of deployable shelters and related shelter systems can result in large improvements in the field.

Therefore, Applicants desire improved systems, kits, assemblies, apparatus and methods for shelter and hub systems for deployment shelters and it is toward these and
5 other challenges the present disclosure is directed.

Summary

In accordance with the present disclosure, hub systems and improved shelter systems and assemblies are provided for deployment of shelters, forts deployment tents and the like. This disclosure provides an improved hub system that is convenient,
5 efficient, easily portable, reliable, durable, and quick for the user, particularly when used in conjunction with other accessories often used in deployment shelters, for example HVAC, lighting, power cords, interior insulation, etc.

In one embodiment of the present disclosure, a hub for assembly of a shelter may include at least one receiver slot, a receiver sleeve, and at least one attachment point.

10 Other embodiments may be considered a hub for assembly of a rapid-deployment shelter. The hub may include, in some examples, a set of receiver slots, a receiver sleeve and a set of attachment projections. The receiver slot may include two parallel slot walls, a slot floor and a center slot wall. The receiver sleeve may be medially positioned to the receiver slots. The set of attachment projections may be rounded or may take on other
15 shapes. The set of attachment projections may be attached at each end to a slot wall.

In some embodiments, a receiver sleeve may include an inner receiver and an outer receiver. The inner receiver and outer receiver may form a pressure lock system. The inner receiver and outer receiver walls may be angled. The angle may, for example, be between about .001 and 1 degrees, or is contemplated to also be more. In some
20 examples, the taper may be at .5 degrees. The inner receiver may be angled inwardly from the floor. The outer receiver may be angled outwardly from the floor. In some examples, the taper of the angle of the outer receiver may be opposite that of the taper of the angle of the inner receiver.

Some examples of frame and hub assemblies include a set of hubs and a set of
25 frame poles. In some examples, the frame and hub assembly may include variations of the hub, for example, partial hubs, by way of example, for corners of the frame assembly. Embodiments may include methods for assembly of the frame and hub assembly in which the frame poles are connected through the hubs. In some examples, a hub may be placed and oriented top down, bottom down and/or on a hub side to form the frame and

hub assembly. There may be a portion of the hubs horizontally oriented in connecting the hubs and a portion of the hubs vertically oriented in the frame and hub assembly. There may be partial hubs included in the frame and hub assembly. Partial hubs may be specialized to accept frame poles in hard to fit positions, for example, in frame and hub assembly corners and/or long frame pole articulations.

5 In still other examples, the inventions of the present disclosure may be considered a frame for an emergency, rapid-deployment shelter system. The frame may include a set of hubs and a set of frame poles, a portion of the frame poles secured with a portion of the hubs to form a skeleton frame for a rapid-deployment shelter system. The rapid-
10 deployment shelter system may include more than one shelter. The rapid-deployment shelter system may include more than one shelter mated with other rapid-deployment shelters. A shelter hub may interconnect more than one rapid-deployment shelter.

Other embodiments may be considered a shelter system including a frame, a cover and at least one hub. The frame may include a plurality of interconnected frame
15 poles. The frame poles may be configured to alternate between a first extended position and a second retracted position. The cover may be configured to mate with the frame and/or be secured to the frame. The hub may include a set of receiver slots, a receiver sleeve, and a set of attachment projections.

In other examples the inventions disclosed may be considered hub and shelter
20 methods, for example a method for a hub, a method for a shelter system kit, a method for an improved shelter and a method for rapid deployment of a shelter according to the disclosure.

The above summary was intended to summarize certain embodiments of the present disclosure. Embodiments will be set forth in more detail in the figures and
25 description of embodiments below. It will be apparent, however, that the description of embodiments is not intended to limit the inventions of the present disclosure, the scope of which should be properly determined by the appended claims.

Brief Description of the Drawings

Embodiments of the disclosure will be better understood by a reading of the Description of Embodiments along with a review of the drawings, in which:

5 Figure 1 is a side perspective view of one example of a hub for a deployment shelter according to an embodiment of the disclosure;

 Figure 2 is a front view of a one example of a deployment shelter with a hub system according to an embodiment of the disclosure;
10

 Figure 3 is a top view of one example of a hub according to the present disclosure;

 Figure 4 is a top view of one example of a hub according to the embodiment of
15 Figure 1;

 Figure 5 is a side perspective view of one example of a pin and a washer element of the hub system;

20 Figure 6 is another example of a bottom view of a hub according to the present disclosure;

 Figure 7 is a side perspective view of one example of a hub according to the embodiment of Figure 1;
25

 Figure 8 is a side perspective view of one example of a portion of a hub assembly of a hub system according to the present disclosure;

Figure 9 is a perspective view of another example of a portion of a hub assembly of a hub system, according to the present disclosure;

5 Figure 10 is a perspective view of one example of a frame and hub assembly of the rapid-deployment frame and shelter system, according to Figure 2;

Figure 11 is a close-up view of one example of the frame and hub assembly according to Figure 10;

10 Figure 12 is a close-up view of one example of a lower portion of the frame and hub assembly according to Figure 10;

Figure 13 is another opposite side perspective view of one example of the frame and hub assembly according to Figure 10;

15

Figure 14 is a close-up view of one example of a corner frame and hub assembly showing an example of a partial hub according to Figure 10;

Figure 15 A-G is perspective view of another example of a frame and hub assembly in a first deployed position and a second retracted position, according to the present disclosure;

20

Figure 16A-B are exploded views of one example of a shelter and shelter frame according to examples of the present disclosure;

25

Figure 17 is a perspective view of one example of a shelter including a hub;

Figures 18-19 are perspective views of examples of a shelter system according to embodiments of the present disclosure; and

Figures 20A-D are perspective views of examples of shelters forming a shelter system according to embodiments of the present disclosure.

Description of Embodiments

In the following description, like reference characters designate like or corresponding parts throughout the several views. Also in the following description, it is to be understood that such terms as "forward," "rearward," "left," "right," "upwardly,"
5 "downwardly," and the like are words of convenience and are not to be construed as limiting terms.

Referring now to the drawings in general, it will be understood that the illustrations are for the purpose of describing embodiments of the disclosure and are not intended to limit the disclosure or any invention thereto. Collapsible shelters generally
10 have a short lifespan as they expand and then collapse into a carryable form repetitively and generally are thrown about to experience a significant amount of wear and tear. These types of shelters are often thought of as readily replaceable and priced accordingly. Rapid deployment shelters, however, are much more significant purchases and are used under extreme conditions in emergency deployments, precarious weather situations, in
15 remote locations and are expected for function seamlessly with higher expectations in repetitive deployments. Applicant realizes that durability, strength and weight associated with rapid deployment shelters are extreme challenges and can all be limiting factors. It is to these and other challenges that Applicant's improved hub and shelter system is directed.

20 Figure 1 shows a side view of one example of a hub 10 for a shelter according to an embodiment of the disclosure. A hub 10 for assembly of a shelter may include at least one receiver slot 12, a receiver sleeve 20, and at least one attachment projection 30. In some examples, at least a portion of the hub 10 is made of glass filled nylon and in other examples; the hub 10 may be entirely made of glass filled nylon. Applicant realized that
25 formulating the hub 10 out of glass filled nylon, for example instead of the traditional metal, could give the hub slightly more flexibility than a metal hub, however, strength and durability were concerns. Applicant's hub 10 may exclude metal parts.

One or more hubs 10 may make up a hub system for a deployment shelter 50, as seen in figure 2. An articulating frame system of frame poles 52 may mate with, provide

a skeleton frame for, a shelter cover. Shelter covers are often made of a fabric or canvas material that may be torn or ripped during contact with traditional frames, especially those with metal parts and assemblies. Applicant's hub reduces the chances of wear and tear on both the frame and the cover of the shelter. In many cases, when a shelter is expanded, a cover is required to be secured to the frame by way of an attachment strap with an attachment buckle that expands between the cover and the hub. The need for such attachment straps have been eliminated with Applicant's improved hub, in one example, by the hub pressure lock structure, described in more detail later. In some examples, however, attachment straps and/or buckles may be desired and are considered with the scope of the inventions of the disclosure.

Any of the shelters shown or described herein may include a variety of field deployment elements. For instance, the shelter may be light weight for easy carry transport and may include an articulated frame, robust coverings/canopy and canopy features, flooring, floor liner, door ends and openings, lighting features, power features, electrical supply, lighting, liners, bedding, bunk bedding, tables, shelter identification tags, emergency response equipment, and additional water features and water bladders, anchor weights, and sand bags. The shelters may be any size and multiple shelters may be joined through door openings and/or door ends to create scalable complexes with the advantages of the inventions herein. Joined shelters may be considered shelter systems including more than one shelter joined at a matched face and include any of the embodiments and features included in the present disclosure. Some shelters may serve as a shelter hub and include scalability of connectivity between two or more shelters.

Particular shelter examples include, but are not limited thereto, a unit with floor space of about fifteen feet by twelve feet and an area of about one hundred and height square feet; a unit with floor space of fifteen feet by eighteen feet and an area of about two hundred and seventy feet; and a variety of other sizes.

In other embodiments, the disclosure includes a shelter kit. In this embodiment, the kit may comprise at least one shelter, e.g. any of the shelters and/or shelter

accessories shown or described, and a plurality of hubs 10, e.g. any of the hub embodiments shown or described.

Other embodiments, seen throughout Figures 3-8, may be considered a hub 10 for assembly of a rapid-deployment shelter 50. The hub may include, in some examples, a set of receiver slots 12, a receiver sleeve 20 and a set of attachment projections 30. The receiver slot 12 may include slot walls 14, a slot floor 16 and a center slot wall. The receiver sleeve 20 may be medially positioned to the receiver slots 12. The set of attachment projections 30 may be rounded or may take on other shapes. The set of attachment projections 30 may be attached at each end to a slot wall 14. In some examples, an attachment area 29 may be formed between two slots. The attachment area 29 may have one side forming a substantially right angle, formed by the intersection of two receiver slot walls. Opposite the attachment area side having a substantially right angle, the area 29 may include a rounded surface. An attachment projection 30 may be cornered between two receiver slots 12.

The receiver slot 12 may include a first slot wall 14 and a second slot wall 14, positioned such that the two slot walls are substantially parallel, and each attached to a slot center wall and a slot floor 16. In some examples, a slot wall 14 of one receiver slot 12 is substantially perpendicular to the slot wall 14 of an adjacent receiver slot 14.

In some embodiments, receiver sleeve 20 may include an inner receiver 24 and an outer receiver 22 and a sleeve bottom 26. The inner receiver 24 and outer receiver 22 may form a pressure lock system. The inner receiver 24 and outer receiver 22 walls may be angled. The angle may, for example, be between about .001 and 1 degrees, or is contemplated to also be more. The inner receiver 24 may be angled inwardly from the floor. The outer receiver 22 may be angled outwardly from the floor. The inner receiver 24 and outer receiver 22 walls may be angled away from each other at the top of the receiver 20 and toward each other toward the floor of receiver 20. The angled inner receiver 24 wall and the angled outer receiver wall 22 may form a pressure lock system for accepting a frame pole 52, for example and specifically a spacer pole 51, and securing the pole with the hub 10.

Attachment projections 30 may be attached on one end to a slot wall 14 that is perpendicular to the slot wall 14 attached to the other attachment projection end.

Attachment projections may be curved, rounded or take on any other applicable shape.

Many shelter accessories 60 (see Figure 9) are utilized with rapid deployment shelters, as previously discussed, and these items often need to be attached or secured with the shelter. Such items as HVAC components and insulation sheets can be heavy and place a large weight load on the shelter, especially the shelter frame, and there is traditionally not a good place to attach such items. Applicant's hub system includes attachment projections 30 and a pin system 80 that collectively simplify assembly of the shelter and also provide unique attachment options for accessory items and attachments, without compromising the frame and shelter integrity and without increasing shelter carry weight. Attachment projections 30 secure attachment objects to the frame securely so that the attachment objections do not move along the frame. In some examples, the rounded outer side of projections 30 presents a curved surface for contact with the shelter canopy and other accessory items, preventing wear and tearing that may occur with a non-rounded surface.

The attachment projections 30 are configured to allow shelter accessory 60 attachment with accessory attachments 60.

The hub weight, in some examples, may be less than or equal to about 1.75 oz. The hub weight in other examples may be between about 1.25 oz. to about 1.75 oz. The hub may be at least about 4mm thick. The hub may be at least about 5mm thick in other examples. Applicant was able to realize a reduced hub weight of over 40% of that of conventional hubs, while increasing the strength and durability of the hub 10.

In some embodiments, attachment projections 30 may be about 0.20 to about 0.260 inches in thickness. The attachment projections 30 may be at least 0.250 inches in thickness. The hub base, flooring between the slot walls 14, may be substantially between 0.150 inches to about 0.200 inches in thickness. The hub base may be at least 0.200 inches in thickness in some examples.

Applicant conducted vertical break testing for the hub to simulate the weight that is often supported from a hanging position on attachment points for rapid deployment shelters by accessory and attachment items. Weight was applied to the hub in increments and increased until vertical break was detected. Applicant desired attachment points with low weight, ease of access, durability and strength. In some examples, hub 10 and the attachment projections 30 may have an average vertical break of above 125 lbs., 145 lbs. or 155 lbs. In some examples, the vertical break may be between about 145 lbs. and about 170 lbs.

Applicant conducted lateral break testing to simulate the side pull that is may be withstood from a side load position. Again, Applicant desired attachment points with low weight, ease of access, durability and strength. Weight was again applied to the hub in increments until vertical break was detected. In some examples, the hub 10 and attachment projections 30 may have an average lateral break of above 150 lbs., 160 lbs., or 170 lbs. In some examples, the lateral break may be between 150 lbs. and about 200 lbs.

Other embodiments may be considered a shelter system 70 including a frame 72, a cover /canopy 56 and at least one hub 10. The frame 72 may include a plurality of interconnected frame poles 52. The frame may include a connector 57. The connector 57 may span between the front right and front left corners of the frame. The connector 57 may also span between the back left and back right corners of the frame. The connectors may be frame poles 52, straps, elastic, nylon or any other suitable material. The connectors may stabilize the frame. The connectors may be a set of connectors joined end to end. The connectors may be frame base connectors. The frame poles 52 may be configured to alternate between a first extended position and a second retracted position. The retracted position may include just the frame poles 52 in a retracted position, the frame poles 52 and the hubs 10 in a retracted position, and/or the frame poles 52, hubs 10 and the canopy 56 in a retracted position, assembled and/or unassembled for storage and transport. The entire shelter system may fully retract in a second position and fully expand without assembly into a first deployed position. The cover 56 may be configured

to mate with the frame 72 and/or be secured to the frame or may be already mated with the frame. The hub 10 may include a set of receiver slots 12, a receiver sleeve 20, and a set of attachment projections 30.

5 In some embodiments the pin system 80 may include a plurality of pins and matched washers. Applicant's pin system, as seen in Figures 5 and 7, may fit through slot openings 17 on slot receiver walls 14 to secure in place attachments and/or frame poles 52. Once a frame pole 52 is mated with a hub 10, the pole 52 may be secured movably to the hub 10 with a pin system 80 with a washer 89 and pin 86. Applicant's articulating frame poles 52 and configuration may include openings that accommodate and match
10 with the openings 17 and the pin system 80. By way of example, the pin 86 and washer 89 may be made of glass filled nylon able to remain durable and also light weight and easy to repeatedly remove and replace into position. In this example, the pin 86 is configured to slide through the hub and tubes of the frame and to mate with its mated washer that is configured to pop over the end of the pin to lock tight. Conventionally,
15 metal pins with split rings have been utilized with shelters, with the split rings being difficult to remove and assemble quickly and extremely difficult to replace in the field. Applicant's pin system increases ease of assembly and removal, maintains strength and decreases weight load. Applicant's pin system is economical, durable and reduces the time for assembly and/or repair of the shelter system.

20 Figures 10-14 show examples of a shelter system, one example including frame and hub assemblies, 70. A frame and hub assembly may include a set of hubs 10 and a set of frame poles 72. In some examples, the frame and hub assembly may include variations of the hub, for example, partial hubs 63, by way of example, for corners of the frame assembly. Embodiments may include methods for assembly of the frame and hub
25 assembly in which the frame poles are connected through the hubs. In some examples, a hub may be placed and oriented top down, bottom down and/or on a hub side (seen in Figure 12) to form the frame and hub assembly. There may be a portion of the hubs horizontally oriented in connecting the frame poles and a portion of the hubs vertically oriented in the frame and hub assembly. There may be partial hubs included in the frame

and hub assembly. Partial hubs 63 may be specialized to accept frame poles in particular hard to fit positions, for example, in frame and hub assembly corners and/or long frame pole articulations.

5 In still other examples, the inventions of the present disclosure may be considered a shelter and frame for an emergency, rapid-deployment shelter system. The frame may include a set of hubs 10 and a set of frame poles 52, at least a portion of the frame poles secured with a portion of the hubs to form a skeleton frame for a rapid-deployment shelter system. The shelter and frame for an emergency, rapid-deployment shelter system fully assembled and movable between a first deployed position and a second retractable
10 position. In the retracted position, the canopy, 56, frame poles 72 and hubs 10 may stay substantially attached with the frame poles 72 collapsing parallel and next to each other. The frame poles 72 may be internal poles, external poles and ceiling poles. Frame poles 72 may, for example, be in pairs 77. The poles in pairs may be connected at about a center point and the poles may retract to be parallel in the same plane. The poles in pairs
15 may be connected at about a center point and the poles may rotate about an axis A (Figure 10, 13) at the connected point to diverge at their ends away from each other. The connected poles may diverge at an angle alpha. The angle alpha may be about 1 to less than 90 degree. The angle alpha may, by way of example, be about 5 to about 25 degrees.

As seen in Figure 11, the frame poles 52 may link with the hubs 10 to form frame
20 72. Attachment projections 30 are configured to accept attachment items.

Figure 12 shows a vertically aligned hub 10. Vertically aligned hubs 10 within the frame 72 may, as shown in Figure 12, configure a space into the frame system and act as a spacer between two surfaces. The lower frame poles 52 in this example connect with a receiver slot 12 on a hub, thus the hub acting as a spacer to maintain a space between at
25 least a portion of the lower frame poles 52 and the ground. In this instance, the space 73 is beneficial and allows portions of the canopy to wrap under the frame 70, and in some examples, without supporting weight.

Figures 15A-G show a shelter system 70 in a retracted position (Figure 15A). The shelter system may include a case 85. The case 85 may be a tough and durable material,

for example, a vinyl material. The shelter may be encased in the cover for transport and storage. In use, the case is removed, and a liner may be included. In this example, the liner is removed. The shelter legs are bunched together in a substantially parallel position in the retracted position (Figure 15B). A user may determine the door ends 59 and the wall ends 61 of the retracted shelter. A door end 59 will typically have at least 5 legs and the wall ends of the shelter typically have less than 5 legs. The shelter may be staged in its desired location. Expansion bars may be located within the frame, for example, top center bars of each wall, to be grasped and pulled apart, away from the retracted shelter on each wall end. The shelter may best, by way of example, move into the deployed position by raising the shelter slightly off the ground as the expansion bars are pulled outwardly as the articulating frame expands (Figure 15C). The user lifts at the center point of each door end at the front and back of the shelter and the frame lifts into place, self-standing and fully deployed (Figure 15D, 15G). A floor 58'/floor liner 58 may be added to the shelter or may be included (Figure 15F). The floor may be aligned to meet the shelter canopy sides and ends. An insulation liner 65 may be attached at the projections 30. Other accessory items may be added to the system 70, by way of example, there may be an HVAC access panel in the canopy at which point an HVAC duct is placed and secured in order to attach to an HVAC system. In other examples, lighting, power, and supplies may also be added to the shelter system.

In other embodiments, the inventions of the present disclosure may be considered a shelter and frame for an emergency, rapid-deployment shelter system 170. A shelter 50 may include a door end 59 including an arch framework, the frame 72 forming an arch frame end 110 at the door end 59. As seen in Figures 2, 16A, and 18, and exploded in Figure 16B. The arched frame end 110 may include angles α_A at the corners of the shelter. The angles α_A may, in some examples include upper angles of greater than 90 degrees. In some examples, the α_A angles in the upper angles of the shelter may be between 90 degrees and 150 degrees. In some examples, the upper angles may more specifically be all above 125 degrees. Still, in other examples, the upper angle 72b may be greater than upper angles 72a and 72c. Upper angle 72b may be in some examples

between 130 degrees and 145 degrees, and preferably in some examples between 135 and 140 degrees. Angles 72a and 72c may in some examples include an angle of between 125 degrees and 135 degrees, and in some examples preferably between 128 degrees and 132 degrees. Angles at legs 72d and 72e may be angles of less than angles 72a and 72c. In
5 some embodiments, angles 72d, 72e may be between 65 degrees and 75 degrees, and more specifically in some examples, between 70 degrees and 74 degrees.

Shelters may be assembled door end 59 to door end 59 to form a scalable shelter complex. In this example, as shown in Figures 18 and 20A-D, one shelter having an arched frame end 110 may mate directly with another shelter having an arched frame end
10 110. In one embodiment, the two shelters, both including the arched frame ends may mate directly between the two arched frame ends 110, without requiring a vestibule or smaller opening structure between the two arched frame ends 110. A shelter attachment 140 may mimic the door end 59 frame dimension and fit with the adjoining shelters to direct a water flow away from the arched frame ends 110 where they connect, and direct
15 it, as a gutter away from the shelter system, see Figure 19. In some examples, the shelter attachment 140 may assist in making a substantially waterproof connection site between two adjoining shelters.

In other examples, a shelter may include more than one door end 59. A shelter with more than one door end 59 may, in some example be a hub shelter 150, allowing the
20 attachment of more than one additional shelters, and in some cases up to four additional shelters for form a shelter system 170 adaptable as a shelter complex. The hub shelter 150 may include, in some embodiments two additional door ends 59 in place of the wall ends 61. As shown in Figures 20A-D this configuration allows the hub shelter 150 to adjoin with other shelters without a narrowing opening between the two shelters. The hub
25 shelter 150 also is adaptable to accommodate at least four shelter attachments to the shelter hub 150. The shelter hub 150 may include four arched frame ends 110 that each mate with shelters having an arched frame end 110. The hub shelter 150 may include a larger surface area along the door end 59, while still mating an arched frame end 110 to the arched frame end 110 of the adjoining shelter 50. The hub shelter 150 may include

other configurations of frame end openings, including a rounded opening by way of example and mate with an adjoining shelter 70 including a frame end opening with the same dimensions so that the two shelters 150, 70 mate without a narrowing in the opening between the two shelter frame end openings. The hub shelter may include
5 corners 112. The corners 112 may project between the shelters 50 adjoining the shelter hub 150 at the frame end openings.

In other examples the inventions disclosed may be considered hub and shelter methods, for example a method for a hub, a method for a shelter system kit, a method for an improved shelter and a method for rapid deployment of a shelter according to the
10 disclosure.

In yet another embodiment of the disclosure, included is a method for assembling a collapsed shelter 10 and securing the shelter 10 with a hub system according to any of the examples disclosed. In one example, the method may include carrying the shelter10 collapsed, separating and/or unfolding the walls 12, expanding the shelter 10, aligning the
15 frame of the shelter with a hub system to secure the shelter, e.g. including any of the embodiments previously shown or described. The method may also include attaching accessory items to an attachment projection 30 of a hub 10.

Portability of the shelter allows any of the shelter embodiments and examples shown and described herein to be transported to remote and difficult to reach locations,
20 for instance because the hub and shelter components are lightweight to carry and collapsible. Often, in rapid deployment situations, shelters may be quickly set-up in a variety of environments, quickly taken-down and remain easily mobile.

Those of ordinary skill in the art having the benefit of this disclosure will recognize that any of the shelters and hub system described herein includes a variety of
25 sizes, shapes, styles and support materials, all of which are considered within the scope of this disclosure.

Numerous characteristics and advantages have been set forth in the foregoing description, together with details of structure and function. Many of the novel features are pointed out in the appended claims. The disclosure, however, is illustrative only, and

changes may be made in detail, especially in matters of shape, size, and arrangement of parts, within the principle of the disclosure, to the full extent indicated by the broad general meaning of the terms in which the general claims are expressed. It is further noted that, as used in this application, the singular forms “a,” “an,” and “the” include
5 plural referents unless expressly and unequivocally limited to one referent.

We Claim:

1. A rapid-deployment shelter system, said shelter system comprising:
a first shelter including a door end,
5 a second shelter including a door end, and
wherein each door end is configured to mate directly one with the other
and form a shelter complex having an interior space without a narrowing
between the door ends.
- 10 2. The shelter system of claim 1, wherein said first shelter door end and said second
shelter door end are arched door ends.
3. The shelter system of claim 1, wherein the first shelter is a hub shelter.
- 15 4. The shelter system of claim 3, wherein the hub shelter door end and the second
shelter door end are arched door ends.
5. The shelter system of claim 4, wherein the hub shelter and the second shelter
adjoin one with another to form a continuous interior space in the shelter
20 complex.
6. The shelter system of claim 5, wherein the arched door ends include a set of upper
angles and a set of lower angles.
- 25 7. The shelter system of claim 6, wherein the set of upper angles are each greater
than the angles of each lower angle in the set of lower angles.
8. The shelter system of claim 7 wherein the top upper angle is greater than the other
upper angles.

9. The shelter system of claim 3 wherein said hub shelter includes a shelter door end along each side of the shelter.
- 5 10. The shelter system of claim 9 wherein each shelter door end is configured to mate with an additional shelter to form a consistent interior space within each adjoining shelter and the shelter hub.
- 10 11. The shelter system of claim 10 wherein each shelter door end is an arched door end.
12. The shelter system of claim 10 including a shelter attachment device that fits along the mated face of the adjoining shelter door ends to form a connection between the adjoining shelters to avoid water penetration.
- 15 13. The shelter system of claim 12 wherein said shelter attachment mimics the dimensions of the arched door ends.
- 20 14. The shelter system of claim 13 wherein said shelter attachment is secured to the adjoining shelters by way of a hook and loop configuration.
- 25 15. A rapid-deployment shelter system, the shelter system comprising:
a frame, said frame including a plurality of interconnected frame poles and said frame configured to alternate between a first extended position and a second retracted position;
a second frame, said second frame including a plurality of interconnected frame poles and said second frame configured to alternate between a first extended position and a second retracted position independent of the frame;
a cover configured to fit with the frame to form a shelter;

a cover configured to fit with the second frame to form a second shelter;
and

wherein said frame and said second frame include matched door end
configurations able to adjoin with one another without a narrowing space being
5 formed between the two matched door end configurations.

16. The shelter system of claim 15 wherein the frame and the second frame form a
shelter complex with a shared interior space.

10 17. The shelter system of claim 16 including a hub in each of the shelters that serves
to connect items in the interior of the shelter and the second shelter in the shared
interior space to one of either the frame or second frame.

15 18. The shelter system of claim 16 wherein the frame and the second frame include
arched door ends.

19. The shelter system of claim 18 including a shelter attachment that fits with the
door ends of the shelter and second shelter.

20 20. The shelter system of claim 15 wherein said shelter is a hub shelter including a
door end along each side of said shelter.

25

30

Abstract

A shelter system is shown and described. A hub for a shelter system is shown and described. A frame for a shelter system is shown and described. In one embodiment, the shelter system includes a frame, a cover and a hub. The frame may be collapsible. The
5 cover is configured to fit with the frame. The hub may include a receiver slot, a receiver sleeve and an attachment projection. The result is a shelter system with reduced set up time, effort and requirements and improved strength and ease of use. The inventions may also be considered a shelter kit and/or a shelter and hub method.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		
The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76. This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.			

Secrecy Order 37 CFR 5.2:

☐	Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)
--------------------------	---

Inventor Information:

Inventor 1				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Jonathan		Urhausen	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 2				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Adam		Barr	
Residence Information (Select One) ☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Eugene	State/Province	OR	Country of Residence ⁱ US
Mailing Address of Inventor:				
Address 1	245 Jackson Street			
Address 2				
City	Eugene	State/Province	OR	
Postal Code	97402	Country ⁱ	US	
Inventor 3				
Legal Name				
Prefix	Given Name	Middle Name	Family Name	Suffix
	Donald		Bierman	

Camel Manufacturing Company, LLC,

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Residence Information (Select One)		☒ US Residency	☐ Non US Residency	☐ Active US Military Service	
City	Eugene	State/Province	OR	Country of Residence ⁱ	US
Mailing Address of Inventor:					
Address 1		245 Jackson Street			
Address 2					
City	Eugene	State/Province	OR		
Postal Code	97402	Country ⁱ	US		
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button.					

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).			
☐ An Address is being provided for the correspondence information of this application.			
Customer Number	4678		
Email Address	docketing@maccordmason.com	<input type="button" value="Add Email"/>	<input type="button" value="Remove Email"/>

Application Information:

Title of the Invention	SHELTER AND HUB SYSTEM		
Attorney Docket Number	9693-012A-CON1	Small Entity Status Claimed	☒
Application Type			
Subject Matter			
Total Number of Drawing Sheets (if any)	30	Suggested Figure for Publication (if any)	

Filing By Reference:

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

Application number of the previously filed application	Filing date (YYYY-MM-DD)	Intellectual Property Authority or Country

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Publication Information:

☐	Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☒	Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

Please Select One:					
☒ Customer Number		☐ US Patent Practitioner		☐ Limited Recognition (37 CFR 11.9)	
Customer Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					
Prefix	Given Name	Middle Name	Family Name	Suffix	Remove
Registration Number					
Additional Representative Information blocks may be generated within this form by selecting the Add button.					

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing benefit claim information in the Application Data Sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.
When referring to the current application, please leave the "Application Number" field blank.

Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)
	Continuation of	16/431322	2019-06-04

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Prior Application Status		Patented	Remove		
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)	Patent Number	Issue Date (YYYY-MM-DD)
16431322	Continuation of	15/639261	2017-06-30	10309093	2019-06-04

Prior Application Status		Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing or 371(c) Date (YYYY-MM-DD)	
15639261	Claims benefit of provisional	62/356793	2016-06-30	

Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the **Add** button.

Foreign Priority Information:

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX) the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

Application Number	Country ⁱ	Filing Date (YYYY-MM-DD)	Access Code ⁱ (if applicable)

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013.

☐ NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant **must opt-out** of the authorization by checking the corresponding box A or B or both in subsection 2 below.

NOTE: This section of the Application Data Sheet is **ONLY** reviewed and processed with the **INITIAL** filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

A. Priority Document Exchange (PDX) - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h)(1).

B. Search Results from U.S. Application to EPO - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

☐ A. Applicant **DOES NOT** authorize the USPTO to permit a participating foreign IP office access to the instant application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.

☐ B. Applicant **DOES NOT** authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

NOTE: Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.								
Applicant 1								
If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.								
			<input type="button" value="Clear"/>					
☒ Assignee	☐ Legal Representative under 35 U.S.C. 117	☐ Joint Inventor						
☐ Person to whom the inventor is obligated to assign.	☐ Person who shows sufficient proprietary interest							
If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:								
Name of the Deceased or Legally Incapacitated Inventor:								
If the Applicant is an Organization check here. ☒								
Organization Name	DLX Enterprises, LLC							
Mailing Address Information For Applicant:								
Address 1	245 Jackson Street							
Address 2								
City	Eugene	State/Province	OR					
Country ⁱ	US	Postal Code	97402					
Phone Number		Fax Number						
Email Address								
Additional Applicant Data may be generated within this form by selecting the Add button.								

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

Assignee 1						
Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication.						
If the Assignee or Non-Applicant Assignee is an Organization check here.			☒			
Organization Name	DLX Enterprises, LLC					
Mailing Address Information For Assignee including Non-Applicant Assignee:						
Address 1	245 Jackson Street					
Address 2						
City	Eugene	State/Province	OR			
Country i	US	Postal Code	97402			
Phone Number		Fax Number				
Email Address						
Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.						

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	9693-012A-CON1
		Application Number	
Title of Invention	SHELTER AND HUB SYSTEM		

Signature:

NOTE: This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). **However, if this Application Data Sheet is submitted with the INITIAL filing of the application and either box A or B is not checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).**

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

Signature	/Kelly B. Robinson/			Date (YYYY-MM-DD)	
First Name	Kelly B.	Last Name	Robinson	Registration Number	72960
Additional Signature may be generated within this form by selecting the Add button.					

Electronic Patent Application Fee Transmittal				
Application Number:				
Filing Date:				
Title of Invention:		SHELTER AND HUB SYSTEM		
First Named Inventor/Applicant Name:		Jonathan Urhausen		
Filer:		Kelly B. Robinson/Nichol Neal		
Attorney Docket Number:		9693-012A-CON1		
Filed as Small Entity				
Filing Fees for Utility under 35 USC 111(a)				
Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Basic Filing:				
UTILITY FILING FEE (ELECTRONIC FILING)	4011	1	75	75
UTILITY SEARCH FEE	2111	1	330	330
UTILITY EXAMINATION FEE	2311	1	380	380
Pages:				
Claims:				
Miscellaneous-Filing:				
Petition:				
Patent-Appeals-and-Interference:				

Description	Fee Code	Quantity	Amount	Sub-Total in USD(\$)
Post-Allowance-and-Post-Issuance:				
Extension-of-Time:				
Miscellaneous:				
Total in USD (\$)				785

Electronic Acknowledgement Receipt

EFS ID:	39291871
Application Number:	16861012
International Application Number:	
Confirmation Number:	8204
Title of Invention:	SHELTER AND HUB SYSTEM
First Named Inventor/Applicant Name:	Jonathan Urhausen
Customer Number:	4678
Filer:	Kelly B. Robinson/Nichol Neal
Filer Authorized By:	Kelly B. Robinson
Attorney Docket Number:	9693-012A-CON1
Receipt Date:	28-APR-2020
Filing Date:	
Time Stamp:	18:27:18
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Drawings-only black and white line drawings	9693-012A-Con1_Drawings.pdf	7218246 2d1787ca4db76f0b07c2411574d5caa6631ed378	no	30

Warnings:

Camel Manufacturing Company, LLC,
Case No. PGR2024-00033; Exhibit 1010

Information:					
2	Oath or Declaration filed	9693-012A-Con1_Declarations.pdf	188100	no	3
			c518fbef97f9a463e0fb42571db9fc860757119c		
Warnings:					
Information:					
3	Power of Attorney	9693-012A-Con1_POA.pdf	55202	no	2
			7b6265024dd43442981d7244972f055272f7127f		
Warnings:					
Information:					
4		9693-012A-Con1_Application.pdf	131696	yes	22
			96cf40fbe8f394fe36d742b5f8ba5c886b9a7aea		
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	18	
	Claims		19	21	
	Abstract		22	22	
Warnings:					
Information:					
5	Application Data Sheet	WebADS.pdf	141375	no	8
			3e9b51810959a7fd2e72ba31b31dff3f1993338		
Warnings:					
Information:					
6	Fee Worksheet (SB06)	fee-info.pdf	35202	no	2
			775c29e5bb9271ad059e503f05184617d7d06e73		
Warnings:					
Information:					
Total Files Size (in bytes):			7769821		

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

New Applications Under 35 U.S.C. 111


If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

National Stage of an International Application under 35 U.S.C. 371

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

New International Application Filed with the USPTO as a Receiving Office

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.






FIG. 2




FIG. 3




FIG. 4




FIG. 5





FIG. 6






FIG. 8





FIG. 9






FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D




FIG. 15E




FIG. 15F




FIG. 15G




Figure 16A




Figure 16B




Figure 17




Figure 18




Figure 19




Figure 20A




Figure 20B




Figure 20C





Figure 20D

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

Title of Invention	SHELTER AND HUB SYSTEM
<p>As the below named inventor, I hereby declare that:</p> <p>This declaration is directed to: ☐ The attached application, or</p> <p>☒ United States application or PCT international application number <u>15/639261</u> filed on <u>June 30, 2017</u></p> <p>The above-identified application was made or authorized to be made by me.</p> <p>I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.</p> <p>I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.</p> <p style="text-align: center;">WARNING:</p> <p>Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.</p>	
LEGAL NAME OF INVENTOR	
<p>Inventor: <u>Jonathan Urhausen</u> X Date (Optional): <u>09/14/17</u></p> <p>Signature: X </p>	
<p>Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form. Use an additional PTO/AIA/01 form for each additional inventor.</p>	

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing this form, call 1-800-PTO-9198 and select option 2.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)****Title of
Invention****SHELTER AND HUB SYSTEM**

As the below named inventor, I hereby declare that:

This declaration
is directed to:☐

The attached application, or


☒United States application or PCT international application number 15/639261filed on June 30, 2017

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001
by fine or imprisonment of not more than five (5) years, or both.**WARNING:**

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

LEGAL NAME OF INVENTORInventor: Adam Barr*Date (Optional): 9/14/17Signature: 


Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form.
Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

**DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN
APPLICATION DATA SHEET (37 CFR 1.76)**

Title of Invention	SHELTER AND HUB SYSTEM	
<p>As the below named inventor, I hereby declare that:</p> <p>This declaration is directed to: ☐ The attached application, or ☒ United States application or PCT international application number <u>15/639261</u> filed on <u>June 30, 2017</u></p> <p>The above-identified application was made or authorized to be made by me.</p> <p>I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.</p> <p>I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.</p> <p style="text-align: center;">WARNING:</p> <p>Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.</p>		
LEGAL NAME OF INVENTOR		
Inventor: <u>Donald Bierman</u>		X Date (Optional): <u>9/14/17</u>
Signature: X 		
<p>Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form. Use an additional PTO/AIA/01 form for each additional inventor.</p>		

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.

SCORE Placeholder Sheet for IFW Content

Application Number: 16861012

Document Date: 04/28/2020

The presence of this form in the IFW record indicates that the following document type was received in electronic format on the date identified above. This content is stored in the SCORE database.

Since this was an electronic submission, there is no physical artifact folder, no artifact folder is recorded in PALM, and no paper documents or physical media exist. The TIFF images in the IFW record were created from the original documents that are stored in SCORE.

- Drawing

At the time of document entry (noted above):

- USPTO employees may access SCORE content via DAV or via the SCORE web page.
- External customers may access SCORE content via PAIR using the Supplemental Content tab.