



US010950300B2

(12) **United States Patent**
Rao

(10) **Patent No.:** **US 10,950,300 B2**

(45) **Date of Patent:** **Mar. 16, 2021**

(54) **LIFETIME MIXED LEVEL NON-VOLATILE
MEMORY SYSTEM**

11/5621; G11C 11/5635; G11C 11/5678;
G11C 16/16; G11C 16/3495; G11C
29/52; G11C 29/79; G11C 2211/5641

(71) Applicant: **VERVAIN, LLC**, Dallas, TX (US)

See application file for complete search history.

(72) Inventor: **G. R. Mohan Rao**, Allen, TX (US)

(56) **References Cited**

(73) Assignee: **Vervain, LLC**, Dallas, TX (US)

U.S. PATENT DOCUMENTS

(*) Notice: Subject to any disclaimer, the term of this
patent is extended or adjusted under 35
U.S.C. 154(b) by 0 days.

7,505,338 B2 * 3/2009 Lee G11C 11/5621
365/185.09

7,855,916 B2 12/2010 Rao

(Continued)

(21) Appl. No.: **16/006,299**

OTHER PUBLICATIONS

(22) Filed: **Jun. 12, 2018**

Goodson et al, "Design Tradeoffs in a Flash Translation Layer."
(Year: 2010).*

(65) **Prior Publication Data**

(Continued)

US 2018/0294029 A1 Oct. 11, 2018

Primary Examiner — Richard Elms

Assistant Examiner — R Lance Reidlinger

(74) *Attorney, Agent, or Firm* — Bill R. Naifeh

Related U.S. Application Data

(60) Continuation of application No. 14/950,553, filed on
Nov. 24, 2015, now Pat. No. 9,997,240, which is a
(Continued)

(51) **Int. Cl.**
G11C 11/56 (2006.01)
G06F 12/02 (2006.01)
(Continued)


(52) **U.S. Cl.**
CPC **G11C 11/5635** (2013.01); **G06F 11/1068**
(2013.01); **G06F 11/1072** (2013.01);
(Continued)

(58) **Field of Classification Search**
CPC G06F 11/1068; G06F 11/1072; G06F
12/0246; G06F 2212/7202; G11C

(57) **ABSTRACT**

A flash controller for managing at least one MLC non-volatile memory module and at least one SLC non-volatile memory module. The flash controller is adapted to determine if a range of addresses listed by an entry and mapped to said at least one MLC non-volatile memory module fails a data integrity test. In the event of such a failure, the controller remaps said entry to an equivalent range of addresses of said at least one SLC non-volatile memory module. The flash controller is further adapted to determine which of the blocks in the MLC and SLC non-volatile memory modules are accessed most frequently and allocating those blocks that receive frequent writes to the SLC non-volatile memory module and those blocks that receive infrequent writes to the MLC non-volatile memory module.

12 Claims, 5 Drawing Sheets



Related U.S. Application Data

continuation of application No. 14/525,411, filed on Oct. 28, 2014, now Pat. No. 9,196,385, which is a division of application No. 13/455,267, filed on Apr. 25, 2012, now Pat. No. 8,891,298.

- (60) Provisional application No. 61/509,257, filed on Jul. 19, 2011.

(51) **Int. Cl.**

G11C 16/34 (2006.01)

G06F 11/10 (2006.01)

G11C 29/52 (2006.01)

G11C 29/00 (2006.01)

G11C 16/16 (2006.01)

(52) **U.S. Cl.**

CPC **G06F 12/0246** (2013.01); **G11C 11/5621** (2013.01); **G11C 11/5678** (2013.01); **G11C 16/16** (2013.01); **G11C 16/3495** (2013.01); **G11C 29/52** (2013.01); **G11C 29/76** (2013.01); **G06F 2212/7202** (2013.01); **G11C 2211/5641** (2013.01)

(56) **References Cited**

U.S. PATENT DOCUMENTS

8,140,800 B2 *	3/2012	Miyachi	G06F 11/1076 711/165
8,825,941 B2	9/2014	Moshayedi et al.	
8,891,298 B2	11/2014	Rao	
9,196,385 B2	11/2015	Roa	
9,997,240 B2	6/2018	Rao	
2008/0181000 A1 *	7/2008	Lasser	G11C 11/5628 365/185.03
2009/0172267 A1 *	7/2009	Oribe	G11C 16/3418 711/103
2009/0268513 A1 *	10/2009	De Ambroggi	G11C 11/005 365/163
2009/0307418 A1 *	12/2009	Chen	G06F 11/1048 711/105
2009/0327591 A1	12/2009	Moshayedi	
2010/0058018 A1 *	3/2010	Kund	G11C 7/04 711/167
2010/0172179 A1 *	7/2010	Gorobets	G06F 12/0246 365/185.09
2010/0325352 A1	12/2010	Schuette et al.	
2011/0050870 A1	3/2011	Hanari	
2011/0060870 A1	3/2011	Rao	
2011/0271043 A1	11/2011	Segal et al.	

OTHER PUBLICATIONS

Hamamoto et al., On the Retention Time Distribution of Dynamic Random Access Memory (DRAM), IEEE Transactions on Electron Devices, vol. 45, No. 6, Jun. 1998.

Park et al., Three-Dimensional 128 Gb MLC Vertical NAND Flash Memory With 24-WL Stacked Layers and 50 MB/s High-Speed Programming; IEEE Journal of Solid-State Circuits, vol. 50, No. 1, Jan. 2015.

Resnati, et al., Temperature Effects in NAND Flash Memories: A Comparison Between 2-D and 3-D Arrays; IEEE Electron Device Letters, vol. 38, No. 4, Apr. 2017.

Cho et al., An Innovative Indicator to Evaluate DRAM Cell Transistor Leakage Current Distribution; Journal of Electron Devices Society, vol. 6, Apr. 26, 2018.

Frank Shu, The Myth of SSD Testing, Flash Memory Summit 2011, Santa Clara, CA.

Bacchini et al., Characterization of Data Retention Faults in DRAM Devices, Nov. 2014.

Michelsoni et al., Architectural and Integration Options for 3D NAND Flash Memories, Computers 2017, 6, 27.

James Myers, Data Integrity in Solid State Drives: What Supernovas Mean to You, IT Peer Network, Feb. 19, 2014.

Bhati et al., DRAM Refresh Mechanisms, Penalties, and Trade-Offs, IEEE Transactions on Computers, vol. 64, No. X, 2015.

Doug Rollins, SSD Enhancements: Protecting Data Integrity and Improving Responsiveness, Industry Perspectives, Jul. 30, 2014.

Luo et al., WARM: Improving NAND Flash Memory Lifetime with Write-hotness Aware Retention Management, IEEE, 2015.

Intel, Understanding the Flash Translation Layer (FTL) Specification, Dec. 1998.

Tae-Sun Chung et al., A Survey of Flash Translation Layer, Journal of Systems Architecture 55, pp. 332-343, 2009.

Seagate Technology LLC, The Transition to Advanced Format 4K Sector Hard Drives, Apr. 2010.

Roberto Bez et al., Introduction to Flash Memory, Proceedings of the IEEE, vol. 91, No. 4, Apr. 2003.

Qingsing Wei et al., WAFTL: A Workload Adaptive Flash Translation Layer with Data Partition, IEEE 27th Symposium on Massive Storage Systems and Technologies (MSST), May 23-27, 2011.

Tae-ho Kgil et al., Improving NAND Flash Based Disk Caches, International Symposium on Computer Architecture, Copyright 2008 IEEE.

Samsung Electronics Co., Ltd., 7th International Symposium on Advanced Gate Stack Technology, RPAM Technology from an Industrial Perspective, Process Development Team/RPAM PJT In-Gyu Baek, Sep. 2010.

Paolo Pavan et al., Flash Memory Cells—An Overview, Proceedings of the IEEE, vol. 85, No. 8, Aug. 1997.

Yoshihisa Iwata et al., A High-Density NAND EEPROM with Block-Page Programming for Microcomputer Applications, IEEE Journal of Solid-State Circuits, vol. 25, No. 2, Apr. 1990.

Tae-Sung Jung et al., A 117-mm² 3.3-V Only 128-Mb Multilevel NAND Flash Memory for Mass Storage Applications, IEEE Journal of Solid-State Circuits, vol. 31, No. 11, Nov. 1996.

Masayoshi Ohkawa et al., A 98 mm² Die Size 3.3V 64-Mb Flash Memory with FN-NOR Type Four-Level Cell, IEEE Journal of Solid-State Circuits, vol. 31, No. 11, Nov. 1996.

Masaki Momodomi et al., An Experimental 4-Mbit CMOS EEPROM with a NAND-Structured Cell, IEEE Journal of Solid-State Circuits, vol. 24, No. 5, Oct. 1989.

Ken Takeuchi et al., A Multipage Cell Architecture for High-Speed Programming Multilevel NAND Flash Memories, IEEE Journal of Solid-State Circuits, vol. 33, No. 8, Aug. 1998.

Shigeru Atsumi et al., A Channel-Erasing 1.8-V-Only 32-Mb NOR Flash EEPROM with a Bitline Direct Sensing Scheme, IEEE Journal of Solid-State Circuits, vol. 35, No. 11, Nov. 2000.

Taehee Cho et al., A Dual-Mode NAND Flash Memory: 1-Gb Multilevel and High-Performance 512-Mb Single-Level Modes, IEEE Journal of Solid-State Circuits, vol. 36, No. 11, Nov. 2001.

Douglas J. Lee et al., Control Logic and Cell Design for a 4K NVRAM, IEEE Journal of Solid-State Circuits, vol. SC-18, No. 5, Oct. 1983.

Duane H. Oto et al., High-Voltage Regulation and Process Considerations for High-Density 5 V-Only E2PROM's, IEEE Journal of Solid-State Circuits, vol. SC-18, No. 5, Oct. 1983.

Gheorghe Samachisa et al., A 128K Flash EEPROM Using Double-Polysilicon Technology, IEEE Journal of Solid-State Circuits, vol. SC-18, No. 5, Oct. 1983.

Nelson Duann, Silicon Motion, Inc., Flash Memory Summit, SIC & MIC Hybrid, Santa Clara, CA, Aug. 2008.

Simona Boboiia, et al., Write Endurance in Flash Drives: Measurements and Analysis, Usenix Conference on File and Storage Technologies, San Jose, CA, Feb. 2010.

Simona Boboiia, et al., Write Endurance in Flash Drives: Measurements and Analysis, Handout at Usenix Conference on File and Storage Technologies, San Jose, CA, Feb. 2010.

Silicon Systems, Increasing Flash SSD Reliability, StorageSearch.com, Apr. 2005.

Ismael Change Chalimi, Intalio, An Intalio White Paper, Cloud Computing is Memory Bound, May 2010.

(56)

References Cited**OTHER PUBLICATIONS**

Hynix, 32Gb NAND Flash, HY27UK08BGFM, Product Description Sheet, Feb. 2007.

Chris Evans, Consultant with Langton Blue, SearchStorage.co.UK, Enterprise MLC: How flash vendors are boosting MLC write endurance, Jun. 3, 2011.

Jesung Kim et al., A Space-Efficient Flash Translation Layer for Compactflash Systems, IEEE Transactions on Consumer Electronics, vol. 48, No. 2, May 2002.

Garth Goodson et al., Design Tradeoffs in a Flash Translation Layer, HPCA West 2010 (High Perf Comp Arch Conference, Bangalore, India.

Adbul Rub Aamer Mohammed, Improving Hot Data Identification for Hybrid SLC/MLC Device; CSci 8980-Advanced Storage Systems, Spring 2009.

Ynag Hu, Achieving Page-Mapping FTL Performance at Block-Mapping FTL Cost by Hiding Address Translation, 26th EIII Symposium on Massive Storage Systems and Technologies (MSST) May 3-7, 2010.

Clinton W. Smullen, IV et al., Accelerating Enterprise Solid-State Disks with Non-Volatile Merge Caching, 2010 International Green Computing Conference, Aug. 15-18, 2010.

Monolithic 3D, Inc. Introducing our monolithic 3D resistive memory architecture, <http://www.monolithic3d.com/2/post/2011/06/introducing-our-3d-resistive-memory-architecture.html>, Jun. 27, 2011.

Song Jiang et al., S-FTL: An Efficient Address Translation for Flash Memory by Exploiting Spatial Locality, Proceedings of the MSST 2011, May 2011.

Greg Atwood et al., Intel Strata Flash TM Memory Technology Overview, Intel Technology Journal Q4 1997.

Moinuddin K. Qureshi et al., Morphable Memory System: A Robust Architecture for Exploiting Multi-Level Phase Change Memories, International Symposium on Computer Architecture, Saint-Malo, France, Jun. 19-23, 2010.

Abhishek Rajimwale et al., Block Management in Solid-State Devices, Usenix Conference, Jun. 14-19, 2009.

Brendan Gregg et al, Sun Storage 7000 Unified Storage System L2ARC: Second Level Adaptive Replacement Cache, Oracle White Paper—Sun Storage 7000 Unified Storage System L2ARC, May 2010.


Chunqiang Tang, FVD: a High-Performance Virtual Machine Image Format for Cloud, USENIX Conference, Jun. 2011.

Anand Lal Shimpi, AnandTech, The Crucial m4 (Micron C400) SSD Review, Mar. 31, 2011.

Anand Lal Shimpi, AnandTech, The Intel SSD 320 Review: 25nm G3 is Finally Here, Mar. 28, 2011.

Micron Technology, Inc., TN-29-42: Wear-Leveling Techniques in NAND Flash Devices Introduction, Oct. 2008.

* cited by examiner

FIG. 1

Failed Data Integrity Test →


LOGICAL ADDRESS RANGE	PHYSICAL ADDRESS RANGE
R0	MLC/Block 0
R1	MLC/Block 1
R2	MLC/Block 2
R3	MLC/Block 3
R4	MLC/Block 4
RN	MLC/Block N


FIG. 2A

Remapping to SLC flash module →

LOGICAL ADDRESS RANGE	PHYSICAL ADDRESS RANGE
R0	MLC/Block 0
R1	MLC/Block 1
R2	SLC/Block 0
R3	MLC/Block 3
R4	MLC/Block 4
RN	MLC/Block N

FIG. 2B

FIG. 3A

FIG. 3B




FIG. 4

1

LIFETIME MIXED LEVEL NON-VOLATILE MEMORY SYSTEM

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a Continuation of U.S. patent application Ser. No. 14/950,553 filed on Nov. 24, 2015, entitled LIFETIME MIXED LEVEL NON-VOLATILE MEMORY SYSTEM, which published on Jun. 2, 2016, as U.S. Application Publication No. 2016-0155496, now U.S. Pat. No. 9,997,240 issued Jun. 12, 2018, which is incorporated by reference in its entirety. U.S. application Ser. No. 14/950,553 is a Continuation of U.S. patent application Ser. No. 14/525,411, filed Oct. 28, 2014, entitled LIFETIME MIXED LEVEL NON-VOLATILE MEMORY SYSTEM, which published on Oct. 1, 2015, as U.S. Publication No. 2015-0278013, now U.S. Pat. No. 9,196,385, issued on Nov. 24, 2015. Application Ser. No. 14/525,411 is a Division of U.S. patent application Ser. No. 13/455,267, filed Apr. 25, 2012, published on Jan. 24, 2013, as U.S. Publication No. 2013-0021846, now U.S. Pat. No. 8,891,298, issued on Nov. 18, 2014, entitled LIFETIME MIXED LEVEL NON-VOLATILE MEMORY SYSTEM. Application Ser. No. 13/455,267 claims the benefit of U.S. Provisional Application No. 61/509,257, filed Jul. 19, 2011, entitled LIFETIME MIXED LEVEL NAND FLASH SYSTEM. U.S. Pat. Nos. 9,997,240; 9,196,385; and 8,891,298 and Patent Application Publication Nos. 2015-0278013 and 2013-0021846 are hereby incorporated by reference in their entirety. This application also incorporates by reference the complete disclosure of U.S. patent application Ser. No. 12/256,362, filed Oct. 22, 2008, published on Apr. 30, 2009, as U.S. Publication No. 2009-0109787, now U.S. Pat. No. 7,855,916, issued on Dec. 21, 2010, entitled NONVOLATILE MEMORY SYSTEMS WITH EMBEDDED FAST READ AND WRITE MEMORIES. This application also incorporates by reference the complete disclosure of U.S. patent application Ser. No. 12/915,177, filed Oct. 29, 2010, published on Mar. 10, 2011, as U.S. Publication No. 2011-0060870, now U.S. Pat. No. 8,194,452, issued on Jun. 5, 2012, entitled NONVOLATILE MEMORY SYSTEMS WITH EMBEDDED FAST READ AND WRITE MEMORIES.

TECHNICAL FIELD

This application relates to a system and method for providing reliable storage through the use of non-volatile memories and, more particularly, to a system and method of increasing the reliability and lifetime of a NAND flash storage system, module, or chip through the use of a combination of single-level cell (SLC) and multi-level cell (MLC) NAND flash storage without substantially raising the cost of the NAND flash storage system. The memory in a total non-volatile memory system may contain some SRAM (static random-access memory), DRAM (dynamic RAM), RRAM (resistive RAM), PCM (phase change memory), MAGRAM (magnetic random-access memory), NAND flash, and one or more HDDs (hard disk drives) when storage of the order of several terabytes is required. The SLC non-volatile memory can be flash, PCM, RRAM, MAGRAM or any other solid-state non-volatile memory as long as it has endurance that is superior to that of MLC flash, and it provides for data access speeds that are faster than that of MLC flash or rotating storage media (e.g., HDDs).

BACKGROUND

Non-volatile memories provide long-term storage of data. More particularly, non-volatile memories can retain the

2

stored data even when not powered. Magnetic (rotating) hard disk drives (HDD) dominate this storage medium due to lower cost compared to solid state disks (SSD). Optical (rotating) disks, tape drives and others have a smaller role in long-term storage systems. SSDs are preferred for their superior performance (fast access time), mechanical reliability and ruggedness, and portability. Flash memory, more specifically NAND flash, is the dominant SSD medium today.

RRAM, PCM, MAGRAIVI and others, will likely play a larger role in the future, each of them having their own advantages and disadvantages. They may ultimately replace flash memories, initially for use as a "write buffer" and later to replace "SLC flash" and "MLC flash." MLC NAND flash is a flash memory technology using multiple levels per cell to allow more bits to be stored using the same number of transistors. In SLC NAND flash technology, each cell can exist in one of two states, storing one bit of information per cell. Most MLC NAND flash memory has four possible states per cell, so it can store two bits of information per cell.

These semiconductor technology driven "flash alternatives," i.e., RRAM, PCM, MAGRAIVI and others, have several advantages over any (SLC or MLC) flash because they: 1) allow data to be written over existing data (without prior erase of existing data), 2) allow for an erase of individual bytes or pages (instead of having to erase an entire block), and 3) possess superior endurance (1,000,000 write-erase cycles compared to typical 100,000 cycles for SLC flash and less than 10,000 cycles for MLC flash).

HDDs have several platters. Each platter contains 250-5,000 tracks (concentric circles). Each track contains 64 to 256 sectors. Each sector contains 512 bytes of data and has a unique "physical (memory) address." A plurality of sectors is typically combined to form a "logical block" having a unique "logical address." This logical address is the address at which the logical block of physical sectors appears to reside from the perspective of an executing application program. The size of each logical block and its logical address (and/or address ranges/boundaries) is optimized for the particular operating system (OS) and software applications executed by the host processor. A computer OS organizes data as "files." Each file may be located (stored) in either a single logical block or a plurality of logical blocks, and therefore, the location of files typically traverses the boundaries of individual (physical) sectors. Sometimes, a plurality of files has to be combined and/or modified, which poses an enormous challenge for the memory controller device of a non-volatile memory system.

SSDs are slowly encroaching on the HDD space and the vast majority of NAND flash in enterprise servers utilizes a SLC architecture, which further comprises a NAND flash controller and a flash translation layer (FTL). NAND flash devices are generally fragmented into a number of identically sized blocks, each of which is further segmented into some number of pages. It should be noted that asymmetrical block sizes, as well as page sizes, are also acceptable within a device or a module containing devices. For example, a block may comprise 32 to 64 pages, each of which incorporates 2-4 Kbit of memory. In addition, the process of writing data to a NAND flash memory device is complicated by the fact that, during normal operation of, for example, single-level storage (SLC), erased bits (usually all bits in a block with the value of '1') can only be changed to the opposite state (usually '0') once before the entire block must be erased. Blocks can only be erased in their entirety, and, when erased, are usually written to '1' bits. However, if an erased block is already there, and if the addresses (block,

3

page, etc.) are allowed, data can be written immediately; if not, a block has to be erased before it can be written to.

FTL is the driver that works in conjunction with an existing operating system (or, in some embedded applications, as the operating system) to make linear flash memory appear to the system like a disk drive, i.e., it emulates a HDD. This is achieved by creating "virtual" small blocks of data, or sectors, out of flash's large erase blocks and managing data on the flash so that it appears to be "write in place" when in fact it is being stored in different locations in the flash. FTL further manages the flash so that there are clean/erased places to store data.

Given the limited number of writes that individual blocks within flash devices can tolerate, wear leveling algorithms are used within the flash devices (as firmware commonly known as FTL or managed by a controller) to attempt to ensure that "hot" blocks, i.e., blocks that are frequently written, are not rendered unusable much faster than other blocks. This task is usually performed within a flash translation layer. In most cases, the controller maintains a lookup table to translate the memory array physical block address (PBA) to the logical block address (LBA) used by the host system. The controller's wear-leveling algorithm determines which physical block to use each time data is programmed, eliminating the relevance of the physical location of data and enabling data to be stored anywhere within the memory array and thus prolonging the service life of the flash memory. Depending on the wear-leveling method used, the controller typically either writes to the available erased block with the lowest erase count (dynamic wear leveling); or it selects an available target block with the lowest overall erase count, erases the block if necessary, writes new data to the block, and ensures that blocks of static data are moved when their block erase count is below a certain threshold (static wear leveling).

MLC NAND flash SSDs are slowly replacing and/or coexisting with SLC NAND flash in newer SSD systems. MLC allows a single cell to store multiple bits, and accordingly, to assume more than two values; i.e., '0' or '1'. Most MLC NAND flash architectures allow up to four (4) values per cell; i.e., '00', '01', '10', or '11'. Generally, MLC NAND flash enjoys greater density than SLC NAND flash, at the cost of a decrease in access speed and lifetime (endurance). It should be noted, however, that even SLC NAND flash has a considerably lower lifetime (endurance) than rotating magnetic media (e.g., HDDs), being able to withstand only between 50,000 and 100,000 writes, and MLC NAND flash has a much lower lifetime (endurance) than SLC NAND flash, being able to withstand only between 3,000 and 10,000 writes. As is well known in the art, any "write" or "program" to a block in NAND flash (floating gate) requires an "erase" (of a block) before "write."

Despite its limitations, there are a number of applications that lend themselves to the use of MLC flash. Generally, MLC flash is used in applications where data is read many times (but written few times) and physical size is an issue. For example, flash memory cards for use in digital cameras would be a good application of MLC flash, as MLC can provide higher density memory at lower cost than SLC memory.

When a non-volatile storage system combines HDD, SLC and MLC (setting aside volatile memory for buffering, caching etc) in a single (hybrid) system, new improvements and solutions are required to manage the methods of writing data optimally for improved life time (endurance) of flash memory. Accordingly, various embodiments of a NAND

4

flash storage system that provides long lifetime (endurance) storage at low cost are described herein.

The following description is presented to enable one of ordinary skill in the art to make and use the disclosure and is provided in the context of a patent application and its requirements. Various modifications to the preferred embodiment and the generic principles and features described herein will be readily apparent to those skilled in the art. Thus, the present disclosure is not intended to be limited to the embodiments shown, but is to be accorded the widest scope consistent with the principles and features described herein.

SUMMARY

According to one embodiment of the present disclosure, there is provided a system for storing data which comprises at least one MLC nonvolatile memory module (hereinafter referred to as "MLC module") and at least one SLC non-volatile memory module (hereinafter referred to as "SLC module"), each module comprises a plurality of individually erasable blocks. The data storage system according to one embodiment of the present disclosure further comprises a controller for controlling both the at least one MLC module and the at least one SLC module. In particular, the controller maintains an address map comprising a list of individual logical address ranges each of which maps to a similar range of physical addresses within either the at least one MLC module or the at least one SLC module. After each write to (flash) memory, the controller conducts a data integrity check to ensure that the data was written correctly. When the data was not written correctly, the controller modifies the table so that the range of addresses on which the write failed is remapped to the next available range of physical addresses within the at least one SLC module. The SLC module can be (NAND) flash, PCM, RRAM, MAGRAIVI or any other solid-state non-volatile memory as long as it has endurance that is superior to that of MLC flash, and it provides for data access speeds that are faster than that of MLC flash or rotating storage media (e.g., HDDs).

According to another embodiment of the present disclosure, there is provided a system for storing data which comprises a controller that is further adapted to determine which of the blocks of the plurality of the blocks in the MLC and SLC non-volatile memory modules are accessed most frequently and wherein the controller segregates those blocks that receive frequent writes into the at least one SLC non-volatile memory module and those blocks that receive infrequent writes into the at least one MLC nonvolatile module.

BRIEF DESCRIPTION OF THE DRAWINGS

The present disclosure will be more fully understood by reference to the following detailed description of one or more preferred embodiments when read in conjunction with the accompanying drawings, in which like reference characters refer to like parts throughout the views and in which: FIG. 1 is a block diagram of a computer system incorporating one embodiment of the present disclosure;

FIGS. 2A and 2B are drawings depicting a translation table/address map in accordance with one embodiment of the present disclosure;

FIGS. 3A and 3B are a flow chart illustrating an exemplary method for use in implementing one embodiment of the present disclosure; and

5

FIG. 4 is a block diagram depicting one embodiment of the present disclosure for implementation within a NAND flash module.

DETAILED DESCRIPTION

The present disclosure is directed to the reliable storage of data in read and write memory, and, in particular, to the reliable storage of data in non-volatile memory, such as, for example, NAND flash. Generally, and in particular regard to NAND flash memory, two separate banks of NAND flash are maintained by a controller. One bank contains economical MLC NAND flash, while a second bank contains high endurance SLC NAND flash. The controller conducts a data integrity test after every write. If a particular address range fails a data integrity test, the address range is remapped from MLC NAND flash to SLC NAND flash. As the SLC NAND flash is used to boost the lifetime (endurance) of the storage system, it can be considerably lesser in amount than the MLC NAND flash. For example, a system may set SLC NAND flash equal to 12.5% or 25% of MLC NAND flash (total non-volatile memory storage space=MLC+SLC).

Turning to the Figures and to FIG. 1 in particular, a computer system 10 depicting one embodiment of the present disclosure is shown. A processor 12 is coupled to a device controller 14, such as a chipset, using a data link well known in the art, such as a parallel bus or packet-based link. The device controller 14 provides interface functions to the processor 12. In some computer systems, the device controller 14 may be an integral part of the (host) processor 12. The device controller 14 provides a number of input/output ports 16 and 18, such as, for example, serial ports (e.g., USB ports and Firewire ports) and network ports (e.g., Ethernet ports and 802.11 “Wi-Fi” ports). The device controller 14 may also control a bank of, for example, DRAM 20. In addition, the device controller 14 controls access to one or more disks 24, such as, for example, a rotating magnetic disk, or an optical disk, as well as two or more types of NAND flash memory. One type of NAND flash memory is a MLC NAND flash memory module 26. Another type of NAND flash memory is a SLC NAND flash memory module 28.

The device controller 14 maintains a translation table/address map which may include address translations for all devices in the computer system. Nonetheless, the discussion in the present disclosure will be limited only to NAND flash memory modules. In particular, the device controller 14 maintains a translation table that maps logical computer system addresses to physical addresses in each one of the MLC- and SLC-NAND flash memory modules 26 and 28, respectively. As MLC flash memory is less expensive than SLC flash memory, on a cost per bit basis, the translation table will initially map all logical NAND flash addresses to the MLC NAND flash memory module 26. The address ranges within the translation table will assume some minimum quantum, such as, for example, one block, although a smaller size, such as one page could be used, if the NAND flash has the capability of erasing the smaller size quantum.

A “read-modify-write” scheme is used to write data to the NAND flash. Data to be written to NAND flash is maintained in DRAM 20. After each write to an address within a particular address range, the device controller 14 will—as time permits—perform a read on the address range to ensure the integrity of the written data. If a data integrity test fails, the address range is remapped from the MLC NAND flash memory module 26 to the next available address range in the SLC NAND flash memory module 28.

6

FIGS. 2A and 2B illustrate one embodiment of a translation table/address map of the present disclosure. In FIG. 2A, a list of logical address ranges (R0-RN) is translated to physical address ranges. As illustrated, all of the logical address ranges are translated to blocks on the MLC NAND flash memory module 26. However, through the application of a data integrity verification check (explained in more detail below) it is determined that, for example, address range R2 corresponds to failed quanta of data stored in block 2 of the MLC NAND flash memory module 26. FIG. 2B shows the quanta of data which failed the data integrity verification check (see FIG. 2A) remapped to the next available range of physical addresses within the SLC NAND flash memory module 28, in this example, SLC/block 0.

FIGS. 3A and 3B are a flow chart illustrating a method for utilizing a NAND flash memory system incorporating one embodiment of the present disclosure. The method begins in a step 100, when a command to write a quantum of data stored in DRAM to a particular location in NAND flash memory is received, in step 102, the quantum of data is read from DRAM into memory within the device controller (which acts as the memory controller). In step 104, both the logical address range and the NAND flash physical address range to which the quantum of data is to be written, is read into memory of the device controller. In step 106, the quantum of data to be written is combined with the contents of the NAND flash memory. In step 108, the NAND flash physical address range to be written is erased. In step 110, the combined data is written to the appropriate NAND flash physical address range. In step 112 the NAND flash physical address range that was written in step 110 is read into device controller memory.

The flowchart continues in FIG. 3B. In step 114 the NAND flash physical address range that was read into device controller memory is compared with the retained data representing the combination of the previous contents of the physical address range and the quantum of data to be written. In step 116 if the retained data matches the newly stored data in the NAND flash memory, the write was a success, and the method exits in step 118. However, if the retained data does not match the newly stored data in the NAND flash memory, the method executes step 120, which identifies the next quantum of available SLC NAND flash memory addresses. In step 122, a check is made to determine if additional SLC NAND flash memory is available, and, if not, the NAND flash memory system is marked as failed, prompting a system alert step 124. However, if additional SLC NAND flash memory is available, the failed NAND flash physical address range is remapped to the next available quantum of SLC NAND flash memory in step 126. Execution then returns to step 110, where the write is repeated.

Another application of one embodiment of the present disclosure, not depicted in any of the drawings, is to allocate “hot” blocks; i.e., those blocks that receive frequent writes, into the SLC NAND flash memory module 28, while allocating “cold” blocks; i.e., those blocks that only receive infrequent writes, into the MLC NAND flash memory module 26. This could be accomplished within the device controller 14 described above, which could simply maintain a count of those blocks that are accessed (written to) most frequently, and, on a periodic basis, such as, for example, every 1000 writes, or every 10,000 writes, transfer the contents of those blocks into the SLC NAND flash memory module 28.

FIG. 4 depicts another embodiment of the present disclosure. The embodiment is entirely resident within a NAND

7

flash module 50. In particular, a standard NAND flash interface 52 is managed by flash translation layer (FTL) logic 54. The flash translation layer (FTL) 54 manages two NAND flash memory banks 56 and 58, whereby memory bank 56 comprises a plurality of MLC NAND flash memory modules 60a and a plurality of SLC NAND flash memory modules 62a. Memory bank 58 comprises a plurality of MLC NAND flash memory modules 60b and a plurality of SLC NAND flash memory modules 62b.

This embodiment of the present disclosure could function similarly to the system level embodiment discussed earlier with reference to FIGS. 1-3B, but the control functions, such as maintenance of the translation table/address map (FIGS. 2A and 2B), could be conducted within the flash translation layer (FTL) 54 instead of in a device controller 14.

Embodiments of the present disclosure relate to a system and method of increasing the reliability and lifetime of a NAND flash storage system, module, or chip through the use of a combination of multi-level cell (MLC) and single-level cell (SLC) NAND flash storage. The above description is presented to enable one of ordinary skill in the art to make and use the disclosure and is provided in the context of a patent application and its requirements. While this disclosure contains descriptions with reference to certain illustrative aspects, it will be understood that these descriptions shall not be construed in a limiting sense. Rather, various changes and modifications can be made to the illustrative embodiments without departing from the true spirit, central characteristics and scope of the disclosure, including those combinations of features that are individually disclosed or claimed herein. Furthermore, it will be appreciated that any such changes and modifications will be recognized by those skilled in the art as an equivalent to one or more elements of the following claims, and shall be covered by such claims to the fullest extent permitted by law.

What is claimed is:

1. A system for storing data comprising:

memory space containing volatile memory space and nonvolatile memory space, wherein the nonvolatile memory space includes both multilevel cell (MLC) memory space and single level cell (SLC) memory space;

at least one controller to operate memory elements and associated memory space;

at least one MLC nonvolatile memory element that can be mapped into the MLC memory space;

at least one SLC nonvolatile memory element that can be mapped into the SLC memory space;

at least one random access volatile memory;

an FTL flash translation layer, wherein the at least one controller, or FTL, or a combination of both maintain an address table in one or more of the memory elements and random access volatile memory;

the controller controlling access of the MLC and SLC nonvolatile memory elements and the random access volatile memory for storage of data therein, the controller, in at least a Write access operation to the MLC nonvolatile memory element, operable to store data in the MLC nonvolatile memory element and retain such stored data in the random access volatile memory;

the controller performing a data integrity test on stored data in the MLC nonvolatile memory element after at least a Write access operation performed thereon by comparing the stored data to the retained data in the random access volatile memory;

wherein the address table maps logical and physical addresses adaptable to the system, wherein the map-

8

ping is performed as necessitated by the system to maximize lifetime, and wherein the mapping maps blocks, pages, or bytes of data in either volatile or nonvolatile, or both, memories; and

wherein a failure of the data integrity test performed by the controller results in a remapping of the address space to a different physical range of addresses and transfer of data corresponding to the stored data to those remapped physical addresses from those determined to have failed the data integrity test to achieve enhanced endurance.

2. The system of claim 1, wherein the FTL flash translation layer is a software module, or a firmware module containing software updates.

3. The system of claim 1, wherein at least one of the random access volatile memory or the MLC and SLC nonvolatile memory elements are embedded in the at least one controller.

4. The system of claim 1, wherein the MLC and SLC nonvolatile memory elements comprise flash memory.

5. The system of claim 1, wherein the random access volatile memory is dynamic random access memory.

6. The system of claim 1, wherein the random access volatile memory is static random access memory.

7. The system of claim 1, wherein the controller, upon detection of a failure of the data integrity test, remaps the data to the SLC nonvolatile memory element.

8. The system of claim 7, wherein the SLC memory element has a higher endurance than the MLC memory element.

9. The system of claim 1, wherein the MLC is a multilevel cell, wherein the multilevel cell stores at least 2 bits per cell.

10. The system of claim 1, wherein the contents of frequently accessed portions of the memory space are periodically moved from the MLC space to the SLC space.

11. The system of claim 1 wherein the MLC allows a single cell to store multiple bits.

12. A system for storing data comprising:

memory space containing volatile memory space and nonvolatile memory space, wherein the nonvolatile memory space includes both multilevel cell (MLC) space and single level cell (SLC) space;

at least one controller to operate memory elements and associated memory space, and to maintain an address table in one or more of the memory elements;

at least one MLC nonvolatile memory element that can be mapped into the nonvolatile memory space;

at least one SLC nonvolatile memory element that can be mapped into the nonvolatile memory space;

at least one random access volatile memory;

the controller controlling access of the MLC and SLC nonvolatile memory elements and the random access volatile memory for storage of data therein, the controller, in at least a Write access operation to the MLC nonvolatile memory element, operable to store data in the MLC nonvolatile memory element and retain such stored data in the random access volatile memory;

the controller performing a data integrity test on stored data in the MLC nonvolatile memory element after at least a Write access operation performed thereon by comparing the stored data to the retained data in the random access volatile memory;

wherein the address table maps logical and physical addresses adaptable to the system, wherein the mapping is performed as necessitated by the system to maximize lifetime, and wherein the mapping maps

blocks, pages, or bytes of data in either volatile or nonvolatile, or both, memories; and wherein a failure of the data integrity test performed by the controller results in a remapping of the address space to a different physical range of addresses and transfer of data corresponding to the stored data to those remapped physical addresses from those determined to have failed the data integrity test to achieve enhanced endurance. 5

* * * * *

10