



US 20240072311A1

(19) **United States**

(12) **Patent Application Publication**
Elfering et al.

(10) **Pub. No.: US 2024/0072311 A1**

(43) **Pub. Date: Feb. 29, 2024**

(54) **ARRANGEMENTS FOR INHIBITING
INTRUSION INTO BATTERY PACK
ELECTRICAL COMPONENTS**

Publication Classification

(71) Applicant: **MILWAUKEE ELECTRIC TOOL
CORPORATION**, Brookfield, WI (US)

(72) Inventors: **James P. Elfering**, Antioch, IL (US);
Cameron R. Schulz, Milwaukee, WI
(US); **Ryan B. Jipp**, Brookfield, WI
(US); **Samuel Sheeks**, Germantown, WI
(US); **Kyle J. Radovich**, West Bend,
WI (US); **Michael Kolden**, Wauwatosa,
WI (US)

(21) Appl. No.: **18/380,097**

(22) Filed: **Oct. 13, 2023**

Related U.S. Application Data

(63) Continuation of application No. 17/202,782, filed on Mar. 16, 2021, which is a continuation of application No. 15/974,151, filed on May 8, 2018, now Pat. No. 10,950,912.

(60) Provisional application No. 62/638,698, filed on Mar. 5, 2018, provisional application No. 62/586,832, filed on Nov. 15, 2017, provisional application No. 62/569,207, filed on Oct. 6, 2017, provisional application No. 62/526,298, filed on Jun. 28, 2017, provisional application No. 62/523,623, filed on Jun. 22, 2017, provisional application No. 62/519,722, filed on Jun. 14, 2017.

(51) **Int. Cl.**

H01M 10/42 (2006.01)

H01M 50/213 (2006.01)

H01M 50/24 (2006.01)

H01M 50/247 (2006.01)

H01M 50/503 (2006.01)

H01M 50/509 (2006.01)

H01M 50/516 (2006.01)

H02J 7/34 (2006.01)

(52) **U.S. Cl.**

CPC **H01M 10/425** (2013.01); **H01M 10/4257**

(2013.01); **H01M 50/213** (2021.01); **H01M**

50/24 (2021.01); **H01M 50/247** (2021.01);

H01M 50/503 (2021.01); **H01M 50/509**


(2021.01); **H01M 50/516** (2021.01); **H02J**

7/342 (2020.01); **H02J 7/0042** (2013.01)

(57)

ABSTRACT

A battery pack and a method of assembling a battery pack. The battery pack may include an outer housing; a cell module supportable by the outer housing, the cell module including a module housing, a plurality of battery cells supported by the module housing, the battery cells having an energy of at least about 60 Watt-hours, a controller operable to control an operation of the battery pack, a conductive strap electrically connected to at least one of the battery cells, a weld strap connected between the controller and the conductive strap, and a terminal electrically connected to the battery cells and operable to connect the battery cells to an electrical device for power transfer; and a vapor-deposited, hydrophobic nano coating applied to at least a portion of the cell module.






FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B







FIG. 10C










FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19




FIG. 20A




FIG. 20B




FIG. 20C




FIG. 20D




FIG. 20E




FIG. 20F




FIG. 20G




FIG. 20H




FIG. 20I




FIG. 20J




FIG. 21A




FIG. 21B




FIG. 21C




FIG. 21D




FIG. 21E




FIG. 21F




FIG. 21G




FIG. 21H




FIG. 22




FIG. 23




FIG. 24




FIG. 25




FIG. 26B




FIG. 26A




FIG. 27B




FIG. 27A




FIG. 28A




FIG. 28B




FIG. 28C




FIG. 29B




FIG. 29A




FIG. 30B




FIG. 30A




FIG. 31A




FIG. 31B




FIG. 32




FIG. 33A





FIG. 33B






FIG. 34B




FIG. 35





FIG. 36






FIG. 38




FIG. 39




FIG. 40A




FIG. 40B




FIG. 41A




FIG. 41B




FIG. 42




FIG. 43




FIG. 44





FIG. 45A








FIG. 45C








FIG. 46A





FIG. 46B






FIG. 48A




FIG. 48B




FIG. 48C




FIG. 48E




FIG. 49A

FIG. 49B






FIG. 49C








FIG. 51A





FIG. 51B






FIG. 53A





FIG. 53B






FIG. 53D




FIG. 53E




FIG. 53F




FIG. 54A




FIG. 54B




FIG. 54C




FIG. 54D




FIG. 54E

ARRANGEMENTS FOR INHIBITING INTRUSION INTO BATTERY PACK ELECTRICAL COMPONENTS

RELATED APPLICATIONS

[0001] This application is a continuation of U.S. patent application Ser. No. 17/202,782, filed Mar. 16, 2021, which is a continuation of U.S. patent application Ser. No. 15/974,151, filed May 8, 2018, now U.S. Pat. No. 10,950,912, which claims priority to U.S. Provisional Patent Application Nos. 62/519,722, filed Jun. 14, 2017; 62/523,623, filed Jun. 22, 2017; 62/526,298, filed Jun. 28, 2017; 62/569,207, filed Oct. 6, 2017; 62/586,832, filed Nov. 15, 2017; and 62/638,698, filed Mar. 5, 2018, the entire contents of all of which are hereby incorporated by reference.

FIELD

[0002] The present invention generally relates to battery packs and, more particularly, to arrangements for inhibiting water intrusion into battery cells and electrical connections of the battery pack.

SUMMARY

[0003] Fluid (e.g., including liquids, such as water, sea water, etc.) or material (e.g., salt spray, snow which typically includes minerals, etc.) may enter a battery pack through various entry points including, for example, battery pack terminals, mechanical latches, mechanical interfaces between portions of a battery pack housing, drain holes in the battery pack housing, etc. If the ingress fluid or material is conductive (e.g., sea water), when such fluid or material enters the battery pack, a short circuit may occur, for example, between positive and negative electrodes of a single battery cell or between cell straps coupled to different groups of battery cells. In some situations, whether a short circuit occurs depends on battery impedance, power capacity, and the spacing/resistance between electrodes.

[0004] In order to avoid such occurrences, independent embodiments of the present invention may provide arrangements for inhibiting or preventing fluid/material intrusion into and/or a short circuit of a battery cell (e.g., a header portion), cells or a battery pack.

[0005] With respect to ingress fluids which are considered to be conductive, sea water has a conductivity of approximately 4.8 Siemens per meter (S/m). In some embodiments, an arrangement may inhibit or prevent a short circuit in a battery pack experiencing intrusion of a fluid having a conductivity of about 4.8 S/m or greater or a conductivity of about 4.5 S/m or greater. In some embodiments, an arrangement may inhibit or prevent a short circuit in a battery pack experiencing intrusion of a fluid having a conductivity of between about 4.0 S/m and 18.0 S/m, between about 4.5 S/m and about 18.0 S/m, or between about 4.8 S/m and about 18.0 S/m.

[0006] In one independent aspect, a battery pack may generally include an outer housing; a cell module connectable to the outer housing, the cell module including a module housing, a plurality of battery cells supported by the module housing, the battery cells having an energy of at least about 60 Watt-hours (Wh), a controller operable to control an operation of the battery pack, a conductive strap electrically connected to at least one of the battery cells, a weld strap connected between the controller and the conductive

strap, and a terminal electrically connected to the battery cells and operable to connect the battery cells to an electrical device for power transfer; and a vapor-deposited coating applied to at least a portion of the cell module.

[0007] The vapor-deposited coating may be applied to at least one of the module housing, at least one of the battery cells, the controller, the conductive strap, and the weld strap. The vapor-deposited coating may be applied to substantially all of the cell module. The vapor-deposited coating may include a poly(p-xylylene) polymer (e.g., parylene). The vapor-deposited coating may include a hydrophobic vapor-deposited coating. The vapor-deposited coating may have a thickness of less than about 20 microns (μm).

[0008] The controller may include a substrate, an electronic component supported on the substrate, and a base coating applied to at least the electronic component, and the vapor-deposited coating may be applied over the base coating. The base coating may be applied to the substrate and the electronic component. The terminal may include a female terminal having opposing contact surfaces operable to engage opposite faces of a mating male terminal of the electrical device, and the vapor-deposited coating may be applied to the female terminal, the opposing contact surfaces being engaged during coating to inhibit application of the vapor-deposited coating to the contact surfaces.

[0009] The cell module may include a first battery cell and a second battery cell, a first conductive strap electrically connected to the first battery cell and a second conductive strap electrically connected to the second battery cell, and a first weld strap electrically connected to the first conductive strap and a second weld strap electrically connected to the second conductive strap, there being a voltage differential between the first weld strap and the second weld strap, the first weld strap being spaced from the second weld strap by a distance equivalent to between 0.6 millimeters (mm) per volt of the voltage differential and about 1.2 mm per volt of the voltage differential. The first weld strap may be spaced from the second weld strap by a distance of between about 5 mm and about 9 mm. The vapor-deposited coating may provide an electrical spacing distance greater than the distance.

[0010] Each battery cell may have a cell diameter of at least about 18 mm and a cell length of at least about 65 mm. Each battery cell may have a cell length of about 70 mm. Each battery cell may have a cell diameter of about 21 mm. The first weld strap may be spaced from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm.

[0011] The first battery cell may be electrically connected in series with the second battery cell, and the cell module may include a third battery cell electrically connected in parallel with the first battery cell. The cell module may include a first string of series-connected battery cells electrically connected in parallel with a second string of series-connected cells. The cell module may include a third string of series-connected battery cells electrically connected in parallel with the first string and with the second string. The first weld strap may be spaced from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm. A voltage potential between the first conductive strap and the second conductive strap may be at least about 8.0 volts (V) and may be no more than about 17.0 V.

[0012] The module housing may include a wall with a surface facing the outer housing, the wall including a

standoff projecting from the surface toward the outer housing to limit an area of engagement between the outer housing and the surface. The outer housing may provide ultra-violet (UV) protection to the vapor-deposited coating.

[0013] The vapor-deposited coating may be applied to at least a portion of the module housing, and the module housing may include a portion exposed after assembly of the battery pack. The exposed surface may be masked during application of the vapor-deposited coating. At least a portion of the exposed surface may be roughened before application of the vapor-deposited coating. The exposed surface may have an edge, the edge being roughened before application of the vapor-deposited coating. The vapor-deposited coating is doped with UV-resistant material. The cell module may include a first module housing portion supporting the plurality of battery cells and a second module housing portion including the exposed portion, the vapor-deposited coating being applied to the first module housing portion, the second module housing portion being connected to the first module housing portion after the vapor-deposited coating is applied to the first module housing portion.

[0014] One of the battery cells may include a cell header, the cell module may further include a seal operable to seal the cell header, and the vapor-deposited coating may be applied to the seal. The seal may include a gasket, and the vapor-deposited coating may be applied to the gasket. The cell module may include a seal operable to seal an interface between the at least one of the battery cells and the conductive strap, and the vapor-deposited coating may be applied to the seal.

[0015] The battery pack may be operable to supply discharge current to a motorized electrical device. The battery pack may be operable to supply discharge current to at least one of a power tool and an outdoor tool. The battery pack may be operable to supply discharge current to a saw. The at least one of a power tool and an outdoor tool may include a hand-held tool, the hand-held tool being supportable by a user during operation.

[0016] Each of the battery cells may have a lithium-based chemistry. The vapor-deposited coating may have a dielectric breakdown strength between 200 Volts/micron (V/ μm) and 300 V/ μm . The vapor-deposited coating may be applied to at least a portion of the plurality of battery cells, and the plurality of battery cells may be operable to supply discharge current to the electrical device to an operating temperature of about 50° C. and about 110° C. The vapor-deposited coating may provide a corrosive resistance to a coated component of less than 10% swelling when exposed to an inorganic reagent or an organic solvent. The vapor-deposited coating may be applied to an at least partially charged battery cell. The battery cell may have a capacity, and the vapor-deposited coating may be applied to a battery cell charged to at least about 20% of the capacity.

[0017] In another independent aspect, a method of assembling a battery pack may be provided. The battery pack may include an outer housing, a cell module including a module housing, at least one battery cell, a controller, a conductive strap electrically connected to the battery cell, a weld strap connected between the controller and the conductive strap, and a terminal electrically connected to the battery cell and operable to connect the battery cell to an electrical device for power transfer. The method may generally include assembling components of the cell module; applying a vapor-

deposited coating to one or more components of the cell module; and mounting the cell module relative to the outer housing.

[0018] Applying may include applying the vapor-deposited coating to at least one of the module housing, the battery cell, the controller, the conductive strap, and the weld strap. Applying may include applying the vapor-deposited coating to substantially all of the assembled cell module. Applying may include applying a poly(p-xylylene) polymer (e.g., parylene). Applying may include applying a hydrophobic vapor-deposited coating. Applying may include applying a vapor-deposited coating having a thickness of less than about 20 μm .

[0019] Assembling components of the cell module may include supporting the battery cell in the module housing, electrically connecting the conductive strap to the battery cell, electrically connecting the weld strap to the controller and to the conductive strap, and electrically connecting the terminal to the controller. Assembling the components of the cell module may include applying a seal to a header of the battery cell. Applying may include applying the vapor-deposited coating to the seal.

[0020] Applying may be performed before supporting the battery cell. Applying may be performed after supporting the battery cell. Applying may be performed after connecting the weld strap.

[0021] The method may further include charging the battery cell. Charging may be performed before applying. The battery cell has a capacity, and charging may include charging the battery cell to at least about 20% of the capacity.

[0022] The controller may include a substrate, an electronic component supported on the substrate, and a base coating applied to at least the electronic component, and applying may include applying the vapor-deposited coating over the base coating. The base coating may be applied to the substrate and the electronic component.

[0023] The terminal may include a female terminal having opposing contact surfaces operable to engage opposite faces of a mating male terminal of the electrical device, and the method may further include, during applying, inhibiting application of vapor-deposited coating to the opposing contact surfaces via engagement of the opposing contact surfaces.

[0024] The cell module may include a first battery cell and a second battery cell, assembling may include electrically connecting a first conductive strap to the first battery cell and a second conductive strap to the second battery cell, and electrically connecting a first weld strap to the first conductive strap and a second weld strap to the second conductive strap, there being a voltage differential between the first weld strap and the second weld strap, and assembling may include spacing the first weld strap from the second weld strap by a distance equivalent to between 0.6 millimeters (mm) per volt of the voltage differential and about 1.2 mm per volt of the voltage differential. Spacing may include spacing the first weld strap from the second weld strap by a distance of between about 5 mm and about 9 mm. Applying may include applying a vapor-deposited coating to provide an electrical spacing distance greater than the distance.

[0025] Each battery cell may have a cell diameter of between about 18 mm and about 21 mm and a cell length of between about 65 mm and about 70 mm, and spacing may

include spacing the first weld strap from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm.

[0026] Assembling components of the cell module may include electrically connecting in parallel a first string of series-connected battery cells, a second string of series-connected battery cells, and a third string of series-connected battery cells, and spacing may include spacing the first weld strap from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm. A voltage potential between the first conductive strap and the second conductive strap may be at least about 8.0 volts (V) and may be no more than about 17.0 V.

[0027] The module housing may include a wall with a surface facing the outer housing, the wall including a standoff projecting from the surface toward the outer housing, and assembling components of the cell module may include limiting an area of engagement between the outer housing and the surface via engagement of the standoff with the outer housing.

[0028] Mounting may include mounting the cell module relative to an outer housing providing ultra-violet (UV) protection to the vapor-deposited coating. The module housing may include a portion exposed after assembly of the battery pack, applying may include applying the vapor-deposited coating to at least a portion of the module housing, and at least one of the following: assembling components of the cell module may include masking the exposed surface before applying; assembling components of the cell module may include, before applying, roughening at least a portion of the exposed surface; applying may include doping the vapor-deposited coating with UV-resistant material; and applying may include applying the vapor-deposited coating to a first module housing portion, a second module housing portion providing the exposed portion being connected to the first module housing portion after the vapor-deposited coating is applied to the first module housing portion.

[0029] The battery cell may include a cell header, the cell module may further include a seal operable to seal the cell header, and applying may include applying the vapor-deposited coating to the seal. The seal may include a gasket, and applying may include applying the vapor-deposited coating to the gasket. The cell module may include a seal operable to seal an interface between the battery cell and the conductive strap, and applying may include applying the vapor-deposited coating to the seal.

[0030] The battery pack may be operable to supply discharge current to a motorized electrical device. The battery pack may be operable to supply discharge current to at least one of a power tool and an outdoor tool. The battery pack may be operable to supply discharge current to a saw. The at least one of a power tool and an outdoor tool may include a hand-held tool, the hand-held tool being supportable by a user during operation.

[0031] The battery cell may have a lithium-based chemistry. Applying may include applying a vapor-deposited coating having a dielectric breakdown strength between 200 Volts/micron (V/ μ m) and 300 V/ μ m. Applying may include applying vapor-deposited coating to the battery cell, and the battery pack may be operable to supply discharge current to the electrical device to an operating temperature of about 50° C. and about 110° C. Applying may include applying a vapor-deposited coating provides a corrosive resistance to a coated component of less than 10% swelling when exposed

to an inorganic reagent or an organic solvent. The battery pack may include a plurality of battery cells supported by the housing, the battery cells having an energy of at least about 60 Watt-hours.

[0032] In yet another independent aspect, a battery pack may generally include an outer housing; and a cell module mounted relative to the outer housing. The cell module may include a module housing, a first battery cell and a second battery cell supported by the module housing, and a first conductive strap electrically connected to the first battery cell and a second conductive strap electrically connected to the second battery cell, and a first weld strap electrically connected to the first conductive strap and a second weld strap electrically connected to the second conductive strap, there being a voltage differential between the first weld strap and the second weld strap, the first weld strap being spaced from the second weld strap by a distance equivalent to between 0.6 millimeters (mm) per volt of the voltage differential and about 1.2 mm per volt of the voltage differential.

[0033] The first weld strap may be spaced from the second weld strap by a distance of between about 5 mm and about 9 mm. Each battery cell may have a cell diameter of at least about 18 mm and a cell length of at least about 65 mm. Each battery cell may have a cell length of about 70 mm. Each battery cell may have a cell diameter of about 21 mm. The first weld strap may be spaced from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm.

[0034] The first battery cell may be electrically connected in series with the second battery cell, and the cell module may include a third battery cell electrically connected in parallel with the first battery cell. The cell module may include a first string of series-connected battery cells electrically connected in parallel with a second string of series-connected cells. The cell module includes a third string of series-connected battery cells electrically connected in parallel with the first string and with the second string, and the first weld strap may be spaced from the second weld strap by a distance of between about 6.5 mm and about 8.5 mm. A voltage potential between the first conductive strap and the second conductive strap may be at least about 8.0 volts (V) and may be no more than about 17.0 V.

[0035] The battery pack may further include a vapor-deposited coating applied to at least a portion of the cell module. The vapor-deposited coating may provide an electrical spacing distance greater than the distance.

[0036] The vapor-deposited coating may be applied to at least one of the module housing, at least one of the battery cells, the controller, the conductive strap, and the weld strap. The vapor-deposited coating may be applied to substantially all of the cell module. The vapor-deposited coating may include a poly(p-xylylene) polymer (e.g., parylene). The vapor-deposited coating may include a hydrophobic vapor-deposited coating. The vapor-deposited coating may have a thickness of less than about 20 microns (μ m).

[0037] The controller may include a substrate, an electronic component supported on the substrate, and a base coating applied to at least the electronic component, and the vapor-deposited coating may be applied over the base coating. The base coating may be applied to the substrate and the electronic component.

[0038] The terminal may include a female terminal having opposing contact surfaces operable to engage opposite faces of a mating male terminal of the electrical device, and the

vapor-deposited coating may be applied to the female terminal, the opposing contact surfaces being engaged during coating to inhibit application of the vapor-deposited coating to the contact surfaces.

[0039] The module housing may include a wall with a surface facing the outer housing, the wall including a standoff projecting from the surface toward the outer housing to limit an area of engagement between the outer housing and the surface. The outer housing may provide ultra-violet (UV) protection to the vapor-deposited coating.

[0040] The vapor-deposited coating may be applied to at least a portion of the module housing, the module housing may include a portion exposed after assembly of the battery pack, and wherein at least one of the following: the exposed surface may be masked during application of the vapor-deposited coating; at least a portion of the exposed surface may be roughened before application of the vapor-deposited coating; the vapor-deposited coating may be doped with UV-resistant material; and the cell module may include a first module housing portion supporting the plurality of battery cells and a second module housing portion including the exposed portion, the vapor-deposited coating being applied to the first module housing portion, the second module housing portion being connected to the first module housing portion after the vapor-deposited coating is applied to the first module housing portion.

[0041] One of the battery cells may include a cell header, the cell module may further include a seal operable to seal the cell header, and the vapor-deposited coating may be applied to the seal. The cell module may include a seal operable to seal an interface between the at least one of the battery cells and the conductive strap, and wherein the vapor-deposited coating is applied to the seal.

[0042] The vapor-deposited coating may have a dielectric breakdown strength between 200 Volts/micron (V/ μm) and 300 V/ μm . The vapor-deposited coating may be applied to at least a portion of the plurality of battery cells, and the plurality of battery cells may be operable to supply discharge current to the electrical device to an operating temperature of about 50° C. and about 110° C. The vapor-deposited coating may provide a corrosive resistance to a coated component of less than 10% swelling when exposed to an inorganic reagent or an organic solvent.

[0043] The vapor-deposited coating may be applied to an at least partially charged battery cell. The battery cell has a capacity, and the vapor-deposited coating may be applied to a battery cell charged to at least about 20% of the capacity.

[0044] The battery pack may be operable to supply discharge current to a motorized electrical device. The battery pack may be operable to supply discharge current to at least one of a power tool and an outdoor tool. The battery pack may be operable to supply discharge current to a saw. The at least one of a power tool and an outdoor tool may include a hand-held tool, the hand-held tool being supportable by a user during operation.

[0045] Each of the battery cells may have a lithium-based chemistry. The battery pack may further include a plurality of battery cells supported by the housing, the battery cells having an energy of at least about 60 Watt-hours.

[0046] In a further independent aspect, a battery pack may generally include a housing; a battery cell supported by the housing and including a cell header, the battery cell having a nominal voltage of between about 3.6 V and about 4.2 V, the battery cell having a capacity of between about 2 Ah and

about 5 Ah; a seal member sealing an interface of the cell header; and a vapor-deposited coating applied to the seal and to at least a portion of the battery cell.

[0047] The seal member may include a soft elastomer member. The soft elastomer member may be positioned at the interface, and the seal member may include a hard plastic member engageable to press the elastomer member into the interface. The battery pack may further include a conductive strap electrically connectable to the cell header and operable to hold the seal member in a position. The conductive strap may be welded to the cell header. The seal may include an adhesive seal adhesively fixed to the cell header.

[0048] The housing may be an outer housing; and the battery pack may further include a cell module mountable relative to the outer housing, the cell module including a module housing, the battery cell, the battery cell being supported by the module housing, a controller operable to control an operation of the battery pack, a conductive strap electrically connected the battery cell, a weld strap connected between the controller and the conductive strap, and a terminal electrically connected to the battery cell and operable to connect the battery cell to an electrical device for power transfer.

[0049] The vapor-deposited coating may be applied to at least a portion of the cell module. The vapor-deposited coating may be applied to substantially all of the cell module. The module housing may be operable to hold the seal member in a position.

[0050] The battery pack may include a plurality of battery cells supported by the housing, the battery cells having an energy of at least about 60 Watt-hours.

[0051] In another independent aspect, a battery pack may generally include an outer housing; a cell module connectable to the outer housing, the cell module including a module housing, a plurality of battery cells supported by the module housing, a controller operable to control an operation of the battery pack, a conductive strap electrically connected to at least one of the battery cells, a weld strap connected between the controller and the conductive strap, a terminal electrically connected to the battery cells and operable to connect the battery cells to an electrical device for power transfer, and a seal member operable to seal a portion of the cell module; and a vapor-deposited coating applied to the seal member.

[0052] Each of the battery cells may include a cell header, and seal member may seal an interface of the cell header. The seal operable may be operable to seal an interface between the at least one of the battery cells and the conductive strap.

[0053] In yet another independent aspect, a battery pack may generally include a housing assembly including an upper housing portion defining an opening, and a lower housing portion connectable to the upper housing portion to define a cavity, the lower housing portion being substantially uninterrupted; a controller supported on the upper housing portion; weld straps electrically connected to the controller and having contact ends; potting compound material sealing a lower section of the upper housing portion, the material covering the controller and the weld straps with the contact ends remaining exposed; a plurality of battery cells supported in the lower housing portion; and conductive straps electrically connected to the battery cells, the exposed contact ends being electrically connected to the conductive straps. The lower housing portion may be sealably con-

nected to the sealed lower section of the upper housing portion to seal the battery cells in the housing assembly.

[0054] In a further independent aspect, a battery pack may generally include a housing assembly including an upper housing portion defining an opening, and a substantially uninterrupted lower housing portion connectable to the upper housing portion to define a cavity; an insert plate including weld straps having exposed first contact ends and oppositely-extending exposed second contact ends; a controller electrically connected to the first contact ends; a plurality of battery cells supported in the lower housing portion; and conductive straps electrically connected to the battery cells, the second contact ends being electrically connected to the conductive straps. The lower housing portion may be sealingly connected to the insert plate to seal the battery cells in the lower housing portion.

[0055] The weld straps may be insert-molded with the insert plate. The weld straps may be supported on and sealed to the insert plate. The upper housing portion may be assembled to the insert plate and the lower housing portion.

[0056] Other independent aspects of the invention may become apparent by consideration of the detailed description and accompanying drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0057] FIG. 1 is a perspective view of a cell in accordance with some embodiments.

[0058] FIG. 2 is a perspective view of a cell in accordance with some embodiments.

[0059] FIG. 3 is another perspective view of the cell shown in FIG. 2 in accordance with some embodiments.

[0060] FIG. 4 is a side view of a cell in a core housing in accordance with some embodiments.

[0061] FIG. 5 is a perspective view of the core housing shown in FIG. 4 including a conducting strip in accordance with some embodiments.

[0062] FIG. 6 is a side view of a cell in a core housing in accordance with some embodiments.

[0063] FIG. 7 is a perspective view of the core housing shown in FIG. 6 including a conducting strip in accordance with some embodiments.

[0064] FIG. 8 is a side view of a cell in a core housing in accordance with some embodiments.

[0065] FIG. 9 is a perspective view of the core housing shown in FIG. 8 including a conductive strip in accordance with some embodiments.

[0066] FIGS. 10A-10C are views of a gasket in accordance with some embodiments.

[0067] FIG. 11 is a perspective view of the core housing shown in FIG. 8 with a conducting strap removed in accordance with some embodiments.

[0068] FIG. 12 is a perspective view of the core housing shown in FIG. 11 with a portion of the core housing removed in accordance with some embodiments.

[0069] FIG. 13 is a perspective view of a core housing illustrating a laser welded conducting strap in accordance with some embodiments.

[0070] FIG. 14 is a perspective view of the laser welded conducting strap shown in FIG. 13 in accordance with some embodiments.

[0071] FIG. 15 is a cross-section view illustrating the laser welded conducting strap shown in FIG. 13 in contact with a cell in accordance with some embodiments.

[0072] FIG. 16 is an exploded view of a battery pack in accordance with some embodiments.

[0073] FIG. 17 is a perspective view of a bottom portion of a housing assembly of a battery pack in accordance with some embodiments.

[0074] FIG. 18 is a perspective view of a portion of a battery pack in accordance with some embodiments.

[0075] FIG. 19 is a perspective cross-sectional view of a portion of the battery pack shown in FIG. 18.

[0076] FIGS. 20A-20J are views of a sealed battery pack, illustrating a method of assembling the battery pack.

[0077] FIGS. 21A-21H are views of another sealed battery pack, illustrating a method of assembling the battery pack.

[0078] FIG. 22 is a perspective view of a cell in accordance with some embodiments.

[0079] FIG. 23 is a perspective view of a cell in accordance with some embodiments.

[0080] FIG. 24 is a perspective view of a cell in accordance with some embodiments.

[0081] FIG. 25 is a perspective view of a cell in accordance with some embodiments.

[0082] FIGS. 26A-26B are perspective views of a portion of a battery pack in accordance with some embodiments.

[0083] FIGS. 27A-27B are perspective views of a battery pack in accordance with some embodiments.

[0084] FIGS. 28A-28C are perspective views of a battery pack and a portion of an electrical device, such as a power tool, an outdoor tool, etc., in accordance with some embodiments.

[0085] FIGS. 29A-29B are perspective views of a battery pack and a portion of an electrical device, such as a power tool, an outdoor tool, etc., in accordance with some embodiments.

[0086] FIGS. 30A-30B are perspective views of battery cells in accordance with some embodiments.

[0087] FIGS. 31A-31B are perspective views of a battery cell in accordance with some embodiments.

[0088] FIG. 32 is a schematic view of a battery cell including a gasket in accordance with some embodiments.

[0089] FIGS. 33A-33B are perspective views of a battery pack illustrating strap routing.

[0090] FIGS. 34A-34B are perspective views of the battery pack of FIGS. 33A-33B illustrating a voltage differential between pairs of straps.

[0091] FIG. 35 is a perspective view of a battery pack illustrating alternative strap routing.

[0092] FIG. 36 is a plan view of the battery pack of FIG. 35 illustrating a voltage differential between pairs of straps.

[0093] FIG. 37 is a plan view of an alternative construction of a battery pack illustrating strap routing.

[0094] FIG. 38 is a perspective view of a battery pack illustrating a core seal.

[0095] FIG. 39 is a perspective view of a battery pack illustrating a core seal.

[0096] FIGS. 40A-40B are views of a core housing of a battery pack illustrating drain holes of the core housing.

[0097] FIGS. 41A-41B are views of examples of battery pack components coated in vapor-deposited coating.

[0098] FIG. 42 is a block diagram of a battery pack illustrating individual cell monitoring.

[0099] FIG. 43 is a view of a cell tap flex circuit.

[0100] FIG. 44 is a schematic view of battery pack components coated in a vapor-deposited coating.

[0101] FIGS. 45A-45E are photographs of battery pack components coated in a vapor-deposited coating.

[0102] FIGS. 46A-46B are views of a portion of a battery pack.

[0103] FIG. 47 is an exploded view of an electronic device, such as a tracking device.

[0104] FIGS. 48A-48E are views of a switch for the battery pack.

[0105] FIGS. 49A-49C are perspective views of battery packs in accordance with some embodiments.

[0106] FIGS. 50A-50B illustrate electrical systems including various electrical devices operable with the battery packs of FIGS. 49A-49C.

[0107] FIGS. 51A-51B are perspective views of battery packs in accordance with some embodiments.

[0108] FIG. 52 illustrates an electrical system including various electrical devices operable with the battery packs of FIGS. 51A-51B.

[0109] FIGS. 53A-53F are views of an assembly process of the battery pack of FIG. 51A.

[0110] FIGS. 54A-54E are view of an assembly process of the battery pack of FIG. 51B.

DETAILED DESCRIPTION

[0111] Before any independent embodiments of the invention are explained in detail, it is to be understood that the invention is not limited in its application to the details of construction and the arrangement of components set forth in the following description or illustrated in the following drawings. The invention is capable of other independent embodiments and of being practiced or of being carried out in various ways. Also, it is to be understood that the phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting.

[0112] Use of “including” and “comprising” and variations thereof as used herein is meant to encompass the items listed thereafter and equivalents thereof as well as additional items. Use of “consisting of” and variations thereof as used herein is meant to encompass only the items listed thereafter and equivalents thereof.

[0113] Relative terminology, such as, for example, “about”, “approximately”, “substantially”, etc., used in connection with a quantity or condition would be understood by those of ordinary skill to be inclusive of the stated value and has the meaning dictated by the context (for example, the term includes at least the degree of error associated with the measurement of, tolerances (e.g., manufacturing, assembly, use) associated with the particular value, etc.). Such terminology should also be considered as disclosing the range defined by the absolute values of the two endpoints. For example, the expression “from about 2 to about 4” also discloses the range “from 2 to 4”.

[0114] The relative terminology may refer to plus or minus a percentage (e.g., 1%, 5%, 10% or more) of an indicated value. For example, with a 10% range, “about 20 Volts” may indicate a range of 18 Volts (V) to 22 V, and “about 1%” may mean from 0.9-1.1. Other meanings of relative terms may be apparent from the context, such as rounding off, so, for example “about 20 V” may also mean from 19.5 V to 20.4 V.

[0115] Also, the functionality described herein as being performed by one component may be performed by multiple components in a distributed manner. Likewise, functionality performed by multiple components may be consolidated and

performed by a single component. Similarly, a component described as performing particular functionality may also perform additional functionality not described herein. For example, a device or structure that is “configured” in a certain way is configured in at least that way but may also be configured in ways that are not listed.

[0116] Various arrangements for inhibiting fluid intrusion into and/or a short circuit of a battery cell (e.g., a header portion), cells or a battery pack operable, for example, as a power source for motorized devices (e.g., power tools, outdoor power equipment, vehicles, etc.), non-motorized devices (e.g., lighting equipment, audio equipment, power supplies, etc.). In some constructions, a sealing arrangement is provided for the battery cell, specifically, the header portion. In some constructions, structure of the battery pack (e.g., the core housing, the conductive strap, the battery housing assembly, etc.) operates to inhibit fluid intrusion alone or in combination with a sealing arrangement. In some constructions, the construction of the battery pack (e.g., spacing between battery straps) operates to inhibit a short circuit if fluid does intrude into the battery pack.

[0117] FIG. 1 illustrates a battery cell 10 including a positive terminal 14, a negative terminal 18 (see FIG. 3), and a cell sleeve or cell covering 22 having a circular opening at the terminals. Typically, a washer, which does not seal the cell header 26, is provided. As described below, a gasket or soft elastomer seal 30 may replace the illustrated washer and be positioned and seal the spacing between the cell terminals. The gasket/seal 30 has an opening allowing electrical connection to the terminals. In some embodiments, the gasket/seal 30 has a strength that is less than approximately 20 kg/cm² to allow venting of the battery cell.

[0118] In FIGS. 2-3, an adhesive seal 34 is positioned over the opening in the cell covering 22 to close off a portion of the cell head. In such constructions, the gasket/seal 30 shown in FIG. 1 may be used under the cell covering 22, and the adhesive seal 34 may be placed over the cell covering 22, the gasket 30, and the header part 26. The adhesive seal 34 may be a sticker, a tape, an adhesive backed rubber, etc.

[0119] In some embodiments, the adhesive seal 34 includes an electrically-insulating material with an adhesive backing. In some embodiments, the adhesive seal 34 may include a top layer of vinyl, polypropylene (PP) or nylon, as the electrically-insulating material, with an acrylic adhesive on the underside. In some embodiments, the adhesive could be applied to both sides of the electrically-insulating material layer to allow the seal 34 to adhere to both the cell 10 and the core housing 38 (or the battery housing (if there is no cell core)).

[0120] As shown in FIGS. 2-3, the illustrated adhesive seal 34 is generally doughnut-shaped with an opening exposing a terminal of the battery cell 10 for welding to the conductive strap 42.

[0121] In other embodiments (see, e.g., FIGS. 31A-31B), the adhesive seal 34 does not include such an opening and covers the battery terminal. In such embodiments, the conductive straps 42 may be welded (e.g., spot welded, laser welded, etc.) through the adhesive seal 34 to electrically couple to the battery terminal. The welding operation heats the conductive strap 42 to thermally introduce a hole through the adhesive seal 34 before attaching to the cell header. Alternatively, points on the conductive strap 42 could physically puncture holes through the seal 34 to begin

welding. Either way, the welding process minimally removes material of the seal **34** and provides a larger sealing area.

[0122] In some embodiments, the strength and/or distribution of the adhesive on the seal **34** are sufficient to prevent the seal **34** from becoming displaced or falling off during normal operation of a device being powered by the battery pack. The strength and/or distribution of the adhesive on the seal **34** are also sufficient to prevent ingress fluid (e.g., water) from penetrating the seal **34**.

[0123] However, in some embodiments, the strength and/or distribution are low enough to allow venting of the battery cell **10** (i.e., gases are able to vent out of the battery cell **10** past the seal **34** even though the seal **34** prevents ingress fluid from entering the battery cell **10**). In such embodiments, the adhesive seal **34** may have a strength that is, for example, less than approximately 20 kg/cm².

[0124] There may be advantages to sealing individual cells **10** compared to sealing groups of cells **10** (e.g., sealing the whole battery pack, sealing the cell core, etc.). For example, seals **34** for individual cells **10** may allow for flexibility in manufacturing for various different pack configurations (e.g., each cell **10** is sealed regardless of the pack configuration). As another example, an individual cell **10** can generally be more accurately sealed compared to a group of cells **10**. As yet another example, an individual cell seal **34** may have greater durability and/or a reduced likelihood that the seal **34** will be displaced from its sealing position.

[0125] In some independent embodiments, the gasket **30** is formed of multiple components, for example, by multi-shot injection molding. As shown in FIGS. 4-5, the illustrated gasket **30** includes two components: a soft elastomer **46**; and a hard plastic **50**. The hard plastic **50** and soft materials **46** may be insert-molded together. The soft elastomer **46** may be a soft material (e.g., silicone) having a durometer of, for example, about 50 on a Shore A scale or higher (though, in other constructions, this value could also be lower than 50). The gasket **30** extends into an opening of the core housing **38**. The hard plastic **50** is pressed down and causes the soft elastomer **46** to be pressed into the opening, improving the seal.

[0126] As shown in FIG. 4, the illustrated soft elastomer **46** is shaped (e.g., has an inwardly-directed annular rib **54**) to fill the opening between the cell header **26** and the covering **22**. The illustrated hard plastic **50** is also shaped (e.g., has an outwardly-directed rib) to transfer the pressing force to the soft elastomer **46**. The gasket **30** (e.g., the soft elastomer **46**) also has an inner rim **58** around the opening engageable by the conducting strap **42**.

[0127] In FIG. 4, the illustrated gasket **30** has a relatively-small outer diameter, fitting within the opening in the core housing **38**. In other constructions (see, e.g., FIG. 8), the gasket **30** has a different diameter (e.g., a larger diameter) and is retained within the core housing **38**.

[0128] It should be understood that the gasket **30** may have a different number of inwardly- and outwardly-directed ribs. For example, in FIG. 8, the gasket **30** has two inwardly-directed ribs **62** (e.g., a radially inner rib **62A** and a radially outer rib **62B**) and no outwardly-directed ribs. In another example (see FIGS. 10A-10C), the gasket **30** has a series of radially-inner inwardly-directed ribs **66** (e.g., two), a series of radially-outer inwardly-directed ribs **70** (e.g., two), and at least one outwardly-directed rib **74** (e.g., one).

[0129] In yet another example (see FIG. 15), the gasket **30** has a series of radially-inner inwardly-directed ribs **78** (e.g., two) and a series of radially-outer inwardly-directed ribs **82** (e.g., four). The ribs(s) may have different shapes and sizes (e.g., moving radial outward in FIG. 15, the ribs in each series increase in length). In general, for the illustrated gaskets **30**, the ribs are for-the-most-part directed inwardly toward the cell **10** rather than outwardly toward the conductive strap **42**.

[0130] The gasket **30** is held in place by a conducting strap **42** or weld of the strap of a cell core of a battery pack. The strap **42** can be laser welded (for straps having a thickness of less than about 0.15 mm) or resistance welded (for straps having a thickness of about 0.15 mm or greater) in place.

[0131] With respect to FIGS. 6-7, in some embodiments, the gasket **30** is formed by a single injection molded soft elastomer **46**. The gasket **30** extends into an opening of the core housing **38**. The gasket **30** is shaped (e.g., with an over-sized inwardly-directed rib **54** and with an outwardly-directed rib **86**) to fill the opening. As with the construction in FIGS. 4-5, the gasket **30** is illustrated being held in place by the conducting strap **42** or weld of the strap.

[0132] With respect to FIGS. 8-12, in some embodiments, the gasket **30** is placed between the core housing **38** and the cell header **26** (e.g., the positive header; a gasket **30** may or may not be placed at the negative header). The gasket **30** is shaped (e.g., with radially-inner and outer inwardly-directed ribs **62** to fill the opening and extend over the covering **22**). As described above, the gasket **30** is illustrated being held in place by the conducting strap **42** or weld of the strap.

[0133] With respect to FIGS. 8-12 (and FIG. 15), in some embodiments, the gasket **30** is insert-molded or over-molded to and formed integrally with the core housing **38**. Upon assembly of the core housing **38**, the header part **26** (e.g., the positive header; again, a gasket **30** may or may not be placed at the negative header) is sealed by the core housing **38** and the insert-molded gasket **30**.

[0134] The conductive strap **42** may be resistance welded (again, for straps having a thickness of about 0.15 mm or greater) or laser welded (for straps having a thickness of less than about 0.15 mm). With respect to FIGS. 13-15, in some embodiments, the conducting strap **42** is laser welded to contact the terminals of the cell **10**.

[0135] FIG. 16 illustrates an exploded view of a battery pack **100**. The cell core **104**, including the core housing **38** supporting the cells **10**, is placed in the main housing **108**. The bottom portion **112** of the main housing **108** may include elevated posts to suspend cells **10** above the main housing **108** floor and higher side walls to allow for the top portion **116** of the main housing **108** to mount over such an elevated cell core **104**. The spacing between the core housing **38** and the main housing **108** may be 3 mm or greater below and/or above the core housing **38**.

[0136] FIG. 17 illustrates a construction of the bottom portion **112** of the main housing **108**. The floor **120** of the bottom portion **112** of the main housing **108** may include a draft or slope to provide intentional direction of fluid within the housing **108** to a vent or drain hole **124**. The floor **120** may be drafted (e.g., starting at the red line in FIG. 17) outwardly towards side walls **128** to allow any fluid to be directed to exit the housing **108** when the battery pack **100** sitting on a flat surface.

[0137] In some embodiments, the side walls **128** of the bottom portion **112** of the main housing **108** may include a

draft or slope. The bottom portion **112** of the main housing **108** may also include intermediate drafts or slopes to also direct the fluid in a direction along the centerline and toward an associated vent or drain hole **124**.

[0138] FIGS. **18-19** illustrate a portion of a battery pack **100** including a seal or gasket **132** between the conductive strap **42** and the core frame or housing **38**. The strap **42** and the core housing **38** provide compression to the gasket **132** to inhibit ingress of fluid to the cell(s) **10** or cell header **26**. The battery pack **100** may also include, as described above, a seal or gasket **30** between the cell **10** and the core housing **38** and/or a gasket **136** between pieces of the core housing **38** to prevent ingress from the opposite side.

[0139] As shown in FIG. **19**, the weld strap **42** and the pieces of the cell core housing **38** sandwich material of a gasket **132** to inhibit ingress to the battery cell **10**. Reference numbers **132**, **136** illustrate possible secondary seal/gasket locations.

[0140] FIGS. **20A-20J** illustrate a sealed battery pack **100**. In the illustrated construction, the battery pack **100** is sealed by potting entire an upper housing portion **116** and removing drain holes **124** at the bottom of the lower housing portion **112**.

[0141] As shown in FIGS. **20C-20F**, openings through the upper housing area **116** and into the housing cavity are sealed, and, in order to accommodate the sealing arrangement, separate weld straps **140** mechanically and electrically connect to the conductive straps **42** of the cell core **104** (see FIGS. **20D** and **20F-20H**). Likewise, drain/vent openings **124** through the lower housing portion **112** are eliminated or closed (see FIG. **20I**). As shown in FIG. **20J**, a seal or gasket **144** is provided between (e.g., ultrasonically welded to, insert molded with, mechanically held by, etc.) the upper housing portion **116** and lower housing portion **112**.

[0142] As shown in FIGS. **20A-20B**, the upper housing portion **116** and the battery pack latches **148** are assembled. The latch cover **152** (see FIG. **20C**) is insert-molded with clear material for a light-emitting diode (LED) or LED cover. In FIG. **20D**, the printed circuit board assembly (PCBA) **156**, including a controller, is assembled to the upper housing section **116**. The separate weld straps **140** are electrically connected to the PCBA **156**. Each weld strap **140** includes a free end **160** for connection to the cell core **104**.

[0143] Spaces proximate the terminals and in the area the upper housing **116** contacts the PCBA **156** are filled (see FIG. **20E**). As shown in FIG. **20F**, potting compound material **164** covers the PCBA **156** and terminal connections and fills the underside of the upper housing area **116**, leaving only the free ends **160** of the weld straps **140** exposed.

[0144] As shown in FIGS. **20G-20H**, the cell core **104**, including the battery cells **10**, the core housing **38**, and the conductive straps **42**, is assembled to the upper housing section **116**, and the weld straps **140** are electrically and mechanically connected to the conductive straps **42**. The sealed lower housing portion **112** is connected to the upper housing section **116** (see FIG. **20I**), and a gasket **132** (rubber foam), connected, in the illustrated construction to the lower housing portion **112** (e.g., by ultrasonic welding), seals the interface.

[0145] In some embodiments, spacing between conductive elements (e.g., weld straps **140**, conductive straps **42**, etc.) within the battery pack **100** is increased to reduce the likelihood of a short circuit when conductive fluid enters the battery pack **100**—generally, the greater the spacing

between conductive elements within the battery pack **100** the more ingress fluid that is necessary to cause a short circuit. Accordingly, spacing between the welding straps **140** (see, e.g., FIG. **20D**) and/or between the conductive straps **42** (see, e.g., FIG. **20H**) may be increased; however, spacing of such conductive components is not increased so much as to negatively impact electrical performance of the conductive components (e.g., significantly increase resistance and/or heat).

[0146] In existing battery packs, the spacing between weld straps may be as small as about 1.0 mm. With the above-described increased spacing, in some embodiments, the spacing between the weld straps **140** (and/or the conductive straps **42**) may be between about 0.5 mm/1 V of voltage differential to about 1.5 mm/1 V of voltage differential. In other embodiments, the spacing may be between about 0.55 mm/1 V of voltage differential and about 1.2 mm/1 V of voltage differential. In still other embodiments, the spacing may be between about 0.7 mm/1 V of voltage differential and about 1.125 mm/1 V of voltage differential. For example, the spacing between weld straps **140** may be about 1 mm/1 V of voltage differential.

[0147] In some examples, the voltage differential between weld straps **140** may be about 8 V, and, for such examples, the corresponding spacing is at least about 3.5 mm or greater or at least 7.5 mm or greater. In some embodiments, the spacing is between about 5 mm and about 9 mm. In other embodiments, the spacing may be between about 6.5 mm and about 8.5 mm. In still other embodiments, the spacing is between about 7.0 mm and about 8.0 mm. In some embodiments, the example spacing distance between straps **140** noted above may be implemented on any type of battery pack **100** (e.g., battery packs **100** with a single cell string (1P), two parallel cell strings (2P), three parallel cell strings (3P), etc., battery packs **100** including 18650 battery cells, 20700 battery cells, 21700 battery cells, etc.).

[0148] In some embodiments, the spacing distance between the weld straps **140** and/or the conductive straps **42** may be different depending on the configuration of the battery pack **100**. In other words, the spacing distance between the weld straps **140** and/or the conductive straps **42** may vary depending on at least one of the impedance and power capacity of the battery pack **100** (e.g., the number of and arrangement of cells **10** in the battery pack **100** (e.g., a single cell string (1P), two parallel cell strings (2P), three parallel cell strings (3P), etc.); the size of the battery cells **10** (e.g., 18650 cells, 20700 cells, 21700 cells, etc.), etc.).

[0149] In some embodiments, a battery pack **100** with higher power capacity and lower impedance may have larger spacing distances between straps **140** and/or the conductive straps **42** than a battery pack with lower power capacity and higher impedance. For example, a first battery pack **100** with two parallel sets of five battery cells **10** (2P) may have straps **140** spaced closer together (e.g., a spacing of about 3.5 mm) than a second battery pack **100** with three parallel sets of five battery cells **10** (e.g., a spacing of about 6.5 mm to about 8.5 mm) because the second battery pack **100** has a larger power capacity than the first battery pack **100**.

[0150] In some embodiments, the spacing distance between the straps **140** and/or the conductive straps **42** may vary based on the type of battery cell **10** (e.g., 18650 cells, 20700 cells, 21700 cells, etc.). As another example, a first battery pack **100** with two parallel sets of five 18650 battery cells **10** may have the straps **140** spaced closer together (e.g.,

a spacing of about 3.5 mm) than a second battery pack 100 with two parallel sets of five 21700 battery cells 10 (e.g., a spacing of about 6.5 mm to about 8.5 mm) because the second battery pack 100 has a larger power capacity than the first battery pack 100.

[0151] FIGS. 21A-21H illustrate another sealed battery pack 100. In the illustrated construction, the battery pack 100 is sealed by an insert 168 positioned between and sealing the lower housing portion 116 from the upper housing portion 120. As shown in FIGS. 21A and 21G, an insert plate 168, molded with a “spider” of weld straps 140, is sealingly connected (e.g., ultrasonically welded) to the sealed lower housing portion 112. In other constructions (not shown), the weld straps 140 may be assembled with or connected to the insert plate 168 with any openings (e.g., to accommodate exposed contact ends) being sealed.

[0152] As mentioned above, the insert 168 includes a plate with the weld straps 140 insert molded therein. The weld straps 140 include exposed contact ends 172 for the PCBA 156 and oppositely-extending (e.g., downwardly) exposed contact ends 160 for the conductive straps 42. As shown in FIG. 21B, the PCBA, with the battery pack terminal block 176, is electrically connected (e.g., soldered) to the upper contact ends 172. The area of the solder connections are filled (e.g., with glue; see FIG. 21C).

[0153] As shown in FIG. 21D, the insert 168 is connected to the core housing 38, and the lower contact ends 160 of the weld straps 140 are electrically-connected (e.g., welded) to the conductive straps 42 (see FIG. 21E). The cell core 104 is positioned within the sealed bottom housing portion 112 (see FIG. 21F), and, as shown in FIG. 21G, the insert 168 and the bottom housing portion 112 are sealingly connected (e.g., ultrasonically-welded). A sealing member 180 (e.g., a gasket, room-temperature-vulcanized (RTV) silicone, etc.; see FIG. 21G) is sealed at the interface between the insert 168 and the bottom housing portion 112. The lower portion of the battery pack 100 forms a sealed unit.

[0154] As shown in FIG. 21H, the upper housing sub-assembly is assembled to the lower portion of the battery pack 100 (shown in FIG. 21G). As described above (see FIGS. 20A-20C), the upper housing sub-assembly includes an upper housing portion 112, latches 148 and a latch cover 152.

[0155] FIG. 22 illustrates a battery cell 10 with a seal arrangement. Material inhibiting or preventing current flow, corrosion between the battery terminals, etc., may fill, be sprayed on, plate, coat, etc., the cell header or adjacent negative portion of the cell. The material may include silicone, electrically-insulating foam, etc.

[0156] FIG. 23 illustrates a battery cell 10 with a sealing sleeve 184. The cell sleeve 184 may include the base sleeve or may be an additional sleeve and may inhibit, prevent and/or close the open space surrounding the cell anode (batt +). This sleeve 184 inhibits or prevents fluid from entering the space below the anode and the space between the anode and cathode. In the illustrated constructions, the diameter of the sleeve 184 decreases to the diameter of the batt + anode and then seals against the anode.

[0157] As provided in FIG. 24, in some constructions, regardless of the method of sealing, the cell 10 is still able to vent excess gases and does not modify or alter vent pressure/characteristics of the current interrupt device (CID) or pressure relief device. In the example of an adhesive seal 34, the adhesive may be weak enough (e.g., have a strength

of, for example, less than 20 kg/cm²) to allow gases to escape. In the example of a seal 30 (e.g., a rubber), the seal may be flexible enough to allow gas to escape.

[0158] As shown in FIG. 25, a battery cell 10 may include a mechanical connection feature 188 in place of the weld surface on the positive battery terminal 14. The feature 188 may include a projection, a threaded fastener, a rivet hole, etc. Such a feature 188 may provide a robust mechanical connection while facilitating connection of the seal, gasket, etc. to the cell header for ingress prevention.

[0159] As shown in FIGS. 26A-26B, a Low Pressure Molding (LPM) process, with polyamide, polyolefin (hot-melt), potting compound, etc., material 192, may encapsulate the cell core 104 to environmentally protect the battery cells 10. The material 192 may inhibit or prevent fluid ingress to the cell headers 26, alone or along with the conductive straps 42. As shown in FIG. 26A, if the material 192 is added before welding, holes 194 added in the material may allow welding of the cell headers 26 to the straps 42.

[0160] In some embodiments, a coating (e.g., a rubberized coating) may be applied to the cell core 104 (e.g., to both sides), after the straps 42 have been welded to the cells 10. Such a coating will completely seal both ends of every cell 10, thereby preventing fluid from contacting any exposed conductive material (e.g., metal) on the cells 10. The coating may be applied by, for example, spraying, dipping, etc. The coating may include a hydrophobic or hydro-resistant material. In some embodiments, the entire cell core 104 may be coated after welding of the straps and the cells.

[0161] The coating material generally should not interfere with the venting features of the cells and should be electrically non-conductive. In addition, the coating material should bond to the materials in the cell core and produce a water tight seal. A wide range of materials may be suitable for the coating. Example materials include polyurethane, FKM fluoroelastomers, ethylene propylene diene monomer (M-class) rubber (EPDM), nitrile, silicone, and combinations thereof. In a specific example, a flexible rubber coating may be applied as a liquid and then dry to a low durometer rubber. Such a coating may be similar to LeakSeal® flexible rubber coating, manufactured by Rust-oleum Corporation, Vernon Hills, Illinois, United States of America.

[0162] In some constructions (see FIGS. 27A-27B), the battery pack 100 may include side housings 196, rather than a bottom housing 112. A seal or sealing material 200 may be provided and compressed between the cell core 104 and the side housings 196. For example, the seal 200 may be similar to the seal 144 between the upper and lower housing portions shown in FIG. 20J. As another example, the seal 200 may be similar to the gaskets 30 shown in FIGS. 11-12 and may be placed between the core housing 38 and the side housings 196. As with the gaskets 30 described above with respect to FIGS. 11-12, the gaskets 30 may be insert-molded or over-molded to and formed integrally with the core housing 38 and be oriented to be between the core housing 38 and the side housings 196. In yet another example, sealing material (e.g., sealing foam) may be introduced between the cell core 104 and the side housings 196.

[0163] In some constructions (not shown), an existing, un-sealed battery pack 100 may be enclosed or sealed. A separate cover, cap or similar device may encompass or cover the un-sealed portion(s) of the existing battery pack

100 to inhibit or prevent certain levels of fluid ingress into the pack **100**. The sealing device may be flexible, rigid or combinations thereof.

[0164] As an example, a boot (e.g., a flexible rubber boot) may be assembled to the battery pack housing **108** to seal one or more drain holes, cover mechanical interface portions, buttons, close and seal the terminal gaps (at least at that portion), etc. Upon engagement with the battery pack **100**, the tool terminals (e.g., the male terminals) would push open the gaps to reach the battery pack terminals. As another example, a rigid housing could also be used to cover the drain holes only or be combined with a more flexible upper portion.

[0165] FIGS. 28A-28C illustrate a battery pack **100** sealed with an electrical device **204**, such as a power tool, an outdoor tool, etc. The battery pack **100** may be partially sealed and be fully sealed when engaged with the electrical device **204** or a sealing cap. As shown in FIG. 28A, a gasket or sealing device **208** is provided on the electrical device **204** interface, and, when the electrical device **204** engages the battery pack **100**, the interface is fully sealed. In other constructions, an insert may seal the electrical device **204** from the battery pack **100**.

[0166] FIGS. 29A-29B illustrate a battery pack **100** with an adjustable (e.g., movable, slidable, etc.) sealing device **212**. When the battery pack **100** is disengaged from an electrical device **204**, the sealing device **212** is in the sealed condition. When the battery pack **100** is installed on an electrical device **204**, the sealing device **204** is in the unsealed condition (e.g., moved out of the sealed condition, the seal is broken or bypassed, etc.). When the battery pack **100** is removed, the sealing device **212** may again be in the sealed condition (e.g., move or return to the sealed condition).

[0167] FIGS. 30A-30B illustrate sealed battery cells **10**. Each cell **10** is individually sealed or encased in an ingress-proof or ingress-resistant housing or material **216**. Because each cell **10** is sealed, a separate sealing arrangement for the cell core **104** or the battery pack **100** may not be required.

[0168] As mentioned above, as shown in FIGS. 31A-31B, in some constructions, the conductive straps **42** can be welded through the seal **34**, without an opening required for access to the cell terminal. For example, an adhesive seal **34** is positioned over the end of the cell **10**. The seal **34** is directly welded through resistance or laser welding of the conductive strap **42** and the cell terminal.

[0169] FIG. 32 generally illustrates a gasket **220** integrated into the cell structure itself. As shown in FIG. 32, the gasket **220** wraps around the header cap **26** and the weld plate **224** to isolate the positive components from the negative can **228**. In FIG. 32, the angled lines illustrate the CID **232**, and the dashed line illustrates a mechanical vent plate **236**.

[0170] In some embodiment, the vent plate **236** of the cell **10** could be made to be highly corrodible, such that, in the presence of conductive fluid or material (e.g., sea water), the vent plate would corrode to disable the battery pack **100** rather than the battery pack **100** experiencing a short circuit.

[0171] The CID **232** connects the weld plate to the positive terminal **14**, and, with an increased cell pressure, the CID **232** may break (e.g., typically at about 10 kg/cm²), disabling the cell **10**. The mechanical vent plate **236** is a

backup to the CID **232** and may break if the rise in pressure is very rapid and quickly reaches its breaking threshold (e.g., typically about 20 kg/cm²).

[0172] It should be understood that, as mentioned above, in some embodiments, the seals, gaskets, etc., described above, that prevent fluid ingress may have a strength that is, for example, less than approximately 20 kg/cm² (e.g., below the breaking threshold of the mechanical vent plate) to, as described above, allow venting of the battery cells **10** (i.e., gases are able to vent out of the battery cells **10**/battery pack **100** through the seals, gaskets, etc. even though the seals, gaskets, etc. prevent ingress fluid from entering the battery pack **100**). In other embodiments, the seals, gaskets, etc. may have a strength less than a different value (e.g., less than about 10 kg/cm², the breaking threshold of the CID **232**).

[0173] As described above, each battery cell **10** may have a nominal voltage between about 3 volts (V) and about 5 V and may have a nominal capacity between about 3 Amp-hours (Ah) and about 5 Ah or more (e.g., up to about 9 Ah). The battery cells **10** may be any rechargeable battery cell chemistry type, such as, for example, lithium (Li), lithium-ion (Li-ion), other lithium-based chemistry, nickel-cadmium (NiCd), nickel-metal hydride (NiMH), etc.

[0174] FIGS. 33A-33B illustrate a strap routing technique, for example, used in a battery pack with 20 series-connected cells (20S1P) **100**. FIG. 33A illustrates a left side of the battery pack **100** showing straps **240** connecting battery cells **10** to each other or to weld joints **244**. Similarly, FIG. 33B illustrates a right side of the battery pack **100** showing straps **240** connecting battery cells **10** to each other and to the weld joints **244**.

[0175] In the illustrated construction, a voltage differential exists between each strap **240**. FIGS. 34A-34B illustrate voltage differentials between adjacent pairs of straps **240** and weld joints **244**. In the illustrated example, the maximum voltage differential between adjacent pairs of straps **240** is shown in white and circled. As illustrated, the maximum voltage differential between adjacent pairs of straps is about 16.8 V.

[0176] FIGS. 35-36 illustrate an alternative strap routing technique, for example, used in the 20S1P pack **100**. FIGS. 35-36 illustrate a right side of the battery pack **100** showing straps **240** connecting battery cells **10** to each other. Referring to FIG. 36, orientation and connection of straps **240** on the right side are shown in solid lines, and the orientation and connection of straps **240** on the left side are shown in dashed lines. In the illustrated embodiment, a consistent voltage differential of about 8.4 V is provided between most of the straps **240**. The straps **240** at one end of the battery pack **100** (e.g., at the top right hand corner in FIG. 36) have the maximum voltage differential of 16.8 V.

[0177] FIG. 37 illustrates an alternative construction of a battery pack **100** and a strap routing technique, for example, used in the 20S1P pack. FIG. 37 illustrates a right side of the battery pack **100** showing straps **240** connecting battery cells **10** to each other in solid lines; the orientation and connection of straps **240** on the left side are shown in dashed lines. In the illustrated embodiment, two battery cells **100** from the top right hand corner (e.g., in the design shown in FIG. 36) are moved to the right (in FIG. 37) of the pack **100**. While the length of the pack **100** is extended when compared to the construction shown in FIGS. 33A-36, the battery pack **100**

of FIG. 37 provides a consistent voltage differential of about 8.4 V between all of the straps 240 connecting battery cells 10 to each other.

[0178] In some embodiments, in addition or in the alternative to seals (e.g., adhesive seals 34) provided in or on battery cells 10, sealing arrangements may also be provided on the core housing 38 to provide ingress protection to straps 240 connecting battery cells 10. FIGS. 38-39 illustrate core seals 248 having different configurations. Similar to the adhesive seal 34 for the battery cells 10, the core seal 248 may include a sticker, a tape, an adhesive backed rubber, etc. The core seal 248 creates a seal to keep fluid (e.g., water) from contacting straps 240 and thus preventing bridging. The core seal 248 may be placed over each side of the cell core 104. In some embodiments, the voltage taps 252 of the core housing 38 may be provided outside the core seal 248. Similar adhesive seals may be used in other locations of the battery pack 100 to seal other components.

[0179] In some embodiments, the adhesive seal 34 and the core seal 248 may not be welded through (e.g., to weld conductive straps to battery cell terminals), and, in such constructions, welding is completed before each seal is installed. In other embodiments, the adhesive seal 34 may be welded through, and the core seal 248 may be added on top of the welded strap 240. Any exposed cell taps may be covered in glue. In yet another embodiment, both the adhesive seal 34 and the core seal 248 may be welded through (e.g., simultaneously). The exposed cells taps may be optionally covered with glue.

[0180] In some embodiments, drain holes 256 may be provided in the core housing 38 of the battery pack 100 to allow fluid to drain. FIGS. 40A-40B illustrate drain holes 256 in the core housing 38. The drain holes 256 may be added at the appropriate location (e.g., in the middle portion of the core) to promote and/or allow fluid to drain between cell bodies and away from the cell electrode area.

[0181] In some embodiments (see FIGS. 41A-41B), a potting or conformal coating material 260 may be applied to sides of the cell core 104 (e.g., to the core shown in FIG. 33B). The conformal coating 260 keeps fluid away from straps 240. However, in some embodiments, the voltage taps 252 may still be exposed for soldering. Conformal coating 260 may also be used for other components of the battery pack 100. Commercially available material such as silicone or other materials marketed and sold by ShinEtsu may be used for conformal coating 260.

[0182] The silicone conformal coating 260 may have a dielectric breakdown strength between about 8 Volt/micron (V/ μ m) to about 30 V/ μ m.

[0183] In some embodiments, as an alternative or in addition to the conformal coating 260, other sealing arrangements, etc., a vapor-deposited film or coating 264 may be applied to the components of the battery pack 100 (see FIGS. 44-45E illustrating vapor-deposited coating of battery pack electronics). Such battery packs 100 are generally high power constructions (e.g., greater than 12 V) in contrast to typical low power usages (e.g., cell phones) in which nano coatings have been employed.

[0184] As described above, the spacing between conductive components (e.g., the weld straps 140, the conductive straps 42, etc.) may be increased. In some embodiments, the vapor-deposited coating 264 may be used in combination with the above-described spacing of conductive components in the battery pack 100 to, for example, reduce the likelihood

of a short circuit when conductive fluid enters the battery pack 100. The vapor-deposited coating 264 may provide an effective electrical spacing between conductive components greater than the actual spacing between such components.

[0185] In general, vapor-deposited coatings are vapor-deposited layers (e.g., with a fluorinated chemistry). The vapor-deposited coating 264 may be a hydrophobic or hydro-resistant material making the substrate upon which the coating 264 is deposited, fluid repellant or resistant. The vapor-deposited coating 264 may be applied to all components of the battery pack 100 (generally excluding the outer housing) to inhibit or prevent fluid ingress generally and/or into gap areas. For example, the cell core 104, the electronics and the terminal block 176 may be nano coated. Vapor-deposited coating allows for uniform thickness on all surfaces.

[0186] Commercially available material, such as parylene, marketed and sold by Diamon MT, or other materials marketed and sold by P2i, Liquipel, etc., may be used for the vapor-deposited coating 264. Parylene refers to a family of chemical vapor-deposited poly(p-xylylene) polymers used as moisture and dielectric barriers. The vapor-deposited coating 264 may include parylene N, C, D, F, combinations thereof.

[0187] As shown in Table 1, below, parylene provides chemical resistance (measured as swelling of the film or coating) to various acids and other common chemicals that would otherwise severely corrode electronics. Due to the vapor-deposited coating 264, the battery pack 100 may have a similar corrosive resistance. The information in the below table and additional information on parylene is available at <https://vsparylene.com/parylene-advantages/properties/>, VSI Parylene, Broomfield, CO, the entire contents of which is hereby incorporated by reference.

TABLE 1

Inorganic Reagents	% Swelling	
	Parylene C	Parylene N
10% Hydrochloric (Non-Oxidizing Acid)	0.0% at 25° C. 0.0% at 75° C.	0.0% at 25° C. 0.0% at 75° C.
37% Hydrochloric (Non-Oxidizing Acid)	0.0% at 25° C. 4.1% at 75° C.	0.2% at 25° C. 2.3% at 75° C.
10% Sulfuric (Non-Oxidizing Acid)	0.3% at 25° C. 0.2% at 75° C.	0.1% at 25° C. 0.2% at 75° C.
95-98% Sulfuric (Non-Oxidizing Acid)	0.4% at 25° C. 5.1% at 75° C.	0.2% at 25° C. 5.3% at 75° C.
10% Nitric (Oxidizing Acid)	0.1% at 25° C. 0.1% at 75° C.	0.1% at 25° C. 0.2% at 75° C.
71% Nitric (Oxidizing Acid)	0.2% at 25° C. 1.85% at 75° C.	0.2% at 25° C. Became Brittle at 75° C.
10% Chromic (Oxidizing Acid)	0.1% at 25° C. 0.0% at 75° C.	0.1% at 25° C. 1.2% at 75° C.
74% Chromic (Oxidizing Acid)	0.0% at 25° C. 7.8% at 75° C.	0.3% at 25° C. 8.2% at 75° C.
10% Sodium Hydroxide (Base)	0.0% at 25° C. 0.5% at 75° C.	0.1% at 25° C. 0.0% at 75° C.
10% Ammonium Hydroxide (Base)	0.2% at 25° C. 0.4% at 75° C.	0.3% at 25° C. 0.4% at 75° C.
100% De-Ionized Water (Inert)	0.0% at 25° C. 0.0% at 75° C.	0.0% at 25° C. 0.0% at 75° C.
Organic Solvents	Parylene C	Parylene N
Isopropyl (Alcohol)	0.1% at 25° C. 0.2% at 75° C.	0.3% at 25° C. 0.3% at 75° C.
Iso-Octane (Aliphatic)	0.4% at 25° C.	0.2% at 25° C.

TABLE 1-continued

Hydrocarbon)	0.5% at 75° C.	0.3% at 75° C.
Pyridene (Amine)	0.5% at 25° C.	0.2% at 25° C.
	0.7% at 75° C.	0.4% at 75° C.
Xylene (Mixed)	2.3% at 25° C.	1.4% at 25° C.
	3.3% at 75° C.	2.1% at 75° C.
Trichloroethylene (TCE)	0.8% at 25° C.	0.5% at 25° C.
	0.9% at 75° C.	0.7% at 75° C.
Chlorobenzene (Chlorinated Aromatic)	1.5% at 25° C.	1.1% at 25° C.
	2.0% at 75° C.	1.7% at 75° C.
O-Dichlorobenzene (Chlorinated Aromatic)	3.0% at 25° C.	0.2% at 25° C.
	1.4% at 75° C.	0.3% at 75° C.
Trichlorotrifluoroethane (Fluorocarbon)	0.2% at 25° C.	0.2% at 25° C.
	0.3% at 75° C.	0.2% at 75° C.
Acetone (Ketone)	0.9% at 25° C.	0.3% at 25° C.
	0.9% at 75° C.	0.4% at 75° C.
2,4-Pentanedione (Ketone)	1.2% at 25° C.	0.6% at 25° C.
	1.8% at 75° C.	0.7% at 75° C.

[0188] In some constructions, the vapor-deposited coating 264 may have corrosive resistance comparable to polypropylene (PP) or polybutylene terephthalate (PBT) material. The vapor-deposited coating 264 may eliminate the need to use special materials for individual parts if the entire assembly is coated. The vapor-deposited coating 264 also facilitates the use of materials/constructions (e.g., a copper stamping) which may otherwise not be suitable due to potential for corrosion.

[0189] Some vapor-deposited coating materials (e.g., parylene with low adhesion and high cohesion) may degrade when exposed to UV light or due to abrasion. In order to inhibit such degradation, a cover (e.g., the outer housing or portions of the housing covering the vapor-deposited coating) formed of UV-rated plastic, such as acrylic, polytetrafluoroethylene (PTFE), Polyvinylidene Fluoride (PVDF), etc., may provide UV protection to the coating 264. In the illustrated constructions, the outer housing 108 provides a UV-protected enclosure for the vapor-deposited coating 264 and the coated components.

[0190] In some embodiments, a portion of the core housing 38 may be exposed through the battery pack housing 108. For example, a bottom portion of the core housing 38 may be exposed through the core housing 38, for example, to reduce the size of the battery pack 100. However, in such a construction, a vapor-deposited coating on the exposed surface may be at risk for abrasion, exposure to damaging UV light, etc. The exposed vapor-deposited coating 264 may wear and flake, and such wear may expand and peel into the interior surfaces of the cell core 104.

[0191] To inhibit or prevent such occurrences, in some constructions, the exposed surface of the core housing 38 may be masked during coating such that there is no vapor-deposited coating on the exposed surface. In some constructions, the exposed surface, including edges and sides, may have an increased surface roughness (e.g., be roughened before application of the vapor-deposited coating 264); the roughened surface may inhibit peeling of the vapor-deposited coating 264 from the exposed surface from spreading to covered surfaces of the core housing 38.

[0192] In some constructions, the vapor-deposited coating 264 may be doped with other materials to improve UV performance (i.e., resistance to UV light) of the vapor-deposited coating 264.

[0193] In some constructions, the core housing 38 may include a housing portion supporting the battery cells and to which the vapor-deposited coating 264 is applied. A bottom

housing portion including the exposed surface may be attached to the rest of the core 104 after the vapor-deposited coating 264 is applied.

[0194] The above techniques may also be used in battery packs 100 in which the core housing 38 is not exposed to promote adhesion and/or durability. The above techniques may be used in battery packs 100 having top and bottom housings, clamshell-style housings, etc.

[0195] The battery pack 100 may have a non-conductive bottom layer (e.g., plastic). If the bottom of the battery pack 100 was not non-conductive plastic, the pack 100 would be much harder to protect and difficult to fixture for chamber placement.

[0196] In some embodiments, only the circuit board 156 may be coated with the vapor-deposited coating 264 with the cell taps and straps 240 exposed. In one example, a layer of coating 264 of about 1 micron (μm) to about 20 μm or more (e.g., 22 μm) may be used to coat the components. A coating of these dimensions may prevent any penetration of fluids, provide structural strength/resistance from deterioration (e.g., during drops or rough handling), etc. In other embodiments, the layer of coating 264 may be thinner (e.g., between about 5 μm and about 15 μm ; between about 1 μm and about 8 μm (e.g., about 6 μm), etc.). In still other embodiments, the layer of coating 264 may be even thinner (e.g., between about 100 nanometer (nm) and about 1,000 nm, between about 10 nm to about 30 nm, etc.).

[0197] In addition, a geometry of the battery pack 100 may be altered using the vapor-deposited coating 264. For example, the vapor-deposited coating 264 may be provided such that a slope is formed on electrical components (e.g., the electronics) promoting run-off of fluids to drain areas (e.g., drain holes) and/or away from such components or cells. The sloping may also provide for a coating of sufficient thickness, even at the thinnest location.

[0198] In some constructions, the vapor-deposited coating 264 may be applied to a terminal member. For example, FIG. 45D illustrates a crab claw terminal with a vapor-deposited coating 264. In such a construction, the two facing sides of the contacts protect each other from the non-conductive dielectric coating thereby maintaining electrical conductivity of the protected contact portions after coating. Accordingly, these contacts do not need to be masked for coating, reducing time and cost. In other constructions (not shown), a terminal without a protecting structure (e.g., a male terminal) may have a vapor-deposited coating 264, and, in such constructions, contact portions may be masked or protected before coating.

[0199] For components subject to multiple insertions/removals (e.g., terminals), protective material (e.g., grease) may be applied to the coating. Using uniform heat transfer materials (e.g., copper, etc.) may provide improved maintenance of the vapor-deposited coating 264. In contrast, non-uniform or multiple material components, may contribute to the coating breaking down, being brittle, melting.

[0200] FIG. 45E illustrates another component, a button 268 (e.g., a sealed “popple dome” style button, for example, for a state-of-charge (SOC) indicator) coated with a vapor-deposited coating 264. The illustrated sealed switch design allows for coating without costly masking with the seal protecting the internal components from the coating.

[0201] In some constructions (see FIGS. 46A-46B), substantially the entire battery pack assembly 100 (including

electronic components), other than the outer housing 108, is coated with a vapor-deposited coating 264.

[0202] The vapor-deposited coating 264 may be susceptible to abrasion. As shown in FIG. 46A, the cell module housing 38 includes a standoff 272 to prevent or inhibit abrasion of the coating by the outer housing walls, for example, by minimizing an area of engagement during assembly (e.g., insertion) and/or via drop, impact, vibration, etc. The illustrated cell module construction (see FIGS. 46A-46B) allows for safe insertion of the coated pack into the outer housings 108 without damaging coating 264. The standoff 272 (e.g., an S-shaped rib between the straps, as illustrated) is proud of the conductive straps 42, allowing the cell core 104 to be inserted without or with a reduced risk of scratching coating on the straps 42, other components, etc. The standoff 272 may also help application of the coating 264 to the straps 42. If the coating 264 on the standoff 272 (e.g., the ribs) itself is scratched during insertion, this is not an issue because the cell module housing is non-conductive plastic.

[0203] In other constructions (not shown), individual battery cells 10 may be coated with a vapor-deposited coating 264, for example, to at least prevent fluid (water) ingress into the cell header 26. While welding of the conductive strap 42 may remove some coating material from the coated cell 10, ingress prevention performance is still improved. With the vapor-deposited coating 264, a washer normally used to hold the cell sleeve may not be required.

[0204] The material of the coating 264 may be transparent or translucent to allow visibility of components of the coated cell (e.g., the sleeve). The material of the coating 264 may be tinted or colored as desired or required. The material of the coating 264 may allow for printing, coloring, etc., on the outer surface of the material without impeding performance of the material.

[0205] In some constructions, the vapor-deposited coating 264 may replace the cell sleeve. In some constructions, the conductive cell can provides a conductive portion of the battery cell 10 (e.g., the negative terminal). The coating 264 may cover and insulate at least portions of the can (e.g., exposed conductive portions of the can).

[0206] In the illustrated construction, each cell 10 is able to vent, if necessary, for example, for protection of the cell 10, the battery pack 100, etc. The vapor-deposited coating material has a construction (e.g., thickness) to provide desired ingress prevention, durability, etc., while allowing cell venting. Further, for cells 10 with a current interrupt device (CID) 232, the coating 264 does not affect performance of the CID 232 which is internal to the cell 10.

[0207] In some constructions, the coating 264 may be applied to the cell header 26. In such constructions, the coating 264 has a construction to provide desired ingress prevention, durability, etc. while allowing cell venting, operation of the CID 232, etc. and without inhibiting performance of the cell 10. The coating material has a thickness such that the coating 264 does not affect heat transfer of the cells 10—the thermal conductivity of the coating 264 is negligible, and the coating 264 does not insulate/has similar properties to air.

[0208] In some constructions, the vapor-deposited coating 264 has a thickness of between about 1 micron (μm) and about 20 μm or more. In some constructions, the thickness of the vapor-deposited coating 264 is between about 5 μm and about 15 μm . In some constructions, the thickness of the

vapor-deposited coating 264 is between about 1 μm and about 8 μm (e.g., about 6 μm). In some constructions, the vapor-deposited coating 264 has a thickness of between about 10 μm and about 22 μm (e.g., less than about 22 μm for a fuel gauge button).

[0209] The vapor-deposited coating 264 may provide improved insulation of conductive parts. With the resulting insulation, voltage potentials and spacings between conductive components can be reduced, thereby reducing the size of the coated components (e.g., the cell module) and the overall assembly (e.g., the battery pack). The coating 264 may facilitate reducing the size of the battery pack 100 while still allowing sufficient fluid drainage/resistance to fluid intrusion or shorting.

[0210] The spacings are voltage dependent and may be about 0.8 mm up to about 15 V; about 1.5 mm up to about 32 V; about 2.0 mm creepage and about 1.5 mm clearance up to about 60 V; about 2.5 mm creepage and about 1.5 mm clearance up to about 130 V. Clearance is the shortest distance through air between two conductive parts, and creepage is the shortest distance between two conductive parts along a surface of any insulating material common to both parts. The vapor-deposited coating 264 may provide comparable performance when applied to components of AC products.

[0211] With the vapor-deposited coating 264 and using a non-sealed outer housing 108, the battery pack 100 is at least dust protected such that, while ingress of dust is not entirely prevented, dust does not enter in sufficient quantity to interfere with the operation of the battery pack 100 with complete protection against contact. Likewise, the battery pack 100 will have liquid protection at least against water projected in powerful jets (12.5 mm nozzles) against the outer housing 108 from any direction with no harmful effects.

[0212] In some constructions, with the vapor-deposited coating 264, the battery pack 100 may be dust tight such that there is no ingress of dust with complete protection against contact. The battery pack 100 will have liquid protection for long-term immersion beyond 1 m—for continuous immersion in water under specified conditions which may mean that the battery pack 100 is equivalent to being hermetically sealed or that water can enter but only in such a manner that the produces no harmful effects.

[0213] Unsealed battery packs without nano coated components may immediately react when immersed in a tank of water. In contrast, when tested, the unsealed battery packs 100 with nano coated components remain functional (e.g., with a working fuel gauge) from about 10 seconds up to and beyond 24 hours of immersion. The battery pack 100 may withstand up to about 75° C. in the presence of liquid. The vapor-deposited coating material (e.g., parylene) will typically withstand at least this temperature and higher temperatures without degrading.

[0214] A high operating temperature of the battery cells of the battery pack 100 is between about 50° C. and about 110° C. In some constructions, when the vapor-deposited coating 264 includes parylene C or parylene N, which each provide good thermal properties, the cell core 104 and the battery pack 100 can withstand continuous exposure to temperatures up to between about 75° C. and about 85° C. (about 80° C.) and short-term exposure of up to between about 90° C. and about 100° C. (about 95° C.).

[0215] Other parylene vapor-deposited coatings 264 may withstand continuous exposure up to 100° C., 200° C., or 350° C. In some embodiments, the cell core 104 with the vapor-deposited coating 264 may withstand continuous exposure to temperatures up to 80° C., 100° C., 120° C., 150° C., 200° C., 250° C., 300° C., or 350° C.

[0216] The parylene vapor-deposited coating 264 has a dielectric breakdown strength between 200 Volts/micron (V/μm) and 300 V/μm. For a coating with a thickness 6 μm, the vapor-deposited coating 264 can withstand between 1200 V and 1800 V before breakdown. In some embodiments, the vapor-deposited coating 264 has a dielectric breakdown strength of up to 200 V/μm, 250 V/μm, or 300 V/μm. Generally, parylene N and parylene F have a higher dielectric breakdown strength than parylene C.

[0217] In some constructions, the vapor-deposited coating 264 may be used in combination with polycarbonate (PC)/plastic.

[0218] Battery packs 100 having cells with lithium-ion chemistry may be subject to shipping regulations. Such shipping regulations may limit the voltage and/or power capacity of the battery pack being shipped. In order to comply with such regulations, battery packs 100 may be shipped with subcores of the battery cells 10 disconnected from each other. In other constructions, a battery pack may include battery cells 10 which are selectively connectable in different configurations (e.g., series, parallel, combination series-parallel, etc.) to provide different selected output capabilities (e.g., nominal voltage, capacity, etc.) for the battery pack.

[0219] The battery pack 100 may include a switch 1315 (see FIGS. 48A-48E) which selectively connects the battery cell 10/subcores together when the battery pack 100 is in use and/or in the selected configuration for use. A similar switch and switching arrangement is described and illustrated in U.S. Provisional Patent Application No. 62/435,453, filed Dec. 16, 2016, and in U.S. patent application Ser. No. 15/845,068, filed Dec. 18, 2017, the entire contents of both of which are hereby incorporated by reference.

[0220] The vapor-deposited coating 264 may be applied to portions of the switch 1315, leaving a minimum portion exposed for operation of the switch 1315 (e.g., only the tracks of the switch 1315 remain exposed instead of entire busbar). In some constructions, operational portions (e.g., the conductive portions) of the switch 1315 may be masked during application of the vapor-deposited coating 264. In some constructions, operational portions of the switch may be engaged during application of the coating 264, the engagement inhibiting application of the vapor-deposited coating 264 to the operational portions. After application of the coating 264, the switch 1315 may be operated a number of times (e.g., ten times) to, for example, confirm or ensure operation of the switch 1315 in its various positions.

[0221] The switch 1315 is configured to be in the first position (see FIG. 48A or 48D; e.g., disconnected or "OFF") and the second position (see FIG. 48B or 48E; e.g., connected or "ON"). The illustrated switch 1315 includes a shell 1500, terminals 605a, 605b, 605c, 605n, a conductive bus 1505, and a non-conductive layer 1510. The shell 1500 may include one or more recesses 1515, a front stop member 1520, and a rear stop member 1525.

[0222] As illustrated in FIGS. 48A-48B, in some embodiments, the conductive bus 1505 and non-conductive layer 1510 are coupled to the user-interface 1330 via a protective

member 1530 having one or more projections 1535 and forming an aperture 1540. The projections 1535 engage with the one or more recesses 1515 of the shell 1500 to prevent unwanted movement between the first and second positions. As illustrated in FIG. 48C, the conductive bus 1505 and the non-conductive layer 1510 may form a plate 1542. Although illustrated with the conductive bus 1505 having four conductive members 1544, in other embodiments, the conductive bus 1505 may have more or fewer conductive members 1544.

[0223] In the illustrated embodiment of FIG. 48C, the conductive members 1544 are approximately flush, or continuous, with the non-conductive layer 1510. Such an embodiment promotes movement of the terminals 605 between connection to the non-conductive layer 1510 and connection to the conductive members 1544 of the conductive bus 1505. In some embodiments, as illustrated in FIG. 48C, the conductive bus 1505 is formed of a continuous conductive material (for example, copper).

[0224] FIGS. 48D-48E illustrates the conductive bus 1505 and non-conductive layer 1510 electrically and/or physically connected to terminals 1546a, 1546b in another embodiment. Each illustrated terminal 1546 includes a first terminal portion 1548a and a second terminal portion 1548b connected via a bus bar 1549. In some embodiments, the bus bar 1549 provides a parallel connection between the terminal portions 1548a, 1548b, while reducing electrical resistance and heat generated via the connection of subcores.

[0225] As illustrated, each terminal portion 1548 includes an upper foot 640 and a lower foot 645, which are substantially similar to the upper and lower feet 640, 645 of terminal 605. Terminals 1546, including bus bar 1549, allow for a single electrical connection between a first plurality of subcores and a second plurality of subcores. In other embodiments, the terminal 1546 may include more than two terminal portions 1548.

[0226] As described above, the coating 264 may be applied when the switch 1315 is in the second position (see FIG. 48B or 48E; e.g., connected or "ON"). Engagement of the terminals 605a, 605b, 605c, . . . 605n with the conductive members 1544 inhibits application of the coating 264 to at least portions of the conductive members 1544 (e.g., at least operational portions of the conductive members 1544 to be engaged by the respective terminals 605 in the second position).

[0227] In other constructions (not shown), the switch 1315 may have a first position corresponding to a first operational configuration (e.g., a nominal voltage about 20 V and a capacity of about 4 Ah) and a second position corresponding to a second operational configuration (e.g., a nominal voltage of about 40 V and a capacity of about 2 Ah). The switch 1315 may include additional positions (e.g., an additional operation configuration, a non-operational configuration (e.g., "OFF"), etc.).

[0228] With the vapor-deposited coating 264, components (e.g., the coding header, the tall 4-pin connector (see FIG. 45C), etc.) of the pack electronics which are normally removed (e.g., at the factory) before shipping, sale or use, for example, to prevent shorting may remain installed, reducing labor cost for removal.

[0229] A metal housing/core may be provided around a pack to compress/coat to avoid abrasion and provide good heat sinking. In some constructions, there may be ultrasonic fixturing of components while being coated.

[0230] The vapor-deposited coating 264 provides another layer of insulation on conductive components to help prevent electrostatic discharge (ESD) between components inside the pack 100. The coating 264 could also provide a benefit in high voltage field environments (e.g., near power lines), as voltage arcs tend to concentrate on corners or sharp-edged components. The coating 264 can provide insulation on those edges.

[0231] In some constructions, the vapor-deposited coating 264 may be applied to a heat sink, facilitating the elimination or reduction of insulating material. This may also allow the removal or reduction of any gap such that the heat sink is mounted directly to improve thermal transfer and reduce cost (i.e., less expensive anodization). The heat sink (and other coated components) may be coated before and after assembly to provide the desired coating characteristics and performance.

[0232] In some constructions, such as for lighting applications, the vapor-deposited coating 264 may be applied to control electronics while allowing greater airflow. The coating 264 may be applied to LED boards, eliminating the need for a sealed compartment (e.g., via gaskets).

[0233] In some constructions, a vapor-deposited coating 264 may be applied to components of a Bluetooth® low energy (BLE) module. The vapor-deposited coating 264 does not interfere with operation, range of the BLE module when compared to a conformal coating. FIG. 47 illustrates a tracking device 274 including a BLE module. Components of the device may be coated such that additional seals (e.g., an o-ring) are not required while maintaining performance of the components. A similar tracking device is described and illustrated in U.S. Provisional Patent Application No. 62/592,181, filed Nov. 29, 2017, the entire contents of which are hereby incorporated by reference.

[0234] In some constructions, use of a vapor-deposited coating 264 may eliminate the need for potting of electronics, depending on structural/thermal needs of the components. While the structure of the potting boat may be retained, the potting material may be eliminated or reduced to the amount needed to help dissipate heat.

[0235] The battery pack 100 assembly process may be as follows: An adhesive label/seal 34, if necessary, may be applied to each cell header 26. The cells 10 are then installed into the cell module frame 38, and fasteners are installed to the frame. The conductive straps 42 are assembled on the frame and welded (e.g., resistance welded) to the cell contacts. The electronics, including the PCB 156, are installed and welded and soldered to provide the necessary electrical connections. After welding and soldering of the electronics, the vapor-deposited coating 264 is applied to the components of the assembled cell module. After coating, fasteners are installed to the bottom housing 112 and then to the top housing 116.

[0236] In some constructions, the vapor-deposited coating 264 may replace or eliminate the need for the adhesive label/seal 34 added to each cell 10. In some constructions, individual cells 10 may be coated with a vapor-deposited coating 264 before installation into the cell module frame 38, eliminating a need for a cell label or seal 34 to protect the cell header 26. In some constructions, the vapor-deposited coating 264 may be provided in addition to the seal/gasket 30 and/or the adhesive seal 34. In these constructions, the vapor-deposited coating 264 may provide a layer of ingress protection in addition to the gasket 30 and/or the

adhesive seal 34. The vapor-deposited coating 264 covers all exposed cell surfaces of the battery cell 10 including the gaskets 30 and the cell header portions 26.

[0237] In some constructions, individual conductive straps 42, weld straps 140, etc., may be coated with a vapor-deposited coating 264 to increase spacings between voltages. Resistance welding through the vapor-deposited coating 264 is possible if the coating (e.g., parylene) is thin enough (e.g., less than or equal to about 20 μm is suitable for welding without impacting operation of any related components (for example, the fuel gauge button)), and, while this may expose the voltage potential at the weld joint, the overall strap-to-strap effective electrical spacing would increase.

[0238] In some constructions, the vapor-deposited coating 264 (e.g., parylene) is applied to coat the battery PCBA 156. The coating 264 provides uniform coating coverage over complex geometries (differences between components, different shapes (e.g., cylinder, rectangular prism, complex polygon, etc.), multiple stacked components, etc.), such as a sense resistor, a tall capacitor, a large resistor, toroid-shaped large inductor, etc.

[0239] In some constructions, motor components may include a vapor-deposited coating 264. For example, a vapor-deposited coating 264 may be applied to the stator laminations which may reduce/adjust (increase) natural resonant frequencies (e.g., due to a change in mass).

[0240] As another example, motor magnets (e.g., sintered primary magnets, sense magnets, etc.) may include a vapor-deposited coating 264. Such a coating may improve the strength of the magnet (e.g., a ferrite sense magnet which may otherwise be very brittle and can fall out if cracked/broken). With respect to a primary magnet, the vapor-deposited coating 264 may replace the nickel-copper-nickel coating which is provided to inhibit rust, reducing the cost. The vapor-deposited coating 264 may also improve adhesion to glue compared to the nickel coating. The magnets may be coated in place after insertion, a potential cost saving. The coating process may allow bulk coating of magnets when un-magnetized.

[0241] The vapor-deposited coating 264 may be applied to winding leads. The coating 264 may reduce breakage on tang leads of small winding wires.

[0242] In some constructions, the vapor-deposited coating 264 may replace a slot liner paper/dielectric in the stator. Generally, the paper is an insulator and does not transfer heat well. In contrast, with certain properties, the vapor-deposited coating 264 could improve heat transfer from the coil to the stator. The vapor-deposited coating 264 may also replace the tape, minimizing spacings between the magnet wire, rotor, and stator. The vapor-deposited coating 264 may help prevent build-up of dust, debris, metal, etc., in coated motor components.

[0243] In some constructions, the vapor-deposited coating 264 may be used to strengthen mounting of components. For example, the vapor-deposited coating 264 may be used to strengthen the mounting of electronic components to the PCBA substrate. A coating with a thickness of 6 μm or greater may improve the mounting between components.

[0244] In some constructions, the vapor-deposited coating 264 contains phase change materials around a battery cell 10. Phase change materials store and release large amounts of energy when the substance changes phase (e.g., freezes, melts, etc.). The phase change material is used to improve

thermal management, for example, heat dissipation during discharge of the battery pack 100.

[0245] The phase change material can be used in conjunction with parylene to form the vapor-deposited coating 264 to improve thermal management of the battery pack 100. Accordingly, the vapor-deposited coating 264 may be used instead of a sleeve or a wrapper around the battery cells 10 containing the phase change material.

[0246] In some constructions, one or more surfaces of the core housing 38 may be made of plastic or other non-conducting material. Using plastic or non-conducting material reduces or prevents the risk of potential short circuiting and allows the core housing 38 to be placed on metal fixtures during application of the vapor-deposited coating 264.

[0247] In some constructions, the application of the vapor-deposited coating 264 is performed to one or more at least partially charged battery cells 10. For example, the battery cell(s) 10 are charged to about 20% state of charge (SOC) before the vapor-deposited coating 264 is applied (e.g., directly to the cell(s) 10, to the cell core 104 after assembly of the cell(s) 10 into the core housing 38, etc.). In some constructions, the vapor-deposited coating 264 is applied to the battery cell(s) 10 that have been charged to at least about 10% SOC, about 20% SOC, about 25% SOC, about 30% SOC, or more. The battery cells 10 may be charged up to about 75% SOC or even about 100% SOC.

[0248] Battery packs 100 may include multiple series strings 276 of battery cells 10 connected in series or parallel to each other. Each series string 276 includes several battery cells 10 connected in series to each other. Each individual cell 10 of the battery packs 100 may be individually monitored by an analog front end (AFE) 280 as shown in FIG. 42.

[0249] A cell tap flex circuit 284 is used to connect the individual cells 10 to the AFE 280. As shown in FIG. 43, the cell tap flex circuit 284 includes cell taps 288 (shown on the circuit board with numerals 1-12) connected to individual cells 10 of the battery pack 100. In the illustrated construction of the cell tap flex circuit 284, all cell taps 288 are on one side of the battery pack 100; in other constructions (not shown), cell taps 288 may be on both sides of the battery pack 100. Traces 292 run from each cell tap 288 to a common connection point 296 to electrically connect the cells 10 to the connection point 296. The connection point 296 is connected to the AFE 280.

[0250] To apply the vapor-deposited coating 264, the PCB 156 is assembled onto the cell core 104 and placed into a chamber of a coating machine. The coating machine reduces the air pressure in the chamber and supplies vapor-deposited coating (e.g., parylene) in amorphous form to be applied to the contents of the chamber. The vapor-deposited coating 264 is then applied to every exposed surface of the cell core 104 and the PCB 156.

[0251] As can be seen in FIG. 43, the traces 292 may run very close to each other on the cell tap flex circuit 284. As such, the traces 292 may short-circuit in the presence of a conductive fluid. For example, conductive fluid or material (e.g., sea water) entering the battery pack 100 and onto the cell tap flex circuit 284 may short-circuit two or more of the traces 292.

[0252] When traces 292 short-circuit, the temperature of the circuit components (e.g., the cells 10, the traces 292, the connection point 296, etc.) may increase rapidly. The illustrated cell tap flex circuit 284 includes resistors 300 (shown on the circuit board with R1-R12) connected on the traces

292 between the cell taps 288 and the connection point 296. Each trace 292 includes at least one resistor 300. If and when a short-circuit occurs, the resistors 300 will break down and fault open, thereby opening the connection between the cell taps 288 and the connection point 296 to inhibit or prevent the battery pack 100 from overheating.

[0253] In some embodiments, the resistors 300 are replaced by positive thermal coefficient resistors/thermistors (PTCs). A PTC is characterized in that its resistance increases with increasing temperature. Accordingly, if and when a short circuit occurs, the PTCs increase their resistance, thereby preventing excess current through the traces 292. That is, rather than breaking down as the resistors 300 will do, PTCs increase their resistance with increasing temperature. This will inhibit or prevent the battery pack 100 from overheating while improving the servicing of the battery pack 100 as the circuit will be operable again once the short circuit condition is alleviated.

[0254] In some constructions, components in an electric power system (e.g., a battery pack 100, an electrical device 204 (a power tool, a charger, etc.)) and the associated components to be coated and/or otherwise sealed (e.g., an adhesive seal on the cell header, etc.) may be determined based on the use/application of the system. For example, if the system will be used in applications involving fluid (e.g., water delivery, plumbing, marine, etc.) or other contamination, relatively more components of the elements of the system may be coated or sealed compared to systems being used in applications not typically involving fluid, contaminants, etc.

[0255] FIGS. 49A-49C and 51A-51B illustrate several embodiments of a battery pack 100 operable to power cordless electrical devices (see FIGS. 50A-50B and 52; e.g., electrical devices, such as power tools, outdoors tools, other motorized devices, non-motorized devices, etc.).

[0256] Each battery pack 100 includes battery cells 10 having a nominal voltage (e.g., between about 3 volts (V) and about 5 V) and a nominal capacity (e.g., between about 3 Amp-hours (Ah) and about 5 Ah or more (e.g., up to about 9 Ah)). The battery cells 10 may be any rechargeable battery cell chemistry type, such as, for example, lithium (Li), lithium-ion (Li-ion), other lithium-based chemistry, nickel-cadmium (NiCd), nickel-metal hydride (NiMH), etc.

[0257] The battery pack 100 includes a number and arrangement of battery cells 10 to provide a desired output (e.g., nominal voltage, capacity, etc.). The battery pack 100 may have a nominal voltage of at least about 12 V up to about 100 V.

[0258] In FIGS. 49A-49C, the battery packs 100A-100C have a nominal voltage of between about 16 V and about 21 V, and the capacity of the battery pack 100A is about three times the capacity of the battery pack 100C (e.g., about 9 Ah compared to about 3 Ah). The battery pack 100A has an energy of between about 140 Watt-hours (Wh) and about 190 Wh, the battery pack 100B has an energy of between about 95 Wh and about 130 Wh, and the battery pack 100C has an energy of between about 45 Wh and about 65 Wh.

[0259] In FIGS. 51A-51B, the battery packs 100D-100E have a nominal voltage of between about 72 V and about 84 V, and the capacity of the battery pack 100E is about two times the capacity of the battery pack 100D (e.g., about 6 Ah compared to about 3 Ah). The battery pack 100D has an

energy of between about 215 Wh and about 255 Wh, and the battery pack **100E** has an energy of between about 430 Wh and about 505 Wh.

[0260] The high power battery pack **100** includes battery cells which are operable to output a sustained operating discharge current of between about 20 Amps (A) and about 130 A (e.g., between about 40 A and about 60 A, between about 60 A and 120 A, between about 80 A and about 110 A, etc.). The battery cells may be operable to output a peak discharge current up to about 200 A.

[0261] In FIGS. **49A-49C**, the battery packs **100A-100C** have an AC internal resistance (ACIR) within a range of approximately 18 milliohms to approximately 23 milliohms. The battery packs **100A-100C** have a DC internal resistance (DCIR) within a range of approximately 15 mΩ to approximately 25 mΩ. In some embodiments, the DCIR of the battery packs **100A-100C** is about 21 mΩ. In FIG. **51A**, the battery pack **100D** has an AC internal resistance (ACIR) within a range of approximately 150 mΩ to approximately 160 mΩ. The battery pack **100D** has a DC internal resistance within a range of approximately 220 mΩ to approximately 260 mΩ. In FIG. **51B**, the battery pack **100E** has an AC internal resistance (ACIR) within a range of approximately 75 mΩ to approximately 80 mΩ. The battery pack **100E** has a DC internal resistance within a range of approximately 130 mΩ to approximately 170 mΩ.

[0262] FIG. **49A** illustrates a battery pack **100A** having a “5S3P” configuration (three parallel-connected strings of five series-connected battery cells), FIG. **49B** illustrates a battery pack **100B** having a “5S2P” configuration (two parallel-connected strings of five series-connected battery cells), and FIG. **49C** illustrates a battery pack **100C** having a “5S1P” configuration (one string of five series-connected battery cells). Similar battery packs are described and illustrated in U.S. Provisional Patent Application Nos. 62/536,807, filed Jul. 25, 2017, and 62/570,828, filed Oct. 11, 2017, entitled “HIGH POWER BATTERY-POWERED SYSTEM,” the entire contents of both of which are hereby incorporated by reference.

[0263] FIGS. **50A-50B** illustrate high power electrical systems **1000**, **1100** including various high power electrical devices for use with the battery pack **100A-100C**. For example, the system **1000** includes motorized power tools (e.g., a circular saw (e.g., a worm drive saw **1010**), a reciprocating saw **1014**, a table saw **1018**, a miter saw **1022**, an angle grinder **1026**, a SDS Max hammer **1030**, a compressor **1034**, a vacuum **1038**, etc.), outdoor tools (e.g., a chain saw **1042**, a string trimmer, a hedge trimmer, a blower, a lawn mower, etc.), other motorized devices (e.g., vehicles, utility carts, off-road vehicles, recreational vehicles, etc.), etc. and non-motorized electrical devices (e.g., a power supply, a light **1046**, a testing device, an audio device **1050**, etc.).

[0264] The system **1100** of electrical devices operable to be powered by an existing battery pack **1104** or the high-power battery pack **100A-100C**. The illustrated electrical devices include various motorized power tools (e.g., a circular saw **1110**, a reciprocating saw **1114**, a grinder **1126**, a vacuum **1138**, a drill **1154**, a nailer **1158**, an impact driver/wrench **1162**, etc.), outdoor tools (e.g., a string trimmer **1166**, a hedge trimmer, a blower **1170**, etc.), etc. and non-motorized electrical devices (e.g., an audio device **1150**, a light **1174**, a testing device, etc.).

[0265] In some constructions, the battery pack **100** has a nominal voltage of up to about 20 V (e.g., about 18 V to about 20 V), and is operable to output only between about 1000 Watts (W) to about 1400 W at a current of between about 50 A to about 70 A. In some constructions, the battery pack **100** is operable to output high power (e.g., a peak power of about 1800 W to about 2400 W or more (2.4 horsepower (hp) to 3.0 hp or more)). In order to achieve this peak power, a high current (e.g., about 100 A or more) is discharged from the battery pack **100**, through the interconnections and components to which the vapor-deposited coating **264** is applied.

[0266] FIG. **51A** illustrates a battery pack **100D** having a “20S1P” configuration (one string of twenty series-connected cells), and FIG. **51B** illustrates a battery pack **100E** having a “20S2P” (two parallel-connected strings of twenty series-connected cells). Similar battery packs are described and illustrated in U.S. Provisional Patent Application No. 62/527,735, filed Jun. 30, 2017, entitled “HIGH POWER BATTERY-POWERED SYSTEM,” the entire contents of which are hereby incorporated by reference.

[0267] FIG. **52** illustrates a high power electrical system **1000** including various high power electrical devices for use with the battery packs **100D-100E**. For example, the system **1000** includes hand-held devices (i.e., devices configured to be supported by an operator during use) and non-hand-held devices (i.e., devices supported on a work surface or support rather than by the operator during use). Such devices include motorized power tools (e.g., a drill, an impact driver, an impact wrench, a rotary hammer, a hammer drill, a saw (a circular saw, a cut-off saw **1010**, a reciprocating saw, a miter saw **1014**, a table saw **1018**, etc.), a core drill **1022**, a breaker **1026**, a demolition hammer, a compressor **1030**, a pump, etc.), outdoor tools (e.g., a chain saw **1034**, a string trimmer, a hedge trimmer, a blower, a lawn mower, etc.), drain cleaning and plumbing tools, construction tools, concrete tools, other motorized devices (e.g., vehicles, utility carts, wheeled and/or self-propelled tools, etc.), etc. and non-motorized electrical devices (e.g., a power supply **1038**, a light **1042**, an AC/DC adapter **1046**, a generator, etc.).

[0268] In other constructions, the battery pack **100D-100E** has a nominal voltage of up to about 80 volts (V). In such constructions, the battery pack **100D-100E** is operable to output high power (e.g., power of about 2760 W to about 3000 W or more (3.7 horsepower (hp) to 4.0 hp or more)) for sustained durations (e.g., at least 5-6 minutes or more). In order to achieve this sustained power, a high sustained current (e.g., about 50 amps (A) or more) is discharged from the battery pack **100D-100E** through the interconnections and components to which the vapor-deposited coating **264** is applied.

[0269] FIGS. **53A-53E** illustrate an assembly process of the battery pack **100D**. The assembly is performed by supporting the battery cells **10** in the core housing **38** (as shown in FIG. **53A**). The conductive straps **42** are added to the battery cells **10** to connect the battery cells **10** in series or parallel (as shown in FIG. **53B**). The PCBA **156** is added to the core housing **38** (as shown in FIG. **53C**). The terminal block **176** may or may not be added in this step.

[0270] The core assembly **104** is then placed in the coating machine and the vapor-deposited coating **264** is performed as described above. Once the core assembly **104** is coated, the core seal **248** is added to the core housing **38** to seal the battery cells **10** (as shown in FIG. **53D**). The core seal **248**

includes cell voltage taps **252** extending outside of the core seal **248** for connection to the PCBA **156** and the terminal block **176**. The flex circuits **284** are then added to the core assembly **104** to couple the battery cells **10** to the PCBA **156** and the terminal block **176** (as shown in FIG. **53E**). The core assembly **104** is then placed in the battery pack housing **108** (as shown in FIG. **53F**).

[0271] In some embodiments, vapor-deposited coating may be performed after adding the seal **248** and/or the flex circuits **284**. In these embodiments, the terminal block **176** may be added before or after the vapor-deposited coating.

[0272] FIGS. **54A-54E** similarly illustrate an assembly process of the battery pack **100E**. The assembly is performed by supporting the battery cells **10** in the core housing **38** (as shown in FIG. **54A**). The conductive straps **42** are added to the battery cells **10** to connect the battery cells **10** in series or parallel (as shown in FIG. **54B**). The PCBA **156** is added to the core housing **38** (as shown in FIG. **54C**). The terminal block **176** may or may not be added in this step.

[0273] The core assembly **104** is then placed in the coating machine and the vapor-deposited coating is performed as described above. Once the core assembly **104** is coated, the core seal **248** is added to the core housing **38** to seal the battery cells **10** (as shown in FIG. **54D**). The core seal **248** includes cell voltage taps **252** extending outside of the core seal **248** for connection to the PCBA **156** and the terminal block **176**. The flex circuits **284** may then added to the core assembly **104** to couple the battery cells **10** to the PCBA **156** and the terminal block **176** (not shown). The core assembly **104** is then placed in the battery pack housing **108** (as shown in FIG. **54E**). In some embodiments, vapor-deposited coating may be performed after adding the seal **248** and/or the flex circuits **284**. In these embodiments, the terminal block **176** may be added before or after vapor-deposited coating.

[0274] Thus, the invention may provide, among other things, arrangements for inhibiting water intrusion into a battery cell **10** or cells **10** in a battery pack **100**. The arrangements may include a sealing arrangement for the battery cell **100** and/or structure of the battery pack **100** operating to inhibit water intrusion.

[0275] Although the invention has been described in detail with reference to certain preferred embodiments, variations and modifications exist within the scope and spirit of one or more independent aspects of the invention as described.

[0276] One or more independent features and/or independent advantages of the invention may be set forth in the claims:

What is claimed is:

1. A water-resistant battery pack comprising:

an outer housing;

a controller operable to control an operation of the battery pack;

a terminal operable to connect to an electrical device for power transfer; and

a cell module within the outer housing, the cell module including:

a module housing,

at least one battery cell supported by the module housing and including a cell header,

a water-resistant ring provided at the cell header, the water-resistant ring including an annular rib protruding in an axial direction of the at least one battery cell, and

a conductive element electrically connecting the at least one battery cell to at least one of the controller and the terminal.

2. The battery pack of claim 1, wherein the annular rib protrudes away from the at least one battery cell.

3. The battery pack of claim 1, wherein the annular rib extends about a radially outer edge of the water-resistant ring.

4. The battery pack of claim 1, wherein the annular rib extends about a radially inner edge of the water-resistant ring.

5. The battery pack of claim 1, wherein the annular rib is a first annular rib, and wherein the water-resistant ring further includes a second annular rib protruding in the axial direction and located radially inward from the first annular rib.

6. The battery pack of claim 1, wherein the module housing defines an opening located adjacent the cell header of the at least one battery cell, and wherein the annular rib fills the opening.

7. The battery pack of claim 1, wherein the annular rib is circular.

8. The battery pack of claim 1, wherein:

the annular rib is a first annular rib;

the water-resistant ring further includes a second annular rib protruding in the axial direction and located radially inward from the first annular rib; and

each of the first annular rib and the second annular rib is circular.

9. A water-resistant battery pack comprising:

an outer housing;

a controller operable to control an operation of the battery pack;

a terminal operable to connect to an electrical device for power transfer; and

a cell module within the outer housing, the cell module including:

a module housing,

at least one battery cell supported by the module housing and including a cell header,

a water-resistant ring provided at the cell header,

a conductive element electrically connecting the at least one battery cell to at least one of the controller and the terminal, and

a protective film applied to at least a portion of the conductive element and positioned between the water-resistant ring and the outer housing.

10. The battery pack of claim 9, wherein the protective film comprises a hydrophobic coating.

11. The battery pack of claim 9, further comprising an insulating sheet provided between the conductive element and the outer housing.

12. The battery pack of claim 9, wherein the cell module includes a plurality of battery cells, the plurality of battery cells including the at least one battery cell, and wherein the plurality of battery cells have an energy of at least 60 Watt-hours.

13. The battery pack of claim 9, wherein the water-resistant ring seals an interface between the at least one battery cell and the conductive element.

14. The battery pack of claim 9, wherein the water-resistant ring includes an annular rib protruding away from the at least one battery cell.

15. The battery pack of claim **14**, wherein the annular rib is a first annular rib, and wherein the water-resistant ring further includes a second annular rib protruding away from the at least one battery cell and located radially inward from the first annular rib.

16. The battery pack of claim **15**, wherein each of the first annular rib and the second annular rib is circular.

17. A water-resistant battery pack comprising:

an outer housing including floor wall and a plurality of side walls oriented transverse to the floor wall;

a controller operable to control an operation of the battery pack;

a terminal operable to connect to an electrical device for power transfer; and

a cell module within the outer housing, the cell module including:

a module housing,

at least one battery cell supported by the module housing and including a cell header,

a conductive element electrically connecting the at least one battery cell to at least one of the controller and the terminal, and

a protective film applied to at least a portion of the conductive element located between the module housing and at least one side wall of the plurality of side walls.

18. The battery pack of claim **17**, wherein the protective film comprises a hydrophobic coating.

19. The battery pack of claim **17**, further comprising an insulating sheet provided between the conductive element and the outer housing.

20. The battery pack of claim **17**, further comprising a water-resistant ring provided at the cell header, the water-resistant ring including an annular rib protruding in an axial direction of the at least one battery cell.

* * * * *