

**PATENT**

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:  
IRIS INTERNATIONAL, INC.

Serial No.: Filed Concurrently

Filed: June 30, 2017

For: FLOW CYTOMETER

Group Art Unit: Not yet assigned

Examiner: Not yet assigned

Atty. Dkt. No.:  
BECC.P0002US.CIP.C1/11706355  
Confirmation No.: Not yet assigned

Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

**CERTIFICATE OF ELECTRONIC TRANSMISSION**  
37 C.F.R. § 1.8

I hereby certify that this correspondence is being  
electronically filed with the United States Patent and  
Trademark Office via EFS-Web on the date below:

June 30, 2017  
Date

/Gina N. Shishima/  
Gina N. Shishima

**PRELIMINARY AMENDMENT**

Commissioner:

Applicant respectfully submits this Preliminary Amendment in the above-referenced case. Consideration of this case in view of the amendments made herein is respectfully requested.

**Amendment to the Specification** beginning on page 2.

**Amendments to the Claims** beginning on page 3.

**Remarks** begin on page 8.

**CYTEK V. BECKMAN**  
**PGR2025-00088**  
**BECKMAN 2016**

## **AMENDMENT TO THE SPECIFICATION**

Please replace the first full paragraph on page 1 of the Specification with the following amended paragraph:

This application is a continuation of U.S. Patent Application No. 14/555,102 filed November 26, 2014, which claims the benefit of priority of U.S. Provisional Patent Application Serial No. 61/911,859 entitled “Flow Cytometer,” filed on December 4, 2013. ~~This application~~ U.S. Patent Application No. 14/555,102 is also a continuation-in-part of International Patent Application Serial No. PCT/US2013/043453 entitled “Flow Cytometer,” filed on May 30, 2013, which claims the benefit of priority under 35 U.S.C. 119 to U.S. Provisional Patent Application Serial No. 61/653,245 entitled “Pulseless Peristaltic Pump,” filed on May 30, 2012, U.S. Provisional Patent Application Serial No. 61/653,328 entitled “Composite Microscope Objective with a Dispersion Compensation Plate,” filed on May 30, 2012, U.S. Provisional Patent Application Serial No. 61/715,819 entitled “Wavelength Division Multiplexing for Extended Light Source,” filed on October 18, 2012, U.S. Provisional Patent Application Serial No. 61/715,836 entitled “Diode Laser Based Optical Excitation System,” filed on October 19, 2012, and U.S. Provisional Patent Application Serial No. 61/816,819 entitled “A Simple Fluidic System for Supplying Pulsation Free Liquid to Flow Cell,” filed on April 29, 2013. All of the above-identified applications are incorporated herein by reference in their entirety.

### **AMENDMENT TO THE CLAIMS**

The listing of claims will replace all prior versions, and listing of claims in the application.

1-363. (cancelled)

364. (New) An optical module for a flow cytometer, the optical module comprising:

- (a) a light source;
  - (b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a collimated beam; and
  - (c) an optical relay arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay configured to project at least a portion of the collimated beam to a first focusing optical element,
- wherein the optical relay is one of a curved mirror and a refractive lens.

365. (New) The optical module of claim 364, wherein the light source is one of light passing through a pinhole and light emitted from a facet of a multimode optical fiber.

366. (New) The optical module of claim 365, wherein the first focusing optical element is configured to focus the collimated beam to a size smaller than 1 millimeter in diameter to a first semiconductor detector.

367. (New) The optical module of claim 364, wherein the light source forms an object, wherein the collimating optical element is configured to project a magnified image of the object, wherein the optical relay is a concave mirror having a radius of curvature approximately equal to the distance between the collimating optical element and the magnified image projected thereby.

368. (New) The optical module of claim 364, wherein the optical relay is a concave-shaped dichroic filter.

369. (New) The optical module of claim 364, wherein the collimating optical element is an achromatic doublet lens.

370. (New) The optical module of claim 364, further comprising a first optical filter arranged between the collimating optical element and the optical relay, the first optical filter configured to separate the collimated beam into a first branch and a second branch.

371. (New) The optical module of claim 370, wherein the collimated beam comprises light of a plurality of wavelengths, wherein the first optical filter is configured to reflect light of a first range of wavelengths to form the first branch of the collimated beam, wherein the first optical filter is configured to pass light of a second range of wavelengths to form the second branch of the collimated beam, wherein the first branch is directed to the optical relay.

372. (New) The optical module of claim 371, further comprising a second focusing optical element arranged to receive the second branch of the collimated beam, the second focusing optical element configured to focus the second branch of the collimated beam to a second semiconductor detector.

373. (New) The optical module of claim 372, wherein the diameter of the collimated beam between the optical relay and the first focusing optical element is substantially the same as the diameter of the collimated beam between the collimating optical element and the second focusing optical element.

374. (New) The optical module of claim 372, further comprising a second optical filter, the second optical filter arranged between the optical relay and the first focusing optical element, the second optical filter configured to pass light of a third range of wavelengths in the first branch of the collimated beam to the first focusing optical element, wherein the third range of wavelengths is a subset of the first range of wavelengths.

375. (New) The optical module of claim 374, wherein successive combinations of optical relay, optical filter, and focusing optical element are cascaded to produce focused spots having a diameter of less than 1 millimeter for multiple ranges of wavelengths of light of the collimated beam.



376. (New) An optical module for a flow cytometer, the optical module comprising:
- (a) a light source;
  - (b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a collimated beam and a first image, wherein the collimated beam has a collimated distance; and
  - (c) an optical relay arranged to receive the collimated beam, the optical relay configured to extend the collimated distance of the collimated beam.
377. (New) The optical module of claim 376, wherein the optical relay is one of a curved mirror and a refractive lens.
378. (New) The optical module of claim 376, wherein the optical relay projects a second image, wherein the second image and the first image are substantially the same size.
379. (New) The optical module of claim 376, wherein the optical relay projects a second image, wherein the collimated beam from the collimating optical element to the first image has substantially the same diameter as the collimated beam from the optical relay to the second image.
380. (New) The optical module of claim 376, further comprising a first focusing optical element arranged to receive the collimated beam from the optical relay at the extended collimated distance, the first focusing optical element configured to focus the extended collimated beam to a first semiconductor detector.
381. (New) The optical module of claim 380, further comprising:
- an optical filter arranged between the collimating optical element and the optical relay, the optical filter configured to separate the collimated beam into a first branch and a second branch, wherein the first branch and the second branch are different colors, wherein the optical relay receives the first branch; and

a second focusing optical element arranged to receive the second branch, the second focusing optical element configured to focus the second branch to a second semiconductor detector.

382. (New) The optical module of claim 380, wherein the optical distance from the collimating optical element to the optical relay is substantially the same as the optical distance from the optical relay to the first focusing optical element.

383. (New) An optical module for a flow cytometer, the optical module comprising:

- (a) a light source providing light that forms an object;
- (b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a first image of the object; and
- (c) an optical relay arranged near the first image, the optical relay configured to receive light from the collimating optical element and to project a second image of the object; wherein the size of the first image is substantially the same as the size of the second image.

384. (New) The optical module of claim 383, wherein the optical distance from the collimating optical element to the first image is substantially the same as the optical distance from the optical relay to the second image.

385. (New) The optical module of claim 383, wherein the light source is an extended light source that forms the object, wherein the first image is a magnified image of the object.

386. (New) The optical module of claim 385, wherein the light source is one of light passing through a pinhole and light emitted from a facet of a multimode optical fiber.

387. (New) The optical module of claim 385, wherein the collimating optical element has an effective size defined by its cross section, wherein the size of the first image is substantially the same as the effective size of the collimating optical element.

388. (New) The optical module of claim 385, wherein the first image is less than approximately 10 times the size of the object.

389. (New) The optical module of claim 385 further comprising a first focusing optical element arranged near the second image, the first focusing optical element configured to focus the light from the optical relay to a size smaller than the object of the light source to a first semiconductor detector.

### **REMARKS**

The specification has been amended to update the priority claim paragraph.

The claims have been amended without prejudice or disclaimer to manage the claims fees. Claims 1-363 have been canceled. Claims 364-389 are pending. Applicant retains the right pursue the subject matter as originally claimed at a later stage in this application or in future applications.

The filing fee has been calculated after amendment of the claims by the preliminary amendment. No new matter is added by entry of this preliminary amendment.

It is believed that no fee is due with this communication, however, should any fees under 37 C.F.R. §§ 1.16 to 1.21 be required for any reason relating to the enclosed document, the Commissioner is authorized to deduct or credit said fees from or to Norton Rose Fulbright US LLP Deposit Account No. 50-1212/BECC.P0002US.CIP.C1/11706355.

The Examiner is invited to contact the undersigned attorney with any questions, comments or suggestions relating to the referenced patent application.

Respectfully submitted,

/Gina N. Shishima/

Gina N. Shishima  
Reg. No. 45,104  
Attorney for Applicant

NORTON ROSE FULBRIGHT US LLP  
98 San Jacinto Blvd., Suite 1100  
Austin, Texas 78701  
(512) 474-5201

Date: June 30, 2017

**POWER OF ATTORNEY BY APPLICANT**

I hereby revoke all previous powers of attorney given in the application identified in either the attached transmittal letter or the boxes below.

|                    |                   |
|--------------------|-------------------|
| Application Number | Filing Date       |
| 14/555,102         | November 26, 2014 |

(Note: The boxes above may be left blank if information is provided on form PTO/AIA/82A.)

- ☒ I hereby appoint the Patent Practitioner(s) associated with the following Customer Number as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above: 129381
- OR**
- ☐ I hereby appoint Practitioner(s) named in the attached list (form PTO/AIA/82C) as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the patent application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above. (Note: Complete form PTO/AIA/82C.)

**Please recognize or change the correspondence address for the application identified in the attached transmittal letter or the boxes above to:**

- ☒ The address associated with the above-mentioned Customer Number
- OR**
- ☐ The address associated with Customer Number: 129381
- OR**

|                         |  |       |  |     |  |
|-------------------------|--|-------|--|-----|--|
| Firm or Individual Name |  |       |  |     |  |
| Address                 |  |       |  |     |  |
| City                    |  | State |  | Zip |  |
| Country                 |  |       |  |     |  |
| Telephone               |  | Email |  |     |  |


I am the Applicant (if the Applicant is a juristic entity, list the Applicant name in the box):

**IRIS INTERNATIONAL, INC.**

- ☐ Inventor or Joint Inventor (title not required below)
- ☐ Legal Representative of a Deceased or Legally Incapacitated Inventor (title not required below)
- ☒ Assignee or Person to Whom the Inventor is Under an Obligation to Assign (provide signer's title if applicant is a juristic entity)
- ☐ Person Who Otherwise Shows Sufficient Proprietary Interest (e.g., a petition under 37 CFR 1.46(b)(2) was granted in the application or is concurrently being filed with this document) (provide signer's title if applicant is a juristic entity)

**SIGNATURE of Applicant for Patent**

The undersigned (whose title is supplied below) is authorized to act on behalf of the applicant (e.g., where the applicant is a juristic entity).

|           |                                                                                     |                 |  |
|-----------|-------------------------------------------------------------------------------------|-----------------|--|
| Signature |  | Date (Optional) |  |
| Name      | Daniel B. Kim                                                                       |                 |  |
| Title     | Assistant Secretary, Iris International, Inc.                                       |                 |  |

**NOTE:** Signature - This form must be signed by the applicant in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. If more than one applicant, use multiple forms.

☒ Total of 1 forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

## DECLARATION (37 CFR 1.63) FOR UTILITY OR DESIGN APPLICATION USING AN APPLICATION DATA SHEET (37 CFR 1.76)

**Title of  
Invention**

FLOW CYTOMETER

As the below named inventor, I hereby declare that:

This declaration  
is directed to:

☐

The attached application, or

☒

United States application or PCT international application number 14/555,102

filed on November 26, 2014

The above-identified application was made or authorized to be made by me.

I believe that I am the original inventor or an original joint inventor of a claimed invention in the application.

I hereby acknowledge that any willful false statement made in this declaration is punishable under 18 U.S.C. 1001 by fine or imprisonment of not more than five (5) years, or both.

### WARNING:

Petitioner/applicant is cautioned to avoid submitting personal information in documents filed in a patent application that may contribute to identity theft. Personal information such as social security numbers, bank account numbers, or credit card numbers (other than a check or credit card authorization form PTO-2038 submitted for payment purposes) is never required by the USPTO to support a petition or an application. If this type of personal information is included in documents submitted to the USPTO, petitioners/applicants should consider redacting such personal information from the documents before submitting them to the USPTO. Petitioner/applicant is advised that the record of a patent application is available to the public after publication of the application (unless a non-publication request in compliance with 37 CFR 1.213(a) is made in the application) or issuance of a patent. Furthermore, the record from an abandoned application may also be available to the public if the application is referenced in a published application or an issued patent (see 37 CFR 1.14). Checks and credit card authorization forms PTO-2038 submitted for payment purposes are not retained in the application file and therefore are not publicly available.

### LEGAL NAME OF INVENTOR

Inventor:

Yong Qin Chen

Date (Optional):

3/9/2015

Signature:



Note: An application data sheet (PTO/SB/14 or equivalent), including naming the entire inventive entity, must accompany this form or must have been previously filed. Use an additional PTO/AIA/01 form for each additional inventor.

This collection of information is required by 35 U.S.C. 115 and 37 CFR 1.63. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 1 minute to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

*If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.*

## Electronic Patent Application Fee Transmittal

**Application Number:**

**Filing Date:**

**Title of Invention:**

FLOW CYTOMETER

**First Named Inventor/Applicant Name:**

Yong Qin Chen

**Filer:**

Gina N. Shishima/Sean Minorini

**Attorney Docket Number:**

BECC.P0002US.CIP.C1

Filed as Large Entity

### Filing Fees for Utility under 35 USC 111(a)

| Description                | Fee Code | Quantity | Amount | Sub-Total in USD(\$) |
|----------------------------|----------|----------|--------|----------------------|
| <b>Basic Filing:</b>       |          |          |        |                      |
| UTILITY APPLICATION FILING | 1011     | 1        | 280    | 280                  |
| UTILITY SEARCH FEE         | 1111     | 1        | 600    | 600                  |
| UTILITY EXAMINATION FEE    | 1311     | 1        | 720    | 720                  |

**Pages:**

|                                          |      |   |     |     |
|------------------------------------------|------|---|-----|-----|
| UTILITY APPL SIZE FEE PER 50 SHEETS >100 | 1081 | 1 | 400 | 400 |
|------------------------------------------|------|---|-----|-----|

**Claims:**

|                        |      |   |    |     |
|------------------------|------|---|----|-----|
| CLAIMS IN EXCESS OF 20 | 1202 | 6 | 80 | 480 |
|------------------------|------|---|----|-----|

**Miscellaneous Filing:**

| Description                       | Fee Code | Quantity | Amount | Sub-Total in USD(\$) |
|-----------------------------------|----------|----------|--------|----------------------|
| Petition:                         |          |          |        |                      |
| Patent-Appeals-and-Interference:  |          |          |        |                      |
| Post-Allowance-and-Post-Issuance: |          |          |        |                      |
| Extension-of-Time:                |          |          |        |                      |
| Miscellaneous:                    |          |          |        |                      |
| Total in USD (\$)                 |          |          |        | 2480                 |



## Electronic Acknowledgement Receipt

|                                             |                                |
|---------------------------------------------|--------------------------------|
| <b>EFS ID:</b>                              | 29659253                       |
| <b>Application Number:</b>                  | 15638461                       |
| <b>International Application Number:</b>    |                                |
| <b>Confirmation Number:</b>                 | 9847                           |
| <b>Title of Invention:</b>                  | FLOW CYTOMETER                 |
| <b>First Named Inventor/Applicant Name:</b> | Yong Qin Chen                  |
| <b>Customer Number:</b>                     | 32425                          |
| <b>Filer:</b>                               | Gina N. Shishima/Sean Minorini |
| <b>Filer Authorized By:</b>                 | Gina N. Shishima               |
| <b>Attorney Docket Number:</b>              | BECC.P0002US.CIP.C1            |
| <b>Receipt Date:</b>                        | 30-JUN-2017                    |
| <b>Filing Date:</b>                         |                                |
| <b>Time Stamp:</b>                          | 09:29:59                       |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a)    |

### Payment information:

|                                          |                       |
|------------------------------------------|-----------------------|
| Submitted with Payment                   | yes                   |
| Payment Type                             | CARD                  |
| Payment was successfully received in RAM | \$ 2480               |
| RAM confirmation Number                  | 063017INTEFSW09311000 |
| Deposit Account                          |                       |
| Authorized User                          |                       |

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

|                 |                                                     |                   |                                           |                  |                  |
|-----------------|-----------------------------------------------------|-------------------|-------------------------------------------|------------------|------------------|
|                 |                                                     |                   |                                           |                  |                  |
| File Listing:   |                                                     |                   |                                           |                  |                  |
| Document Number | Document Description                                | File Name         | File Size(Bytes)/ Message Digest          | Multi Part /.zip | Pages (if appl.) |
| 1               | Application Data Sheet                              | ADS.pdf           | 1823403                                   | no               | 9                |
|                 |                                                     |                   | 9c7f2cce1337f7bbba78b386071f88c4dea25fb2  |                  |                  |
| Warnings:       |                                                     |                   |                                           |                  |                  |
| Information:    |                                                     |                   |                                           |                  |                  |
| 2               |                                                     | Specification.pdf | 505440                                    | yes              | 138              |
|                 |                                                     |                   | 305d2b2731b7eaece7f3b934cff9c1679e1ad6b54 |                  |                  |
|                 | Multipart Description/PDF files in .zip description |                   |                                           |                  |                  |
|                 | Document Description                                |                   | Start                                     | End              |                  |
|                 | Specification                                       |                   | 1                                         | 91               |                  |
|                 | Claims                                              |                   | 92                                        | 137              |                  |
|                 | Abstract                                            |                   | 138                                       | 138              |                  |
| Warnings:       |                                                     |                   |                                           |                  |                  |
| Information:    |                                                     |                   |                                           |                  |                  |
| 3               | Drawings-only black and white line drawings         | Figures.pdf       | 529991                                    | no               | 35               |
|                 |                                                     |                   | c8151d7b037cda22e2059cb1b55625ba51d5413e  |                  |                  |
| Warnings:       |                                                     |                   |                                           |                  |                  |
| Information:    |                                                     |                   |                                           |                  |                  |
| 4               | Preliminary Amendment                               | prelimamend.pdf   | 119969                                    | no               | 8                |
|                 |                                                     |                   | 7205cfa623669ca2edde936f285702a7fa06641f  |                  |                  |
| Warnings:       |                                                     |                   |                                           |                  |                  |
| Information:    |                                                     |                   |                                           |                  |                  |
| 5               | Power of Attorney                                   | POA.pdf           | 121286                                    | no               | 1                |
|                 |                                                     |                   | 21bf1e7c3997c5b3c737a450d4138b3a32fde4cb  |                  |                  |

Page 14 of 630

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                           |              |                                              |    |   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------|--------------|----------------------------------------------|----|---|
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                           |              |                                              |    |   |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                           |              |                                              |    |   |
| 6                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Oath or Declaration filed | Oath.pdf     | 63613                                        | no | 1 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                           |              | 182c557bb1bdf14df0127166a46e0c30673f<br>ef2e |    |   |
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                           |              |                                              |    |   |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                           |              |                                              |    |   |
| 7                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Fee Worksheet (SB06)      | fee-info.pdf | 38305                                        | no | 2 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                           |              | c3d7122b17f4193c4c9d383a2e9c7ca3d20<br>b42dc |    |   |
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                           |              |                                              |    |   |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                           |              |                                              |    |   |
| <b>Total Files Size (in bytes):</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                           |              | 3202007                                      |    |   |
| <p><b>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</b></p> <p><b><u>New Applications Under 35 U.S.C. 111</u></b><br/> <b>If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</b></p> <p><b><u>National Stage of an International Application under 35 U.S.C. 371</u></b><br/> <b>If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</b></p> <p><b><u>New International Application Filed with the USPTO as a Receiving Office</u></b><br/> <b>If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</b></p> |                           |              |                                              |    |   |

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                |                        |                     |
|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                | Application Number     |                     |
| Title of Invention                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | FLOW CYTOMETER |                        |                     |
| <p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p> |                |                        |                     |

**Secrecy Order 37 CFR 5.2:**

|                          |                                                                                                                                                                                                                                       |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <input type="checkbox"/> | Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.) |
|--------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|

**Inventor Information:**

|                                                                                                                                                                            |                    |                |             |                      |                        |  |
|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------|----------------|-------------|----------------------|------------------------|--|
| Inventor                                                                                                                                                                   | 1                  |                |             |                      | <a href="#">Remove</a> |  |
| Legal Name                                                                                                                                                                 |                    |                |             |                      |                        |  |
| Prefix                                                                                                                                                                     | Given Name         | Middle Name    | Family Name | Suffix               |                        |  |
|                                                                                                                                                                            | Yong               | Qin            | Chen        |                      |                        |  |
| Residence Information (Select One) • <input checked="" type="radio"/> US Residency <input type="radio"/> Non US Residency <input type="radio"/> Active US Military Service |                    |                |             |                      |                        |  |
| City                                                                                                                                                                       | San Jose           | State/Province | CA          | Country of Residence | US                     |  |
| Mailing Address of Inventor:                                                                                                                                               |                    |                |             |                      |                        |  |
| Address 1                                                                                                                                                                  | 4097 Cortona Court |                |             |                      |                        |  |
| Address 2                                                                                                                                                                  |                    |                |             |                      |                        |  |
| City                                                                                                                                                                       | San Jose           | State/Province | CA          |                      |                        |  |
| Postal Code                                                                                                                                                                | 95135              | Country        | US          |                      |                        |  |
| All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the <b>Add</b> button. <a href="#">Add</a>            |                    |                |             |                      |                        |  |

**Correspondence Information:**

|                                                                                                                                       |                                    |                           |                              |
|---------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|---------------------------|------------------------------|
| Enter either Customer Number or complete the Correspondence Information section below.<br>For further information see 37 CFR 1.33(a). |                                    |                           |                              |
| <input type="checkbox"/> An Address is being provided for the correspondence information of this application.                         |                                    |                           |                              |
| Customer Number                                                                                                                       | 32425                              |                           |                              |
| Email Address                                                                                                                         | aoipdocket@nortonrosefulbright.com | <a href="#">Add Email</a> | <a href="#">Remove Email</a> |

**Application Information:**

|                                         |                     |                                           |                          |
|-----------------------------------------|---------------------|-------------------------------------------|--------------------------|
| Title of the Invention                  | FLOW CYTOMETER      |                                           |                          |
| Attorney Docket Number                  | BECC.P0002US.CIP.C1 | Small Entity Status Claimed               | <input type="checkbox"/> |
| Application Type                        | Nonprovisional      |                                           |                          |
| Subject Matter                          | Utility             |                                           |                          |
| Total Number of Drawing Sheets (if any) | 35                  | Suggested Figure for Publication (if any) |                          |

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

## Filing By Reference:

Only complete this section when filing an application by reference under 35 U.S.C. 111(c) and 37 CFR 1.57(a). Do not complete this section if application papers including a specification and any drawings are being filed. Any domestic benefit or foreign priority information must be provided in the appropriate section(s) below (i.e., "Domestic Benefit/National Stage Information" and "Foreign Priority Information").

For the purposes of a filing date under 37 CFR 1.53(b), the description and any drawings of the present application are replaced by this reference to the previously filed application, subject to conditions and requirements of 37 CFR 1.57(a).

|                                                        |                          |                                            |
|--------------------------------------------------------|--------------------------|--------------------------------------------|
| Application number of the previously filed application | Filing date (YYYY-MM-DD) | Intellectual Property Authority or Country |
|                                                        |                          |                                            |

## Publication Information:

☐ Request Early Publication (Fee required at time of Request 37 CFR 1.219)

☐ **Request Not to Publish.** I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application **has not and will not** be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

## Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Either enter Customer Number or complete the Representative Name section below. If both sections are completed the customer Number will be used for the Representative Information during processing.

|                    |                                                  |                        |                                                         |
|--------------------|--------------------------------------------------|------------------------|---------------------------------------------------------|
| Please Select One: | <input checked="" type="radio"/> Customer Number | US Patent Practitioner | <input type="radio"/> Limited Recognition (37 CFR 11.9) |
| Customer Number    | 32425                                            |                        |                                                         |

## Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, 365(c), or 386(c) or indicate National Stage entry from a PCT application. Providing benefit claim information in the Application Data Sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78.

When referring to the current application, please leave the "Application Number" field blank.

|                          |                 |                          |                                    |
|--------------------------|-----------------|--------------------------|------------------------------------|
| Prior Application Status |                 | Remove                   |                                    |
| Application Number       | Continuity Type | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
|                          | Continuation of | 14/555102                | 2014-11-26                         |

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

|                                                                                                                       |                               |                          |                                    |
|-----------------------------------------------------------------------------------------------------------------------|-------------------------------|--------------------------|------------------------------------|
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| 14/555102                                                                                                             | Claims benefit of provisional | 61/911859                | 2013-12-04                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| 14/555102                                                                                                             | Continuation in part of       | PCT/US2013/043453        | 2013-05-30                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| PCT/US2013/043453                                                                                                     | Claims benefit of provisional | 61/653245                | 2012-05-30                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| PCT/US2013/043453                                                                                                     | Claims benefit of provisional | 61/653328                | 2012-05-30                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| PCT/US2013/043453                                                                                                     | Claims benefit of provisional | 61/715819                | 2012-10-18                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| PCT/US2013/043453                                                                                                     | Claims benefit of provisional | 61/715836                | 2012-10-19                         |
| Prior Application Status                                                                                              |                               |                          | <a href="#">Remove</a>             |
| Application Number                                                                                                    | Continuity Type               | Prior Application Number | Filing or 371(c) Date (YYYY-MM-DD) |
| PCT/US2013/043453                                                                                                     | Claims benefit of provisional | 61/816819                | 2013-04-29                         |
| Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the <b>Add</b> button. |                               |                          | <a href="#">Add</a>                |

## Foreign Priority Information:

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

This section allows for the applicant to claim priority to a foreign application. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55. When priority is claimed to a foreign application that is eligible for retrieval under the priority document exchange program (PDX)<sup>i</sup> the information will be used by the Office to automatically attempt retrieval pursuant to 37 CFR 1.55(i)(1) and (2). Under the PDX program, applicant bears the ultimate responsibility for ensuring that a copy of the foreign application is received by the Office from the participating foreign intellectual property office, or a certified copy of the foreign priority application is filed, within the time period specified in 37 CFR 1.55(g)(1).

| Application Number | Country <sup>i</sup> | Filing Date (YYYY-MM-DD) | Access Code <sup>i</sup> (if applicable) |
|--------------------|----------------------|--------------------------|------------------------------------------|
|                    |                      |                          |                                          |

Additional Foreign Priority Data may be generated within this form by selecting the **Add** button.

## Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications

☐ This application (1) claims priority to or the benefit of an application filed before March 16, 2013 and (2) also contains, or contained at any time, a claim to a claimed invention that has an effective filing date on or after March 16, 2013.

NOTE: By providing this statement under 37 CFR 1.55 or 1.78, this application, with a filing date on or after March 16, 2013, will be examined under the first inventor to file provisions of the AIA.

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

## Authorization or Opt-Out of Authorization to Permit Access:

When this Application Data Sheet is properly signed and filed with the application, applicant has provided written authority to permit a participating foreign intellectual property (IP) office access to the instant application-as-filed (see paragraph A in subsection 1 below) and the European Patent Office (EPO) access to any search results from the instant application (see paragraph B in subsection 1 below).

Should applicant choose not to provide an authorization identified in subsection 1 below, applicant **must opt-out** of the authorization by checking the corresponding box A or B or both in subsection 2 below.

**NOTE:** This section of the Application Data Sheet is **ONLY** reviewed and processed with the **INITIAL** filing of an application. After the initial filing of an application, an Application Data Sheet cannot be used to provide or rescind authorization for access by a foreign IP office(s). Instead, Form PTO/SB/39 or PTO/SB/69 must be used as appropriate.

### 1. Authorization to Permit Access by a Foreign Intellectual Property Office(s)

**A. Priority Document Exchange (PDX)** - Unless box A in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the European Patent Office (EPO), the Japan Patent Office (JPO), the Korean Intellectual Property Office (KIPO), the State Intellectual Property Office of the People's Republic of China (SIPO), the World Intellectual Property Organization (WIPO), and any other foreign intellectual property office participating with the USPTO in a bilateral or multilateral priority document exchange agreement in which a foreign application claiming priority to the instant patent application is filed, access to: (1) the instant patent application-as-filed and its related bibliographic data, (2) any foreign or domestic application to which priority or benefit is claimed by the instant application and its related bibliographic data, and (3) the date of filing of this Authorization. See 37 CFR 1.14(h)(1).

**B. Search Results from U.S. Application to EPO** - Unless box B in subsection 2 (opt-out of authorization) is checked, the undersigned hereby **grants the USPTO authority** to provide the EPO access to the bibliographic data and search results from the instant patent application when a European patent application claiming priority to the instant patent application is filed. See 37 CFR 1.14(h)(2).

The applicant is reminded that the EPO's Rule 141(1) EPC (European Patent Convention) requires applicants to submit a copy of search results from the instant application without delay in a European patent application that claims priority to the instant application.

### 2. Opt-Out of Authorizations to Permit Access by a Foreign Intellectual Property Office(s)

☐ A. Applicant **DOES NOT** authorize the USPTO to permit a participating foreign IP office access to the instant application-as-filed. If this box is checked, the USPTO will not be providing a participating foreign IP office with any documents and information identified in subsection 1A above.

☐ B. Applicant **DOES NOT** authorize the USPTO to transmit to the EPO any search results from the instant patent application. If this box is checked, the USPTO will not be providing the EPO with search results from the instant application.

**NOTE:** Once the application has published or is otherwise publicly available, the USPTO may provide access to the application in accordance with 37 CFR 1.14.



|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

## Applicant Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                          |                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------|--------------------------------------------------|
| <b>Applicant</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 1                                        | <a href="#">Remove</a>                           |
| <p>If the applicant is the inventor (or the remaining joint inventor or inventors under 37 CFR 1.45), this section should not be completed. The information to be provided in this section is the name and address of the legal representative who is the applicant under 37 CFR 1.43; or the name and address of the assignee, person to whom the inventor is under an obligation to assign the invention, or person who otherwise shows sufficient proprietary interest in the matter who is the applicant under 37 CFR 1.46. If the applicant is an applicant under 37 CFR 1.46 (assignee, person to whom the inventor is obligated to assign, or person who otherwise shows sufficient proprietary interest) together with one or more joint inventors, then the joint inventor or inventors who are also the applicant should be identified in this section.</p> <p style="text-align: right;"><a href="#">Clear</a></p> |                                          |                                                  |
| <input checked="" type="radio"/> Assignee                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Legal Representative under 35 U.S.C. 117 | Joint Inventor                                   |
| Person to whom the inventor is obligated to assign.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                          | Person who shows sufficient proprietary interest |
| If applicant is the legal representative, indicate the authority to file the patent application, the inventor is:                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                          |                                                  |
| <div style="border: 1px solid black; height: 20px; width: 100%;"></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                          |                                                  |
| Name of the Deceased or Legally Incapacitated Inventor: <div style="border: 1px solid black; height: 20px; width: 100%;"></div>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |                                          |                                                  |
| If the Applicant is an Organization check here. <input checked="" type="checkbox"/>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                          |                                                  |
| Organization Name                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | IRIS INTERNATIONAL, INC.                 |                                                  |
| <b>Mailing Address Information For Applicant:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                          |                                                  |
| Address 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | 9172 Eton Avenue                         |                                                  |
| Address 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |                                          |                                                  |
| City                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Chatsworth                               | State/Province                                   |
| Country                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | US                                       | Postal Code                                      |
| Phone Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                          | Fax Number                                       |
| Email Address                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                          |                                                  |
| Additional Applicant Data may be generated within this form by selecting the Add button. <a href="#">Add</a>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                          |                                                  |

## Assignee Information including Non-Applicant Assignee Information:

Providing assignment information in this section does not substitute for compliance with any requirement of part 3 of Title 37 of CFR to have an assignment recorded by the Office.

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                      |                      |                      |                                       |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------|----------------------|----------------------|---------------------------------------|
| <b>Assignee</b>                                                                                                                                                                                                                                                                                                                                                                                                                                        | 1                    |                      |                      |                                       |
| Complete this section if assignee information, including non-applicant assignee information, is desired to be included on the patent application publication. An assignee-applicant identified in the "Applicant Information" section will appear on the patent application publication as an applicant. For an assignee-applicant, complete this section only if identification as an assignee is also desired on the patent application publication. |                      |                      |                      |                                       |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                      |                      |                      | <input type="button" value="Remove"/> |
| If the Assignee or Non-Applicant Assignee is an Organization check here.                                                                                                                                                                                                                                                                                                                                                                               |                      |                      |                      | <input type="checkbox"/>              |
| Prefix                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Given Name           | Middle Name          | Family Name          | Suffix                                |
| <input type="text"/>                                                                                                                                                                                                                                                                                                                                                                                                                                   | <input type="text"/> | <input type="text"/> | <input type="text"/> | <input type="text"/>                  |
| <b>Mailing Address Information For Assignee including Non-Applicant Assignee:</b>                                                                                                                                                                                                                                                                                                                                                                      |                      |                      |                      |                                       |
| Address 1                                                                                                                                                                                                                                                                                                                                                                                                                                              |                      | <input type="text"/> |                      |                                       |
| Address 2                                                                                                                                                                                                                                                                                                                                                                                                                                              |                      | <input type="text"/> |                      |                                       |
| City                                                                                                                                                                                                                                                                                                                                                                                                                                                   | <input type="text"/> | State/Province       | <input type="text"/> |                                       |
| Country <sup>i</sup>                                                                                                                                                                                                                                                                                                                                                                                                                                   | <input type="text"/> | Postal Code          | <input type="text"/> |                                       |
| Phone Number                                                                                                                                                                                                                                                                                                                                                                                                                                           | <input type="text"/> | Fax Number           | <input type="text"/> |                                       |
| Email Address                                                                                                                                                                                                                                                                                                                                                                                                                                          | <input type="text"/> |                      |                      |                                       |
| Additional Assignee or Non-Applicant Assignee Data may be generated within this form by selecting the Add button.                                                                                                                                                                                                                                                                                                                                      |                      |                      |                      | <input type="button" value="Add"/>    |

**Signature:**

**NOTE:** This Application Data Sheet must be signed in accordance with 37 CFR 1.33(b). However, if this Application Data Sheet is submitted with the **INITIAL** filing of the application and either box A or B is not checked in subsection 2 of the "Authorization or Opt-Out of Authorization to Permit Access" section, then this form must also be signed in accordance with 37 CFR 1.14(c).

This Application Data Sheet **must** be signed by a patent practitioner if one or more of the applicants is a **juristic entity** (e.g., corporation or association). If the applicant is two or more joint inventors, this form must be signed by a patent practitioner, **all** joint inventors who are the applicant, or one or more joint inventor-applicants who have been given power of attorney (e.g., see USPTO Form PTO/AIA/81) on behalf of **all** joint inventor-applicants.

See 37 CFR 1.4(d) for the manner of making signatures and certifications.

|                                                                                     |                    |           |                   |                                    |
|-------------------------------------------------------------------------------------|--------------------|-----------|-------------------|------------------------------------|
| <b>Signature</b>                                                                    | /Gina N. Shishima/ |           | Date (YYYY-MM-DD) | 2017-06-30                         |
| First Name                                                                          | Gina N.            | Last Name | Shishima          | Registration Number                |
|                                                                                     |                    |           |                   | 45104                              |
| Additional Signature may be generated within this form by selecting the Add button. |                    |           |                   | <input type="button" value="Add"/> |

|                                           |                |                        |                     |
|-------------------------------------------|----------------|------------------------|---------------------|
| <b>Application Data Sheet 37 CFR 1.76</b> |                | Attorney Docket Number | BECC.P0002US.CIP.C1 |
|                                           |                | Application Number     |                     |
| Title of Invention                        | FLOW CYTOMETER |                        |                     |

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

## Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

## FLOW CYTOMETER

### CROSS-REFERENCE TO RELATED APPLICATIONS

This application claims the benefit of priority of U.S. Provisional Patent Application  
5 Serial No. 61/911,859 entitled “Flow Cytometer,” filed on December 4, 2013. This  
application is also a continuation-in-part of International Patent Application Serial No.  
PCT/US2013/043453 entitled “Flow Cytometer,” filed on May 30, 2013, which claims the  
benefit of priority under 35 U.S.C. 119 to U.S. Provisional Patent Application Serial No.  
61/653,245 entitled “Pulseless Peristaltic Pump,” filed on May 30, 2012, U.S. Provisional  
10 Patent Application Serial No. 61/653,328 entitled “Composite Microscope Objective with a  
Dispersion Compensation Plate,” filed on May 30, 2012, U.S. Provisional Patent  
Application Serial No. 61/715,819 entitled “Wavelength Division Multiplexing for  
Extended Light Source,” filed on October 18, 2012, U.S. Provisional Patent Application  
Serial No. 61/715,836 entitled “Diode Laser Based Optical Excitation System,” filed on  
15 October 19, 2012, and U.S. Provisional Patent Application Serial No. 61/816,819 entitled  
“A Simple Fluidic System for Supplying Pulsation Free Liquid to Flow Cell,” filed on  
April 29, 2013. All of the above-identified applications are incorporated herein by  
reference in their entirety.

20

### BACKGROUND

#### Technical Field

The present disclosure relates generally to the technical field of flow cytometry and,  
more particularly, to the structure and operation of an improved flow cytometer together  
with various individual subassemblies included therein.

25

#### Background

Flow cytometry is a biophysical technique employed in cell counting, sorting,  
biomarker detection and protein engineering. In flow cytometry, cells suspended in a  
stream of liquid pass through an electronic detection apparatus. Flow cytometry allows  
simultaneous multiparametric analysis of physical and/or chemical characteristics of up to  
30 thousands of cells per second.

Flow cytometry has various applications including in the fields of molecular biology, pathology, immunology, plant biology and marine biology. Flow cytometry also has broad application in medicine (especially in transplantation, hematology, tumor immunology and chemotherapy, prenatal diagnosis, genetics and sperm sorting for sex preselection). In marine biology, the autofluorescent properties of photosynthetic plankton can be exploited by flow cytometry in characterizing abundance and community composition. In protein engineering, flow cytometry is used in conjunction with yeast display and bacterial display to identify cell surface-displayed protein variants with desired properties. A common variation of flow cytometry is physically sorting particles based on their properties thereby purifying a population of interest.

## SUMMARY OF DISCLOSURE

The present disclosure provides an improved flow cytometer together with various improved components included therein, as well as component groups with interacting components.

In certain embodiments, the present disclosure provides a simple and reliable diode laser based optical system capable of delivering a focused laser beam of elliptical cross section with a Gaussian like intensity distribution along its minor axis and a width along major axis optimized for flow cytometric applications.

In certain embodiments, the present disclosure provides an imaging quality microscope objective that is easy to manufacture and has long working distance, large numerical aperture, large field of view and minimal chromatic aberration.

In certain embodiments, the present disclosure provides a simple fluidics system for flow cytometers that is not only reliable, compact and easy to manufacture, but also capable of supporting velocity critical applications such as in instruments with multiple spatially separated excitation laser beams or in droplet sorters.

In certain embodiments, the present disclosure provides a simple design for a peristaltic pump providing a pulseless liquid flow.

In certain embodiments, the present disclosure provides a peristaltic pump with minimal pulsation.

In certain embodiments, the present disclosure provides a peristaltic pump that is simple to manufacture and operate.

5           In certain embodiments, the present disclosure provides a device capable of collimating a light beam from an extended light source over an extended distance without significantly expanding the beam diameter.

          In certain embodiments, the present disclosure provides a Wavelength Division Multiplexing (WDM) system to separate a light beam into multiple colored bands. The  
10   WDM system may be compatible with low noise semiconductor detectors. In addition, due to the diversity of fluorescent probes, the WDM system may be reconfigurable.

          According to an exemplary embodiment, a flow cytometer may include:

1. a Laser Diode (LD) based optical subsystem for impinging a beam of light upon particles passing through a viewing zone;
- 15       2. a composite microscope objective for gathering and imaging light scattered from or fluoresced by particles passing through the viewing zone;
3. a fluidic subsystem for supplying a liquid sheath flow to the viewing zone;
4. a peristaltic pump for injecting a liquid sample flow carrying particles that pass together with the liquid sheath flow through the viewing zone;
- 20       5. a multimode optical fiber that receives scattered and fluoresced light from the viewing zone that the composite microscope objective gathers images; and
6. a wavelength division multiplexer for optically separating light received via the optical fiber into color bands.

          According to an exemplary embodiment, the LD based optical subsystem for  
25   illuminating particles passing through the flow cytometer's viewing zone may generally include:

1. a laser diode oriented with its slow axis parallel to the direction of flow;
2. a collimating lens that converts the diverging beam from the LD into a collimated beam of elliptical shape with its major axis perpendicular to the flow;

3. a focusing lens system that reduces the laser beam at the viewing zone to an optimal width in the direction perpendicular to the flow; and

4. finally a high power cylindrical focusing element placed in the proximity of the viewing zone with its axis perpendicular to the direction of flow.

5       The high power cylindrical focusing element may transpose the far field profile of the LD along its slow axis to its Fourier conjugate at the viewing zone along the direction of flow, while maintains the transverse beam profile, such that the laser beam profile at the viewing zone is optimal for flow cytometric applications.

10       According to an exemplary embodiment, the composite microscope objective may generally include:

1. a concave spherical mirror;

2. a transparent aberration compensation plate with the flow cytometer's a viewing zone being located between the mirror and the plate. Scatter and fluorescence light emitted from particles in the viewing zone is collected by the mirror and reflected back toward the compensation plate. Optical aberrations originating from the mirror are significantly reduced after light passes through the compensation plate. In one embodiment of the present disclosure, the viewing zone may be located inside a flow cell provided by rectangular glass cuvette with a small rectangular channel through which a particle carrying liquid flows. The concave mirror may be made of an optically transparent material, such as glass or optical quality plastics, of plano-convex shape with a highly-reflective coating on the convex side for internal reflection. The plano-side of the mirror may be either gel-coupled or bonded to one side surface of the cuvette. The plano-aspheric compensation plate may be made of a transparent material, such as glass or optical quality plastics, with the plano side gel-coupled or bonded to the opposite side of the cuvette. The plano-convex shaped mirror and the aspheric compensation plate may also be formed integrally with the cuvette. In yet another embodiment of the present disclosure, the viewing zone may be in a jet stream with both the concave mirror and the compensation plate being free standing from the viewing zone, and the mirror may be a front surface concave mirror.

15  
20  
25

30       According to an exemplary embodiment, the fluidic system may generally include a sheath liquid reservoir from which a liquid pump draws sheath liquid. Sheath liquid then



flows from the liquid pump to an inlet of a T-coupling. One outlet arm of the T-coupling connects to a bypass that returns a fraction of the pumped sheath liquid back to the sheath liquid reservoir with the returned sheath liquid flowing into air within the sheath liquid reservoir. A second outlet arm of the T-coupling connects to a sheath route that includes a reservoir capsule followed by a particle filter and then the flow cell. The sheath liquid exiting the flow cell then goes to the waste tank. The fluidic resistance along the bypass is designed to be lower than the fluidic resistance along the sheath route. Consequently, only a small fraction of the sheath liquid goes through the flow cell. Note that typical sheath flow rate in flow cytometric applications is a few tens of milliliter per minute. The bypass therefore permits using higher flow rate liquid pumps that not only are much less expensive and more reliable, but also operates at higher pulsation frequency which is much easier to attenuate. Since the exit of the bypass route connects to air, it also serves as a large fluidic capacitor for significantly reducing pulsation in sheath liquid flowing along the sheath route. During operation, the inlet portion of the filter cartridge is filled with air. Therefore, the filter cartridge also serves as a fluidic capacitor, for further reducing pulsation in the sheath liquid at the flow cell to negligible level. Due to the large fluidic resistance at the flow cell, the air trapped near the inlet of the filter cartridge becomes compressed. If the liquid pump is turned off, the compressed air in filter cartridge being pushed back towards the sheath liquid reservoir becomes stored in the reservoir capsule whose size is chosen to prevent the trapped air from reaching the T-coupling.

According to an exemplary embodiment, the peristaltic pump may generally include a plurality of rollers located at the periphery of a rotor that moves the rollers circularly inside a housing's arcuate curved track and a compressible tube that the rollers compress against the track. In one embodiment of the present disclosure, the track of the peristaltic pump's housing may have one recess so the compressible tube is progressively decompressed to full expansion then compressed to full closure every time one of the rollers moves past the recess. The location and shape of the recess maintains the total volume of liquid within the compressible tube from the recess to the pump's outlet substantially invariant. The effect of tube expansion as a roller moves past the pump's outlet is compensated by the tube compression when a different other roller immediately upstream of the pump outlet moves into the recess' compressing section. In another embodiment of

the present disclosure, the track of the pump housing may contain a plurality of recesses, providing for a plurality of roller upstream of the pump outlet to progressively modify the tube compression in multiple sections along the compressible tube. The locations and shapes of the plurality of recesses are designed such that the modification of tube compression at these sections substantially compensates the effect due to the tube expansion near the pump outlet. In yet another embodiment of the present disclosure, the compressible tube is kept fully closed underneath the roller except in the inlet and exit sections. A variable speed motor may be used to drive the pump. When a roller reaches the exit section, the motor's rotation may programmatically speed up to compensate for the tube's expansion.

According to an exemplary embodiment, a wavelength division multiplexer ("WDM") may include at least two optical elements. The first optical element collimates a beam of light received from an extended light source, such as the light from a pinhole or from a multimode optical fiber. The first optical element magnifies the extended light source, for example, as defined by the pinhole, or the core of the multimode optical fiber, to an image having a size similar to the effective cross section of the first optical element thereby creating a collimated light beam between the first optical element and its image. A second optical element is positioned near the image, and relays the first optical element with unit magnification down the optical path. In this way, the second optical element effectively doubles the collimated path length. Additional optical elements in the same 1:1 image relay configuration may also be included to further extend the collimated optical path. The cascaded unit-magnification image relay architecture of the present disclosure extends the collimated optical path length without large beam expansion. As a result, WDM techniques well-established in the optical communication industry can be readily adapted for fluorescence light detection. In particular, multiple colored bands present in the beam of light can be separated using dichroic filters located along the optical path with the separated light being tightly focused into small spots compatible with low noise semiconductor photodetectors.

In one embodiment of a WDM, the first optical element is a lens and the second element is a concave mirror, although it is apparent to those skilled in the art that other types of refractive and/or reflective optical components may also be used to achieve the

same design goal. The optical path in the WDM of the present disclosure may be folded using dichroic filters. In one embodiment of the present disclosure, the light path may be folded into a zig-zag configuration. To facilitate the flow cytometer's reliable reconfiguration, each dichroic filter may be bonded to a mechanical holder having a reference surface that is optically parallel to the filter's reflective surface. As a result, all of the WDM's filters can be accurately positioned along the optical path by referencing the filter's holder against a common optical flat. In another embodiment of the present disclosure, the collimated beam passing through the dichroic filter is further branched out into multiple colored bands using secondary dichroic filters. It is apparent to those skilled in the art that dichroic filters may be inserted anywhere along the long, narrow and collimated beam path afforded by the present disclosure's relay imaging to thereby permit delivering a tightly focused beam to photo detectors using a variety of optical configurations, such as the star configuration discussed in United States Patent no. 6,683,314, the branched configuration discussed in United States Patent no. 4,727,020 and other types of WDM optical configuration widely practiced in the optical communication industry. Instead of concave mirrors, the WDM may be replaced by curved dichroic filters to further increase the number of colored bands selected by the WDM.

According to some exemplary embodiments, an optical system for impinging beams of light into a viewing zone in which a sample flow carrying objects and a sheath flow pass through includes a first light source for emitting a first beam of light along a first beam path to illuminate objects in the viewing zone at a first location, a second light source for emitting a second beam of light along a second beam path to illuminate objects in the viewing zone at a second location, a beam compressing optical element for reducing widths of the first and second beams of light on their major axes to a width less than the width of the sheath flow, and a first chromatic compensation element located on at least one of the first beam path and the second beam path for compensating chromatic aberration in the viewing zone such that the first location and the second locations are on a common plane parallel to the direction of the sample flow. The wavelength of the second light source is different from the wavelength of the first light source. The chromatic compensation allows compensating the properties of the different paths, resulting e.g. from the different wavelengths, the different path lengths, different locations in the flow path etc. This applies

also for multiple compensating elements in different paths, in particular when using two, three or more wavelengths for illumination.

According to some exemplary embodiments, an optical system includes a first light source for emitting a first beam of light to illuminate objects at a first location in a viewing zone, a composite microscope objective for imaging light scattered from and fluoresced by the objects at the first location in the viewing zone at an image plane external to the composite microscope, and a beam splitter for reflecting or transmitting scattered and fluoresced light, wherein the light source and the image plane are on two sides of the beam splitter. The composite microscope includes a concave mirror and an aberration corrector plate. The aberration corrector plate is an aspheric lens that has a first zone with negative optical power and a second zone with positive optical power radially inside the first zone. The viewing zone is positioned between the concave mirror and the aberration corrector plate. This allows a compact build-up, as the illumination and the detection of light scattered from and fluoresced by the objects in the viewing zone may be conducted from the same side of the microscope objective.

According to some exemplary embodiments, an axial light detection system includes a concave mirror for reflecting light that propagates from a viewing zone, and a detector for measuring axial light loss produced by an object in the viewing zone by detecting light reflected by the concave mirror. This allows an effective detection of light loss which may serve as a base for better interpretation of the measured values.

According to some exemplary embodiments, a power monitoring system for adjusting power of a light source includes a first light source for emitting a first beam of light, a second light source for emitting a second beam of light, a first dichroic filter for reflecting the first beam of light and passing the second beam of light, a second dichroic filter for reflecting the second beam of light, a first detector for measuring residual power of the first and second beams of light downstream of the first dichroic filter on a time-division multiplexing basis, and a control unit coupled with the first detector and the first and second light sources, wherein the control unit adjusts power of one or more of the first and second light sources based on measured residual power of the first and second beams of light by the first detector. This allows an effective detection of light power which may

serve as a base for better interpretation of the measured values, as well as an effective control procedure, in particular when controlling or adaption respective light sources.

According to another exemplary embodiment, an optical system includes an objective adapted for imaging light scattered from and fluoresced by an illuminated object within a viewing zone, an optical transmission member for propagating light received from the aspheric lens, a wavelength division multiplexer (WDM) for receiving light propagated by the optical transmission member. The objective includes an aspheric lens with a first zone with negative optical power and a second zone inside the first zone with positive optical power, and a concave mirror for reflecting light scattered from and fluoresced by the illuminated object through the aspheric lens, wherein the viewing zone is located between said concave mirror and the aspheric lens. The WDM includes a first optical element that produces a beam of light with an image of substantially the same size as the effective size of said first optical element, at least one dichroic filter located between said first optical element and said image, a second optical element located in one of said branches, and an image relay optical element located near the image produced by said first optical element in the other branch. The dichroic filter separates the beam of light into two branches of distinctive colors. The beam of light in said branch is focused to a spot by said second optical element. The image relay optical element produces an image of said first optical element at substantially unit magnification. This allows an adapted combined operation of the microscope objective and the WDM, as well as the optical coupling there between. In particular the microscope objective and the WDM as well as the optical coupling may be adapted to match to each other with respect to wavelength and other parameters.

According to another exemplary embodiment, an optical system includes a light source for emitting a beam of light to illuminate an object in a viewing zone, a concave mirror for receiving and reflecting light scattered from and fluoresced by the illuminated object, an aspheric lens with a first zone with negative optical power and a second zone inside the first zone with positive optical power, wherein light reflected by the concave mirror passes through the aspheric lens, and wherein the viewing zone is located between said concave mirror and the aspheric lens, an optical transmission member for receiving and propagating light from the aspheric lens, and a multiplexer for receiving light from the

optical transmission member and separating the light into at least two colors. This allows an adapted combined operation of the illumination system, the microscope objective and the WDM, as well as the optical coupling there between. In particular the illumination system, the microscope objective and the WDM as well as the optical coupling may be adapted to  
5 match to each other with respect to wavelength and other parameters.

According to another exemplary embodiment, an apparatus for imaging light scattered from and fluoresced by an illuminated object within a viewing zone includes a fluid delivery system for delivering an object to a viewing zone, a light source for illuminating the object in the viewing zone, a concave mirror located on one side of the  
10 viewing zone for reflecting light scattered from and fluoresced by the illuminated object, and an aspheric lens located on another side of the viewing zone for receiving the light reflected by the concave mirror and forming an image at an image plane, the aspheric lens having a first zone with negative optical power and a second zone radially inside the first zone with positive optical power. This allows an adapted combined operation of the fluid  
15 delivery system, the illumination system, and the microscope objective. In particular the fluid delivery system, the illumination system, and the microscope objective may be adapted to match to each other with respect to wavelength and other parameters.

According to other exemplary embodiments, an optical method for impinging beams of light into a viewing zone includes directing a first beam of light to illuminate  
20 objects in a viewing zone to produce scattered and fluoresced light, reflecting the scattered and fluoresced light using a concave mirror toward an aberration corrector plate, correcting aberrations in the reflected light with the aberration corrector plate, wherein the aberration corrector plate has a first zone with negative optical power a second zone radially inside the first zone with positive optical power, and reflecting or transmitting the corrected light  
25 using a beam splitter.

According to other exemplary embodiments, an optical method for detecting light includes reflecting light that propagates from a viewing zone using a concave mirror, and measuring axial light loss produced by an object in the viewing zone by detecting light reflected by the concave mirror.

According to other exemplary embodiments, a method of gathering and imaging light scattered from or fluoresced by objects in a viewing includes delivering an object to a viewing zone, illuminating the object in the viewing zone to produce scattered and fluoresced light, reflecting the scattered and fluoresced light using a concave mirror toward  
5 a transparent aberration corrector plate, and correcting spherical aberrations in the reflected light with the transparent aberration corrector plate, wherein the transparent aberration corrector plate has a first zone with negative optical power and a second zone radially inside the first zone with positive optical power.

According to other exemplary embodiments, a composite microscope objective  
10 adapted for imaging light scattered from and fluoresced by an object present within a viewing zone, comprises a viewing zone, a concave mirror arrangement, an exit area and an illumination beam forming arrangement, wherein the viewing zone is arranged between the concave mirror arrangement and the exit area, and wherein the concave mirror is arranged to reflect scattered and fluoresced light impinging from an object present in the viewing  
15 zone to the exit area, and wherein the illumination beam forming arrangement is arranged so that an illumination beam entering the illumination beam forming arrangement is pre-definitely formed at the viewing zone. According to other exemplary embodiments there may be provided an aberration corrector plate, in particular an aspheric lens in the exit area. This allows an effective build-up of the microscope objective. It should be noted that the  
20 aberration corrector plate is not necessary when providing a concave mirror shape allowing a sufficient imaging of the light scattered and fluoresced from an object in the viewing zone. If required an aberration corrector plate, in particular an aspheric lens may be arranged in the exit area.

According to other exemplary embodiments a wavelength division multiplexer  
25 (WDM) for separating light emitted from a light source into multiple colored bands comprises an imaging optical arrangement, a dichroic filter arrangement, a semiconductor photo detector, and a focusing optical arrangement, wherein the imaging optical arrangement forms a beam of light from the light emitted from a light source and produces an image of substantially the same size as the effective size of said imaging optical  
30 arrangement, and wherein the dichroic filter arrangement is located between said imaging optical arrangement and said image, and separates the beam of light into a first branch and

a second branch of distinctive colors, and wherein the semiconductor photo detector is located in the first branch, and wherein the focusing optical arrangement is located between the dichroic filter arrangement and the semiconductor photo detector so as to focus the beam of light onto the semiconductor photo detector. Thus, an effective detection arrangement may be provided, which may be operated with a semiconductor detector. The semiconductor detector may be a semiconductor photo detector. The semiconductor detector may be an avalanche photo diode or a carbon nanotube detector. Thus, a reduced signal to noise ratio can be achieved.

In first aspect of the disclosure, a flow cytometer includes a laser diode (LD) based optical subsystem for directing a beam of light into a viewing zone of said flow cytometer through which a sample liquid carrying particles flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, a composite microscope objective for imaging light scattered from and fluoresced by a particle present within the viewing zone, a fluidic subsystem for supplying the liquid sheath flow to the viewing zone, the liquid sheath flow lacking pulsations, a peristaltic pump for supplying the sample liquid carrying the particles, the sample liquid being hydrodynamically focused within the viewing zone by the liquid sheath flow, a peristaltic pump for supplying the sample liquid carrying the particles, the sample liquid being hydrodynamically focused within the viewing zone by the liquid sheath flow, and a wavelength division multiplexer (WDM) for separating into multiple colored bands a beam of light emitted initially from the viewing zone and imaged by the composite microscope objective into an optical fiber for transmission to the WDM. The LD based optical subsystem may include a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis, a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass through the viewing zone, a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath



flow, a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which particles pass through the viewing zone whereby said minor axis of said beam of light becomes focused at the viewing zone, and the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged. The composite microscope objective may include a concave mirror upon which scattered and fluoresced light impinges and an aberration corrector plate made of optically transparent material. The aberration corrector plate is an aspheric lens that has a first zone of said aberration corrector plate having negative optical power outside a neutral zone and a second zone of said aberration corrector plate inside the neutral zone having positive optical power light. The neutral zone is the thinnest portion of the aberration corrector plate. Light reflected from the concave mirror passes through said aberration corrector plate. The viewing zone of said flow cytometer is located between said concave mirror and said aberration corrector plate. The fluidic subsystem may include a liquid pump for supplying liquid drawn from a reservoir and a T-coupling having at least one (1) inlet and two (2) outlets. The inlet of said T-coupling receives liquid from said liquid pump. A first fraction of the liquid received by the inlet flows via a first one of the outlets and via a bypass conduit back to the reservoir. A second fraction of the liquid received by the inlet flows via a second one of the outlets and via a particle filter to the viewing zone of said flow cytometer. The peristaltic pump may include a pump housing having a arcuate curved track formed therein that extends between a pump inlet and a pump outlet, a plurality of rollers that are attached to a rotor, the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside said pump housing, and a compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing. The arcuate curved track includes an exit section and at least one pumping section along the arcuate curved track between the pump inlet and the pump outlet. As a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks contact with said compressible tube. Said compressible tube is compressed to fully closed by at least one of said rollers. The wavelength division multiplexer (WDM) may include a collimating optical element that

magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element, at least one dichroic filter located between said collimating optical element and said image, said dichroic filter separating the collimated beam of light into two (2) branches of distinctive colors, a focusing optical element located in one of said  
5 branches, the beam of light in said branch being focused to a spot having a diameter of less than 1.0 mm by said focusing optical element, and an image relay optical element located near the image produced by said collimating optical element in the other branch, said image relay optical element producing an image of said collimating optical element at substantially unit magnification.

10 In second aspect of the disclosure, said cuvette may have a rectangularly-shaped cross-section, and the viewing zone of the flow cytometer is located within a channel having a rectangularly-shaped cross-section that is located within said cuvette.

In third aspect of the disclosure, said cuvette may have a tubularly-shaped cross-section, and the viewing zone of the flow cytometer is located within a channel having a  
15 circularly-shaped cross-section that is located within said cuvette.

In fourth aspect of the disclosure, the sample liquid and the liquid sheath flow form a jet stream in which the viewing zone of the flow cytometer is located.

In fifth aspect of the disclosure, said cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

20 In sixth aspect of the disclosure, said cylindrical focusing element is separated from said rectangularly-shaped cuvette.

In seventh aspect of the disclosure, said cylindrical focusing element is separated from said tubularly-shaped cuvette.

In eighth aspect of the present disclosure, said cylindrical focusing element is  
25 separated from said jet stream.

In ninth aspect of the present disclosure, the flow cytometer further comprises a polarization conditioning element through which said collimated elliptical beam of light passes.

In tenth aspect of the present disclosure, an optical image of the viewing zone is formed outside the composite microscope objective.

In eleventh aspect of the present disclosure, the viewing zone is located within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

In twelfth aspect of the present disclosure, said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

In thirteenth aspect of the present disclosure, the plano-surface of said plano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

In fourteenth aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

In fifteenth aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In sixteenth aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In seventeenth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In eighteenth aspect of the present disclosure, the plano-concave back surface mirror formed integrally with said cuvette means.

In nineteenth aspect of the present disclosure, said aberration corrector plate is a plano-aspherical lens.

In twentieth aspect of the present disclosure, a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said plano-concave back surface mirror.

In twenty-first aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In twenty-second aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In twenty-third aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In twenty-fourth aspect of the present disclosure, the plano-aspherical lens is formed integrally with said cuvette.

5 In twenty-fifth aspect of the present disclosure, said aberration corrector plate is detached from said cuvette.

In twenty-sixth aspect of the present disclosure, the viewing zone is inside a jet stream.

10 In twenty-seventh aspect of the present disclosure, said concave mirror is a front surface mirror.

In twenty-eighth aspect of the present disclosure, the viewing zone is located on a surface of a flat, transparent substrate.

In twenty-ninth aspect of the present disclosure, said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

15 In thirtieth aspect of the present disclosure, the plano-surface of said plano-concave back surface mirror is optically coupled to said flat, transparent substrate.

In thirty-first aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

20 In thirty-second aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In thirty-third aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In thirty-fourth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

25 In thirty-fifth aspect of the present disclosure, said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

In thirty-sixth aspect of the present disclosure, said aberration corrector plate is detached from said flat, transparent substrate.

In thirty-seventh aspect of the present disclosure, the particle filter has inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so  
5 that air becomes trapped within the particle filter at the inlet thereto.

In thirty-eighth aspect of the present disclosure when said liquid pump is turned off air cannot enter into the bypass conduit.

In thirty-ninth aspect of the present disclosure, the flow cytometer further comprises a small capsule disposed between the second one of the outlets of said T-coupling and the  
10 particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

In fortieth aspect of the present disclosure, the flow cytometer further comprises a length of tubing disposed between the second one of the outlets of said T-coupling and the  
15 particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

In forty-first aspect of the present disclosure, the flow cytometer further comprises an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

In forty-second aspect of the present disclosure, the flow cytometer further  
20 comprises an adjustable valve located between the second one of the outlets of the T-coupling and the viewing zone for restricting liquid flow therebetween.

In forty-third aspect of the present disclosure, the throughput of the liquid pump is adjustable.

In forty-fourth aspect of the present disclosure, the arcuate curved track of said  
25 pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along the arcuate curved track, and said compressible tube at said recess section becoming decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

In forty-fifth aspect of the present disclosure, the peristaltic pump includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to the pump outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

In forty-sixth aspect of the present disclosure, said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

In forty-seventh aspect of the present disclosure, the peristaltic pump includes a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

In forty-eighth aspect of the present disclosure, both angular spacing between adjacent pairs of recess sections, and angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

In forty-ninth aspect of the present disclosure, shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

In fiftieth aspect of the present disclosure, a speed of said rotor is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

In fifty-first aspect of the present disclosure, at least one additional dichroic filter is located between said image relay optical element and the image produced by said image

relay optical element, said dichroic filter producing two (2) branches of the beam of light having distinctive colors.

In fifty-second aspect of the present disclosure, another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot  
5 having a diameter of less than 1.0 mm.

In fifty-third aspect of the present disclosure, wherein successive combinations of said image relay optical element, dichroic filter, and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

10 In fifty-fourth aspect of the present disclosure, the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

15 In fifty-fifth aspect of the present disclosure, the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM thereby providing consistent optical alignment when installing the dichroic filter into the WDM.

In fifty-sixth aspect of the present disclosure, the LD based optical subsystem  
20 includes a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis, a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass through the  
25 viewing zone, a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath flow, a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element  
30 being oriented perpendicular to the direction in which particles pass through the viewing

zone whereby said minor axis of said beam of light becomes focused at the viewing zone, and the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

5 In fifty-seventh aspect of the present disclosure, the optical subsystem may further comprise a cuvette having a rectangularly-shaped cross-section, and the viewing zone may be located within a channel having a rectangularly-shaped cross-section that is located within said cuvette.

10 In fifty-eighth aspect of the present disclosure, the optical subsystem further comprises a cuvette having a tubularly-shaped cross-section, and the viewing zone is located within a channel having a circularly-shaped cross-section that is located within said cuvette.

In fifty-ninth aspect of the present disclosure, the sample liquid and the liquid sheath flow form a jet stream in which the viewing zone is located.

15 In sixtieth aspect of the present disclosure, cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

In sixty-first aspect of the present disclosure, said cylindrical focusing element is separated from said rectangularly-shaped cuvette.

In sixty-second aspect of the present disclosure, said cylindrical focusing element is separated from said tubularly-shaped cuvette.

20 In sixty-third aspect of the present disclosure, said cylindrical focusing element is separated from said jet stream.

In sixty-fourth aspect of the present disclosure, the optical subsystem (50) further comprises a polarization conditioning element through which said collimated elliptical beam of light passes.

25 In sixty-fifth aspect of the present disclosure, a method for delivering an elliptically shaped beam of light using a LD based optical subsystem (50), the beam of light having a smooth profile at a focus of a minor axis thereof that is located at a viewing zone through which a sample liquid flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, the method



includes the steps of:

providing a LD that emits a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis, impinging the diverging beam of light emitted by the LD upon a collimating lens for converting the diverging beam of light emitted therefrom into a collimated elliptical beam of light wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which sample liquid passes through the viewing zone, after passing through said collimating lens, impinging the collimated elliptical beam of light upon an beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which sample liquid passes through the viewing zone becomes less than a width of said liquid sheath flow, and after passing through said beam compressing optical element, impinging the beam of light upon a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which sample liquid passes through the viewing zone whereby said minor axis of said beam of light becomes focused at the viewing zone, and the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

In sixty-sixth aspect of the present disclosure, the viewing zone is located within a channel having a rectangularly-shaped cross-section that is located within a cuvette.

In sixty-seventh aspect of the present disclosure, the viewing zone is located within a channel having a circularly-shaped cross-section that is located within a cuvette.

In sixty-eighth aspect of the present disclosure, the viewing zone is located within a jet stream.

In sixty-ninth aspect of the present disclosure, the method further comprises a step of establishing an optical contact between said cylindrical focusing element and an entrance face of said cuvette.

In seventieth aspect of the present disclosure, the method further comprises a step of establishing a spacing between said cylindrical focusing element and said cuvette.

In seventy-first aspect of the present disclosure, the method further comprises a step of establishing a spacing between said cylindrical focusing element and said cuvette.

In seventy-second aspect of the present disclosure, the method further comprise a step of establishing a spacing between said cylindrical focusing element and said jet stream.

5 In seventy-third aspect of the present disclosure, the method further comprises a step of inserting a polarization conditioning element between the collimating lens and the beam compressing optical element whereby the collimated elliptical beam of light passes through the polarization conditioning element.

10 In seventy-fourth aspect of the present disclosure, The composite microscope objective includes a concave mirror upon which scattered and fluoresced light impinges and an aberration corrector plate made of optically transparent material. The aberration corrector plate is an aspheric lens that has a first zone of said aberration corrector plate having negative optical power outside a neutral zone and a second zone of said aberration corrector plate inside the neutral zone having positive optical power light. The neutral zone  
15 is the thinnest portion of the aberration corrector plate. Light reflected from the concave mirror passes through said aberration corrector plate. The viewing zone of said flow cytometer is located between said concave mirror and said aberration corrector plate.

In seventy-fifth aspect of the present disclosure, an optical image of the viewing zone is formed outside the composite microscope objective.

20 In seventy-sixth aspect of the present disclosure, the viewing zone is located within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

In seventy-seventh aspect of the present disclosure, said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

25 In seventy-eighth aspect of the present disclosure, a plano-surface of said plano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

In seventy-ninth aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

In eightieth aspect of the present disclosure an index matching gel accomplishes the optical coupling.

In eighty-first aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

5 In eighty-second aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In eighty-third aspect of the present disclosure, the plano-concave back surface mirror formed integrally with said cuvette means.

10 In eighty-fourth aspect of the present disclosure, said aberration corrector plate is a plano-aspherical lens.

In eighty-fifth aspect of the present disclosure, a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said plano-concave back surface mirror.

15 In eighty-sixth aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In eighty-seventh aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In eighty-eighth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

20 In eighty-ninth aspect of the present disclosure, the plano-aspherical lens is formed integrally with said cuvette.

In ninetieth aspect of the present disclosure said aberration corrector plate is detached from said cuvette.

25 In ninety-first aspect of the present disclosure, the viewing zone is inside a jet stream.

In ninety-second aspect of the present disclosure, said concave mirror is a front surface mirror.

In ninety-third aspect of the present disclosure, the viewing zone is located on a surface of a flat, transparent substrate.

In ninety-fourth aspect of the present disclosure, said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

5 In ninety-fifth aspect of the present disclosure, a plano-surface of said plano-concave back surface mirror is optically coupled to said flat, transparent substrate.

In ninety-sixth aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

10 In ninety-seventh aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In ninety-eighth aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In ninety-ninth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

15 In one hundredth aspect of the present disclosure, said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

In one hundred first aspect of the present disclosure, said aberration corrector plate is detached from said flat, transparent substrate.

20 In one hundred second aspect of the present disclosure, a method for characterizing microscopic species using a microscope objective device includes a concave mirror, an aberration corrector plate made of optically transparent material, and a viewing zone located in between said concave mirror and said aberration corrector plate. The aberration corrector plate is an aspheric lens that has a first zone of said aberration corrector plate having negative optical power outside a neutral zone and a second zone of said aberration  
25 corrector plate inside the neutral zone having positive optical power light. The neutral zone is the thinnest portion of the aberration corrector plate.

In one hundred third aspect of the present disclosure, an optical image of the viewing zone is formed outside the device.

In one hundred fourth aspect of the present disclosure, the viewing zone is located within a flow channel contained in a rectangularly-shaped cuvette means made of optically transparent material.

5 In one hundred fifth aspect of the present disclosure, said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

In one hundred sixth aspect of the present disclosure, a plano-surface of said plano-concave back surface mirror means is optically coupled to a flat surface of said cuvette means.

10 In one hundred seventh aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

In one hundred eighth aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In one hundred ninth aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

15 In one hundred tenth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In one hundred eleventh aspect of the present disclosure the plano-concave back surface mirror is formed integrally with said cuvette.

20 In one hundred twelfth aspect of the present disclosure, said aberration corrector plate is a plano-aspherical lens.

In one hundred thirteenth aspect of the present disclosure, a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette means opposite of said concave mirror.

25 In one hundred fourteenth aspect of the present disclosure an index matching gel accomplishes the optical coupling.

In one hundred fifteenth aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

In one hundred sixteenth aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In one hundred seventeenth aspect of the present disclosure, the plano-aspherical lens is formed integrally with said cuvette.

5 In one hundred eighteenth aspect of the present disclosure, said aberration corrector plate is detached from said cuvette.

In one hundred nineteenth aspect of the present disclosure, the viewing zone is inside a jet stream.

10 In one hundred twentieth aspect of the present disclosure, said concave mirror is a front surface mirror.

In one hundred twenty-first aspect of the present disclosure, the viewing zone is located on a surface of a flat, transparent substrate.

In one hundred twenty-second aspect of the present disclosure said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

15 In one hundred twenty-third aspect of the present disclosure, a plano-surface of said plano-concave back surface mirror means is optically coupled to said flat, transparent substrate.

In one hundred twenty-fourth aspect of the present disclosure, an optical adhesive material accomplishes the optical coupling.

20 In one hundred twenty-fifth aspect of the present disclosure, an index matching gel accomplishes the optical coupling.

In one hundred twenty-sixth aspect of the present disclosure, an index matching fluid accomplishes the optical coupling.

25 In one hundred twenty-seventh aspect of the present disclosure, optical contact bonding accomplishes the optical coupling.

In one hundred twenty-eighth aspect of the present disclosure, said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

In one hundred twenty-ninth aspect of the present disclosure, said aberration corrector plate is detached from said flat, transparent substrate.

5 In one hundred thirtieth aspect of the present disclosure, a fluidic subsystem for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem includes a liquid pump for supplying liquid drawn from a reservoir and a T-coupling having at least one inlet and two outlets. The inlet of said T-coupling receives liquid from said liquid pump. A first fraction of the liquid received by the inlet flows via a first one of the outlets and via a bypass conduit back to the reservoir. A second fraction of the liquid received by the inlet flows via a second one of the outlets and via a particle filter to the viewing zone of said  
10 flow cytometer.

In one hundred thirty-first aspect of the present disclosure, the particle filter has an inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so that air becomes trapped within the particle filter at the inlet thereto.

15 In one hundred thirty-second aspect of the present disclosure, when said liquid pump is turned off air cannot enter into the bypass conduit.

In one hundred thirty-third aspect of the present disclosure, the fluidic subsystem further comprises a small capsule disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

20 In one hundred thirty-fourth aspect of the present disclosure, the fluidic subsystem further comprises a length of tubing disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

25 In one hundred thirty-fifth aspect of the present disclosure, the fluidic subsystem further comprises an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

In one hundred thirty-sixth aspect of the present disclosure, the fluidic subsystem further comprises an adjustable valve located between the second one of the outlets of the T-coupling and the outlet of the fluidic subsystem for restricting liquid flow therebetween.

In one hundred thirty-seventh aspect of the present disclosure, the throughput of the liquid pump is adjustable.

5 In one hundred thirty-eighth aspect of the present disclosure, a method for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem includes a liquid pump for supplying liquid drawn from a reservoir and a T-coupling having at least one (1) inlet and two (2) outlets. The inlet of said T-coupling receives liquid from said liquid pump. A first fraction of the liquid received by the inlet flows via a first one of the outlets and via a bypass conduit back to the reservoir. A second fraction of the liquid received by the inlet flows via a second one of the outlets and via a particle filter to the viewing zone of  
10 said flow cytometer.

In one hundred thirty-ninth aspect of the present disclosure, during normal operation certain amount of air is trapped near the inlet portion of said filter cartridge means.

In one hundred fortieth aspect of the present disclosure said reservoir means holds sufficient amount of liquid such that when said pump means is turned off, portion of the  
15 tubing between said T-coupling means and said reservoir means is still filled with liquid, preventing said trapped air from leaking into said bypass means.

In one hundred forty-first aspect of the present disclosure, said reservoir means is a capsule.

20 In one hundred forty-second aspect of the present disclosure, said reservoir means is a piece of tubing.

In one hundred forty-third aspect of the present disclosure an adjustable flow restrictor means is placed in the bypass route.

In one hundred forty-fourth aspect of the present disclosure an adjustable flow restrictor means is placed in the sheath route.

25 In one hundred forty-fifth aspect of the present disclosure, the throughput of the sheath pump is adjustable.

In one hundred forty-sixth aspect of the present disclosure, a peristaltic pump includes a pump housing having an arcuate curved track formed therein that extends between a pump inlet and a pump outlet, a plurality of rollers that are attached to a rotor,



the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside said pump housing, and a compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing. The arcuate curved track includes an exit  
5 section and at least one pumping section along the arcuate curved track between the pump inlet and the pump outlet. As a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks contact with said compressible tube. Said compressible tube is compressed to fully closed by at least one of  
10 said rollers.

In one hundred forty-seventh aspect of the present disclosure, the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section  
15 becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

In one hundred forty-eighth aspect of the present disclosure, the peristaltic pump includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to  
20 the pump outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

In one hundred forty-ninth aspect of the present disclosure, said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section  
25 of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

In one hundred fiftieth aspect of the present disclosure, the peristaltic pump has a plurality of recess sections respectively interspersed between immediately adjacent pairs of  
30 a plurality of pumping sections.

In one hundred fifty-first aspect of the present disclosure, both angular spacing between adjacent pairs of recess sections, and angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section are substantially the same as the angular spacing between each pair of immediately adjacent roller.

5 In one hundred fifty-second aspect of the present disclosure, shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

10 In one hundred fifty-third aspect of the present disclosure, a speed of said rotor is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

In one hundred fifty-fourth aspect of the present disclosure, a method for delivering  
15 liquid using a peristaltic pump includes a pump housing having a arcuate curved track formed therein that extends between a pump inlet and a pump outlet, a plurality of rollers that are attached to a rotor, the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside said pump housing, and a compressible tube sandwiched between  
20 said rollers and the arcuate curved track of said pump housing. The arcuate curved track includes an exit section and at least one pumping section along the arcuate curved track between the pump inlet and the pump outlet. As a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks  
25 contact with said compressible tube. Said compressible tube is compressed to fully closed by at least one of said rollers.

In one hundred fifty-fifth aspect of the present disclosure the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along  
30 the arcuate curved track, and wherein said compressible tube at said recess section becomes

decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

In one hundred fifty-sixth aspect of the present disclosure, the peristaltic pump includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet; The angular spacing between the compression part of said recess section adjacent to  
5 the pump outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

In one hundred fifty-seventh aspect of the present disclosure, said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of  
10 said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

In one hundred fifty-eighth aspect of the present disclosure, the pump has a plurality  
15 of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

In one hundred fifty-ninth aspect of the present disclosure, both angular spacing between adjacent pairs of recess sections, and angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section are substantially  
20 the same as the angular spacing between each pair of immediately adjacent roller.

In one hundred sixtieth aspect of the present disclosure, shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said  
25 rollers progressively rolls off said exit section of the arcuate curved track.

In one hundred sixty-first aspect of the present disclosure, a speed of said rotor of the peristaltic pump is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

In one hundred sixty-second aspect of the present disclosure, the wavelength division multiplexer (WDM) includes a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element, at least one dichroic filter located between said collimating optical element and said image, said dichroic filter separating the collimated beam of light into two (2) branches of distinctive colors, a focusing optical element located in one of said branches, the beam of light in said branch being focused to a spot having a diameter of less than 1.0 mm by said focusing optical element, and an image relay optical element located near the image produced by said collimating optical element in the other branch, said image relay optical element producing an image of said collimating optical element at substantially unit magnification.

In one hundred sixty-third aspect of the present disclosure, at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of the beam of light having distinctive colors.

In one hundred sixty-fourth aspect of the present disclosure, another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

In one hundred sixty-fifth aspect of the present disclosure, successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

In one hundred sixty-sixth aspect of the present disclosure, the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

In one hundred sixty-seventh aspect of the present disclosure, the reference surface of the filter holder rests against an optically flat surface of an reference block included in

the WDM thereby providing consistent optical alignment when installing the dichroic filter into the WDM.

In one hundred sixty-eighth aspect of the present disclosure, a method for separating beam of light into colored bands using a WDM includes a collimating optical element that  
5 magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element, at least one dichroic filter located between said collimating optical element and said image, said dichroic filter separating the collimated beam of light into two (2) branches of distinctive colors, a focusing optical element located in one of said branches, the beam of light in said branch being focused to a spot having a diameter of less  
10 than 1.0 mm by said focusing optical element, and an image relay optical element located near the image produced by said collimating optical element in the other branch, said image relay optical element producing an image of said collimating optical element at substantially unit magnification.

In one hundred sixty-ninth aspect of the present disclosure, at least one additional  
15 dichroic filter may be located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of beam of light having distinctive colors.

In one hundred seventieth aspect of the present disclosure, another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a  
20 spot having a diameter of less than 1.0 mm.

In one hundred seventy-first aspect of the present disclosure, successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

25 In one hundred seventy-second aspect of the present disclosure, the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

In one hundred seventy-third aspect of the present disclosure, the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM thereby providing consistent optical alignment when installing the dichroic filter into the WDM.

5           In one aspect of the disclosure, a flow cytometer having a wavelength division multiplexer (WDM), which includes an extended light source providing light that forms an object, a collimating optical element that captures light from the extended light source and projects a magnified image of the object as a first light beam, and a first focusing optical element configured to focus the first light beam to a size smaller than the object of the  
10       extended light source to a first semiconductor detector.

          In an additional aspect of the disclosure, a flow cytometer includes a viewing zone where a particle in a flow stream is illuminated by light, and a composite microscope objective. The composite microscope objective further includes a concave mirror configured to gather light scattered from or fluoresced by the illuminated particle and to  
15       reflect the light back towards the viewing zone, and an aberration corrector plate configured to reduce optical aberrations in the reflected light caused by the concave mirror.

          In an additional aspect of the disclosure, a flow cytometer having a fluidic system, which includes a liquid pump for supplying liquid drawn from a reservoir, and a T-coupling having at least one inlet and two outlets. The inlet of the T-coupling receives the liquid  
20       from the liquid pump. The first fraction of the liquid received by the inlet flows via a first one of the outlets and via a bypass conduit back to the reservoir. The second fraction of the liquid received by the inlet flows via a second one of the outlets and via a particle filter to the outlet of the fluidic system.

          In an additional aspect of the disclosure, a flow cytometer having a peristaltic pump,  
25       which includes a pump housing having an arcuate curved track formed therein that extends between a pump inlet and a pump outlet, a plurality of rollers that are attached to a rotor, the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside the pump housing, a compressible tube sandwiched between the rollers and the arcuate curved  
30       track of the pump housing, and a recess section located between the at least two pumping

sections. The compressible tube at the recess section is not fully closed. The arcuate curved track further includes an exit section and at least two pumping sections along the arcuate curved track between the pump inlet and the pump outlet. As one of the plurality of rollers rolls through the exit section, the compressible tube adjacent to the roller progressively expands from fully closed at a beginning of the exit section to fully open at the pump outlet where the roller breaks contact with the compressible tube. The compressible tube is compressed to fully closed by at least one of the plurality of rollers at the at least two pumping sections.

In an additional aspect of the disclosure, a flow cytometer having a laser diode (LD) system, which includes a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis, a collimating lens for converting the diverging beam of light emitted from the LD into a collimated elliptical beam of light, the minor axis of the collimated elliptical beam of light being oriented parallel to a direction in which particles pass through a viewing zone, a beam compressing optical element for reducing the size of the elliptical beam of light at the viewing zone whereby a width of the elliptical beam of light oriented perpendicular to the direction in which the particles pass through the viewing zone is less than a width of a liquid sheath flow, and a cylindrical focusing element positioned adjacent to the viewing zone with an axis of the cylindrical focusing element being oriented perpendicular to the direction in which the particles pass through the viewing zone whereby the minor axis of the elliptical beam of light becomes focused at the viewing zone; and the size of the major axis of the elliptical beam of light at the viewing zone remains essentially unchanged.

The foregoing has outlined rather broadly the features and technical advantages of the present application in order that the detailed description that follows may be better understood. Additional features and advantages will be described hereinafter which form the subject of the claims. It should be appreciated by those skilled in the art that the conception and specific aspect disclosed may be readily utilized as a basis for modifying or designing other structures for carrying out the same purposes of the present application. It should also be realized by those skilled in the art that such equivalent constructions do not depart from the spirit and scope of the present application and the appended claims. The

novel features which are believed to be characteristic of aspects, both as to its organization and method of operation, together with further objects and advantages will be better understood from the following description when considered in connection with the accompanying figures. It is to be expressly understood, however, that each of the figures is  
5 provided for the purpose of illustration and description only and is not intended as a definition of the limits of the present claims.

### **BRIEF DESCRIPTION OF THE DRAWINGS**

FIG. 1 is a diagram schematically illustrating an embodiment of a flow cytometer in  
10 accordance with the present disclosure that includes:

- a) a LD based optical illumination subsystem;
- b) a composite microscope objective upon which light emitted from the LD based optical illumination subsystem impinges, the composite microscope objective having a fluid-passing channel formed therethrough with a particle illumination viewing zone  
15 located inside a cuvette thereof;
- c) a fluidic system for supplying a pulsation free flow of sheath liquid to the fluid-passing channel formed through the composite microscope objective;
- d) a peristaltic pump for introducing a pulsation free flow of sample liquid that carries cells or particles to be analyzed into the sheath flow of liquid supplied by the fluidic  
20 system; and
- e) a wavelength division multiplexer ("WDM") having a zig-zag configuration for separating a beam of light into several different colored bands, the WDM receiving light via an optical fiber that is scattered from cells or particles as they pass through the composite microscope objective's fluid passing channel and are illuminated therein by light  
25 emitted from the LD based optical illumination subsystem.

FIG. 2 is a schematic view depicting a typical high power edge emitting LD that illustrates the fast and slow axes of light emitted therefrom.

FIG. 2A shows a typical far field profile for a laser beam emitted from the LD chip depicted in FIG. 2.



FIG. 3A depicts a 3-dimensional view of a conventional LD based optical illumination subsystem for flow cytometric instruments together with the system's flow cell.

5 FIG. 3B depicts a typical time dependent profile of light scattering from a cell or particle passing through the laser beam depicted in FIG. 3A at the focus thereof within the system's flow cell.

FIG. 4A is an elevational view of an alternative prior art LD based optical illumination subsystem configuration across the liquid flowing through the fluid-passing channel with the beam profile at the focus thereof in the flow cytometer system's viewing  
10 zone.

FIG. 4B is a plan view along the liquid flowing through the fluid-passing channel of the alternative prior art LD based optical illumination subsystem depicted in FIG. 4A.

FIG. 5A is an elevational view across liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1, wherein the LD's slow axis oriented transversely to the liquid flow in accordance with one aspect of the present disclosure.  
15

FIG. 5B is a plan view along liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1, wherein the LD's slow axis oriented transversely to the liquid flow in accordance with one aspect of the present disclosure.

20 FIG. 5C depicts a typical time dependent profile of light scattering from a cell or particle passing through the fluid passing channel of the composite microscope objective depicted in FIG. 1.

FIG. 5D depicts a perspective view of the cylindrical lens of the LD based optical subsystem coupled with the composite microscope objective in accordance with one aspect  
25 of the present disclosure.

FIG. 5E depicts an enlarged view of the beam profile shown in FIG. 5D.

FIG. 6 is a perspective view of an alternative embodiment of a LD based optical illumination subsystem in accordance with one aspect of the present disclosure adapted for

use in a flow cytometer system in which a jet stream of liquid passes through the viewing zone.

FIG. 6A is an enlarged perspective view of the alternative embodiment of a LD based optical illumination subsystem of Fig. 6 depicting in greater detail the jet stream of liquid passes through the viewing zone.

FIG. 7 is a perspective view of an alternative embodiment of a LD based optical illumination subsystem in accordance with one aspect of the present disclosure adapted for use in a flow cytometer system which orients the LD's slow axis parallel to the direction of liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1.

FIG. 8 is a perspective view of a composite microscope objective in accordance with one aspect of the present disclosure adapted for use in the flow cytometer system depicted in FIG. 1, the composite microscope objective having a fluid-passing channel formed therethrough with the particle illumination viewing zone located inside a cuvette therein.

FIG. 8A is a perspective view of a combined microscope objective in accordance with one aspect of the present disclosure.

FIG. 8B illustrates the combined microscope objective depicted in FIG. 8A coupled with a flow cell in accordance with one aspect of the present disclosure.

FIG. 9A is a cross-sectional elevational view of the composite microscope objective taken along the line 9A-9A in FIG. 8 that includes ray traces from three (3) spatially separated locations in the viewing zone to an image plane for the objective illustrating scatter and fluorescence emission propagation.

FIGs. 9B1-9B3 are spot diagrams near the image plane depicted in FIG. 9A for the three (3) spatially separated light emission locations depicted in FIG. 9A.

FIG. 10 is a cross-sectional elevational view similar to that of FIG. 9A for an alternative embodiment composite microscope objective in accordance with one aspect of the present disclosure that includes ray traces from three (3) spatially separated locations in

a viewing zone therein to an image plane for the objective illustrating scatter and fluorescence emission propagation.

FIG. 11 is a perspective view of yet another alternative embodiment a composite microscope objective in accordance with one aspect of the present disclosure adapted for use in the flow cytometer system depicted in FIG. 1, the alternative embodiment composite microscope objective having a fluid-passing channel formed therethrough with the particle illumination viewing zone located inside a cuvette therein.

FIG. 12 is a perspective view of an embodiment of a composite microscope objective in accordance with one aspect of the present disclosure adapted for use in the flow cytometer system depicted in FIG. 1, adapted for use wherein a viewing zone is located inside the jet stream depicted in FIGs. 6 and 6A.

FIG. 13 is a perspective view of an embodiment of a composite microscope objective in accordance with one aspect of the present disclosure adapted for use wherein a viewing zone is located on the surface of a microscope slide.

FIG. 14 is a schematic diagram depicting a fluidic system in accordance with one aspect of the present disclosure for supplying stable liquid sheath flow to a flow cytometer flow cell that includes:

1. a small capsule located between a sheath liquid pump and the flow cell; and
2. a particle filter located between the small capsule and the flow cell, both the particle filter and the small capsule providing air reservoirs for dampening pump pulsations.

FIG. 15 is a schematic diagram depicting an embodiment of a fluidic subsystem similar to that illustrated in FIG 14 that replaces the small capsule with a length of tubing for providing an air reservoir.

FIGs. 16A and 16B are histograms that compare measured particle flight times at the flow cell when the inlet portion of the particle filter has air trapped therein (FIG. 16A), and when there is no air within the fluidic subsystem between the sheath liquid pump and the flow cell (FIG. 16B).

FIG. 17 is a perspective view of a 3-roller peristaltic pump in accordance with one aspect of the present disclosure depicting the pump's rollers, tube and surrounding pump housing.

FIGs. 18A through 18D depict simplified views for several states of the 3-roller peristaltic pump depicted in FIG. 17 with the rollers in different locations.

FIGs. 19 is a detailed longitudinal cross-sectional view of the peristaltic pump's tube being partially compressed by the pump's roller.

FIG. 19A and 19B are detailed cross-sectional views orthogonal to the peristaltic pump's tube's length taken along the lines 19A and 19B in FIG. 19 illustrating the tube's partial compression by the roller.

FIGs. 20A and 20B are schematic diagrams illustrating the pump's rollers and tube viewed along the pump's circular coordinates to depicting the pulseless flow provided by the peristaltic pump.

FIG. 21 is a graph depicting the functional relationship with respect to the roller position when it rolls off the exit section of the compressible tube of:

1. the total volume of liquid in the exit half of the pump; as well as
2. the liquid volumes in the pump's:
  - a. recess section; and
  - b. exit section.

FIG. 22 is a simplified plan view of a 4-roller peristaltic pump in accordance with one aspect of the present disclosure.

FIG. 23 is a simplified plan view of a 6-roller peristaltic pump in accordance with one aspect of the present disclosure.

FIG. 24A is a longitudinal cross-sectional illustration of rollers and a compressible tube for a pulsation minimizing 3-roller peristaltic pump in accordance with one aspect of the present disclosure having a rotor with programmable speed.

FIG. 24B is simplified plan view illustrating the pulsation minimizing 3-roller peristaltic pump in accordance with one aspect of the present disclosure having a rotor with programmable speed.

FIG. 24C is a graph depicting for the pulsation minimizing peristaltic pump depicted in FIG. 24B having a programmable speed rotor:

1. negative volume change rate with respect to the roller position;
2. rotor speed; and
- 5 3. pump flow rate.

FIG. 25 is a diagram illustrating optical ray tracing for an exemplary 6 port wavelength division multiplexer ("WDM") using a zig-zag configuration in accordance with one aspect of the present disclosure.

FIG. 25A illustrates a top view of a light detection assembly of the WDM  
10 illustrated in FIG. 25 in accordance with one aspect of the present disclosure.

FIG. 25B illustrates a front perspective view of the light detection assembly of the WDM illustrated in FIGs. 25 and 25A.

FIG. 26 is a diagram illustrating ray tracing of prior art collimating devices showing the device's limitation in collimating an extended light source.

15 FIG. 27 is a perspective illustration of an embodiment of a 6 port WDM using a combination of zig-zag and branched configurations in accordance with one aspect of the present disclosure.

FIG. 28 is a perspective illustration of another embodiment of a WDM having concave dichroic filters in accordance with one aspect of the present disclosure.

20 FIGs. 29A and 29B are perspective illustrations depicting an assembly process for constructing a replaceable dichroic filter assembly for a reconfigurable WDM in accordance with the present disclosure.

FIG. 29C is a perspective illustration of a replaceable dichroic filter assembly build in accordance with the illustrations of FIGs. 29A and 29B.

25 FIGs. 30A and 30B are perspective illustrations of a WDM in accordance with one aspect of the present disclosure depicting installing into the WDM the replaceable dichroic filter assembly depicted in FIG. 29C and its removal therefrom.

FIG. 31 is a diagram schematically illustrating an optical system with a single light source in accordance with one aspect of the present disclosure.

FIG. 32 is a diagram schematically illustrating an optical system with multiple light sources in accordance with one aspect of the present disclosure.

FIG. 33 illustrates an enlarged view of beams of light shown in FIG. 32.

FIG. 34 is a diagram schematically illustrating an optical system with chromatic compensation elements in accordance with one aspect of the present disclosure.

FIG. 35 is a diagram schematically illustrating a power monitoring system in accordance with one aspect of the present disclosure.

FIG. 36 is a diagram schematically illustrating an optical system in accordance with one aspect of the present disclosure.

FIG. 37 is a diagram schematically illustrating an axial light loss detection system in accordance with one aspect of the present disclosure.

FIG. 38 is a diagram schematically illustrating an axial light loss detection system coupled with a second light detection system in accordance with one aspect of the present disclosure.

## DETAILED DESCRIPTION

### Flow Cytometer

A flow cytometer system may include one or more following components.

1. A flow cell through which a liquid stream, usually called a sheath flow, carries and hydrodynamically aligns cells or particles so that they pass single file through the flow cell.

2. A measuring subsystem system coupled to the flow cell that detects cells or particles passing through the flow cell and is usually either:

- a. an impedance or conductivity measuring subsystem; or
- b. an optical illumination subsystem together with an optical sensing subsystem.

3. A conversion subsystem for converting the output signal from the measuring subsystem into computer processable data.

4. A computer for analyzing the data produced by the conversion subsystem.

The optical illumination subsystem provides a collimated and then focused beam of light, usually laser light of a single wavelength, that impinges upon the hydrodynamically-focused stream of liquid passing through the flow cell. Accordingly, the flow cytometer system may have one or more light sources that may include:

1. one or more lamps, e.g., mercury or xenon;
2. one or more high-power water-cooled lasers, e.g., argon, krypton or dye laser;
3. one or more low-power air-cooled lasers, e.g., argon (488 nm), HeNe (red-633 nm), HeNe (green) and HeCd (UV); and/or
4. one or more diode lasers (blue, green, red and violet).

The optical sensing subsystem includes one or more detectors aimed where the focused liquid stream passes through the light beam. Such detectors may include:

1. detectors in line with the light beam (Forward Scatter or FSC);
2. detectors perpendicular to it (Side Scatter or SSC); and
3. fluorescence detectors.

Each suspended particle passing through the beam scatters the light, and fluorescent material present in the particle or attached to the particle excited by the impinging light emit light at a longer wavelength than that of the impinging light.

Detecting and analyzing brightness changes in a combination of scattered and fluorescent light at each detector (one for each fluorescent emission peak) permits deriving various types of information about the physical and chemical structure of each individual particle. FSC correlates with cell volume. Due to light being scattered off of internal components within a cell, SSC depends on the inner complexity of the particle (i.e., shape of the nucleus, the amount and type of cytoplasmic granules or the membrane roughness). Some flow cytometers omit a fluorescence detector and detect only scattered light. Other flow cytometers form images of each cell's fluorescence, scattered light, and transmitted light. The flow cytometer system's conversion subsystem, which may include one or more amplifiers which may be either linear or logarithmic, generally includes one or

more Analogue-to-Digital Converters ("ADCs") for converting the measuring subsystem's output signal into data that is then processed by the computer.

Modern flow cytometers usually include up to four (4) lasers and numerous fluorescence detectors. Increasing the number of lasers and detectors permits labeling cells with several different antibodies, and can more precisely identify a target population by their phenotypic markers. Some instruments can even capture digital images of individual cells, allowing for the analysis of a fluorescent signal location within or on the surface of cells.

FIG. 1 depicts a flow cytometer in accordance with one aspect of the present disclosure identified by the general reference number 40. The flow cytometer 40 may include:

1. a LD based optical subsystem 50;
2. a composite microscope objective 60;
3. a fluidic subsystem 70 for supplying a liquid sheath flow;
4. a peristaltic pump 80 for injecting a liquid sample flow that contains particles to be analyzed into the liquid sheath flow supplied by the fluidic subsystem 70, the liquid sample flow becoming hydrodynamically focused by the liquid sheath flow passes through a viewing zone with the composite microscope objective 60 gathering and imaging light scattered and/or fluoresced by particles in the viewing zone;
5. an optical fiber 852 that receives light scattered and/or fluoresced by particles in the viewing zone that the composite microscope objective 60 gathers and images;
6. a wavelength division multiplexer 90 ("WDM 90") for optically processing scattered and/or fluoresced light received from the optical fiber 852; and
7. a photodetector system 938 to detect the light processed by the WDM 90.

### **Optical Subsystem 50**

In most of the instruments, particles of interest, such as blood cells or microspheres, are carried by the sheath flow using hydrodynamic focusing into a viewing zone inside a



cuvette or jet stream and illuminated there by a focused laser beam. The technique provides the means to accurately identify and count particles of interest without being overwhelmed by background noise occurring outside a registration time window (Practical Flow Cytometry, Howard M. Shapiro, Wiley (2003) ISBN 0471411256). To increase detection  
5 sensitivity, the cross section of the focused laser beam is usually elliptical, with the minor axis along the direction of flow. In order to maintain the threshold integrity, the laser profile must have a smooth or bell shaped profile along the flow direction. One common method for producing such a beam is to elongate a 5 nearly collimated circular Gaussian beam along the direction of flow with a beam expander made of either prism or cylindrical  
10 lens pair, then focus the beam down with a spherical lens. Since the shape of the beam at the focus is the spatial Fourier transform of the beam at far field, this produces a Gaussian shaped elliptical spot with minor axis along the flow.

Conventional lasers are expensive, bulky and power hungry. More recently, laser diodes ("LD") have become available. Differing from conventional lasers, the new  
15 generation of LDs is cost effective, compact and power efficient, and shows great promise for new generation of compact biomedical instruments. A LD emits light having an elliptical cross-section with the ellipse's major axis, frequently called the fast axis, perpendicular to the LD's junction, and the ellipse's minor axis, frequently called the slow axis, parallel to the LD's junction. Unfortunately, the beam quality of a typical LD,  
20 particularly along its fast axis, leaves much to be desired, preventing its wide acceptance in flow cytometric applications.

In principle, the quality of the LD beam can be significantly improved by spatial filtering. If a small pinhole or a single mode optical fiber is positioned at the focal point of a lens, such that it only accepts the lowest order spatial mode, the beam passing through the  
25 pinhole or single mode optical fiber will be of nearly perfect Gaussian shape. United States Patent no. 5,788,927 discloses that such a beam can then be collimated and expanded in the direction of flow through the cytometer, and finally focused down to an elliptical shaped Gaussian beam with minor axis along the flow direction. Unfortunately, the size of desktop instrumentation limits the diameter of a pinhole to less than 5 micron. The core size of a  
30 visible wavelength single mode optical fiber also has a similar dimension. The challenge to

manufacture such a precision spatial filter and maintain its long-term stability not only increases the cost of LD based laser system, but also reduces its reliability.

More recently, in an effort to reduce the possible side lobes due to the edge effect of limited numerical aperture of collimating lens, United States Patent no. 6,713,019 (“the ‘019 patent”) discloses rotating the LD by ninety degrees (90°) such that its slow axis is parallel to the direction of flow. A beam diffusing section, such as a concave cylindrical lens, is then introduced to diffuse the collimated beam in the direction perpendicular to the flow, followed by a beam spot forming section, such as a spherical focusing lens, to form an elliptical spot within the cytometer's particle viewing zone. As described in detail in the ‘019 patent, the laser beam after the spot forming section is extremely astigmatic. In particular, the width of the beam at the viewing zone in the direction perpendicular to the flow is comparable or even wider than the width of the flow channel. This not only reduces the amount of laser energy impinging upon the particle and consequently the signal intensity, but also increases undesired background scattering from the liquid-flow cell interface. Instead of rotating the LD, United States Patent nos. 7,385,682 and 7,561,267 disclose using a large numerical aperture aspheric lens for LD collimation. Such a design, however, cannot correct the fringe effect inherent in the LD’s beam profile. Consequently, there presently exists a need for a simple LD based optical system for use in flow cytometers that can reliably produce a focused elliptical beam with near Gaussian shape along its minor axis and a width along major axis.

In accordance with one aspect of the present disclosure, the optical subsystem 50 may include a LD 501 that, as depicted in greater detail in FIG. 2, emits a diverging beam of light from an edge thereof. As more graphically depicted in FIGs 2 and 2A, the diverging beam of light has an elliptically shaped cross-sectional profile with both a major axis, a.k.a. the fast axis, and a minor axis, a.k.a. the slow axis. The diverging beam of light emitted from the LD 501 may impinge upon a collimating lens 502 which converts the diverging beam of light emitted by LD 501 into a collimated beam of light having an elliptical cross-section. Although not essential, the optical subsystem 50 may also include an optional mirror 503 positioned to direct the collimated elliptical beam of light towards the composite microscope objective 60. A plano-convex lens 504, positioned near the composite microscope objective 60, may reduce the major axis of the elliptically shaped beam of light

that is oriented perpendicular to the direction in which the liquid sample and the surrounding liquid sheath flow through the viewing zone within the composite microscope objective 60. At the viewing zone, the width of the elliptically shaped beam of light:

1. perpendicular to the direction in which the liquid sample flow passes through the viewing zone may be slightly less than the width of the liquid sheath flow; while

2. still sufficiently wide so particles in the sample flow pass through a nearly flat portion of the elliptically shaped beam of light at the beam's maximum intensity.

In accordance with one aspect of the present disclosure, it is apparent to those skilled in the art that the plano-convex lens 504 may be replaced by other types of optical elements such as an achromatic doublet lens or combination of spherical lenses, cylindrical lenses, and/or prism pairs. Alternatively, the mirror 503 and the lens 504 may also be replaced by a concave mirror. For polarization sensitive applications of the flow cytometer 40, an optional polarization conditioning element, such as a half-wave plate, may also be placed in the collimated section of the beam of light extending from the collimating lens 502 to the lens 504. Finally, before passing through the viewing zone the beam of light may pass through a high power cylindrical lens 505, positioned adjacent to the viewing zone. As depicted in FIG. 1, the axis of the cylindrical lens 505 is oriented perpendicular to the direction in which the liquid sample flow passes through the viewing zone, and the focal length of the cylindrical lens 505 produces a tight focusing of the beam of light's minor axis at the viewing zone.

An advantage of the optical subsystem 50 in comparison with conventional LD based optical subsystem may be discerned more clearly in FIGs. 2 and 2A. Most commercially available laser diodes suitable for use in a flow cytometer emit a beam of light from an edge thereof. As depicted in FIG. 2, a gain section 509 of such a LD chip 510 is highly confined in the transverse direction indicated by an arrow 511. Consequently, to achieve high output power LD manufacturers often sacrifice beam quality, particularly along the transverse or fast axis direction that is oriented parallel to the arrow 511. FIG. 2A shows this characteristic of light emitted from a LD wherein multiple fringes 512 due to gain confinement are clearly visible at the far field in the minor axis direction of the emitted beam of light. It should be noted that the fringes 512 appearing in the illustration of FIG.

2A contain only a minor amount of total energy in the beam of light, and therefore have little impact on the conventional M-square characterization of the corresponding beam profile. However, as discussed in greater detail below, the fringes 512 do have a detrimental effect on the performance of conventional flow cytometers. Alternatively, gain  
5 confinement along the slow axis direction of an edge emitting LD that is oriented perpendicular to the arrow 511 is much more relaxed. Consequently, as shown in FIG. 2A, the far field beam profile is much smoother along the slow axis of the LD's beam of light.

FIG. 3A depicts a conventional LD based optical subsystem for a flow cytometer. Those elements depicted in FIG. 3A that are common to the optical subsystem 50  
10 illustrated in FIG. 1 carry the same reference numeral distinguished by a prime (') designation. As depicted in FIG. 3A, the conventional optical subsystem orients the fast axis of the LD 501 parallel to the direction in which the liquid sample flow passes through the viewing zone. In its most simplified configuration, the elliptical beam profile of the LD 501' is directly transposed by the spherical focusing lens 504' into the viewing zone. In an  
15 attempt to achieve optimal aspect ratio for the focused beam of light, various different conventional LD based optical subsystems have also included beam shaping optical elements in addition to those depicted in FIG. 3A.

The detrimental effect of fringes 512 along the fast axis of the LD 501' for conventional optical subsystem configurations clearly appears in the light scattering time  
20 profile depicted in FIG. 3B. Since scattering or fluorescence intensity is directly proportional to the local laser power impinging upon a particle, any fine structure in the beam of light's profile along the direction in which the liquid sample flow passes through the viewing zone will appear in the time profile of the signal produced by the flow cytometer. Such structures in the time profile are indistinguishable from signals generated  
25 by small particles, and will therefore cause the flow cytometer to trigger falsely and misidentify particles. In addition, the fringes 512 will also lead to uncertainty in the measurement of other cytometric parameters, such as in the area and width of the pulse depicted in FIG. 3B.

FIGs. 4A and 4B depict a yet another prior art optical subsystem for LD based flow  
30 cytometric applications disclosed in the '019 patent identified previously. Those elements

depicted in FIGs. 4A and 4B that are common to the optical subsystem 50 illustrated either in FIG. 1 or 3A carry the same reference numeral distinguished by a double prime (") designation. As depicted in FIGs. 4A and 4B, by orienting the slow axis of the LD 501" parallel to the direction in which the liquid sample flow passes through the viewing zone the optical subsystem depicted in FIGs. 4A & 4B effectively overcomes the problem caused by the fringes 512 as described above. Unfortunately, the beam-diffusing element 513" placed before the spherical focusing lens 504" in FIGs. 4A and 4B to diffuse the beam of light perpendicular to the direction in which the liquid sample flow passes through the viewing zone produces a highly astigmatic beam of light near the viewing zone. Specifically, focusing this astigmatic beam of light at the viewing zone in the direction in which the liquid sample flow passes through the viewing zone increases the width of the beam of light perpendicular to the direction in which the liquid sample flow passes through the viewing zone so the beam's width become similar to or even wider than the sheath flow. Consequently, the optical subsystem depicted in FIGs. 4A and 4B not only diminishes the amount of light energy impinging upon particles flowing through the viewing zone, the optical subsystem also increases undesirable scattering of light from the interface between the liquid sheath flow and adjacent parts of the composite microscope objective 60.

FIG. 5 highlights the main differences between the optical subsystem disclosed in the '019 patent and the optical subsystem 50 depicted in FIG. 1. Instead of placing an out-of-plane beam-diffusing element 513" before the spherical beam focusing lens 504 as shown in FIG. 4, the high power cylindrical lens 505, depicted in FIGs. 5A and 5B as a cylindrical plano-convex lens, may be placed along the beam of light after the spherical beam focusing lens 504 and may be juxtaposed with the composite microscope objective 60. As shown in FIGs. 5A and 5B, the cylindrical lens 505 may focus the minor axis of the beam of light in the viewing zone while leaving the major axis of the beam of light essentially unchanged. Consequently, the optical subsystem 50 depicted in FIGs. 1, 5A and 5B may establish a beam of light profile at the viewing zone which is elliptical with:

1. a tightly focused minor axis that spans across the combined liquid sample and sheath flows; and

2. a smooth minor axis profile in the direction of the combined liquid sample and sheath flows that is the Fourier conjugate of the far field beam profile along the slow axis of LD 501.

Meanwhile, as shown in FIG. 5B, the out-of-plane beam width may be unaffected by the cylindrical lens 505. FIG. 5C shows a measured time profile of light scattered from a micro particle using the optical subsystem 50 depicted in FIGs. 1, 5A and 5B. The LD 501 used in making the measurement presented in FIG. 5C is the same as that used in generating the measured time profile of light scattered from a micro particle appearing in FIG. 3B. As shown in FIG. 5C, the side lobes caused by the fringes 512 along the fast axis of the LD 501 no longer have any material effect on performance of the flow cytometer 40.

FIG. 5D illustrates a perspective view of the cylindrical lens 505 of the LD based optical subsystem 50 coupled with the composite microscope objective 60 in accordance with some embodiments of the present disclosure. A beam of light may pass through the cylindrical lens 505 and a cuvette 603 of the microscope objective 60 substantially along the z axis and establish a beam profile 524 on a x-y plane at the viewing zone inside a flow channel 604 of the composite microscope objective 60.

FIG. 5E illustrates an enlarged view of the beam profile 524 shown in FIG. 5D in accordance with some embodiments of the present disclosure. FIG. 5E shows that the minor axis of the beam of light may be along the y axis and substantially parallel to the direction of liquid sample and sheath flows and the major axis of the beam of light may be along the x axis and substantially perpendicular to the direction of liquid sample and sheath flows.

FIG. 6 depicts yet another alternative diode laser based optical subsystem in accordance with some embodiments of the present disclosure adapted for use in a flow cytometer. Those elements depicted in FIGs. 6 and 6A that are common to the optical subsystem 50 illustrated in FIGs. 1, 5A and 5B carry the same reference numeral distinguished by a triple prime ("") designation. The optical subsystem 50''' depicted in FIGs. 6A and 6B is almost identical to that shown in FIGs. 1, 5A and 5B except that the viewing zone occurs without a composite microscope objective 60 because it occurs in a free-flowing jet stream 519 that includes both the sample and sheath flows that is emitted

from a nozzle 518. Consequently, for the configuration of the optical subsystem 50''' depicted in FIGs. 6A and 6B, the high power cylindrical lens 505 is detached from the viewing zone that is located within the jet stream 519.

In the exemplary embodiments of the present disclosure depicted in FIGs. 1, 5A, 5B, 6A and 6B, the minor axis, i.e. the slow axis, of the LD 501 is substantially oriented perpendicular to the direction in which the liquid sample flow passes through the viewing zone. However, it will be apparent to those skilled in the art that using an alternative optical configuration the major axis, i.e. the fast axis, of the LD 501 may be reoriented to be perpendicular to the direction in which the liquid sample flow passes through the viewing zone. FIG. 7 depicts one example of such an alternative configuration of optical elements. Those elements depicted in FIG.7 that are common to the optical subsystem 50 illustrated in FIGs. 1, 5A, 5B, 6A and 6B carry the same reference numeral distinguished by a quadruple prime ('''') designation. As shown, the slow axis of the LD 501''' is oriented in the z-direction. The beam of light emitted from the LD 501''' is then rotated to the in-plane y-direction by a pair of ninety degrees (90°) reflection mirrors 523a and 523b. In the illustration of FIG. 7, a normal to the first elliptically-shaped light beam reorienting mirror 523a is oriented in the x-y plane at forty-five degrees (45°) to the x-axis, and a normal to the second elliptically-shaped light beam reorienting mirror 523b is oriented in the y-z plane at forty-five degrees (45°) to the z-axis.

## **Composite Microscope Objective 60**

Modern flow cytometers include a spatial filter, usually either a mechanical pinhole or a large core optical fiber, located at an image location of an objective lens to prevent undesired background light from entering the cytometer's detector(s). Because particles remain in the cytometer's viewing zone for a few microseconds, microscope objectives with large numerical aperture must be used to maximize light collection efficiency. To support multiple spatially separated excitation laser beams in flow cytometers, as disclosed in United States Patent No. 4,727,020, it is also desirable to use an objective with large field of view. In order to achieve these goals, United States Patent Nos. 6,510,07 and 7,110,192 disclose an objective design using a modified apochromat with a gel-coupled or epoxy bonded near hemisphere lens as the optical element closest to the sample that is followed

by multiple meniscus lenses. While such microscope objectives provide both a satisfactory numerical aperture and field of view, they significantly sacrificed image quality thereby:

1. limiting effective use of the spatial filter; and
2. exhibiting poor background light discrimination.

5 Further, such refractive microscope objectives are bulky, expensive to manufacture and often exhibit severe chromatic aberration. To overcome these limitations, Published Patent Cooperation Treaty ("PCT") Patent Application No. WO 01/27590 discloses an alternative objective design based on a spherical concave mirror. The design offers large numerical aperture and good image quality along the optical axis. However, due to its poor  
10 off-axis characteristics, such a design is unsuitable for flow cytometers having multiple, spatially separated laser beams.

FIG. 8 depicts one embodiment in accordance with the present disclosure for the composite microscope objective 60 depicted in FIGs. 1, 5A, 5B and 7. As depicted in FIG. 8, the composite microscope objective 60 may image a viewing zone that is located inside a  
15 prismatically-shaped glass cuvette 603 within a small flow channel 604, that may have a rectangular cross-sectional shape, through which passes the particle carried by combined liquid sample and sheath flows. A plano-concave back-surface mirror 601 included in the composite microscope objective 60 may be made of an optically transparent material that may have a refractive index similar to that of the glass cuvette 603, such as glass or optical  
20 quality plastics. To minimize optical loss, the back-surface mirror 601 may include a flat front surface that is optically coupled to an abutting flat surface of the prismatically-shaped cuvette 603. Optical coupling of the back-surface mirror 601 to the cuvette 603 may employ an index-matching gel, optical adhesive or direct optical bonding. Alternatively, the back-surface mirror 601 may also be formed integrally with the cuvette 603.

25 The composite microscope objective 60 may also include a plano-aspheric corrector plate 602 that is also made of an optically transparent material that may have a refractive index similar to that of the glass cuvette 603, such as glass or optical quality plastics. To reduce optical loss, a flat surface of the corrector plate 602 may be optically coupled to an abutting flat surface of the prismatically-shaped cuvette 603 on a face thereof that is  
30 diametrically opposite to the back-surface mirror 601. Optical coupling of the corrector



plate 602 to the cuvette 603 may employ an index-matching gel, optical adhesive or direct optical bonding. The aspheric surface of the corrector plate 602 furthest from the corrector plate 602 may carry an anti-reflective coating to reduce optical transmission loss, although such a coating is not a mandatory requirement for a composite microscope objective 60 in accordance with some embodiments of the present disclosure. The shape of the aspheric surface of the corrector plate 602 is similar to that in a classical Schmidt camera, (Schmidt, B., *Mitt. Hamburg Sternwart* 7 (36) 1932). As known by those skilled in the art, the corrector plate of a Schmidt camera includes a circularly shaped neutral zone where the corrector plate does not deviate rays of light passing through the plate. For use in the composite microscope objective 60, outside of the neutral zone of the corrector plate 602, where the plate thickness is thinnest, the corrector plate 602 may have negative optical power while inside the neutral zone the corrector plate 602 may have positive optical power. The exact shape of the aspheric corrector plate 602 may be readily obtained using any commercially available optical ray tracing tool by any person having ordinary skill in the art. Note that in the flow cytometer 40, the beam of light generated by the optical subsystem 50 depicted in FIGs. 1, 5A, 5B and 7 enters the cuvette 603 perpendicularly to the flow channel 604 through one (1) of the two (2) faces of the cuvette 603 that do not abut the back-surface mirror 601 or corrector plate 602.

## 20 **Combined Microscope Objective 65**

FIG. 8A illustrates a perspective view of a combined microscope objective 65 in accordance with some embodiments of the present disclosure. The combined microscope objective 65 may include the composite microscope objective 60, as illustrated in FIG. 8 and the cylindrical lens 505. The cylindrical lens 505 may direct a beam of light to the viewing zone in the flow channel 604 to illuminate particles in the sample flow. After particles are illuminated in the viewing zone, the composite microscope objective 60 then may collect imaging light scattered from and fluoresced by particles within the view zone.

FIG. 8B illustrates a perspective view of the combined microscope objective 65 coupled with a flow cell 619 in according with some embodiments of the present disclosure. Liquid sample 623 may be pumped up from a sample tube 621 into a flow section 620 of the flow cell 619 by a pump 624. The pump 624 may be the peristaltic pump

80, as illustrated in FIG. 17. Liquid sheath 622 may be also pumped into the flow section 620 of the flow cell 619. The pump for pumping the liquid sheath 622 into the flow cell 619 may be a part of the fluidic system 70, as illustrated in FIG. 14 or 15. The liquid sample 623 may be combined with the liquid sheath 622 in the flow section 620 of the flow cell 619 and then hydro-dynamically focused within the viewing zone inside the flow channel 604 of the combined microscope objective 65. The combined microscope objective 65 or the composite microscope objective 60 may be positioned on the flow cell 619. Persons skilled in the art may also refer to a combination of the microscope objective 65 or the composite microscope objective 60 and the flow cell 619 as a flow cell. The cross-sectional area of the flow section 620 at the top of the flow cell 619 may be smaller than the cross-sectional area of the flow section 620 at the bottom of the flow cell 619 to facilitate hydrodynamic focusing of the liquid sample 623 in the viewing zone. It should be noted that the various aspects of the present disclosure are not limited to specific direction of liquid sheath or sample flow and specific shape of the flow cell or the microscope objective.

FIG. 9A depicts the result of ray tracing for the embodiment of composite microscope objective 60 illustrated in FIG. 8. As depicted in FIG. 9A, scatter and fluorescence emissions from three (3) spatially separated locations in the flow channel 604 near the center of the cuvette 603 may:

1. initially propagate toward back-surface mirror 601 and pass first through the cuvette 603 to be internally reflected by the back-surface mirror 601;
2. then pass through the cuvette 603;
3. subsequently pass through the aspheric corrector plate 602; and
4. finally forms three (3) distinct images near an image plane 605.

Note that rays traversing the composite microscope objective 60 depicted in FIG. 9A are nearly optically-uniform and that light emitted near the center of the cuvette 603 traverses the corrector plate 602 at near normal incidence. Consequently, the composite microscope objective 60 introduces very little chromatic dispersion in light emitted near the center of the cuvette 603.

Further, it is well known in the astrophysics community that Schmidt camera offers the unparalleled combination of a fast focal ratio and a large field of view with near diffraction limited optical performance. The principal drawback in a conventional Schmidt camera is that the image surface lies inside the instrument. For the composite microscope  
5 objective 60, light near the center of the cuvette 603 propagates opposite to that of a conventional Schmidt camera and therefore the image surface lies outside the composite microscope objective 60. Consequently, the present disclosure takes full advantage of the optical performance of the Schmidt camera without experiencing its limitation. FIGs. 9B1 through 9B3 depict spot diagrams near the image plane 605 for three (3) emission  
10 locations, 606, 607, 608 in viewing zone within the flow channel 604 that may be separated 150 micron from each other. The diameters of all images depicted in FIGs. 9B1 through 9B3 may be less than 35 microns.

Light emitted from the viewing zone within the flow channel 604 of the composite microscope objective 60 depicted in FIGs. 8 and 9A that traverses the aspheric corrector  
15 plate 602 may suffer from a small amount of chromatic aberration. FIG. 10 depicts an alternative embodiment for the composite microscope objective 60 depicted in FIGs. 1, 5A, 5B and 7 in accordance with some embodiments of the present disclosure. Those elements depicted in FIG. 10 that are common to the composite microscope objective 60 illustrated in FIGs. 8 and 9A carry the same reference numeral distinguished by a prime (')  
20 designation. The shapes of the back-surface mirror 601' and the aberration corrector plate 602' depicted in FIG. 10 are modified slightly to produce collimated afocal images of the emission locations near the viewing zone within the flow channel 604'. In FIG. 10 the composite microscope objective 60' may include a chromatic compensating doublet lens 609 inserted between the corrector plate 602' and the image plane 605'. In addition to  
25 focusing the light emitted from the corrector plate 602' onto the image plane 605', the doublet lens 609 may also serve to further reduce the residual chromatic aberration introduced by the aspheric corrector plate 602'.

It is not essential that the flat surface of the corrector plate 602 to be optically coupled to the cuvette 603. FIG. 11 depicts an alternative embodiment of the composite  
30 microscope objective 60 in accordance with some embodiments of the present disclosure. Those elements depicted in FIG. 11 that are common to the composite microscope

objective 60 illustrated in FIGs. 8 and 9A carry the same reference numeral distinguished by a double prime (") designation. FIG. 11 depicts the aberration corrector plate 602" optically decoupled from the cuvette 603". Although not essential for operation of the composite microscope objective 60", to improve the light transmission efficiency both  
5 surfaces of the corrector plate 602" and the exposed flat surface of the cuvette 603" may carry an anti-reflectively coating. It is understood that the corrector plate 602" shown in FIG. 11 may be held in fixed relationship to the combined back-surface mirror 601 and cuvette 603 by a mechanical support not depicted in FIG. 11. Similar to the composite microscope objective 60 and 60' depicted respectively in FIGs. 9A and 10, the  
10 composite microscope objective 60" with detached corrector plate 602" may be configured to provide either finite focal length image, or an afocal system which in turn is focused to a finite distance image plane by an additional chromatic compensating doublet lens 609.

FIG. 12 depicts yet another alternative embodiment of the composite microscope objective 60. Those elements depicted in FIG. 12 that are common to the composite  
15 microscope objective 60 illustrated in FIGs. 8, 9A and 11 carry the same reference numeral distinguished by a triple prime (""") designation. The composite microscope objective 60"" depicted in FIG. 12 is adapted for collecting scatter and fluorescence emissions from cells or other microscopic particles carried in the jet stream 519 emitted by the nozzle 518. The composite microscope objective 60"" may include a concave, spherically shaped, front  
20 surface mirror 610 and an aberration corrector plate 612. The front surface mirror 610 may be made of glass or other types of hard material with a highly reflective coating on the concave surface 611 or made of metal with polished concave surface 611. Similar to the corrector plate 602, the plano-aspheric corrector plate 612 may be made of a thin piece of transparent material, such as glass or optical quality plastics. The aspheric surface may be  
25 formed on either side of the corrector plate 612. Both surfaces of the corrector plate 612 may be coated with an anti-reflective coating to reduce optical transmission loss, although such a coating is not a mandatory requirement for a corrector plate 612 in accordance with some embodiments of the present disclosure. It is understood that the front surface mirror 610 and the corrector plate 612 may be held in fixed relationship to each other by a  
30 mechanical support not depicted in FIG. 12. Scatter and fluorescence light emitted from cells or other types of microscopic particles in the viewing zone inside the jet stream 519

may be reflected by the concave surface 611 of the front surface mirror 610. The aberration due to reflection from the concave surface 611 may be corrected by the corrector plate 612 after light traverses through the corrector plate 612. It is understood by those having skill in the art that the composite microscope objective 60''' may be configured to provide either a finite focused image similar to that depicted in FIG. 9A, or a collimated afocal image which is focused at finite distance from the composite microscope objective 60''' by a chromatic aberration correction doublet similar to the doublet lens 609 depicted in FIG. 10.

FIG. 13 depicts an adaptation of the composite microscope objective 60 for imaging specimens fixed to the surface of a transparent substrate such as a glass slide. Those elements depicted in FIG. 13 that are common to the composite microscope objective 60 illustrated in FIGs. 8, 9A and 11 carry the same reference numeral distinguished by a quadruple prime ('''') designation. The composite microscope objective 60'''' depicted in FIG. 13 may include two (2) optical elements, one a plano-concave back surface mirror 617 made of a transparent material, such as glass or optical quality plastics, and an aberration corrector plate 618. As depicted in FIG. 13, the specimen to be imaged may be fixed to a front surface 615 of a transparent, usually glass slide 616. The slide 616 may be optically coupled, for example, using a thin layer of index matching fluid, to the flat surface of the back surface mirror 617. Scatter and fluorescence light emitted by the specimen may:

1. initially propagate through the slide 616 and the back surface mirror 617;
2. be internally reflected by the back surface mirror 617 back through the slide 616;
3. then pass through the corrector plate 618; and
4. finally form an image at an image plane that is located beyond the corrector plate 618.

## **Fluidic Subsystem 70**

The performance of a flow cytometer depends critically on a stable liquid sheath flow. In particular, flow cytometers that have multiple spatially separated excitation laser beams or perform droplet sorting rely on a constant velocity of the liquid sheath flow for timing synchronization. As disclosed in United States Patent No. 5,245,318, conventional

flow cytometers provide a stable liquid sheath flow by using an airtight fluidic system that either:

1. applies constant air pressure in a sheath liquid reservoir to push the fluid through the flow cell; or

5           2. by sucking the fluid from the sheath liquid reservoir through the flow cell using a vacuum pump.

These systems are bulky, expensive to manufacture, and prone to failure. More recently, United States Patent No. 8,187,888 discloses including a sheath liquid subsystem that pumps the liquid sheath flow from the sheath liquid reservoir into the viewing zone and  
10 a waste sheath liquid pump that pumps waste sheath liquid from the viewing zone into the waste tank. Although it appears that the disclosed sheath liquid subsystem has never been used in velocity critical flow cytometers, this patent reports that the disclosed sheath liquid subsystem overcomes most of the drawbacks of conventional sheath liquid flow stabilization by:

15           1. damping pump pulsations by locating:

- a. one fluidic capacitor between the sheath liquid pump and the flow cell; and
- b. another fluidic capacitor between the flow cell and the waste pump; and

2. a pump controller whose operation is responsive to a pressure sensor that measures the pressure difference between the inlet and outlet of the flow cell.

20           However, the disclosed sheath liquid subsystem has other limitations. For example, the pressure sensor located near the outlet of the flow cell could be a potential source of contamination.

FIG. 14 depicts a fluidic subsystem 70 in accordance with some embodiments of the present disclosure that includes a sheath liquid reservoir 702 and a liquid pump 701 that  
25 draws sheath liquid from the sheath liquid reservoir 702. The liquid pump 701 may be a diaphragm pump, a peristaltic pump, a piston pump, or any types of continuous fluid pump. An outlet of the liquid pump 701 may connect to an inlet of a T-coupling 703 that receives sheath liquid from the liquid pump 701. The T-coupling 703 may have two (2) outlets. The first outlet may connect to a bypass conduit 710 for returning a fraction of the sheath liquid

received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702. Returning a fraction of the sheath liquid received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702 is advantageous for two (2) reasons.

5           1. As depicted in FIG. 14, the bypass conduit 710 is left open to the surrounding atmosphere which effectively dampens pulsation to thereby significantly reducing the pulsation inherent in the operation of the liquid pump 701.

          2. Returning a fraction of the sheath liquid received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702 also effectively reduces the  
10       throughput of the liquid pump 701 thereby allowing the use of comparatively high flow rate, low cost pumps in the flow cytometer 40.

Denote the flow resistance of the bypass conduit 710 as " $r$ " and the flow resistance of path from the T-coupling 703 to the flow channel 604 of the cuvette 603 as " $R$ ." The output resistance to the sheath pump  $R_p$  is then equal to:

15           
$$R_p \frac{rR}{r+R} \quad (1)$$

Since  $R \gg r$ , the behavior of the liquid pump 701 is therefore dominated by the resistance of the bypass conduit 710 whose fluid dynamic properties may be temperature insensitive. Thus, the configuration of the fluidic subsystem 70 depicted in FIG. 14 may also provide a simple mechanism for achieving a temperature insensitive sheath liquid flow  
20       to the flow channel 604. As depicted in FIG. 14, the second outlet of the T-coupling 703 connects to the flow channel 604 that extends through the cuvette 603 first via a small reservoir capsule 704 and then via a filter cartridge 705. As depicted in FIG. 15, a piece of tubing 704', which may be, for example, about 4 ft. long may be substituted for the small reservoir capsule 704. During initialization of the fluidic subsystem 70, some air becomes  
25       trapped in the filter cartridge 705 near its inlet which as depicted in FIG. 15 is located above an outlet of the filter cartridge 705. The air trapped in the filter cartridge 705 may act as an additional fluidic capacitor effectively reducing to negligible level the pulsation in sheath liquid emitted into the flow channel 604. Due to the large fluidic resistance at the flow channel 604, the air trapped inside the filter cartridge 705 becomes compressed. When

the liquid pump 701 is turned off, a trapped in the filter cartridge 705 is pushed back towards the T-coupling 703 analogous to a discharging capacitor. Without the small reservoir capsule 704, some air ejected from the filter cartridge 705 reaches the bypass conduit 710 due to its low fluidic resistance, and will be pushed out of the fluidic subsystem 70 once the liquid pump 701 is turned on again. Without additional air supply, such a scenario will repeat until most of the air becomes purged from the fluidic subsystem 70 causing the filter cartridge 705 to lose its effectiveness as a pulsation damper. The purpose of the small reservoir capsule 704 or the piece of tubing 704' is therefore to provide a reservoir for isolating the filter cartridge 705 from the bypass conduit 710 ensuring that air trapped inside the filter cartridge 705 remains within the fluidic subsystem 70 despite repeated on-off operations of the liquid pump 701.

The pulsation damping effect of the trapped air near the inlet of the filter cartridge 705 is clearly evident in the histograms depicted in FIGs. 16A and 16B. FIG. 16A depicts measured particle flight times at the flow channel 604 when a pocket of air is trapped near the inlet of the filter cartridge 705. FIG. 16B depicts measured particle flight times at the flow channel 604 when the trapped air is purged from the fluidic subsystem 70. The result depicted in the histograms of FIGs. 16A and 16B is made using two (2) knife edge shaped laser beams focused near the center of the flow channel 604 that are spaced approximately 200 micrometers apart. The horizontal axis of the FIGs. 16A and 16B is the flight time a particle takes from one laser beam to the other measured by recording the peak arrival time of light scattered from the particle at ninety degrees (90°) from the excitation beams. In both cases, the average flight time for particles to cross the two laser beams is the same. As shown in FIG. 16A, when the filter cartridge 705 retains some air, all particles take about the same amount of time to cross the two laser beams. If the filter cartridge 705 retains no air, as shown in FIG. 16B, the distribution of flight times not only broadens, but also becomes bimodal. In other words, some particles take less time while others take longer than average amount of time to cross the two laser beams, a phenomenon that can be easily attributed to sheath liquid velocity pulsation at the flow channel 604.

In the embodiments of the present disclosure discussed so far, the fluidic resistance along bypass conduit 710 as well as between the T-coupling 703 and the flow channel 604



may not be adjustable. As should be apparent to those ordinary skilled in the art, flow restrictors such a fixed restrictor or adjustable valves 712, 712' and 711, 711' and may be advantageously inserted in the bypass conduit 710 and between the T-coupling 703 and the flow channel 604 to permit adjusting the flow rate through the flow channel 604.

5 Alternatively, the velocity of sheath liquid flowing through the flow channel 604 may also be adjusted using a liquid pump 701 that is driven by a variable speed brushless DC motor.

### **Peristaltic Pump 80**

Peristaltic pumps are volumetric pumps in which a set of linearly or circularly  
10 moving rollers progressively compress a compressible tube to propel the fluid through the tube. Peristaltic pumps are widely used particularly to pump clean/sterile or aggressive fluids to avoid cross contamination with exposed pump components. Conventional peristaltic pump exhibits a pulsation. Each time a roller rolls off the tube near the pump outlet, caused by the temporary increase of tube volume when the compressed tube expands  
15 back to its original shape. The pulsation is undesirable in applications that require smooth flow. Many attempts have been made in the past to reduce the pulsation. For example, United States Patent Nos. 3,726,613 and 3,826,593 introduced a cam operated pusher which synchronously exerts an external pressure on the tube to compensate for the tube expansion. In United States Patent No. 4,834,630, a plurality of tubes mounted on  
20 segmented rollers are joined together at the pump inlet and outlet by T-shaped couplers such that pulsations from individual tubes would be reduced by averaging. United States Patent No. 7,645,127 proposed a pump tube with slightly larger inner diameter near the inlet so that the tube decompression near the pump outlet is compensated by the compression of a larger volume tube near the inlet. The various methods either significantly  
25 increased the complexity of the peristaltic pump or had limited success in reducing the pulsation effect.

A peristaltic pump 80 in accordance with some embodiments of the present disclosure is illustrated in FIG. 17. The pump may include a housing 809 with arcuate curved track 808, three rollers 810, 811 and 812 attached to a rotor 816 rotatable within the  
30 housing 809, and a compressible tube 807 sandwiched between the arcuate curved track 808 of the housing 809 and the rollers 810, 811 and 812, in particular at the surface 814 of

rollers 810, 811 and 812. As depicted schematically in FIGs. 18A through 18D, the rollers 810, 811 and 812 of the peristaltic pump 80 are spaced at substantially equal angular distances, separations or spacings from each other around the perimeter of the rotor 816. The rollers 810, 811, 812 may rotate about a longitudinal axis thereof, so that limited friction occurs between the rollers and the compressible tube. This may also apply for the subsequently described rollers. For simplicity, it is assumed in the following discussions that the rotor 816 rotates counterclockwise, although it is to be understood that the discussions apply equally well to a peristaltic pump with clockwise rotating rotor. The compressible tube 807 of the housing 809 may be divided into several sections:

1. an open section between point 801 and point 806 where the compressible tube 807 experiences no compression;
2. a pump inlet section between point 801 and point 802 where the compressible tube 807 is progressively compressed until fully closed when a roller rolls over the section;
3. two pumping sections between point 802 and point 803, as well as between point 804 and point 805 wherein the compressible tube 807 is fully closed by the roller;
4. a recess section between point 803 and point 804 in which the compressible tube 807 progressively expands from fully closed to fully open as a roller rolls through the expansion part of the recess section from point 803 to point 813;
5. then the compressible tube 807 is progressively compressed to fully closed as a roller rolls through a compression part of the recess section from point 813 to point 804; and
6. the exit section between point 805 and point 806 where the compressible tube 807 progressively expands from fully closed to fully open as a roller rolls through the section.

In other words, when a roller rolls anticlockwise over the compressible tube 807 from inlet point 801 to outlet point 806, the inner gap of the compressible tube 807 may:

1. progressively decrease from fully open at point 801, to fully closed at point 802 and remain closed until point 803;
2. then progressively expand back to fully open at point 813;

3. then progressively decrease to fully closed at point 804, and remain closed until the roller reaches point 805; and

4. finally progressively expand back to fully open at point 806.

The size of the gap inside the compressible tube 807 is schematically illustrated in FIGs. 18A through 18D as the spacing between dashed circle and the solid compressible tube 807. As illustrated in FIGs. 18A through 18D, in this embodiment of the peristaltic pump 80, the angular distances, separations or spacings between points 801 and 803, points 802 and 813, point 813 and 805, as well as between point 804 and 806 may be identical to the angle between adjacent rollers. As a result, when the roller 810 rolls through the pumping section from point 804 to point 805, as depicted in FIGs. 18A through 18B, its interaction with the compressible tube 807 may completely determine the fluid flow rate of the peristaltic pump 80. Once the roller 810 reaches the exit section between point 805 and 806, as shown in FIG. 18C, the compressible tube 807 underneath the roller 810 may start to progressively expand and a gap may start to grow. Meanwhile, the roller 811 may arrive at the compression part of the recess section and start to progressively compress the compressible tube 807. In the peristaltic pump 80, the shape of the compression part of the recess section between point 813 and point 804 along the compressible tube 807 is such that the volume of liquid pushed out by the compression of the underneath roller 811 in the compression part of the recess section between point 813 and point 804 may substantially fill the volume created by the compressible tube 807 expansion underneath roller 810 in the exit section between point 805 and point 806. During this period, the compressible tube 807 is partially open underneath both rollers 810 and 811 and completely closed underneath roller 812. Consequently, the pumping action may be mainly delivered by roller 812. In particular, since by design the total volume of liquid in the section of the compressible tube 807 between point 813 and point 816 remains substantially constant during this period, the flow rate of the peristaltic pump 80 in the state shown in FIG. 18C may remain substantially the same as that in the state shown in FIGs. 18A and 18B. Once the roller 810 passes point 806, roller 811 reaches the pumping section between point 804 and point 805. Note there is no physical difference between the rollers 810, 811 and 812, the flow rate of the peristaltic pump 80 may therefore remain substantially constant throughout the entire process.

The mechanism of the pulseless peristaltic pump in accordance with some embodiments of the present disclosure may be understood more clearly if it is viewed along a circular coordinate following the movement of the rollers. Referring to FIG. 19, denote as  $V$  the volume of the fluid inside a compressible tube 819 from the outlet to a nearest roller 820 that closes off the compressible tube 819, i.e., the amount of fluid represented by the hatched area 818 shown in FIG. 19. Clearly,  $V$  depends on the angular position,  $\theta$ , of the roller 820, as well as  $\delta$ , the amount of tube compression exerted by all other downstream rollers.

$$V = V(\theta, \delta_1, \delta_2, \dots) \quad (2)$$

Consequently, the flow rate,  $F$ , of a peristaltic pump is related to the time derivative of  $V$  by:

$$-F = \frac{dv}{dt} = \frac{\partial v}{\partial \theta} R + \sum_i \frac{\partial v}{\partial \delta_i} \frac{d\delta_i}{dt} \quad (3)$$

Here  $R$  is the rotational speed of the rotor and the subscripts are used to identify multiple downstream rollers. The first term on the right hand side of Eqn. (3) represents the contribution from the roller that closes off the tube. The partial derivative  $\frac{\partial v}{\partial \theta}$  is therefore independent of  $\theta$ . The summation term represents contributions from all other downstream rollers partially compressing the compressible tube 819. Now let  $\Delta S$  be the cross sectional area change due to the compression of the compressible tube 819 by the roller 817, and  $L$  be the length of tube where its cross sectional shape is affected by the tube compression. Then, it is obvious to a person skilled in the art that  $L$  is proportional to the tube compression  $\delta$ , and  $\Delta S$  proportional to its square,  $\delta^2$ . Consequently,  $\Delta V$ , the volume of fluid lost due to the compression of the compressible tube 807 by the roller, follows Eqn. (4):

$$\Delta V \propto L \cdot \Delta S \propto \delta^3 = (D - G)^3 \quad (4)$$

where  $D$  is the inner diameter of the compressible tube and  $G$  is the minimum gap indicated in FIGs. 19, 19A and 19B which is also represented in FIGs. 18A through 18D by the spacing between the dashed circle and the solid track 808 of the housing 809. FIG. 19A and

19B are detailed cross-sectional views orthogonal to the peristaltic pump's tube's length taken along the lines 19A and 19B in FIG. 19 illustrating the tube's partial compression by the roller. FIG. 19A shows the cross-sectional area 818a taken along the line 19A in FIG. 19. FIG. 19B shows the cross-sectional area 818b taken along the line 19B in FIG. 19.

5 Now referring to FIGS. 20A and 20B, in the circular coordinate system, FIG. 20A corresponds to the state of pump shown in FIGS. 18A and 18B. During this period, there is no roller downstream of the roller 810' and the summation term in Eqn. (3) vanishes. FIG. 20B corresponds to the state of the pump shown in FIG. 18C. The compressible tube 807 is closed off by roller 812' and partially compressed by the rollers 810' and 811'. However,

10 volumetric changes introduced by the two rollers 810' and 811' substantially cancel each other. Consequently, the summation term in Eqn.(3) vanishes as well. As a result, the flow rate of the peristaltic pump 80 may remain substantially constant regardless of roller positions.

The shape of the compressible tube 807 satisfying the above requirement can be readily derived from Eqn. (4). Referring to FIG. 18C, if the gaps of the arcuate curved track 808 in the compression part of the recess section between point 813 and point 804,  $G_{13,4}$ , and in the exit section between point 805 and point 806,  $G_{5,6}$ , follow the equation:

$$(D - G_{13,4})^3 + (D - G_{5,6})^3 = D^3 \quad (5)$$

then the total fluid volume in the two sections may remain substantially constant, as shown in FIG. 21. In the peristaltic pump 80, the shape of the pump housing 809 may be symmetrical with respect to its center line, such that the entrance half of the pump housing 809 is the mirror image of the exit half of the housing 809, as shown in FIG. 17. The peristaltic pump 80 can therefore be operated both in counterclockwise and clockwise rotation with very little pulsation, although it is understood that the symmetry is not

20 required to realize a pulseless peristaltic pump in accordance with some embodiments of the present disclosure. For example, as long as the gaps of the arcuate curved track 808 in the section between point 813 and point 803,  $G_{13,3}$ , and in the section between point 802 and point 801,  $G_{2,1}$ , follow Eqn. (6)

$$(D - G_{13,3})^3 + (D - G_{2,1})^3 = D^3 \quad (6)$$

a peristaltic pump in accordance with some embodiments of the present disclosure will exhibit little pulsation when the rotor 816 rotates clockwise.

FIG. 22 depicts an alternative embodiment of a peristaltic pump in accordance with some embodiments of the present disclosure. Those elements depicted in FIG. 22 that are common to the peristaltic pump 80 illustrated in FIG. 17 carry the same reference numeral distinguished by a prime (') designation. The peristaltic pump 80' may include an arcuate curved track 808' having two (2) recesses 818 and 819, and four (4) rollers 820, 821, 822 and 823. In the embodiment depicted in FIG. 22, the fluid volume loss due to the tube expansion near the outlet of the pump is compensated by the combined effect of the compression of the compressible tube by rollers 820 and 823 near the two recesses 818 and 819.

FIG. 23 depicts yet another alternative embodiment of a peristaltic pump in accordance with the present disclosure. Those elements depicted in FIG. 23 that are common to the peristaltic pump 80 illustrated in FIG. 17 and the peristaltic pump 80' illustrated in FIG. 22 carry the same reference numeral distinguished by a double prime (") designation. The peristaltic pump 80" may include six (6) rollers 820, 821, 822, 823, 824, 825 and an arcuate curved track 808" having two recesses 818" and 819". In the peristaltic pump 80", the fluid volume loss due to the tube expansion near the outlet of the pump is compensated by the action of the roller immediately upstream of the one recess 818" or 819" near the pump outlet.

Pulsation due to the expansion of a compressed compressible tube near the outlet of a peristaltic pump may also be overcome by a peristaltic pump having a programmable rotor speed. FIGs. 24A through 24C illustrate pertinent aspects of an alternative embodiment mechanism for minimizing peristaltic pump pulsation in accordance with the present disclosure for a 3-roller peristaltic pump. As depicted in FIG. 24B, the track 828 is substantially circular between the pump inlet and pump exit section. Consequently, as indicated by the spacing between the dashed circle 829 and the solid curve of the track 828, the compressible tube is completely closed by various ones of the pump's three (3) rollers 825, 826, 827 between the pump inlet and pump outlet. FIG. 24A illustrates schematically in a circular coordinate system the roller positions for the peristaltic pump depicted in FIG.

24B. Since there is only one roller downstream of the one that closes off the tube, Eqn. (3) is much simplified:

$$-F = R \left( \frac{\partial V_c}{\partial \theta} + \frac{\partial V_c}{\partial \delta} \frac{d\delta}{d\theta} \right) \quad (7)$$

Here the tube compression  $\delta(\theta)$  is explicitly expressed as a function of roller position  $\theta$ . The terms inside the parentheses represent the change rate of fluid volume with respect to roller position. The first term is the contribution from the roller that closes off the tube, i.e., roller 827 in FIG. 24A, and the second term the contribution from the roller in the exit section. Note that by definition, the volume change rate is negative and the second term inside the parentheses vanishes when there is no roller in the exit section. The dotted curve in FIG. 24C is a representative plot of the negative volume change rate with respect to the position of the roller. The bump along the curve, due to the tube expansion when a roller rolls off the tube near the pump outlet, is the cause for pulsation in conventional peristaltic pumps having a constant rotor speed. However, for the peristaltic pump depicted in FIGS. 24A through 24C, the rotor speed,  $R$ , shown as dashed curve in FIG. 24C, may be set to vary in synchronism with the rotor position and inversely proportional to the change rate of the fluid volume. Consequently, the flow rate of the pump, which is the product of the rotor speed and the change rate of the fluid volume, may remain constant, as indicated by the solid line at the top of FIG. 24C. Note the terms inside the parentheses of Eqn. (7) may be uniquely determined by the mechanical structure of the pump. The rotor speed profile can therefore be readily generated from the shape of the track 828 in accordance with Eqn. (4). To those skilled

in the art, there are many ways to realize a programmable rotor, for example, with stepping motor or DC servo motor.

## WDM Device 90

In many multicolor fluorescence detection instrumentations, such as flow cytometers, (Practical Flow Cytometry, Howard M. Shapiro, Wiley (2003) ISBN 0471411256), the fluorescence light emitted from the object of interest is:

1. collected by a microscope objective;

2. reimaged through a small pinhole or a multimode optical fiber;
3. then collimated and separated into multiple colored bands; and
4. finally detected by photo detector, such as photomultiplier tube (PMT), PIN photodiode or avalanche photodiode (APD).

5           A PMT is essentially a special type of electron tube. This “pre-semiconductor age” device is bulky and expensive. In addition, it has poorer quantum efficiency and less reproducible spectral response than silicon based semiconductor detectors, particularly in the biologically important red to near infrared spectral region. Despite the disadvantages, PMT has excellent noise characteristics. For example, the dark current of a typical 13mm  
10 PMT (e.g., the R9305 from Hamamatsu Corporation of Japan) is only about 1nA. In contrast, an APD’s dark current would be 10 times greater even if its active area were reduced to 1/20th of that of the PMT. As a result, PMT has been the de-facto low-level light detector in many commercial fluorescence detection flow cytometers. Only in certain scientific applications where event rate is low and dark current may be discriminated  
15 against by expensive photon- counting techniques that the PMT has been replaced by APD detectors. (c.f., High-Throughput Flow Cytometric DNA Fragment Sizing, A.V. Orden, R.A. Keller, and W. P.Ambrose, *Anal. Chem.*, 2000, 72 (1), p 37–41). More recently, a Geiger mode APD array was also promoted as PMT replacement. (For example, the multi pixel photon counter of Hamamatsu Photonics of Japan and the solid-state photomultiplier  
20 of SensL Inc. of Ireland.) These detectors, however, also have high dark current and are nonlinear at high event rate.

          The only industry where APD has found wide acceptance is in optical communication. It is known that if the APD’s active area is reduced to less than 1mm<sup>2</sup>, the corresponding dark current will be reduced to the same level as a PMT. In optical  
25 communication, the light is a laser beam out of single mode optical fiber. Such a beam can be easily collimated then focused down to an area much smaller than 1mm<sup>2</sup>. It should be noted that the color separation devices used in the fluorescence light detection instruments, as described in United States Patent Vo. 6,683,314 and references therein, are almost identical in function and architecture to the wavelength division multiplexers (WDM)  
30 widely used in optical communication, as described in United States Patent Nos. 4,482,994,



and 5,786,915. A fundamental reasons preventing the use of small area APD in fluorescence detection instrumentation is the well-known theorem of etendue conservation: the fluorescence light coming through a pinhole or multimode optical fiber is an extended light source with an etendue hundreds of times greater than that of a laser beam out of a single mode optical fiber. Consequently, as illustrated in FIG. 26, it cannot be collimated over an extended distance unless the diameter of the beam is significantly expanded. Unfortunately, the larger the beam diameter, the greater the technical challenge to focus it down to a small spot. Since efficient color separation can only be accomplished economically with collimated light beam, small area APD has not been considered viable for multicolor fluorescence light detection applications. Clearly, a technology capable of collimating a large etendue light beam over an extended distance without significantly expanding the beam diameter would be highly desirable. Such a technology would enable a WDM like device for fluorescence light detection with characteristics comparable to low noise semiconductor detectors.

FIG. 25 shows the optical ray trace for an exemplary 6 port wavelength division multiplexer of the present disclosure using zig-zag configuration. As shown in FIG. 25, fluorescence light going through a pinhole or emitted from the facet of a multimode optical fiber, such as the optical fiber 852 depicted in FIG. 1, forms an extended object or light source at location 901, i.e. the optical input of the WDM 90. The size of the object is defined by the diameter of the pinhole or the core diameter of the multimode optical fiber. Note that the practical size of the pinhole or the core diameter of the multimode optical fiber is measured in millimeters, in contrast to the diameter of single mode optical fibers that are measured in micrometers. Consequently, the etendue of the fluorescence light source, defined as the product of beam size and its divergence angle, is hundreds times greater than its counterpart in optical communication. According to the theorem of the conservation of etendue (Julio Chaves, *Introduction to Nonimaging Optics*, CRC Press, 2008 [ISBN 978-1420054293]), light from such an extended source, similar to that from a flash light, can only be kept collimated for a very limited distance, particularly when the diameter of the collimated portion needs to be small.

As depicted in FIG. 25, a collimating optical element, in this case an achromatic doublet lens 902, may capture the light from source 901, and project a magnified image of

the object near a final focusing lens 905. The size of the image near 905 may be kept approximately the same as the effective size of the collimating optical element 902. Consequently, beam of light propagating between the collimating optical element 902 and the focusing lens 905 may be effectively collimated. As shown in FIG. 25, so long as the  
5 magnification factor is kept small, for example, less than around 10, using a simple singlet lens as the focusing lens 905, the collimated beam of light can readily be focused down to a spot smaller than that of the beam of light received by the WDM 90 at location 901. The ability to focus the beam of light down to such a small size permits placing a small area semiconductor detector at a focal point 906 of the focusing lens 905 for efficient photo  
10 detection.

A dichroic filter 903, oriented at a slanted angle, may be inserted into the optical path in between the collimating optical element 902 and the focusing lens 905. The dichroic filter 903 may pass the color band of interest and reflects the remaining colors in the beam of light for further processing within the WDM 90. An optional band pass filter 904 may be  
15 inserted following the dichroic filter 903 to further improve the color isolation capability of the WDM 90.

Light reflected from the dichroic filter 903 may impinge upon a second optical element 907, such as a concave mirror. The concave mirror 907 may have a radius of curvature approximately equal to the distance between the collimating optical element 902 and the  
20 image near focusing lens 905. The concave mirror 907 therefore creates a second image of the collimating lens 902 near a second focusing lens 908. The light beam between the concave mirror 907 and the second image at the lens 908 may have substantially the same diameter as the beam of light between the collimating lens 902 and the first image near the focusing lens 905. The relay imaging concave mirror 907 therefore effectively doubles the  
25 collimated beam path without expanding the beam's diameter. Again, the extended yet collimated beam can be easily focused down to a spot smaller than that of the light source at 901. The diameter of the spot may be smaller than 1mm, for example, around  $600\text{ }\mu\text{m}$ . A second dichroic filter 909 may then be inserted in between the relay imaging concave mirror 907 and the second image near focusing lens 908. The second dichroic filter 909  
30 may pass another band of color in the beam of light received by the WDM 90 at location

901 and reflect the remainder of the impinging beam of light for further processing. The first and second dichroic filters 903 and 909 may be inserted approximately midway between the collimating optical element 902 and the focusing lens 905 and between the relay imaging concave mirror 907 and the second image near focusing lens 908, respectively.

As shown in FIG. 25, additional relay collimating optical elements 910, 911, 912, 913 and dichroic filters 914, 915, 916, 917 can be cascaded in the same way to produce multiple images near focusing lenses 918, 919, 920 and 921, each of these images corresponding to a specific color band of light received by the WDM 90 at location 901. As shown in FIG. 25, due to the present disclosure's 1:1 imaging relay architecture, the spots of light produced by focusing lenses 905, 908, 918, 919, 920 and 921 are all smaller than the source of the beam of light, and therefore can be easily captured by small area APD's.

Although FIG 25 illustrates a 6-port wavelength division multiplexer for a beam of light from the extended light source, it is readily apparent to those skilled in the art that WDM's having different numbers of ports can be easily built in accordance with some embodiments of the present disclosure. It is also apparent to those skilled in the art that although the WDM 90 may use achromatic doublets as the first collimating optical element, singlet lens can also be used since the images created before the focusing lenses 905, 908, 918, 919, 920 and 921 are all nearly monochromatic. Instead of using concave mirrors for relaying the beam of light reflected from the dichroic filters, one may also use refractive optics, such as a convex lens, as a relay element to extend the path of the collimated beam of light. One of the advantages of the zig-zag architecture used in the WDM 90, however, is the possibility for using array detectors, which would lead to a more compact WDM suitable for portable instrumentation.

FIG. 25A illustrates a top view of a light detection assembly 937 with the WDM 90 illustrated in FIG. 25 in accordance with some embodiments of the present disclosure. The light detection assembly 937 may include the WDM 90 and a photodetector system 938. A beam of light which emits from the facet of the optical fiber 852 may be processed by the WDM 90 and detected by the photodetector system 938. The concave mirrors 907, 910, 911, 912, and 913 and the dichroic filters 903, 909, 914, 915, 916, and 917 may be formed

on two sides of a reference block 935. The reference block 935 may be made of glass or any material which allows light to pass through it. Accordingly, a zig-zag optical pattern, as illustrated in FIG. 25 may be formed among the collimating optical element 902, the dichroic filters 903, 909, 914, 915, 916, and 917, the reference block 935, the concave mirrors 907, 910, 911, 912, and 913, and the focusing lens 905, 908, 918, 919, 920, and 921. After being processed by the WDM 90, the beam of light emitting from the facet of the optical fiber 852 may split into multiple colored bands with different wavelengths to be detected by photodetectors 940, 941, 942, 943, 944, and 945, respectively. The photodetector can be, but is not limited to, a semiconductor detector, an avalanche photodetector (APD), and a carbon nanotube detector.

In some embodiments, the concave mirrors 907, 910, 911, 912, and 913 may be structurally formed on a relaying assembly 939. It should be understood by those having skill in the art that the concave mirror can be replaced with a convex lens, which is also able to converge and relay the beam of light.

In some embodiments, the dichroic filter can be replaced with a mirror to prevent the beam of light from entering a photodetector when a user wants to decrease the number of light signal channels to be detected. It should be understood by those having skill in the art that the dichroic filter can also be replaced by a dichroic mirror, a beam splitter, or any optical element which is able to split or filter a beam of light.

FIG. 25B illustrates a front view of the light detection assembly 937 with the WDM 90 illustrated in FIGs. 25 and 25A in accordance with some embodiments of the present disclosure. The light detection assembly 937 may have a top cover 940 which is openable. Therefore, the user can open the top cover 940 to change the dichroic mirrors 903, 909, 914, 915, 916, and 917 and modify the light detection system 938 or the WDM 90 inside.

FIG. 26 illustrates an optical ray trace for a prior art collimating device. The technique depicted in FIG. 26 is extensively used in conventional multicolor fluorescence instruments, for example, in United States Patent No. 6,683,314. As shown in FIG. 26, the beam of light diverges rapidly beyond the image 924 created by the collimating optical element 923. Consequently, the only option for constructing a multi-color device is to insert dichroic filters in between the collimating element 923 and its image 924.

Due to the constraint of etendue conservation, the diameter of the collimated beam must be significantly expanded to accept multiple dichroic filters in the section. The expanded beam creates serious challenge to refocusing the collimated beam down to small spots suitable for small area semiconductor detectors. To overcome these difficulties, some instrument manufacturers have chosen to use PMT exclusively for fluorescence detection such as in the main stream flow cytometers manufactured by Becton-Dickinson, Beckman Coulter and Partec 's and the MegaBACE series of DNA sequencers by GE Amersham. Other instruments, such as the Luminex multiplexed bead analyzers, have selected certain color bands with known bright fluorescence, and uses large area APD for detecting light in the selected color bands.

FIG. 27 illustrates a perspective view of an alternative embodiment for a 6-port WDM 90 using a combination of zig-zag and branched configurations. The design is a modification of zig-zag configuration depicted in FIG. 25. In the alternative embodiment depicted in FIG. 27, band pass filter 904 of FIG. 25 may be replaced by a dichroic filter 904'. The filter 904' is positioned to let one color pass through and reflects other colors at ninety degrees ( $90^\circ$ ). The optical path length of the beam of light passing through the dichroic filter 904' and that being reflected from the 904' are substantially the same, such that one arm is focused by lenses 905 and the other by lens 905' to small spots compatible with small area semiconductor detectors placed at focal location 906 and 906'. As shown in FIG. 25, the remaining color of the light reflected by dichroic filter 903 is relay imaged by a concave mirror 907 and the configuration including optical elements 903, 904', 905 and 905' is cascaded two (2) more times to form a 6 port-WDM.

FIG. 28 illustrates a perspective view of an alternative embodiment for a 8-port WDM 90. By replacing the concave mirrors 907 and 910 in FIG. 27 with concave shaped dichroic filters 907' and 910', the WDM depicted in FIG. 28 may provide 2 more color bands in comparison with the WDMs depicted in FIGs. 25 and 27.

Numerous fluorescence probes for use in flow cytometry have been developed over the years. More recently, multiple fluorescence proteins have also become an important tool in biomedical studies. To accommodate different types of fluorescence probe, various

techniques have been developed to enable user selection of dichroic filters suitable for their particular needs. A significant challenge for replaceable dichroic filters is avoiding direct contact of the coated filter surface with any hard flow cytometer reference frame. Repeated direct contact between the coated filter surface and any hard reference frame may damage a replaceable dichroic filter. Presently, most conventional solutions addressing this problem use precision-machined mechanical spacers for holding replaceable dichroic filters in place. One example of such a solution appears in United States Patent No. 6,683,314. However, such a solution becomes unreliable if the detector's active area is smaller than  $1.0 \text{ mm}^2$ .

FIGs. 29A and 29B depict fabricating a replaceable dichroic filter assembly 934 illustrated in FIG. 29C suitable for small area detectors. Assembly of the replaceable dichroic filter assembly 934 begins in FIG. 29A which depicts constructing a reference template for its fabrication. The reference template may be a staircase made of two (2) optically parallel glass plates 925 and 926. Bonding the two (2) glass plates 925 and 926 together in optical contact can ensure that a surface 929 of the glass plate 925 becomes optically parallel to a surface 930 of the glass plate 926. A front surface 932 of a replaceable dichroic filter 927 may then be pressed against the surface 929 of the template. A filter holder 928, which loosely fits the dichroic filter 927, may include a reference surface 931 and a filter slot 933. During assembly of the replaceable dichroic filter, the filter slot 933 may be partially filled with epoxy adhesive and the reference surface 931 of the filter holder 928 may be pressed against the surface 930 of the template while filter holder 928 slides toward the dichroic filter 927. While the epoxy adhesive sets, part of the dichroic filter 927 remains seated within the filter slot 933 while pressure is applied against the dichroic filter 927 and filter holder 928. It should be apparent to those skilled in the art that the epoxy adhesive may be either UV or thermally curable, or made by blending together components of an A/B mixture. FIG. 29C depicts a dichroic filter fabricated as depicted in FIGs. 29A and 29B and described above. The assembly process depicted in FIGs. 29A and 29B and described above can ensure that the front surface 932 of the replaceable dichroic filter assembly 934 can be optically parallel to the reference surface 931, and indented with respect to the latter at a spacing accurately determined by the thickness of the glass plate 925. The dichroic filter 927 depicted in FIGs. 29A, 29B, and

29C may be the dichroic filters 903, 909, 914, 915, 916, or 917 used with the WDM illustrated in FIG. 25 or the dichroic filter 903 or the filter 904' used with the WDM illustrated in FIG. 27.

FIGs. 30A and 30B depict an embodiment of the present disclosure where the fore-  
mentioned replaceable dichroic filter assembly 934 is used in the WDM 90 for optically  
processing a beam of light from an extended light source. A notable feature of the WDM 90  
is a glass reference block 935 having an optically flat surface. As will be apparent to those  
skilled in the art, the glass reference block 935 may be made of other materials. As shown  
in FIG 30B, when installing a dichroic filter 927 the reference surface 931 of the  
replaceable dichroic filter assembly 934 may slide against the flat surface of the glass  
reference block 935 and be kept in contact therewith by a spring loaded screw 936.  
Consequently, the coated front surface 932 of the replaceable dichroic filter assembly 934  
can remain optically parallel to the optical flat and accurately located. In the meantime, the  
indentation of front surface 932 with respect to the reference surface 931 may protect it  
from in physical contact with any object during filter replacement. It is apparent to those  
skilled in the art that many modifications and variations of the described embodiments of  
the replaceable dichroic filter assembly 934 are possible. For example, an alternative  
embodiment of the present disclosure may be a pedestal assembled using a first and a  
second round optical flat. When assembling the replaceable dichroic filter assembly 934,  
the reference surface of a filter holder may rest against a surface of the first optical flat and  
the coated surface of the dichroic filter may rest against the flat surface of the second  
optical flat. Epoxy bonding then may hold the coated surface of the dichroic filter optically  
parallel to the reference surface of a filter holder, yet indented at a distance accurately  
determined by the thickness of the second optical flat.

#### **Optical System with Single Light Source 41**

FIG. 31 is a diagram schematically illustrating an optical system with a single light  
source 41 in accordance with some embodiments of the present disclosure. The optical  
system with a single light source 41 may include a LD based optical subsystem 50, a  
composite microscope objective 60, a WDM 90, and a light detection system 938. The  
beam of light may propagate substantially along the z axis and enter the composite  
microscope objective 60 from the LD based optical subsystem 50 to illuminate particles

present within the viewing zone inside the composite microscope objective 60. The light scattered from and fluoresced by particles may then be reflected by the concave mirror 601, corrected by the corrector plate 602, and collected by the optical fiber 852 substantially along the x axis. The optical fiber 852 may be fixed by a fiber holder 940.

5           Common wavelengths of light sources may include, but not limited to, 375nm, 405nm, 440nm, 488nm, 502nm, 534nm, 561nm, 591nm, 637nm, and 637nm. The light detection system 938 may be coupled with circuits for processing light signals. The more ports the WDM 90 has, the more light signal channels the user can use.

## 10   **Optical System with Multiple Light sources 42**

FIG. 32 is a diagram schematically illustrating an optical system with multiple light sources 42 in accordance with some embodiments of the present disclosure. The optical system with multiple light sources 42 may include multiple LD based optical subsystems 50, multiple WDMs 90, multiple light detection systems 938, and a composite microscope objective 60 with a viewing zone. The number of WDMs 90 may correspond to the number of LD based optical subsystems 50. In FIG. 32, the optical system with multiple light sources 42 includes three laser diodes 501 for emitting multiple beams of light with different wavelengths, three collimating lenses 502 in front of the three LDs for collimating the beams of light respectively, three dichroic filters 506, 507, and 508 for passing beams of light with certain wavelength range or reflecting beams of light with certain wavelength range, a plano-convex lens 504 for shaping the beams of light on the major axis, a cylindrical lens 505 for focusing the beams of light onto three spatially separated locations in the flow channel 604, a composite microscope objective 60 for directing the light scattered from and fluoresced by the illuminated particles at three spatially separated locations to be collected by three optical fibers 852, respectively, three optical fibers 852 for collecting scatter and fluorescence emissions and transmitting the emissions to three WDMs 90, respectively, and three WDMs 90 and light detection systems 938 for processing and detecting the scatter and fluorescence light, respectively. The direction of beams of light entering the composite microscope objective 60 may be perpendicular to the direction of scatter and fluoresce emissions to be collected by the optical fiber 852. It should be noted that the plano-convex lens 504 and the cylindrical lens 505 can be replaced



with any conventional beam shaper and any focusing lens. It should also be noted that the various aspects of the present disclosure are not limited to specific numbers of laser diodes, collimating lenses, dichroic filters, plano-convex lenses, composite microscope objectives, optical fibers, WDMs, and light detection systems and specific wavelength and direction of each beam of light.

FIG. 33 illustrates an enlarged view of beams of light 509 and 510 shown in FIG. 32. The beams of light 509 and 510 are emitted from different laser diodes 501 with different wavelengths and then are focused onto spatially divided locations in the flow channel 604 inside the composite microscope objective 60.

### **Optical System with Chromatic Compensation Elements 51**

FIG. 34 is a diagram schematically illustrating an optical system with chromatic compensation elements 51 in accordance with one aspect of the present disclosure in accordance with some embodiments of the present disclosure. The optical system with chromatic compensation elements 51 may include the optical system with multiple light sources 42, as shown in FIG. 32, and multiple chromatic compensation elements 514, 515, and 516. Each of the chromatic compensation elements 514, 515, and 516 may be positioned on the beam paths of beams of light emitting from light sources 511, 512, and 513, respectively, and compensate chromatic aberration in the viewing zone. As such, the beams of light emitting from the light sources 511, 512, and 513 with different wavelengths may be focused onto three spatially divided locations on a common plane which is in the viewing zone and substantially parallel to the direction of a sample flow. The optical properties of chromatic compensation elements 514, 515, and 516 may be different from each other. For example, their thicknesses and shapes may be different to accommodate various beams of light with different wavelengths.

In some embodiments, the optical system shown in FIG. 34 may only need one or two chromatic compensation elements to compensate chromatic aberration in the viewing zone. It should be noted that the various aspects of the present disclosure are not limited to specific numbers or optical properties of chromatic compensation elements.

### Power Monitoring System 43

FIG. 35 is a diagram schematically illustrating a power monitoring system 43 in accordance with some embodiments of the present disclosure. The power monitoring system 43 may include a first light source 513 for emitting a first beam of light, a second light source 512 for emitting a second beam of light, a first dichroic filter 519 for reflecting the first beam of light and passing the second beam of light, a second dichroic filter 518 for reflecting the second beam of light, a first detector 401 for measuring residual power of the first and second beams of light downstream of the first dichroic filter 519 on a time-division multiplexing basis, and a control unit 522 coupled with the first detector 401, the first light source 513, and the second light source 512. The first detector 401 may be positioned near or coupled to the first dichroic filter 519. The first and second light sources 513 and 512 may emit beams of light with different wavelengths.

In order to reduce interference between the residual power of the first and second beams of light, the first detector 401 may measure the residual power of the first beam of light when the second light source 512 is off or measure the residual power of the second beam of light when the first light source 513 is off. The residual power of the first and second beams of light may include power of the first beam of light passing through the first dichroic filter 519 and power of the second beam of light reflected by the first dichroic filter 519.

In some embodiments, the control unit 522 may include a feedback circuit to increase the power of the light source when residual power of the light source drops below a certain level or to lower the power of the light source when the residual power of the light source increases above a certain level.

In some embodiments, a second detector 400 may be applied with the power monitoring system 43 and positioned near or coupled to the second dichroic filter 518 to measure the residual power of the second beam of light downstream of the second dichroic filter 518. The residual power of the second beam of light downstream of the second dichroic filter 518 may include power of the second beam of light passing through the second dichroic filter 518. The second detector 400 may also be coupled to the control

circuit 522. When the second detector 400 is applied to the power monitoring system 43, the first detector 401 may only need to monitor the residual power of the first beam of light.

In some embodiments, a third light source 511 for emitting a third beam of light and a third dichroic filter 517 for reflecting the third light may be also applied with the power monitoring system 43. The third light source 511 may be also coupled to the control circuit 522. As such, the first detector 401 may measure residual power of the first, second, and third beams of light downstream of the first dichroic filter 519 on a time-division multiplexing basis.

In some embodiments, the second detector 400 may measure residual power of the second and third beams of light downstream of the second dichroic filter 518 on a time-division multiplexing basis. The residual power of the second and third beams of light downstream of the second dichroic filter 518 may include power of the second beam of light passing through the second dichroic filter 518 and power of the third beam of light reflected by the second dichroic filter 518.

In some embodiments, a third detector (not shown in FIG. 35) may also be applied with the power monitoring system 43 and positioned near or coupled to the third dichroic filter 517 to measure residual power of the third beam of light downstream of the third dichroic filter 517. The third detector may be also coupled to the control circuit 522. The residual power of the third beam of light at the downstream of the third dichroic filter 517 may include power of the third beam of light passing through the third dichroic filter 517.

The second beam of light can either be detected by the first detector 401 or the second detector 400. The third beam of light can be detected by the first detector 401, the second detector 400, or the third detector which is positioned near or coupled to the third dichroic filter 517. The control circuit 522 may control the operation of the detectors and light sources.

It should be understood by those having skill in the art that the dichroic filter can also be replaced by a dichroic mirror or a beam splitter. It should also be noted that the various aspects of the present disclosure are not limited to specific numbers of light sources, dichroic filters, and detectors.

## Optical System 44

FIG. 36 is a diagram schematically illustrating an optical system 44 in accordance with some embodiments of the present disclosure. The optical system 44 may include a composite microscope objective 60, as shown in FIG. 8, a light source 403, and a beam splitter 402. The light source 403 may emit beams of light to illuminate objects in a viewing zone, which is located in a flow channel 604 inside a cuvette 603. The composite microscope objective 60 may image light scattered from and fluoresced by the objects in the viewing zone at an image plane 404 external to the composite microscope objective 60. The light source 403 and the image plane 404 may be located on two sides of the beam splitter 402.

The composite microscope objective 60 may include a concave mirror 601 and an aberration corrector plate 602 coupled to the two sides of the cuvette 603. The aberration corrector plate 602 may be an aspheric lens that has a first zone with negative optical power and a second zone with positive optical power radially inside the first zone. A neutral zone may be the thinnest portion of the aberration corrector plate 602 and located between the first zone and the second zone. The aspheric lens may be a plano-aspherical lens. The concave mirror may be a plano-concave back surface mirror or a front surface mirror. The concave mirror 604 and the aberration corrector plate 602 may be made of an optically transparent material.

In FIG. 36, the beam of light emitting from the light source 403 may be reflected by the beam splitter 402 and enter into the composite microscope objective 60 to illuminate objects in the viewing zone. The light scattered from and fluoresced by objects may be reflected by the concave mirror 604, transmit through the aberration corrector plate 602 and the beam splitter 402, and form an image at the image plane 404 external to the composite microscope objective 60. The light source 403 may include multiple laser diodes 403a, 403b, and 403c emitting multiple beams of light with different wavelengths to illuminate objects at multiple locations in the flow channel 604. Accordingly, multiple images 404a, 404b, 404c may be formed at the image plane 404.

In some embodiments, the locations of the light source 403 and the image plane 404 may be swapped. Accordingly, the beam of light emitting from the light source 403 may

transmit through the beam splitter 402 and enter into the composite microscope objective 60 to illuminate objects in the viewing zone. The light scattered from and fluoresced by objects may be reflected by the concave mirror 604, transmit through the aberration corrector plate 602, be reflected by the beam splitter 402, and form an image at the image plane 404 external to the composite microscope objective 60.

In some embodiments, the viewing zone may be located in a jet stream or a surface of a substrate containing objects (not shown in FIG. 36). The objects may be delivered into the viewing zone by a fluidic system, such as a fluidic system shown in FIG. 14 or 15.

In some embodiments, the scattered and fluoresced light imaged at the image plane 404 may be received by a fiber (not shown in FIG. 36) which transmits the light to a photodetector. The scattered and fluoresced light may be processed by a wavelength division multiplexer (WDM) (not shown in FIG. 36) before being detected by the photodetector. The WDM may be configured as a WDM illustrated in FIGs. 25, 25A, and 25B. The photodetector can be, but not limited to, a semiconductor photodetector, a multi-pixel photon counter, and a carbon nanotube detector.

In some embodiments, the light source 403 may emit coherent light or incoherent light. The light source 403 can be single or multiple laser diodes, light emitting diodes, illumination devices emitting beam of light, or any combination of them.

In some embodiments, a chromatic compensating lens (not shown in the figure) may be inserted between the aberration corrector place 602 and the image plane 404 to serve to reduce the residual chromatic aberration.

### **Axial Light Loss Detection System 45**

FIG. 37 is a diagram schematically illustrating an axial light loss detection system 45 in accordance with some embodiments of the present disclosure. The axial light loss detection system 45 may include a concave mirror 406 for reflecting light that propagates from a viewing zone and a detector 408 for measuring axial light loss produced by the object in the viewing zone by detecting light reflected by the concave mirror 406. The light reflected by the concave mirror 406 may include forward scattered light (FSC) and remaining light of beam of light entering into the viewing zone from a light source 412 to

irradiate the object therein, which is so called axial light loss (ALL). The axial light loss of the beam of light along its propagation direction may result from the object passing through the beam of light. The beam of light may be blocked or absorbed by the object.

5 The axial light loss detection system 45 may utilize the concave mirror 406 to direct both FSC and remaining light into the detector 408 in order to determine the size of object. The FSC and remaining light may have the same wavelength, and therefore the signals of FSC and remaining light detected by the detector 408 may be proportional to square of the sum of their electric fields as follows:

$$(E_{FSC} + E_{ALL})^2 \quad (8)$$

10  $E_{FSC}$  represents the electric field of FSC.  $E_{ALL}$  represents the electric field of remaining light.

On the contrary, a conventional ALL detection system disclosed in prior art usually requires a pinhole positioned along a laser beam path to block FSC in order to detect remaining light of the laser beam. Accordingly, the signals of remaining light detected by an ALL detector is proportional to square of its electric field as follows:

$$(E_{ALL})^2 \quad (9)$$

Further, a conventional FSC detection system disclosed in prior art usually requires a mask positioned along a laser beam path to block remaining light of the laser beam in order to detect FSC. Accordingly, the light signals of FSC detected by a FSC detector is proportional to square of its electric field as follows:

$$(E_{FSC})^2 \quad (10)$$

Apparently, neither of the conventional ALL detection system nor conventional FSC detection system could operate without using a pinhole or a mask.

25 In some embodiments, the concave mirror 406 may be an ellipsoidal mirror or a combination of a flat mirror and a lens. The detector 408 may be an axial light loss detector to determine the size of the object.

In some embodiments, the detector 408 may be in a heterodyne mode detecting the coherent interference of FSC and the remaining light. The wavelengths of FSC and remaining light may be the same.

5 In some embodiments, a light source 412 emitting beam of light may be used to illuminate the object in the viewing zone. The optical axis of the beam of light is substantially perpendicular to the flow direction of the object.

In some embodiments, multiple light sources 412 emitting beams of light with different wavelengths may be used to illuminate the objects in the viewing zone. When multiple light sources 412 are applied to the axial light loss detection system 45, a filter 407  
10 may be positioned upstream of the detector 408 to separate the light irradiated by the first light source and reflected by the concave mirror 406 and the light irradiated by the second light source and reflected by the concave mirror 406. As such, the detector 408 may measure them separately, for example, on a time-division multiplexing basis.

In some embodiments, the viewing zone may be located within a microscope  
15 objective 410. The viewing zone may be located in a flow channel 409, a jet stream, or a substrate. In some embodiments, a cylindrical lens 411 may be coupled to the microscope objective 410 to focus beams of light emitting from the light source 412 to the viewing zone. The optical axis of the cylindrical lens 411 is substantially perpendicular to the optical axis of the light reflected by the concave mirror 406.

20 FIG. 38 is a diagram schematically illustrating an axial light loss detection system 45 coupled with a second light detection system 413 in accordance with some embodiments of the present disclosure. The axial light loss detection system 45 may utilize a composite microscope objective 60, as illustrated in FIG. 8 The composite microscope objective 60 may include a second concave mirror 415 and an aberration corrector plate 414 located on  
25 two sides of the viewing zone of the composite microscope objective 60. The optical axes of the second concave mirror 415 and the aberration corrector plate 414 are substantially parallel to the optical axis of the light reflected by the concave mirror 406. The FSC and remaining light propagating from the viewing zone may be reflected by the concave mirror 406 and detected by the detector 408 while the side-scattered fluoresced light may be  
30 reflected by the second concave mirror 415, propagate out of the composite microscope

objective 60 via the aberration corrector plate 414, and be detected by the second light detection system 413.

In some embodiments, one or more control circuits may be coupled with one or more of the detector 408, the second light detection system 413, and the light source 412 to process detected light signals. As known by one skilled in the art, the control circuit may include an amplifier to amplify detected light signals, a noise filter to reduce noise interference, and a processor to process detected light signals and generate corresponding information regarding the properties of the object.

## 10 Alternative Combined Microscope Objective

FIGs. 11, 12 and 13 illustrate the build-up of a composite microscope objective 60 adapted for imaging light scattered from and fluoresced by an object present within a viewing zone. The illustrated composite microscope objective comprises a viewing zone, a concave mirror arrangement 601, 610, 617, an exit area and an illumination beam forming arrangement 505, as illustrated in FIG. 8A. It should be noted that in Fig. 11, 12 and 13 the beam forming arrangement is not illustrated. The viewing zone in Fig. 11 may be located in e.g. a channel 604 of a cuvette 603. In FIG. 12, the viewing zone may be located e.g. along the droplets of the jet stream 519 leaving the nozzle 518. In FIG. 13, the viewing zone maybe located e.g. in the plane of the substrate. The exit area of the microscope objective is an area through which scattered light and fluoresced light impinging from an object present in the viewing zone passes, which scattered and fluorescent light is reflected by the concave mirror of the microscope objective. The aberration corrector plate 602 in FIG. 11, 612 in FIG. 12 and 618 in FIG. 13 may be located in the exit area. It should be noted that the corrector plate may be used, in particular in combination with a spherical mirror 601, 610, 617. However the corrector plate may be omitted when using a concave mirror having already implemented a correcting shape. Thus, the exit area does not have to include a corrector, if a concave mirror has an appropriate shape and the gain of the corrector plate is not required. As can be seen in FIGs. 11, 12 and 13, the viewing zone is arranged between the concave mirror arrangement and the exit area. The concave mirror 601, 610, 617 is arranged to reflect scattered and fluoresced light impinging from an object present in the



viewing zone to the exit area. The illumination beam forming arrangement 505 is illustrated e.g. in FIG. 8A. Fig. 8A illustrates an arrangement of FIG. 11 having attached illumination beam arrangement 505 to the cuvette 603. The illumination beam arrangement 505 is arranged so that an illumination beam entering the illumination beam forming arrangement is pre-definitely formed at the viewing zone. A path of an illumination beam from an illumination system can be seen e.g. in FIG. 1 or 3A. FIGs 11, 12 and 13 as well as FIG. 8A illustrate that the concave mirror arrangement, the viewing zone and the exit area are arranged along a first axis, also referred to as x-axis. FIG. 9A illustrated that an optical image of the viewing zone, e.g. within channel 604 in FIG. 9A is formed outside the composite microscope objective in the image plane 605 with image locations 606, 607 and 608. The illumination beam forming arrangement 505 is arranged so that an illumination beam impinges the viewing zone along a second axis, also referred to as z-axis, which is substantially perpendicular to said x-axis. The above described cuvette 603 may be manufactured of an optical transparent material, wherein the viewing zone is formed in the cuvette, in particular in the channel 604 of the cuvette 603. The channel extends along a third axis, also referred to as y-axis being substantially perpendicular to the x-axis and the z-axis, so that a liquid flow in the channel flows along the y-axis, as illustrated e.g. in FIG. 5D, wherein the viewing zone is located within the channel. FIG. 8 and 8A illustrated that the cuvette 603 may be of rectangular cross section in a plane of the first axis/x-axis and second axis/z-axis. It should be noted that the cross section of the cuvette 603 may also be of a form, that a sheath flow covering the sample flow forces the sample flow into a rectangular cross section. The cross section of the channel 604 may be constant along the y-axis, but may also vary along the y-axis. In particular the channel may have a focused cross section in the area of the viewing zone. The viewing area may include a plurality of predefined viewing points distributed along the y-axis for different illumination wavelengths, as can be seen in FIG. 33, or along the z-axis, which may be a varying focal point varying along the z-axis, when adjusting the objective 60 with respect to the illumination system 50, as will described later. Although element 505 may be allocated to the illumination system 50, element 505 may also be part of the objective 60, in particular it may be attached to the cuvette 603. The illumination beam forming arrangement 505 is adapted to compress an illumination beam, so that the illumination beam in the viewing

zone has a compressed dimension along the y-axis. The illumination beam forming arrangement 505 may be a cylindrical lens, in particular having a cylindrical axis parallel to the x-axis, as can be seen in FIGs. 5D and 5E. It should be noted that the illumination beam forming arrangement can be assembled by a plurality of optical elements, so that the arrangement 505 may not have a defined axis. The aberration corrector arrangement 602, 612, 618 may be arranged in the exit area, as can be seen in FIGs. 11, 12 and 13. The aberration corrector arrangement may be an aspheric lens made of optically transparent material. As can be seen in FIG. 9A, said aberration corrector arrangement may have a first zone with negative optical power, a second zone radially inside the first zone with positive optical power, and a neutral zone between the first zone and the second zone. The neutral zone in FIG. 9A is thinner than each of the first zone and the second zone, so that light reflected from the concave mirror arrangement passing through said aberration corrector arrangement forms a focal area. Although FIG. 9A illustrates a corrector plate with convex and concave portions, it should be noted that the positive and negative optical power may be achieved by using different optical materials at different locations of the corrector plate. The concave mirror arrangement 601, the viewing zone and the aberration corrector arrangement 602 form a reversed Schmidt camera. The concave mirror arrangement may be formed by plane-convex lens, as can be seen in FIG. 11. The concave mirror may be a plano-concave back surface mirror. The plano-concave back surface mirror may be made from an optically transparent material. As can be seen in FIG. 8A a plano-surface of said plano-concave back surface mirror is optically coupled to a flat surface of said cuvette. Plano-concave back surface mirror means that although the optical lens body is a plano-convex lens body, the surface when seeing into the mirror, which is the inside of the optic body, is concave. The plano-surface of said plano-concave back surface mirror may also be optically coupled to said flat, transparent substrate, as can be seen in FIG. 13. Said concave mirror may also be a front surface mirror, as can be seen from FIG. 12. It should be noted that the mirror of FIG. 12 can also be used in combination with a cuvette, and the mirror of FIG. 11 can also be used for a jet stream. The concave mirror arrangement, the aberration corrector arrangement and the illumination beam forming arrangement may be attached to the cuvette by at least one of index matching gel, index matching fluid, optical adhesive

material and optical contact bonding. It should be noted that also a combination may be used for attaching.

As can be seen in FIGs. 1, 3A, 31, 32 or 34-38, the composite microscope objective 60 may be combined with or comprise an illumination system. Although not mandatory, the illumination may be an illumination system as described above, in particular with a laser source 501, an collimating optical arrangement 502 to form a collimated laser beam and a beam shaping arrangement 504, 505 being adapted to shape a collimated beam, wherein the beam shaping arrangement includes the illumination beam forming arrangement 505. The laser source may be a laser diode and the collimating arrangement may be arranged with respect to the laser diode so as to form a collimated beam. As an alternative, the laser source may be a conventional laser with an optic arrangement to form a collimated beam of a desired cross section. The laser diode and the collimation optical arrangement, or alternatively the conventional laser with the optics are adapted to form a beam having an elliptical cross section having a major axis and a minor axis, wherein the minor axis is oriented substantially along the y-axis and the major axis is oriented substantially along the x-axis, as can be seen in FIG. 5E. The beam shaping arrangement may include a major axis optical beam compressing arrangement 504 being adapted to compress at least the major axis of the collimated elliptical beam. The illumination beam forming arrangement 505 is adapted to compress at least the minor axis of the collimated elliptical beam. This can be seen for example in FIGs 1, 3A or 6.

The viewing zone may be movable along the z-axis with respect to the illumination system so as to vary a focus of the compressed elliptical beam within the viewing zone along the z-axis. This allows a scanning along the z-axis. In particular this allows to sense or scan properties of a cell in the viewing zone at different locations. It should be understood, that either the objective 60 may be controllably moved or the illumination system 50 or both. It should also be understood that the variation of the focus may also be achieved by moving single components of the illumination system, e.g. one of the mirrors 523b, 523a or the element 504, as illustrated in FIG. 7. Also single components of the objective may be moved to vary the focus along the z-axis. The actuation can be conducted by e.g. piezo actuators or acoustic actuators. In particular the varying focus can be achieved by a modulation or an sinusoidal oscillation of the respective component. Thus the cuvette

is movable with respect to the laser source so as to spatially vary a focus of the laser source in the channel. For this purpose, a control unit can be provided being adapted to control the movement of components of the composite microscope objective along the z-axis so as to spatially vary a focus of the laser source in the channel. It should be noted that likewise also  
5 a variation of the focus can be achieved along the y-axis or even the x-axis.

### **Combined Wavelength Division Multiplexer (WDM) with Semiconductor Photo Detector**

FIGs. 25, 27, and 28 illustrate a wavelength division multiplexer (WDM) for  
10 separating light emitted from a light source into multiple colored bands. The wavelength division multiplexer may comprise an imaging optical arrangement 902, a dichroic filter arrangement 903, 904, a semiconductor photo detector 906 and a focusing optical arrangement 905. The imaging optical arrangement 902 forms a beam of light from the light emitted from a light source 901 and produces an image of substantially the same size  
15 as the effective size of said imaging optical arrangement. The light source may be an outlet of an optical fiber, which fiber may transfer detected light from the microscope objective 60 to the WDM. The dichroic filter arrangement 903, 904 may be located between said imaging optical arrangement 902 and said image, and separates the beam of light into a first branch and a second branch of distinctive colors. As can be seen in FIG. 25, the first branch  
20 travels toward element 905, whereas the second branch travels toward element 907. The semiconductor photo detector 906 is located in the first branch behind the focusing optical arrangement 905, which is located between the dichroic filter arrangement 903, 904 and the semiconductor photo detector 906 so as to focus the beam of light onto the semiconductor photo detector. Light means an electromagnetic wave, coherent or non-coherent,  
25 particularly having a wavelength which transits the used optical elements. In particular, the term light is not limited to the visible part of light, e.g., light between 380nm and 780nm. It should be noted that also infrared light and ultraviolet light may be used, if the used optical components are capable of being operated with such wavelengths. The focusing optical element arrangement 905 is located in or in proximity to an image plane of said image. It  
30 should be noted that the imaging arrangement 902 as well as the focusing arrangement 905

may be composed of more than one optical element. In particular, a plurality of lenses may be combined so as to form the imaging arrangement 902 or the focusing arrangement 905. Likewise the dichotic filters may be composed of more than one filter or optic element. In particular to compose particular properties of the respective arrangements. The focusing

5 optical arrangement and the semiconductor photo sensor may be arranged to each other that the beam of light is focused to a spot having a diameter of less than 1.0 mm, particularly of less than 0.6 mm. In particular when using semiconductor sensors the signal to noise ration SNR can be significantly reduced. As can be seen in FIG. 25, the wavelength division multiplexer as described above may further comprise an image relay optical arrangement

10 907. This image relay optical arrangement may be located in or in proximity to an image plane produced by said imaging optical arrangement in the second branch, wherein said image relay optical arrangement is adapted to produce an image of said imaging optical arrangement in a third branch having substantially the same size as the image in the second branch. The third branch in FIG. 25 is the beam traveling from the element 907 toward

15 element 909. The effective size of the optical element is the area where beams from the object transit the optical element. Consequently, producing an image of substantially the same size as the effective size of said optical element means that between the optical element and the image the beam is within a virtual parallel tube. For illustration purposes, in the hypothetical case the object is a pinhole the optical element produces a collimated

20 beam. The image relay optical arrangement 907 may be a concave mirror. Alternatively the image relay optical arrangement 907 may be a combination of a lens and a mirror, in particular a plane mirror. The wavelength division multiplexer as described above may further comprise an additional dichroic filter arrangement 909, wherein the additional dichroic filter arrangement is located between said image relay optical arrangement 907 and

25 an image produced by said image relay optical arrangement 907. Said additional dichroic filter arrangement 909 from the third branch produces a fourth branch and a fifth branch of the beam of light having distinctive colors. The fourth branch in FIG. 25 is the beam traveling from the dichroic filter 909 toward the focusing element 908, whereas the fifth branch is the beam traveling from the dichroic filter toward the element 910. The above

30 described wavelength division multiplexer further may comprise an additional focusing optical arrangement 908 and an additional semiconductor photo detector, wherein the

additional focusing optical arrangement 908 is located in the fourth branch and focuses the beam of light in the fourth branch so as to focus the beam of light onto the additional semiconductor photo detector. The wavelength division multiplexer may further comprise a plurality of image relay optical arrangements 910, 911, 912, 913, a plurality of dichroic filter arrangements 914, 915, 916, 917, a plurality of semiconductor photo detectors and a plurality of focusing optical arrangements 918, 919, 920, 921, wherein each of the plurality of focusing optical arrangements is arranged between a respective one of the plurality of dichroic filter arrangements and a respective one of the plurality of semiconductor photo detectors so as to form a cascaded arrangement, as can be seen in FIG. 25. The additional focused spots may have a diameter of less than 1.0 mm, particularly of less than 0.6 mm for multiple colored bands of said beam of light. The plurality of dichroic filter arrangements are arranged in a common plane, as can be seen in FIG. 25A. The wavelength division multiplexer may further comprise a plan-parallel optical basis having a first surface and second surface parallel thereto, wherein the plurality of dichroic filter arrangements are arranged parallel, preferably in abutment to the first surface of the plan-parallel optical basis, as described with respect to the WDM 90. The dichroic filter arrangements are assembled using a template that includes two optically flat glass plates bonded together in optical contact, wherein the dichroic filter arrangements are bonded to a filter holder using the template such that a coated filter surface of the dichroic filter arrangements are indented and optically parallel to a reference surface of the filter holder, as can be seen in FIGs 29A, B and C. The reference surface of the filter holder rests against an optically flat surface of an reference block included in the wavelength division multiplexer thereby providing consistent optical alignment when installing the dichroic filter arrangements into the wavelength division multiplexer. The respective image relay optical arrangements may be formed into the second surface of the plan-parallel optical basis, as can be seen in FIG. 25A. At least one of the semiconductor photo detectors is an avalanche photo diode detector. As an alternative or in addition, at least one of the semiconductor photo detectors is a carbon nanotube detector.

30

## Industrial Applicability

Although an embodiment of the present disclosure of an LD based optical system for flow cytometric application has been described in some detail, and equally advantageous embodiments have also been described for a stream based flow cytometric instrument, it will be apparent to those of ordinary skill in the art that many modifications and variations of the described embodiment are possible in the light of the above teachings without departing from the principles and concepts of the disclosure as set forth in the claims.

Although an embodiment of the present disclosure of wavelength division multiplexing device for separating light beam from an extended light source into multiple color bands has been described in some detail, and several other equally advantageous embodiments have also been described, it will be apparent to those ordinary skilled in the art that many modifications and variations of the described embodiments are possible in the light of the above teachings without departing from the principles and concepts of the disclosure as set forth in the claims.

Although the present disclosure describes certain exemplary embodiments, it is to be understood that such disclosure is purely illustrative and is not to be interpreted as limiting. Consequently, without departing from the spirit and scope of the disclosure, various alterations, modifications, and/or alternative applications of the disclosure will, no doubt, be suggested to those skilled in the art after having read the preceding disclosure. Accordingly, it is intended that the following claims be interpreted as encompassing all alterations, modifications, or alternative applications as fall within the true spirit and scope of the disclosure.

25

## WHAT IS CLAIMED IS:

1. A flow cytometer (40) comprising:
  - a) a laser diode ("LD") based optical subsystem (50) for directing a beam of  
5 light into a viewing zone of said flow cytometer (40) through which a sample liquid carrying particles flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, the optical subsystem (50) including:
    - i. a LD for emitting a diverging beam of light from an edge thereof, the  
10 diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;
    - ii. a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass  
15 through the viewing zone;
    - iii. a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath flow; and  
20 v. a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which particles pass through the viewing zone whereby:
      - 1) said minor axis of said beam of light becomes focused at the  
viewing zone; and
      - 2) the size of said major axis of said elliptical beam of light at  
25 the viewing zone remains essentially unchanged;
  - b) a composite microscope objective (60) for imaging light scattered from and fluoresced by a particle present within the viewing zone, the composite microscope objective (60) including:
    - i. a concave mirror upon which scattered and fluoresced light impinges;  
30



ii. an aberration corrector plate made of optically transparent material wherein said aberration corrector plate is an aspheric lens that has:

1) a first zone of said aberration corrector plate outside a neutral zone thereof where said aberration corrector plate:

5 A. is thinnest; and

B. has negative optical power; and

2) a second zone of said aberration corrector plate inside the neutral zone has positive optical power

light reflected from the composite microscope objective (60) passing  
10 through said aberration corrector plate,

the viewing zone of said flow cytometer (40) being located between said concave mirror and said aberration corrector plate;

c) a fluidic subsystem (70) for supplying the liquid sheath flow to the viewing zone, the liquid sheath flow lacking pulsations, the fluidic subsystem (70) including:

15 i. a liquid pump for supplying liquid drawn from a reservoir;

ii. a T coupling having at least one (1) inlet and two (2) outlets,

1) the inlet of said T coupling receiving liquid from said liquid pump;

2) a first fraction of the liquid received by the inlet flowing via a  
20 first one of the outlets and via a bypass conduit back to the reservoir; and

3) a second fraction of the liquid received by the inlet flowing via a second one of the outlets and via a particle filter to the viewing zone of said flow cytometer (40);

d) a peristaltic pump 80 for supplying the sample liquid carrying the particles,  
25 the sample liquid being hydrodynamically focused within the viewing zone by the liquid sheath flow, the peristaltic pump 80 comprising:

i. a pump housing having an arcuate curved track formed therein that extends between a pump inlet and a pump outlet;

ii. a plurality of rollers that are attached to a rotor, the rollers having a  
30 substantially equal angular spacing between each pair of immediately adjacent rollers, the

rotor being rotatable together with the rollers attached thereto inside said pump housing;  
and

ii a compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing, the arcuate curved track including:

5 1) an exit section wherein, as a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks contact with said compressible tube; and

2) at least one pumping section along the arcuate curved track  
10 between the pump inlet and the pump outlet wherein said compressible tube is compressed to fully closed by at least one of said rollers; and

e) a wavelength division multiplexer 90 ("WDM (90)") for separating into multiple colored bands a beam of light emitted initially from the viewing zone and imaged by the composite microscope objective (60) into an optical fiber for transmission to the  
15 WDM (90), the WDM (90) comprising:

i. a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;

ii. at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light  
20 into two (2) branches of distinctive colors;

iii. a focusing optical element located in one of said branches, wherein the beam of light in said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and

iv. an image relay optical element located near the image produced by  
25 said collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.

2. The flow cytometer (40) of claim 1 wherein said cuvette has a rectangularly-shaped , and wherein the viewing zone of the flow cytometer (40) is located within a  
30 channel having a rectangularly-shaped cross-section that is located within said cuvette.

3. The flow cytometer (40) of claim 1 wherein said cuvette has a tubularly-shaped cross-section, and wherein the viewing zone of the flow cytometer (40) is located within a channel having a circularly-shaped cross section that is located within said cuvette.

4. The flow cytometer (40) of claim 1 wherein the sample liquid and the liquid  
5 sheath flow form a jet stream in which the viewing zone of the flow cytometer (40) is located.

5. The flow cytometer (40) of claim 2 wherein said cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

6. The flow cytometer (40) of claim 2 wherein said cylindrical focusing  
10 element is separated from said rectangularly-shaped cuvette.

7. The flow cytometer (40) of claim 3 wherein said cylindrical focusing element is separated from said tubularly-shaped cuvette.

8. The flow cytometer (40) of claim 4 wherein said cylindrical focusing element is separated from said jet stream.

15 9. The flow cytometer (40) of claim 1 further comprising a polarization conditioning element through which said collimated elliptical beam of light passes.

10. The flow cytometer (40) of claim 1 wherein an optical image of the viewing zone is formed outside the composite microscope objective (60).

11. The flow cytometer (40) of claim 10 wherein the viewing zone is located  
20 within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

12. The flow cytometer (40) of claim 11 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

13. The flow cytometer (40) of claim 12 wherein the plano-surface of said  
25 plano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

14. The flow cytometer (40) of claim 13 wherein an optical adhesive material accomplishes the optical coupling.

15. The flow cytometer (40) of claim 13 wherein an index matching gel accomplishes the optical coupling.

30 16. The flow cytometer (40) of claim 13 wherein an index matching fluid accomplishes the optical coupling.

Specification.doc

17. The flow cytometer (40) of claim 13 wherein optical contact bonding accomplishes the optical coupling.

18. The flow cytometer (40) of claim 13 wherein the plano-concave back surface mirror formed integrally with said cuvette means.

5 19. The flow cytometer (40) of claim 11 wherein said aberration corrector plate is a plano-aspherical lens.

20. The flow cytometer (40) of claim 19 wherein a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said plano-concave back surface mirror.

10 21. The flow cytometer (40) of claim 20 wherein an index matching gel accomplishes the optical coupling.

22. The flow cytometer (40) of claim 20 wherein an index matching fluid accomplishes the optical coupling.

15 23. The flow cytometer (40) of claim 20 wherein optical contact bonding accomplishes the optical coupling.

24. The flow cytometer (40) of claim 20 wherein the plano-aspherical lens is formed integrally with said cuvette.

25. The flow cytometer (40) of claim 19 wherein said aberration corrector plate is detached from said cuvette.

20 26. The flow cytometer (40) of claim 10 wherein the viewing zone is inside a jet stream.

27. The flow cytometer (40) of claim 25 wherein said concave mirror is a front surface mirror.

25 28. The flow cytometer (40) of claim 10 wherein the viewing zone is located on a surface of a flat, transparent substrate.

29. The flow cytometer (40) of claim 28 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

30. The flow cytometer (40) of claim 29 wherein the plano-surface of said plano-concave back surface mirror is optically coupled to said flat, transparent substrate.

30 31. The flow cytometer (40) of claim 30 wherein an optical adhesive material accomplishes the optical coupling.

Specification.doc

32. The flow cytometer (40) of claim 30 wherein an index matching gel accomplishes the optical coupling.

33. The flow cytometer (40) of claim 30 wherein an index matching fluid accomplishes the optical coupling.

5 34. The flow cytometer (40) of claim 30 wherein optical contact bonding accomplishes the optical coupling.

35. The flow cytometer (40) of claim 29 wherein said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

10 36. The flow cytometer (40) of claim 28 wherein said aberration corrector plate is detached from said flat, transparent substrate.

37. The flow cytometer (40) of claim 1 wherein the particle filter has inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so that air becomes trapped within the particle filter at the inlet thereto.

15 38. The flow cytometer (40) of claim 37 wherein when said liquid pump is turned off air cannot enter into the bypass conduit.

39. The flow cytometer (40) of claim 38 further comprising a small capsule disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

20 40. The flow cytometer (40) of claim 38 further comprising a length of tubing disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

41. The flow cytometer (40) of claim 38 further comprising an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

25 42. The flow cytometer (40) of claim 38 further comprising an adjustable valve located between the second one of the outlets of the T coupling and the viewing zone for restricting liquid flow therebetween.

43. The flow cytometer (40) of claim 38 wherein the throughput of the liquid pump is adjustable.

30 44. The flow cytometer (40) of claim 1 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further

Specification.doc

including at least one recess section located between said pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

5           45.     The flow cytometer (40) of claim 44 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to the pump outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

10           46.     The flow cytometer (40) of claim 44 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate  
15 curved track.

            47.     The flow cytometer (40) of claim 44 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

            48.     The flow cytometer (40) of claim 46 wherein both:  
20           a)     angular spacing between adjacent pairs of recess sections; and  
            b)     angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section  
are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

25           49.     The flow cytometer (40) of claim 47 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

30           50.     The flow cytometer (40) of claim 1 wherein a speed of said rotor is programmably controlled to vary substantially in inverse proportion to the fluid volume

Specification.doc

change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

51. The flow cytometer (40) of claim 1 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of the beam of light having distinctive colors.

52. The flow cytometer (40) of claim 51 wherein another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

53. The flow cytometer (40) of claim 52 wherein successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

54. The flow cytometer (40) of claim 52 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

55. The flow cytometer (40) of claim 54 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90) thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).

56. A LD based optical subsystem (50) for impinging a beam of light into a viewing zone in which a particle is present, the optical subsystem (50) comprising:

a) a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;

b) a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass through the viewing zone;

Specification.doc

c) a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath flow; and

5 d) a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which particles pass through the viewing zone whereby:

i. said minor axis of said beam of light becomes focused at the viewing zone; and

10 ii. the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

57. The optical subsystem (50) of claim 56 further comprising a cuvette having a rectangularly-shaped cross-section, and wherein the viewing zone is located within a channel having a rectangularly-shaped cross section that is located within said cuvette.

15 58. The optical subsystem (50) of claim 56 further comprising a cuvette having a tubularly-shaped cross-section, and wherein the viewing zone is located within a channel having a circularly-shaped cross-section that is located within said cuvette.

59. The optical subsystem (50) of claim 56 wherein the sample liquid and the liquid sheath flow form a jet stream in which the viewing zone is located.

20 60. The optical subsystem (50) of claim 57 wherein said cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

61. The optical subsystem (50) of claim 57 wherein said cylindrical focusing element is separated from said rectangularly-shaped cuvette.

25 62. The optical subsystem (50) of claim 58 wherein said cylindrical focusing element is separated from said tubularly-shaped cuvette.

63. The optical subsystem (50) of claim 59 wherein said cylindrical focusing element is separated from said jet stream.

64. The optical subsystem (50) of claim 56 further comprising a polarization conditioning element through which said collimated elliptical beam of light passes.

30 65. A method for delivering an elliptically shaped beam of light using a LD based optical subsystem (50), the beam of light having a smooth profile at a focus of a

Specification.doc



minor axis thereof that is located at a viewing zone through which a sample liquid flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, the method comprising the steps of:

- a) providing a LD that emits a diverging beam of light from an edge thereof,  
5 the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;
- b) impinging the diverging beam of light emitted by the LD upon a collimating lens for converting the diverging beam of light emitted therefrom into a collimated elliptical beam of light wherein the minor axis of said collimated elliptical beam of light is  
10 oriented parallel to a direction in which sample liquid passes through the viewing zone;
- c) after passing through said collimating lens, impinging the collimated elliptical beam of light upon an beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which sample liquid  
15 passes through the viewing zone becomes less than a width of said liquid sheath flow; and
- d) after passing through said beam compressing optical element, impinging the beam of light upon a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which sample liquid passes through the viewing zone whereby:  
20
  - i. said minor axis of said beam of light becomes focused at the viewing zone; and
  - ii. the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

66. The method of claim 65 wherein the viewing zone is located within a  
25 channel having a rectangularly-shaped cross-section that is located within a cuvette.

67. The method of claim 65 wherein the viewing zone is located within a channel having a circularly-shaped cross-section that is located within a cuvette.

68. The method of claim 65 wherein the viewing zone is located within a jet stream.

30 69. The method of claim 66 further comprising a step of establishing an optical contact between said cylindrical focusing element and an entrance face of said cuvette.

Specification.doc

70. The method of claim 66 further comprising a step of establishing a spacing between said cylindrical focusing element and said cuvette.

71. The method of claim 67 further comprising a step of establishing a spacing  
5 between said cylindrical focusing element and said cuvette.

72. The method of claim 68 further comprising a step of establishing a spacing between said cylindrical focusing element and said jet stream.

73. The method of claim 65 further comprising a step of inserting a polarization conditioning element between the collimating lens and the beam compressing optical  
10 element whereby the collimated elliptical beam of light passes through the polarization conditioning element.

74. A composite microscope objective (60) adapted for imaging light scattered from and fluoresced by a particle present within a viewing zone comprising:

a) a concave mirror upon which scattered and fluoresced light impinges;  
15 b) an aberration corrector plate made of optically transparent material wherein said aberration corrector plate is an aspheric lens that has:

i. a first zone of said aberration corrector plate outside a neutral zone thereof where said aberration corrector plate:

1) is thinnest; and  
20 2) has negative optical power; and

ii. a second zone of said aberration corrector plate inside the neutral zone has positive optical power,

light reflected from the composite microscope objective (60) passing through said aberration corrector plate,

25 the viewing zone being located between said concave mirror and said aberration corrector plate.

75. The composite microscope objective (60) of claim 74 wherein an optical image of the viewing zone is formed outside the composite microscope objective (60).

76. The composite microscope objective (60) of claim 75 wherein the viewing  
30 zone is located within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

Specification.doc

77. The composite microscope objective (60) of claim 76 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

78. The composite microscope objective (60) of claim 77 wherein a plano-surface of said plano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

79. The composite microscope objective (60) of claim 78 wherein an optical adhesive material accomplishes the optical coupling.

80. The composite microscope objective (60) of claim 78 wherein an index matching gel accomplishes the optical coupling.

81. The composite microscope objective (60) of claim 78 wherein an index matching fluid accomplishes the optical coupling.

82. The composite microscope objective (60) of claim 78 wherein optical contact bonding accomplishes the optical coupling.

83. The composite microscope objective (60) of claim 78 wherein the plano-concave back surface mirror formed integrally with said cuvette means.

84. The composite microscope objective (60) of claim 76 wherein said aberration corrector plate is a plano-aspherical lens.

85. The composite microscope objective (60) of claim 84 wherein a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said plano-concave back surface mirror.

86. The composite microscope objective (60) of claim 85 wherein an index matching gel accomplishes the optical coupling.

87. The composite microscope objective (60) of claim 85 wherein an index matching fluid accomplishes the optical coupling.

88. The composite microscope objective (60) of claim 85 wherein optical contact bonding accomplishes the optical coupling.

89. The composite microscope objective (60) of claim 85 wherein the plano-aspherical lens is formed integrally with said cuvette.

90. The composite microscope objective (60) of claim 84 wherein said aberration corrector plate is detached from said cuvette.

91. The composite microscope objective (60) of claim 75 wherein the viewing zone is inside a jet stream.

92. The composite microscope objective (60) of claim 90 wherein said concave mirror is a front surface mirror.

5 93. The composite microscope objective (60) of claim 75 wherein the viewing zone is located on a surface of a flat, transparent substrate.

94. The composite microscope objective (60) of claim 93 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

10 95. The composite microscope objective (60) of claim 94 wherein a plano-surface of said plano-concave back surface mirror is optically coupled to said flat, transparent substrate.

96. The composite microscope objective (60) of claim 95 wherein an optical adhesive material accomplishes the optical coupling.

15 97. The composite microscope objective (60) of claim 95 wherein an index matching gel accomplishes the optical coupling.

98. The composite microscope objective (60) of claim 95 wherein an index matching fluid accomplishes the optical coupling.

99. The composite microscope objective (60) of claim 95 wherein optical contact bonding accomplishes the optical coupling.

20 100. The composite microscope objective (60) of claim 94 wherein said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

101. The composite microscope objective (60) of claim 93 wherein said aberration corrector plate is detached from said flat, transparent substrate.

25 102. A method for characterizing microscopic species using a microscope objective device comprising:

a) A concave mirror;

b) An aberration corrector plate made of optically transparent material wherein said aberration corrector plate is an aspheric lens with the zone of said plate means outside of the neutral zone wherein the thickness of said plate means is thinnest, having negative  
30 optical power, and the zone inside the neutral zone having positive optical power

c) A viewing zone located in between said concave mirror and said aberration corrector plate.

103. The method of claim 102 wherein an optical image of the viewing zone is formed outside the device.

5 104. The method of claim 103 wherein the viewing zone is located within a flow channel contained in a rectangularly-shaped cuvette means made of optically transparent material.

105. The method of claim 104 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

10 106. The method of claim 105 wherein a plano surface of said plano-concave back surface mirror means is optically coupled to a flat surface of said cuvette means.

107. The method of claim 106 wherein an optical adhesive material accomplishes the optical coupling.

15 108. The method of claim 106 wherein an index matching gel accomplishes the optical coupling.

109. The method of claim 106 wherein an index matching fluid accomplishes the optical coupling.

110. The method of claim 106 wherein optical contact bonding accomplishes the optical coupling.

20 111. The method of claim 106 wherein the plano-concave back surface mirror is formed integrally with said cuvette.

112. The method of claim 104 wherein said aberration corrector plate is a plano-aspherical lens.

25 113. The method of claim 112 wherein a plano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette means opposite of said concave mirror.

114. The method of claim 113 wherein an index matching gel accomplishes the optical coupling.

30 115. The method of claim 113 wherein an index matching fluid accomplishes the optical coupling.

116. The method of claim 113 wherein optical contact bonding accomplishes the optical coupling.

117. The method of claim 113 wherein the plano-aspherical lens is formed integrally with said cuvette.

5 118. The method of claim 112 wherein said aberration corrector plate is detached from said cuvette.

119. The method of claim 102 wherein the viewing zone is inside a jet stream.

120. The method of claim 119 wherein said concave mirror is a front surface mirror.

10 121. The method of claim 102 wherein the viewing zone is located on a surface of a flat, transparent substrate.

122. The method of claim 121 wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

123. The method of claim 122 wherein a plano surface of said plano-concave  
15 back surface mirror means is optically coupled to said flat, transparent substrate.

124. The method of claim 123 wherein an optical adhesive material accomplishes the optical coupling.

125. The method of claim 123 wherein an index matching gel accomplishes the optical coupling.

20 126. The method of claim 123 wherein an index matching fluid accomplishes the optical coupling.

127. The method of claim 123 wherein optical contact bonding accomplishes the optical coupling.

25 128. The method of claim 122 wherein said plano-concave back surface mirror is formed integrally with said flat, transparent substrate.

129. The method of claim 128 wherein said aberration corrector plate is detached from said flat, transparent substrate.

130. A fluidic subsystem (70) for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem (70), the fluidic subsystem (70) comprising:

- 30 a) a liquid pump for supplying liquid drawn from a reservoir;  
b) a T-coupling having at least one (1) inlet and two (2) outlets,

Specification.doc

- i. the inlet of said T coupling receiving liquid from said liquid pump;
- ii. a first fraction of the liquid received by the inlet flowing via a first one of the outlets and via a bypass conduit back to the reservoir; and
- iii. a second fraction of the liquid received by the inlet flowing via a second one of the outlets and via a particle filter to the outlet of the fluidic subsystem (70).

131. The fluidic subsystem (70) of claim 130 wherein the particle filter has inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so that air becomes trapped within the particle filter at the inlet thereto.

132. The fluidic subsystem (70) of claim 131 wherein when said liquid pump is turned off air cannot enter into the bypass conduit.

133. The fluidic subsystem (70) of claim 132 further comprising a small capsule disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

134. The fluidic subsystem (70) of claim 132 further comprising a length of tubing disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

135. The fluidic subsystem (70) of claim 132 further comprising an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

136. The fluidic subsystem (70) of claim 132 further comprising an adjustable valve located between the second one of the outlets of the T-coupling and the outlet of the fluidic subsystem (70) for restricting liquid flow therebetween.

137. The fluidic subsystem (70) of claim 132 wherein the throughput of the liquid pump is adjustable.

138. A method for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem (70), the method comprising:

- a) a liquid pump for supplying liquid drawn from a reservoir;
- b) a T coupling having at least one (1) inlet and two (2) outlets,
  - i. the inlet of said T coupling receiving liquid from said liquid pump;
  - ii. a first fraction of the liquid received by the inlet flowing via a first one of the outlets and via a bypass conduit back to the reservoir; and

Specification.doc

iii. a second fraction of the liquid received by the inlet flowing via a second one of the outlets and via a particle filter to the outlet of the fluidic subsystem (70).

139. The method of claim 138 wherein during normal operation certain amount of air is trapped near the inlet portion of said filter cartridge means.

5 140. The method of claim 139 wherein said reservoir means holds sufficient amount of liquid such that when said pump means is turned off, portion of the tubing between said T-coupling means and said reservoir means is still filled with liquid, preventing said trapped air from leaking into said bypass means.

141. The method of claim 140 wherein said reservoir means is a capsule.

10 142. The method of claim 140 wherein said reservoir means is a piece of tubing.

143. The method of claim 140 wherein an adjustable flow restrictor means is placed in the bypass route.

144. The method of claim 140 wherein an adjustable flow restrictor means is placed in the sheath route.

15 145. The method of claim 140 wherein the throughput of the sheath pump is adjustable.

146. A peristaltic pump 80 comprising:

a) a pump housing having an arcuate curved track formed therein that extends between a pump inlet and a pump outlet;

20 b) a plurality of rollers that are attached to a rotor, the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside said pump housing; and

c) a compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing, the arcuate curved track including:

25 i. an exit section wherein, as a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks contact with said compressible tube; and



ii. at least one pumping section along the arcuate curved track between the pump inlet and the pump outlet wherein said compressible tube is compressed to fully closed by at least one of said rollers.

147. The peristaltic pump 80 of claim 146 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

148. The peristaltic pump 80 of claim 147 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to the pump outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

149. The peristaltic pump 80 of claim 147 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

150. The peristaltic pump 80 of claim 147 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

151. The peristaltic pump 80 of claim 149 wherein both:

- a) angular spacing between adjacent pairs of recess sections; and
  - b) angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section
- are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

152. The peristaltic pump 80 of claim 150 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate

Specification.doc

curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

153. The peristaltic pump 80 of claim 146 wherein a speed of said rotor is  
5 programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

154. A method for delivering liquid using a peristaltic pump 80 comprising:  
a) a pump housing with arcuate curved track;  
10 b) A plurality of rollers attached to a rotor means rotatable inside said pump housing;  
c) Said plurality of rollers spaced at substantially equal angular spacing from each other;  
d) A compressible tube sandwiched between said rollers and the arcuate curved  
15 track of said pump housing;  
e) Said arcuate curved track of said pump housing including an exit section, wherein said compressible tube being progressively decompressed to full expansion when one of said rollers rolls off the compressible tube at the pump outlet;  
f) At least one pumping section along the arcuate curved track of said pump  
20 housing between the pump inlet and pump outlet wherein said compressible tube is compressed to full closure by one of said rollers.

155. The method of claim 154 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along the  
25 arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

156. The method of claim 155 wherein the peristaltic pump 80 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet; The angular  
30 spacing between the compression part of said recess section adjacent to the pump outlet and

said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

157. The method of claim 155 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

158. The method of claim 155 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

159. The method of claim 157 wherein both:

- a) angular spacing between adjacent pairs of recess sections; and
  - b) angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section
- are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

160. The method of claim 158 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

161. The method of claim 154 wherein a speed of said rotor of the peristaltic pump 80 is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

162. A WDM (90) for separating a beam of light emitted from an into multiple colored bands, the WDM (90) comprising:

- a) a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;

b) at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light into two (2) branches of distinctive colors;

c) a focusing optical element located in one of said branches, wherein the beam  
5 of light in said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and

d) an image relay optical element located near the image produced by said collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.  
10 163. The WDM (90) of claim 162 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of the beam of light having distinctive colors.

164. The WDM (90) of claim 163 wherein another focusing optical element is  
15 located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

165. The WDM (90) of claim 164 wherein successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands  
20 of said beam of light.

166. The WDM (90) of claim 164 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference  
25 surface of the filter holder.

167. The WDM (90) of claim 166 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90) thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).

30 168. A method for separating beam of light emitted from an into colored bands using a WDM (90) comprising:

Specification.doc

a) a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;

b) at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light into two  
5 (2) branches of distinctive colors;

c) a focusing optical element located in one of said branches, wherein the beam of light of said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and

d) an image relay optical element located near the image produced by said  
10 collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.

169. The method of claim 168 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of beam of  
15 light having distinctive colors.

170. The method of claim 169 wherein another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

171. The method of claim 170 wherein successive combinations of said image  
20 relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

172. The method of claim 170 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact,  
25 and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

173. The method of claim 172 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90)  
30 thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).

Specification.doc

174. An optical system for impinging beams of light into a viewing zone in which a sample flow carrying objects and a sheath flow pass through, comprising:

a first light source for emitting a first beam of light along a first beam path to illuminate objects in the viewing zone at a first location;

5 a second light source for emitting a second beam of light along a second beam path to illuminate objects in the viewing zone at a second location, wherein the wavelength of the second light source is different from the wavelength of the first light source;

a beam compressing optical element for reducing widths of the first and second beams of light on their major axes to a width less than the width of the sheath flow; and

10 a first chromatic compensation element located on at least one of the first beam path and the second beam path for compensating chromatic aberration in the viewing zone such that the first location and the second locations are on a common plane parallel to the direction of the sample flow.

175. The optical system of claim 174, further comprising a cuvette in which the  
15 viewing zone is located.

176. The optical system of any one of claims 174 and 175, wherein the sample flow and the sheath flow form a jet stream in which the viewing zone is located.

177. The optical system of any one of claims 174 to 176, further comprising a collimating lens for converting the first beam of light and the second beam of light into  
20 collimated elliptical beams of light, wherein the minor axes of the collimated elliptical beams of light are substantially parallel to the direction of the sample flow.

178. The optical system of any one of claims 174 to 177, wherein the beam compressing optical element reduces widths of the first and second beams of light on their major axes, wherein the major axes are substantially perpendicular to the direction of the  
25 sample flow.

179. The optical system of any one of claims 174 to 178, further comprising a cylindrical focusing element positioned adjacent to the viewing zone with an axis of the cylindrical focusing element being oriented perpendicular to the direction of the sample flow.

180. The optical system of claim 179, wherein the cylindrical focusing element focuses the first beam of light and the second beam of light on their minor axes in the viewing zone.

181. The optical system of any one of claims 174 to 180, further comprising a  
5 second chromatic compensation element, wherein the first chromatic compensation element is located on the first beam path, wherein the second chromatic compensation element is located on the second beam path.

182. The optical system of claim 181, wherein the first chromatic compensation element and the second chromatic compensation element have different optical properties.

10 183. The optical system of any one of claims 174 to 182, further comprising a first wavelength division multiplexer (WDM) and a second WDM to process light scattered from and fluoresced by objects at the first and second locations, respectively.

184. The optical system of any one of claims 174 to 183, further comprising a  
15 third light source for emitting a third beam of light along a third beam path to illuminate objects in the viewing zone at a third location, wherein the wavelength of the third light source is different from the wavelengths of the first and second light sources.

185. The optical system of claim 184, further comprising a third chromatic  
compensation element located on the third beam path for compensating chromatic  
aberration in the viewing zone such that the first location, the second location, and the third  
20 location are on the common plane parallel to the direction of the sample flow.

186. The optical system of any one of claims 184 and 185, further comprising a  
third wavelength division multiplexer (WDM) to process light scattered from and  
fluoresced by objects at the third location.

187. An optical system comprising:  
25 a first light source for emitting a first beam of light to illuminate objects at a first location in a viewing zone;

a composite microscope objective for imaging light scattered from and fluoresced  
by the objects at the first location in the viewing zone at an image plane external to the  
composite microscope, wherein the composite microscope includes a concave mirror and  
30 an aberration corrector plate, wherein the aberration corrector plate is an aspheric lens that  
has a first zone with negative optical power and a second zone with positive optical power

Specification.doc

radially inside the first zone, wherein the viewing zone is positioned between the concave mirror and the aberration corrector plate; and

a beam splitter for reflecting or transmitting scattered and fluoresced light, wherein the light source and the image plane are on two sides of the beam splitter.

5           188.   The optical system of claim 187, wherein the aspheric lens further comprises a neutral zone between the first and second zones.

189.   The optical system of claim 188, wherein the neutral zone is the thinnest portion of the aspheric lens.

10           190.   The optical system of any one of claims 187 to 189, further comprising a cuvette with a flow channel, wherein the viewing zone is located in the flow channel.

191.   The optical system of claim 190, further comprising a fluidic system to deliver the objects to the viewing zone in the flow channel.

192.   The optical system of any one of claims 190 and 191, wherein the cuvette has a rectangular-shaped cross section and is made of optically transparent material.

15           193.   The optical system of any one of claims 190 to 192, wherein the aspheric lens and the concave mirror are coupled to or separated from the cuvette.

194.   The optical system of any one of claims 190 to 193, wherein the aspheric lens and the concave mirror are coupled to the cuvette by one or more of an optical adhesive material, an index matching gel, an index matching fluid, and an optical contact  
20   bonding.

195.   The optical system of any one of claims 187 to 189, further comprising a jet stream, wherein the viewing zone is located in the jet stream.

196.   The optical system of any one of claims 187 to 189, further comprising a substrate, wherein the viewing zone is located on the surface of the substrate.

25           197.   The optical system of claim 196, wherein the substrate is flat and made of optically transparent material.

198.   The optical system of any one of claims 187 to 197, wherein the concave mirror is a plano-concave back surface mirror or a front surface mirror made of an optically transparent material.

30           199.   The optical system of any one of claims 187 to 198, wherein the aspheric lens is a plano-aspherical lens.

Specification.doc



200. The optical system of any one of claims 187 to 199, wherein the first beam of light is reflected by the beam splitter and enters the composite microscope objective, wherein the scattered and fluoresced light propagates out of the composite microscope objective and transmits through the beam splitter.

5           201. The optical system of claim 200, wherein the optical axis of the first beam of light reflected by the beam splitter and entering into the composite microscope objective is substantially parallel to the optical axis of the scattered and fluoresced light propagating out of the composite microscope objective.

10           202. The optical system of any one of claims 187 to 199, wherein the first beam of light transmits through the beam splitter and enters the composite microscope objective, and wherein the scattered and fluoresced light propagates out of the composite microscope objective and is reflected by the beam splitter.

15           203. The optical system of claim 202, wherein the optical axis of the first beam of light transmitting through the beam splitter and entering into the composite microscope objective is substantially parallel to the optical axis of the scattered and fluoresced light propagating out of the composite microscope objective.

204. The optical system of any one of claims 187 to 203, further comprising a detector to detect the scattered and fluoresced light propagating out of the composite microscope objective.

20           205. The optical system of claim 204, further comprising an optical transmission member for propagating the scattered and fluoresced light received at the image plane to the detector.

25           206. The optical system of any one of claims 204 and 205, further comprising a wavelength division multiplexer (WDM) to process the scattered and fluoresced light to be detected by the detector, wherein the scattered and fluoresced light is separated into multiple colored bands.

207. The optical system of claim 206, wherein the wavelength division multiplexer (WDM) comprises:

30           i. a collimating optical element that produces an image of substantially the same size as the effective size of the collimating optical element;

- ii. at least one dichroic filter located between the collimating optical element and the image, wherein the dichroic filter separates the collimated beam of light into two branches of distinctive colors;
- iii. a focusing optical element located in one of the branches, wherein the beam of light in the branch is focused to a spot by the focusing optical element; and
- iv. an image relay optical element located near the image produced by the collimating optical element in the other branch, wherein the image relay optical element produces an image of the collimating optical element at substantially unit magnification.

208. The optical system of claim 187, wherein the first light source emits coherent light or incoherent light.

209. The optical system of any one of claims 187 to 208, further comprising a second light source for emitting a second beam of light to illuminate objects at a second location in the viewing zone, wherein the first and second locations are spatially separated.

210. The optical system of claim 209, further comprising a first detector and a second detector to detect the scattered and fluoresced light by the objects at the first and second locations, respectively.

211. The optical system of claim 210, further comprising a first optical transmission member and a second optical transmission member for propagating the scattered and fluoresced light by the objects at the first and second locations received at the image plane to the first and the second detectors, respectively.

212. The optical system of any one of claims 210 and 211, further comprising a first wavelength division multiplexer (WDM) and a second WDM to process the scattered and fluoresced light to be detected by the first and second detectors, wherein the scattered and fluoresced light is separated into multiple colored bands.

213. A light detection system comprising:  
a concave mirror for reflecting light that propagates from a viewing zone; and  
a detector for measuring axial light loss produced by an object in the viewing zone by detecting light reflected by the concave mirror.

214. The light detection system of claim 213, wherein the detector is an axial light loss detector to measure the axial light loss produced by the object in order to determine the size of the object.

215. The light detection system of any one of claims 213 and 214, further comprising a first light source emitting a first beam of light to irradiate the object in the viewing zone, wherein the axis of irradiation is substantially perpendicular to the flow direction of the object.

216. The light detection system of claim 215, wherein the light reflected by the concave mirror includes forward scattered light and remaining light of the first beam of light, wherein the axial light loss of the first beam of light results from the object passing through the first beam of light, and wherein the optical axis of the remaining light is substantially paralleled to the axis of irradiation.

217. The light detection system of claim 216, wherein the forward scattered light and the remaining light have the same wavelength.

218. The light detection system of any one of claims 216 and 217, wherein the detector is in a heterodyne mode measuring coherent interference of the forward scattered light and the remaining light.

219. The light detection system of any one of claims 215 to 218, further comprising a second light emitting a second beam of light to irradiate the object in the viewing zone, wherein the wavelength of the second beam of light is different from the wavelength of the first beam of light.

220. The light detection system of claim 219, further comprising a filter upstream of the detector to separate the light irradiated by the first light source and reflected by the concave mirror from the light irradiated by the second light source and reflected by the concave mirror in order for the detector to measure them separately.

221. The light detection system of any one of claims 213 to 220, wherein the viewing zone is located within a microscope objective.

222. The light detection system of claim 221, further comprising a cylindrical lens coupled with the microscope objective, wherein the optical axis of the cylindrical lens is substantially perpendicular to the optical axis of the light reflected by the concave mirror.

223. The light detection system of any one of claims 221 and 222, further comprising a second concave mirror and an aberration corrector plate located on two sides of the viewing zone of the microscope objective, wherein the optical axes of the second concave mirror and the aberration corrector plate are substantially parallel to the optical  
5 axis of the light reflected by the concave mirror.

224. The light detection system of claim 223, wherein light side-scattered from and fluoresced by the object in the viewing zone is reflected by the second concave mirror and propagates out of the microscope objective via the aberration corrector plate, wherein the aberration corrector plate is an aspheric lens that has a first zone with negative optical  
10 power and a second zone with positive optical power radially inside the first zone.

225. The light detection system of claim 224, further comprising a second light detection system to detect and process the light side-scattered from and fluoresced by the object in the viewing zone of the microscope objective.

226. The light detection system of any one of claims 213 to 225, wherein the  
15 concave mirror is an ellipsoidal mirror.

227. The light detection system of any one of claims 213 to 225, wherein the concave mirror is a combination of a flat mirror and a lens.

228. A power monitoring system for adjusting power of a light source,  
comprising:

- 20 a first light source for emitting a first beam of light;
- a second light source for emitting a second beam of light;
- a first dichroic filter for reflecting the first beam of light and passing the second beam of light;
- a second dichroic filter for reflecting the second beam of light;
- 25 a first detector for measuring residual power of the first and second beams of light downstream of the first dichroic filter on a time-division multiplexing basis; and
- a control unit coupled with the first detector and the first and second light sources, wherein the control unit adjusts power of one or more of the first and second light sources based on measured residual power of the first and second beams of light by the first  
30 detector.

229. The power monitoring system of claim 228, wherein the first detector is positioned near the first dichroic filter.

230. The power monitoring system of any one of claims 228 and 229, wherein the first detector is coupled to the first dichroic filter.

5        231. The power monitoring system of any one of claims 228 to 230, wherein the residual power of the first and second beams of light includes power of the first beam of light passing through the first dichroic filter and power of the second beam of light reflected by the first dichroic filter.

232. The power monitoring system of any one of claims 228 to 230, wherein the  
10 first detector measures the residual power of the first beam of light when the second light source is off to reduce interference between the residual power of the first and second beams of light.

233. The power monitoring system of any one of claims 228 to 230, wherein the  
15 first detector measures the residual power of the second beam of light when the first light source is off to reduce interference between the residual power of the first and second beams of light.

234. The power monitoring system of any one of claims 228 to 233, wherein the  
control unit includes a feedback circuit to increase the power of the light source when  
residual power of the light source drops or to lower the power of the light source when the  
20 residual power of the light source increases.

235. The power monitoring system of any one of claims 228 to 234, further  
comprising a second detector positioned near the second dichroic filter to measure the  
residual power of the second beam of light downstream of the second dichroic filter,  
wherein the second detector is coupled to the control circuit.

25        236. The power monitoring system of claim 235, wherein the residual power of the second beam of light downstream of the second dichroic filter includes power of the second beam of light passing through the second dichroic filter.

237. The power monitoring system of any one of claims 228 to 236, further  
comprising a third light source for emitting a third beam of light and a third dichroic filter  
30 acting as a mirror to reflect the third beam of light, wherein the third light source is coupled to the control circuit.

Specification.doc

238. The power monitoring system of claim 237, wherein the first detector measures residual power of the first, second, and third beams of light downstream of the first dichroic filter on a time-division multiplexing basis.

239. The power monitoring system of any one of claims 237 and 238, further comprising a second detector positioned near the second dichroic filter to measure residual power of the second and third beams of light downstream of the second dichroic filter on a time-division multiplexing basis, wherein the second detector is coupled to the control circuit.

240. The power monitoring system of claim 234, wherein the residual power of the second and third beams of light downstream of the second dichroic filter includes power of the second beam of light passing through the second dichroic filter and power of the third beam of light reflected by the second dichroic filter.

241. The power monitoring system of any one of claims 237 to 240, further comprising a third detector positioned near the third dichroic filter to measure residual power of the third beams of light downstream of the third dichroic filter, wherein the third detector is coupled to the control circuit.

242. The power monitoring system of claim 241, wherein the residual power of the third beam of light downstream of the third dichroic filter includes power of the third beam of light passing through the third dichroic filter.

243. The power monitoring system of any one of claims 228 to 242, wherein the second dichroic filter is one of a dichroic filter and a mirror.

244. An optical system comprising:

a) an objective adapted for imaging light scattered from and fluoresced by an illuminated object within a viewing zone comprising:

- i. an aspheric lens with a first zone with negative optical power and a second zone inside the first zone with positive optical power; and
- ii. a concave mirror for reflecting light scattered from and fluoresced by the illuminated object through the aspheric lens, wherein the viewing zone is located between said concave mirror and the aspheric lens;

b) an optical transmission member for propagating light received from the aspheric lens; and

- 5 c) a wavelength division multiplexer (WDM) for receiving light propagated by the optical transmission member, the wavelength division multiplexer (WDM) comprising:
- i. a first optical element that produces a beam of light with an image of substantially the same size as the effective size of said first optical element;
  - ii. at least one dichroic filter located between said first optical element and said image, wherein said dichroic filter separates the beam of light into two branches of distinctive colors;
  - 10 iii. a second optical element located in one of said branches, wherein the beam of light in said branch is focused to a spot by said second optical element; and
  - iv. an image relay optical element located near the image produced by said first optical element in the other branch, wherein said image relay optical element produces an image of said first optical element at substantially unit magnification.
- 15

245. The optical system of claim 244, wherein the aspheric lens further comprises a neutral zone between the first and second zones.

20 246. The optical system of claim 245, wherein the neutral zone is the thinnest portion of the aspheric lens.

247. The optical system of any one of claims 244 to 246, wherein the concave mirror comprises a spherical mirror.

248. The optical system of any one of claims 244 to 247, wherein the aspheric lens comprises a plano-aspheric lens.

25 249. The optical system of any one of claims 244 to 248, further comprising a cuvette with a flow channel, wherein the viewing zone is located in the flow channel.

250. The optical system of claim 249, further comprising a fluidic system to deliver objects to the viewing zone in the flow channel.

30 251. The optical system of any one of claims 249 and 250, wherein the cuvette has a rectangularly-shaped cross-section.

252. The optical system of any one of claims 249 to 251, wherein the aspheric lens and concave mirror are coupled to the cuvette.

253. The optical system of any one of claims 244 to 252, wherein the optical transmission member comprises an optical fiber.

5        254. The optical system of claim 253, wherein the optical fiber comprises a multimode fiber.

255. The optical system of any one of claims 244 to 254, wherein the first optical element is a collimating element.

10       256. The optical system of any one of claims 244 to 254, wherein the second optical element is a focusing element.

257. The optical system of any one of claims 244 to 256, wherein the image relay optical unit comprises a concave mirror.

258. The optical system of any one of claims 244 to 257, wherein the spot is less than 1.0 mm.

15       259. The optical system of any one of claims 244 to 258, further comprising a filter holder for holding the dichroic filter, the filter holder having a reference surface parallel to a surface of the dichroic filter.

260. The optical system of claim 259, further comprising a reference block with a flat surface, wherein the reference surface of the filter holder is pressed against the flat surface of the reference block.

261. The optical system of claim 260, wherein the reference surface of the filter holder and the surface of the dichroic filter are offset.

262. The optical system of any one of claims 244 to 261, wherein the image relay optical unit comprises a convex lens.

25       263. An optical system comprising:

- a) a light source for emitting a beam of light to illuminate an object in a viewing zone;
- b) a concave mirror for receiving and reflecting light scattered from and fluoresced by the illuminated object;
- 30       c) an aspheric lens with a first zone with negative optical power and a second zone inside the first zone with positive optical power,



wherein light reflected by the concave mirror passes through the aspheric lens, and wherein the viewing zone is located between said concave mirror and the aspheric lens;

- d) an optical transmission member for receiving and propagating light from the aspheric lens; and
- e) a multiplexer for receiving light from the optical transmission member and separating the light into at least two colors.

264. The system of claim 263, wherein the light source comprises a laser for generating a laser beam.

265. The system of claim 264, further comprising optical elements for collimating and shaping the laser beam.

266. The system of any one of claims 263 to 265, wherein the multiplexer comprises a wavelength division multiplexer (WDM) comprising:

- i. a first optical element that receives light from the optical transmission member and produces an image of substantially the same size as the effective size of said first optical element;
- ii. at least one dichroic filter located between said first optical element and said image, wherein said dichroic filter separates the light into two branches of different colors;
- iii. a second optical element for focusing one of said branches of light to a spot; and
- iv. an image relay optical unit located near the image produced by said first optical unit in the other branch, wherein said image relay optical unit produces an image of said first optical element at substantially unit magnification.

267. The system of claim 266, wherein the first optical element is a collimating element.

268. The system of any one of claims 266 and 267, wherein the second optical element is a focusing element.

269. The system of any one of claims 266 to 268, wherein the image relay optical unit comprises a concave mirror.

270. The system of any one of claims 266 to 269 wherein the image relay optical unit comprises a convex lens.

271. The system of any one of claims 266 to 270, wherein the spot is less than 1.0 mm.

272. The system of any one of claims 266 to 271, further comprising a filter holder for holding the dichroic filter, the filter holder having a reference surface parallel to  
5 a surface of the dichroic filter.

273. The system of claim 272, further comprising a reference block with a flat surface, wherein the reference surface of the filter holder is pressed against the flat surface of the reference block.

274. The system of claim 273, wherein the reference surface of the filter holder  
10 and the surface of the dichroic filter are offset.

275. An apparatus for imaging light scattered from and fluoresced by an illuminated object within a viewing zone comprising:

- a) a fluid delivery system for delivering an object to a viewing zone;
- b) a light source for illuminating the object in the viewing zone;
- 15 c) a concave mirror located on one side of the viewing zone for reflecting light scattered from and fluoresced by the illuminated object;
- d) an aspheric lens located on another side of the viewing zone for receiving the light reflected by the concave mirror and forming an image at an image plane, the aspheric lens having a first zone with negative optical power and a  
20 second zone radially inside the first zone with positive optical power.

276. The apparatus of claim 275, further comprising a cuvette with a flow channel coupled to the fluid delivery system, wherein the viewing zone is in the flow channel.

277. The apparatus claim 276, wherein the concave mirror and the aspheric lens are coupled to the cuvette.

278. The apparatus of claim 275, wherein the viewing zone is located on a surface  
25 of a flat, transparent substrate.

279. The apparatus of claim 275, wherein the viewing zone is located inside a jet stream.

280. The apparatus of an one of claim 276 to 279, wherein a flow along the  
30 channel or jet stream comprises a sheath flow and a sample flow.

281. The apparatus of any one of claims 275 to 280, wherein the light source comprises a coherent light source.

282. The apparatus of claim 281, wherein the coherent light source comprises a laser diode.

5        283. The apparatus of any one of claims 275 to 282, further comprising a third zone located between the first and second zones, wherein the third zone has neutral optical power.

284. The apparatus of claim 283, wherein the third zone is the thinnest portion of the aspheric lens.

10       285. A method of gathering and imaging light scattered from or fluoresced by objects in a viewing zone comprising the steps of:

delivering an object to a viewing zone;

illuminating the object in the viewing zone to produce scattered and fluoresced light;

15       reflecting the scattered and fluoresced light using a concave mirror toward a transparent aberration corrector plate; and

correcting spherical aberrations in the reflected light with the transparent aberration corrector plate, wherein the transparent aberration corrector plate has a first zone with negative optical power and a second zone radially inside the first zone with positive optical power.

20

286. The method of claim 285, wherein the step of delivering an object comprises forming a jet stream in the viewing area, said jet stream containing at least one object.

287. The method of any one of claims 285 and 286, wherein the step of delivering an object comprises:

25       forming a liquid sheath flow in the viewing zone; and

injecting a sample flow carrying at least one object into the sheath flow.

288. The method of any one of claims 285 to 287, wherein the step of illuminating the object comprises directing a laser beam at the object.

289. The method according to any one of claims 285 to 288, wherein the step of reflecting light comprises reflecting light with a spherical mirror.

30

290. The method of any one of claims 285 to 289, further comprising propagating the light to a remote location using an optical fiber.

291. The method of claim 290, wherein the step of propagating the light occurs after the step of correcting spherical aberrations.

5        292. The method of any one of claims 290 and 291, further comprising collimating the propagated beam of light to produce a collimated beam of light; filtering the collimated beam of light to produce a first beam of a color of interest and a first reflected beam;

             focusing the first beam to form a first spot smaller than that of the first beam; and  
10        detecting the first spot.

293. The method of claim 292, further comprising:

             filtering the second reflected beam to produce a second beam of a color of interest and a second reflected beam;

             focusing the second beam to form a second spot smaller than that of the second  
15        beam; and  
             detecting the second spot.

294. An optical method for impinging beams of light into a viewing zone comprising:

             directing a first beam of light to illuminate objects in a viewing zone to produce  
20        scattered and fluoresced light;

             reflecting the scattered and fluoresced light using a concave mirror toward an aberration corrector plate;

             correcting aberrations in the reflected light with the aberration corrector plate, wherein the aberration corrector plate has a first zone with negative optical power a second  
25        zone radially inside the first zone with positive optical power; and

             reflecting or transmitting the corrected light using a beam splitter.

295. The optical method of claim 294, wherein the directing the first beam of light includes reflecting the first beam of light into the viewing zone using the beam splitter when the corrected light is transmitted through the beam splitter.

296. The optical method of claim 294, wherein the directing the first beam of light includes transmitting the first beam of light into the viewing zone using the beam splitter when the corrected light is reflected by the beam splitter.

297. The optical method of any one of claims 294 to 296, wherein the optical axis  
5 of the first beam of light entering into the viewing zone is substantially parallel to the optical axis of the corrected light.

298. The optical method of any one of claims 294 to 297, further comprising detecting the corrected light.

299. The optical method of any one of claims 294 to 298, further comprising  
10 propagating the corrected light to a remote location using an optical fiber.

300. The optical method of any one of claims 294 to 299, further comprising processing the corrected light using a wavelength division multiplexer (WDM) to separate the corrected light into multiple colored bands.

301. The optical method of claim 300, wherein the wavelength division  
15 multiplexer (WDM) comprises:

- i. a collimating optical element that produces an image of substantially the same size as the effective size of the collimating optical element;
- ii. at least one dichroic filter located between the collimating optical element and the image, wherein the dichroic filter separates the  
20 collimated beam of light into two branches of distinctive colors;
- iii. a focusing optical element located in one of the branches, wherein the beam of light in the branch is focused to a spot by the focusing optical element; and
- iv. an image relay optical element located near the image produced by the  
25 collimating optical element in the other branch, wherein the image relay optical element produces an image of the collimating optical element at substantially unit magnification.

302. The optical method of any one of claims 294 to 301, wherein the first beam of light is coherent light or incoherent light.

303. An optical method for detecting light comprising:  
reflecting light that propagates from a viewing zone using a concave mirror; and

Specification.doc

measuring axial light loss produced by an object in the viewing zone by detecting light reflected by the concave mirror.

304. The optical method of claim 303, further comprising directing a first beam of light to irradiate the object in the viewing zone, wherein the axis of irradiation is  
5 substantially perpendicular to the flow direction of the object.

305. The optical method of any one of claims 303 and 304, wherein the light reflected by the concave mirror includes forward scattered light and remaining light of the first beam of light, wherein the axial light loss of the first beam of light results from the object passing through the first beam of light, and wherein the optical axis of the remaining  
10 light is substantially paralleled to the axis of irradiation.

306. The optical method of claim 305, wherein the forward scattered light and the remaining light have the same wavelength.

307. The optical method of any one of claims 305 and 306, further comprising measuring coherent interference of the forward scattered light and the remaining light.

308. The optical method of any one of claims 303 to 307, further comprising directing a second light to irradiate the object in the viewing zone, wherein the wavelength of the second beam of light is different from the wavelength of the first beam of light.  
15

309. The optical method of claim 308, further comprising separating the light irradiated by the first light source and reflected by the concave mirror from the light  
20 irradiated by the second light source and reflected by the concave mirror using a filter in order to measure them on a time-division multiplexing basis.

310. The optical method of any one of claims 303 to 309, wherein the viewing zone is located within a microscope objective.

311. The optical method of claim 310, further comprising a cylindrical lens  
25 coupled with the microscope objective, wherein the optical axis of the cylindrical lens is substantially perpendicular to the optical axis of the light reflected by the concave mirror.

312. The optical method of any one of claims 310 and 311, further comprising a second concave mirror and an aberration corrector plate located on two sides of the viewing zone of the microscope objective, wherein the optical axes of the second concave mirror  
30 and the aberration corrector plate are substantially parallel to the optical axis of the light reflected by the concave mirror.

Specification.doc

313. The optical method of claim 312, wherein light side-scattered from and fluoresced by the object in the viewing zone is reflected by the second concave mirror and propagates out of the microscope objective via the aberration corrector plate, wherein the aberration corrector plate is an aspheric lens that has a first zone with negative optical  
5 power and a second zone with positive optical power radially inside the first zone.

314. The optical method of claim 313, further comprising a second light detection system to detect and process the light side-scattered from and fluoresced by the object in the viewing zone of the microscope objective.

315. The optical method of any one of claims 303 to 314, wherein the concave  
10 mirror is an ellipsoidal mirror.

316. The optical method of any one of claims 303 to 314, wherein the concave mirror is a combination of a flat mirror and a lens.

317. A composite microscope objective (60) adapted for imaging light scattered from and fluoresced by an object present within a viewing zone, the composite microscope  
15 objective comprising:

- a) a viewing zone;
- b) a concave mirror arrangement;
- c) an exit area; and
- d) illumination beam forming arrangement;

20 wherein the viewing zone is arranged between the concave mirror arrangement and the exit area;

wherein the concave mirror is arranged to reflect scattered and fluoresced light impinging from an object present in the viewing zone to the exit area;

25 wherein the illumination beam forming arrangement is arranged so that an illumination beam entering the illumination beam forming arrangement is pre-definitely formed at the viewing zone.

318. The composite microscope objective of claim 317, wherein the concave mirror arrangement, the viewing zone and the exit area are arranged along a first axis/x-axis.

319. The composite microscope objective of any one of claims 317 and 318, wherein an optical image of the viewing zone is formed outside the composite microscope objective.

320. The composite microscope objective of any one of claims 317 to 319,  
5 wherein the illumination beam forming arrangement is arranged so that an illumination beam impinges the viewing zone along a second axis/z-axis substantially perpendicularly to said first axis/x-axis.

321. The composite microscope objective of any one of claims 317 to 320, further comprising a cuvette,  
10 wherein the cuvette is of an optical transparent material, wherein the viewing zone is formed in the cuvette.

322. The composite microscope objective of claim 321, wherein the cuvette includes a channel, wherein the channel extends along a third axis/y-axis being substantially perpendicular to the first axis/x-axis and the second axis/z-axis, so that a  
15 liquid flow in the channel flows along the third axis/y-axis, wherein the viewing zone is located within the channel.

323. The composite microscope objective of any one of claims 317 to 322, wherein the cuvette is of rectangular cross section in a plane of the first axis/x-axis and second axis/z-axis.

20 324. The composite microscope objective of any one of claims 317 to 323, wherein the channel is of rectangular cross section in a plane of the first axis/x-axis and second axis/z-axis.

325. The composite microscope objective of any one of claims 317 to 320, further comprising a jet stream,  
25 wherein the viewing zone is arranged in the jet stream.

326. The composite microscope objective of any one of claims 317 to 320, wherein the viewing zone is located on a surface of a flat, transparent substrate.

327. The composite microscope objective of any one of claims 317 to 326, wherein the illumination beam forming arrangement is adapted to compress an illumination  
30 beam, so that the illumination beam in the viewing zone has a compressed dimension along the third axis/y-axis.

Specification.doc



328. The composite microscope objective of claim 327, wherein the illumination beam forming arrangement is a cylindrical lens having a cylindrical axis parallel to the first axis/x-axis.

329. The composite microscope objective of any one of claims 317 to 328, further comprising an aberration corrector arrangement,  
wherein the aberration corrector arrangement is arranged in the exit area.

330. The composite microscope objective of claim 329, wherein the aberration corrector arrangement is an aspheric lens made of optically transparent material.

331. The composite microscope objective of any one of claims 329 and 330,  
wherein said aberration corrector arrangement comprises:  
i. a first zone with negative optical power;  
ii. a second zone radially inside the first zone with positive optical power; and  
iii. a neutral zone between the first zone and the second zone,  
wherein the neutral zone is thinner than each of the first zone and the second zone,  
so that light reflected from the concave mirror arrangement passing through said  
aberration corrector arrangement forms a focal area.

332. The composite microscope objective of any one of claims 317 to 331,  
wherein the concave mirror arrangement, the viewing zone and the aberration corrector arrangement form a reversed Schmidt camera.

333. The composite microscope objective of any one of claims 317 to 332,  
wherein the concave mirror arrangement is formed by plane-convex lens.

334. The composite microscope objective of any one of claims 317 to 332,  
wherein said concave mirror is a plano-concave back surface mirror made from an optically transparent material.

335. The composite microscope objective of claim 334, wherein a plano-surface of said plano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

336. The composite microscope objective of claim 334, wherein a plano-surface of said plano-concave back surface mirror is optically coupled to said flat, transparent substrate.

337. The composite microscope objective of any one of claims 317 to 332, wherein said concave mirror is a front surface mirror.

338. The composite microscope objective of any one of claims 317 to 332, wherein at least one of the concave mirror arrangement, the aberration corrector  
5 arrangement and the illumination beam forming arrangement is attached to the cuvette by one selected from a group, the group consisting of index matching gel, index matching fluid, optical adhesive material and optical contact bonding.

339. The composite microscope objective of any one of claims 317 to 338, further comprising an illumination system,  
10 wherein the illumination system comprises:

a laser source, a collimating optical arrangement to form a collimated laser beam and a beam shaping arrangement being adapted to shape a collimated beam, wherein the beam shaping arrangement includes the illumination beam forming arrangement.

340. The composite microscope objective of claim 339, wherein the laser source  
15 is a laser diode and the collimating arrangement is arranged with respect to the laser diode so as to form a collimated beam.

341. The composite microscope objective of claim 339, wherein the laser diode and the collimation optical arrangement are adapted to form a beam having an elliptical cross section having a major axis and a minor axis, wherein the minor axis is oriented  
20 substantially along the third axis/z-axis and the major axis is oriented substantially along the first axis/x-axis.

342. The composite microscope objective of any one of claims 317 to 341, wherein the beam shaping arrangement includes a major axis optical beam compressing arrangement being adapted to compress at least the major axis of the collimated elliptical  
25 beam.

343. The composite microscope objective of any one of claims 317 to 342, wherein the illumination beam forming arrangement is adapted to compress at least the minor axis of the collimated elliptical beam.

344. The composite microscope objective of any one of claims 339 to 343,  
30 wherein the illumination system is an optical system according to any one of claims 174 to 187.

Specification.doc

345. The composite microscope objective of any one of claims 339 to 344, wherein the viewing zone is movable along the second axis/z-axis with respect to the illumination system so as to vary a focus of the compressed elliptical beam within the viewing zone along the second axis/z-axis.

5           346. The composite microscope objective of any one of claims 339 to 342, wherein the cuvette is movable with respect to the laser source so as to spatially vary a focus of the laser source in the channel.

          347. The composite microscope objective of any one of claims 339 to 342, further comprising a control unit being adapted to control the movement of components of the  
10 composite microscope objective along the second axis/z-axis so as to spatially vary a focus of the laser source in the channel.

348. A wavelength division multiplexer (WDM) for separating light emitted from a light source into multiple colored bands, the wavelength division multiplexer comprising:

- 15           a) an imaging optical arrangement,
- b) a dichroic filter arrangement,
- c) a semiconductor photo detector,
- d) a focusing optical arrangement

          wherein the imaging optical arrangement forms a beam of light from the light emitted from a light source and produces an image of substantially the same size as the  
20 effective size of said imaging optical arrangement;

          wherein the dichroic filter arrangement is located between said imaging optical arrangement and said image, and separates the beam of light into a first branch and a second branch of distinctive colors;

          wherein the semiconductor photo detector is located in the first branch;  
25           wherein the focusing optical arrangement is located between the dichroic filter arrangement and the semiconductor photo detector so as to focus the beam of light onto the semiconductor photo detector.

349. The wavelength division multiplexer according to claim 348, wherein the focusing optical element arrangement is located in or in proximity to an image plane of said  
30 image.

350. The wavelength division multiplexer according to any one of claims 348 and 349, wherein focusing optical arrangement and the semiconductor photo sensor are arranged to each other that the beam of light is focused to a spot having a diameter of less than 1.0 mm, particularly of less than 0.6 mm.

5           351. The wavelength division multiplexer according to any one of claims 348 to 350, further comprising an image relay optical arrangement,

              wherein the image relay optical arrangement is located in or in proximity to an image plane produced by said imaging optical arrangement in the second branch, wherein said image relay optical arrangement is adapted to produce an image of said imaging  
10       optical arrangement in a third branch having substantially the same size as the image in the second branch.

352. The wavelength division multiplexer according to claim 351, wherein the image relay optical arrangement is a concave mirror.

              353. The wavelength division multiplexer according to any one of claims 351 and  
15       352, further comprising an additional dichroic filter arrangement,

              wherein the additional dichroic filter arrangement is located between said image relay optical arrangement and an image produced by said image relay optical arrangement, wherein said additional dichroic filter arrangement from the third branch produces a fourth branch and a fifth branch of the beam of light having distinctive colors.

20           354. The wavelength division multiplexer according to claim 353, further comprising an additional focusing optical arrangement and an additional semiconductor photo detector,

              wherein the additional focusing optical arrangement is located in the fourth branch and focuses the beam of light in the fourth branch so as to focus the beam of light onto the  
25       additional semiconductor photo detector.

355. The wavelength division multiplexer according to any one of claims 348 to 354, further comprising a plurality of image relay optical arrangements, a plurality of dichroic filter arrangements, a plurality of semiconductor photo detectors and a plurality of focusing optical arrangements, wherein each of the plurality of focusing optical  
30       arrangements is arranged between a respective one of the plurality of dichroic filter

arrangements and a respective one of the plurality of semiconductor photo detectors so as to form a cascaded arrangement.

356. The wavelength division multiplexer according to claim 355, wherein the additional focused spots having a diameter of less than 1.0 mm, particularly of less than 0.6  
5 mm for multiple colored bands of said beam of light.

357. The wavelength division multiplexer according to any one of claims 348 to 356, wherein the plurality of dichroic filter arrangements are arranged in a common plane.

358. The wavelength division multiplexer according to any one of claims 348 to 357, further comprising a plan-parallel optical basis having a first surface and second  
10 surface parallel thereto,

wherein the plurality of dichroic filter arrangements are arranged parallel, preferably in abutment to the first surface of the plan-parallel optical basis.

359. The wavelength division multiplexer according to any one of claims 348 to 358, wherein the dichroic filter arrangements are assembled using a template that includes  
15 two optically flat glass plates bonded together in optical contact, wherein the dichroic filter arrangements are bonded to a filter holder using the template such that a coated filter surface of the dichroic filter arrangements are indented and optically parallel to a reference surface of the filter holder.

360. The wavelength division multiplexer according to claim 359, wherein the  
20 reference surface of the filter holder rests against an optically flat surface of an reference block included in the wavelength division multiplexer thereby providing consistent optical alignment when installing the dichroic filter arrangements into the wavelength division multiplexer.

361. The wavelength division multiplexer according to any one of claims 358 to  
25 360, wherein the respective image relay optical arrangements are formed into the second surface of the plan-parallel optical basis.


362. The wavelength division multiplexer of any one of claims 348 to 361, wherein at least one of the semiconductor photo detectors is an avalanche photo diode detector.

30 363. The wavelength division multiplexer of any one of claims 348 to 362, wherein at least one of the semiconductor photo detectors is a carbon nanotube detector

Specification.doc

## ABSTRACT

The disclosed flow cytometer includes a wavelength division multiplexer (WDM). The WDM includes an extended light source providing light that forms an object, a collimating  
5 optical element that captures light from the extended light source and projects a magnified image of the object as a first light beam, and a first focusing optical element configured to focus the first light beam to a size smaller than the object of the extended light source to a first semiconductor detector. The disclosed flow cytometer further includes a composite  
10 microscope objective to direct light emitted by a particle in a flow channel in a viewing zone of the composite microscope to the extended light source, a fluidic system and a peristaltic pump configured to supply liquid sheath and liquid sample to the flow channel, and a laser diode system to illuminate the particle in the flow channel.








FIG. 2A








FIG. 3B




FIG. 4A







FIG. 4B






FIG. 5D






FIG. 5E







FIG. 8




FIG. 8A




FIG. 8B







FIG. 9B1




FIG. 9B2




FIG. 9B3




FIG. 10




FIG. 11





FIG. 12






FIG. 14




FIG. 15




FIG. 16A





FIG. 16B






FIG. 18A

FIG. 18B

FIG. 18C

FIG. 18D




FIG. 19




FIG. 19A

FIG. 19B






FIG. 20A




FIG. 20B




FIG. 21




FIG. 22




FIG. 23




FIG. 24A




FIG. 24B




FIG. 24C




FIG. 25




FIG. 25A




FIG. 25B




FIG. 26











FIG. 27







*FIG. 30A**FIG. 30B*








FIG. 32

*FIG. 33*







FIG. 35







FIG. 37





|                                                                                   |                                                   |                                  |                                       |
|-----------------------------------------------------------------------------------|---------------------------------------------------|----------------------------------|---------------------------------------|
| <b>PATENT APPLICATION FEE DETERMINATION RECORD</b><br>Substitute for Form PTO-875 | Application or Docket Number<br><b>15/638,461</b> | Filing Date<br><b>06/30/2017</b> | <input type="checkbox"/> To be Mailed |
|-----------------------------------------------------------------------------------|---------------------------------------------------|----------------------------------|---------------------------------------|

ENTITY: ☒ LARGE ☐ SMALL ☐ MICRO

**APPLICATION AS FILED – PART I**

(Column 1)

(Column 2)

| FOR                                                                        | NUMBER FILED                                                                                                                                                                                                                  | NUMBER EXTRA | RATE (\$) | FEE (\$) |
|----------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|-----------|----------|
| <input type="checkbox"/> BASIC FEE<br>(37 CFR 1.16(a), (b), or (c))        | N/A                                                                                                                                                                                                                           | N/A          | N/A       |          |
| <input type="checkbox"/> SEARCH FEE<br>(37 CFR 1.16(k), (i), or (m))       | N/A                                                                                                                                                                                                                           | N/A          | N/A       |          |
| <input type="checkbox"/> EXAMINATION FEE<br>(37 CFR 1.16(o), (p), or (q))  | N/A                                                                                                                                                                                                                           | N/A          | N/A       |          |
| TOTAL CLAIMS<br>(37 CFR 1.16(i))                                           | minus 20 =                                                                                                                                                                                                                    | *            | X \$ =    |          |
| INDEPENDENT CLAIMS<br>(37 CFR 1.16(h))                                     | minus 3 =                                                                                                                                                                                                                     | *            | X \$ =    |          |
| <input type="checkbox"/> APPLICATION SIZE FEE<br>(37 CFR 1.16(s))          | If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s). |              |           |          |
| <input type="checkbox"/> MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j)) |                                                                                                                                                                                                                               |              |           |          |
| * If the difference in column 1 is less than zero, enter "0" in column 2.  |                                                                                                                                                                                                                               |              | TOTAL     |          |

**APPLICATION AS AMENDED – PART II**

(Column 1)

(Column 2)

(Column 3)

| AMENDMENT       | 06/30/2017                                                                               | CLAIMS REMAINING AFTER AMENDMENT | MINUS | HIGHEST NUMBER PREVIOUSLY PAID FOR | PRESENT EXTRA | RATE (\$) | ADDITIONAL FEE (\$) |
|-----------------|------------------------------------------------------------------------------------------|----------------------------------|-------|------------------------------------|---------------|-----------|---------------------|
|                 | Total (37 CFR 1.16(i))                                                                   | * 26                             | Minus | ** 26                              | = 0           | X \$80 =  | 0                   |
|                 | Independent (37 CFR 1.16(h))                                                             | * 3                              | Minus | ***3                               | = 0           | X \$420 = | 0                   |
|                 | <input type="checkbox"/> Application Size Fee (37 CFR 1.16(s))                           |                                  |       |                                    |               |           |                     |
|                 | <input type="checkbox"/> FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |                                  |       |                                    |               |           |                     |
| TOTAL ADD'L FEE |                                                                                          |                                  |       |                                    |               | <b>0</b>  |                     |

(Column 1)

(Column 2)

(Column 3)

| AMENDMENT       | CLAIMS REMAINING AFTER AMENDMENT                                                         | MINUS | HIGHEST NUMBER PREVIOUSLY PAID FOR | PRESENT EXTRA | RATE (\$) | ADDITIONAL FEE (\$) |
|-----------------|------------------------------------------------------------------------------------------|-------|------------------------------------|---------------|-----------|---------------------|
|                 | Total (37 CFR 1.16(i))                                                                   | *     | Minus                              | **            | =         | X \$ =              |
|                 | Independent (37 CFR 1.16(h))                                                             | *     | Minus                              | ***           | =         | X \$ =              |
|                 | <input type="checkbox"/> Application Size Fee (37 CFR 1.16(s))                           |       |                                    |               |           |                     |
|                 | <input type="checkbox"/> FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |       |                                    |               |           |                     |
| TOTAL ADD'L FEE |                                                                                          |       |                                    |               |           |                     |

\* If the entry in column 1 is less than the entry in column 2, write "0" in column 3.

\*\* If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".

\*\*\* If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".

The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1.

LIE  
eugenia v. hardy

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

| <b>PATENT APPLICATION FEE DETERMINATION RECORD</b><br>Substitute for Form PTO-875                                                                                                                                                                                                                                                                                                                          |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               | Application or Docket Number<br>15/638,461 |                    |                         |                    |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------|----------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|---------------|--------------------------------------------|--------------------|-------------------------|--------------------|
| <b>APPLICATION AS FILED - PART I</b>                                                                                                                                                                                                                                                                                                                                                                       |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
| (Column 1)                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                 | (Column 2)                       |                                                                                                                                                                                                                               | SMALL ENTITY                       |               | OTHER THAN SMALL ENTITY                    |                    |                         |                    |
| FOR                                                                                                                                                                                                                                                                                                                                                                                                        | NUMBER FILED                                                    | NUMBER EXTRA                     | RATE(\$)                                                                                                                                                                                                                      | FEE(\$)                            |               | RATE(\$)                                   | FEE(\$)            |                         |                    |
| BASIC FEE<br>(37 CFR 1.16(a), (b), or (c))                                                                                                                                                                                                                                                                                                                                                                 | N/A                                                             | N/A                              | N/A                                                                                                                                                                                                                           |                                    |               | N/A                                        | 280                |                         |                    |
| SEARCH FEE<br>(37 CFR 1.16(k), (l), or (m))                                                                                                                                                                                                                                                                                                                                                                | N/A                                                             | N/A                              | N/A                                                                                                                                                                                                                           |                                    |               | N/A                                        | 600                |                         |                    |
| EXAMINATION FEE<br>(37 CFR 1.16(o), (p), or (q))                                                                                                                                                                                                                                                                                                                                                           | N/A                                                             | N/A                              | N/A                                                                                                                                                                                                                           |                                    |               | N/A                                        | 720                |                         |                    |
| TOTAL CLAIMS<br>(37 CFR 1.16(j))                                                                                                                                                                                                                                                                                                                                                                           | 26                                                              | minus 20 = *                     | 6                                                                                                                                                                                                                             |                                    |               | x 80 =                                     | 480                |                         |                    |
| INDEPENDENT CLAIMS<br>(37 CFR 1.16(h))                                                                                                                                                                                                                                                                                                                                                                     | 3                                                               | minus 3 = *                      |                                                                                                                                                                                                                               |                                    |               | x 420 =                                    | 0.00               |                         |                    |
| APPLICATION SIZE FEE<br>(37 CFR 1.16(s))                                                                                                                                                                                                                                                                                                                                                                   |                                                                 |                                  | If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s). |                                    |               | 400                                        |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
| MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))                                                                                                                                                                                                                                                                                                                                                          |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               | 0.00                                       |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                 |                                  |                                                                                                                                                                                                                               | TOTAL                              |               | TOTAL                                      | 2480               |                         |                    |
| * If the difference in column 1 is less than zero, enter "0" in column 2.                                                                                                                                                                                                                                                                                                                                  |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
| <b>APPLICATION AS AMENDED - PART II</b>                                                                                                                                                                                                                                                                                                                                                                    |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
| (Column 1)                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                 | (Column 2)                       |                                                                                                                                                                                                                               | (Column 3)                         |               | SMALL ENTITY                               |                    | OTHER THAN SMALL ENTITY |                    |
| AMENDMENT A                                                                                                                                                                                                                                                                                                                                                                                                |                                                                 | CLAIMS REMAINING AFTER AMENDMENT |                                                                                                                                                                                                                               | HIGHEST NUMBER PREVIOUSLY PAID FOR | PRESENT EXTRA | RATE(\$)                                   | ADDITIONAL FEE(\$) | RATE(\$)                | ADDITIONAL FEE(\$) |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Total<br>(37 CFR 1.16(i))                                       | *                                | Minus                                                                                                                                                                                                                         | **                                 | =             | x                                          | =                  | x                       | =                  |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Independent<br>(37 CFR 1.16(h))                                 | *                                | Minus                                                                                                                                                                                                                         | ***                                | =             | x                                          | =                  | x                       | =                  |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Application Size Fee (37 CFR 1.16(s))                           |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            | FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               | TOTAL<br>ADD'L FEE                         |                    | TOTAL<br>ADD'L FEE      |                    |
| AMENDMENT B                                                                                                                                                                                                                                                                                                                                                                                                |                                                                 | CLAIMS REMAINING AFTER AMENDMENT |                                                                                                                                                                                                                               | HIGHEST NUMBER PREVIOUSLY PAID FOR | PRESENT EXTRA | RATE(\$)                                   | ADDITIONAL FEE(\$) | RATE(\$)                | ADDITIONAL FEE(\$) |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Total<br>(37 CFR 1.16(i))                                       | *                                | Minus                                                                                                                                                                                                                         | **                                 | =             | x                                          | =                  | x                       | =                  |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Independent<br>(37 CFR 1.16(h))                                 | *                                | Minus                                                                                                                                                                                                                         | ***                                | =             | x                                          | =                  | x                       | =                  |
|                                                                                                                                                                                                                                                                                                                                                                                                            | Application Size Fee (37 CFR 1.16(s))                           |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            | FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |
|                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               | TOTAL<br>ADD'L FEE                         |                    | TOTAL<br>ADD'L FEE      |                    |
| * If the entry in column 1 is less than the entry in column 2, write "0" in column 3.<br>** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".<br>*** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".<br>The "Highest Number Previously Paid For" (Total or Independent) is the highest found in the appropriate box in column 1. |                                                                 |                                  |                                                                                                                                                                                                                               |                                    |               |                                            |                    |                         |                    |



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION<br>NUMBER | FILING or<br>371(c) DATE | GRP ART<br>UNIT | FIL FEE REC'D | ATTY. DOCKET NO     | TOT CLAIMS | IND CLAIMS |
|-----------------------|--------------------------|-----------------|---------------|---------------------|------------|------------|
| 15/638,461            | 06/30/2017               | 2877            | 2480          | BECC.P0002US.CIP.C1 | 26         | 3          |

CONFIRMATION NO. 9847

## FILING RECEIPT

32425  
NORTON ROSE FULBRIGHT US LLP  
98 SAN JACINTO BOULEVARD  
SUITE 1100  
AUSTIN, TX 78701-4255



0000000092845078

Date Mailed: 07/19/2017

Receipt is acknowledged of this non-provisional patent application. The application will be taken up for examination in due course. Applicant will be notified as to the results of the examination. Any correspondence concerning the application must include the following identification information: the U.S. APPLICATION NUMBER, FILING DATE, NAME OF APPLICANT, and TITLE OF INVENTION. Fees transmitted by check or draft are subject to collection. Please verify the accuracy of the data presented on this receipt. **If an error is noted on this Filing Receipt, please submit a written request for a Filing Receipt Correction. Please provide a copy of this Filing Receipt with the changes noted thereon. If you received a "Notice to File Missing Parts" for this application, please submit any corrections to this Filing Receipt with your reply to the Notice. When the USPTO processes the reply to the Notice, the USPTO will generate another Filing Receipt incorporating the requested corrections**

### Inventor(s)

Yong Qin Chen, San Jose, CA;

### Applicant(s)

IRIS INTERNATIONAL, INC., Chatsworth, CA;

**Power of Attorney:** The patent practitioners associated with Customer Number 129381

### Domestic Priority data as claimed by applicant

This application is a CON of 14/555,102 11/26/2014  
which claims benefit of 61/911,859 12/04/2013  
and is a CIP of PCT/US2013/043453 05/30/2013  
which claims benefit of 61/653,245 05/30/2012  
and claims benefit of 61/653,328 05/30/2012  
and claims benefit of 61/715,819 10/18/2012  
and claims benefit of 61/715,836 10/19/2012  
and claims benefit of 61/816,819 04/29/2013

**Foreign Applications** for which priority is claimed (You may be eligible to benefit from the **Patent Prosecution Highway** program at the USPTO. Please see <http://www.uspto.gov> for more information.) - None.

*Foreign application information must be provided in an Application Data Sheet in order to constitute a claim to foreign priority. See 37 CFR 1.55 and 1.76.*

**Permission to Access Application via Priority Document Exchange:** Yes

**Permission to Access Search Results:** Yes

Applicant may provide or rescind an authorization for access using Form PTO/SB/39 or Form PTO/SB/69 as appropriate.

**If Required, Foreign Filing License Granted:** 07/18/2017

The country code and number of your priority application, to be used for filing abroad under the Paris Convention, is **US 15/638,461**

**Projected Publication Date:** 10/26/2017

**Non-Publication Request:** No

**Early Publication Request:** No  
**Title**

FLOW CYTOMETER

**Preliminary Class**

356

**Statement under 37 CFR 1.55 or 1.78 for AIA (First Inventor to File) Transition Applications:** No

## **PROTECTING YOUR INVENTION OUTSIDE THE UNITED STATES**

Since the rights granted by a U.S. patent extend only throughout the territory of the United States and have no effect in a foreign country, an inventor who wishes patent protection in another country must apply for a patent in a specific country or in regional patent offices. Applicants may wish to consider the filing of an international application under the Patent Cooperation Treaty (PCT). An international (PCT) application generally has the same effect as a regular national patent application in each PCT-member country. The PCT process **simplifies** the filing of patent applications on the same invention in member countries, but **does not result** in a grant of "an international patent" and does not eliminate the need of applicants to file additional documents and fees in countries where patent protection is desired.

Almost every country has its own patent law, and a person desiring a patent in a particular country must make an application for patent in that country in accordance with its particular laws. Since the laws of many countries differ in various respects from the patent law of the United States, applicants are advised to seek guidance from specific foreign countries to ensure that patent rights are not lost prematurely.

Applicants also are advised that in the case of inventions made in the United States, the Director of the USPTO must issue a license before applicants can apply for a patent in a foreign country. The filing of a U.S. patent application serves as a request for a foreign filing license. The application's filing receipt contains further information and guidance as to the status of applicant's license for foreign filing.

Applicants may wish to consult the USPTO booklet, "General Information Concerning Patents" (specifically, the section entitled "Treaties and Foreign Patents") for more information on timeframes and deadlines for filing foreign patent applications. The guide is available either by contacting the USPTO Contact Center at 800-786-9199, or it can be viewed on the USPTO website at <http://www.uspto.gov/web/offices/pac/doc/general/index.html>.

For information on preventing theft of your intellectual property (patents, trademarks and copyrights), you may wish to consult the U.S. Government website, <http://www.stopfakes.gov>. Part of a Department of Commerce initiative, this website includes self-help "toolkits" giving innovators guidance on how to protect intellectual property in specific

countries such as China, Korea and Mexico. For questions regarding patent enforcement issues, applicants may call the U.S. Government hotline at 1-866-999-HALT (1-866-999-4258).

**LICENSE FOR FOREIGN FILING UNDER**  
**Title 35, United States Code, Section 184**  
**Title 37, Code of Federal Regulations, 5.11 & 5.15**

**GRANTED**

The applicant has been granted a license under 35 U.S.C. 184, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" followed by a date appears on this form. Such licenses are issued in all applications where the conditions for issuance of a license have been met, regardless of whether or not a license may be required as set forth in 37 CFR 5.15. The scope and limitations of this license are set forth in 37 CFR 5.15(a) unless an earlier license has been issued under 37 CFR 5.15(b). The license is subject to revocation upon written notification. The date indicated is the effective date of the license, unless an earlier license of similar scope has been granted under 37 CFR 5.13 or 5.14.

This license is to be retained by the licensee and may be used at any time on or after the effective date thereof unless it is revoked. This license is automatically transferred to any related applications(s) filed under 37 CFR 1.53(d). This license is not retroactive.

The grant of a license does not in any way lessen the responsibility of a licensee for the security of the subject matter as imposed by any Government contract or the provisions of existing laws relating to espionage and the national security or the export of technical data. Licensees should apprise themselves of current regulations especially with respect to certain countries, of other agencies, particularly the Office of Defense Trade Controls, Department of State (with respect to Arms, Munitions and Implements of War (22 CFR 121-128)); the Bureau of Industry and Security, Department of Commerce (15 CFR parts 730-774); the Office of Foreign Assets Control, Department of Treasury (31 CFR Parts 500+) and the Department of Energy.

**NOT GRANTED**

No license under 35 U.S.C. 184 has been granted at this time, if the phrase "IF REQUIRED, FOREIGN FILING LICENSE GRANTED" DOES NOT appear on this form. Applicant may still petition for a license under 37 CFR 5.12, if a license is desired before the expiration of 6 months from the filing date of the application. If 6 months has lapsed from the filing date of this application and the licensee has not received any indication of a secrecy order under 35 U.S.C. 181, the licensee may foreign file the application pursuant to 37 CFR 5.15(b).

---

***SelectUSA***

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The U.S. offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to promote and facilitate business investment. SelectUSA provides information assistance to the international investor community; serves as an ombudsman for existing and potential investors; advocates on behalf of U.S. cities, states, and regions competing for global investment; and counsels U.S. economic development organizations on investment attraction best practices. To learn more about why the United States is the best country in the world to develop

technology, manufacture products, deliver services, and grow your business, visit <http://www.SelectUSA.gov> or call +1-202-482-6800.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name             | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|------------------|-------|-----------|---------------------|
|             | A1        | 315667          | 4/14/85  | Serdinko         | 417   | 475       | 10/20/84            |
|             | A2        | 2385495         | 9/25/45  | Brian            | 250   | 487.1     | 8/21/43             |
|             | A3        | 2669709         | 2/16/54  | Glancy et al.    | 348   | 784       | 10/19/60            |
|             | A4        | 2764147         | 9/25/56  | Brunner          | 126   | 247       | 2/23/51             |
|             | A5        | 3199341         | 08/10/65 | Heuer Jr. et al. | 73    | 807       | 05/28/62            |
|             | A6        | 3411293         | 11/19/68 | Akins            | 60    | 454       | 10/20/66            |
|             | A7        | 3542491         | 11/24/70 | Newman           | 417   | 295       | 5/27/69             |
|             | A8        | 3661460         | 5/9/72   | Elking et al.    | 356   | 36        | 8/28/70             |
|             | A9        | 3726613         | 4/10/73  | von Casimir      | 417   | 477.1     | 10/12/70            |
|             | A10       | 3826593         | 7/30/74  | von Casimir      | 417   | 53        | 5/11/73             |
|             | A11       | 3873204         | 3/25/75  | Friedman et al.  | 356   | 39        | 11/29/72            |
|             | A12       | 3946239         | 3/23/76  | Salzman et al.   | 250   | 461.2     | 1/24/75             |
|             | A13       | 3953727         | 4/27/76  | d'Auria et al.   | 398   | 88        | 1/17/75             |
|             | A14       | 3989381         | 11/2/76  | Fulwyler         | 356   | 39        | 5/5/75              |
|             | A15       | 4073574         | 2/14/78  | Clarke et al.    | 359   | 728       | 10/1/76             |
|             | A16       | 4188543         | 2/12/80  | Brunsting et al. | 250   | 458.1     | 4/24/78             |
|             | A17       | 4189236         | 2/19/80  | Hogg et al.      | 356   | 317       | 3/20/78             |
|             | A18       | 4244045         | 1/6/81   | Nosu et al.      | 398   | 86        | 1/31/79             |
|             | A19       | 4482994         | 11/13/84 | Ishikawa         | 398   | 86        | 6/7/82              |
|             | A20       | 4515274         | 5/7/85   | Hollinger et al. | 209   | 3.1       | 12/2/81             |
|             | A21       | 4564342         | 1/14/86  | Weber et al.     | 417   | 477.6     | 7/24/84             |
|             | A22       | 4576556         | 3/18/86  | Thompson         | 417   | 477.12    | 4/2/80              |
|             | A23       | 4623225         | 11/18/86 | Forkner          | 359   | 669       | 6/29/84             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A24       | 4727020         | 2/23/88  | Recktenwald        | 435   | 6.11      | 2/25/85             |
|             | A25       | 4745285         | 5/17/88  | Recktenwald et al. | 250   | 458.1     | 8/21/86             |
|             | A26       | 4778253         | 10/18/88 | Siga et al.        | 359   | 819       | 3/26/86             |
|             | A27       | 4834630         | 5/30/89  | Godwin             | 417   | 475       | 2/16/88             |
|             | A28       | 4871249         | 10/3/89  | Watson             | 356   | 73        | 7/1/88              |
|             | A29       | 4920275         | 4/24/90  | Itoh               | 250   | 574       | 12/30/88            |
|             | A30       | 4950136         | 8/21/90  | Haas et al.        | 417   | 477.7     | 8/14/89             |
|             | A31       | 4976590         | 12/11/90 | Baldwin            | 417   | 53        | 6/8/88              |
|             | A32       | 4997275         | 3/5/91   | Gaucher et al.     | 356   | 72        | 9/23/88             |
|             | A33       | 5050963         | 9/24/91  | Murakami           | 359   | 808       | 10/9/90             |
|             | A34       | 5142462         | 8/25/92  | Kashima            | 362   | 268       | 4/27/90             |
|             | A35       | 5157917         | 10/27/92 | Liang et al.       | 60    | 2261.1    | 05/20/91            |
|             | A36       | 5177641         | 1/5/93   | Kobayashi et al.   | 359   | 820       | 10/30/90            |
|             | A37       | 5230614         | 7/27/93  | Zanger et al.      | 417   | 477.9     | 6/3/92              |
|             | A38       | 5245318         | 9/14/93  | Tohge et al.       | 340   | 611       | 12/15/92            |
|             | A39       | 5251060         | 10/5/93  | Uenishi et al.     | 359   | 328       | 9/30/92             |
|             | A40       | 5257917         | 11/02/93 | Minarik et al.     | 417   | 475       | 10/02/92            |
|             | A41       | 5299066         | 3/29/94  | Rombult            | 359   | 819       | 8/12/92             |
|             | A42       | 5317162         | 5/31/94  | Pinsky et al.      | 250   | 461.2     | 9/9/92              |
|             | A43       | 5369476         | 11/29/94 | Bowers et al.      | 399   | 49        | 1/28/92             |
|             | A44       | 5373395         | 12/13/94 | Adachi             | 359   | 652       | 5/10/93             |
|             | A45       | 5396487         | 3/7/95   | Abe et al.         | 359   | 819       | 10/31/91            |
|             | A46       | 5467225         | 11/14/95 | Manabe             | 359   | 661       | 11/1/94             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name            | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-----------------|-------|-----------|---------------------|
|             | A47       | 5470211         | 11/28/95 | Knott et al.    | 417   | 477.9     | 8/11/94             |
|             | A48       | 5475210         | 12/12/95 | Taguchi et al.  | 250   | 205       | 6/8/93              |
|             | A49       | 5548395         | 8/20/96  | Kosaka          | 356   | 73        | 8/31/92             |
|             | A50       | 5583683         | 12/10/96 | Scobey          | 398   | 79        | 6/15/95             |
|             | A51       | 5615200         | 3/25/97  | Hoshino et al.  | 369   | 112.04    | 4/14/95             |
|             | A52       | 5746585         | 5/5/98   | McDunn et al.   | 417   | 477.11    | 12/31/96            |
|             | A53       | 5748372         | 5/5/98   | Kitagawa        | 359   | 565       | 4/17/96             |
|             | A54       | 5777674         | 7/7/98   | Ohmuro          | 348   | 338       | 4/10/95             |
|             | A55       | 5781351         | 7/14/98  | Murakami et al. | 359   | 808       | 5/31/96             |
|             | A56       | 5786915         | 7/28/98  | Scobey          | 398   | 82        | 10/22/96            |
|             | A57       | 5788927         | 8/4/98   | Farrell et al.  | 422   | 63        | 6/30/96             |
|             | A58       | 5805363         | 9/8/98   | Okuda et al.    | 359   | 819       | 7/17/97             |
|             | A59       | 5850292         | 12/15/98 | Braun           | 356   | 419       | 11/13/97            |
|             | A60       | 5915925         | 6/29/99  | North Jr.       | 417   | 36        | 1/7/97              |
|             | A61       | 5971713         | 10/26/99 | North Jr.       | 417   | 36        | 12/29/98            |
|             | A62       | 6008920         | 12/28/99 | Hendrix         | 398   | 79        | 3/11/98             |
|             | A63       | 6017194         | 1/25/00  | North Jr.       | 417   | 36        | 12/31/98            |
|             | A64       | 6102678         | 8/15/00  | Peclat          | 417   | 477.7     | 4/3/98              |
|             | A65       | 6135734         | 10/24/00 | Isozumi et al.  | 417   | 542       | 9/23/98             |
|             | A66       | 6159686         | 12/12/00 | Kardos et al.   | 435   | 6         | 01/30/98            |
|             | A67       | 6200101         | 3/13/01  | North Jr.       | 417   | 36        | 7/6/99              |
|             | A68       | 6252719         | 6/26/01  | Eichenbaum      | 359   | 634       | 3/19/99             |
|             | A69       | 6315952         | 11/13/01 | Sklar et al.    | 422   | 63        | 6/10/99             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                          |                                    |
|-----------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|------------------------------------|
| Form PTO-1449 (modified)                                                                                                          | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>   |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) | Applicant:<br><b>IRIS INTERNATIONAL, INC</b>             |                                    |
|                                                                                                                                   | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b>  |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i>         | Other Art<br><i>See Page 10-11</i> |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A70       | 6510007         | 1/21/03  | Blasenheim         | 359   | 659       | 8/21/01             |
|             | A71       | 6542306         | 4/1/03   | Goodman            | 359   | 634       | 3/16/01             |
|             | A72       | 6572255         | 6/3/03   | Husher             | 366   | 132       | 4/24/01             |
|             | A73       | 6608682         | 8/19/03  | Ortyn et al.       | 356   | 419       | 10/12/01            |
|             | A74       | 6618143         | 9/9/03   | Roche et al.       | 356   | 339       | 10/2/01             |
|             | A75       | 6638481         | 10/28/03 | Sklar et al.       | 422   | 63        | 9/19/01             |
|             | A76       | 6647175         | 11/11/03 | LoRegio et al.     | 385   | 24        | 10/8/01             |
|             | A77       | 6683314         | 1/27/04  | Oostman Jr. et al. | 250   | 461.2     | 8/28/01             |
|             | A78       | 6713019         | 3/30/04  | Ozasa et al.       | 422   | 82.09     | 3/27/02             |
|             | A79       | 6748133         | 6/8/04   | Liu et al.         | 385   | 24        | 11/26/01            |
|             | A80       | 6767188         | 7/27/04  | Vrane et al.       | 417   | 40        | 8/15/02             |
|             | A81       | 6768593         | 7/27/04  | Jutamulia          | 359   | 641       | 7/24/03             |
|             | A82       | 6788409         | 9/7/04   | Goodwin            | 356   | 339       | 9/3/02              |
|             | A83       | 6794671         | 9/21/04  | Nicoli et al.      | 250   | 574       | 7/17/02             |
|             | A84       | 6813017         | 11/2/04  | Hoffman et al.     | 356   | 317       | 10/19/00            |
|             | A85       | 6839367         | 1/4/05   | Nagamatsu et al.   | 372   | 34        | 3/16/01             |
|             | A86       | 6870679         | 3/22/05  | Randall et al.     | 359   | 580       | 6/10/02             |
|             | A87       | 6870976         | 3/22/05  | Chen et al.        | 385   | 14        | 3/13/01             |
|             | A88       | 6897954         | 5/24/05  | Bishop et al.      | 356   | 317       | 12/20/02            |
|             | A89       | 6941047         | 9/6/05   | Capewell et al.    | 385   | 47        | 3/1/04              |
|             | A90       | 6954722         | 10/11/05 | Parks et al.       | 702   | 194       | 10/17/03            |
|             | A91       | 6975400         | 12/13/05 | Ortyn et al.       | 356   | 419       | 7/28/03             |
|             | A92       | 7038778         | 5/2/06   | Yamauchi           | 356   | 419       | 8/13/02             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A93       | 7072540         | 7/4/06   | Szapiel et al.     | 385   | 24        | 4/22/03             |
|             | A94       | 7110192         | 9/19/06  | Sauter et al.      | 359   | 754       | 1/12/05             |
|             | A95       | 7113266         | 9/26/06  | Wells              | 356   | 73        | 3/30/05             |
|             | A96       | 7127356         | 10/24/06 | Nicoli et al.      | 702   | 26        | 5/18/04             |
|             | A97       | 7129505         | 10/31/06 | Oostman Jr. et al. | 250   | 458.1     | 10/17/03            |
|             | A98       | 7212343         | 5/1/07   | He et al.          | 359   | 618       | 7/11/03             |
|             | A99       | 7260328         | 8/21/07  | Kropp              | 398   | 82        | 2/24/03             |
|             | A100      | 7262838         | 8/28/07  | Fritz              | 356   | 73        | 1/16/04             |
|             | A101      | 7268953         | 9/11/07  | Matthae et al.     | 359   | 656       | 6/7/06              |
|             | A102      | 7305018         | 12/4/07  | Otoma              | 372   | 50.1      | 12/29/05            |
|             | A103      | 7381565         | 6/3/08   | Kurabayashi et al. | 436   | 63        | 3/20/06             |
|             | A104      | 7385682         | 6/10/08  | Chu et al.         | 356   | 73        | 9/7/06              |
|             | A105      | 7430048         | 9/30/08  | Reel et al.        | 356   | 432       | 2/16/06             |
|             | A106      | 7450229         | 11/11/08 | Ortyn et al.       | 356   | 326       | 5/4/05              |
|             | A107      | 7453915         | 11/18/08 | Imai               | 372   | 50.1      | 12/5/06             |
|             | A108      | 7456960         | 11/25/08 | Cerni et al.       | 356   | 336       | 11/15/05            |
|             | A109      | 7496463         | 2/24/09  | Nicoli et al.      | 702   | 104       | 9/12/06             |
|             | A110      | 7505131         | 3/17/09  | Roth               | 356   | 317       | 3/6/08              |
|             | A111      | 7507588         | 3/24/09  | Mehrpouyan et al.  | 436   | 518       | 4/14/06             |
|             | A112      | 7561267         | 7/14/09  | Luo et al.         | 356   | 336       | 12/22/06            |
|             | A113      | 7580120         | 8/25/09  | Hamada et al.      | 356   | 73        | 4/6/06              |
|             | A114      | 7623243         | 11/24/09 | Kato               | 356   | 419       | 9/13/04             |
|             | A115      | 7645127         | 1/12/10  | Hagen et al.       | 417   | 477.12    | 6/29/06             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name              | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-------------------|-------|-----------|---------------------|
|             | A116      | 7668422         | 2/23/10  | Kropp             | 385   | 47        | 3/12/04             |
|             | A117      | 7758324         | 6/20/10  | Baumann et al.    | 417   | 477.2     | 5/12/05             |
|             | A118      | 7768120         | 8/3/10   | Takashima         | 257   | 706       | 12/27/07            |
|             | A119      | 7781227         | 8/24/10  | Mehrpouyan et al. | 436   | 523       | 3/4/09              |
|             | A120      | 7787197         | 8/31/10  | Chen              | 359   | 793       | 9/4/08              |
|             | A121      | 7835000         | 11/16/10 | Graves et al.     | 356   | 338       | 11/3/06             |
|             | A122      | 7876436         | 1/25/11  | Chu               | 356   | 338       | 10/31/07            |
|             | A123      | 7894047         | 2/22/11  | Hamada et al.     | 356   | 39        | 7/24/09             |
|             | A124      | 7952981         | 3/31/11  | Suzuki            | 369   | 121       | 10/23/08            |
|             | A125      | 7981661         | 7/19/11  | Rich              | 435   | 286.5     | 4/17/07             |
|             | A126      | 8009189         | 8/30/11  | Ortyn et al.      | 348   | 80        | 6/3/08              |
|             | A127      | 8049185         | 11/1/11  | Hayashi et al.    | 250   | 459.1     | 2/4/09              |
|             | A128      | 8149525         | 4/3/12   | Do                | 359   | 797       | 3/28/07             |
|             | A129      | 8157547         | 4/17/12  | Vrielink          | 417   | 477.3     | 4/23/07             |
|             | A130      | 8187888         | 5/29/12  | Rich              | 436   | 63        | 7/8/11              |
|             | A131      | 8213472         | 7/3/12   | Hirai et al.      | 372   | 36        | 1/23/08             |
|             | A132      | 8229707         | 7/24/12  | Olson et al.      | 702   | 189       | 7/4/11              |
|             | A133      | 8233146         | 7/31/12  | Chen              | 356   | 246       | 1/5/10              |
|             | A134      | 8253938         | 8/28/12  | Vacca et al.      | 356   | 337       | 5/26/11             |
|             | A135      | 8270098         | 9/18/12  | Fukuta et al.     | 359   | 784       | 2/19/09             |
|             | A136      | 8284402         | 10/9/12  | Frazier et al.    | 356   | 419       | 2/26/10             |
|             | A137      | 8337096         | 12/25/12 | Shen et al.       | 385   | 89        | 11/30/09            |
|             | A138      | 8345237         | 1/1/13   | Tsukii et al.     | 356   | 338       | 12/23/11            |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name                  | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-----------------------|-------|-----------|---------------------|
|             | A139      | 8405048         | 3/26/13  | Hayashi               | 250   | 458.1     | 2/4/09              |
|             | A140      | 8432541         | 4/30/13  | Rich                  | 356   | 246       | 11/4/10             |
|             | A141      | 8436371         | 5/7/13   | Medendorp Jr., et al. | 257   | 88        | 5/24/07             |
|             | A142      | 8436993         | 5/7/13   | Kaduchak et al.       | 356   | 337       | 2/3/12              |
|             | A143      | 8488244         | 7/16/13  | Li et al.             | 359   | 618       | 2/17/11             |
|             | A144      | 8507279         | 8/13/13  | Ball et al.           | 436   | 10        | 6/2/10              |
|             | A145      | 2004165828      | 08/26/04 | Capewell et al.       | 385   | 47        | 03/01/04            |
|             | A146      | 20020067895     | 06/06/02 | Flanders              | 385   | 88        | 12/01/00            |
|             | A147      | 20020141902     | 10/3/02  | Ozasa et al.          | 422   | 82.09     | 3/27/02             |
|             | A148      | 20030142720     | 7/31/03  | Bradburn et al.       | 372   | 108       | 5/24/02             |
|             | A149      | 20040218184     | 11/4/04  | Joregenson et al.     | 356   | 419       | 2/27/04             |
|             | A150      | 20050084402     | 4/21/05  | Vanek                 | 417   | 477.3     | 10/27/04            |
|             | A151      | 20060221325     | 10/5/06  | Wells                 | 356   | 73        | 3/30/05             |
|             | A152      | 20060245964     | 11/2/06  | Koslov                | 417   | 477.1     | 6/29/06             |
|             | A153      | 20060256335     | 11/16/06 | Chen                  | 356   | 369       | 5/3/06              |
|             | A154      | 20060292021     | 12/28/06 | Tu                    | 417   | 477.1     | 11/7/02             |
|             | A155      | 20070124947     | 6/7/07   | Munroe et al.         | 33    | 286       | 10/25/06            |
|             | A156      | 20080024758     | 1/31/08  | Tabata                | 356   | 39        | 7/26/07             |
|             | A157      | 20080241911     | 10/2/08  | Ueno et al.           | 435   | 287.1     | 3/28/08             |
|             | A158      | 20090091746     | 4/9/09   | Fukuda et al.         | 356   | 73        | 10/1/08             |
|             | A159      | 20090190128     | 7/30/09  | Cerni et al.          | 356   | 336       | 11/24/08            |
|             | A160      | 20110014075     | 1/20/11  | Reif et al.           | 417   | 477.12    | 7/1/10              |
|             | A161      | 20110032522     | 2/10/11  | Graves et al.         | 356   | 338       | 10/12/10            |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name              | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-------------------|-------|-----------|---------------------|
|             | A162      | 20120156074     | 6/21/12  | Kusch et al.      | 417   | 477.3     | 2/4/10              |
|             | A163      | 20120274925     | 11/1/12  | Chen et al.       | 356   | 73        | 11/1/12             |
|             | A164      | 20120281204     | 11/8/12  | Hoshishima et al. | 356   | 72        | 1/13/11             |
|             | A165      | 20120282126     | 11/8/12  | Brandt et al.     | 417   | 477.9     | 11/4/10             |
|             | A166      | 20120287419     | 11/15/12 | Sharpe et al.     | 356   | 51        | 5/11/12             |
|             | A167      | 20130010181     | 1/10/13  | Baba              | 348   | 360       | 3/14/11             |
|             | A168      | 20130020498     | 1/24/13  | Ebi et al.        | 250   | 435       | 7/18/12             |
|             | A169      | 20130050782     | 2/28/13  | Heng et al.       | 358   | 494       | 2/17/12             |
|             | A170      | 20130070243     | 3/21/13  | Goehde            | 356   | 338       | 11/9/12             |
|             | A171      | 20130094102     | 4/18/13  | Baba              | 359   | 784       | 7/13/10             |
|             | A172      | 20130204538     | 8/8/13   | Rich              | 702   | 21        | 10/25/11            |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                   |
|-------------|-----------|-----------------|----------|---------|----------------------------|
|             | B1        | CN 102087198    | 6/8/11   | China   | Chinese (English abstract) |
|             | B2        | CN 102818794    | 12/12/12 | China   | Chinese (English abstract) |
|             | B3        | CN 102818795    | 12/12/12 | China   | Chinese (English abstract) |
|             | B4        | CN 102818796    | 12/12/12 | China   | Chinese (English abstract) |
|             | B5        | CN 201917509U   | 8/3/11   | China   | Chinese (English abstract) |
|             | B6        | CN 201936066U   | 8/17/11  | China   | Chinese (English abstract) |
|             | B7        | CN 201984209U   | 9/21/11  | China   | Chinese (English abstract) |
|             | B8        | EP 0889319      | 1/7/99   | EPO     | German (English abstract)  |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                       |
|-------------|-----------|-----------------|----------|---------|--------------------------------|
|             | B9        | EP 1004907      | 4/22/09  | EPO     | English                        |
|             | B10       | EP 1953526      | 8/6/08   | EPO     | English                        |
|             | B11       | EP 2381475      | 3/4/15   | EPO     | English                        |
|             | B12       | EP 459764A2     | 12/4/91  | EPO     | English                        |
|             | B13       | EP 459764B1     | 12/11/96 | EPO     | English                        |
|             | B14       | EP 757346A1     | 2/5/97   | EPO     | English                        |
|             | B15       | EP 757346B1     | 11/14/01 | EPO     | English                        |
|             | B16       | EP 758755A2     | 2/19/97  | EPO     | English                        |
|             | B17       | JP 05333245     | 12/17/93 | Japan   | Japanese (English abstract)    |
|             | B18       | JP 2004-341204  | 12/02/04 | Japan   | Japanese (English Abstract)    |
|             | B19       | JP 2012-026837  | 02/09/12 | Japan   | Japanese (English Abstract)    |
|             | B20       | JP 829726       | 2/2/96   | Japan   | Japanese (English translation) |
|             | B21       | JP H04-184241   | 07/01/92 | Japan   | Japanese (English Abstract)    |
|             | B22       | JP H09-502794   | 03/18/97 | Japan   | Japanese (English Abstract)    |
|             | B23       | JP H10-73528    | 03/17/98 | Japan   | Japanese (English Abstract)    |
|             | B24       | WO 0057173      | 9/28/00  | WIPO    | English                        |
|             | B25       | WO 0127590      | 4/19/01  | WIPO    | English                        |
|             | B26       | WO 0140764      | 6/7/01   | WIPO    | English                        |
|             | B27       | WO 03012403     | 2/13/03  | WIPO    | French (English abstract)      |
|             | B28       | WO 2005033654   | 4/14/05  | WIPO    | English                        |
|             | B29       | WO 2006013316   | 2/9/06   | WIPO    | English                        |
|             | B30       | WO 2009095358   | 8/6/09   | WIPO    | German (English abstract)      |
|             | B31       | WO 2009098867   | 8/13/09  | WIPO    | Japanese (English abstract)    |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language |
|-------------|-----------|-----------------|----------|---------|----------|
|             | B32       | WO 2011026942   | 3/10/11  | WIPO    | English  |
|             | B33       | WO 2012056217   | 5/3/12   | WIPO    | English  |
|             | B34       | WO 2012177367   | 12/27/12 | WIPO    | English  |
|             | B35       | WO 2013013229   | 1/24/13  | WIPO    | English  |
|             | B36       | WO 2013093035   | 6/27/13  | WIPO    | English  |
|             | B37       | WO 9307471      | 4/15/93  | WIPO    | English  |
|             | B38       | WO 9316368      | 8/16/93  | WIPO    | English  |
|             | B39       | WO 9429695      | 12/22/94 | WIPO    | English  |
|             | B40       | WO 9714066A2    | 4/17/97  | WIPO    | English  |

### Other Art (Including Author, Title, Date Pertinent Pages, Etc.)

| Exam. Init. | Ref. Des. | Citation                                                                                                                                                   |
|-------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | C1        | Brogioli et al., "Heterodyne near-field scattering," <i>Applied Physics Letters</i> 81(22):4109-4111, 2002.                                                |
|             | C2        | Extended European Search Report for EP 13796734.5, mailed March 18, 2016                                                                                   |
|             | C3        | Goda et al., "Serial time-encoded amplified imaging for observation of fast dynamic phenomena," <i>Nature</i> 458:1145-1149. 2009                          |
|             | C4        | International Search Report and Written Opinion for PCT/US2013/043453 mailed December 20, 2013.                                                            |
|             | C5        | International Search Report and Written Opinion for PCT/US2014/067682 mailed April 9, 2015.                                                                |
|             | C6        | Office Action issued in Japanese Patent Application No. 2015-515208, issued May 29, 2017 (English Translation Provided) (Attorney Docket No. BECC.P0002JP) |
|             | C7        | Schmidt, B., "Ein lichtstarkes komafreies Spiegelsystem," <i>Mitteilungen der Haburger Sternwarte in Bergedorf</i> 7(36):15-17, 1932.                      |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                                                 |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                                                 | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                                                 | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                                                 | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i>                                | Other Art<br><i>See Page 10-11</i>                       |                                   |
| <b>Other Art (Including Author, Title, Date Pertinent Pages, Etc.)</b>                                                            |                                                                                 |                                                          |                                   |
| C8                                                                                                                                | Smiley, C. H., "The Schmidt Camera," <i>Popular Astronomy</i> 44:415-421, 1936. |                                                          |                                   |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

## Electronic Acknowledgement Receipt

|                                             |                                   |
|---------------------------------------------|-----------------------------------|
| <b>EFS ID:</b>                              | 29963470                          |
| <b>Application Number:</b>                  | 15638461                          |
| <b>International Application Number:</b>    |                                   |
| <b>Confirmation Number:</b>                 | 9847                              |
| <b>Title of Invention:</b>                  | FLOW CYTOMETER                    |
| <b>First Named Inventor/Applicant Name:</b> | Yong Qin Chen                     |
| <b>Customer Number:</b>                     | 32425                             |
| <b>Filer:</b>                               | Gina N. Shishima/Hannah Wimberley |
| <b>Filer Authorized By:</b>                 | Gina N. Shishima                  |
| <b>Attorney Docket Number:</b>              | BECC.P0002US.CIP.C1               |
| <b>Receipt Date:</b>                        | 02-AUG-2017                       |
| <b>Filing Date:</b>                         | 30-JUN-2017                       |
| <b>Time Stamp:</b>                          | 15:38:48                          |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a)       |

### Payment information:

|                        |    |
|------------------------|----|
| Submitted with Payment | no |
|------------------------|----|

### File Listing:

| Document Number | Document Description | File Name                 | File Size(Bytes)/<br>Message Digest     | Multi Part /.zip | Pages (if appl.) |
|-----------------|----------------------|---------------------------|-----------------------------------------|------------------|------------------|
| 1               |                      | BECCP0002USCIP_C1_IDS.pdf | 238151                                  | yes              | 13               |
|                 |                      |                           | f50cbe4fb81d5d828c299d6846b266a94dc8730 |                  |                  |

|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                            |              |            |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------|--------------|------------|
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | <b>Multipart Description/PDF files in .zip description</b> |              |            |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | <b>Document Description</b>                                | <b>Start</b> | <b>End</b> |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Transmittal Letter                                         | 1            | 2          |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Information Disclosure Statement (IDS) Form (SB08)         | 3            | 13         |
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                            |              |            |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                            |              |            |
| <b>Total Files Size (in bytes):</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                            | 238151       |            |
| <p><b>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</b></p> <p><b><u>New Applications Under 35 U.S.C. 111</u></b><br/> <b>If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</b></p> <p><b><u>National Stage of an International Application under 35 U.S.C. 371</u></b><br/> <b>If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</b></p> <p><b><u>New International Application Filed with the USPTO as a Receiving Office</u></b><br/> <b>If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</b></p> |                                                            |              |            |

**PATENT**

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:  
IRIS INTERNATIONAL, INC.

Serial No.: 15/638,461

Filed: June 30, 2017

For: FLOW CYTOMETER

Group Art Unit: Not Yet Assigned

Examiner: Not Yet Assigned

Atty. Dkt. No.: BECC.P0002US.CIP.C1/11706355

Confirmation No.: 9847

Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

**CERTIFICATE OF ELECTRONIC TRANSMISSION**  
37 C.F.R. § 1.8

I hereby certify that this correspondence is being electronically filed with the United States Patent and Trademark Office via EFS-Web on the date below:

August 2, 2017  
Date

/Gina N. Shishima/  
Gina N. Shishima

**INFORMATION DISCLOSURE STATEMENT**

Commissioner:

In compliance with the duty of disclosure under 37 C.F.R. § 1.56, it is respectfully requested that this Information Disclosure Statement be entered and the documents listed on attached Form PTO-1449 be considered by the Examiner and made of record. Copies of the listed documents required by 37 C.F.R. § 1.98(a)(2) are enclosed for the convenience of the Examiner.

In accordance with 37 C.F.R §§ 1.97(g), (h), this Information Disclosure Statement is not to be construed as a representation that a search has been made, and is not to be construed to be an admission that the information cited is, or is considered to be, material to patentability as defined in 37 C.F.R. § 1.56(b).

The present Information Disclosure Statement is being filed within three months of the filing date of the subject application, and hence is believed to be timely filed in accordance with

37 C.F.R. § 1.97(b). No fees are believed to be due in connection with the filing of this Information Disclosure Statement, however, should any fees under 37 C.F.R. §§ 1.16 to 1.21 be deemed necessary for any reason relating to these materials, the Commissioner is authorized to deduct the appropriate fees from Norton Rose Fulbright US LLP Deposit Account No.: 50-1212/BECC.P0002US.CIP.C1/11706355.

This application is a continuation application of Serial No. 14/555,102 , filed November 26, 2014, and is relied upon for an earlier filing date under 35 U.S.C. § 120. In accordance with 37 C.F.R. § 1.98(d), copies of the listed documents are not enclosed as they have been previously cited by or submitted to the Patent and Trademark Office in prior application Serial No. 14/555,102.

Applicant respectfully requests that the listed documents be made of record in the present case.

Respectfully submitted,

/Gina N. Shishima/

Gina N. Shishima  
Reg. No. 45,104  
Attorney for Applicant

NORTON ROSE FULBRIGHT US LLP  
98 San Jacinto Blvd., Suite 1100  
Austin, TX 78701  
(512) 474-5201

Date: August 2, 2017



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NUMBER | FILING OR 371(C) DATE | FIRST NAMED APPLICANT | ATTY. DOCKET NO./TITLE |
|--------------------|-----------------------|-----------------------|------------------------|
| 15/638,461         | 06/30/2017            | Yong Qin Chen         | BECC.P0002US.CIP.C1    |

**CONFIRMATION NO. 9847**

32425  
NORTON ROSE FULBRIGHT US LLP  
98 SAN JACINTO BOULEVARD  
SUITE 1100  
AUSTIN, TX 78701-4255

## PUBLICATION NOTICE



\*OC000000095036238\*

**Title:**FLOW CYTOMETER

**Publication No.**US-2017-0307506-A1

**Publication Date:**10/26/2017

## NOTICE OF PUBLICATION OF APPLICATION

The above-identified application will be electronically published as a patent application publication pursuant to 37 CFR 1.211, et seq. The patent application publication number and publication date are set forth above.

The publication may be accessed through the USPTO's publically available Searchable Databases via the Internet at [www.uspto.gov](http://www.uspto.gov). The direct link to access the publication is currently <http://www.uspto.gov/patft/>.

The publication process established by the Office does not provide for mailing a copy of the publication to applicant. A copy of the publication may be obtained from the Office upon payment of the appropriate fee set forth in 37 CFR 1.19(a)(1). Orders for copies of patent application publications are handled by the USPTO's Public Records Division. The Public Records Division can be reached by telephone at (571) 272-3150 or (800) 972-6382, by facsimile at (571) 273-3250, by mail addressed to the United States Patent and Trademark Office, Public Records Division, Alexandria, VA 22313-1450 or via the Internet.

In addition, information on the status of the application, including the mailing date of Office actions and the dates of receipt of correspondence filed in the Office, may also be accessed via the Internet through the Patent Electronic Business Center at [www.uspto.gov](http://www.uspto.gov) using the public side of the Patent Application Information and Retrieval (PAIR) system. The direct link to access this status information is currently <https://portal.uspto.gov/pair/PublicPair>. Prior to publication, such status information is confidential and may only be obtained by applicant using the private side of PAIR.

Further assistance in electronically accessing the publication, or about PAIR, is available by calling the Patent Electronic Business Center at 1-866-217-9197.

Office of Data Management, Application Assistance Unit (571) 272-4000, or (571) 272-4200, or 1-888-786-0101

|                                                                                                                                   |                                               |                                                 |                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------|-------------------------------------------------|----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                               | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1</b> | Serial No.:<br><b>15/638,461</b> |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                               | Applicant:<br><b>IRIS INTERNATIONAL, INC.</b>   |                                  |
|                                                                                                                                   |                                               | Filing Date:<br><b>June 30, 2017</b>            | Group:<br><b>2884</b>            |
| U.S. Patent Documents<br><i>See Page 1</i>                                                                                        | Foreign Patent Documents<br><i>See Page 1</i> | Other Art<br><i>See Page 2</i>                  |                                  |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name          |
|-------------|-----------|-----------------|----------|---------------|
|             | A173      | 2005/0134836    | 06/23/05 | Paldus et al. |
|             | A174      | 2012/0211679    | 08/23/12 | Heng et al.   |
|             | A175      | 4,673,289       | 06/16/87 | Gaucher       |
|             | A176      | 7,630,147       | 12/08/09 | Kar et al.    |
|             | A177      | 7,889,263       | 02/15/11 | Ortyn et al.  |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                    |
|-------------|-----------|-----------------|----------|---------|-----------------------------|
|             | B41       | JP 2003-505707  | 02/12/03 | Japan   | Japanese (English Abstract) |
|             | B42       | JP 2004-500572  | 01/08/04 | Japan   | Japanese (English Abstract) |
|             | B43       | JP 2008-534960  | 08/28/08 | Japan   | Japanese (English Abstract) |
|             | B44       | JP 2010-085194  | 04/15/10 | Japan   | Japanese (English Abstract) |
|             | B45       | JP H03-197641   | 08/29/91 | Japan   | Japanese (English Abstract) |
|             | B46       | JP H05-119035   | 05/14/93 | Japan   | Japanese (English Abstract) |
|             | B47       | JP S55-144226   | 11/11/80 | Japan   | Japanese (English Abstract) |
|             | B48       | JP S61-184427   | 08/18/86 | Japan   | Japanese (English Abstract) |
|             | B49       | WO 2013/181453  | 12/05/13 | WIPO    | English                     |

29764669.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



|                                                                                                                                   |                                                 |                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------|
| Form PTO-1449 (modified)                                                                                                          | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1</b> | Serial No.:<br><b>15/638,461</b> |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) | Applicant:<br><b>IRIS INTERNATIONAL, INC.</b>   |                                  |
|                                                                                                                                   | Filing Date:<br><b>June 30, 2017</b>            | Group:<br><b>2884</b>            |
| U.S. Patent Documents<br><i>See Page 1</i>                                                                                        | Foreign Patent Documents<br><i>See Page 1</i>   | Other Art<br><i>See Page 2</i>   |

### Other Art (Including Author, Title, Date Pertinent Pages, Etc.)

| Exam.<br>Init. | Ref.<br>Des. | Citation                                                                                                                                                 |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | C9           | Office Action issued in Chinese Patent Application No. 201380039184.6, dated February 12, 2018 (Attorney Docket No. BECC.P0002CN)                        |
|                | C10          | Office Action issued in Japanese Patent Application No. 2015-515208, dated May 02, 2018 (Attorney Docket No. BECC.P0002JP)                               |
|                | C11          | Office Action issued in Japanese Patent Application No. 2016-216891, dated December 04, 2017 (English Translation) (Attorney Docket No. BECC.P0002JP.D1) |

29764669.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



Espacenet

Bibliographic data: JP2004500572 (A) — 2004-01-08

## FIBER OPTIC SCANNER

Inventor(s):

Applicant(s):

**Classification:** - international: G01N21/25; G01N21/64; G01N21/76; G01N33/53; G01N37/00; G02B21/00; G02B26/10; G02B6/036;  
 (IPC1-7): G01N21/64; G01N21/76; G01N33/53;  
 G01N37/00; G02B26/10; G02B6/22  
 - cooperative: G01N21/645; G01N21/6452; G01N21/6456;  
G01N21/76; G02B21/002; G01N2021/6484

**Application number:** JP20010568124 20010313

**Priority number(s):** US20000188873P 20000313 ; WO2001US08043 20010313

**Also published as:** AU4362701 (A) CA2401511 (A1) EP1264168 (A2)  
US2002037149 (A1) WO0169302 (A2) more

Abstract not available for JP2004500572 (A)

Abstract of corresponding document: WO0169302 (A2)

The disclosed scanning structure includes an apparatus for light delivery and light receiving from a light-excitable area on a substrate to be measured by the scanning structure. The light delivery and receiving apparatus may include an optical fiber having a proximal end and a distal end which transmits light having a certain wavelength or light with several varying wavelengths to excite the substrate samples. This optical fiber may also simultaneously receive light which may be emitted by fluorescing samples on the substrate. The scanning structure also may further include a holder for the optical fiber that is able to transverse variable distances over the substrate to be measured or examined. Holders may include galvano scanners as well as resonating suspension beams. A light source, e.g., a laser, may be optically coupled to the optic fiber's proximal end. And this light source may be of a certain wavelength, but multiple light sources each having a different wavelength may also be used simultaneously by coupling the light sources into either a single optic fiber through wavelength multiplexers or by placing individual optic fibers carrying differing wavelengths in close proximity to each other. As the light is transmitted down to the substrate through the

optic fiber, the fiber is sufficiently close to the substrate microarray so that it can also receive the emitted fluorescing light.

(19) 日本国特許庁 (JP)

(12) 公表特許公報 (A)

(11) 特許出願公表番号

特表2004-500572

(P2004-500572A)

(43) 公表日 平成16年1月8日 (2004. 1. 8)

(51) Int. Cl. <sup>7</sup>

F I

テーマコード (参考)

GO 1 N 21/64

GO 1 N 21/64

F

2 GO 4 3

GO 1 N 21/76

GO 1 N 21/76

2 GO 5 4

GO 1 N 33/53

GO 1 N 33/53

M

2 HO 4 5

GO 1 N 37/00

GO 1 N 37/00

1 O 2

2 HO 5 0

GO 2 B 6/22

GO 2 B 6/22

審査請求 未請求 予備審査請求 有 (全 72 頁) 最終頁に続く

(21) 出願番号 特願2001-568124 (P2001-568124)

(86) (22) 出願日 平成13年3月13日 (2001. 3. 13)

(85) 翻訳文提出日 平成14年9月13日 (2002. 9. 13)

(86) 国際出願番号 PCT/US2001/008043

(87) 国際公開番号 W02001/069302

(87) 国際公開日 平成13年9月20日 (2001. 9. 20)

(31) 優先権主張番号 60/188, 873

(32) 優先日 平成12年3月13日 (2000. 3. 13)

(33) 優先権主張国 米国 (US)

(71) 出願人 502305788

ジェノスペクトラ, インコーポレイティド  
アメリカ合衆国, カリフォルニア 945  
55, フレモント, ダンバートン サーク  
ル 6519

(74) 代理人 100077517

弁理士 石田 敬

(74) 代理人 100092624

弁理士 鶴田 準一

(74) 代理人 100108383

弁理士 下道 晶久

(74) 代理人 100082898

弁理士 西山 雅也

(74) 代理人 100081330


弁理士 樋口 外治

最終頁に続く

(54) 【発明の名称】 光ファイバ走査装置

(57) 【要約】

開示される走査構造には、該走査構造で測定される基板上の光励起可能領域に対する光伝達及び受光装置が含まれている。この光伝達及び受光装置には、基端及び先端を有する光ファイバが含まれていてもよい。この光ファイバは、ある波長の光又はいくつかの多様な波長の光を伝達して、基板のサンプルを励起する。また、この光ファイバは、基板上のサンプルに蛍光を発生させることにより放出された光を、同時に受光してもよい。さらに、走査構造には、測定又は検査対象となる基板上を可変の距離を持って横切ることが可能な光ファイバホルダーが含まれていてもよい。ホルダには、ガルバノスキャナや共振懸架ビームが含まれていてもよい。例えばレーザ等の光源が、光ファイバの基端に光学的に連結されてもよい。この光源は、ある波長のものであってもよいが、異なる波長の複数の光源が、波長マルチプレクサで光源を単一の光ファイバに結合するか、あるいは、異なる波長を伝達する個別の光ファイバを互いに近接させて配置することにより、同時に用いられてもよい。光は、光フ



**【特許請求の範囲】****【請求項1】**

基板上の光励起可能領域へ光を導くとともに該光励起可能領域から発せられた光を受光する走査構造であって、該走査構造は、第1の波長の光及び第2の波長の光を伝達し、基端及び先端を有する光ファイバを備え、該光ファイバは、前記光励起可能領域が前記第1の波長の光を受光したときに発生する前記第2の波長の光の少なくとも一部を受光するように構成された走査構造。

**【請求項2】**

前記第1の波長の光及び前記第2の波長の光を伝達する追加的な複数本の光ファイバをさらに備え、前記の追加的な各光ファイバは、基端及び先端を有するとともに、前記基板の前記光励起可能領域に充分近接した状態で移動して、該光ファイバが、前記光励起可能領域が前記第1の波長の光を受光したときに発生する前記第2の波長の光の少なくとも一部を捉えるように構成された請求項1に記載の走査構造。

**【請求項3】**

前記光ファイバの先端と前記追加的な光ファイバの先端とが、固定された関係で保持されている請求項2に記載の走査構造。

**【請求項4】**

前記光ファイバの前記基端に光学的に連結されて、前記第2の波長の光を受光する検出器をさらに備えた請求項1～3のいずれか一項に記載の走査構造。

**【請求項5】**

前記光ファイバが前記基板を走査するように該基板を移動させるべく構成された基板ホルダをさらに備えた請求項1～4のいずれか一項に記載の走査構造。

**【請求項6】**

前記光ファイバが前記基板の前記光励起可能領域を移動するのに充分である第1の位置及び第2の位置間の距離を移動する光ファイバホルダをさらに備えた請求項1～5のいずれか一項に記載の走査構造。

**【請求項7】**

前記光励起可能領域を励起するために前記第1の波長の光を発する光源をさらに備え、該光源は、前記第1の波長の光が前記光ファイバの先端から出射するように、該光ファイバの基端に光学的に連結されている請求項1～6のいずれか一項に記載の走査構造。

**【請求項8】**

基板上の光励起可能領域へ光を導くとともに該光励起可能領域から発せられた光を受光する走査構造であって、該走査構造は、

- a) 基端及び先端を有し、第1の波長の光及び第2の波長の光を伝達する光ファイバと、
  - b) 前記光励起可能領域が前記第1の波長の光を受光したときに、前記光励起可能領域から前記第2の波長の光が発せられる前記基板の前記光励起可能領域を移動するのに充分である第1の位置及び第2の位置間の距離を移動する光ファイバホルダと、
  - c) 前記光励起可能領域を励起するために前記第1の波長の光を発する光源であって、前記第1の波長の光が前記光ファイバの先端から出射するように、該光ファイバの基端に光学的に連結された光源とを備え、
  - d) 前記光ファイバは、マイクロアレイに充分近接して、該光ファイバが、前記光励起可能領域により生じた前記第2の波長の光を、該光ファイバの先端で受光し、該第2の波長の光を該光ファイバの基端へ伝達するように、前記ホルダに取り付けられ、
  - e) 前記ホルダは、前記光源が前記第1の波長の光を発しているときに、前記第1の位置及び前記第2の位置間を移動するように構成されている
- 走査構造。

**【請求項9】**

前記走査構造は、先端部分及び基端部分を有するビームをさらに備え、前記先端部分は、前記ホルダを備え、前記ビームは、該ビームの基端で、マウントに取り付けられるとともに

に、該ビームの先端部分が前記第1の位置及び前記第2の位置間を移動するように構成された請求項1～8のいずれか一項に記載の走査構造。

【請求項10】

前記ビームは、ガルバノメータの可動ビームである請求項9に記載の走査構造。

【請求項11】

前記ビームは、前記第1の位置及び前記第2の位置間を、該ビームの共振周波数で移動する請求項9に記載の走査構造。

【請求項12】

前記ビームの共振周波数が圧電的に駆動される請求項11に記載の走査構造。

【請求項13】

前記ビームの共振周波数が磁氣的に駆動される請求項11に記載の走査構造。

【請求項14】

前記ビームの基端は、該ビームの基端が動かないように、前記マウントに取り付けられた請求項9に記載の走査構造。

【請求項15】

前記ホルダは、前記第1の位置及び前記第2の位置間を水平移動するように構成され、前記走査構造は、前記ホルダが前記第1の位置及び第2の位置の少なくとも一方に達したときに、該ホルダを垂直方向に反発させる磁石をさらに備えた請求項8～14のいずれか一項に記載の走査構造。

【請求項16】

前記光源は、前記第1の波長の光を発するレーザを備えた請求項7～15のいずれか一項に記載の走査構造。

【請求項17】

前記走査構造は、第1の分岐チャネル及び第2の分岐チャネルを有する光学フィルタをさらに備え、該光学フィルタは、該第1の分岐チャネルで、前記レーザからの前記第1の波長の光を受光するように構成されるとともに、該第2の分岐チャネルを通じて、前記受光可能領域からの前記第2の波長の光を伝達するように構成された請求項1～16のいずれか一項に記載の走査構造。

【請求項18】

前記走査構造は、前記第1の位置及び前記第2の位置で規定される線に対して概ね垂直な方向に向って、基板を移動させる基板平行移動ステージをさらに備えた請求項8～17のいずれか一項に記載の走査構造。

【請求項19】

前記ホルダは、前記光ファイバが基板に対して垂直以外の角度になるようにしておく請求項8～18のいずれか一項に記載の走査構造。

【請求項20】

前記光ファイバの先端を規定する表面は、前記基板と実質的に平行である請求項8～19のいずれか一項に記載の走査構造。

【請求項21】

前記光ファイバは、毛管ファイバをさらに備えた請求項1～20のいずれか一項に記載の走査構造。

【請求項22】

前記光ファイバは、第1の屈折率の内側コア及び該内側コアの外側にあり第2の屈折率の外側コアを備えたダブルコアファイバであり、前記第1の屈折率は、前記第2の屈折率よりも大きい請求項1～20のいずれか一項に記載の走査構造。

【請求項23】

基板上の光励起可能領域へ光を導くとともに該光励起可能領域から発せられた光を受光する走査構造であって、該走査構造は、

a) 複数本の光ファイバであって、各光ファイバは、対応する基端及び対応する先端を有して、予め選択された複数の異なる波長の光を伝達し、各波長は各光ファイバに対応して

いる複数本の光ファイバを備え、

b) 前記複数本の光ファイバは、第1の波長の光及び第2の波長の光を伝達する第1の光ファイバを少なくとも具備し、

c) 前記複数本の光ファイバが、前記光励起可能領域が少なくとも前記第1の波長の光を受光したときに、該光励起可能領域から少なくとも前記第2の波長の光が発せられる前記基板の前記光励起可能領域に沿って移動するのに十分な距離を有する第1の位置及び第2の位置間を移動する前記複数本の光ファイバ用のホルダと、

d) 前記各光ファイバに対応した複数の光源であって、前記光励起可能領域を励起するために前記第1の波長の光を少なくとも発し、少なくとも前記第1の波長の光が少なくとも前記第1の光ファイバの先端から出射するように、前記複数本の光ファイバの対応する基端に光学的に連結された複数の光源とを、前記走査構造が備え、

e) 前記複数本の光ファイバは、マイクロアレイに充分近接して、各光ファイバが、前記光励起可能領域により生じた少なくとも前記第2の波長の光を、各光ファイバの先端で受光し、この少なくとも第2の波長の光を少なくとも前記第1の光ファイバの基端へ伝達するように、前記ホルダに取り付けられ、

f) 前記ホルダは、前記複数の光源が少なくとも前記第1の波長の光を発しているときに、前記第1の位置及び前記第2の位置間を移動するように構成されている走査構造。

【請求項24】

先端部分及び基端部分を有するビームをさらに備え、前記先端部分は、前記ホルダを備え、前記ビームは、そのビームの基端で、マウントに取り付けられるとともに、そのビームの先端部分が前記第1の位置及び前記第2の位置間で移動するように構成された請求項23に記載の走査構造。

【請求項25】

前記ビームは、ガルバノメータの可動ビームである請求項24に記載の走査構造。

【請求項26】

前記ビームは、前記第1の位置及び前記第2の位置間を、そのビームの共振周波数で移動する請求項24に記載の走査構造。

【請求項27】

前記ビームの共振周波数が圧電駆動される請求項26に記載の走査構造。

【請求項28】

前記ビームの共振周波数が磁気駆動される請求項26に記載の走査構造。

【請求項29】

前記ビームの基端は、該ビームの基端が動かないように、前記マウントに取り付けられた請求項24に記載の走査構造。

【請求項30】

前記ホルダは、前記第1の位置及び前記第2の位置間を水平移動するように構成され、前記走査構造は、前記ホルダが前記第1の位置及び第2の位置の少なくとも一方に達したときに、該ホルダを垂直に反発させる磁石をさらに備えた請求項23～29のいずれか一項に記載の走査構造。

【請求項31】

前記複数の光源は、少なくとも前記第1の波長の光を発する複数のレーザを備えた請求項23～30のいずれか一項に記載の走査構造。

【請求項32】

前記走査構造は、少なくとも第1の分岐チャネル及び第2の分岐チャネルを有する複数の光学フィルタをさらに備え、該光学フィルタは、その第1の分岐チャネルで、前記複数のレーザからの少なくとも前記第1の波長の光を受光するように構成されるとともに、その第2の分岐チャネルを通じて、前記光励起可能領域からの少なくとも前記第2の波長の光を伝達するように構成された請求項23～31のいずれか一項に記載の走査構造。

【請求項33】

前記複数本の光ファイバのうちの少なくとも1本は、複数の毛管ファイバをさらに備えた請求項23～32のいずれか一項に記載の走査構造。

【請求項34】

前記複数本の光ファイバのうちの少なくとも1本は、第1の屈折率を有する内側コア及び該内側コアの外側にある第2の屈折率を有する外側コアを備えたダブルコアファイバであり、前記第1の屈折率は、前記第2の屈折率よりも大きい請求項23～33のいずれか一項に記載の走査構造。

【請求項35】

前記複数本の光ファイバの先端は、複数のファイバ読取ヘッドを備え、各先端は、予め選択されたバンドル構成を有している請求項23～34のいずれか一項に記載の走査構造。

【請求項36】

前記複数本の光ファイバの先端は、複数のファイバ読取ヘッドを備え、各先端は、線状に隣接している請求項23～34のいずれか一項に記載の走査構造。

【請求項37】

基板上の光励起可能領域へ光を導くとともに該光励起可能領域から発せられた光を受光する走査構造であって、該走査構造は、

a) 複数本の光ファイバであって、各光ファイバは、対応する基端及び対応する先端を有して、予め選択された異なる複数の波長の光を伝達し、各波長は各光ファイバに対応している複数本の光ファイバを備え、

b) 前記複数本の光ファイバは、少なくとも第1の波長の光及び少なくとも第2の波長の光を伝達し、

c) 前記複数本の光ファイバの対応する先端のそれぞれを、主基端及び主先端を有する少なくとも1本の主光ファイバに、光学的に結合する複数のマルチプレクサと、

d) 前記主光ファイバが、前記光励起可能領域が少なくとも前記第1の波長の光を受光したときに、該光励起可能領域から少なくとも前記第2の波長の光が発せられる前記基板の前記光励起可能領域に沿って移動するのに十分な距離を有する第1の位置及び第2の位置間を移動する前記主光ファイバ用のホルダと、

e) 前記複数の各光ファイバに対応した複数の光源であって、前記光励起可能領域を励起するために前記第1の波長の光を少なくとも発し、少なくとも前記第1の波長の光が少なくとも1つの前記マルチプレクサを通じて前記主光ファイバの先端から出射するように、前記複数本の光ファイバの対応する基端に光学的に結合された複数の光源とを備え、

f) 前記主光ファイバは、マイクロアレイに充分近接して、前記光励起可能領域により生じた少なくとも前記第2の波長の光を、前記主光ファイバの先端で受光し、前記少なくとも第2の波長の光を、前記複数のマルチプレクサを通じて、前記複数本の光ファイバの基端へ伝達するように、前記ホルダに取り付けられ、 g) 前記ホルダは、前記複数の光源が少なくとも前記第1の波長の光を発しているときに、前記第1の位置及び前記第2の位置間を移動するように構成されている

走査構造。

【請求項38】

先端部分及び基端部分を有するビームをさらに備え、前記先端部分は、前記ホルダを備え、前記ビームは、該ビームの基端で、マウントに取り付けられるとともに、該ビームの先端部分が前記第1の位置及び前記第2の位置間で移動するように構成された請求項37に記載の走査構造。

【請求項39】

前記ホルダは、前記第1の位置及び前記第2の位置間を水平移動するように構成され、前記走査構造は、前記ホルダが前記第1の位置及び第2の位置の少なくとも一方に達したときに、当該ホルダを垂直に反発させる磁石をさらに備えた請求項37～38のいずれか一項に記載の走査構造。

【請求項40】

前記複数の光源は、少なくとも前記第1の波長の光を発する複数のレーザを備えた請求項



37～39のいずれか一項に記載の走査構造。

【請求項41】

前記走査構造は、少なくとも第1の分岐チャネル及び第2の分岐チャネルを有する複数の光学フィルタをさらに備え、該光学フィルタは、その第1の分岐チャネルで、前記複数のレーザからの少なくとも前記第1の波長の光を受光するように構成されるとともに、その第2の分岐チャネルを通じて、前記光励起可能領域からの少なくとも前記第2の波長の光を伝達するように構成された請求項37～40のいずれか一項に記載の走査構造。

【請求項42】

前記主光ファイバは、毛管ファイバをさらに備えた請求項37～41のいずれか一項に記載の走査構造。

【請求項43】

前記主光ファイバは、第1の屈折率を有する内側コア及び該内側コアの外側にある第2の屈折率を有する外側コアを備えたダブルコアファイバからなり、前記第1の屈折率は、前記第2の屈折率よりも大きい請求項37～41のいずれか一項に記載の走査構造。

【請求項44】

前記光ファイバは、該光ファイバの先端における径が、該光ファイバの全長に亘っての径と同じである請求項1～43のいずれか一項に記載の走査構造。

【請求項45】

被検体の表面へ光を導くとともに該表面からの光を受光する走査構造であって、前記被検体は、前記表面が第1の波長の光を受光すると第2の波長の光を発するものであり、前記表面は、(i)第1の方向に配列されたプローブの1次元のマイクロアレイであって、前記プローブが第2の方向に幅を有しているマイクロアレイ、又は(ii)基板の第1の方向及び第2の方向に沿って配列されたプローブの2次元のマイクロアレイを有し、前記走査構造は、

- a) 前記表面の少なくとも一部に、前記第1の波長の光を照射する光源と、
- b) 先端が前記表面に十分に近接して、前記表面で発せられた前記第2の波長の光を捉えるように配置された導光ロッドと、
- c) 前記導光ロッドを、前記表面上で第1の位置から第2の位置まで前記第2の方向に沿って移動させるように構成されたキャリアであって、前記第1の位置と前記第2の位置との距離は、(i)前記1次元のマイクロアレイについては、少なくともプローブの幅、又は(ii)前記2次元のマイクロアレイについては、前記第2の方向に最も離れたプローブ間の距離となっているキャリアとを、備えた走査構造。

【請求項46】

前記導光ロッドの基端が、前記光源により発生した前記第1の波長の光の少なくとも一部を受光し、その光を該導光ロッドの先端へ伝達するように、前記導光ロッドが構成されている請求項45に記載の走査構造。

【請求項47】

前記導光ロッドは、光ファイバを備えた請求項45又は46に記載の走査構造。

【請求項48】

前記走査構造は、第2の導光ロッドをさらに備え、該第2の導光ロッドが、前記光源からの前記第1の波長の光を該第2の導光ロッドの基端にて受光するように構成されるとともに、前記光が、前記基板の表面の近傍にある該第2の導光ロッドの先端から出射するように構成された請求項45～47のいずれか一項に記載の走査構造。

【請求項49】

前記第2の導光ロッドは、光ファイバを備えた請求項48に記載の走査構造。

【請求項50】

前記基板は、実質的に円形であり、該基板の光励起可能領域に対して垂直な回転軸を規定している請求項1～49のいずれか一項に記載の走査構造。

【請求項51】

被検体の表面へ光を導くとともに該表面からの光を受光する走査構造であって、前記被検

体は、前記表面が第1の波長の光を受光すると第2の波長の光を発するものであり、前記表面は、第1の方向に配列されたプローブの1次元のマイクロアレイであって、前記プローブが第2の方向に幅を有しているマイクロアレイを有し、前記走査構造は、

- a) 前記表面の少なくとも一部に、前記第1の波長の光を照射する光源と、
  - b) 先端が前記表面に十分に近接して、前記表面で発せられた前記第2の波長の光を捉えるように固定的に配置された導光ロッドと、
  - c) 前記導光ロッドを、前記表面上で第1の位置から第2の位置まで前記第1の方向に沿って移動させるように構成されたステージであって、前記第1の位置及び前記第2の位置間の距離は、少なくとも前記第1の方向に沿って配列されたプローブ間の距離になっているステージとを、
- 備えた走査構造。

【請求項52】

前記導光ロッドの基端が、前記光源により発生した前記第1の波長の光の少なくとも一部を受光し、該光を該導光ロッドの先端へ伝達するように前記導光ロッドが構成された請求項51に記載の走査構造。

【請求項53】

前記導光ロッドは、光ファイバを備えた請求項51又は52に記載の走査構造。

【請求項54】

前記走査構造は、前記基板上的前記光励起可能領域からの前記第2の波長の光を受光するように構成され、前記光励起可能領域には、約10マイクロメートル乃至約500マイクロメートルの径を有する該領域内に乾式サンプルが含まれている請求項1～53のいずれか一項に記載の走査構造。

【請求項55】

前記走査構造は、前記基板上的前記光励起可能領域からの前記第2の波長の光を受光するように構成され、前記光励起可能領域には、約10マイクロメートル乃至約500マイクロメートルの径を有する該領域内に湿式サンプルが含まれている請求項1～53のいずれか一項に記載の走査構造。

【請求項56】

前記走査構造は、前記基板上的前記光励起可能領域からの前記第2の波長の光を受光するように構成され、前記光励起可能領域には、約100マイクロメートル乃至約1000マイクロメートルの径を有する該領域内に湿式サンプルが含まれている請求項1～53のいずれか一項に記載の走査構造。

【請求項57】

前記光ファイバ又は前記導光ロッドは、第1の光励起可能領域からの前記第2の波長の光を受光するために十分に小さい径であるものの隣接した第2の光励起可能領域からは受光しない請求項54～56のいずれか一項に記載の走査構造。

【請求項58】

第1のターゲット分子と第1のプローブとの会合及び第2のターゲット分子と第2のプローブとの会合の存在を検出する方法であって、前記第1のプローブは、基板表面の第1の部分上にあって前記第1のターゲット分子と相補的な第1の分子を複数含み、前記第2のプローブは、基板表面の第2の部分上にあって前記第2のターゲット分子と相補的な第2の分子を複数含み、前記プローブは、前記基板上的複数のプローブのうちの1つであり、これらプローブは、(i) 前記基板に沿って配列されたプローブの1次元のマイクロアレイであって、前記基板の第2の方向に沿って配列された複数のプローブを有し、前記複数の各プローブは、前記基板上的第1の方向に幅を有する1次元のマイクロアレイ、又は(i i) 前記基板の第1の方向及び第2の方向に沿って配列されたプローブの2次元のマイクロアレイであって、前記第1の方向に沿って配列された複数のプローブ及び前記第2の方向に沿って配列された複数のプローブを有する2次元のマイクロアレイのいずれかとなっており、前記ターゲット分子は、第1の波長の光が照射されたときに第2の波長の光を発する成分を有し、前記方法は、

- a) 前記基板表面の前記第1の部分に、前記第1の波長の光を照射し、
  - b) 光検出器と前記表面の前記第1の部分との前記第1の方向に沿った相対移動により、前記第2の波長の光の存在を検出して、前記第1のターゲット分子が前記第1のプローブと会合しているかどうか判別し、
  - c) 前記基板を前記第2の方向へ進め、
  - d) 前記基板表面の前記第2の部分に前記第1の波長の光を照射し、前記光検出器を前記表面の前記第2の部分に亘って前記第1の方向へ移動させることにより、前記第2の波長の光の存在を再び検出して、前記第2のターゲット分子が前記第2のプローブと会合しているかどうか判別する
- 行為を含む方法。

【請求項59】

前記光検出器は、第1の光ファイバを備えた請求項58に記載の方法。

【請求項60】

前記照射の行為は、前記第1の光ファイバの基端に前記第1の波長の光を照射して、前記第1の波長の光を前記第1の光ファイバの先端から射出し、前記基板の前記第1の部分及び前記第2の部分照射することを含む請求項59に記載の方法。

【請求項61】

前記照射の行為は、第2の光ファイバの基端に前記第1の波長の光を照射して、前記第1の波長の光を前記第2の光ファイバの先端から射出し、前記基板の前記第1の部分及び前記第2の部分照射することを含む請求項59に記載の方法。

【請求項62】

走査装置により蛍光部分の存在を検出する方法であって、前記方法は、前記光ファイバの先端から出射する第1の波長の光で前記蛍光部分を励起して、第2の波長の光を放出させるように、前記走査装置のホルダの光ファイバの先端を位置ずけて、前記光ファイバの前記先端を前記蛍光部分に十分に近接させて、前記光ファイバの前記先端が前記第2の波長の光を受光して、前記第2の波長の光を前記光ファイバの前記基端へ伝達させる方法。

【請求項63】

前記方法は、前記光ファイバの前記先端を、該先端が前記蛍光部分の存在する表面に対して垂直とならないように配置する請求項62に記載の方法。

【請求項64】

走査装置で用いられるリニアステージの位置を検出する方法であって、

- a) 対応する第1の信号を有する第1のビーコンを、前記ステージ上の第1の位置に配置し、
  - b) 前記第1の信号よりも弱い第2の信号が対応している第2のビーコンを、前記ステージ上の第2の位置に少なくとも配置し、該第2の位置は、前記第1のビーコンから所定の距離にあるとともに前記第1のビーコンから前記第2のビーコンへの線が第1の方向を規定するようになっており、
  - c) 前記ステージを前記第1の方向へ移動させ、
  - d) 前記ステージを移動させている間に、検出器により前記第1の信号、そして前記第2の信号を検出し、
  - e) 検出した前記第1の信号及びより弱い前記第2の信号を、前記ステージの対応する位置に関連づける
- 行為を含む方法。

【請求項65】

前記検出器は、リニアCCDである請求項64に記載の方法。

【請求項66】

前記第1のビーコン及び第2のビーコンは、光ファイバを備えた請求項64又は65に記載の方法。

【請求項67】

前記所定の距離は、前記リニアCCDよりも短い請求項65又は64に記載の方法。

## 【請求項68】

走査構造を、高いスループットのスクリーニング用に構成された基板に用いる方法であって、前記走査構造は、光源及び検出器を有し、前記方法は、前記光源からの光を前記基板に照射し、該基板から受光した光を前記検出器で検出する方法。

## 【請求項69】

前記基板には、1平方センチメートル当たり少なくとも400個のマイクロウェルが含まれる請求項68に記載の方法。

## 【請求項70】

前記基板には、1平方センチメートル当たり少なくとも1000個のマイクロウェルが含まれる請求項68に記載の方法。

## 【請求項71】

前記基板には、液体内のプローブが含まれる請求項68～70のいずれか一項に記載の方法。

## 【請求項72】

前記基板から受光される前記光は、サンプルの蛍光により発生される請求項68～71のいずれか一項に記載の方法。

## 【請求項73】

前記基板から受光される前記光は、化学ルミネセンスにより発生される請求項68～71のいずれか一項に記載の方法。

## 【請求項74】

前記基板から受光される前記光には、前記光源により供給された光における少なくとも1つの波長が欠けている請求項68～71のいずれか一項に記載の方法。

## 【発明の詳細な説明】

## 【0001】

## 〔関連出願の参照〕

本発明は、2000年3月13日に出願された米国仮出願番号60/188,873による権利を主張し、参考としてここにその全てが盛り込まれている。

## 【0002】

## 〔技術分野〕

本発明は、DNAマイクロアレイ、タンパク質マイクロアレイ、及び化合物マイクロアレイのような、マイクロプレート (microplate) におけるマイクロアレイ (microarrays) 又はマイクロウェル (microwells) を、走査するための装置及び方法に関する。

## 【0003】

## 〔背景〕

マイクロアレイとは、基板上の所定の位置に固定された生物学又は化学サンプル (「プローブ」) のスポットの列である。各スポットには、単一の生物学的物質又は化学物質のいくつかの分子が含まれている。マイクロアレイは、1つ又はそれ以上の生物学的又は化学的サンプルを含んだ液体 (「ターゲット」) に浸される。通例、ターゲットは、マイクロアレイ上で1つ又はそれ以上の相補的なプローブと互に影響し合う。特に、DNAマイクロアレイでは、プローブがオリゴヌクレオチド又はcDNA菌株 (strains) であり、ターゲットが蛍光又は放射性ラベルがなされたDNAサンプルである。ターゲット中の分子鎖は、プローブのマイクロアレイ中の相補的な分子鎖とハイブリッドを形成する。

## 【0004】

ハイブリッド化されたマイクロアレイは、マイクロアレイ・リーダーにより検査される。マイクロアレイ・リーダーは、放射性ラベルの存在を検出するか、あるいは、レーザや他のエネルギー源を用いて蛍光ラベルを励起することにより、該蛍光ラベルを刺激し、光を放射させる。マイクロアレイ・リーダーは、マイクロアレイにおけるラベルの放射の位置及び強度を検出する。プローブは、マイクロアレイにおける予め定められた既知の位置に配置されているので、液体中の一連のターゲットは、蛍光又は放射線が検出された位置及び蛍光又は放射線の強度により、識別される。

## 【0005】

従って、マイクロアレイ・リーダは、マイクロアレイ技術の装置における重要な部分の1つである。現在、2種類のマイクロアレイ・リーダが利用可能である。第1種のものは、その一例が米国特許第5,324,633号に記述されており、走査顕微鏡の原理に基づくものである。それによると、2以上の波長のレーザビームが組み合わせられ、マイクロアレイ上の1つのスポットに集束されて、蛍光ラベルを励起する。組み合わせられたレーザビームは、2軸の平行移動ステージ上でマイクロアレイを動かすか、あるいは、顕微鏡のレンズを一方の軸で動かし、マイクロアレイ基板を他方の軸で動かすことにより、マイクロアレイ全体を各点毎に高い空間解像度（ $\sim 10\mu\text{m}$ ）で走査する。第2種のものは、その一例がWO00/12759号に示されており、CCD画像装置を用いて、マイクロアレイからの蛍光の放出を、小領域毎に一度に検出してゆく。アークランプのような広帯域の光源が、蛍光の励起に用いられている。

## 【0006】

走査顕微鏡技術では、コストに大きく影響するのは、その光学系である。これは、光学系が、波長の異なる複数のレーザビームを結合して正確に並べ、その後、別々の検出チャンネルへと再び分割しなければならないためである。顕微鏡のレンズ及びスライドキャリアの双方とも、かさばって重く、高速に動かすことができない。このことにより、走査スピードが制限される。

## 【0007】

CCD方式のシステムでは、画像装置及びレンズの双方がコストに大きく影響する。ここでは、励起光は、エネルギー密度を大幅に減少させて、広範囲に拡がってしまう。この減少を補償するために、露光時間を数十分の1秒まで延ばさなければならない。露光時間が長いので、CCD画像装置は、妥当なSN比を維持するために、冷却されている必要がある。冷却されている大型のこのようなCCD画像装置は、現在のところ非常に高価である。さらに、このシステムの光学レンズは、色収差及び広い視野に亘る像の歪曲が補正されていなければならない。このことにより、走査顕微鏡の各点毎のシステムにおけるレンズに比べて、コストが非常に上昇する。そのうえ、スライドの全領域（ $25\text{mm}\times 75\text{mm}$ ）に対応するのに十分な解像度と大きさを持ったCCD画像装置は、現在のところ存在しない。CCD方式のシステムでは、機械的な走査が、これまで通り必要とされる。これにより、マイクロアレイ・リーダが低速になる。現在、ほとんどの市販のマイクロアレイ・リーダは、 $25\text{mm}\times 70\text{mm}$ のスライドの走査を完了するのに、5分以上を要する。これは、多くの用途に対しておそすぎる。

## 【0008】

光ファイバは、近接場走査顕微鏡法に用いられてきている（D. W. Pohl, "Scanning near-field optical microscopy" in *Advances in Optical and Electron Microscopy* 12, C. J. R. Sheppard and T. Mulvey, Eds. (Academic Press, London, 1990); M. H. P. Moers, W. H. J. Kalle, A. G. T. Ruiter, J. C. A. G. Wiegant, A. K. Raap, J. Greve, B. G. De Grooth, N. F. van Hulst, *J. Microscopy* 182, p. 40, (1996)）。ここでは、光エネルギーは、直径がサブマイクロメートルにまで縮小されて、光ファイバ先端に導かれる。ファイバ先端は、被検面のナノメートルの数十分の1以下のところに置かれる。そして、ファイバ先端は、小領域（通常 $10\text{nm}$ 角）を走査し、被検面からの直接散乱光を受光する。（Chuck, 開示されている発明で、ファイバのコアが集光を最大化するには大きすぎ、集光された光は、被検体からの蛍光のように、間接的に放出されたものである。）

一方、光ファイバ・リーダ・ヘッドは、ABIのTaqmanリーダ（US5589351）のようないくつかの機器で、マイクロタイタープレート（microtiter plate）から放出された蛍光を受光するのに用いられてきた。ここで、リーダの空間解

像度は、数ミリメートルのオーダーである。励起光と受光された光とは、バンドルにおける別々のファイバで伝達される。光学ヘッドは、被検体から比較的大きく隔てられている。

【0009】

〔概要〕

以下に十分に記述するように、本発明により、プローブのマイクロアレイ又はサンプル（マイクロウェルに収納された乾式又は湿式）を走査するいくつかのシステム、装置、手段、及び方法が提供される。本開示内容のこの部分により、本発明の顕著な点についての要約が提供されるが、この部分は、本発明を、当該部分について考察された特徴及び実施形態のみに限定するように解釈されるためのものではない。むしろ、本発明には、特許請求の範囲とともに当該部分及びそれに続く部分で考察される全ての装置、システム、及び方法が含まれている。

【0010】

開示される走査構造には、該走査構造で測定される基板上の光励起可能領域に対する光伝達及び受光装置が含まれている。この光伝達及び受光装置は、基端及び先端を有する光ファイバを備えていてもよい。この光ファイバは、ある波長の光又はいくつかの多様な波長の光を伝達して、サンプルを照射する。これにより、発光が励起されたり1つかそれ以上の波長がサンプルに吸収されたりする。また、この光ファイバは、基板上のサンプルに蛍光を発生させることにより放出されるかあるいは他の方式で生じた、反射又は回折した光を、同時に受光してもよい。さらに、走査構造には、検査対象の基板上を可変の間隔で横切ることが可能な光ファイバホルダが含まれていてもよい。例えば、ホルダには、ガルバノスキャナや共振懸架ビームが含まれていてもよい。基板のサンプルを励起する光を発生させるために、例えばレーザ等の光源が、光ファイバの基端に光学的に結合されてもよい。異なった波長の複数の光源が、波長マルチプレクサで光源を単一の光ファイバに結合するか、あるいは、異なる波長を伝達する個別の光ファイバを互いに近接させて配置することにより、同時に用いられてもよい。光は、光ファイバを通じて基板へと伝達され、光ファイバは、発せられた蛍光をも受光できるように、この基板に十分に近接している。

【0011】

本発明のある実施形態は、蛍光を発するものとして記述されているが、本発明には、他の形式による光の発生も含まれている。他の形式として、化学ルミネセンス、及び、光が吸収されて吸収スペクトルが生じ、それが走査構造の導光部分（例えばファイバ又はロッド）により伝達されること等がある。このように、基板上の光励起可能領域は、湿式及び乾式のサンプルを含んだ基板の一部である。サンプルは、走査構造の導光部分により基板に伝達された複数の波長のうちのある波長が吸収された領域あるいは、基板（蛍光や化学ルミネセンスのような）により受光した光とは異なる波長の光を発生する。従って、基板上の光励起可能領域で「発生」した第2の波長は、光源により供給されていない波長であってもよく、光源から伝達されて、サンプルや基板により反射又は回折するものの光励起可能領域における基板やサンプルには吸収されていない波長であってもよい。このように、走査構造は、光を検出するか、あるいは、光においてある波長が欠落していることを検出するように、構成されうる。

【0012】

走査装置の空間解像度は、励起光のエネルギーを伝達するファイバのコアの径にほぼ等しいので、好適なコア径は、 $5\mu\text{m}$ 、 $10\mu\text{m}$ の空間解像度の走査装置に対して、それぞれ $5\mu\text{m}$ 、 $10\mu\text{m}$ となる。このようなコア径は、通信ファイバで容易に入手可能である。ファイバ先端でコアのサイズを小さくする必要はない。

【0013】

開示される本走査装置は、通常の正方形又は長方形の基板上のマイクロアレイの他にも、CDのように回転する基板を読み取ること、及び1次元のマイクロアレイにも適用可能である。

【0014】

開示される本発明は、マイクロアレイに加え、高いスループットでスクリーニングするこ

との用途において、顕微鏡的リアクションウェルのアレイを読むことにさらに適用可能である。

#### 【0015】

現在のところ、HTSからの出力信号は、蛍光、化学ルミネセンス、あるいは吸光度であってもよく、これらは、「マイクロプレート・リーダー」と称する装置を用いて検出される。本発明は、現在のDNAマイクロアレイと同等のサイズ及び密度（例えば、約500ウェル/cm<sup>2</sup>よりも高密度、好ましくは約1000ウェル/cm<sup>2</sup>よりも高密度、より好ましくは約2000ウェル/cm<sup>2</sup>よりも高密度、さらに好ましくは約5000ウェル/cm<sup>2</sup>よりも高密度）のマイクロウェルアレイ内の溶液からのこのような信号を読み取る走査装置に関する。マイクロウェルの内径は、約100マイクロメートルから約1000マイクロメートルであり、好ましくは約500マイクロメートル未満であり、より好ましくは200マイクロメートル未満である。ある特定の実施形態では、本発明の光ファイバ走査装置は、マイクロウェル内の溶液からの信号の読取装置に適用されている。例えば、光ファイバが基板となす角度は、垂直であってもよく、反射を防ぎながらも光が存在するかどうかを検出できるような垂直に近い角度であってもよい。ファイバ径は、マイクロウェルの径に基づいて選択されてもよい。走査前に読取装置が待機する時間は、サンプル及びプローブ（例えば、オリゴヌクレオチド、タンパク質、又は反応物）にサンプルと会合又は反応させるのに必要な反応又は会合時間に基づいて選択されてもよい。光ファイバによって読取装置が、スクリーニングシステムに統合可能となる柔軟性が提供される。

#### 【0016】

##### 〔発明の詳細な説明〕

本発明では、多くの基本的な光学部材が、励起光を伝達することに、あるいは蛍光の放出を受光することにも、用いられてもよい。このような光学部材として、導光ロッド及び光ファイバのような部材が、含まれていてもよい。光学部材として光ファイバを用いることが好ましく、以下に開示する実施形態では、このような光ファイバを例として用いることが考察される。しかしながら、本発明はこれに限定されるものではない。

#### 【0017】

図1（a）に、本発明の一実施形態としての走査構造10が、図示されている。この図において、レーザ14から射出された励起レーザ光20は、光ファイバ12の基端28に入る前に、フィルタ16により反射される。光ファイバ12は、励起光20を導いて、当該光ファイバ12の先端26から、マイクロアレイ・サンプル30上の例えばDNAプローブ等のサンプルを照射する。マイクロアレイ・サンプル30は、上述の如く、基板32及びプローブ34から構成されていてもよい。フィルタ16は、光の予め選択した波長又は帯域を反射しつつ、同時に、反射光における所望の波長又は帯域を通過できるように、選択的に設計されていてもよい。プローブ34から発せられた蛍光20'は、同ファイバ12により受光され、フィルタ16を通過した後、検出器18へ導かれる。本実施形態10における励起光20及び蛍光20'は、フィルタ16によって分離される。フィルタ16は、所定の波長の光を反射させる一方で、特定の波長を透過可能としている。図1（a）に示された特定の実施形態では、フィルタ16が、励起光20を反射するように設計されていてもよい。また、図1（a）におけるレーザ14と検出器18の位置を交換することにより、このシステムに、蛍光を反射するフィルタが用いられてもよい。

#### 【0018】

図1（b）には、同システム設計の代替的な実施形態22が図示されている。ここでは、かさばっていた光ビーム分割及び結合構造が、光ファイバカップラ24で置き換えられている。この記述の全体に亘り、別々の実施形態における構造で同一の番号が付されたものは、その機能が類似している。また、カップラ24は、特定の波長を他の分岐ファイバへと選択的に結合する波長多重（WDM: wavelength domain multiplexer）であってもよい。好ましくは、励起光を遮断するために、検出器18の前に、追加のフィルタ16が配置されてもよい。

#### 【0019】

さらなる他の実施形態では、レーザの代わりに、励起光20の光源として発光ダイオード(LED)が用いられる。単一のLED、又は複数のLEDで各LEDが別々の波長の光を発するものを、基板32に直に近接して配置してもよい。このようにしても、光ファイバ12が蛍光20<sup>\*</sup>を集光可能であり、光ファイバの基端28にあるレーザ14を置換可能である。

#### 【0020】

図2に示すように、光ファイバの先端26から出射する光36は、ファイバの開口数(NA)で規定される固有の角度で発散する。光ビームがファイバで導かれるために、光ビームは、以下の両条件を満たさなければならない。1) 光ビームは、ファイバの開口数で規定されるコアの領域に入射すること、そして、2) 光ビームは、ファイバの軸に対して、NAよりも小さい角度をなしていること。例えば、矢で示された光ビーム38は、上記の両条件を満たしているため、コア領域42に導かれる。しかし、光ビーム40は、上記条件の一方のみを満たしているだけなので、導かれることなく、コア領域42ではなくクラッド44に入射する。

#### 【0021】

図1の(a)及び(b)に図示された実施形態において、ビームの発散及び導光条件により、ファイバのコアに非常に近い領域へ発せられた光が集光される。ファイバの集光能力は、2つの要素で規定される。すなわち、1) コアのサイズ、及び2) NAである。これら2つのパラメータが大きくなるほど、ファイバ12の集光能力が高くなる。しかしながら、コアのサイズが大きくなると、システムの空間解像度が低下するおそれがある。ファイバ先端12と基板32との間隔が $d_c/2NA$ 以内であれば、空間解像度は、ファイバのコアのサイズにほぼ等しい。ここで、 $d_c$ は、ファイバのコア42の直径とする。基板32がファイバ先端12から $d_c/2NA$ の間隔より大きく離れていれば、蛍光を受光する効率が著しく低下する。標準的な通信ファイバは、そのコア径が約 $9\mu m$ であり、 $NA=0.12$ である。従って、本発明の走査構造を構成するのに標準的な通信ファイバが用いられると、基板表面がファイバ端面27から $38\mu m$ 以内に保たれていれば、約 $10\mu m$ の空間解像度が達成可能となる。 $NA$ が0.66のファイバが報告されている。ファイバ端面27を基板の約 $7\mu m$ 以内に保つことにより、集光能力を約2.7倍に引き上げる可能性が存在する。

#### 【0022】

ファイバ12を基板32に近接させておくように、いくつかの方法を用いる。

#### 【0023】

本発明の走査構造の第1実施形態では、ファイバ先端12と基板32表面との間隔がリアルタイムで検出され、この間隔が能動的に制御される。間隔の大きさは、干渉計を用いた光学干渉のような通常の方法で検出され、干渉計から取得した信号に応答して動作する例えば圧電アクチュエータ(米国特許第6,142,444号記載のようなもの)に、光ファイバを取り付けることにより、制御される。

#### 【0024】

本発明の第2の走査構造は、基板近傍でファイバ先端が高速動作することにより発生するエアクッション上に、マイクロアレイ基板32全体に亘ってファイバ12の先端を空気力学的に「浮ばせる」ことができるように、構成されている。これは、例えば、フロッピーディスクドライブ(TM)、ハードドライブ、及びCD-ROMドライブに使用されている技術である。フロッピーディスクドライブ(TM)の読取ヘッドは、厚さが2マイクロメートルのエアギャップで浮遊する。エアギャップは、回転するフロッピーディスク(TM)及び読取ヘッド間に発生したいわゆる「地面効果」により空気力学的に形成される。読取ヘッドとフロッピーディスク(TM)との相対動作により、真空が形成されて読取ヘッドがフロッピーディスク(TM)表面へ引き付けられる。しかし、読取ヘッドが表面に近接してゆくと、読取ヘッド及び表面間のギャップにおいて圧力が充分に増大し、読取ヘッドはディスク表面に接触しない。

#### 【0025】



この「地面効果」が、本発明の走査装置に適用されてもよい。ファイバ先端が基板表面において十分に早く動作して、ファイバ及び基板間の相対動作により、ファイバ先端は、基板表面の数マイクロメータ以内に引き付けられる。図3に示すように、ファイバ先端は、読取ヘッド50内に収容されていてよい。読取ヘッド50は、基板32とともにベンチュリを形成するような形状を有しており、それにより気流に地面効果を発生させる。以下に詳述するように、読取ヘッドは、1本の光ファイバが、該ファイバを基板表面全体に亘って移動するホルダに取り付けられたものであってもよく、あるいは、読取ヘッドは、光ファイバの束がホルダに取り付けられたものであってもよい。図3に示すように、読取ヘッドにおける基板に対向した表面は、側面から見てパラボラ状の形状を有していてもよい。あるいは、図1や図2に示すように、読取ヘッドは、平坦な表面を有していてもよい。読取ヘッドすなわちファイバ先端が、反対方向へ移動する際に、方向を変えるために減速してマイクロアレイを走査するので、速度が地面効果を得るのに必要な速度より小さければ、読取ヘッドやファイバ先端が、基板又は基板のホルダの一部に接触するおそれがある。

#### 【0026】

磁気及び空気力学的浮揚を併用した走査構造46では、読取ヘッドやファイバ先端が走査中に方向を変えるために減速する時に、読取ヘッドやファイバ先端が基板や基板ホルダに接触するのを、防止することができる。図3に示すように、走査構造46のマイクロアレイ基板32は、極性の方向が同じの一対の磁石48で支持されている。光ファイバが組み込まれた読取ヘッド50は、永久磁石が組み込まれて形成されるか、あるいは、それ自体が磁化されて（磁性材料で形成される場合）、その極性が支持磁石48の対と同じになっており、読取ヘッド及び磁石48間で斥力が発生する。基板32の中央の位置1では、読取ヘッド50は、比較的速く動作し、空気力学的に浮揚する。読取ヘッド50は、基板32の端へと位置2から位置3へ移動するにつれて、おそくなってゆく。おそくなると、空気力学的な浮揚力が減少するが、読取ヘッド50は、磁気支持部48からの磁力により支持され、当該読取ヘッドがマイクロアレイ基板32や磁石48に接触しないように浮揚した状態が保たれる。

#### 【0027】

本発明の走査構造の第3の実施形態は、特に、表面が粗い基板上のマイクロアレイのラベルを励起して検出するのに適している。但し、その用途は、表面の粗い基板上のマイクロアレイに限定されるものではない。図4に示す走査構造52では、読取ヘッド50を一定な状態で空気力学的に浮揚させておくために、光ファイバ56間に毛管54が組み込まれていてもよい。複数本のファイバが用いられる場合には、それらは、任意に束ねられるか、あるいは、高速又は冗長性を持たせてマイクロアレイを走査できるように、周知の空間配列で連続的に又は規則正しい配列に束ねられる。毛管ファイバ54を通じて、気体を下方へ吹きつけることにより、極めて薄い気体クッション58が、読取ヘッド50及び基板32間に形成される。空気や窒素のような不活性な気体であれば、何でも使用可能である。ファイバ方式の読取ヘッド50は極めて軽いため、読取ヘッド50を基板32上に浮揚させて、両者を数マイクロメータのオーダの小さな間隔に保つのに、小さな正の圧力で充分なはずである。正の圧力の大きさは、読取ヘッド50の個々の設計に依存する。

#### 【0028】

信号対雑音比の向上、複数波長での励起及び受光、並びに走査機構といったいくつかの特徴について、以下、考察する。

#### 【0029】

〔信号対雑音比の向上〕

ファイバ12の長さ方向の軸が、基板32の表面に対して実質的に垂直であると、元の励起光20のうちのある部分は、ファイバ12の端面27を出て基板32で反射され、そして、ファイバ12へと戻ってくる。これにより、信号中にバックグラウンドノイズが生じる。図1の(a)及び(b)に示すように、このバックグラウンドノイズは、システム中のフィルタ16により抑制しうる。フィルタ16は、それがなければ検出器18が検出し

てしまう望ましくない波長の光を反射することにより、バックグラウンドノイズを抑制するように作用する。しかしながら、発せられた蛍光が比較的小さいために、フィルタが抑制するにもかかわらず、かなりのレベルのノイズがなおも存在するおそれがある。より高い信号対雑音比 (SN比) を有する走査構造では、基板32の表面に対して角度 $\theta$ で傾いたファイバ12が、含まれている。この角度は、図1及び図5に示すように、ファイバ12のNAよりもわずかに大きい。この構成により、反射された励起光は、光ファイバで検出器へと導かれるのではなく、ファイバの壁面を透過するようになる。

#### 【0030】

SN比がより高い走査構造の代替的な実施形態には、基板32の表面と実質的に平行に端面27が研磨されたファイバ12が、含まれている。このように研磨すると、全ての光 (励起光20を含む) が、直接、ファイバ端面27及びマイクロアレイ基板32で反射され、ファイバ12の軸とNAより大きい角度で交差するので、この光がファイバコア42を通じて検出器18へ導かれることがない。一方、蛍光20'は、あらゆる方向へ発せられ、端面が研磨されていないファイバに受光されるのと同じ割合の光20'が、その信号レベルを変化させずにファイバ12に受光される。その結果、システムのSN比は、著しく向上する。

#### 【0031】

SN比が向上した他の走査構造には、ダブルコアファイバ60が用いられている。図5に示すように、ダブルコアファイバ60は、2つの同軸のコア62、64を有し、コア62の屈折率は、コア64の屈折率よりも大きくなっている。ダブルコアファイバ60の相対屈折率の縦断面図を、図5に示す。この図において、ピーク70は、インナーコア62の相対屈折率に相当し、ピーク72は、アウターコア64の相対屈折率に相当し、ピーク74は、ファイバ60のクラッドの相対屈折率に相当する。

#### 【0032】

ダブルコアファイバ60を備えた走査構造は、レーザからの光をインナーコア62を通じて伝達する一方、基板からアウターコア64へ入射した光については、100%に近い結合比 (coupling ratio) を有する。このように、ダブルコアファイバは、コアセレクトティブカプラ (core-selective coupler) として機能する。

#### 【0033】

アウターコア64は、インナーコア62よりも低い屈折率を有するので、インナーコア62に対してクラッドのように機能する。従って、ダブルコアファイバが図1の (b) のシステムに用いられると、例えばレーザから発せられた励起光20は、臨界角より小さな角度でインナーコア62に入射し、励起光は、実質的に、インナーコア62内に閉じ込められる。

#### 【0034】

アウターコア64内の光は、このダブルコアファイバにより外側に結合されることになる。インナーコア62の臨界角より大きな角度でアウターコア64に入射した光は、インナーコア62へと内部反射することがないので、主にアウターコア64で見い出され、インナーコア62には実質的にレーザからの光だけに任せられた状態となる。

#### 【0035】

さらに、インナーコア62は、該インナーコア62から出射した後の光ビーム68の発散が小さくなるように、小さなNAを有していてもよい。一方、発せられた蛍光66の大部分は、アウターコア64に入射して、ファイバ60を遡って検出器へと伝達する。このような方法で、集光効率が著しく向上し、そのために、SN比が向上することになる。さらに、アウターコア64は、インナーコア62よりもはるかに大径に形成可能であるため、集光された光の強度は、ファイバ12の端面27と基板32との間隔に決定的に依存するということがより少なくなる。このため、機器設計の許容度及び自由度がより高くなる。

#### 【0036】

ダブルコアファイバ60を製造する一方法として、化学気相成長法 (CVD) がある。こ

れによると、例えばシラン及び $O_2$ をともなった気体のGe等のドーパントを、通常のファイバ形成チューブ（プリフォーム）の内面に第1の濃度で蒸着させ、層を形成する。次に、ドーパント（第1の濃度のドーパントと同じか又は同様の通常のドーパントからなる）を、第1の濃度よりも高い第2の濃度で、前記層上にドーパしてもよい。その後、プリフォームを伸ばしてファイバ60を形成する。

#### 【0037】

##### 〔複数波長での励起及び受光〕

通常、本発明の走査構造は、少なくとも2つの別々の波長の光を伝達する。2つの波長の光とは、ある波長の励起光、及び、蛍光マーカから発せられた他の波長の蛍光である。現在知られている技術として、5つまでの別々の励起及び／又は受光波長を有する走査装置がある。現状のマイクロアレイ走査装置では、波長の異なる全ての光ビームが、顕微鏡の対物レンズに通じた単一の光路に集約される。通常の走査装置で用いられている複数の大きな光学コンポーネントには、これらの大きな光学コンポーネントの運搬及び移動させるために、高精度のアライメント及び複雑な構成が必要とされる。高精度で大きな光学コンポーネントにより、現行の走査装置はかさばって高価なものとなっている。さらに、集約された光路を有する現行の光学検出器では、ある波長を他のものから分離することが、困難であることが多い。2つ以上のレーザが同時に稼動しているときには、SN比が悪化する。現行の多くのマイクロアレイ走査装置では、走査速度を大幅に低下させてしまうという犠牲を払いながら、一度に一つのレーザに切り替えることにより、この問題の発生を防止している。

#### 【0038】

図6に、本発明の走査構造76を示す。ここでは、複数の波長に対応した複数の光源 $14_{\lambda_1} \sim 14_{\lambda_n}$ が、波長多重（WDM）78<sub>1</sub>、78<sub>n</sub>を用いて、単一の光ファイバ12に集約されている。この走査構造は単純である。これは、特に、現行の走査装置で現在使用されている例えばレンズ及びミラーアセンブリのための複雑な支持構造を必要としない光ファイバ12の柔軟性によるものである。WDM78<sub>1</sub>、78<sub>n</sub>は、例えば、プレーナ又は溶融型カプラの作製することにおいて電気通信業界で周知の技術を用いて、作製される。

#### 【0039】

本発明の一実施形態では、複数波長の光ビームが、マイクロアレイ基板32全体に亘って同時に走査されるが、これら光ビームは、正確に同じ位置にある必要はない。図7に、代替的な実施形態80を示す。これによると、1つの波長が、他の波長からより容易に、速度の犠牲を払うことなく分離されている。図7に示すように、各波長の光 $14_{\lambda_1} \sim 14_{\lambda_n}$ が、別々であっても比較的近接した位置を照射する一方、同期して走査することを可能にする応用例に応じていくつかの所望の構成に、光ファイバ12を配列してもよい。束になった光ファイバは、例えば、ファイバが挿入されてその順序を保つように束ねるガイドプレートを使用して、あるいは使用せずに、形成されてもよい。ここに言及された全ての論文、特許、及び特許出願は、その全体が一体に組み入れられる。光ファイバ12は、極めて軽量で、細く正確な直径なので、各波長毎に別々のファイバを用いて、同期したマルチスポット走査が実現する。ここで、個々のファイバ12がマイクロアレイ状に束ねられて、光ファイバ走査ヘッドを形成してもよい。このようなマイクロアレイは、規則的な配列又はランダムなバンドルとなるように、束ねられてもよい。バンドル中のファイバの本数は任意であるが、多くの例で、その本数は10よりも少ない。システムにおける各ファイバの先端の相対位置が既知となるため、どちらの変形例も実現可能である。ファイバ端が極めて近接しているにもかかわらず、全てのファイバ12が、同一のスポットを照射するように集束される必要はない。但し、そのようになされても、さしつかえない。逆に、各光ファイバ12は、別々のスポットを同時に照射し、必要に応じて各スポットから同時に蛍光を集光するように、配列されてもよい。

#### 【0040】

##### 〔走査機構〕

光ファイバ12は、極めて軽いので、上記の走査ヘッド50は、非常に高速に移動し、それにより、マイクロアレイを読み取る速度が増大する。図8に、走査装置82の実施形態を示す。ここでは、光ファイバ12の読取ヘッド50が、通常のガルバノスキャナ (Galvano scanner) 84によりY方向に往復移動する。ガルバノスキャナ84は、光ファイバ12及び読取ヘッド50を保持した懸架ビーム (suspension beam) 86を、所望の角度 $\alpha$ に亘って、基板32の幾何学的構成に応じた所望の周波数で、移動させるように設定されている。走査装置は、Xステージ位置決め機構を備えていてもよい。Xステージ位置決め機構は、基板を読取ヘッドの下側を移動させるとともに、光ファイバ12がX軸上のどの位置を読み取っているのかを確定する情報を提供する。光ファイバ12のY軸上の位置は、ガルバノスキャナ84に組み込まれた角度エンコーダにより検出される。ガルバノスキャナ84が懸架ビーム86をY方向に移動させると、基板32は、通常の移動ステージ88によりX方向に段階的に移動する。

#### 【0041】

図9に、走査装置90の代替的な実施形態を示す。この実施形態では、ガルバノスキャナ84及び懸架ビーム86が、共振アクティベータ92及び共振懸架ビーム94に置き換えられている。ここでは、光ファイバ読取ヘッド50は、共振懸架ビーム94がその共振周波数で共振アクティベータにより駆動されることにより、Y方向に往復するように振動する。共振懸架ビーム94近傍に配置された圧電素子のような任意個数の通常の共振アクティベータ92装置により、あるいは、共振懸架ビーム94の両側に配置された磁気素子により駆動されて、共振が発生する。どちらの実施形態であっても、読取ヘッド50は、基板32の端部又は外側で止まるように設定される。基板32の端部や外側には、プローブが存在していない。読取ヘッド50及び基板32間の接触（それにより汚染を防止）は、基板32上に読取ヘッド50を浮揚させるのに用いた空気力学的浮揚機構を実装すること等による通常の、あるいは、上述のいくつかの方法により、防止される。

#### 【0042】

図8及び図9に示す個々の実施形態では、走査ヘッド50は、Y方向における湾曲した経路を通る。このことは、未処理のデータにおける画像の画素が、ほとんどの画像ファイルのような矩形の格子状になっていないことを意味する。しかしながら、各画素の正確な位置が登録されているかぎり、この走査装置で生成される画像ファイルは、通常のソフトウェアによって標準的な画像ファイルに変換可能である。どちらの実施形態においても、X位置は、移動ステージ88の通常的位置エンコーダにより記録されてもよい。図8に示す実施形態では、Y位置は、ガルバノスキャナ84が角度 $\alpha$ に亘って掃引することにより生じる角変位から算出されてもよい。図9に示す実施形態では、Y位置は、いくつかの異なった方法のうちの任意のものにより、算出されてもよい。1つの方法として、共振懸架ビーム94の両側表面上の既知の位置における変形歪力を、通常の歪ゲージを用いることにより測定して記録する方法がある。2番目の方法では、新規の光学方式位置測定装置が用いられる。これについては後ほど詳述する。この方法は、このような測定の目的に適合したものである。第3の方法として、共振周期をリアルタイムで測定し、経時的な振動の両極値間の読取ヘッド50の位置を算出する方法がある。

#### 【0043】

図10 (a) 乃至図10 (c) には、CCDアレイ及び光ファイバビーコンが組み込まれた単純な位置検出装置96の代替的な実施形態が示されている。この実施形態は、スライドする大きさおよび移動速度が多様であったとしても、実施可能である。

#### 【0044】

図10 (a) 乃至図10 (c) に示すように、光ファイバ98、100が、移動ステージ106の移動部分に、ビーコンとして実装されている。固定ステージ104は、移動ステージ106とは異なり、静止している。その代わりに、ステージ104が動いて、ステージ106が固定されていてもよい。第1のビーコン98は最も明るく、第2のビーコンはより暗くというようになっている。また、リニアCCDアレイ102が、ステージの固定部分104又はステージの移動部分106に実装されていてもよい。近接した2つのビー

コン98, 100の間隔は、リニアCCDアレイ102よりもわずかに短い。移動開始時に、リニアCCDアレイ102は、そのピクセルアレイの一端において、単一の明るいスポットを検出する。図10の(a)に示すように、このスポットの位置は、移動ステージ106の相対位置を示している。図10の(b)、図10の(c)に順に示すように、ステージ106が移動してゆきながら第1のビーコン98がリニアCCD102の範囲を越える手前で、このスポットがリニアCCDの他端へ移動してゆくと、第2のビーコン100が移動してきて、位置監視が継続される。全範囲に亘る移動ステージ106の位置を絶対位置で監視可能とするのに必要であれば、ビーコンは、いくつ用いられてもよい。

【0045】

CCDの長さと比較したビーコンの分離間隔の一例として、ピクセルアレイに沿ったスポットの正確な位置は、中心軌跡アルゴリズム(centroid algorithm)を用いて、少なくともピクセルのピッチの約 $1/50$ まで算出されてもよい。例えば、通常の2048ピクセルでピッチが $24\mu\text{m}$ の代表的で安価なCCDアレイ102を考慮すると、リニアCCDアレイ102の有効な長さは、約49mmである。2つのファイバビーコンを例えば約40mm間隔で実装すると、位置検出装置96は、移動ステージ106の位置を、約80mmの範囲に亘って $0.48\mu\text{m}$ の解像度で監視可能となる。これは、マイクロアレイ走査装置のためには、充分過ぎるものである。

【0046】

図11に示すように、位置検出装置96は、1次元のマイクロアレイ108の実施形態に用いられてもよい。ここで、特許出願中の米国特許出願番号60/244,418(名称「Gene Thread」, 発明者: Shiping Chen, Yuling Luo, and Anthony Chen, 出願日: 2000年10月30日)に記述されているように、1次元のマイクロアレイ108は、移動ステージ106上に位置していてもよい。この米国特許出願番号60/244,418は、その全てがここに一体に組み入れられる。1次元のマイクロアレイ108上には、ハイブリッド化のためのサンプルが含まれた標準的なプローブ110が配列されていてもよい。その代わりに、プローブは、所望の応用例に応じた様々な構成で配置されてもよい。いくつかの例として、プローブは、直線状112にあるいは斜め114に配置されてもよい。どのような場合であっても、プローブの位置は、上述の方法及び装置のいずれかを用いて、監視され読み取られる。

【0047】

その代わりに、本発明の走査装置の一実施形態では、1次元のマイクロアレイ108が当該読取ヘッド50の下側を移動する一方で、読取ヘッド50は、固定された状態で、走査可能となってもよい。これにより、1次元だけのプローブ110がステージ106上で一方向に移動しているため、読取ヘッドを振動させる必要がなくなる。

【0048】

また、位置検出装置96を調整するのに、ビーコン98, 100をその相対的なピーク強度で識別するシステムが用いられてもよい。図10の(a)乃至図10の(c)に示すように、CCDアレイは、該アレイ上の位置の関数になった相対的な信号強度を出力する。所与の信号強度が、所与のビーコンに対応している。例えば、第1のビーコン98は、最も明るいビーコンであるため、最も明るい信号98<sup>+</sup>に対応し、第2のビーコン100は、第1のビーコン98よりも暗いビーコンであり、より暗い信号100<sup>+</sup>に対応し、以下同様である。従って、CCDアレイからの出力は、ビーコンをその相対強度で監視することにも用いられうる。その代わりに、スポットの大きさやビーコンにおけるファイバの本数により、個々のビーコンが識別されてもよい。例えば、第1のビーコン98が、一本のファイバを備えていて、CCD上に単一のスポットを形成し、第2のビーコン100が、近接配置された2つの光ファイバを備えていて、近接した2つのスポットを形成するといふようにである。なお、第2のビーコン100の2つのファイバは、第1のビーコン98と第2のビーコン100との間隔に比べて、極めて小さな間隔で互いに離れていてもよい。例えば、隣接した第1及び第2のビーコン98, 100が40mm離れていて、第2のビーコン100の2つのファイバが0.1mmといった小さな間隔で離れていてもよい。

## 【 0 0 4 9 】

さらに、X方向における必要な走査範囲が約30mmよりも小さい場合に、単一のビーコンが、CCDアレイ又はアナログ位置検出装置とともに用いられてもよい。例えば、アナログ位置検出装置は、ストリップ上の光のスポット位置に比例した2端子における差動電圧出力が得られる連続フォトレジスタ・ストリップであってもよい。

## 【 0 0 5 0 】

図12に、回転位置検出機構116を備えた走査装置の実施形態を示す。ここでは、マイクロアレイは、回転する基板122上に形成されている。基板122は、上記の特許出願中の米国特許出願番号60/244,418に記載されているように、CD-ROMディスクに類似した形状を有している。本実施形態では、マイクロアレイ基板122は、回転ステージ120により連続的に回転し、その一方で、1つの光学読取ヘッド118又は複数のヘッドが段階的に径方向へ移動して、マイクロアレイ基板122表面の全体を走査してもよい。この設計の利点は、成熟したCD-ROM設計及び製造能力による多くの利点だが、システムコストを削減可能とすることにある。基板が連続的に高速で回転しうるので、通常の読取機構によるよりも高速の読取速度が達成可能である。走査装置の本実施形態には、上述のように、基板122における光学又は磁気マークが組み込まれてもよい。これにより、読取ヘッドの位置が指示されるようになる。

## 【 0 0 5 1 】

走査装置には、上述のような光ファイバを有する読取ヘッド118の他にも、コンパクトディスク(CD)リーダに見られるものに似た大きな光学レンズに基づく読取ヘッドが組み込まれてもよい。このように構成されることにより、現行のCD-ROMドライブの成熟した技術の利点が存分に活かされう。

## 【 0 0 5 2 】

マイクロアレイ走査装置が高いスループットの読取装置として用いられている場合、このシステムにおけるマイクロアレイ基板は、マイクロ反応ウェル(micro reaction well)に置き換えられてもよい。マイクロ反応ウェルは、流体で満たされている。全ての型のマイクロアレイ走査装置が、この用途に適合可能であろう。特に、開示されている発明がこの用途に用いられた場合、光ファイバは、励起光のエネルギーをウェルに導き、発せられた光を同時に集光する。ウェルアレイは、一方向に移動してもよい。この際、読取ヘッドは、他の方向へ移動する。走査を完全なものにするため、通常、当該他の方向は直交方向である。一方、アレイが固定されていて、読取ヘッドにより両方向への走査運動が得られてもよい。読取ヘッドは、開示されている発明では光ファイバ式であるため、光源から独立して移動可能である。このことにより、コンパクトで経済的な構造設計を実現するための自由度が追加される。

## 【 0 0 5 3 】

本発明のどの実施形態においても、走査構造は、基板上の乾式領域又は湿式領域からの光を受光できるように構成されている。本発明のある好適な実施形態では、当該領域の直径は、約10マイクロメートル乃至約500マイクロメートルである。他の好適な実施形態では、当該領域は、直径が約100乃至1000マイクロメートルのマイクロウェルである。通常、当該領域は既知のスポット形成技術により形成され、また、ウェル内の液体は断面が円形であるため、当該領域は、直径を有するものとして記述されているが、円形の形状に限定されるものではない。

## 【 0 0 5 4 】

走査構造は、特定のサイズのいくつかの方式の領域からの第2の波長の光を受光するように、構成されう。例えば、ファイバ又はロッドは、この領域からの光を読み取るのに適した直径になっている。(すなわち、ファイバ又はロッドが所与の領域からの信号を読み取っている時にはいつでも2以上の領域からはみ出すほどには、この直径は大きくない。)検出器は、既知の技術によりタイミングが調節され、読み取られるべき領域を横切る走査構造の導光部分に対応した、所与の時刻及び/又は所与の位置で信号を読み取る。走査速度は、アレイ密度に対応させて変更されてもよい。また、これらの技術の任意のものが

組み合わせられて、用いられてもよい。

【0055】

基板の光に反応する領域は乾式であっても湿式であってもよい。遺伝子又はタンパク質のマイクロアレイは、マイクロウェルが反応や会合 (association) の生成物を含むことがある (高いスループットの薬品のスクリーニングで発生するように) ので、走査装置を使って読み取られてもよい。このようなマイクロアレイとしては、WO99/55460、WO99/55461、EP0955084、WO00/53736、WO00/53739、2001年1月10日出願の米国特許出願番号09/758,873、2001年2月22日出願の米国特許出願番号09/791,998、2001年2月22日出願の米国特許出願番号09/791,410、及び2001年2月22日出願の米国特許出願番号09/791,411 (これらのうち最後の4件は、本出願人による発明) に、記述されているものがある。これらの全てがここに一体に組み入れられる。

【0056】

本発明の走査構造は、上述したような高いスループットのために構成された基板と組み合わせられて用いられてもよい。この走査構造は、光源及び検出器を備えている。基板は、光源からの光を受光し、検出器は、基板からの光を受光して、1つ又はそれ以上の波長の光が存在するかどうかを検出する。オリゴヌクレオチドを含んだマイクロアレイ上のハイブリッド化を検出するのに用いられる他の走査装置が、同様に使用されてもよい。このようなマイクロアレイは、上述の背景の部分で考察されている。例えば、これらのマイクロアレイには、液体サンプルの処理のために、1平方センチメートル当たり少なくとも100、400、又は1000のマイクロウェルが含まれている。

【0057】

本発明は、特定の実施形態を参照して記述されているが、この記述は、本発明の適用例に過ぎず、これにより何らの制限がなされるものではない。様々な改良及び開示された実施形態の特徴の組み合わせが、通常の技術を有する者に今や明らかとなり、これらは、本発明の範囲に属するものである。ここに考察又は言及された全ての参考文献は、その全体が一体に組み入れられる。

【図面の簡単な説明】

【図1】 (a) 及び (b) はプローブ・マイクロアレイを走査するために用いられる本発明の実施形態を示す図である。

【図2】 光ファイバがその先端面のコアの部分に極めて近接した領域を励起し、照射された領域の一部からの光が同ファイバに受光されうことを示す図である。

【図3】 読取ヘッド支持用に磁氣的及び空気力学的浮揚を組み合わせた実施形態を示す図である。

【図4】 読取ヘッド支持用に薄い気体クッションを発生させるための実施形態を示す図である。

【図5】 一様でない屈折率のダブルコア光ファイバを示す図である。

【図6】 複数の異なった波長を単一の光路にまとめた走査装置の実施形態を示す図である。

【図7】 異なった波長の個々のファイバを束ねるか近接させて構成した走査装置の実施形態を示す図である。

【図8】 ガルバノスキャナを利用した走査装置の実施形態の側面図及び平面図である。


【図9】 共振懸架ビームを利用した走査装置の実施形態の側面図及び平面図である。

【図10】 移動ステージの固定ステージに対する移動、及び強度の異なる複数のビーコンを用いてそれを測定することを示す図である。


【図11】 図10 (a)、図10 (b)、及び図10 (c) の移動ステージを利用した1次元のマイクロアレイ上に配置された様々な複数のプローブを示す図である。

【図12】 回転する基板を備えた走査装置の実施形態を示す図である。


【図1】




【図2】




【図3】




【図4】



【図8】



【図5】





【図9】




Fig. 9

【図10】




Fig. 10(c), 10(d), and 10(e)

【図12】




Fig. 12

## 【国際公開パンフレット】

## (12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
20 September 2001 (20.09.2001)

PCT

(10) International Publication Number  
WO 01/69302 A2

- (51) International Patent Classification: G02B 26/00 (81) Designated States (*optional*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GL, GM, HR, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (21) International Application Number: PCT/US01/08043
- (22) International Filing Date: 13 March 2001 (13.03.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 60/188,873 13 March 2000 (13.03.2000) US
- (71) Applicant (*for all designated States except US*): GENOSPECTRA, INC. [US/US]; 455-ND Reemont Blvd, Suite 506, Fremont, CA, 94538 (US).
- (72) Inventor: and
- (73) Inventor/Applicant (*for US only*): CHEN, Shuping [GB/US]; 13818 Cloosfoot Terrace, Rockville, MD 20850 (US).
- (74) Agent: HOLLAND, Charles, D. et al., Morrison & Foerster LLP, 755 Page Mill Road, Palo Alto, CA, 94304-1018 (US).
- (84) Designated States (*regional*): ARIP patent: (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent: (AK, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent: (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent: (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— *without international search report and to be republished upon receipt of that report*
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*



(54) Title: RUBBER OPTIC SCANNER

WO 01/69302 A2

(57) Abstract: The disclosed scanning structure includes an apparatus for light delivery and light receiving from a light-excitable area on a substrate to be measured by the scanning structure. The light delivery and receiving apparatus may include an optical fiber having a proximal end and a distal end which transmits light having a certain wavelength or light with several varying wavelengths to excite the substrate samples. This optical fiber may also simultaneously receive light which may be emitted by fluorescing samples on the substrate. The scanning structure also may further include a holder for the optical fiber that is able to transverse variable distances over the substrate to be measured or scanned. Holders may include galvanic scanners as well as resonating suspension beams. A light source, e.g., a laser, may be optically coupled to the optic fiber's proximal end. And this light source may be of a certain wavelength, but multiple light sources each having a different wavelength may also be used simultaneously by coupling the light sources into either a single optic fiber through wavelength multiplexers or by placing individual optic fibers carrying differing wavelengths in close proximity to each other. As the light is transmitted down to the substrate through the optic fiber, the fiber is sufficiently close to the substrate microarray so that it can also receive the emitted fluorescing light.

WO 01/69302

PCT/US01/08043

**FIBER OPTIC SCANNER****CROSS-REFERENCE TO RELATED APPLICATIONS**

This application claims the benefit of U.S. provisional application  
60/188,873 filed Mar. 13, 2000 which is incorporated herein by reference in its  
entirety.

**TECHNICAL FIELD**

The invention relates to equipment and methods for scanning microarrays  
or microwells in a microplate, such as DNA microarrays, protein microarrays, and  
compound microarrays.

**BACKGROUND**

A microarray is an array of spots of biological or chemical samples  
("probes") immobilized at predefined positions on a substrate. Each spot contains  
a number of molecules of a single biological material or chemical. The microarray  
is flooded with a fluid containing one or more biological or chemical samples (the  
"target"), which typically interact with one or more complementary probes on the  
microarray. In DNA microarrays in particular, the probes are oligonucleotide or  
cDNA strains, and the target is a fluorescent or radioactive-labeled DNA sample.  
The molecular strands in the target hybridize with complementary strands in the  
probe microarray.

The hybridized microarray is inspected by a microarray reader, which  
detects the presence of the radioactive label or which stimulates the fluorescent  
label to emit light by exciting the label using a laser or other energy source. The  
reader detects the position and strength of the label emission in the microarray.  
Since the probes are placed in predetermined and thus known positions in the  
microarray, target sequences in the fluid are identified by the position at which  
fluorescence or radiation is detected and the strength of the fluorescence or  
radiation.

WO 01/69302

PCT/US01/08043

A microarray reader is therefore one of the key pieces of equipment in microarray technology. Currently, there are two types of microarray readers available. The first type, an example of which is depicted in U.S. Pat. No. 5,324,633, is based on scanning microscope principles, where laser beams at two or more wavelengths are combined and focused on a single spot on the microarray to excite the fluorescent labels. The combined laser beam scans across the entire microarray point-by-point at a high spatial resolution ( $\sim 10 \mu\text{m}$ ) by either carrying the microarray on a two-axis translation stage, or moving the microscope lens in one axis and the microarray substrate on the other. The second type, an example of which is illustrated in WO00/12759, uses a CCD imager to detect the fluorescent emission from the microarray one small region at a time. A broadband light source, such as an arc lamp, is used to excite fluorescence.

For scanning microscope technology, the cost driver is its optical system, as it has to combine and precisely align multiple laser beams at different wavelengths and later re-split them into separate detection channels. Both the microscope lens and the slide carrier are bulky and heavy and cannot be moved very fast, which limits scanning speed.

In the CCD based system, the imager and lens are both the main cost drivers. Here, the excitation light is expanded to a large area causing a great reduction in energy density. The exposure time has to be extended several tens of seconds to compensate for this reduction. Because of the long exposure time, the CCD imager has to be cooled to maintain a reasonable signal to noise ratio. Such a cooled, large format CCD imager is very expensive at present. In addition, the optical lens in the system has to be corrected for chromatic aberrations and image distortions over a large field of view, which significantly increases its cost in comparison to the lens in the point-to-point system in a scanning microscope. Furthermore, there is currently no CCD imager with sufficient resolution and format to cover the entire area of a slide (25 mm x 75 mm). Mechanical scanning is still required for CCD based systems, which reduces the speed of the reader. At present, most microarray readers on the market require 5 minutes or more to

WO 01/69302

PCT/US01/08043

complete the scanning of a 25 mm x 70 mm slide, which is too slow for many applications.

Optical fibers have been used in near field scanner microscopy (D.W. Pohl, "Scanning near-field optical microscopy" in *Advances in Optical and Electron Microscopy* 12, C.J.R. Sheppard and T. Malvey, Eds. (Academic Press, London, 1990); M.H.P. Moers, W.H.J. Kalle, A.G.T. Ruiter, J.C.A.G. Wiegant, A.K. Raap, J. Grove, B.G. De Groot, N.F. van Hulst, *J. Microscopy* 182, p. 40, (1996)), where light energy is guided to a fiber tip reduced to sub-micron in diameter. The fiber tip is brought to within several tens of nanometer of the surface to be inspected. Then, the tip scans over a small area (normally within 10mm square) and collects the direct scattering light from the inspected surface. (Chuck, In the disclosed invention, the fiber core is much larger to maximize the light collection and the collected light is indirect emission, such as fluorescence from the object under inspection.)

On the other hand, optical fiber reader head has been use to collect fluorescent emission from microtiter plates in a number of instruments such as ABI's Taqman reader [US5 589 351]. Here the spatial resolution of the reader is in the order of several millimeters. The excitation and receiving lights travel through different fibers in a bundle. The optical head is kept at a relative large distance from the object.

#### SUMMARY

The invention provides a number of systems, components, means, and methods for scanning probe microarrays or samples (dry or liquid, as contained in microwells) as are more fully described below. This section of the disclosure provides a summary of some salient points of the invention, but this section is not to be interpreted as limiting the scope of the invention to only those features and embodiments discussed in this section. Instead, the invention involves all components, systems, and methods discussed in this and the following sections as well as the appended claims.

WO 01/69302

PCT/US01/08043

The disclosed scanning structure includes an apparatus for light delivery and light receiving from a light-excitable area on a substrate to be measured by the scanning structure. The light delivery and receiving apparatus may be comprised of an optical fiber having a proximal end and a distal end which transmits light having a certain wavelength or light with several varying wavelengths to illuminate the samples and excite light emission or have one or more of the wavelengths absorbed by the samples. This optical fiber may also simultaneously receive light which may be emitted by fluorescing samples on the substrate or light that has otherwise encountered the samples and been reflected or diffracted. The scanning structure also may further include a holder for the optical fiber that is able to traverse variable distances over the examined substrate. Examples of holders may include galvano scanners as well as resonating suspension beams. To generate the light which excites the substrate samples, a light source, e.g., a laser, may be optically coupled to the optic fiber's proximal end. Multiple light sources each having a different wavelength may be used simultaneously by coupling the light sources into either a single optic fiber through wavelength multiplexers or by placing individual optic fibers carrying differing wavelengths in close proximity to each other. As the light is transmitted down to the substrate through the optic fiber, the fiber is sufficiently close to the substrate microarray so that it can also receive the emitted fluorescing light.

Although certain embodiments of the invention are described as causing fluorescence, the invention also includes other forms of light generation such as chemiluminescence and light absorption so that an absorption spectrum is generated and transmitted by the light conducting portion (e.g. fiber or rod) of the scanning structure. Thus, a light excitable area on a substrate is a portion of the substrate containing a wet or dry sample that either generates light of a different wavelength than the light received by the substrate (such as by fluorescence or chemiluminescence) or an area that absorbs one wavelength of multiple wavelengths transmitted to the substrate by the light conduction portion of the scanning structure. Therefore, a second wavelength that is "generated" by the light excitable area on the substrate may be a wavelength that is not provided by

WO 01/69302

PCT/US01/08043

the light source or may be a wavelength that the light source transmits and is reflected or diffracted by the sample or substrate but the substrate or sample in the light-excitatable area does not absorb. Thus, a scanning structure can be configured to detect light or to detect the absence of a wavelength of light.

As the spatial resolution of the scanner equals approximately the diameter of the fiber core that transmits the excitation light energy, the preferred core diameter is therefore 5 $\mu$ m, 10 $\mu$ m for scanner with 5 $\mu$ m or 10 $\mu$ m spatial resolutions, respectively. Such core diameters are readily available in communication fibers. There is no need to reduce the core size at the fiber tip.

Aside from microarrays on traditional square or rectangular substrates, the disclosed scanner can be adapted to read a rotating substrate in the manner of a CD and one dimensional microarrays.

In addition to microarrays, the disclosed invention can further be adapted to read arrays of microscopic reaction wells in high throughput screening applications.

At present, the output signals of HTS, which could be fluorescence, chemiluminescence or absorbance are detected using a device referred as "microplate readers". This invention relates to a scanner that reads such signals from solutions in microwell arrays with size and density comparable to today's DNA microarrays (e.g., more than about 500 wells/cm<sup>2</sup>, preferably more than about 1,000 wells/cm<sup>2</sup>, more preferably more than about 2,000 wells/cm<sup>2</sup>, and even more preferably more than about 5,000 wells/cm<sup>2</sup>). The inner diameter of the microwell is from about 100 microns to about 1,000 microns, preferably no more than about 500 microns, and more preferably no more than about 200 microns. In a specific embodiment, the optical fiber scanner of this invention is adapted as a reader of signals from solutions in microwells. For instance, the angle that the optical fiber makes with the substrate may be vertical or near vertical to avoid reflection but also detect the presence or absence of light. The diameter of the fiber may be selected based on the diameter of the microwells. The length of time that the reader waits before scanning may be selected based on the reaction or association time needed for the sample and probe (oligonucleotide, protein, or

WO 01/69302

PCT/US01/08043

reactant, for instance) to associate or react with the sample. The optical fibers provide the flexibility that enables the reader to be integrated into the screening system.

5                    BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1(a) and 1(b) depict embodiments of the present invention used in scanning probe microarrays.

Figure 2 illustrates that an optical fiber excites an area very close to its core region in the distal end facet, and light from a portion of the illuminated area may be collected by the same fiber.

Figure 3 depicts an embodiment combining magnetic and aerodynamic levitation for read head support.

Figure 4 depicts an embodiment for generating a thin gas cushion for read head support.

Figure 5 depicts a double-core optical fiber having varying refractive indexes.

Figure 6 depicts a scanner embodiment for combining multiple different wavelengths into a single optical path.

Figure 7 depicts a scanner embodiment for bundling or closely configuring separate fibers having light of differing wavelengths.

Figure 8 depicts a side view and a top view of a scanner embodiment utilizing a galvano scanner.

Figure 9 depicts a side view and a top view of a scanner embodiment utilizing a resonating suspension beam.

Figures 10(a), 10(b), and 10(c) depict the progression and measurement of a translation stage relative in a stationary stage using beacons of varying strength.

Figure 11 depicts multiple varying probes disposed upon a one dimensional microarray utilizing the translation stage of Figures 10(a), 10(b), and 10(c).

Figure 12 depicts a scanner embodiment having a rotating substrate.



WO 01/69302

PCT/US01/08043

DETAILED DESCRIPTION OF THE INVENTION

In this invention, many basic optical elements for the delivery of excitation light and possibly also for the collection of the fluorescent emission may be used. Such optical elements may include devices such as light-guiding rods and optical fibers. It may be preferable to use optical fiber as the optical element and the embodiments disclosed in the following discuss the use of such optical fibers as examples; however, the invention is not so limited.

One embodiment of the invention, a scanning structure (10), is illustrated in Figure 1(a) where an excitation laser light (20) emitted from laser (14) is reflected by filter (16) before excitation laser light (20) is coupled into a proximal end (28) of optical fiber (12), which guides excitation light (20) to illuminate the sample, e.g., DNA probes, on microarray sample (30) through distal end (26) of optical fiber (12). Microarray sample (30) may be comprised of substrate (32) and probes (34), as discussed above. Filter (16) may be selectively designed to reflect a pre-selected wavelength or range of light while simultaneously allowing the passing of a desired wavelength or range of reflected light. The fluorescent light (20') emitted from probes (34) may be collected by the same fiber (12) and is guided to detector (18) after passing through filter (16). The excitation light (20) and fluorescent light (20') in embodiment (10) are separated by filter (16), which reflects light at a specific wavelength while allowing a particular wavelength to pass through. In the particular embodiment depicted in Figure 1(a), filter (16) may be designed to reflect excitation light (20). The system can also be adapted to use a filter that reflects the fluorescent light by swapping the positions of laser (14) and detector (18) in Figure 1(a).

Figure 1(b) depicts an alternative embodiment (22) of the same system design where the bulk optic beam splitting and coupling structure is replaced by a fiber optic coupler (24). Structures in different embodiments depicted with the same numbering are used to indicate similar function throughout this description. Coupler (24) can also be a wavelength domain multiplexer (WDM) which selectively couples a particular wavelength to the other fiber branch. An

WO 01/69302

PCT/US01/08043

additional filter (16) may preferably be placed in front of detector (18) to reject the excitation light.

Yet another embodiment utilizes light emitting diodes (LEDs) as a source of excitation light (20) rather than a laser. A single LED or multiple LEDs each emitting light at a different wavelength may be disposed directly adjacent substrate (32) yet still allow optical fiber (12) to gather fluorescent light (20') or replace laser (14) at the optical fiber proximal end (28).

As depicted in Figure 2, light (36) exiting optical fiber distal end (26) will diverge at a characteristic angle defined by the numerical aperture (NA) of the fiber. In order for a light beam to be guided by the fiber, the light beam should satisfy both of the following conditions: 1) the light beam enters the fiber within the core region, defined by the numerical aperture of the fiber; and 2) the light beam intersects the fiber axis at an angle smaller than NA. For example, light beam (38), as represented by an arrow, can be guided into core region (42) because it satisfies both of the above conditions. However, light beams (40) are not guided and enter cladding (44) rather than core region (42) because they only satisfy one of the above conditions.

Because of the beam divergence and guiding conditions, the light emitted in the region very close to the core of the fiber is collected in the embodiments illustrated in Figures 1(a) and (b). The light collection power of the fiber is determined by two factors: 1) the core size; and 2) the NA. The larger these two parameters, the higher the light collection power of fiber (12). However, a large core size may reduce the spatial resolution of the system. The spatial resolution is approximately equal to the size of the fiber core when the distance between fiber tip (12) and substrate (32) is within  $d_c/2NA$ , where  $d_c$  is the diameter of fiber core (42). If substrate (32) is greater than distance,  $d_c/2NA$ , away from fiber tip (12), the efficiency of fluorescent light collection may be significantly reduced. Standard telecommunication fibers have a core diameter of about  $9\mu m$  and  $NA = 0.12$ . Therefore, if a standard telecommunication fiber is used to form a scanning structure of this invention, a spatial resolution of approximately  $10\mu m$  can be achieved if the substrate surface is kept within about  $38\mu m$  from fiber facet (27).

WO 01/69302

PCT/US01/08043

Fibers with NAs as large as 0.66 have been reported. The potential exists to boost light collecting power by about 27 times by having fiber facet (27) kept to within about 7  $\mu\text{m}$  of the substrate.

5 Several measures may be adopted to provide a fiber (12) in close proximity to substrate (32).

A first embodiment of a scanning structure of this invention detects the distance between fiber tip (12) and substrate (32) surface in real time and actively controls this gap. The size of the gap may be detected by conventional methods such as optical interferometry using interferometers, and the gap is controlled by  
10 attaching the fiber to e.g. a piezoelectric actuator (such as the one described in U.S. Pat. No. 6,142,444) that moves in response to signals received from the interferometers.

A second scanning structure of the invention is configured to allow the tip of fiber (12) to aerodynamically "float" across microarray substrate (32) on a  
15 cushion of air created by rapid movement of the fiber tip near the substrate. This is a technology used in floppy disk drives, hard drives, and CD-ROM drives, for instance. The read head of a floppy disk drive is suspended by an air gap a couple of micrometers thick, which is created aerodynamically through a so-called "ground effect" created by the air between the rotating floppy disk and the read  
20 head. The relative movement of the read head and floppy disk creates a vacuum that draws the read head to the floppy disk surface, but as the read head nears the surface, sufficient pressure builds within the gap between the read head and the disk surface that the read head does not contact the disk surface.

This "ground effect" may be applied to a scanner of this invention. The  
25 fiber tip moves sufficiently rapidly across the surface of the substrate that the relative movement between the fiber and substrate draws the fiber tip to within a few microns of the surface of the substrate. As illustrated in Fig. 3, the fiber tip may be housed in a read head (50) having a shape that, together with substrate (32), forms a venturi through which the air flows to create the ground effect. A  
30 read head may be one optical fiber attached to a holder that moves the fiber across the surface of the substrate, or a read head may be a bundle of optical fibers

WO 01/69302

PCT/US01/08043

attached to a holder as discussed in further detail below. The surface of the read head that faces the substrate surface may have a parabolic shape in profile as illustrated in Fig. 3, or the read head may have a flat face as illustrated in Fig. 1 or Fig. 2. If the velocity is less than the velocity needed to create the ground effect, the read head or fiber tip may contact the substrate or a portion of a substrate holder as the read head or fiber tip slows to reverse direction and scan the microarray while traveling in the opposite direction.

A scanning structure (46) having a combined magnetic and aerodynamic levitation can prevent the read head or fiber tip from contacting the substrate or substrate holder as the read head or fiber tip slows to reverse direction during scanning. As illustrated in Figure 3, microarray substrate (32) of scanning structure (46) is supported on a pair of magnets (48) each having a similar polarity direction. The read head (50) with integrated optical fibers may be formed with integrated permanent magnets or may itself be magnetized (when formed of a magnetic material) so that its polarity is similar to the pair of support magnets (48) to provide a repulsive force between the read head and magnets (48). At the middle of substrate (32) at Position 1 where read head (50) moves relatively fast, read head (50) floats aerodynamically. As read head (50) moves toward the edge of substrate (32) from Position 2 to Position 3, read head (50) slows. This slowing reduces the aerodynamic float, but the read head (50) is supported by the magnetic force from magnetic supports (48) to maintain a read head (50) suspension that prevents the read head from contacting the microarray substrate (32) or magnets (48).

A third embodiment of a scanning structure of the invention is particularly well-suited to activate and detect labels of a microarray on a substrate having a rough surface, although its use is not limited to a microarray on a substrate having a rough surface. In scanning structure (52) illustrated in Figure 4, a fiber capillary (54) may be incorporated among optical fibers (56) to maintain a consistent aerodynamic float for read head (50). If multiple fibers are used, they may be banded together randomly, or they may be placed in a linear or ordered array with known spacings to allow faster or redundant microarray scanning. A very

WO 01/69302

PCT/US01/08043

thin gas cushion (58) may be generated between read head (50) and substrate (32) by blowing a gas down through capillary fiber (54). Any inert gas may be used such as air or nitrogen. Because fiber-based read head (50) is very light, a small amount of positive pressure should be sufficient to float read head (50) over substrate (32) and maintain a small distance on the order of a few microns between them. The amount of positive pressure will depend on the specific design of read head (50).

A number of features such as signal-to-noise ratio improvement, multiple wavelength excitation and collection, and scanning mechanisms are discussed in the following sections.

#### Signal-to-Noise Ratio Improvement

If an axis along the length of fiber (12) is substantially perpendicular to the surface of substrate (32), a certain amount of the original excitation light (20) will be reflected off a facet (27) of fiber (12) to the substrate (32) and then back to fiber (12), thereby producing background noise in the signal. This background noise may be suppressed by filter (16) in the system, as depicted in Figure 1(a) and 1(b). Filter (16) acts to suppress the background noise by reflecting light of unwanted wavelengths that the detector (18) would otherwise detect. However, because of the relative weakness of the emitted fluorescent light, there may still be a significant level of noise despite the filter suppression. One scanning structure having a greater signal to noise ratio (SNR) includes a fiber (12) which is tilted relative to the surface of substrate (32) by an angle,  $\theta$ , which angle is slightly larger than the NA of fiber (12), as depicted in Figures 1 and 5. This configuration allows the reflected excitation light to pass through the wall of the fiber instead of being guided to the detector by the optical fiber.

An alternative embodiment of a scanning structure with greater SNR includes a fiber (12) in which its facet (27) is polished so that it is substantially parallel to the surface of substrate (32). This polishing causes any light (including excitation light(20)) directly reflected off a fiber facet (27) and microarray substrate (32) to intersect the fiber (12) axis at an angle larger than the NA thus

WO 01/69302

PCT/US01/08043

preventing this light from being guided to the detector (18) via fiber core (42). On the other hand, fluorescent light (20\*) is emitted in all directions and the same proportion of light (20\*) as is captured by a fiber with unpolished facet will be captured by fiber (12) leaving its signal level unaffected. As a result, the SNR in the system can be improved significantly.

Another scanning structure having enhanced SNR employs a double-core fiber (60) which, as depicted in Figure 5, has two concentric cores (62, 64), with the refractive index of core (62) being greater than the refractive index of core (64). A relative refractive index profile of double-core fiber (60) is seen in Figure 5 where peak (70) corresponds to the relative refractive index of inner core (62), peak (72) corresponds to the index of outer core (64), and peak (74) corresponds to the index of the cladding of fiber (60).

A scanning structure having a double-core fiber (60) has a near 100% coupling ratio to light received from the substrate in its outer core (64) while light from the laser travels to the substrate through the inner core (62), and thus the double-core fiber acts as a core-selective coupler.

Outer core (64) acts like cladding to inner core (62) because outer core (64) has a lower refractive index than inner core (62). Consequently, when a double-core fiber is used in the system depicted in Figure 1(b), excitation light (20) from e.g. a laser is launched into inner core (62) at an angle less than the critical angle, and the excitation light is essentially confined to inner core (62).

The light in outer core (64) will be coupled out by this double-core fiber. Light entering outer core (64) at an angle greater than the critical angle for inner core (62) does not undergo internal reflection in inner core (62) and is therefore found primarily in outer core (64), leaving essentially only light from the laser in inner core (62).

Moreover, inner core (62) may have a small NA so that dispersion of the light beam (68) after exiting inner core (62) is small. Most of the fluorescent emissions (66), on the other hand, are collected by outer core (64) and travel back up fiber (60) to the detector. In this way, the light collection efficiency can be increased significantly, which in turn boosts the SNR. In addition, because the

WO 01/69302

PCT/US01/08043

outer core (64) can be made much larger in diameter than inner core (62), the intensity of the collected light is less critically dependent upon the distance between the facet (27) of fiber (12) and substrate (32), providing more tolerance and freedom in the instrument design.

5 One method for fabricating double-core fiber (60) involves chemical vapor deposition (CVD). This involves depositing a first concentration of a dopant, e.g., Ge in gaseous form with silane and O<sub>2</sub>, on the inner surface of a conventional fiber-forming tube (preform) to form a layer. Then, a second concentration of  
10 dopant (consisting either of the same dopant as the first concentration or a similar typical dopant) greater than the first concentration may be doped upon the layer, followed by stretching the preform to form fiber (60).

#### Multiple Wavelength Excitation and Collection

A scanning structure of the invention typically carries at least two separate  
15 wavelengths of light, the excitation light having one wavelength and the fluorescent light emitted by the fluorescent markers having another wavelength. Scanners having up to five separate excitation and/or collection wavelengths are currently known in the art. In current microarray scanners, all light beams at  
20 different wavelengths are combined into a single optical path through an objective lens of a microscope. The bulk optical components used in a conventional scanner require precision alignment and complicated structural configurations to carry and move a number of the bulk optical components. The high precision and bulk optical components make current scanners bulky and expensive. Further, it  
25 is often difficult to separate one wavelength from another in existing optical detectors having a combined optical path. The SNR suffers when more than one laser is activated simultaneously. Many existing microarray scanners avoid this problem by switching on one laser at a time but at the cost of a much slower scanning speed.

Figure 6 depicts a scanning structure (76) of the invention in which  
30 multiple light sources (14<sub>A1</sub> to 14<sub>An</sub>) having multiple corresponding wavelengths are combined into a single optic fiber (12) through the use of Wavelength

WO 01/69302

PCT/US01/08043

Division Multiplexers (WDM) (78<sub>1</sub>, 78<sub>n</sub>). The scanning structure is simple, especially since the flexibility of optical fiber (12) eliminates the need for complex supporting structures for e.g. lens and mirror assemblies as are currently used in existing scanners. WDMs (78<sub>1</sub>, 78<sub>n</sub>) are formed using techniques well-

5 known in the telecommunications industry to form planar or fused fiber couplers, for instance.

In one embodiment of the invention, multiple wavelength light beams may be scanned simultaneously across microarray substrate (32), but the light beams need not be in exactly the same location. Figure 7 depicts an alternative

10 embodiment (80) which isolates one wavelength from another more easily without paying a speed penalty. As depicted in Figure 7, optic fibers (12) may be arranged in a number of desired configurations depending upon the application to allow for each wavelength light (14<sub>N</sub> to 14<sub>M</sub>) to scan in synchronization while illuminating a separate yet relatively closely-spaced location. Bundled optic

15 fibers may be formed with or without the use of, e.g., a guide plate into which the fibers are inserted and then bundled to preserve their order. All articles, patents, and patent applications mentioned herein are incorporated by reference in their entirety. Because optical fibers (12) are extremely light-weight and have a very small, precise diameter, synchronized multi-spot scanning can be achieved by

20 using separate fibers for each wavelength. Here, the individual fibers (12) may be bundled in a microarray to form a fiber optic scanning head. Such a microarray may be bundled in an ordered array or in a random bundle. The number of fibers in a bundle may be any number, but in many instances the number will be less than ten. Either variation is feasible since the relative positions of the distal ends

25 of each fiber (12) will be known in the system. Despite the close proximity of the fiber ends, all of the fibers (12) need not be focused to illuminate the same spot, although this may be done. Rather, each of the fibers (12) may be arranged so that they illuminate and optionally also gather fluorescent light from multiple spots simultaneously.

#### Scanning Mechanism



WO 01/69302

PCT/US01/08043

Because optical fibers (12) are very light, scanning head (50) described above can be moved very quickly, thereby increasing the microarray read speed. Figure 8 depicts an embodiment of a scanning apparatus (82) where read head (50) of optical fiber (12) is moved back and forth in the Y-direction by a conventional galvano scanner (84). Galvano scanner (84) may be set to move suspension beam (86), which holds optic fiber (12) and read head (50), through a desired angle,  $\alpha$ , and at a desired frequency depending upon the geometric configuration of substrate (32). The scanning apparatus can have an X-stage positioner, which moves the substrate beneath the read head and also provides information to determine where along the X axis the optic fiber (12) is reading. The optical fiber (12) position in the Y direction is determined by an angular encoder incorporated in the galvano scanner (84). As galvano scanner (84) moves suspension beam (86) in the Y direction, substrate (32) may be step-moved in the X-direction by a conventional translation stage (88).

Figure 9 depicts an alternative embodiment of a scanning apparatus (90) where galvano scanner (84) and suspension beam (86) are replaced by resonance activators (92) and resonating suspension beam (94). Here, optical fiber read head (50) is oscillated back-and-forth in the Y-direction as resonating suspension beam (94) is forced to its resonant frequency by resonance activators (92). Resonance may be actuated by any number of conventional resonance activator (92) devices such as a piezo device adjacent to resonating suspension beam (94) or by a magnetic device on each side of resonating suspension beam (94). In either embodiment, read head (50) may be set to stop at the edge or outside substrate (32), where there is no probe. Preventing contact (and thereby preventing contamination) between read head (50) and substrate (32) may be avoided by any number of conventional or previously-mentioned methods such as by the implementation of the aerodynamic suspension mechanism used to float read head (50) over substrate (32).

With the particular embodiments depicted in Figures 8 and 9, scanning head (50) travels in a curved path in the Y-direction. This implies that image pixels in the row data will not be in a square grid as in most image files.

WO 01/69302

PCT/US01/08043

However, as long as the precise position of each pixel is registered, the image file generated with this scanner can be converted into a standard image file by conventional software. The X-position in either embodiment may be registered by a conventional position encoder on translation stage (88). For the embodiment depicted in Figure 8, the Y-position may be calculated from the angular position generated by galvanometer scanner (84) as it sweeps through angle,  $\alpha$ . For the embodiment depicted in Figure 9, the Y-position may be calculated by any one of several different methods. One method involves measuring and recording the strain at known locations on the surfaces of each side of resonating suspension beam (94) by the use of conventional strain gauges. A second method involves a new optically based position measurement device, described further below, which may be adapted for such measurement purposes. A third method involves measuring the resonant period in real-time and then calculating the position of read head (50) between the two extremes of the oscillation through time.

Figures 10(a) to 10(e) illustrate an alternative embodiment for a simpler position sensing device (96) incorporating a CCD array and fiber optic beacons. This embodiment may be feasible despite variations in slide size and translational velocities.

As illustrated in Figure 10(a) to 10(e), optical fibers (98, 100) are installed on the moving part of translation stage (106) as beacons while stationary stage (104) remains stationary relative to translation stage (105). Alternatively, stage (106) may be held stationary while stage (104) moves. First beacon (98) is the brightest, second beacon (100) is dimmer, and so on. Linear CCD array (102) may also be installed on the stationary (104), or moving (106), part of the stage. The separation between two adjacent beacons (98, 100) is slightly smaller than the length of linear CCD array (102). At the start of the translation, linear CCD array (102) will detect a single bright spot at the one end of its pixel array. The position of this spot indicates the relative position of translation stage (106), as depicted in Figure 10(a). As this spot moves to the other end of linear CCD (102) during the translation of stage (106) and before first beacon (98) is out of the range of linear CCD (102), second beacon (100) has moved in to continue the position

WO 01/69302

PCT/US01/08043

monitoring, as depicted successively in Figures 10(b) and 10(c). Any number of beacons may be used if necessary so that the position of translation stage (106) throughout the entire range can be monitored in an absolute manner.

As an example of beacon separation distances relative to a CCD length, the precise position of the spot along the pixel array can be calculated to at least about 1/50 of pixel pitch using a centroid algorithm. Considering, e.g., a typical low cost CCD array (102) with a conventional 2048 pixels and a 24  $\mu\text{m}$  pitch, the effective length of linear CCD array (102) is approximately 49 mm. By installing two fiber beacons at, e.g., about 40 mm of separation, position sensing device (96) may be capable of monitoring translation stage (106) position over about a 80 mm range at a resolution of about 0.48  $\mu\text{m}$ , which is more than sufficient for a microarray scanner.

Position sensing device (96) may be utilized for an embodiment of a one dimensional microarray (108), as depicted in Figure 11. Here, a one dimensional microarray (108) as described in copending U.S. Patent Application Ser. No. 60/244,418 entitled "Gene Thread," inventors Shiping Chen, Yuling Lao, and Anthony Chen, and filed on Oct. 30, 2000, which is herein incorporated by reference in its entirety, may be positioned on translation stage (106). Disposed upon one dimensional microarray (108) may be standard probes (110) containing samples for hybridization. Probes may alternatively be placed in varying configurations depending upon the desired applications. Some examples may include placing probes in a linear manner (112) or diagonally (114). In any case, the position of the probes may be monitored and read using any of the methods and apparatus as described above.

An embodiment of the scanning apparatus of the invention may alternatively allow scanning by having a read head (50) which is held stationary while one dimensional microarray (108) moves below read head (50). This would eliminate the need for an oscillating read head since only the one dimensional probes (110) are moving on stage (106) in a single direction.

The setup for position sensing device (96) may also incorporate a system which identifies beacons (98, 100) through their relative peak intensities. As seen

WO 01/69302

PCT/US01/08043

in Figures 10(a) to 10(e), the CCD array outputs relative signal strengths as a function of position along the array. A given signal strength corresponds to a given beacon. For instance, first beacon (98) is the brightest beacon and thus corresponds to the brightest signal (98') and second beacon (100), which is dimmer than first beacon (98), corresponds to the dimmer signal (100') on the CCD output, and so on. Therefore, outputs from a CCD array may be utilized in tracking beacons by their relative intensities. Alternatively, different beacons may also be identified through the spot size or the number of fibers in the beacon. For example, the first beacon (98) may comprise a single fiber forming a single spot on the CCD. The second beacon (100) may comprise two closely positioned optical fibers forming two adjacent spots, and so on. Note that the two fibers in second beacon (100) may separate from each other by a very small distance relative to the distance between first and second beacons (98, 100); e.g., first and second adjacent beacons (98, 100) may be separated by 40 mm while the two fibers in second beacon (100) may be separated from each other by a small distance such as 0.1 mm.

In addition, where the required scanning range in the X-direction is less than, approximately 30 mm, a single beacon with a CCD array or an analog position sensing device may be used. The analog position sensing device may be, for instance, a continuous photoresistor strip having differential voltage output at its two terminals proportional to the position of a light spot on the strip.

Figure 12 illustrates an embodiment of a scanning apparatus having a rotating position sensing mechanism (116), where the microarray is fabricated on rotating substrate (122) that has a shape similar to a CD-ROM disk as described in the aforementioned copending U.S. Patent Application Ser. No. 60/244,418. In this embodiment, microarray substrate (122) may be rotated continuously by rotating stage (120) while optical read head (118) or multiple heads moves step-wise in a radial direction to scan across the entire microarray surface (122). An advantage of this design is that it allows full benefit of the mature CD-ROM design and manufacturing capability to reduce the system cost. Because the substrate may be rotated continuously at high speed, the reading speed can be

WO 01/69302

PCT/US01/08043

accomplished faster than by conventional scanning mechanisms. This embodiment of the scanning apparatus may incorporate optical or magnetic markers in the substrate (122), as described above, which provide an indication of the position of the read head.

5 A scanning apparatus may incorporate read heads based on bulk optical lenses similar to what is found in a compact disk (CD) reader in addition to a read head (118) having a fiber optic as described above. This configuration may take full advantage of the existing mature technology in CD-ROM drives.

10 When microarray scanners are adapted as readers in high throughput screening, the microarray substrate in the system is replaced by an array of micro reaction wells, which are filled with fluids. All types of microarray scanners may be adapted for this application. In particular, when the disclosed invention is used for this application, the optical fiber guides excitation light energy to wells and collects emission light at the same time. The well array may move in one  
15 direction while the read head moves in the other, usually orthogonal direction to complete scanning action. On the other hand, the read head may provide the scanning motion in both directions while the array is kept stationary. Because the read head is fiber optic in the disclosed invention, it can be moved independent of the light source. This provides added flexibility to enable a compact, economical  
20 structure design.

In any of the embodiments of the invention, the scanning structure may be configured to receive light from a dry area or a wet area on a substrate. In one preferred embodiment of the invention, the area has a diameter between about 10  
25 microns and about 500 microns. In another preferred embodiment, the area is a microwell having a diameter between about 100 and about 1000 micron. The areas are described as having a diameter because typically the areas are spots as are formed by known spotting techniques or liquid contained in wells having a circular cross section, although the areas are not confined to circular shapes.

A scanning structure can be configured to receive light of a second  
30 wavelength from an area of a specified size a number of ways. For example, the fiber or rod will have a diameter suitable to read light from the area (that is, the

WO 01/69302

PCT/US01/08043

5 diameter is not so large that it overlaps two or more areas at all times the fiber or rod is reading a signal from a given area). The detector may be timed by known techniques to read signals at given times and/or given locations that correspond to the light conductive portion of the scanning structure intersecting the area to be read. The scanning speed may be altered to accommodate array density. Any combination of these techniques may also be used.

10 The substrate areas that react to light may be dry or wet. Microarrays of genes or proteins may be read using the scanner, as can microwells containing products of reaction or association (such as those encountered in high-throughput screening of drugs). Such microarrays include those described in WO99/55460, WO99/55461, EP 0 955 084, WO00/53736, WO00/53739, U.S. application no. 09/758,873, filed Jan. 10, 2001, 09/791,998, filed Feb. 22, 2001, 09/791,410, filed Feb. 22, 2001, and 09/791,411, filed Feb. 22, 2001 (the latter four of which are inventions of the present applicant), all of which are incorporated by reference  
15 herein in their entirety.

A scanning structure of the invention may be used in conjunction with a substrate configured for high throughput screening as described above. The scanning structure has a light source and a detector. The substrate receives light from the light source, and a detector receives light from the substrate to detect the  
20 presence or absence of one or more wavelengths of light. Other scanners as are used to determine hybridization on a microarray containing oligonucleotides may be used in this manner as well. Such microarrays are discussed in the Background section above. These microarrays may contain at least 100, 400, or 1000 microwells per square centimeter for liquid sample processing, for instance.

25 Although the invention has been described with reference to particular embodiments, the description is only an example of the invention's application and should not be taken as a limitation. Various adaptations and combinations of features of the embodiments disclosed are now readily apparent to those of ordinary skill and are within the scope of the invention. All references discussed or referred to herein are incorporated by reference in their entirety as if fully put  
30 forth herein.

WO 01/69302

PCT/US01/08043

**WHAT IS CLAIMED IS:**

1. A scanning structure for delivering light to and receiving light emitted from a light-excitabile area on a substrate, said scanning structure comprising an optical fiber that transmits light of a first wavelength and light of a second wavelength and having a proximal end and a distal end, which optical fiber is configured to receive at least a portion of the light of the second wavelength that is generated when said light-excitabile area receives the light of the first wavelength.
2. A scanning structure according to claim 1 and further comprising additional optical fibers that transmit the light of the first wavelength and the light of the second wavelength, each of said additional optical fibers having proximal ends and distal ends and being configured to traverse the light-excitabile area of the substrate in sufficient proximity to the substrate that said optical fibers capture at least a portion of the light of the second wavelength that is generated when said light-excitabile area receives the light of the first wavelength.
3. A scanning structure according to claim 2 wherein the distal end of said optical fiber and the distal ends of said additional optical fibers are held in a fixed relationship.
4. A scanning structure according to any of claims 1-3 further comprising a detector optically coupled to said proximal end of said optical fiber to receive the light of the second wavelength.
5. A scanning structure according to any of claims 1-4 further comprising a holder for the substrate that is configured to move the substrate as said optical fiber scans the substrate.
6. A scanning structure according to any of claims 1-5 further comprising a holder for said optical fiber that moves between a first position and a second

WO 01/69302

PCT/US01/08043

position, the distance between said first position and said second position being sufficient that said optical fiber traverses the light-excitabile area of the substrate.

- 5 7. A scanning structure according to any of claims 1-6 and further comprising a light source that emits light of said first wavelength to excite the light-excitabile area, which light source is optically coupled to the proximal end of the optical fiber so that the light of the first wavelength exits the distal end of the optical fiber.
- 10 8. A scanning structure for delivering light to and receiving light emitted from a light-excitabile area on a substrate, said scanning structure comprising
- 15 a) an optical fiber having a proximal end and a distal end that transmits light of a first wavelength and light of a second wavelength;
- b) a holder for the optical fiber that moves between a first position and a second position, the distance between said first position and said second position being sufficient that the optical fiber traverses the light-excitabile area of the substrate, which light-excitabile area emits light of the second wavelength when said light-excitabile area receives light of the first wavelength,
- 20 c) a light source that emits light of said first wavelength to excite the light-excitabile area, which light source is optically coupled to the proximal end of the optical fiber so that the light of the first wavelength exits the distal end of the optical fiber,
- 25 d) wherein the optical fiber is attached to the holder so that the optical fiber is sufficiently close to the microarray that the optical fiber receives said light of the second wavelength produced by the light-excitabile area at the distal end of the optical fiber and transmits the light of the second wavelength to the proximal end of the optical fiber, and
- 30 e) wherein the holder is configured to be moved between the first position and the second position when the light source emits the light having the first wavelength.



WO 01/69302

PCT/US01/08043

9. A scanning structure according to any of claims 1-8, wherein the scanning structure further comprises a beam having a distal portion and a proximal portion, said distal portion comprises said holder, the beam is attached to a mount at the proximal end of the beam, and the beam is configured so that the distal portion of the beam moves between the first position and the second position.
10. A scanning structure according to claim 9, wherein the beam is a movable arm of a galvanometer.
11. A scanning structure according to claim 9, wherein the beam moves between the first position and the second position at a resonant frequency of the beam.
12. A scanning structure according to claim 11, wherein the resonant frequency of the beam is actuated piezoelectrically.
13. A scanning structure according to claim 11, wherein the resonant frequency of the beam is actuated magnetically.
14. A scanning structure according to claim 9, wherein the proximal end of the beam is attached to the mount such that the proximal end of the beam is not movable.
15. A scanning structure according to any of claims 8-14 wherein the holder is configured to move horizontally between the first position and the second position, and wherein the scanning structure further comprises a magnet configured to repel the holder in a vertical direction when the holder reaches at least one of said first position and said second position.

WO 01/69302

PCT/US01/08043

16. A scanning structure according to any of claims 7-15, wherein the light source comprises a laser which emits the light at the first wavelength.
- 5 17. A scanning structure according to any of claims 1-16, wherein the scanning structure further comprises an optical filter comprising a first branch channel and a second branch channel, which optical filter is configured to receive the light of the first wavelength from the laser in the first branch channel and which optical filter is configured to transmit the light of the second wavelength from the light-excitabile area through the second branch channel.
- 10 18. A scanning structure according to any of claims 8-17, wherein the scanning structure further comprises a substrate translation stage that moves the substrate along a direction generally perpendicular to a line defined by the first position and the second position.
- 15 19. A scanning structure according to any of claims 8-18, wherein the holder secures the optical fiber at an angle other than perpendicular to the substrate.
- 20 20. A scanning structure according to any of claims 8-19, wherein a surface defining the distal end of the optical fiber is substantially parallel with the substrate.
- 25 21. A scanning structure according to any of claims 1-20, wherein the optical fiber further comprises a capillary fiber.
- 30 22. A scanning structure according to any of claims 1-20, wherein the optical fiber is a double core fiber comprising an inner core having a first refractive index and an outer core exterior to the inner core and having a second refractive index, said first refractive index being greater than the second refractive index.

WO 01/69302

PCT/US01/08043

23. A scanning structure for delivering light to and receiving light emitted from a light-excitable area on a substrate, said scanning structure comprising
- a) a plurality of optical fibers each having a corresponding proximal end and a corresponding distal end that transmit light having a plurality of differing preselected wavelengths, each of the wavelengths corresponding to each of the plurality of optical fibers,
  - b) said plurality of optical fibers comprising at least a first optical fiber that transmits light having a first wavelength and light of a second wavelength,
  - c) a holder for the plurality of optical fibers that moves between a first position and a second position, the distance between said first position and said second position being sufficient that the plurality of optical fibers traverse the light-excitable area of the substrate, which light-excitable area emits light of at least the second wavelength when said light-excitable area receives light of at least the first wavelength,
  - d) a plurality of light sources corresponding to each of the plurality of optical fibers that emit light of at least the first wavelength to excite the light-excitable area, which light sources are optically coupled to each of the corresponding proximal ends of the plurality of optical fibers so that the light of at least the first wavelength exits the distal end of at least the first optical fiber,
  - e) wherein the plurality of optical fibers are attached to the holder so that the plurality of optical fibers are sufficiently close to the microarray that each of the optical fibers receive said light of at least the second wavelength produced by the light-excitable area at the distal ends of the plurality of optical fibers and transmits the light of at least the second wavelength to at least the proximal end of the first optical fiber, and
  - f) wherein the holder is configured to be moved between the first position and the second position when the plurality of light sources emits the light having at least the first wavelength.

WO 01/69302

PCT/US01/08043

24. A scanning structure according to claim 23, wherein the scanning structure further comprises a beam having a distal portion and a proximal portion, said distal portion comprises said holder, the beam is attached to a mount at the proximal end of the beam, and the beam is configured so that the distal portion of the beam moves between the first position and the second position.
25. A scanning structure according to claim 24, wherein the beam is a movable arm of a galvanometer.
26. A scanning structure according to claim 24, wherein the beam moves between the first position and the second position at a resonant frequency of the beam.
27. A scanning structure according to claim 26, wherein the resonant frequency of the beam is actuated piezoelectrically.
28. A scanning structure according to claim 26, wherein the resonant frequency of the beam is actuated magnetically.
29. A scanning structure according to claim 24, wherein the proximal end of the beam is attached to the mount such that the proximal end of the beam is not movable.
30. A scanning structure according to any of claims 23-29 wherein the holder is configured to move horizontally between the first position and the second position, and wherein the scanning structure further comprises a magnet configured to repel the holder in a vertical direction when the holder reaches at least one of said first position and said second position.
31. A scanning structure according to any of claims 23-30, wherein the plurality of light sources comprises a plurality of lasers which emit the light of at least the first wavelength.

WO 01/69302

PCT/US01/08043

32. A scanning structure according to any of claims 23-31, wherein the scanning structure further comprises a plurality of optical filters, each of said optical filters comprising at least a first branch channel and a second branch channel, which optical filters are configured to receive the light of at least the first wavelength from the plurality of lasers in the first branch channel and which optical filters are configured to transmit the light of at least the second wavelength from the light-excitabile area through the second branch channel.
33. A scanning structure according to any of claims 23-32, wherein at least one of the plurality of optical fibers comprises a plurality of capillary fibers.
34. A scanning structure according to any of claims 23-33, wherein at least one of the plurality of optical fibers comprises a double core fiber comprising an inner core having a first refractive index and an outer core exterior to the inner core and having a second refractive index, said first refractive index being greater than the second refractive index.
35. A scanning structure according to any of claims 23-34, wherein the distal ends of the plurality of optical fibers comprise a multiple fiber read head where each of the distal ends have a preselected bundled configuration.
36. A scanning structure according to any of claims 23-34, wherein the distal ends of the plurality of optical fibers comprise a multiple fiber read head where each of the distal ends are linearly adjacent.
37. A scanning structure for delivering light to and receiving light emitted from a light-excitabile area on a substrate, said scanning structure comprising
- a) a plurality of optical fibers each having a corresponding proximal end and a corresponding distal end that transmit light having a plurality of differing

WO 01/69302

PCT/US01/08043

preselected wavelengths, each of the wavelengths corresponding to each of the plurality of optical fibers,

b) wherein the plurality of optical fibers transmits light of at least a first wavelength and light of at least a second wavelength,

5 c) a plurality of multiplexers which optically couple each of the corresponding distal ends of the plurality of optical fibers into at least one main optical fiber having a main proximal end and a main distal end,

d) a holder for the main optical fiber that moves between a first position and a second position, the distance between said first position and said second position being sufficient that the main optical fiber traverses the light-excitabile area of the substrate, which light-excitabile area emits light of at least the second wavelength when said light-excitabile area receives light of at least the first wavelength,

15 e) a plurality of light sources corresponding to each of the plurality of optical fibers that emit light of at least the first wavelength to excite the light-excitabile area, which light sources are optically coupled to each of the corresponding proximal ends of the plurality of optical fibers so that the light of at least the first wavelength exits the main distal end via at least one of the multiplexers,

20 f) wherein the main optical fiber is attached to the holder so that the main optical fiber is sufficiently close to the microarray that the main optical fiber receives said light of at least the second wavelength produced by the light-excitabile area at the distal end of the main optical fiber and transmits the light of at least the second wavelength to the proximal ends of the plurality of optical fibers via the plurality of multiplexers, and

25 g) wherein the holder is configured to be moved between the first position and the second position when the plurality of light sources emits the light having at least the first wavelength.

30 38. A scanning structure according to claim 37, wherein the scanning structure further comprises a beam having a distal portion and a proximal portion, said

WO 01/69302

PCT/US01/08043

distal portion comprises said holder, the beam is attached to a mount at the proximal end of the beam, and the beam is configured so that the distal portion of the beam moves between the first position and the second position.

- 5 39. A scanning structure according to any of claims 37-38 wherein the holder is configured to move horizontally between the first position and the second position, and wherein the scanning structure further comprises a magnet configured to repel the holder in a vertical direction when the holder reaches at least one of said first position and said second position.
- 10 40. A scanning structure according to any of claims 37-39, wherein the plurality of light sources comprises a plurality of lasers which emit the light of at least the first wavelength.
- 15 41. A scanning structure according to any of claims 37-40, wherein the scanning structure further comprises a plurality of optical filters, each of said optical filters comprising at least a first branch channel and a second branch channel, which optical filters are configured to receive the light of at least the first wavelength from the plurality of lasers in the first branch channel and which
- 20 optical filters are configured to transmit the light of at least the second wavelength from the light-excitability area through the second branch channel.
42. A scanning structure according to any of claims 37-41, wherein the main optical fibers comprises a capillary fiber.
- 25 43. A scanning structure according to any of claims 37-41, wherein the main optical fibers comprises a double core fiber comprising an inner core having a first refractive index and an outer core exterior to the inner core and having a second refractive index, said first refractive index being greater than the
- 30 second refractive index.

WO 01/69302

PCT/US01/08043

44. A scanning structure according to any of claims 1-43 wherein said optical fiber has a diameter at its distal end that is identical to a diameter along the length of the optical fiber.
45. A scanning structure for delivering light to and receiving light from a surface of an object which emits light at a second wavelength when said surface receives light at a first wavelength, said surface having either (i) a one-dimensional microarray of probes arranged along a first direction, said probes having a width in a second direction, or (ii) a two-dimensional microarray of probes arranged along the first direction and a second direction of the substrate, said scanning structure comprising
- a) a light source for illuminating at least a portion of the surface with light at the first wavelength;
  - b) a light-guiding rod positioned so that a distal end of the light-guiding rod is sufficiently close to said surface that light of said second wavelength emitted at the surface is captured by the light-guiding rod; and
  - c) a carrier configured to carry the light-guiding rod over the surface from a first position to a second position along said second direction, the distance between said first position and said second position being (i) at least the width of the probes for the one-dimensional microarray or (ii) the distance between probes furthest from one another along said second direction for said two-dimensional microarray.
46. A scanning structure according to claim 45, wherein the light-guiding rod is configured so that a proximal end of the light-guiding rod receives at least a portion of the light of the first wavelength generated by said light source and transmits said light to the distal end of the light-guiding rod.
47. A scanning structure according to claim 45 or claim 46, wherein said light-guiding rod comprises an optical fiber.



WO 01/69302

PCT/US01/08043

48. A scanning structure according to any of claims 45-47, wherein said scanning structure further comprises a second light-guiding rod configured to receive the light of the first wavelength from the light source at a proximal end of the second light-guiding rod and configured so that said light exits a distal end of the second light-guiding rod and near the surface of the substrate.
49. A scanning structure according to claim 48, wherein said second light-guiding rod comprises an optical fiber.
50. A scanning structure according to any of claims 1-49, wherein the substrate is substantially circular and defines a rotational axis perpendicular to the light-excitabile area of the substrate.
51. A scanning structure for delivering light to and receiving light from a surface of an object which emits light at a second wavelength when said surface receives light at a first wavelength, said surface having a one-dimensional microarray of probes arranged along a first direction, said probes having a width in a second direction, said scanning structure comprising
- a) a light source for illuminating at least a portion of the surface with light at the first wavelength;
  - b) a light-guiding rod fixedly positioned so that a distal end of the light-guiding rod is sufficiently close to said surface that light of said second wavelength emitted at the surface is captured by the light-guiding rod; and
  - c) a stage configured to translate the surface from a first position to a second position along said first direction, the distance between said first position and said second position being at least the distance between probes arranged along said first direction.
52. A scanning structure according to claim 51, wherein the light-guiding rod is configured so that a proximal end of the light-guiding rod receives at least a

WO 01/69302

PCT/US01/08043

portion of the light of the first wavelength generated by said light source and transmits said light to the distal end of the light-guiding rod.

53. A scanning structure according to claim 51 or claim 52, wherein said light-guiding rod comprises an optical fiber.
54. A scanning structure according to any of claims 1-53 wherein the scanning structure is configured to receive light of the second wavelength from the light-excitabile area on the substrate, and wherein the light-excitabile area contains a dry sample in said area having a diameter of between about 10 micron and about 500 micron.
55. A scanning structure according to any of claims 1-53 wherein the scanning structure is configured to receive light of the second wavelength from the light-excitabile area on the substrate, and wherein the light-excitabile area contains a wet sample in said area having a diameter of between about 10 micron and about 500 micron.
56. A scanning structure according to any of claims 1-53 wherein the scanning structure is configured to receive light of the second wavelength from the light-excitabile area on the substrate, and wherein the light-excitabile area contains a wet sample in said area having a diameter of between about 100 micron and about 1000 micron.
57. A scanning structure according to any of claims 54-56 wherein said optical fiber or said light-conducting rod has a diameter sufficiently small to receive light of the second wavelength from a first light-excitabile area but not an adjacent second light-excitabile area.
58. A method for determining the presence of association of a first target molecule to a first probe and a second target molecule to a second probe, the first probe comprising a plurality of first molecules complementary to the first target molecule on a first portion of a surface of a substrate and the second probe

WO 01/69302

PCT/US01/08043

- comprising a plurality of second molecules complementary to the second target molecule on a second portion of the surface of the substrate, the probe being a member of a plurality of probes on the substrate in either (i) a one-dimensional microarray of probes arranged along the substrate, wherein said
- 5 one-dimensional microarray has a plurality of probes arranged along a second direction of the substrate, each probe of said plurality having a width along a first direction on the substrate, or (ii) a two-dimensional microarray of probes arranged along the first direction and the second direction of the substrate, wherein said two-dimensional microarray has a plurality of probes arranged
- 10 along the first direction and a plurality of probes arranged along the second direction and wherein the target molecule has a component that provides light of a second wavelength when illuminated with light of a first wavelength, said method comprising the acts of
- 15 a) illuminating the first portion of the surface of the substrate with light at the first wavelength;
- b) detecting the presence of light at the second wavelength by relative movement between a light detector and the first portion of the surface along the first direction to determine whether the first target molecule has associated with the first probe;
- 20 c) advancing the substrate in the second direction; and
- d) again detecting the presence of light at the second wavelength by illuminating the second portion of the surface of the substrate with the light at the first wavelength and moving the light detector across the second portion of the surface in the first direction to determine whether the
- 25 second target molecule has associated with the second probe.
59. A method according to claim 58, wherein the light detector comprises a first optical fiber.
- 30 60. A method according to claim 59, wherein the act of illuminating comprises shining the light of the first wavelength into a proximal end of the first optical

WO 01/69302

PCT/US01/08043

fiber so that said light of the first wavelength exits a distal end of the first optical fiber to illuminate said first portion and said second portion of the substrate.

5 61. A method according to claim 59, wherein the act of illuminating comprises shining the light of the first wavelength into a proximal end of a second optical fiber so that said light of the first wavelength exits a distal end of the second optical fiber to illuminate said first portion and said second portion of the substrate.

10 62. A method of making a scanner that detects the presence of a fluorescent moiety, said method comprising positioning a distal end of an optical fiber in a holder of the scanner such that light of a first wavelength exiting the distal end of the optical fiber excites the fluorescent moiety to emit light of a second wavelength, and positioning said distal end of the optical fiber sufficiently  
15 close to the fluorescent moiety that the distal end of the optical fiber receives the light of the second wavelength and transmits the light of the second wavelength to a proximal end of the optical fiber.

20 63. A method according to claim 62, wherein said method comprises positioning the distal end of the optical fiber so that the distal end is not perpendicular to a surface on which the fluorescent moiety resides.

25 64. A method for determining the position of a linear stage for use in a scanner, comprising the acts of  
a) positioning a first beacon on the stage at a first location, said first beacon having a corresponding first signal;  
b) positioning at least a second beacon on the stage at a second location  
30 which is at a predetermined distance from the first beacon such that a line from the first beacon to the at least second beacon defines a first direction,

WO 01/69302

PCT/US01/08043

- said at least second beacon having a corresponding second signal weaker than the first signal;
- c) translating the stage along the first direction;
- d) while translating the stage, detecting the first signal and then the second signal with a detector;
- 5 e) correlating the detected first signal and the weaker second signal with the corresponding stage location.
65. A method according to claim 64, wherein the detector is a linear CCD.
- 10 66. A method according to claim 64 or claim 65, wherein the first beacon and the second beacon comprise optic fibers.
67. A method according to claim 65 or claim 64, wherein the predetermined distance is less than the linear CCD.
- 15 68. A method of using a scanning structure for a substrate configured for high throughput screening, wherein the scanning structure has a light source and a detector, said method comprising illuminating the substrate with light from the light source and detecting light received from the substrate with the detector.
- 20 69. A method according to claim 68, wherein the substrate contains at least 400 microwells per square centimeter.
70. A method according to claim 68, wherein the substrate contains at least 1000 microwells per square centimeter.
71. A method according to any of claims 68-70, wherein the substrate contains a probe in a liquid.
- 25 72. A method according to any of claims 68-71, wherein said light received from the substrate is produced by sample fluorescence.



WO 01/69302

PCT/US01/08043

73. A method according to any of claims 68-71, wherein said light received from the substrate is produced by chemiluminescence.

74. A method according to any of claims 68-71, wherein said light received from the substrate lacks at least one wavelength of light provided by the light source.



5



WO 01/69302

28

PCT/US01/08043





WO 01/69302

3/8

PCT/US01/08043




Fig. 5

WO 01/69302

4/8

PCT/US01/08043




Fig. 6





Fig. 7

WO 01/69302

5/8

PCT/US01/08043



WO 01/69302

6/8

PCT/US01/08043





Fig. 9

WO 01/69302

7/8

PCT/US01/08843



Figs. 10(a), 10(b), and 10(c)




Fig. 11

WO 01/69302

8/8

PCT/US01/08843




Fig. 12

## 【国際公開パンフレット（コレクトバージョン）】

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)


(19) World Intellectual Property Organization  
International Bureau(43) International Publication Date  
20 September 2001 (20.09.2001)

PCT

(10) International Publication Number  
WO 01/69302 A3

- (51) International Patent Classification: G01N 21/64
- (21) International Application Number: PCT/US01/08043
- (22) International Filing Date: 13 March 2001 (13.03.2001)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data: 66/188,873 13 March 2000 (13.03.2000) US
- (71) Applicant (for all designated States except US): GENOSPECTRA, INC. (US/US); 46540 Preston Blvd, Suite 506, Fremont, CA 94538 (US).
- (72) Inventor; and  
(73) Inventor/Applicant (for US only): CHEN, Shihping (GB/US); 13818 Coasefoot Terrace, Rockville, MD 20850 (US).
- (74) Agents: HOLLAND, Charles, D. et al., Morrison & Foerster LLP, 755 Page Mill Road, Palo Alto, CA 94304-1018 (US).
- (81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BE, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GR, GM, HU, ID, IL, IN, IS, JP, KB, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.
- (84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BI, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).
- Published:  
— with international search report
- (58) Date of publication of the international search report: 21 March 2002
- For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: FIBER OPTIC SCANNER



(57) Abstract: The disclosed scanning structure includes an apparatus for light delivery and light receiving from a light excitable area on a substrate to be measured by the scanning structure. The light delivery and receiving apparatus may include an optical fiber having a proximal end and a distal end which transmits light having a certain wavelength or light with several varying wavelengths to excite the substrate samples. This optical fiber may also simultaneously receive light which may be emitted by fluorescing samples on the substrate. The scanning structure also may further include a holder for the optical fiber that is able to transverse variable distances over the substrate to be measured or examined. Holders may include galvanic scanners as well as resonating suspension beams. A light source, e.g., a laser, may be optically coupled to the optic fiber's proximal end. And this light source may be of a certain wavelength, but multiple light sources each having a different wavelength may also be used simultaneously by coupling the light sources into either a single optic fiber through wavelength multiplexers or by placing individual optic fibers carrying differing wavelengths in close proximity to each other. As the light is transmitted down to the substrate through the optic fiber, the fiber is sufficiently close to the substrate microarray so that it can also receive the emitted fluorescing light.

| INTERNATIONAL SEARCH REPORT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         |                                                                                    | International Application No.<br>PCT/US 01/08043                   |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------|--------------------------------------------------------------------|
| A. CLASSIFICATION OF SUBJECT MATTER<br>IPC 7 601N21/64                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                    |                                                                    |
| According to International Patent Classification (IPC) or to both national classification and IPC                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                                                                                    |                                                                    |
| B. FIELDS SEARCHED<br>Minimum documentation searched (classification system followed by classification symbols)<br>IPC 7 601N 602B                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |                                                                                    |                                                                    |
| Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                    |                                                                    |
| Electronic data base consulted during the international search (name of data base and, where practical, search terms used)<br>EPO-Internal, WPI Data, PAJ                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           |                                                                                    |                                                                    |
| C. DOCUMENTS CONSIDERED TO BE RELEVANT                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |                                                                                    |                                                                    |
| Category *                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Citation of document, with indication, where appropriate, of the relevant passages | Relevant to claim No.                                              |
| X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | EP 0 266 881 A (ASTROMED LTD)<br>11 May 1988 (1988-05-11)                          | 1-4, 7, 8,<br>23, 37,<br>45-47,<br>51, 58,<br>64, 68, 72<br>23, 37 |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | the whole document                                                                 |                                                                    |
| X                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | US 5 968 766 A (POWERS LINDA)<br>19 October 1999 (1999-10-19)                      | 1-5                                                                |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | column 5, line 5 - line 15; figure 1                                               | 8, 23, 37,<br>45, 51,<br>58, 64                                    |
| A                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | US 4 877 966 A (TONEI L DAVID ET AL)<br>31 October 1989 (1989-10-31)               | 1, 8, 23,<br>37, 45,<br>51, 58, 64                                 |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | column 1 - column 4; figure 1                                                      |                                                                    |
| -/-                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                                    |                                                                    |
| <input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                    |                                                                    |
| * Special categories of cited documents:<br>"A" document defining the general state of the art which is not considered to be of particular relevance<br>"E" earlier document but published on or after the international filing date<br>"L" document which may throw doubts on priority claims or which is cited to establish the publication date of another claim or of other special reason (as specified)<br>"O" document relating to an oral disclosure, use, exhibition or other means<br>"P" document published prior to the international filing date but later than the priority date claimed<br>"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention<br>"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone<br>"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other cited documents, such combination being obvious to a person skilled in the art<br>"A" document member of the same patent family |                                                                                    |                                                                    |
| Date of the latest completion of the international search<br>13 December 2001                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                                                    | Date of mailing of the international search report<br>20/12/2001   |
| Name and mailing address of the ISA<br>European Patent Office, P.O. Box 5018, Postfach 2<br>M - 2200 Wien, Austria<br>Tel. (+31-70) 340-2040, Ts. 31 551 epo int.<br>Fax (+31-70) 340-2016                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                    | Authorized officer<br>Hervé, D                                     |

Form PCT/AR/210 (second sheet) July 1999

page 1 of 2



INTERNATIONAL SEARCH REPORT

International Application No.

PCT/US 01/08043

| C/Continuation DOCUMENTS CONSIDERED TO BE RELEVANT |                                                                                                                              |                                    |
|----------------------------------------------------|------------------------------------------------------------------------------------------------------------------------------|------------------------------------|
| Category*                                          | Content of document, with indication where appropriate, of the relevant passages                                             | Relevant to claim No.              |
| A                                                  | US 5 764 157 A (GORFINKEL VERA ET AL)<br>21 July 1998 (1998-07-21)<br><br>column 10, line 9 -column 11, line 15;<br>figure 4 | 1, 8, 23,<br>37, 45,<br>51, 58, 64 |

1

Form PCT/IS9/C16 (continuation of second sheet) (July 1999)

page 2 of 2

| INTERNATIONAL SEARCH REPORT            |                  |                         |                  | International Application No. |  |
|----------------------------------------|------------------|-------------------------|------------------|-------------------------------|--|
| Information on patent family members   |                  |                         |                  | PCT/US 01/08043               |  |
| Patent document cited in search report | Publication date | Patent family member(s) | Publication date |                               |  |
| EP 0266881                             | A                | 11-05-1988              | EP 0266881 A2    | 11-05-1988                    |  |
|                                        |                  |                         | GB 2196734 A     | 05-05-1988                    |  |
|                                        |                  |                         | JP 63091537 A    | 22-04-1988                    |  |
| US 5968766                             | A                | 19-10-1999              | NONE             |                               |  |
| US 4877966                             | A                | 31-10-1989              | US 4758727 A     | 19-07-1988                    |  |
| US 5784157                             | A                | 21-07-1998              | AU 1080097 A     | 11-06-1997                    |  |
|                                        |                  |                         | CA 2237222 A1    | 29-05-1997                    |  |
|                                        |                  |                         | EP 0862735 A1    | 09-09-1998                    |  |
|                                        |                  |                         | WO 9719342 A1    | 29-05-1997                    |  |

Form PCT/ISA/210 (part) family annex (July 1999)

(51)Int.Cl.<sup>7</sup> F I テーマコード ( 参考 )  
G O 2 B 26/10 G O 2 B 26/10 1 0 9

(81)指定国 AP (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), EA (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), EP (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OA (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG), AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW

(72)発明者 チェン, シピン

アメリカ合衆国, カリフォルニア 9 4 5 3 9, フレモント, クーガー サークル 4 5 0 8 4

F ターム (参考) 2G043 AA01 BA16 EA01 FA06 GA03 GB01 GB19 HA05 HA09 JA02

KA09 LA03 MA01

2G054 AA06 EA03 GA04 GE01

2H045 AE05

2H050 AC13 AC28 AC87

【要約の続き】

られた蛍光をも受光するのに充分に、この基板に近接している。

**Espacenet****Bibliographic data: JP2008534960 (A) — 2008-08-28**

---

**FLOW CYTOMETER FOR DIFFERENTIATING SMALL PARTICLES IN SUSPENSION****Inventor(s):****Applicant(s):****Classification:**     - international:     **G01N15/14; G01N21/05; G01N21/49**  
                              - cooperative:     **G01N15/1404; G01N15/1434****Application number:**     JP20080504110 20060316     Global Dossier**Priority number (s):**     WO2006US09449 20060316 ; US20050094723 20050330**Also published as:**     EP1924837 (A1) US2006221325 (A1) US7113266 (B1)  
                              WO2006104699 (A1)

Abstract not available for JP2008534960 (A)

Abstract of corresponding document: US7113266 (B1)

A flow cytometer includes an optical flow cell through which particles to be characterized on the basis of at least their respective side-scatter characteristics are caused to flow seriatim. A plane-polarized laser beam produced by a laser diode is used to irradiate the particles as they pass through a focused elliptical spot having its minor axis oriented parallel to the particle flow path. Initially, the plane of polarization of the laser beam extends perpendicular to the path of particles through the flow cell. A half-wave plate or the like is positioned in the laser beam path to rotate the plane of polarization of the laser beam so that it is aligned with the path of particles before it irradiated particles moving along such path.

(19) 日本国特許庁 (JP)

(12) 公表特許公報 (A)

(11) 特許出願公表番号

特表2008-534960

(P2008-534960A)

(43) 公表日 平成20年8月28日 (2008.8.28)

|                        |                |             |
|------------------------|----------------|-------------|
| (51) Int. Cl.          | F I            | テーマコード (参考) |
| GO 1 N 15/14 (2006.01) | GO 1 N 15/14 P | 2 G O 5 7   |
| GO 1 N 21/05 (2006.01) | GO 1 N 21/05   | 2 G O 5 9   |
| GO 1 N 21/49 (2006.01) | GO 1 N 21/49 Z |             |

審査請求 未請求 予備審査請求 未請求 (全 13 頁)

(21) 出願番号 特願2008-504110 (P2008-504110)  
 (86) (22) 出願日 平成18年3月16日 (2006. 3. 16)  
 (85) 翻訳文提出日 平成19年9月28日 (2007. 9. 28)  
 (86) 国際出願番号 PCT/US2006/009449  
 (87) 国際公開番号 W02006/104699  
 (87) 国際公開日 平成18年10月5日 (2006. 10. 5)  
 (31) 優先権主張番号 11/094, 723  
 (32) 優先日 平成17年3月30日 (2005. 3. 30)  
 (33) 優先権主張国 米国 (US)

(71) 出願人 507316789  
 ベックマン コールター, インコーポレ  
 イテッド  
 アメリカ合衆国 カリフォルニア 928  
 34, フラートン, エヌ. ハーバー  
 ブールバード 4300, メール コ  
 ード エー-42-シー

(74) 代理人 100078282  
 弁理士 山本 秀策

(74) 代理人 100062409  
 弁理士 安村 高明


(74) 代理人 100113413  
 弁理士 森下 夏樹

最終頁に続く

(54) 【発明の名称】 懸濁液中の小粒子を区別するためのフローサイトメータ

## (57) 【要約】

フローサイトメータは、光学フローセルを含み、特性調査されるべき粒子が該光学フローセルを順次流され、該粒子は、少なくともそのそれぞれの側面散乱特性に基づいて、特性調査される。レーザダイオードによって生成される平面偏光レーザビームは、該粒子が、集束楕円スポットを通過する際に、該粒子を照射するために使用され、該集束楕円スポットは、その短軸が、該粒子フロー経路に平行に向けられる。最初に、該レーザビームの該偏光面は、該フローセルを通過する粒子の該経路に対して垂直に延びる。半波長板などが、該レーザビーム経路に配置され、該レーザビームの該偏光面を回転する。その結果として、該レーザビームは、そのような経路に沿って移動する粒子を照射する前に、粒子の該経路と整列される。



## 【特許請求の範囲】

## 【請求項1】

(a) 粒子調査ゾーンを有する光学フローセルであって、特性調査されるべき粒子が実質的に線形な粒子経路に沿って、一度に一個ずつ、該ゾーンを通過し得る、光学フローセルと、

(b) 平面偏光レーザービームを生成するためのレーザーであって、該レーザーは、該レーザービームの偏光面が、該粒子経路に垂直であるように向けられる、レーザーと、

(c) 該粒子調査ゾーン内に、該粒子経路上に中心を置く楕円スポットとして、該レーザービームを集束するためのビーム成形レンズ系であって、該楕円スポットの短軸は、該粒子経路と平行に配置される、ビーム成形レンズ系と、

(d) 該粒子経路と、該レーザービームが該粒子調査ゾーンで粒子を照射する方向とに対して実質的に垂直な方向に、該集束楕円スポットによって照射された粒子によって散乱されると、該レーザービームの一部分を検出するように配置された側面散乱光検出器と、

(e) 該レーザーと該光学フローセルとの間の該レーザービームの中に配置された偏光回転光学素子であって、該光学素子は、該レーザービームが該粒子調査ゾーンで、粒子を照射する前に、該レーザービームの偏光面を回転する役割を果たす、偏光回転光学素子と

を備える、フローサイトメータ。

## 【請求項2】

前記偏光回転光学素子は、前記粒子照射レーザービームの偏光面を前記粒子経路に実質的に平行にするために十分な量、該レーザービームの偏光面を回転する役割を果たす、請求項1に記載の装置。

## 【請求項3】

前記偏光回転光学素子は、前記レーザービームの偏光面を90°回転するように動作する、請求項2に記載の装置。

## 【請求項4】

前記偏光回転光学素子は、半波長板を備える、請求項3に記載の装置。

## 【請求項5】

前記偏光回転光学素子は、一対の四分の一波長板を備える、請求項3に記載の装置。

## 【請求項6】

(a) 線形粒子経路を有する光学フローセルであって、該線形粒子経路に沿って特性調査されるべき粒子が順次通過し得る、光学フローセルと、

(b) 相互に垂直な長軸と短軸とを有する楕円断面の平面偏光レーザービームを生成するためのレーザーダイオードであって、該レーザーダイオードは、該楕円断面の該長軸が、該粒子経路に対して垂直に延びるように配置される、レーザーダイオードと、

(c) 該粒子経路上に互いに垂直な長軸と短軸とを有する楕円スポットに、該レーザービームを集束するためのレンズ系であって、該スポットは、該集束スポットの該短軸が該粒子経路と平行であるように向けられる、レンズ系と、

(d) 粒子フローの方向と、該レーザービームが該粒子経路に沿って移動する粒子を照射する方向とに対して実質的に垂直な方向に散乱される、レーザー放射を検出するために配置された側面散乱光検出器と、

(e) 該レーザービームの中に配置された光学素子であって、該光学素子は、該レーザービームが、該粒子経路上の粒子を照射する前に、該レーザービームの偏光面を90°回転する機能を有する、光学素子と

を備える、フローサイトメータ。

## 【請求項7】

前記光学素子は、半波長板を備える、請求項6に記載の装置。

## 【請求項8】

前記光学素子は、タンデムに配置された一対の四分の一波長板を備える、請求項6に記載の装置。

## 【請求項9】

(a) 粒子調査ゾーンを有する光学フローセルであって、特性調査されるべき粒子が、実質的に線形な粒子経路に沿って、一度に一個ずつ、該ゾーンを通過するようにされ得る、光学フローセルと、

(b) 相互に垂直な長軸と短軸とを有する拡大楕円断面の平面偏光レーザービームを生成するレーザーであって、該レーザービームは、該拡大楕円断面の該長軸に平行な平面内で平面偏光され、該偏光面が、該線形粒子経路に対して実質的に垂直となるように、該光学フローセルに対して向けられる、レーザーと、

(c) 該レーザービームの大部分を収集して、コリメートし、コリメートレーザービームを提供するためのコリメートレンズであって、該コリメートレンズは、該拡大楕円断面の一部分を切頭するようにさらに動作し、これによって、該コリメートレンズの両側に現れる偽光源を生成する、コリメートレンズと、

(d) (i) 該粒子調査ゾーン内の該線形粒子経路上に中心を置く楕円スポットとして、該コリメートレーザービームを集束するため、および (ii) 該集束楕円スポットの両側上で、該集束楕円スポットの該長軸に沿って、該偽光源からの光を、偽光スポットとして、集光するためのビーム成形レンズ系であって、該ビーム成形レンズ系は、該集束楕円スポットの該短軸が該粒子経路と平行に延びるように、該集束楕円スポットを向けるのに有効であり、これによって、該偽光スポットが、該粒子経路の両側に該粒子経路から間隔を空けて配置される、ビーム成形レンズ系と、

(e) 該粒子経路と、該レーザービームが該粒子調査ゾーンで粒子を照射する方向とに対して実質的に垂直な方向に、該集束楕円スポットによって照射される粒子から、散乱される、レーザー放射を検出するために配置された側面散光乱検出器と、

(f) 該レーザービームの中に配置された偏光回転光学素子であって、該偏光回転光学素子は、該レーザービームが該粒子調査ゾーンで粒子を照射する前に、該レーザービームの偏光面を90°回転するように適合されている、偏光回転光学素子と

を備える、フローサイトメータ。

## 【請求項10】

前記偏光回転光学素子は、前記レーザービームの前記コリメートされる部分の中に配置される、請求項9に記載の装置。

## 【請求項11】

前記偏光回転光学素子は、半波長板を備える、請求項9に記載の装置。

## 【請求項12】

前記偏光回転光学素子は、タンデムに配置された一対の四分の一波長板を備える、請求項9に記載の装置。

## 【発明の詳細な説明】

## 【技術分野】

## 【0001】

(発明の背景)

(発明の分野)

本発明は、液体懸濁液中の小粒子、例えば、様々なタイプの血球を区別するために、一般的に使用されるタイプのフローサイトメータにおける改善に関する。より具体的には、本発明は、例えば、レーザーダイオードから発光された平面偏光放射を使用し、この平面偏光放射は、光学フローセルを通過する個々の粒子の光学散乱特性を検出するために、このような粒子を照射し、これによって、各粒子を、特定のクラスまたはタイプのメンバとして、特徴づけるタイプのフローサイトメータにおける改善に関する。

## 【背景技術】

## 【0002】

(従来技術)

フローサイトメータは、粒子懸濁液中の種々のタイプの個々の小さな粒子を区別するために、一般的に使用され、この区別は、各粒子の光散乱および/または蛍光の特性をベ-

子調査ゾーンを有する光学的に透明なフローセルと、該粒子が該粒子調査ゾーンを通過する際に、このような粒子を一度に一個ずつ照射するためのレーザ光源と、該照射された粒子からの散乱放射と、対象のクラスまたはタイプ内の特定の粒子に事前に付けられた蛍光色素によって発せられる蛍光放射との双方を受けるように、該フローセルの周りに戦略的に置かれている複数の光学検出器とを、一般的に含む。典型的に、光検出器は、光検出器の光感知素子の幾何学的形状によって決定される角度範囲内の前方散乱放射と、照射レーザビームの方向と粒子経路の方向とに、実質的に垂直な方向に散乱される側面散乱放射との双方を検出するように配置される。光検出器のそれぞれの出力は、次いで、公知の方法で処理され、照射された粒子のそれぞれを特定のクラスまたはタイプのメンバとして識別する。通常、フローサイトメータは、各クラスにおける粒子の数または各タイプの粒子の数を示すヒストグラムまたは散布図を提供する。

#### 【0003】

上記のタイプのフローサイトメータにおいて、粒子照射レーザ光源として、レーザダイオードを用いることが、ますます一般的になってきている。このようなソリッドステートデバイスは、サイズおよび経済性を基に考慮すると、より従来型のガスレーザ、例えば、ヘリウムネオンレーザおよびアルゴンレーザよりも好まれることが多い。これらのデバイスは、比較的小さなサイズであるので、器具筐体の中に、容易に配置され、方向付けされ、任意の様々な設計目的を達成し得る。レーザダイオードは、多くの点で、有利であると考慮され得る一方で、レーザダイオードは、不利な点がない分けではない。例えば、比較的低パワーのデバイスであることに加え、レーザダイオードは、典型的に、実用のためにコリメートされなくてはならない非コリメート放射を発する。多くのデバイスにおいて、アクティブな半導体素子または「ダイ」から発せられる出力放射は、比較的速く発散する傾向がある。なぜなら、ダイは、通常、形状が長方形であるために、発せられた放射は、相互に垂直な平面で、異なるように発散するからである。したがって、レーザダイオードからの放射出力の形状は、典型的には、拡大楕円の形状であり、一般に、比較的大きな発散角度、例えば、 $30^\circ$  で一つの平面に拡がり、その一方で、かなり小さな発散角度、例えば、 $10^\circ$  で垂直な平面に拡がる。この拡大ビーム内のレーザエネルギーを捕獲し、コリメートするために、レーザ源に非常に接近して、比較的高い開口数のコリメートレンズを配置することは、一般的である。このコリメートレンズは、より小さな角度でレーザ源から発散するエネルギーの全てを容易に収集する一方で、しばしば、より大きな角度で発散するビームの一部分を切頭する。多くのレーザダイオードにおいて、この切頭の結果、回折光および／または反射光からなる一対の異質 (extraneous) 光源または偽光源 (spurious light source) (あるいは遠視野回折パターン) が、ビーム切頭が発生するコリメートレンズの両側に現れる。これらの偽光源は、通常、コリメートされた主ビームに比べて、比較的弱い強度である一方で、偽光源は、フローサイトメータの性能に対して問題となり得る。例えば、レーザダイオードからの出力ビームを、フローセルを通過して移動する粒子を照射するために適合された楕円スポットに集束するとき、その集束楕円スポットは、一対の比較的弱く、境界が不鮮明な放射のローブ (lobe)、すなわち「光ローブ」をともなう。これらの光ローブは、コリメートレンズの両側から発する放射の集束偽ビームを表す。これらの光ローブは、集束楕円スポットの両側で、その境界の外側に現れる。これらの光ローブが、粒子経路の中に位置する場合には、これらの光ローブは、フローサイトメータの信号処理を複雑化するように機能する低レベルの光散乱信号および蛍光信号を生じる。具体的には、このような低レベルの信号は、小さな粒子から発するように見えるが、これらの小さな粒子は、粒子サンプルには、実際は、存在しない。

#### 【0004】

Ozasaらへ付与された米国特許 (特許文献1) においては、上述の光ローブ問題が、フローサイトメータにおけるレーザダイオードの向きを単に調整するだけで、対処される。すなわち、上述の光ローブは、フローセルを通過する粒子経路の外側に、すなわち、粒子経路に垂直である平面にローブを配置するように置かれる。Ozasaらは、フロー



サイトメータにおけるレーザダイオードを、拡大楕円の長軸が、（通常、垂直である）フローセルを通過する粒子フローの方向に平行となるように向けることは、従来通りであると指摘している。レーザダイオードをこのように向けると、ビームが集束されて、円筒レンズと集光レンズとの組み合わせを通過するときに、粒子照射楕円となることを可能にする。この粒子照射楕円は、（a）その楕円の短軸に平行な平面内に、回折限界があり、（b）フローセル内の公称粒子経路上に、その中心が位置し、その短軸がそのような経路と平行に延びる。なぜなら、集束楕円は、粒子経路に平行な平面内に回折限界があるために、集束ビームのフラックス密度が最大化され、このことによって、器具の光散乱および蛍光検出の感度が強化される。また、粒子経路に平行な平面内に回折限界があるので、集束楕円は、時間ドメイン内に（すなわち、粒子フローの方向に）、比較的接近して一緒に移動する複数の粒子の同時照射（および検出）ができない。しかし、Ozasaらが指摘するように、フローサイトメータにおけるレーザダイオードの従来の向きの著しい欠点は、フローサイトメータが、上述の光ローブを、直接、粒子経路に配置するように機能するので、この結果、実際には存在しない小さな粒子を誤って検出し、カウントすることである。この問題に対するOzasaらの解決策は、上述のように、レーザダイオードをそのサポート筐体に対して、単に90°回転することである。これは、拡大楕円の長軸が、今では水平であること、すなわち、フローセルを通過する（通常は垂直である）粒子経路に垂直となるようにするためである。これは、ローブ放射を、粒子経路の両側で、その外側にシフトする効果を有する。このように向ける結果、フローセルを通過する粒子で、光ローブによって照射されず、したがって、このような照射の結果として、放射を散乱し得ないし、また蛍光放射も発し得ない。したがって、光検出器のそれぞれの出力におけるこのようなローブ放射の存在を相殺する必要はない。レーザダイオードのこのように向けると、その結果として、集束楕円スポットが90°回転し、この楕円の長軸が望ましからぬように粒子経路と整列されるが、Ozasaらは、ビーム形成光学系に追加レンズを追加することによって、この状況を回避していることに留意されたい。追加レンズは、集束楕円の形状を修復して、レーザダイオードが回転する前に生じた形状に、すなわち、短軸が粒子経路と平行である楕円にするために動作する。

【0005】

Ozasaらの特許で教示されるレーザダイオードの向きは、確認された光ローブ問題を解決し得るが、照射粒子によって散乱される放射の検出に影響を与える別の光学問題を生成することが見出された。より具体的には、照射粒子からの側面散乱放射（すなわち、照射ビームの光軸と、フローセルを通過する粒子経路との双方に対して、90°で散乱する放射）を検出することが望ましいとき、レーザダイオードの示唆された（水平の）向きは、側面散乱信号の信号対ノイズ比（SNR）を劇的に減少させる効果を有することが見出された。このSNRの減少の程度は、側面散乱パラメータが粒子の特性調査プロセスの一部として使用され得ないほどである。

【特許文献1】米国特許第6,713,019号明細書

【発明の開示】

【発明が解決しようとする課題】

【0006】

（発明の概要）

上記の議論の観点から、本発明の目的は、確認された問題、すなわち、レーザダイオードの拡大楕円出力ビームの長軸が、フローセルを通過する粒子経路に対して垂直となるように、レーザダイオードが向けられるときの側面散乱放射を検出する問題に対する解決策を提供することである。

【課題を解決するための手段】

【0007】

本発明の一つの局面に従うと、レーザダイオードからの出力ビームは、そのビームが最も速く発散している平面内で、平面偏光されることが、認識される。さらに、フローサイトメータにおける側面散乱放射の測定は、照射レーザビームの偏光面がフローセルを通過

する粒子経路の方向に平行でなくてはならないことを要求することが、認識される。さらに、上述されたタイプ、すなわち、レーザダイオードの向きが、確認された「光ローブ」問題を排除するために、 $90^\circ$  回転するタイプのフローサイトメータにおいて、粒子照射レーザビームの偏光面は、もはや粒子経路に平行ではなく、それゆえ、側面散乱放射を検出する能力が割り引かれることが、認識される。したがって、このような器具を用いて側面散乱測定を行うために、照射ビームの偏光面と粒子経路との間で必要な関係を新たに確立することが必要である。

#### 【0008】

以上の観点から、本発明に従って構成されたフローサイトメータは、以下のエレメント、すなわち、(a) 粒子調査ゾーンを有する光学フローセルであって、特性調査されるべき粒子が、実質的に線形な粒子経路に沿って、一度に一個ずつ、該ゾーンを通過し得る、光学フローセルと、(b) 平面偏光レーザビームを生成するレーザ源であって、このようなレーザは、該レーザビームの該偏光面が、該粒子経路に垂直となるように向けられる、レーザ源と、(c) 該粒子調査ゾーン内で、該粒子経路上に中心を置かれた楕円スポットとして、該レーザビームを集束するためのビーム成形レンズ系であって、このような楕円スポットの短軸は、該粒子経路に平行に配置される、ビーム成形レンズ系と、(d) 該粒子経路と、該レーザビームが該粒子調査ゾーンで粒子を照射する方向とに、実質的に垂直な方向に、該集束楕円スポットによって照射された粒子によって散乱される、該レーザビームの一部分を検出するように配置された側面散乱光検出器と、(e) 該レーザ源と該光学フローセルとの間の該レーザビーム経路に配置された偏光回転光学素子であって、このような光学素子は、従来技術の系のように、このような経路に垂直に配置されるよりもむしろ、該レーザビームの該偏光面を該粒子経路と実質的に平行に配置されるのに十分な量、回転する役割を果たす、偏光回転光学素子とを備える。好ましくは、上記偏光回転光学素子は、半波長板、または2つの四分の一波長板の組み合わせのいずれかを備え、この板は、上記レーザビームの上記偏光面を $90^\circ$  回転させるように役立つ。

#### 【0009】

本発明およびその利点は、添付図面を参照しながら、以下の好ましい実施形態の詳細な説明から、より良く理解される。添付図面において、同様の記号は、同様のパーツを意味する。

#### 【発明を実施するための最良の形態】

#### 【0010】

(好ましい実施形態の詳細な説明)

ここで、図面を参照すると、図1は、発散レーザビームLBを発するタイプの従来型レーザダイオードLDを示し、この発散レーザビームLBは、2つの異なる発散角 $\theta_1$ および $\theta_2$ に従って、サイズを拡大する楕円断面を有する。図示されるように、これらの角度は、相互に垂直な平面内で測定され、一方の角度、この場合は、角 $\theta_1$ が、他方の角度よりも通常は実質的に大きい。レーザダイオードの特徴であるように、発光レーザビームLBは、平面P内で、平面偏光される。平面Pは、ビームの拡大楕円断面の長軸A'に平行である。楕円断面の短軸A''は、当然、長軸A'に対して垂直である。

#### 【0011】

図2において、図1のレーザダイオードLDが、上述された以前のタイプのフローサイトメータで具現化されているように示される。解析されるべき粒子、例えば、血球を含む粒子サンプルPSは、矢印Aの方向に、光学的に透明なフローセル6の中に、ノズル7によって導入される。シース液体Sは、ノズル7によって提供される粒子ストリームを囲むような方法で、フローセルに供給され、これによって、一般的に垂直に配置されるフローセルの中心軸に、粒子ストリームのフローを流体力学的に制約する役割を果たす。シース流体の流速は、粒子サンプルがノズル7によって導入される速度と組み合わせさせて、粒子が、フローセルの中心に位置する粒子調査ゾーンZ'を1度に1個ずつ通過するようにさせる。レーザダイオードによって発された発散レーザビームLBは、コリメータレンズ3によって、コリメートされ、その結果コリメートされた主ビームMBは、円筒レンズ4お

よび集光レンズ5の組み合わせを通され、主ビームを粒子調査ゾーンでの楕円スポット焦点に導く。上述の理由から、この分野において、レーザダイオードの楕円出力ビームの長軸A'がフローセルを通過する(通常垂直な)粒子経路に平行に延びるように、レーザダイオードを向けることが、従来行われてきた。(この向きにおいて、レーザビームの偏光面Pもまた、粒子経路に平行に延びることに留意されたい。)楕円ビームがこの垂直な向きであるにも関わらず、ビームは、集束スポットの短軸が粒子経路に平行に延びる、楕円スポット焦点に導かれる。このことは、上述の技術的な利点を提供する。

#### 【0012】

図2に示されるレーザダイオードの向きで、コリメートレンズ3は、通常、ビームがより速く拡大する平面、すなわち、角 $\theta_1$ が測定される垂直な平面内の発散するレーザビームの一部分を切頭する。コリメートレンズが、発散レーザビームに対して中心に位置すると仮定すると、この切頭は、比較的低強度の一对の偽ビームSB1およびSB2を生成する。この一对の偽ビームは、切頭が生じるコリメートレンズ3の両側3aおよび3bから発するように見える。上述のように、楕円スポットとして、主ビームを集束することに加え、レンズ4および5は、主ビームMBの集束ビームスポットBSの両側に、これらの偽ビーム(「光ローブ」)をビームスポットBS1およびBS2として、集束するように機能する。図示されるように、これらの偽ビームスポットのそれぞれの強度S1およびS2は、主ビームの強度S0よりも実質的に低い。それにも関わらず、これらの偽ビームスポットは、フローセルを通過する粒子経路上に直接位置する。したがって、フローセルを通過する各粒子は、3箇所照射され、そのうちの1箇所(中央箇所)のみが、望ましい。以下で議論される光散乱・蛍光検出器は、次いで、偽ビームからの信号を受けるので、このため、粒子分化プロセスにおいて、これらの信号を無視するためのスキームを必要とする。

#### 【0013】

図3に模式的に示されるフローサイトメータにおいて、図1および図2のレーザダイオードLDが、 $90^\circ$ 回転していることが、理解される。その結果として、発散レーザビームLBが、図面の平面内と、粒子経路の平面内とで、その小さな角 $\theta_2$ で拡大する。レーザダイオードのこの向きにおいて、その拡大楕円出力ビームの長軸A'は、今や水平面内に延び、粒子経路と、図面の平面内に対して垂直である。したがって、レーザビームの部分は、コリメートレンズによって、依然として、切頭されるものの、その結果得られる(図2に示される)偽ビームスポットBS1およびBS2は、粒子経路と整列して位置するのではなく、むしろ、今や粒子経路の両側に位置する。レーザダイオードのこの向きは、レーザビームの偏光面Pを水平面内に、粒子経路に対して垂直に向ける効果を有することに留意すべきである。したがって、ビームスポットBS1およびBS2は、フローセルを通過する粒子を照射する位置には、もはや位置しない一方で、ビームの偏光面が、ここでは、問題となる。

#### 【0014】

図4Aおよび図4Bを参照すると、ベクトルEによって示されるように、垂直なX/Z平面内で偏光される平面偏光ビームBによって照射される小粒子P'は、図示されるような水平なY/Z平面の光を散乱する役割を果たすことが、図4Aに示される。水平面での散乱光は、前方散乱FSH、側面散乱SSH、および全ての中間角度での前方散乱FSH'を含め、その垂直な偏光を維持し、水平面内での任意の角度で測定されるその強度は、照射粒子の物理的および光学的性質のみによって決定される。しかしながら、垂直なX/Z平面に前方に散乱される光の強度は、測定角 $\theta$ に依存し、角度 $\theta$ が、前方への散乱光が垂直上向き(または下向き)に導かれ、これによって前方への散乱光が垂直方向での側面散乱光SSVになる位置である、 $90^\circ$ (水平なY/Z平面に対して測定)に近づくにつれて、このような散乱光の強度は、示されるように、ゼロに近づくことに、留意されたい。実際、垂直な偏光面での波振動は、垂直な方向の散乱ビーム強度を相殺するように機能する。同様に、図4Bに示されるように、ビーム源が、 $90^\circ$ 回転し、その偏光面が、今や水平である、すなわち、Y/Z平面にあるような場合、垂直(X/Z)平面に散乱する

光の強度は、このビーム源の向きによる影響を受けないが、水平 (Y/Z) 平面に散乱された光は、測定がなされる角 $\beta$ に依存する。水平面内の側面散乱光SSHの強度は、角 $\beta$ が $90^\circ$ に近づくと、ゼロになることに、留意されたい。この情報を上述のフローサイトメータ環境に適用すると、側面散乱信号が、図3に示されるダイオードレーザの向きで検出されない理由が、理解される。そのように向くと、図4の散乱条件が適合し、検出する側面散乱信号が存在しない。

【0015】

以上の議論において、図5は、本発明が役立ち、本発明が具現化されるタイプのフローサイトメータ10を模式的に示す。図示されるように、本発明のフローサイトメータは、光学フローセルFCを含み、このフローセルFCを介して、特性調査されるべき種々の粒子P'を含む粒子サンプルPSが、流される。サンプルは、例えば、このサンプル内に、特性調査されるべき粒子が、様々なタイプの血球（例えば、単球、リンパ球、好塩基球など）の形で存在する血液全体のサンプルを備え得る。フローセルは、光学的に透明な筐体12を備え、筐体12は狭い中央チャネルを規定し、このチャネルを通過して、粒子が一度に一個ずつ流れ、その間に、レーザダイオードLDによって提供される集束レーザビームB'によって照射される。図示されるように、レーザダイオードは、その発散楕円出力ビームが、垂直平面内でよりも水平面内でより速く拡大するように向けられる。これによって、上述の偽ビームスポットは、図3を参照して上記で議論されたように、フローセルを通過する垂直な粒子の両側で、外側に位置する。粒子調査ゾーンZを通過し、集束レーザビームによって照射されると、各個々の粒子はビーム光を散乱し、照射された粒子のタイプに従って、蛍光放射を発する。前方散乱光14は、レンズ16によって収集され、適切な光検出器18上に集束され、光検出器18の出力FSは、マイクロプロセッサMPに加えられる。軸方向ビーム光は、適切な光ストップ20によって吸収される。側面散乱光22、すなわち、水平 (Y/Z) 平面内に $90^\circ$ で散乱されたビーム光は、選択された粒子によって運ばれる蛍光色素によって発せられるマルチカラーの蛍光24と一緒に、レンズ26によって収集され、コリメートされ、その結果得られたコリメートビーム28は、コリメートビーム経路に対して $45^\circ$ で配置された一対の二色性ミラー30、32にパスされるか、あるいは二色性ミラー30、32によって反射される。側面散乱光33は、ミラー30によって反射され、適切な光検出器34、典型的には光電子増幅管へと向かう。ミラー30を通過するか、透過し、ミラー32によって反射される第一の波長の蛍光35は、第二の光検出器36に導かれる。ここでもまた、第二の光検出器は、好ましくは、光電子増幅管である。ミラー30とミラー32との双方を通過する第二の波長の蛍光は、第三の光検出器40に導かれる。ここでもまた、第三の光検出器は、好ましくは、光電子増幅管のタイプのものである。光検出器34、36、および40のそれぞれの出力SS、FL1、およびFL2は、処理のために、マイクロプロセッサに供給される。フローセルを通過する各粒子から得られた光散乱信号および蛍光信号に加え、調査される各粒子のコルター体積を表すインピーダンス信号Zを検出することは、一般的である。このような信号は、フローセルの調査ゾーンを通過して定電流を通すことと、このゾーン内の粒子の電気インピーダンスによってもたらされる電流の変化をモニタすることとによって、導出される。粒子が大きければ大きいほど、電流の変化が大きい。粒子調査の両側に配置された一対の電極44、46の間に接続された定電流回路42は、そのゾーンを通過するのに必要な電流を提供し、このような電流内の粒子に由来する変化を検出するように動作する。回路42の出力Z'もまた、マイクロプロセッサに供給される。マイクロプロセッサが、FL1、FL2、SS、FS、およびZ'の入力信号を、1つ以上の公知のアルゴリズムに従って、同時に処理すると、マイクロプロセッサは、典型的には、複数の散布図SGの形式で、出力を提供する。散布図SGは、粒子サンプルPSの中の粒子の相対数と種々のタイプとを示す。

【0016】

上記で指摘されたように、図3を参照して議論されたように向けられたレーザダイオードには、レーザビームの偏光面Pが、粒子フローの方向に対して垂直であることにおいて

、問題がある。図5のフローサイトメータに示されるように、拡大楕円E'の長軸は、コリメートレンズ3を通過したコリメートビームの長軸がそうであるように、水平面内にある。ビームの偏光面Pは、長軸に平行であるので、図4Aは、水平面内における側面散乱放射が、水平面内の波面振動によって相殺されることを示す。したがって、本発明に従うと、光学素子50は、レーザビームB'の中に、好ましくは、コリメートレンズ3と円筒レンズ4との間のビームのコリメートされる部分の中に配置される。素子50は、ビームの偏光面を十分な量、回転することによって、レーザビームの偏光面が、フローセルを通過する（垂直な）粒子経路と、今や実質的に平行となるように、レーザビームの偏光面を向ける効果を有する。したがって、レーザダイオードを回転させて、望ましくない偽スポットを排除することのメリットは、側面散乱光を検出することを可能にすることのメリットと組み合わされる。なぜなら、偏光面は、このような側面散乱光を検出するために必要な向きにあるからである。好ましくは、素子50は、レーザビームの偏光面を90°回転させるように動作し、従来の半波長板の形式を採る。代替として、素子50は、タンデムに配置された2つの四分の一波長板の形式であり得る。

【0017】

本発明は、好ましい実施形態を参照して記載されてきたが、本発明の精神から逸脱することなく様々な変更がなされ得ることは、理解される。このような変更は、添付の請求項の範囲内に収まることを意図される。

【図面の簡単な説明】

【0018】

【図1】図1は、従来のレーザダイオードからの発散出力ビームを示す。


【図2】図2は、フローサイトメータの光学フローセル内の所望箇所で、発散レーザビームを集束するための従来技術の光学系の模式図である。

【図3】図3は、フローサイトメータの光学フローセル内の所望箇所で、発散レーザビームを集束するための従来技術の光学系の模式図である。


【図4】図4Aおよび図4Bは、平面偏光光源の偏光面における変化が、光散乱に与える影響を示す。

【図5】図5は、本発明を具現化するフローサイトメータの斜視模式図である。


【図1】

FIG. 1  
従来技術

【図2】

FIG. 2  
従来技術

【図3】

FIG. 3  
従来技術

【図4A】




FIG. 4A

【図4B】




FIG. 4B

【図5】




FIG. 5

## INTERNATIONAL SEARCH REPORT

International application No.

PCT/US06/09449

## A. CLASSIFICATION OF SUBJECT MATTER

IPC: G01N 21/00( 2006.01)

USPC: 356/73

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 356/73,336,342,369

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
NONEElectronic data base consulted during the international search (name of data base and, where practicable, search terms used)  
Please See Continuation Sheet

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category * | Citation of document, with indication, where appropriate, of the relevant passages   | Relevant to claim No. |
|------------|--------------------------------------------------------------------------------------|-----------------------|
| A          | US 5,798,827 A (FRANK et al.) 25 August 1998 (25.08.1998), see entire document.      | 1-12                  |
| A          | US 6,228,652 B1 (RODRIGUEZ et al.) 08 May 2001 (08.05.2001), see entire document.    | 1-12                  |
| A          | US 6,794,671 B2 (NICOLI et al.) 21 September 2004 (21.09.2004), see entire document. | 1-12                  |
| A,P        | US 2005/0112541 A1 (DURACK et al.) 26 May 2005 (26.05.2005), see entire document.    | 1-12                  |

☐ Further documents are listed in the continuation of Box C.☐ See patent family annex.

| * Special categories of cited documents:                                                                                                                                |                                                                                                                                                                                                                                                  |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| "A" document defining the general state of the art which is not considered to be of particular relevance                                                                | "T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention                                              |
| "B" earlier application or patent published on or after the international filing date                                                                                   | "X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone                                                                     |
| "L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | "Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art |
| "O" document referring to an oral disclosure, use, exhibition or other means                                                                                            | "&" document member of the same patent family                                                                                                                                                                                                    |
| "P" document published prior to the international filing date but later than the priority date claimed                                                                  |                                                                                                                                                                                                                                                  |

Date of the actual completion of the international search

21 June 2006 (21.06.2006)

Date of mailing of the international search report

07 JUL 2006

Name and mailing address of the ISA/US

Mail Stop PCT, Attn: ISA/US  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

Authorized officer

JOSE DEES

Telephone No. 571-272-1569

Facsimile No. (571) 273-3201

Form PCT/ISA/210 (second sheet) (April 2005)

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US06/09449

Continuation of B. FIELDS SEARCHED Item 3:  
USPGPUB, USPAT, USOCR, EPO, JPO, DERWENT, IBM\_TDB search notes: (cytomet\$3 and (flow adj cell) and laser and spot and  
(minor adj axis) and ((side adj scatter\$3) or side-scatter\$3) and (polarisation or polarization or polarized)) and @ad <= "20050330"



(81)指定国 AP(BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), EA(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), EP(AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, LV, MC, NL, PL, PT, RO, SE, SI, SK, TR), OA(BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG), AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, LY, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NG, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW

(72)発明者 ウェールズ, マーク エー.

アメリカ合衆国 フロリダ 33331, デービー, セネカ サークル 16245

Fターム(参考) 2G057 AA02 AA14 AB04 AB08 AC01 AC05 BA05

2G059 AA05 BB06 BB13 DD12 EE02 EE05 EE07 EE11 FF12 GG01

JJ07 JJ11 JJ13 JJ19 JJ20 KK02 KK03



Espacenet

Bibliographic data: JP2010085194 (A) — 2010-04-15

## SAMPLE ANALYZER

**Inventor(s):** KUSUZAWA HIDEO ± (KUSUZAWA HIDEO)**Applicant(s):** SYSMEX CORP ± (SYSMEX CORP)

**Classification:** - **international:** G01N15/14; G01N21/17; G01N21/64  
 - **cooperative:** G01N15/1425; G01N15/1434; G01N15/147;  
G01N2015/1497


**Application number:** JP20080253498 20080930 Global Dossier

**Priority number (s):** JP20080253498 20080930

**Also published as:** CN101713723 (A) EP2169382 (A2) US2010079762 (A1)

## Abstract of JP2010085194 (A)

PROBLEM TO BE SOLVED: To provide a sample analyzer capable of sharply imaging the contour of a particle of erythrocyte, or the like. ;SOLUTION: This sample analyzer 10 is equipped with a flow cell 30 for forming a sample flow, and an imaging system 24 for acquiring a particle image by imaging a particle contained in the sample flow in the flow cell 30. The imaging system 24 has a light source 61 for irradiating near ultraviolet light to the sample flow in the flow cell 30, and a camera 64 for imaging the particle in the sample flow irradiated with the near ultraviolet light from the light source 61. ;COPYRIGHT: (C)2010,JPO&INPIT



(19) 日本国特許庁(JP)

(12) 公開特許公報(A)

(11) 特許出願公開番号

特開2010-85194

(P2010-85194A)

(43) 公開日 平成22年4月15日(2010.4.15)

|                        |                |             |
|------------------------|----------------|-------------|
| (51) Int. Cl.          | F 1            | テーマコード (参考) |
| GO 1 N 15/14 (2006.01) | GO 1 N 15/14 D | 2 GO 4 3    |
| GO 1 N 21/17 (2006.01) | GO 1 N 21/17 A | 2 GO 5 9    |
| GO 1 N 21/64 (2006.01) | GO 1 N 21/64 Z |             |

審査請求 未請求 請求項の数 10 O L (全 14 頁)

(21) 出願番号 特願2008-253498 (P2008-253498)  
(22) 出願日 平成20年9月30日 (2008. 9. 30)

(71) 出願人 390014960  
シスメックス株式会社  
兵庫県神戸市中央区脇浜海岸通 1 丁目 5 番  
1 号  
(74) 代理人 110000280  
特許業務法人サンクレスト国際特許事務所  
(72) 発明者 楠澤 英夫  
兵庫県神戸市中央区脇浜海岸通 1 丁目 5 番  
1 号 シスメックス株式会社内  
F ターム (参考) 2G043 AA04 BA16 DA05 EA01 EA14  
FA06 HA09 JA02 KA02 KA03  
KA08 KA09 LA02 LA03 NA06

最終頁に続く


(54) 【発明の名称】 試料分析装置

## (57) 【要約】

【課題】 赤血球等の粒子の輪郭を鮮明に撮像することができる試料分析装置を提供する。

【解決手段】 試料分析装置 10 は、試料流を形成するためのフローセル 30 と、フローセル 30 中の試料流に含まれる粒子を撮像して粒子画像を取得するための撮像系 24 と、を備える。撮像系 24 は、フローセル 30 中の試料流に対して近紫外光を照射する光源 61 と、光源 61 の近紫外光が照射された試料流中の粒子を撮像するカメラ 64 と、を有する。

【選択図】 図 4



**【特許請求の範囲】****【請求項1】**

試料流を形成するためのフローセルと、  
前記フローセル中の試料流に対して近紫外光を照射する光源と、  
前記光源によって近紫外光が照射された試料流に含まれる粒子を撮像する撮像部と、備える試料分析装置。

**【請求項2】**

前記光源がパルス発光するように構成されている請求項1に記載の試料分析装置。

**【請求項3】**

前記フローセル中の前記試料流に含まれる粒子を検出するための粒子検出手段と、  
前記粒子検出手段によって粒子が検出された場合にその粒子を撮像するように前記撮像部を制御する撮像制御手段と、をさらに備えている請求項1又は2に記載の試料分析装置。

**【請求項4】**

前記粒子検出手段が、  
前記光源によって照射される近紫外光よりも長い波長の光を前記フローセル中の試料流に対して照射する第2の光源と、  
この第2の光源の照射光によって励起される粒子からの蛍光を受光する受光部と、を有している請求項3に記載の試料分析装置。

**【請求項5】**

前記光源、第2の光源および粒子検出手段は、前記光源からの近紫外光の照射によって励起された粒子からの蛍光によって粒子が検出されないように構成されている請求項4に記載の試料分析装置。

**【請求項6】**

表示部と、  
前記撮像部によって撮像された粒子画像を前記表示部に表示させる表示制御手段と、をさらに備えている請求項1～5のいずれか1つに記載の試料分析装置。

**【請求項7】**

前記表示制御手段は、前記撮像部によって粒子が撮像された場合に、前記表示部にその粒子の粒子画像を表示させるように構成されている請求項6に記載の試料分析装置。

**【請求項8】**

前記フローセルと前記撮像部との間に配置され、かつ近紫外光を選別して透過させるように構成された光選別部をさらに備える請求項1～7のいずれか1つに記載の試料分析装置。

**【請求項9】**

前記光源と前記フローセルとの間に配置された照明レンズ系と、前記フローセルと前記撮像部との間に配置された撮像レンズ系とをさらに備え、

前記照明レンズ系の開口数が前記撮像レンズ系の開口数と同等又は前記開口数よりも小さく設定されている請求項1～8のいずれか1つに記載の試料分析装置。

**【請求項10】**

前記撮像制御手段は、前記粒子検出手段によって変形赤血球が検出された場合に、その変形赤血球を撮像するように前記撮像部を制御する請求項3に記載の試料分析装置。

**【発明の詳細な説明】****【技術分野】****【0001】**

本発明は、例えば尿や血液などの試料を分析するための試料分析装置に関する。

**【背景技術】****【0002】**

従来、撮像機能を有するフローサイトメータが知られている。例えば、下記特許文献1には、粒子含有試料を試料流に変換するシースフローセルと、近赤外光で前記試料流を照

明する近赤外光源と、近赤外光で照明された試料流中の粒子を撮像する撮像器と、撮像された粒子像を画像処理する画像処理部を備えた撮像機能付きフローサイトメータが開示されている。

【特許文献1】特開平10-73528号公報

【発明の開示】

【発明が解決しようとする課題】

【0003】

特許文献1に記載のフローサイトメータは、試料流を照明する光源として近赤外光源が用いられており、この近赤外光源から照明される近赤外光は粒子に対する透過性が高いため、粒子内部の状態を好適に撮像することが可能である。したがって、例えば、試料に含まれる細胞の核部分等を撮像するのに適している。

その反面、近赤外光を用いると、背景像と粒子像とのコントラストが明瞭に現れず、粒子の輪郭がぼやけしまうことがあった。

【0004】

本発明は、上記課題に鑑みてなされたものであり、赤血球等の粒子の輪郭を鮮明に撮像することができる試料分析装置を提供することを目的とする。

【課題を解決するための手段】

【0005】

本発明は、試料流を形成するためのフローセルと、前記フローセル中の試料流に対して近紫外光を照射する光源と、前記光源によって近紫外光が照射された試料流に含まれる粒子を撮像する撮像部と、を備えることを特徴とする。

以上のように光源の照射光を近紫外光とすると、当該照射光が粒子に照射されたときの散乱効率が向上する。つまり、近紫外光は粒子に対する透過性が低いため、粒子が存在する部分では光が透過せずに暗く映り、粒子の周囲の背景部分は明るく映る。このため、粒子像と背景像とのコントラストが明瞭となり、粒子の輪郭が鮮明に現れた粒子画像を得ることができる。

【0006】

本発明の試料分析装置は、近紫外光源がパルス発光するように構成されていることが好ましい。これにより、フローセルを流れる粒子を瞬間的に照射、撮像することができるため、粒子像が試料流方向に伸びたりすることがなく、実際の粒子形状に近い粒子像を得ることができる。

【0007】

本発明の試料分析装置は、前記フローセル中の前記試料流に含まれる粒子を検出するための粒子検出手段と、前記粒子検出手段によって粒子が検出された場合にその粒子を撮像するように前記撮像部を制御する撮像制御手段と、をさらに備えていることが好ましい。

この場合、粒子が粒子検出手段によって検出されたときだけ、その粒子を撮像部によって撮像することが可能となる。したがって、フローセルを粒子が通過した場合にのみその粒子を撮像するので、試料に含まれる粒子の画像のみを得ることができる。

なお、撮像制御手段は、粒子検出手段によって変形赤血球が検出された場合に、撮像部によってその変形赤血球を撮像するように構成することができる。本発明による試料分析装置は、上記のとおり光源として近紫外光を照射可能な光源を備えているため、試料中に含まれる変形赤血球を自動的に検出し、輪郭が鮮明に撮像された変形赤血球の画像を得ることができる。これにより、臨床的意義の高い変形赤血球の変形の形態等を把握し、あるいはその変形の程度によってその変形赤血球の由来（生体試料に混入した部位）を知るための有用な臨床情報を得ることができる。

【0008】

前記粒子検出手段は、前記光源によって照射される近紫外光よりも長い波長の光を前記フローセル中の試料流に対して照射する第2の光源と、この第2の光源の照射光によって励起される粒子からの蛍光を受光する受光部と、を有していることが好ましい。

一般に、粒子に光を照射することによって励起される蛍光は、照射した光の波長よりも

長くなることが知られている。本発明のように第2の光源として近紫外光よりも波長の長いものを使用すると、第2の光源の照射光により粒子から発せられる蛍光と、近紫外光源によって発せられる蛍光波長帯の差を大きくすることができる。したがって、近紫外光源から発せられた光と、第2の光源によって粒子から発せられた蛍光とが重複する場合であっても、2つの光源からの光をフィルタ等を用いることによって正確に選別することができる。よって、撮像部や受光部に対してそれぞれ適切な波長の光を受光させることが可能となり、鮮明な粒子画像や正確な検出データを得ることができる。

【0009】

さらに、前記近紫外光源、第2の光源および粒子検出手段は、近紫外光源からの近紫外光の照射によって励起された粒子からの蛍光によって粒子が検出されないように構成されていることが好ましい。

このような構成とすることにより、近紫外光源の発光によって粒子検出手段に影響を及ぼすことがなく、粒子を正確に検出することができる。

【0010】

本発明の試料分析装置は、表示部と、前記撮像部によって撮像された粒子画像を前記表示部に表示させる表示制御手段と、をさらに備えていることが好ましい。また、前記表示制御手段は、前記撮像部によって粒子が撮像された場合に前記表示部にその粒子の粒子画像を表示させるように構成されていてもよい。

このような構成を採用することによって、撮像部によって撮像された粒子画像を、表示部を介して目視により確認することができる。

【0011】

本発明の試料分析装置は、前記フローセルと前記撮像部との間に配置され、かつ近紫外光を選別して透過させるように構成された光選別部をさらに備えることが好ましい。これによって、近紫外光源から照射された近紫外光以外の光を遮り、輪郭が鮮明に現れた粒子画像を確実に取得することができる。

【0012】

本発明の試料分析装置は、前記光源と前記フローセルとの間に配置された照明レンズ系と、前記フローセルと前記撮像部との間に配置された撮像レンズ系とを備えていてもよい。この場合、前記照明レンズ系の開口数が前記撮像レンズ系の開口数と同等又は前記開口数よりも小さく設定されていることが好ましい。

このような構成を採用することによって、粒子の輪郭部に生じる回折散乱縞の少ない鮮明な粒子画像を撮像することができる。

【発明の効果】

【0013】

本発明の試料分析装置によれば、輪郭が明瞭な粒子画像を取得することができる。

【発明を実施するための最良の形態】

【0014】

図1は、本発明の実施形態に係る試料分析装置の斜視図、図2は、試料分析装置の全体構成を示すブロック図である。本実施形態においては、試料分析装置10として、尿中有形成成分分析装置を例にとり説明する。

【0015】

〔試料分析装置の全体構成〕

図1に示すように、尿中有形成成分分析装置（以下、単に分析装置という）10は、搬送部11と、試料の測定等を行う測定部12と、この測定部12に接続され、測定結果の分析等を行うシステム制御部13とを備え、搬送部11によって移送されたラック31の試験管32から試料としての尿を吸引し、この尿から有形成分や細菌等の粒子の情報を検出、分析するように構成されている。

【0016】

図2に示すように、分析装置10の測定部12は、試験管32（図1）に収容された尿から試料を調製するための試料調製部14と、試料中の有形成分や細菌等を検出し、検出

された粒子の特徴に応じた電気信号をアナログ信号処理回路16へ出力するための光学検出部(粒子検出手段)15と、光学検出部15からの出力の増幅やフィルタ処理等を行うアナログ信号処理回路16と、アナログ信号処理回路16の出力をデジタル信号に変換するA/Dコンバータ17と、デジタル信号に対して所定の波形処理を行うデジタル信号処理回路18と、デジタル信号処理回路18と接続されたマイクロコンピュータ20と、マイクロコンピュータ20に接続されたLANアダプタ21とを備えている。システム制御部13を構成するパソコン(PC)13は、このLANアダプタ21を介して測定部12とLAN接続されており、このパソコン13により、測定部12で取得したデータの解析が行われる。アナログ信号処理回路16、A/Dコンバータ17、及びデジタル信号処理回路18は、光学検出部5が出力する電気信号を処理するための信号処理部22を構成している。

#### 【0017】

さらに、測定部12は、デジタル信号処理回路18に接続された撮像制御手段23と、この撮像制御手段23によって試料から粒子(有形成分)を撮像するように制御される撮像系24とを備えている。撮像制御手段23は、CPUやRAM、ROM等のメモリを有する前記マイクロコンピュータ20の一機能部として構成されている。

#### 【0018】

##### 〔試料調製部の概略構成〕

図3は試料調製部14及び光学検出部15の構成を示す概略図である。試験管32に入った尿(検体)は、吸引管26を用いて図示しないシリンジポンプにより吸引され、試料調製部14へ分注される。本実施形態における試料調製部14は第1試料調製部14uと第2試料調製部14bとで構成されており、これら第1、第2試料調製部14u、14bのそれぞれに尿の定量されたアリコートが分配される。

#### 【0019】

第1試料調製部14uの尿アリコートは、希釈液27uと染色液(染色試薬)28uが混合されて当該染色液28uに含まれる色素により染色が施される。この染色試料は赤血球、白血球、上皮細胞、円柱等の比較的大きい尿中有形成分を分析するための懸濁液となる。

一方、第2試料調製部14bの尿アリコートは、希釈液27bと染色液(染色試薬)28bが混合されて当該染色液28bに含まれる色素により染色が施される。この染色試料は細菌を分析するための懸濁液となる。

#### 【0020】

以上のようにして調製された2種類の懸濁液(試料)は、先に第1試料調製部14uの懸濁液(第1の試料)が光学検出部15に導かれ、シースフローセル30においてシース液に包まれた細い流れを形成し、そこに、光源からの光が照射される。その後同様に、第2試料調製部14bの懸濁液(第2の試料)が光学検出部15に導かれ、シースフローセル30において細い流れを形成し、光源からの光が照射される。以上のような各動作は、マイクロコンピュータ20(制御部)の制御によって図示しない駆動部や電磁弁等を動作させることにより、自動的に行われる。

#### 【0021】

##### 〔光学検出部及び撮像系の構成〕

図4は、光学検出部15及び撮像系24の構成を示す模式図である。光学検出部15は、半導体レーザからなる光源41、光源41の光をシースフローセル30に集光するためのコンデンサレンズ42、シースフローセル30を流れる試料中の粒子からの前方散乱光を受光する第1受光部としてのフォトダイオード43、この前方散乱光をフォトダイオード43に集光するための集光レンズ44を備えている。本実施形態の光源41には、640nm付近にピーク波長を有する赤色光を発光する半導体レーザが用いられている。なお、光源41として、前記半導体レーザに代えて、ガスレーザや発光ダイオードを用いることもできる。

#### 【0022】

光学検出部15は、シースフローセル30を流れる試料中の粒子からの側方蛍光及び側方散乱光を平行光に変換するコリメータレンズ45、この平行光を反射させる第1ダイクロイックミラー46、第1ダイクロイックミラー46によって反射された側方蛍光及び側方散乱光を集光する対物レンズ47、対物レンズ47を透過した側方蛍光をさらに透過し、側方散乱光を反射させる第2ダイクロイックミラー48、第2ダイクロイックミラー48を透過した側方蛍光を受光する第2受光部としてのフォトマルチプライヤ49、第2ダイクロイックミラー48で反射された側方散乱光を受光する第3受光部としてのフォトマルチプライヤ50を備えている。

【0023】

光学検出部15のフォトダイオード43及びフォトマルチプライヤ49、50によって受光された光はそれぞれ電気信号に変換され、前方散乱光信号、側方散乱光信号、及び側方蛍光信号として信号処理部22（図2参照）に入力され、信号処理部22において所定の処理がなされた後、検出データ（検出信号）としてマイクロコンピュータ20のメモリに格納される。また、この検出データは、LANアダプタ21を介してシステム制御部13を構成するパソコンに送信され、パソコン13において解析される。

【0024】

一方、撮像系24は、図4に示すように、光学検出部15の光源41の光軸に対して上面視で90度交差した光軸を有する光源61を備えている。この光源61は、光学検出部15の光源41よりも短い波長の光、具体的には385nm付近にピーク波長を有する光を発光する発光ダイオードが用いられている。また、撮像系24の光源61の光軸は、光学検出部15の光源41の光軸よりも試料流方向のやや下流側に配置されている。

なお、光源61は近紫外域にピーク波長を有する光を発光する光源であればよく、例えば200nm～400nmの間にピーク波長を有する光を発光する光源を用いることができる。

【0025】

光源61はパルス発光するように制御され、好ましくは100ns以下の発光時間で発光するように制御される。これにより、シースフローセル30を流れる粒子を瞬間的に照射して撮像することができる。粒子を瞬間的に照射して撮像することには、次のような利点がある。すなわち、シースフローセル30に向かって光を照射し続けると、フローセルを高速で流れる粒子が試料流の方向に伸びた像となって撮像されてしまうことがあるが、粒子を瞬間的に照射して撮像することで、実際の粒子の形状に近い、正確な粒子像を撮像することができる。

発光ダイオードをパルス発光させるための駆動回路としては、例えば特開2005-269051号公報に記載の回路を用いることができる。

【0026】

さらに、撮像系24は、光源61の近紫外光をシースフローセル30に集光する照明レンズ系62と、シースフローセル30を流れる試料中の粒子を撮像する撮像部としてのCCDカメラ64と、シースフローセル30に照射された近紫外光をカメラ64に入射させる撮像レンズ系63とを備えている。

照明レンズ系62は、コリメータレンズ65及び集光レンズ66を備え、コリメータレンズ65は、光源61の近紫外光を平行光に変換し、集光レンズ66はこの平行光をシースフローセル30に集光する。また、コリメータレンズ65と集光レンズ66との間には、照明レンズ系62の開口数（NA）を所定に設定するアイリス（絞り部）67が設けられている。本実施形態のアイリス67は、照明レンズ系62の開口数を0.4に設定するものとされている。

【0027】

撮像レンズ系63は、コリメータレンズ45と結像レンズ69とを備えており、コリメータレンズ45は、シースフローセル30を透過した光を平行光に変換する。このコリメータレンズ45は、光学検出部15の光源41による粒子からの側方散乱光及び側方蛍光を平行光に変換するものが兼用されている。



結像レンズ69は、第1ダイクロイックミラー46を透過した近紫外光を集光し、カメラ64の受光面に結像する。

【0028】

また、コリメータレンズ45と結像レンズ69との間には、可視光を遮るカットフィルタ70と、近紫外光のみを透過するバンドパスフィルタ（光選別部）71とが設けられている。このカットフィルタ70とバンドパスフィルタ71とによってカメラ64には確実に近紫外光が入射するようになっている。

【0029】

撮像レンズ系63の開口数は、照明レンズ系62の開口数よりも大きい値に設定されている。具体的に、照明レンズ系62の開口数はアイリス67によって0.4に設定されているので、撮像レンズ系63の開口数はこれよりも大きい値、例えば0.55に設定される。このように撮像レンズ系63の開口数を照明レンズ系62の開口数よりも大きい値に設定することによって、照明レンズ系62を経てシースフローセル30に照射された近紫外光は撮像レンズ系63のコリメータレンズ45や結像レンズ69の中心部分のみを透過することになる。このため、各レンズ45、69の収差等の影響が小さくなり、ボケや歪み等の少ない良好な粒子画像を得ることが可能となる。さらに、粒子の輪郭部分の回折散乱縞が少なくなり、鮮明な粒子画像を得ることができる。

【0030】

光学検出部15の光源41は640nm付近にピーク波長を有する赤色光を照射し、撮像系24の光源61は385nm付近にピーク波長を有する光（近紫外光）を照射する。そして、光学検出部15の光源41による粒子からの側方蛍光及び側方散乱光は、撮像系24の光源61の近紫外光と平行な光となり、これらは互いに重複する。また、光学検出部15の光源41による粒子からの側方散乱光は、当該光源41と同一のピーク波長（約640nm）を有するのに対して、側方蛍光は、これよりも長い波長（例えば約660～800nm）となる。

【0031】

そのため、本実施形態では、第1ダイクロイックミラー46として、波長が370～400nmの近紫外光を透過し、それ以外の波長の光を反射するものが用いられており、カメラ64側には近紫外光以外の光が入射しないように構成されている。また、第2ダイクロイックミラー48は、波長が660～800nmの光を透過し、それ以外の波長の光を反射するものが用いられており、フォトマルチプライヤ49には、側方蛍光以外の光が入射しないように構成されている。

【0032】

なお、フォトマルチプライヤ50には、370～400nm及び660～800nmの波長を除く波長の光が入射する可能性があり、撮像系24の光源61から比較的波長の短い光（例えば、400～420nm程度）が入射することも考えられるので、フォトマルチプライヤ50の手前には、光学検出部15の光源41による粒子の側方散乱光のみを入射させるべく、約640nm波長付近の光を透過するバンドパスフィルタ51を設けておくことが望ましい。

【0033】

光学検出部15は、試料流中の粒子の前方散乱光、側方散乱光、及び側方蛍光を検出し、これらの検出信号は信号処理部22を介してマイクロコンピュータ20へ入力される。そして、マイクロコンピュータ20の一機能部である撮像制御手段23は、入力された検出信号に応じて粒子画像を撮像するように撮像系24を制御している。

【0034】

一般に、光学検出部15によって取得される前方散乱光、側方散乱光、及び側方蛍光は、その信号の強度によって赤血球、白血球、上皮細胞等の粒子の種類や大きさを判別できることが知られている。そして、本実施形態の撮像制御手段23は、光学検出部15の検出信号から粒子の種類や大きさを判別し、その粒子が予め定められた所定の粒子であると判断した場合に撮像系24によって当該粒子を撮像し、所定の粒子以外の粒子であると判

断した場合には、その粒子は撮像しない（光源6 1を発光しない）ように構成されている。

【0035】

なお、撮像系2 4によって撮像された粒子画像のデータは、マイクロコンピュータ2 0のメモリに格納される。また、粒子画像のデータは、LANアダプタ2 1を介してシステム制御部を構成するパソコン1 3に送信され、当該パソコン1 3において所定の処理がなされる。

【0036】

ここで、撮像系2 4の光源6 1、光学検出部1 5の光源4 1および光学検出部1 5は、撮像系2 4の光源6 1からの近紫外光の照射によって励起された粒子からの蛍光によって、粒子が検出されないように構成されている。具体的には、次のように構成されている。

光学検出部1 5は、光源4 1によって照射された粒子からの蛍光に基づいて、その粒子を検出可能な光量に対する閾値が予め設定されている。撮像系2 4の光源6 1は、光源6 1が近紫外光を照射することによって励起された粒子からの蛍光の光量が上記閾値未満となるように、その光量が調整されている。

このような構成とすることにより、光源6 1の発光によって光学検出部1 5に影響を及ぼすことがなく、正確に粒子を検出することができる。

【0037】

〔システム制御部の構成〕

図5は、システム制御部1 3のブロック図である。システム制御部1 3は、パーソナルコンピュータ等よりなり、制御部本体7 1と、表示部7 2と、入力部7 3とから主構成されている。制御部本体7 1は、CPU7 1 aと、ROM7 1 bと、RAM7 1 cと、ハードディスク7 1 dと、読出装置7 1 eと、入出力インターフェース7 1 fと、画像出力インターフェース7 1 gと、通信インターフェース7 1 iから主構成されている。これらの間は、バス7 1 hによって通信可能に接続されている。

【0038】

CPU7 1 aは、ROM7 1 bに記憶されているコンピュータプログラム及びRAM7 1 cにロードされたコンピュータプログラムを実行することが可能である。ROM7 1 bは、マスクROM、PROM、EPROM、EEPROM等によって構成されており、CPU7 1 aに実行されるコンピュータプログラム及びこれに用いるデータ等が格納されている。RAM7 1 cは、SRAM又はDRAMなどによって構成されている。RAM7 1 cは、ROM7 1 b及びハードディスク7 1 dに記録されているコンピュータプログラムの読み出しに用いられる。また、これらのコンピュータプログラムを実行するときに、CPU7 1 aの作業領域として利用される。

【0039】

ハードディスク7 1 dは、オペレーティングシステム及びアプリケーションプログラムなど、CPU7 1 aに実行させるための種々のコンピュータプログラム及びそのコンピュータプログラムの実行に用いるデータがインストールされている。例えば、ハードディスク7 1 dには、米マイクロソフト社が製造販売するWindows（登録商標）等のグラフィカルユーザーインターフェース環境を提供するオペレーティングシステムがインストールされている。

【0040】

また、ハードディスク7 1 dには、測定部1 2への測定オーダ（動作命令）の送信、測定部1 2で測定した測定結果の受信及び処理、処理した分析結果の表示等を行う操作プログラムがインストールされている。この操作プログラムは、当該オペレーティングシステム上で動作するものとしている。

【0041】

読出装置7 1 eは、フレキシブルディスクドライブ、CD-ROMドライブ、又はDVD-ROMドライブなどによって構成されており、可搬型記録媒体に記録されたコンピュ

ータプログラム又はデータを読み出すことができる。入出力インターフェース71 fは、例えば、USB、IEEE1394、RS-232Cなどのシリアルインターフェース、SCSI、IDE、IEEE1284などのパラレルインターフェース、及びD/A変換器、A/D変換器などからなるアナログインターフェースなどから構成されている。入出力インターフェース71 fには、キーボード及びマウスからなる入力部73やプリンタ等の出力デバイス74が接続されている。そして、ユーザーが入力部29を使用することにより、パーソナルコンピュータにデータを入力することが可能である。通信インターフェース71 iは測定部12と接続されており、測定部12との間でデータ等の送受信を行うことが可能である。

【0042】

画像出力インターフェース71 gは、LCD又はCRTなどで構成された表示部72に接続されており、CPU71 aから与えられた画像データに応じた映像信号を表示部28に出力するようになっている。表示部28は、入力された映像信号にしたがって、画像（画面）を表示する。

【0043】

システム制御部13には、測定部12の信号処理部22で処理された前方散乱光信号、側方散乱光信号、及び側方蛍光信号がマイクロコンピュータ20によってLANアダプタ21を介して送信される。システム制御部13では、前方散乱光信号、側方散乱光信号、及び側方蛍光信号に基づいて、試料中の粒子が赤血球、白血球、上皮細胞、円柱、細菌等に分類される。また、システム制御部13は、尿中の粒子（有形成分）を分析するためのスキュッタグラムを作成し、このスキュッタグラムは表示部72に表示される。また、システム制御部13には、撮像系24により撮像された所定の粒子の画像データがマイクロコンピュータ20によってLANアダプタ21を介して送信され、この画像データはシステム制御部13の表示部72に表示される。

【0044】

〔粒子の撮像処理手順〕

以下、撮像系24によって所定の粒子（本実施形態では変形赤血球）を撮像するための手順について説明する。図6は、当該手順を示すフローチャートである。

図6のステップS1では、システム制御部（PC）13によって、測定開始の指示が受け付けられたか否かが判断される。この測定開始の指示は、オペレータが入力部73（図5参照）を構成するキーボードやマウスを操作することによって行われる。システム制御部13は、測定開始の指示が受け付けられたと判断すると（Yes）、測定部12のマイクロコンピュータ20に対して測定開始信号を送信する（ステップS2）。

【0045】

測定部12のマイクロコンピュータ（制御部）20は、システム制御部13から送信された測定開始信号が受信されたか否かを判断する（ステップS11）。マイクロコンピュータ20は、測定開始信号が受信されたと判断すると（Yes）、試料を調製してシースフローセル30に試料流を形成させるように試料調製部14を制御する（ステップS12、S13）。

【0046】

ついで、ステップS14において、測定部12のマイクロコンピュータ20は、光源41によってシースフローセル30に光を照射し、フォトダイオード43及びフォトマルチプライヤ49、50によって試料流中の粒子からの前方散乱光、側方散乱光、側方蛍光を受光するように光学検出部15を制御する。フォトダイオード43及びフォトマルチプライヤ49、50によって光が受光されると、受光された光に基づく電気信号が信号処理部22によって処理される。信号処理部22によって処理された電気信号は、検出信号としてマイクロコンピュータ20に入力され、メモリに格納される。マイクロコンピュータ20は、撮像制御手段23によって、当該検出信号が所定の粒子、すなわち変形赤血球の検出信号であるか否かを判断する（ステップS15）。具体的には、マイクロコンピュータ20は、光学検出部15によって検出された粒子に基づく検出信号が赤血球に特有の信号

強度であり、かつ正常な赤血球よりも小さい粒子からの信号であると判断した場合に、その検出信号が変形赤血球から得られた信号であると判断する。

そして、マイクロコンピュータ20は、当該検出信号が変形赤血球の検出信号であると判断した場合（Yes）にステップS16へ処理を進め、変形赤血球の検出信号ではないと判断した場合（No）にステップS17へ処理を進める。

【0047】

ステップS16において、マイクロコンピュータ20は、粒子画像を撮像するように撮像系24（光源61、カメラ64）を制御する。具体的には、マイクロコンピュータ20は、撮像系24の光源61を発光する制御を実行し、撮像系24の光源61が発光したタイミングでカメラ64によってフローセル中の画像を取り込む制御を実行する。そして、カメラ64によって撮像された粒子画像のデータはマイクロコンピュータ20のメモリに格納される。

【0048】

ステップS17において、測定部12のマイクロコンピュータ20によってシースフローセル30内の試料流が終了しているか否かが判断され、マイクロコンピュータ20は、シースフローセル30内の試料流が終了していないと判断した場合（No）にはステップS14に処理を戻し、シースフローセル30内の試料流が終了していると判断した場合（Yes）にはステップS18へ処理を進める。

【0049】

ステップS18において、測定部12のマイクロコンピュータ20は、メモリに格納してある光学検出部15による検出信号のデータや撮像系24による粒子画像のデータをシステム制御部13に送信し、処理を終了する。

ステップS3において、システム制御部13の制御部本体71によって、測定部12からのデータが受信されたか否かが判断され、システム制御部13の制御部本体71は、データが受信されたと判断すると（Yes）、ステップS4へ処理を進める。

【0050】

ステップS4において、システム制御部13は、受信したデータの解析を行う。そして、システム制御部13は、測定部12から送信されたデータの中に粒子画像のデータが含まれているか否かを判断し（ステップS5）、粒子画像データが含まれていると判断した場合（Yes）には、その粒子画像を表示部72に表示させ（ステップS6）、処理を終了する。

【0051】

以上説明したように、本実施形態では、撮像系24の光源61として、近紫外光源が用いられている。近紫外光は、可視光や近赤外光に比べて波長が短いので、粒子に対する透過性が低く、散乱効率が低い。したがって、近紫外光が照射された粒子の部分は近紫外光が強く散乱してカメラ64には暗く撮像され、粒子の周囲では近紫外光が散乱しないので明るく撮像される。この作用によって粒子とその背景とのコントラストが明瞭で、粒子の輪郭が鮮明に現れた画像を得ることができる。

【0052】

また、例えば光源として近赤外光を用いた場合には、光学分解能を上げるために高開口数のレンズを使用する必要があり、焦点深度が浅くなるため、焦点深度内に粒子が収まるようにフローセルを狭窄化しなければならず、単位時間あたりに処理できるサンプル量が少なくなってしまう。

この点、本実施形態では、近赤外光より波長の短い近紫外光を用いたことにより、高開口数のレンズを使用したとしても十分な焦点深度をとることができ、フローセルを狭める必要がない。

【0053】

一般に、血尿、特に糸球体性の血尿に含まれる赤血球には変形が見られ、その変形の態様もこぶ状、ねじれ状等多様である。そのため、試料としての尿に含まれる変形赤血球を判別するには、当該赤血球の輪郭を正確に捉えることが要求される。この点、本実施形態

のように撮像系24の光源61として近紫外光源を用いれば、撮像された粒子が変形赤血球であるか否かという判断や、変形赤血球の形態の判断を正確に行うことが可能となり、粒子画像を腎臓疾患等の診断に有効に役立てることができる。

特に、変形赤血球のうち、脱ヘモグロビン化された赤血球（ゴースト赤血球）は、その粒子像のコントラストが現れにくい。そこで、このようなゴースト赤血球を撮像する場合に、光源として近紫外光を用いた本実施形態の試料分析装置を用いることで、粒子の輪郭が明確なゴースト赤血球の粒子画像を得ることができる。

【0054】

なお、光学検出部15の光源41には赤色光源が用いられているが、この光源41の光が照射された粒子によって励起される側方蛍光は、当該光源41の光よりも波長が長くなる。このため、本実施形態では、撮像系24の光源61として光学検出部15の光源41よりも波長の短い近紫外光源を用いることによって、撮像系24の光源61の近紫外光と、光学検出部15の光源41による粒子の側方蛍光との波長の差が大きくなるように構成してある。これにより、図4に示すように、撮像系24の光源61の近紫外光と、粒子の側方蛍光とは互いに平行な重複する光となるが、これらの波長の差が大きいために、第1ダイクロイックミラー46を用いて適切に選別することができる。

【0055】

本発明は上記実施の形態に限定されるものではなく適宜設計変更可能である。

例えば、本発明の試料分析装置は、尿中有形成成分分析装置に限らず、血液分析装置等の他の試料分析装置にも適用することができる。また、撮像系によって撮像する粒子は赤血球に限定されるものではなく、白血球や上皮細胞等、近紫外光源を用いて撮像することが可能なあらゆる粒子を対象とすることができる。撮像系の光源は、発光ダイオードに限らず半導体レーザを用いることも可能である。

【図面の簡単な説明】

【0056】

【図1】本発明の実施形態に係る尿中有形成成分分析装置（試料分析装置）を示す斜視図である。

【図2】尿中有形成成分分析装置の全体構成を示すブロック図である。

【図3】試料調製部の概略構成図である。

【図4】光学検出部及び撮像系の構成を示す模式図である。

【図5】システム制御部のブロック図である。


【図6】粒子画像の撮像処理手順を示すフローチャートである。

【符号の説明】


【0057】

- 10 試料分析装置
- 12 測定部
- 13 システム制御部
- 15 光学検出部
- 20 マイクロコンピュータ
- 23 撮像制御手段
- 24 撮像系
- 30 シースフローセル
- 41 光源（第2の光源）
- 49 フォトマルチプライヤ（受光部）
- 61 光源
- 62 照明レンズ系
- 63 撮像レンズ系
- 64 CCDカメラ（撮像部）


【図1】




【図2】




【図3】




【図4】



【図5】



【図6】



F ターム(参考) 2G059 AA05 BB13 BB14 CC16 DD12 EE01 EE02 EE07 EE11 FF01  
FF03 FF12 GG01 GG02 GG03 GG08 HH02 HH03 HH06 JJ02  
JJ07 JJ11 KK02 KK03 KK04 MM10 PP04





Espacenet

**Bibliographic data: JPH03197641 (A) — 1991-08-29**


---

**LEAD FRAME MATERIAL**

**Inventor(s):** ETO MASATOSHI; YUKI NORIO ± (ETO MASATOSHI, ; YUKI NORIO)

**Applicant(s):** NIPPON MINING CO ± (NIPPON MINING CO LTD)

**Classification:** - **international:** **C22C19/05; C22C38/00; C22C38/10; C22C38/58; H01L23/48;** (IPC1-7): C22C19/05; C22C38/00; C22C38/10; C22C38/58; H01L23/48

- **cooperative:**

**Application number:** JP19890337768 19891226

**Priority number (s):** JP19890337768 19891226

**Abstract of JPH03197641 (A)**

**PURPOSE:** To obtain a high strength lead frame material excellent in etching characteristic and sealing characteristic by specifying a composition consisting of C, Si, P, S, O, N, Co, Ni, elements for improving strength and thermal expansion coefficient, such as Cu, and Fe. **CONSTITUTION:** A lead frame material having high strength and hardness and excellent in etching characteristic, sealing characteristic, and formability can be obtained by providing a composition which consists of, by weight,  $\leq 0.015\%$ , preferably  $\leq 0.005\%$ , of C,  $0.001-0.15\%$ , preferably  $0.001-0.05\%$ , of Si,  $\leq 0.01\%$ , preferably  $\leq 0.003\%$ , of P,  $\leq 0.005\%$  S,  $\leq 0.010\%$  O,  $\leq 0.005\%$  N,  $5-30\%$  Co,  $15-55\%$  Ni, further  $0.01-5.0\%$  of one or more elements among Cu, Mn, Cr, Mo, W, V, Nb, Ta, Ti, Zr, Hf, B, Be, Mg, and Ca, and the balance Fe with inevitable impurities and also providing a structure in which crystalline grain size at the time of the final annealing is regulated, preferably, to  $\leq 50\mu\text{m}$ .

## ⑫ 公開特許公報(A) 平3-197641

⑤Int. Cl.<sup>5</sup>

識別記号

庁内整理番号

⑬公開 平成3年(1991)8月29日

C 22 C 38/00  
19/05  
38/10  
38/58  
H 01 L 23/48Z  
J 7047-4K  
8928-4K

V 9054-5F

審査請求 未請求 請求項の数 5 (全6頁)

⑭発明の名称 リードフレーム材

⑯特 願 平1-337768

⑰出 願 平1(1989)12月26日

⑱発 明 者 衛 藤 雅 俊 神奈川県高座郡寒川町倉見3番地 日本鋳業株式会社倉見工場内

⑲発 明 者 結 城 典 夫 神奈川県高座郡寒川町倉見3番地 日本鋳業株式会社倉見工場内

⑳出 願 人 日本鋳業株式会社 東京都港区虎ノ門2丁目10番1号

㉑代 理 人 弁理士 今 井 毅

## 明 細 書

## 1. 発明の名称

リードフレーム材

## 2. 特許請求の範囲

## (1) 重量割合にて

C: 0.015%以下, Si: 0.001~0.15%,

P: 0.01%以下, S: 0.005%以下,

O: 0.010%以下, N: 0.005%以下,

Co: 5~30%, Ni: 15~55%

であって、更にCu, Mn, Cr, Mo, W, V, Nb, Ta, Ti, Zr, Hf, B, Be, Mg及びCaの1種以上をも合計で0.01~5.0%含むと共に、残部がFe及び不可避免の不純物から成ることを特徴とする、エッチング加工性及び封着性に優れた高強度リードフレーム材。

(2) C含有量が0.005重量%以下である、請求項1に記載のリードフレーム材。

(3) Si含有量が0.001~0.05重量%である、請求

項1又は2に記載のリードフレーム材。

(4) P含有量が0.003重量%以下である、請求項1乃至3の何れかに記載のリードフレーム材。

(5) 最終焼鈍時の結晶粒径が50 $\mu$ m以下である、請求項1乃至4の何れかに記載のリードフレーム材。

## 3. 発明の詳細な説明

## 〈産業上の利用分野〉

この発明は、エッチング加工性、封着性並びに成形加工性に優れ、かつ強度の高いリードフレーム材に関するものである。

## 〈背景技術とその課題〉

一般に、半導体機器類においてはリード材の特性もその性能やコストに大きな影響を及ぼすことが知られているが、このような半導体機器のリード材としては、従来から、熱膨張係数が低く、かつ半導体素子やセラミックスと比較的良好な接着性、封着性を示すFe-Ni系合金が好んで使用されてきた。

ところが、最近、一段と加速の割合を増してきたLSIの高集積化傾向は使用するリードフレームの多ピン化を更に推進する結果をもたらしているが、リードフレームの多ピン化には素材厚の薄い方が有利であるため、薄板化に対応できるように従来にも増して強度及び硬度の高いリードフレーム材が要求されるようになった。

また、リードフレームが多ピン化されると必然的にピン間隔が狭くなり、ピン自体の幅も小さくなるが、それに対処するには精度の一層高いエッチング加工が必要となる。そのため、多ピン用に供されるリードフレーム材では、高強度や高硬度の他に、形成されるピン幅やピン間隔の制御性につながる“エッチング加工性”が優れていることも重要な要求特性となっていた。

ところで、Fe-Ni系合金製リードフレーム材のエッチング加工工程は、一般に、脱脂したリードフレーム材の両面にフォトリソを塗布しパターンを焼き付けて現像した後、塩化第2鉄を主成分とするエッチング液でエッチング加工し、その

後前記レジストを除去する工程から構成されているのが普通である。そして、この際のエッチング性を決める要因としては“レジストの密着性”や“エッチング速度”等が挙げられるが、これらの中でも素材のエッチング速度が最も重要な因子となっており、エッチング速度が速くなるにつれてリードフレーム材に形成されるピン幅、ピン間隔の制御性が容易化することから、該エッチング速度によってエッチング加工性の評価が概ね決定されてしまうと言っても過言ではなかった。

従って、半導体機器の集積度が上昇するに伴い、リードフレーム材には強度特性に加えて“より速いエッチング速度(即ち良好なエッチング加工性)”特性も求められてきた訳であるが、未だ十分に満足できるエッチング加工性、強度及び硬度、更には封着性並びに成形加工性等を兼備した材料が見出されていないのが現状であった。

このようなことから、本発明の目的は、強度及び硬度が高く、しかも優れたエッチング加工性、封着性並びに成形加工性をも併せ持つところの、

集積度の高い半導体機器への適用を意図した場合でも十分な性能を発揮し得るリードフレーム材を工業的に安定して提供し得る手段を確立することに置かれた。

#### (課題を解決するための手段)

本発明者等は、上記目的を達成すべく、特にFe-Ni-Co系合金リードフレーム材が有する比較的高い強度や低い熱膨張係数等に着眼して、これらの特性を更に向上させると共に、そのエッチング加工性や成形加工性を顕著に改善することの可能性を探りながら研究を重ねた結果、次のような新しい知見を得ることができた。即ち、

(a) Ni及びCoを主要成分としたFe合金において、そのC、Si及びPの含有量を、更にはN含有量をも特定の低い値に制限した場合には、該合金のエッチング速度が顕著に改善されるようになる、

(b) しかも、上記合金に幾つかの選ばれた特定の元素の1種又は2種以上を所定の割合で含有させた場合には、リードフレーム材としての所要特性に格別な悪影響を及ぼすことなく材料の強度を

効果的に向上することができる上、Ni及びCo含有量の注意深い調整の下での上記特定元素の添加は、その熱膨張係数をモールドレジンや半導体チップのそれに近付けるのに極めて有効な手段となる、

(c) また、上記合金材料においてもその結晶粒径が強度及び成形加工性に少なからぬ影響を及ぼすが、該結晶粒径を特定値以下に抑える手立てを講じることによってリードフレームの多ピン化にとって好ましい“材料強度の更なる向上”が期待できる上、成形加工性も改善される、

(d) 従って、Fe-Ni-Coを基本成分とした合金におけるNi、Co、C、Si及びP等の含有量を総合的に調整すると同時に、これに特定合金元素の添加を行うか、或いは更に結晶粒径調整をも実施すると、強度、熱膨張係数、封着性、成形加工性等の特性に優れ、しかも非常に良好なエッチング加工性をも備えたリードフレーム材の実現が可能となる。

本発明は、上記知見事項等を基にして完成されたものであり、

「リードフレーム材を、

C: 0.015%以下(以降、成分含有割合は重量%とする)、

Si: 0.001~0.15%, P: 0.01%以下、

S: 0.005%以下、O: 0.010%以下、

N: 0.005%以下、Co: 5~30%、

Ni: 15~55%

であって、更にCu, Mn, Cr, Mo, W, V, Nb, Ta, Ti, Zr, Hf, B, Be, Mg及びCaの1種以上をも合計で0.01~5.0%含むと共に、残部がFe及び不可避免の不純物から成る成分組成に構成することにより、優れたエッチング加工性、封着性及び成形加工性と、高い強度、硬度とを兼備せしめた点」に特徴を有している。

なお、上記本発明に係るリードフレーム材において、

a) C含有量を0.005%以下とする、

b) Si含有量を0.001~0.05%に調整する、

c) P含有量を0.003%以下とする、

なる条件を単独で、或いは組み合わせて採用すれ

度の確保が困難となる。従って、Ni含有量は15~55%と定めた。

#### Co

Coもリードフレーム材の熱膨張係数を決定するのに重要な成分であると同時に、材料の強度及び硬度を向上させるのに有効な成分でもある。しかし、Co含有量が5%未満であると熱膨張係数が所望値を超えて大きくなるばかりでなく、リードフレーム材の所望強度、硬度の確保も困難となる。一方、30%を超えてCoを含有させても熱膨張係数が所望値を超えて大きくなってしまふ。従って、Co含有量は5~30%と定めた。

#### C

リードフレーム材中のC含有量が0.015%を超えると鉄炭化物の生成が起こり、これがリードフレーム材のエッチング加工性を害する。従って、C含有量の上限を0.015%と定めたが、固溶Cもエッチング加工性に悪影響を与えることからC含有量は低いほど良く、出来れば0.005%以下にまで抑制するのが望ましい。

ば、得られるエッチング加工性改善効果は特に顕著となり、また

d) 最終焼鈍時(最終焼鈍終了時)の結晶粒径を50 $\mu$ m以下に調整する、

との手立てによって強度や成形性が一層向上して安定化することから、必要に応じてこれらの1つ又は幾つかを適用することにより多ピンリードフレームの製造にも十分な対応が可能である。

次に、本発明において、リードフレーム材の成分組成を前記の如くに限定した理由を各成分の作用と共に詳述する。

#### (作用)

##### Ni

Niはリードフレーム材の熱膨張係数を決定するのに重要な成分であり、封着時や封着後におけるパッケージとの熱膨張差を小さくして優れた封着性、耐湿信頼性を確保するためには、Ni含有量を15~55%に調整する必要がある。また、Niにはリードフレーム材の強度及び硬度を向上させる作用もあるが、Ni含有量が15%未満では所望強度、硬

##### Si

Siは脱酸材として必要な元素であるが、一方でリードフレーム材のエッチング加工性に大きな影響を及ぼす元素でもある。即ち、Si含有量が増加するとエッチング速度が遅くなってエッチング加工性を悪化する。このため、良好なエッチング加工性を確保するにはSi含有量を0.15%以下に調整する必要がある。特に、多ピンタイプのリードフレーム材の場合には一段と良好なエッチング加工性が要求されることから、Si含有量は好ましくは0.05%以下にまで低減するのが良い。ただ、Si含有量を0.001%未満の領域にまで低減すると脱酸効果が認められなくなってしまう。従って、Si含有量は0.001~0.15%と定めたが、上述したように出来れば0.001~0.05%に調整するのが好ましい。

##### P

Pも、Siと同様、過剰に含有させるとリードフレーム材のエッチング加工性に害を与える元素である。そして、上記エッチング加工性への悪影響

はP含有量が0.01%を超えるとより顕著化することから、P含有量は0.01%以下と定めた。しかし、P含有量を0.003%以下にまで低減するとエッチング加工性改善効果が一層顕著となるため、望ましくは0.003%以下に調整するのが良い。

#### S

S含有量が0.005%を超えるとリードフレーム材中に硫化物系介在物が多くなり、エッチング加工時の欠陥となってピン折れ等を引き起こすようになる。従って、S含有量は0.005%以下と限定した。

#### O

O含有量が0.010%を超えるとリードフレーム材中に酸化物系介在物が多くなり、やはりエッチング加工時の穿孔欠陥となることから、O含有量を0.010%と限定した。

#### N

N含有量が0.005%を超えてもリードフレーム材のエッチング加工性が悪化することから、N含有量の上限を0.005%と定めた。

Cu, Mn, Cr, Mo, W, V, Nb, Ta, Ti, Zr, Hf, B,

Be, Mg及びCa

これらの元素は何れもリードフレーム材の強度や熱膨張係数を上昇させる作用を有しているため、材料強度の向上、並びに熱膨張係数を上げてレジンモールドのそれに近付けることで封着性をより改善する目的で1種又は2種以上が含有せしめられる。しかし、それらの含有量が合計で0.01%未満であると前記作用による所望の効果が得られず、一方、合計の含有量が5.0%を超えた場合には材料が硬くなり過ぎて成形加工性の悪化を招く他、適正な熱膨張係数の確保も困難となることから、上記成分の含有量を合計量で0.01~5.0%と定めた。

なお、先にも説明したように、最終焼鈍を施した際の結晶粒径を50 $\mu$ m以下に制御することは強度と成形加工性の効果的な改善につながることから、好ましくは最終焼鈍時の結晶粒径を50 $\mu$ m以下に調整する手立てを講じるのが良い。ここで、結晶粒度の制御は、焼鈍前の加工度、焼鈍温度、

焼鈍時間等の調整によって可能であることは言うまでもない。

続いて、本発明の効果を実施例により更に具体的に説明する。

#### (実施例)

まず、真空溶解により調整した材料を鑄造し、熱間圧延及び酸洗の後に冷間圧延と焼鈍を繰り返すと共に、最終焼鈍後に加工度：40%の冷間圧延を施し、更に500℃で1時間の歪取り焼鈍を施して第1表に示す如き成分組成の冷延板(板厚：0.15mm)を製造した。

次に、これらの冷延板を脱脂後、レジスト膜を塗布し所定パターンを焼き付けて現像してから、塩化第2鉄溶液を用いたエッチング加工により何れも同一条件の下で128ピンのリードフレームを作成した。

そして、得られたリードフレームにつき、「エッチング性」の評価として「エッチング加工後のアウターリードピン幅とそのバラツキ」を、「機械的特性」の評価として「引張強さ」、「ビッカ-

第 1 表 の 1

| 材料種別             | 化 学 成 分 (重量%) |       |      |       |       |       |       |      |        |                      |                             | 結晶粒径<br>( $\mu\text{m}$ ) | エッチング性                       |             | 機 械 的 性 質      |   | 封着性 |
|------------------|---------------|-------|------|-------|-------|-------|-------|------|--------|----------------------|-----------------------------|---------------------------|------------------------------|-------------|----------------|---|-----|
|                  | C             | Si    | P    | S     | O     | N     | Ni    | Co   | 他の添加元素 | Fe及び不純物              | ピン幅平均値<br>( $\mu\text{m}$ ) |                           | ピン幅標準偏差<br>( $\mu\text{m}$ ) | 硬 さ<br>(Hv) | 加 工 性<br>(曲げ性) |   |     |
| 本<br>発<br>明<br>材 | 1             | 0.001 | 0.03 | 0.003 | 0.002 | 0.004 | 0.002 | 29.3 | 16.8   | Cu : 4.36            | 残                           | 35                        | 403                          | 2           | 255            | ○ | ○   |
|                  | 2             | 0.003 | 0.03 | 0.002 | 0.003 | 0.002 | 0.003 | 29.5 | 17.1   | Nb : 3.21            | 残                           | 20                        | 401                          | 3           | 249            | ○ | ○   |
|                  | 3             | 0.004 | 0.02 | 0.001 | 0.004 | 0.004 | 0.002 | 28.3 | 17.4   | Mn : 4.29            | 残                           | 19                        | 407                          | 3           | 240            | ○ | ○   |
|                  | 4             | 0.005 | 0.02 | 0.003 | 0.001 | 0.005 | 0.004 | 29.3 | 17.4   | Cr : 3.15            | 残                           | 22                        | 405                          | 3           | 252            | ○ | ○   |
|                  | 5             | 0.001 | 0.04 | 0.002 | 0.002 | 0.002 | 0.002 | 28.4 | 17.0   | Mo : 4.74            | 残                           | 33                        | 404                          | 4           | 245            | ○ | ○   |
|                  | 6             | 0.003 | 0.05 | 0.002 | 0.004 | 0.006 | 0.002 | 29.8 | 17.8   | W : 3.21             | 残                           | 34                        | 405                          | 5           | 239            | ○ | ○   |
|                  | 7             | 0.002 | 0.04 | 0.001 | 0.002 | 0.007 | 0.004 | 28.5 | 16.9   | V : 2.65             | 残                           | 20                        | 407                          | 8           | 250            | ○ | ○   |
|                  | 8             | 0.003 | 0.03 | 0.003 | 0.005 | 0.005 | 0.003 | 29.9 | 17.5   | Nb : 3.46            | 残                           | 15                        | 405                          | 6           | 262            | ○ | ○   |
|                  | 9             | 0.004 | 0.02 | 0.002 | 0.003 | 0.004 | 0.005 | 29.7 | 16.8   | Ta : 3.30            | 残                           | 26                        | 406                          | 4           | 260            | ○ | ○   |
|                  | 10            | 0.003 | 0.02 | 0.002 | 0.002 | 0.007 | 0.002 | 28.2 | 17.2   | Ti : 2.74            | 残                           | 29                        | 409                          | 4           | 255            | ○ | ○   |
|                  | 11            | 0.004 | 0.03 | 0.003 | 0.003 | 0.005 | 0.003 | 29.1 | 17.4   | Zr : 1.45            | 残                           | 24                        | 407                          | 6           | 246            | ○ | ○   |
|                  | 12            | 0.003 | 0.01 | 0.001 | 0.001 | 0.009 | 0.002 | 28.6 | 16.7   | Hf : 3.29            | 残                           | 26                        | 408                          | 7           | 248            | ○ | ○   |
|                  | 13            | 0.001 | 0.01 | 0.002 | 0.002 | 0.004 | 0.001 | 29.6 | 16.9   | B : 0.95             | 残                           | 24                        | 404                          | 4           | 255            | ○ | ○   |
|                  | 14            | 0.004 | 0.04 | 0.001 | 0.002 | 0.002 | 0.003 | 29.5 | 17.0   | Be : 0.44            | 残                           | 22                        | 403                          | 2           | 254            | ○ | ○   |
|                  | 15            | 0.003 | 0.03 | 0.001 | 0.001 | 0.004 | 0.002 | 30.8 | 17.2   | Mg : 0.68            | 残                           | 30                        | 406                          | 7           | 242            | ○ | ○   |
|                  | 16            | 0.002 | 0.03 | 0.003 | 0.001 | 0.004 | 0.004 | 27.2 | 16.8   | Ca : 0.45            | 残                           | 31                        | 407                          | 8           | 239            | ○ | ○   |
|                  | 17            | 0.003 | 0.05 | 0.002 | 0.002 | 0.002 | 0.001 | 27.8 | 16.7   | Ti : 0.87, Mo : 3.32 | 残                           | 20                        | 408                          | 7           | 259            | ○ | ○   |
|                  | 18            | 0.002 | 0.04 | 0.003 | 0.004 | 0.002 | 0.001 | 29.6 | 17.0   | Zr : 0.38, Nb : 1.39 | 残                           | 22                        | 406                          | 6           | 242            | ○ | ○   |

(注) 「加工性」及び「封着性」の評価結果は、○…良好、×…不良、でそれぞれ表示した。

第 1 表 の 2

| 材料種別 | 化 学 成 分 (重量%) |       |      |       |       |       |       |      |        |                        |                             | 結晶粒径<br>( $\mu\text{m}$ ) | エッチング性                       |             | 機 械 的 性 質      |   | 封着性 |
|------|---------------|-------|------|-------|-------|-------|-------|------|--------|------------------------|-----------------------------|---------------------------|------------------------------|-------------|----------------|---|-----|
|      | C             | Si    | P    | S     | O     | N     | Ni    | Co   | 他の添加元素 | Fe及び不純物                | ピン幅平均値<br>( $\mu\text{m}$ ) |                           | ピン幅標準偏差<br>( $\mu\text{m}$ ) | 硬 さ<br>(HV) | 加 工 性<br>(曲げ性) |   |     |
| 本発明材 | 19            | 0.013 | 0.03 | 0.002 | 0.002 | 0.009 | 0.004 | 30.4 | 16.8   | Ti : 3.13              | 残                           | 18                        | 410                          | 9           | 261            | ○ | ○   |
|      | 20            | 0.003 | 0.14 | 0.002 | 0.003 | 0.007 | 0.003 | 30.3 | 16.7   | Zr : 2.18              | 残                           | 20                        | 413                          | 10          | 256            | ○ | ○   |
|      | 21            | 0.008 | 0.04 | 0.001 | 0.003 | 0.003 | 0.005 | 28.8 | 17.4   | Mo : 4.48              | 残                           | 34                        | 411                          | 12          | 247            | ○ | ○   |
|      | 22            | 0.006 | 0.02 | 0.009 | 0.004 | 0.004 | 0.003 | 29.2 | 17.2   | Nb : 3.40              | 残                           | 31                        | 413                          | 9           | 242            | ○ | ○   |
|      | 23            | 0.010 | 0.10 | 0.004 | 0.002 | 0.003 | 0.001 | 29.6 | 17.4   | Nb : 4.31              | 残                           | 35                        | 414                          | 7           | 235            | ○ | ○   |
|      | 24            | 0.002 | 0.03 | 0.009 | 0.003 | 0.004 | 0.003 | 30.0 | 17.9   | Cr : 4.28              | 残                           | 42                        | 415                          | 10          | 239            | ○ | ○   |
|      | 25            | 0.004 | 0.12 | 0.003 | 0.004 | 0.002 | 0.002 | 29.2 | 17.2   | Zr : 0.38, Nb : 1.42   | 残                           | 20                        | 412                          | 10          | 243            | ○ | ○   |
|      | 26            | 0.003 | 0.03 | 0.002 | 0.003 | 0.002 | 0.003 | 29.5 | 17.1   | Nb : 3.21              | 残                           | 52                        | 403                          | 3           | 231            | ○ | ○   |
| 比較材  | 27            | 0.005 | 0.05 | 0.001 | 0.004 | 0.003 | 0.003 | 28.5 | 16.7   | —                      | 残                           | 20                        | 405                          | 8           | 204            | ○ | ×   |
|      | 28            | 0.022 | 0.04 | 0.001 | 0.002 | 0.004 | 0.002 | 29.5 | 16.8   | Ti : 2.84              | 残                           | 22                        | 437                          | 21          | 243            | ○ | ○   |
|      | 29            | 0.005 | 0.27 | 0.002 | 0.002 | 0.002 | 0.002 | 30.2 | 17.0   | Zr : 1.50              | 残                           | 19                        | 428                          | 18          | 245            | ○ | ○   |
|      | 30            | 0.004 | 0.04 | 0.014 | 0.003 | 0.004 | 0.003 | 30.5 | 17.4   | Nb : 3.51              | 残                           | 28                        | 424                          | 14          | 235            | ○ | ○   |
|      | 31            | 0.003 | 0.10 | 0.005 | 0.012 | 0.005 | 0.005 | 29.3 | 17.1   | Mo : 4.65              | 残                           | 33                        | 408                          | 8           | 244            | × | ○   |
|      | 32            | 0.006 | 0.04 | 0.009 | 0.005 | 0.002 | 0.003 | 30.5 | 17.4   | ■ Ti : 3.42, Cr : 4.55 | 残                           | 29                        | 438                          | 20          | 264            | × | ○   |
|      | 33            | 0.004 | 0.05 | 0.005 | 0.002 | 0.003 | 0.002 | 28.7 | 16.9   | ■ W : 4.30, Cr : 3.32  | 残                           | 39                        | 425                          | 17          | 275            | × | ○   |
|      | 34            | 0.002 | 0.02 | 0.004 | 0.002 | 0.011 | 0.003 | 30.5 | 16.7   | Nb : 3.36              | 残                           | 105                       | 407                          | 6           | 218            | ○ | ○   |
|      | 35            | 0.004 | 0.03 | 0.003 | 0.004 | 0.004 | 0.005 | 29.7 | 17.0   | ■ Nb : 0.003           | 残                           | 30                        | 404                          | 6           | 205            | ○ | ○   |

(注1) \*印は、本発明で規定する条件から外れていることを示している。

(注2) 「加工性」及び「封着性」の評価結果は、○…良好、×…不良、でそれぞれ表示した。

ス硬さ”及び“加工性(曲げ性)”を、また「封着性」の評価として 樹脂封着後に熱サイクル(80℃×60min×1回)を付与した際のクラック発生の有無をそれぞれ調査した。なお、前記加工性(曲げ性)の評価は、90度繰り返し曲げ試験(曲げ半径:0.15mm)に従って実施した。

これらの調査結果を、最終焼鈍時の結晶粒径と共に第1表に併記した。

第1表に示される結果からも明らかなように、本発明材では何れも十分な強度と硬度を有し、かつ優れたエッチング性、成形加工性及びに封着性を示すのに対して、成分組成が本発明で規定する条件を満たしていない比較材では上記リードフレーム材に要求される特性の何れかが劣っていることが分かる。

即ち、本発明材1～26は、比較材28～30に比べてピン幅が狭く、エッチング速度が速いことが確認できる。また、エッチングによって形成されたピン幅の標準偏差(S.D.)も小さく、優れた寸法精度のリードフレーム製品が得られることも分かる。

比較材35は、逆に強度改善成分の含有量が少ないために十分な強度(硬さ)を示さない。

#### (効果の総括)

以上に説明した如く、この発明によれば、優れたエッチング加工性、封着性及び成形加工性と、高い強度及び硬度とを兼備したリードフレーム材の提供が可能となり、半導体機器の更なる高集積化を容易化できるなど、産業上極めて有用な効果がもたらされる。

そして、本発明材の中でも、特に本発明材1～18はC、Si、Pの含有量が共により好ましい範囲にコントロールされているため、本発明材19～25と比較して一段と優れたエッチング性を示していることも確認できる。

また、本発明材8と比較材34との比較からも、リードフレーム材の結晶粒径が50μmを大きく上回るようになると十分な強度(硬さ)を確保出来ないことが分かる。

一方、比較材28～30は、各々Si、P、Cの含有量が高いためにエッチングによって形成されたピン幅が広く、バラツキも大きい。

比較材27は、強度改善並びに熱膨張係数上昇成分が添加されていないために十分な強度が得られず、熱膨張係数も小さ過ぎて封着性にも劣る。

比較材31は、S含有量が高いために曲げ加工試験でピン折れが発生した。

比較材32及び33は、強度改善成分の含有量が多過ぎるため曲げ加工性が悪く、エッチング加工性にも劣っている。

出願人 日本鉱業株式会社  
代理人 弁理士 今井 毅



Espacenet

Bibliographic data: JPH05119035 (A) — 1993-05-14

## IMAGING FLOW SIGHT METER

**Inventor(s):** OGINO SHINICHI ± (OGINO SHINICHI)

**Applicant(s):** TOA MEDICAL ELECTRONICS ± (TOA MEDICAL ELECTRONICS CO LTD)

**Classification:** - **international:** G01N15/14; G01N21/64; G01N33/48; G01N33/49; (IPC1-7): G01N15/14; G01N21/64; G01N33/48; G01N33/49  
 - **cooperative:** G01N15/1434; G01N15/1463; G01N15/1436; G01N15/1459; G01N2015/144; G01N2015/1488; G01N2021/177; G01N21/6456

**Application number:** JP19910277560 19911024

**Priority number (s):** JP19910277560 19911024

**Also published as:** DE69214770 (T2) EP0538551 (A2) EP0538551 (A3) EP0538551 (B1) JP3212647 (B2) more


## Abstract of JPH05119035 (A)

**PURPOSE:**To increase a fluorescent intensity emitted from cells and to enable all the time image taking of a fluorescent image frame by providing a wave length selection means that reflects exciting beam to an opposite side to an irradiation side of flow cell irradiation light and makes fluorescence permeate through it, or a reflecting means that reflects the exciting beam.

**CONSTITUTION:**An image flow sight meter takes image of a fluorescent image frame of flowing

particles in a flow cell 5. As a light source, a light source 1 for fluorescence excitation is used.; Dichroic mirrors 3 and 3a which are a wave length selection means to reflect exciting beam permeating from the flow cell 5, and to make the fluorescent from the

Fig. 1





cells permeate, a photomultiplier tube 8 to detect the fluorescence from the cells, and a judging circuit 13 for cell passing, which judges whether the detected particles are suitable for image taking of fluorescent image frame or not, and then generates the predetermined signal Sn.

(19)日本国特許庁 (J P)

(12) 公 開 特 許 公 報 (A)

(11)特許出願公開番号

特開平5-119035

(43)公開日 平成5年(1993)5月14日

| (51)Int.Cl. <sup>5</sup> | 識別記号 | 序内整理番号   | F I | 技術表示箇所 |
|--------------------------|------|----------|-----|--------|
| G 0 1 N 33/48            | M    | 7055-2 J |     |        |
| 15/14                    | C    | 7005-2 J |     |        |
| 33/49                    | A    | 7055-2 J |     |        |
| // G 0 1 N 21/64         | Z    | 9115-2 J |     |        |

審査請求 未請求 請求項の数11(全 6 頁)

(21)出願番号 特願平3-277560

(22)出願日 平成3年(1991)10月24日

(71)出願人 390014960

東亜医用電子株式会社

兵庫県神戸市中央区港島中町7丁目2番1号

(72)発明者 荻野 真一

兵庫県神戸市中央区港島中町7丁目2番1号 東亜医用電子株式会社内


(74)代理人 弁理士 湯浅 恭三 (外5名)

(54)【発明の名称】 イメージングフローサイトメータ

(57)【要約】

【目的】 フローセルの照射光が照射される側とは反対側に励起光を反射し蛍光は透過させる波長選択手段あるいは、励起光を反射させる反射手段を設けることで、励起光の強度を向上することによって、細胞から発せられる蛍光強度を増し蛍光画像の撮像を常に可能とする。

【構成】 フローセル5を流れる粒子の蛍光画像を撮像するイメージングフローサイトメータにおいて、光源として蛍光励起光源1を使用し、フローセル5から透過した励起光を反射し細胞からの蛍光を透過させる波長選択手段であるダイクロイックミラー3、3aと、細胞からの蛍光を検出する光電子増倍管8と、該検出信号に基づき被検出粒子が蛍光画像撮像に適したものであるか否かを判定し所定の制御信号s nを発する細胞通過判定回路13を備えたものである。



## 【特許請求の範囲】

【請求項1】 細胞の被検出粒子成分を含む試料液を扁平な流れにする流路が形成されたフローセルと、該フローセルの試料液に光を照射する光源と、試料液中の被検出粒子の静止画像を撮像する撮像手段と、該撮像手段からの画像データに基づき所望のデータ処理を行う画像処理手段とを含み、該フローセル中を流れる粒子の蛍光画像を撮像し分析するイメージングフローサイトメータにおいて、該光源からの照射光は蛍光励起用の光であり試料液の扁平流に対し正面から照射され、該撮像手段は正面あるいは背面からの細胞の蛍光画像を撮像するものであり、該フローセルから透過した励起光を反射させ細胞から発せられた蛍光を透過させる波長選択手段と、該撮像手段とは別に該フローセル内の細胞から発せられた蛍光を検出する検出手段と、該検出手段の検出信号に基づき被検出粒子を検出し該被検出粒子が該撮像手段の蛍光画像撮像に適したものであるか否かを判定し所定の制御信号を発する判定制御手段とを備えたことを特徴とするイメージングフローサイトメータ。

【請求項2】 請求項1の波長選択手段は平面を有することを特徴とするイメージングフローサイトメータ。

【請求項3】 請求項1の波長選択手段は凹面を有することを特徴とするイメージングフローサイトメータ。

【請求項4】 請求項1の波長選択手段は前記フローセル背面に密着して設けられたことを特徴とするイメージングフローサイトメータ。

【請求項5】 請求項1の波長選択手段は前記フローセル背面上に形成された蒸着膜であることを特徴とするイメージングフローサイトメータ。

【請求項6】 細胞の被検出粒子成分を含む試料液を扁平な流れにする流路が形成されたフローセルと、該フローセルの試料液扁平流領域に光を照射する光源と、試料液中の被検出粒子の静止画像を撮像する撮像手段と、該撮像手段からの画像データに基づき所望のデータ処理を行う画像処理手段とを含み、該フローセル中を流れる粒子の蛍光画像を撮像し分析するイメージングフローサイトメータにおいて、該光源からの照射光は蛍光励起用の光であり試料液扁平流に対し一側面から照射され、該撮像手段は正面あるいは背面からの細胞粒子の蛍光画像を撮像するものであり、該フローセルから透過した励起光を反射させる反射手段と、該撮像手段とは別に該フローセル内の細胞から発せられる蛍光を検出する検出手段と、該検出手段の検出信号に基づき被検出粒子を検出し、該被検出粒子が該撮像手段の蛍光画像撮像に適したものであるか否かを判定し所定の制御信号を発する判定制御手段とを備えたことを特徴とするイメージングフローサイトメータ。

【請求項7】 請求項6の反射手段は平面を有することを特徴とするイメージングフローサイトメータ。

【請求項8】 請求項6の反射手段は凹面を有すること

を特徴とするイメージングフローサイトメータ。

【請求項9】 請求項6の反射手段はフローセル面に密着して設けられたことを特徴とするイメージングフローサイトメータ。

【請求項10】 請求項6の反射手段はフローセル背面上に形成された蒸着膜であることを特徴とするイメージングフローサイトメータ。

【請求項11】 請求項6のフローセルの一側面に照射励起光を通過させる開口部を設けた凹面を有する反射手段をさらに備えたことを特徴とするイメージングフローサイトメータ。

## 【発明の詳細な説明】

## 【0001】

【産業上の利用分野】 本発明は細胞の蛍光画像を撮像するイメージングフローサイトメータに関するものである。

## 【0002】

【従来の技術】 細胞から発せられる蛍光または蛍光染色を施した細胞から発せられる蛍光を測定するフローサイトメータにおいて、励起用光源としてレーザ光源が使用されることが多い。これは、レーザを使用することによって測定領域を小さく絞り込むことが可能となるため測定領域での単位面積当たりの照射強度を強くすることができ、細胞から得られる蛍光の強度を強くすることができるからである。

【0003】 しかし、レーザを使用した場合、励起波長が特定の波長に制限されるため蛍光染色液が制限されるという問題があった。また、光源の大きさが大きく、価格が高いという問題もあった。これらの問題を解決するために励起用光源としてXeランプ等を使用し、励起光選択フィルターとして干渉フィルターを使用することによって励起光の波長を選択するという方法が用いられていた。しかし、レーザのように照射領域を小さく絞ることができないため、高い蛍光強度が得られないという問題があった。励起光強度の問題は、特願平3-33151、33189、33137、33138号のように蛍光画像を撮像する装置において顕著に示されている。そして、細胞の蛍光画像を得るためより強い蛍光強度とするため以下の方法が取られていた。

【0004】 1. 励起光源として発光強度の高いものを使用する。

【0005】 2. 励起光を極力小さな領域に絞り込む。

【0006】 3. 光電子増倍率素子であるイメージンテンシファイアにより弱い蛍光を増幅する。

【0007】 しかしながら、細胞から発せられる蛍光強度が弱い場合に、イメージンテンシファイアによって過度の増幅をすると光電ノイズによりS/N比が下がるため画質が劣化するという欠点があった。このため、実質的な最大増幅率を制限されてしまい、細胞の蛍光画像の撮像に必要な蛍光の強度が不足するという問題点があった。

【0008】

【発明が解決しようとする課題】解決しようとする問題点は、励起光源の光強度が弱い場合に細胞の蛍光像の撮像に必要な蛍光の強度が不足するという点である。

【0009】

【課題を解決するための手段】本発明は、イメージングフローサイトメータにおいてフローセルの照射光が照射される側とは反対側に励起光を反射し蛍光は透過させる波長選択手段あるいは、励起光を反射させる反射手段を設け、励起光の強度を向上させるものである。

【0010】

【実施例】図1は、本発明装置の第一の実施例の構成図である。本装置は、試料液を扁平な流れにする流路が形成されたフローセル5中に細胞を流し特定の細胞に対してその細胞像を撮像するものである。特に、本発明では、フローセル5を流れる細胞を常時監視し蛍光を発する細胞の蛍光像のみを選択的に撮像するものである。なお、図1、図7の実施例は落射型と呼ばれる構成となっている。蛍光励起光源1は、連続発光型のXeランプを使用し、励起光を発するものであり、撮像用光源として作用する。コリメータレンズ2は、蛍光励起光源1から発する光を平行にすることを目的とする。励起光選択フィルター4は、フローセル5を流れる細胞を通過する光の波長を選択するものである。具体的には、対象とする細胞あるいは、蛍光染色液に対して最適な波長を選択して、光を透過するものである。ダイクロイックミラー3は、励起光選択フィルター4を透過した励起光を所定の方向に反射することによって対物レンズ6に入射させるものである。なお、ダイクロイックミラー3は、蛍光は透過する特性を有する。また、ダイクロイックミラー3aはフローセル5内の細胞から発せられた蛍光を選択透過し、励起光を反射するものである。ダイクロイックミラー3、3aの波長透過率の特性例を図2に示す。対物レンズ6aは、細胞から発せられた蛍光を集光、収束して、検出手段である光電子増倍管8に導くものである。光電子増倍管8と対物レンズ6aとの間に配され、光電子増倍管8の前方にあるスリット7は、フローセル5内の撮像領域において細胞から発せられる蛍光の検出領域を制限するものである。スリット7の光透過部aは、図3に示すように一辺は、ビデオカメラ12の視野領域の幅 $150\mu\text{m}$ に一致しており、他辺は、フローセル5に対応して約 $20\mu\text{m}$ であることが望ましい。このため、対物レンズ6aとして10倍のレンズを使用する場合には $0.2\times 1.5\text{mm}$ 、40倍を使用する場合には $0.8\times 6\text{mm}$ とすれば良い。従って、スリット7の光透過部aは、 $20\times 150\mu\text{m}$ であり、蛍光像撮像部bは、 $150\times 150\mu\text{m}$ の大きさとなっている。細胞通過判定回路13は光電子増倍管8から出力された信号に所定の処理を行い目的とする細胞であるか否かを判断し、目的の細胞である場合には、電子シャッター9を動作させるシャッター動作ト

リガー信号snを発する機能を有する回路である。細胞通過判定回路13の信号処理の例を図8、図9により説明する。細胞から発せられた蛍光信号ksのパルス幅が所定のパルス幅pwを有する信号である場合、もしくは信号強度が所定のスレシヨールドレベルs1以上の値である場合、もしくはその両方の条件を満たす場合のいずれかにより目的とする細胞であるか否かを判断する。電子シャッター9は、細胞から発せられた蛍光のうち対物レンズ6によって受光された光をイメージインテンシファイア10に入射させるか否かを選択するものであり、細胞通過判定回路13によって、その動作が制御される。また、電子シャッター9の開放時間はサンプルとして使用される細胞の流速によって決定される。例えば、細胞の流速が $1\text{m/sec}$ の場合、およそ $1\mu\text{s}$ としなければならない。これ以上の時間開放すると、イメージインテンシファイア10に結像する蛍光像が流れてしまい静止像が得られなくなってしまう。イメージインテンシファイア10は、光電子増倍素子であり、その光電面に入射した光を $10^3$ から $10^6$ 倍に増幅して蛍光面側に出力する。また、電子シャッター9の代わりに電子シャッター9の機能を内蔵したイメージインテンシファイア10とすることもできる。結像レンズ11は、イメージインテンシファイア10の蛍光面より出力された像を集光、収束し、ビデオカメラ12のCCD素子に結像するものである。

【0011】以下、装置の動作に従って説明する。蛍光励起光源1から出力された励起光は、コリメータレンズ2を通過後、ダイクロイックミラー3によって反射される。その反射光は、対物レンズ6で集光されて常時、フローセル5に照射されている。フローセル5内の細胞から発せられる蛍光のみがダイクロイックミラー3aを通過してスリット7を透過後、光電子増倍管8に入射する。光電子増倍管8からの検出信号は細胞通過判定回路13によって目的とする細胞か否かが判定される。そして、目的とする細胞であれば、細胞通過判定回路13から出力されるシャッター動作トリガー信号snにより電子シャッター9が開放される。なお、ダイクロイックミラー3aによって反射された励起光成分の光は、再びフローセル5内の細胞に照射される。この時、フローセル5とダイクロイックミラー3aの間隔は十分に短いので細胞に直接照射される励起光と反射されてきた励起光の時間差は殆ど無く、同時に照射されたのと同じ状態となるため、細胞には約2倍の照度の励起光が照射されたのと等価な励起光強度が得られることとなる。細胞から発せられる蛍光は、すべての方向に対して等方的であるので、フローセル5からの蛍光は、光電子増倍管8が蛍光信号を検出するのと同時に対物レンズ6を介して電子シャッター9にも入射する。この際、細胞通過判定回路13によって目的とする細胞であると判定されている場合には、電子シャッター9が開放されており、細胞の蛍光

像がイメージインテンシファイア10の光電面に結像する。イメージインテンシファイア10によって蛍光像が増幅され出力面である蛍光面に出力され、この増幅された像が結像レンズ11によりビデオカメラ12のみがCCD素子に結像され、細胞の蛍光像が得られることとなる。図4は、本発明のフローセル5付近の図を示す。

【0012】励起光は、対物レンズ6で集光されて図の右側からフローセル5に照射される。また、フローセル5の左側のダイクロイックミラー3aにより、励起光は反射され再び細胞に照射される。一方、細胞から発せられた蛍光はダイクロイックミラー3aを通過し、光電子増倍管8に入射する。なお、ダイクロイックミラー3aは、図5に示すような凹面形状のものを使用することも可能である。この場合、ダイクロイックミラー3aからの反射光の焦点位置をフローセル5内の測定領域に合わせれば凹面鏡の周辺部に入射する励起光についても測定領域に集光できるため励起光の照度をさらに向上することができる。また、図6に示すように、フローセル5の背面に波長選択膜を蒸着することも可能である。

【0013】図7に、本発明の第二の実施例を示す。

【0014】本実施例は、細胞監視系と撮像系を同一光路内に配置することによって構成を簡略化したものである。なお、この場合にはダイクロイックミラー3と電子シャッター9との間にハーフミラー16を挿入する必要がある。これは、ハーフミラー16により反射した蛍光を光電子増倍管8で検出し、ハーフミラー16を透過した蛍光を撮像手段12で撮像するためである。図10に本発明の第三の実施例を示す。

【0015】本実施例は、細胞監視系、撮像系と励起光照射系を直角に配置することによってダイクロイックミラー3、3aを省いたものである。この場合、細胞から発する蛍光として、側方からの蛍光を測定するため波長選択手段としてのダイクロイックミラー3、3aの代わりに反射手段17を蛍光励起用光源1とは反対側のフローセル5の側方に配置する必要がある。反射手段17としては、例えば平面鏡または、図5と同様に焦点位置をフローセル5内の測定領域の位置に合わせた凹面鏡を使用する。反射手段17の配置は図4、図5、図6の実施例のダイクロイックミラー3aと同様に考えれば良い。

【0016】さらに、図11に示すように励起光の集光レンズ15とフローセル5と間に図12に示すような中心に円形開口を有する凹面鏡17を設けることによって凹面部の反射のため励起光の照度をさらに向上させることも可能である。

【0017】

【発明の効果】以上説明したように本発明のイメージン

グフローサイトメータは、試料液扁平流の背後に設けられた波長選択手段あるいは反射手段の反射によって、細胞から発せられる励起光を細胞全体に照射することができ、かつ試料液の細胞に反射による励起光が照射されるため、試料液の片側から照射した場合の約2倍の励起光照度が得られるという効果がある。

【図面の簡単な説明】

【図1】イメージングフローサイトメータの第一の実施例の構成図である。

【図2】波長選択手段であるダイクロイックミラーの波長透過率の特性図である。

【図3】フローセルにおける撮像エリアとスリットの関係を示す図である。

【図4】フローセル付近の構成図である。

【図5】ダイクロイックミラーを凹面とした場合のフローセル付近の構成図である。

【図6】フローセルの背面に波長選択手段である蒸着膜を設けた場合のフローセル付近の構成図である。

【図7】イメージングフローサイトメータの第二の実施例の構成図である。

【図8】細胞通過判定回路の信号処理の説明図である。

【図9】細胞通過判定回路の信号処理の説明図である。

【図10】イメージングフローサイトメータの第三の実施例の構成図である。


【図11】第三の実施例において凹面鏡を設けた場合のフローセル付近の構成図である。

【図12】凹面鏡の円形開口をしめす平面図である。


【符号の説明】

- 1 蛍光励起用光源
- 2 コリメータレンズ
- 3、3a ダイクロイックミラー
- 4 励起光選択フィルター
- 5 フローセル
- 6、6a 対物レンズ
- 7 スリット
- 8 光電子増倍管
- 9 電子シャッター
- 10 イメージインテンシファイア
- 11 結像レンズ
- 12 ビデオカメラ
- 13 細胞通過判定回路
- 14 画像処理装置
- 15 集光レンズ
- 16 ハーフミラー
- 17、17a 反射鏡


【図1】




【図2】




【図11】




【図6】




【図8】




【図3】




【図4】




【図5】




【図12】




【図7】



【図9】



【図10】



## 【手続補正書】

【提出日】平成4年3月13日

## 【手続補正1】

【補正対象書類名】明細書

【補正対象項目名】0009

【補正方法】変更

【補正内容】

【0009】

【課題を解決するための手段】本発明は、イメージングフローサイトメータにおいてフローセルの照射光が照射される側とは反対側に励起光を反射し蛍光は透過させる波長選択手段あるいは、励起光を反射させる反射手段を設け、励起光の強度を向上させることによって、細胞から発せられる蛍光強度を向上させるものである。

## 【手続補正2】

【補正対象書類名】明細書

【補正対象項目名】0016

【補正方法】変更

【補正内容】

【0016】さらに、図11に示すように励起光の集光

レンズ15とフローセル5との間に図12に示すような中心に円形開口を有する凹面鏡17を設けることによって凹面部の反射させ励起光の照度をさらに向上させることも可能である。

## 【手続補正3】

【補正対象書類名】明細書

【補正対象項目名】0017

【補正方法】変更

【補正内容】

【0017】

【発明の効果】以上説明したように本発明のイメージングフローサイトメータは、試料液偏平流の背後に設けられた波長選択手段あるいは反射手段による励起光の反射によって、励起光を細胞全体に照射することができ、かつ試料液中の細胞に反射による励起光が照射されるため、試料液の片側から照射した場合の約2倍の励起光照度が得られる。その結果、細胞から発せられる蛍光の強度が向上するという効果がある。



Espacenet

**Bibliographic data: JPS55144226 (A) — 1980-11-11**

---

## IMAGE PROJECTOR

**Inventor(s):** KOUNOSU OSAMU ± (KONOSU OSAMU)

**Applicant(s):** MATSUSHITA ELECTRONICS CORP ± (MATSUSHITA ELECTRONICS CORP)

**Classification:** - **international:** **G02B13/16; G02B13/18; G02B17/08; G02B27/18; G03B21/00; G03B21/10; G03B21/28; H04N5/74;**  
(IPC1-7): G03B21/10; G03B21/28; H04N5/74  
- **cooperative:**

**Application number:** JP19790053125 19790427

**Priority number (s):** JP19790053125 19790427

**Also published as:** JPS6249602 (B2)

## Abstract of JPS55144226 (A)

**PURPOSE:** To eliminate the need for changing the curvature of the light emitting surface of a braun tube gainst the change of screen by providing an aberration correction lens used for the device of projecting images on a screen by way of a concave mirror, movably in the main beam axis direction. **CONSTITUTION:** A concave mirror 9 and fluorescent screen 10 are fixed to a holding and fixing means 11. An aberration correction lens 8 is designed in the position suitable for the intermediate curvature of two kinds of screens 1, 2 is fixed to a moving means 12 and is movable on the main beam axis Z-Z'. If the position of the aberration correction lens 8 is determined at, e.g., A, with respect to the screen 1 of a front projection type television, the sharp images having no deviations are obtainable in the screen 1.; For the screen 2 of back projection type, only required is to determine the position of the aberration correction lens at, e.g., B. At this time, the radius of curvature of the fluorescent screen 10 may be constant and therefore there is no need for changing the kinds of the braun tube.



① 日本国特許庁 (JP)

① 特許出願公開

⑫ 公開特許公報 (A)

昭55—144226

⑤ Int. Cl.<sup>3</sup>  
G 03 B 21/10  
21/28  
// H 04 N 5/74

識別記号

庁内整理番号  
6401—2H  
6401—2H  
6246—5C

④ 公開 昭和55年(1980)11月11日

発明の数 1  
審査請求 未請求

(全 4 頁)

④ 画像投写装置

門真市大字門真1006番地松下電  
子工業株式会社内

① 特 願 昭54—53125

① 出 願 人 松下電子工業株式会社

② 出 願 昭54(1979)4月27日

門真市大字門真1006番地

⑦ 発 明 者 鴻巣理

④ 代 理 人 弁理士 中尾敏男 外1名

明 細 書

1、発明の名称

画像投写装置

2、特許請求の範囲

画像を凹面鏡および収差補正レンズを介してスクリーン上に投写する装置において、上記収差補正レンズを主光線軸方向に移動可能としたことを特徴とする画像投写装置。

3、発明の詳細な説明

本発明は、画像投写装置に関するものである。

投写型テレビジョンの画像投写装置として従来より第1図に示すものが知られている。

すなわち、発光面3からの映像は、凹面鏡5で反射され収差補正レンズ6を通過して反射スクリーン1または2に写し出される。

このような投写型テレビジョン装置において、投写スクリーンは、前面投写型の場合は、凹面の反射体から成る球面反射スクリーン1が用いられ、

また裏面投写型の場合は光の透過体から成る平面透過型スクリーン2が用いられる。

前者の投写型テレビジョン装置においては、視聴者は、スクリーン1に対して凹面鏡5の側に位置し、後者の投写型テレビジョンにおいては視聴者は、スクリーン2に対して凹面鏡5と反対側に位置する。

以上の例のように、投写型テレビジョン受像装置のタイプが異なると、スクリーン1、2の曲率が変わるため、同スクリーン上にずれのない鮮明な画像を得るためには、発光面3の曲率を変化させる必要があった。

しかし、複数種類のスクリーン曲率に対してブラウン管4の発光面3の曲率を変化させることはブラウン管4全体の設計を変更させることになり、工場での生産性向上およびコストの面から好ましくなかった。

本発明は上記問題点を解決するためになされたもので、スクリーン1、2の変更があっても発光面3の曲率の補正を必要としない画像投写装置を提供するものである。

以下、図面にもとづいてこの発明の構成を説明

する。第1図は投写型テレビジョン受像装置の側面図であり、1, 2はそれぞれ前面投写型テレビジョンのスクリーン、裏面投写型テレビジョンのスクリーン、3はブラウン管の螢光面、4はブラウン管、5は凹面球、6, 7は収差補正レンズをそれぞれ示すことは前述の説明の通りである。

図中の記号  $R_s$  はスクリーン1の曲率半径、 $R_o$  は収差補正レンズ6の曲率半径、 $R_1$  は収差補正レンズ6と螢光面3との距離、 $R_2$  は螢光面3の曲率半径、 $L$  はスクリーン1またはスクリーン2と収差補正レンズ6との距離、 $X_l$  は補正レンズ6が7へ移動したときの移動距離、 $T_o$  は補正レンズの中央厚み、 $D_o$  は凹面球5の全長をそれぞれあらわす。

この発明者はスクリーン1, 2の変更があっても螢光面3の曲率の補正を必要としない画像投写装置を実現しようと研究の結果、主光線軸  $Z-Z'$  上の位置を適切にえらぶことによってスクリーン面曲率がある範囲で変化しても、螢光面3の曲率を固定したままでスクリーン上にブレのない鮮明

な画像を得ることに成功した。

即ち、第1図において前面投写型テレビジョンのスクリーン1に対しては収差補正レンズ6の形状と位置が設計され、裏面投写型の2に対して収差補正レンズ7の形状と位置が設計される。上記設計においては、ブラウン管4を変更せず螢光面3の曲率を一定にしてある。発明者の研究によると上記2種類の収差補正レンズ曲面の形状差は極めてわずかであり、実用上同一のものにすることが可能であることが判明(第1表に示す)した。

第1表に、スクリーン曲率半径の変化による各定数の最適値を一実施例として示す。

(以下 余 白)

第1表 スクリーン曲率半径の変化による  
各定数の最適値の差

| 項 目              | 記 号       | 前面投写型テレビの各定数             | 裏面投写型テレビの各定数             |
|------------------|-----------|--------------------------|--------------------------|
| スクリーン曲率半径        | $R_s/R_o$ | 6.667                    | ~                        |
| 凹面鏡直径            | $D_o/R_o$ | 0.827                    | 0.827                    |
| CRT面位置           | $R_1/R_o$ | 0.47                     | 0.47                     |
| CRT面曲率半径         | $R_2/R_o$ | 0.48                     | 0.48                     |
| 補正レンズ中央厚み        | $T_o/R_o$ | 0.0213                   | 0.0213                   |
| 補正レンズ位置          | $X_l/R_o$ | 0                        | 0.0133                   |
| 補正レンズ屈折率         | $n$       | 1.5163                   | 1.5163                   |
| 投 写 距 離          | $L/R_o$   | 4.298                    | 4.298                    |
| 収差補正レンズ<br>曲面の係数 | $a_1$     | $-381660 \times 10^{-1}$ | $-383507 \times 10^{-1}$ |
|                  | $a_2$     | $232335 \times 10^{-2}$  | $234307 \times 10^{-2}$  |
|                  | $a_3$     | $342567 \times 10^{-3}$  | $319424 \times 10^{-3}$  |
|                  | $a_4$     | $103328 \times 10^{-4}$  | $282048 \times 10^{-4}$  |
|                  | $a_5$     | $-948900 \times 10^{-5}$ | $-519199 \times 10^{-5}$ |
|                  | $a_6$     | $172538 \times 10^{-6}$  | $730862 \times 10^{-6}$  |
|                  | $a_7$     | $-145198 \times 10^{-7}$ | $-548461 \times 10^{-7}$ |
|                  | $a_8$     | $631129 \times 10^{-8}$  | $215508 \times 10^{-8}$  |
|                  | $a_9$     | $-110177 \times 10^{-9}$ | $-345189 \times 10^{-9}$ |

第1表で収差補正レンズ曲面の係数について注目し、まずそれらが何をあらわすかを考案し、次に上記2種類のテレビの収差補正レンズの形状を比較する。

収差補正レンズ6の中央からの距離  $r$  におけるレンズの厚みは次式であらわされる。

$$T(r) = T_o + \sum_{N=1}^9 a_N \left( \frac{r}{R_o} \right)^{2N} \dots\dots (A)$$

ただし、 $T_o$  は収差補正レンズ6の中央での厚み、 $R_o$  は凹面球5の曲率半径である。上式(A)において、 $\frac{r}{R_o} \leq 1$  より、 $a_N \left( \frac{r}{R_o} \right)^{2N}$  の値は、

$N(1 \sim 9)$  が大きいほど、小さくなり、収差補正レンズの形状決定に寄与する度合いは小さくなる。すなわち、2つのレンズの形状を比較する場合、収差補正レンズ曲面の係数  $a_1, a_2, \dots, a_9$  のうち、 $a_1, a_2, a_3$  のみ比較すればほぼ十分である。

第1表より、スクリーン曲率半径が6.667の前面投写型のスクリーン1とスクリーン曲率半径

7  
 が無限大の裏面投写型のスクリーン2とのそれぞれの収差補正レンズ曲面の係数 $a_1, a_2, \dots, a_9$ の数値を比較すると、収差補正レンズ曲面の形状決定の大きな要件となる。低次の係数 $a_1, a_2, a_3$ の値は、上記両方のスクリーンの場合で極めて近似していることがわかる。高次の係数 $a_4, a_5, \dots, a_9$ の値は上記両者のスクリーンで、大きく異なっているが、これらの高次係数の値は低次係数よりも収差補正レンズ曲面の形状決定に及ぼす影響はきわめて小さい。

以上のことより、曲率半径の異なる2種類のスクリーン1, 2に対して収差補正レンズ6の曲率半径をほぼ一定に保ち、かつ蛍光面4の曲率半径を一定にしたままで、上記2種類のスクリーン1, 2にそれぞれずれのない鮮明な画像を得ることが可能であることが確かめられた。その際、2種類の投写型テレビジョンで調整すべきパラメータは収差補正レンズ6の移動距離 $X_L$ のみである。

第2図は、本発明の収差補正レンズが移動する画像投写装置であり、8は収差補正レンズ、9は

凹面球、10はブラウン管の螢光面、11は保持固定部、12は収差補正レンズと一体の移動部をそれぞれ示す。凹面鏡9、螢光面10は保持固定具11に固定されている。収差補正レンズ8は第1図の2種類のスクリーン1, 2の中間の曲率に対して適当な位置で設計してあり、移動具12に固定され、主光線軸 $Z-Z'$ 上で移動することができる。前面投写型テレビジョンのスクリーン1に対しては収差補正レンズ8の位置をたとえばAに定めれば、スクリーン1にズレのない鮮明な画像が得られる。また、裏面投写型のスクリーン2に対しては収差補正レンズの位置をたとえばBに定めればよい。その際、螢光面10の曲率半径は一定でよいため、ブラウン管の種類を変化させる必要はない。

この発明は投写型テレビ用の画像投写装置は、上記のような構成をもつものであるから、曲率半径の異なる複数のスクリーンに対して光学的に適合することが可能であり、ブラウン管は異なった型のテレビジョンに対して共通して使用できる。


9  
 そのためこの発明は生産性向上およびコストの低減に貢献する発明と言える。

#### 4、図面の簡単な説明

第1図は投写型テレビジョン受像装置の一例を示す側面図、第2図は本発明の一実施例における投写型テレビジョンの画像投写装置の側面図である。


8……収差補正レンズ、9……凹面鏡、10……螢光面、11……保持固定具、12……収差補正レンズと一体の移動部。

代理人の氏名 弁理士 中 尾 敏 男 ほか1名



第1図

第 2 図





Espacenet

**Bibliographic data: JPS61184427 (A) — 1986-08-18**

---

**APPARATUS FOR MEASURING LASER WAVELENGTH FOR COHERENT ANTI-STOKES RAMAN SPECTRAL DIFFRACTION**

**Inventor(s):** TOCHIGI KENJI ± (TOCHIGI KENJI)  
**Applicant(s):** HITACHI LTD ± (HITACHI LTD)  
**Classification:** - **international:** **G01J3/44; G01J9/00; G01N21/65;**  
(IPC1-7): G01J3/44  
- **cooperative:** **G01J3/44**  
**Application number:** JP19850024415 19850213  
**Priority number(s):** JP19850024415 19850213  
**Also published as:** JPH0588408 (B2)

**Abstract of JPS61184427 (A)**

**PURPOSE:** To dispense with temp. control in measurement, by using the atomic spectrum of neon or argon and the molecular spectrum of an iodine molecule receiving no effect of circumferential temp. as the measuring standards of a wavelength.  
**CONSTITUTION:** The wavelength of pulse laser beam from wavelength variable pulse laser 4 is continuously changed to record the change in the intensity of coherent anti-stokes Raman beam 11 on a recorder 21 as a spectrum and, at the same time, the absorption spectra based on optical galvanic effect of pulse laser beams by neon and iodine are recorded on the recorder 27.; Therefore, by using the known absorption wavelengths of neon and iodine recorded on the recorder 27 simultaneously with the coherent anti-stokes Raman beam 11 as standards, the wavelength of the wavelength variable pulse laser 4 generating the coherent anti-stokes Raman beam 11 can be measured with high accuracy.

## ⑫ 公開特許公報(A)

昭61-184427

⑤Int.Cl.<sup>4</sup>

識別記号

庁内整理番号

④公開 昭和61年(1986)8月18日

G 01 J 3/44

7172-2G

審査請求 未請求 発明の数 1 (全5頁)

⑤4発明の名称 コヒーレント反ストークスラマン分光用レーザ波長測定装置

②1特 願 昭60-24415

②2出 願 昭60(1985)2月13日

⑦2発 明 者 梶 木 憲 治 横浜市戸塚区吉田町292番地 株式会社日立製作所生産技術研究所内

⑦1出 願 人 株式会社日立製作所 東京都千代田区神田駿河台4丁目6番地

⑦4代 理 人 弁理士 中村 純之助

## 明 細 書

## 1. 発明の名称

コヒーレント反ストークスラマン分光用レーザ波長測定装置

## 2. 特許請求の範囲

発振波長固定のパルスレーザと、該パルスレーザに同期して上記発振波長固定パルスレーザの発振波長より長波長のレーザを発振する波長可変パルスレーザと、上記発振波長固定パルスレーザ光および波長可変パルスレーザ光を試料部に集光させる光学系と、上記試料のレーザ集光部から発生する固定波長パルスレーザ光より短波長のコヒーレント反ストークスラマン光を集光する光学系と、上記コヒーレント反ストークスラマン光を検出、記録する記録部とからなるコヒーレント反ストークスラマン分光用レーザ波長測定装置において、上記試料透過後の波長可変パルスレーザ光をネオンあるいはアルゴン封入およびよう素封入の各中空陰極放電管に入射し、直流放電することにより

得られるネオンあるいはアルゴンの原子吸収線波長とよう素分子の分子吸収線波長とが、上記波長可変パルスレーザ光の波長に一致した場合に、上記中空陰極放電管内にそれぞれ生じる電圧変化量を検出する手段と、上記電圧変化量をコヒーレント反ストークスラマンスペクトルと並列に上記記録部に記録する手段とを備えたことを特徴とするコヒーレント反ストークスラマン分光用レーザ波長測定装置。

## 3. 発明の詳細な説明

## 〔発明の利用分野〕

本発明はコヒーレント反ストークスラマン分光用波長可変パルスレーザの波長測定に係り、特に高分解能測定時のレーザ波長位置の高精度測定に好適なコヒーレント反ストークスラマン分光用レーザ波長測定装置に関するものである。

## 〔発明の背景〕

従来、レーザの発振線幅が回折格子分光光度計の分解能である約  $0.5\text{ cm}^{-1}$  (20 GHz) 以下の場合には、発振波長の測定法として AIAA-83-1478(1983

年)における Stufflebeam, Verdick および Hall による“CARS DIAGNOSTICS OF HIGH PRESSURE AND TEMPERATURE GASES”と題する文献に記載されているように Fabry-Perot エタロンを用いた干渉法を使用していた。この方法においては、波長が変化することによって Fabry-Perot エタロンを透過する光強度が、干渉により周期的に変化することを利用するものである。しかし上記方法では、透過光のピーク強度の位置の間隔は正確に求められても波長の位置の絶対値測定ができないため、波長が既知である Kr ランプの発光線などで波長位置の校正を行わなければならないという欠点がある。また Fabry-Perot エタロンの温度変化により干渉周期変化が起るため、このエタロンの温度コントロールが必要であった。さらに Fabry-Perot エタロンを透過した光の強度で測定しなければならないため、測定精度がよい光検出器が必要であり、また照明光など周囲からの妨害光の影響も除去しなければならないという欠点があった。

#### 〔発明の目的〕

$\text{cm}^{-1}$  以下で非常に多数の吸収が高精度に測定されている。したがってこれらの原子、分子の光ガルバノ効果を組合わせて用い、コヒーレント反ストークスラマン分光用の波長可変パルスレーザ光をネオンまたはアルゴンと、よう素の中空陰極放電管に入射させて光ガルバノ効果を測定することにより、波長可変パルスレーザ光の発振波長の絶対測定が可能になる。この場合、吸収波長間隔が長いネオンあるいはアルゴンの光ガルバノ効果測定と、吸収波長間隔が短いよう素の光ガルバノ効果測定とを併用することにより、ラマン線幅が  $0.5 \text{ cm}^{-1}$  程度の気体分子のコヒーレント反ストークスラマン分光測定の波長可変パルスレーザの発振波長測定、ひいてはラマンシフト値の高精度測定が可能になる。すなわち、本発明によるコヒーレント反ストークスラマン分光用レーザ波長測定装置は、発振波長固定のパルスレーザと、該パルスレーザに同期して上記発振波長固定パルスレーザの発振波長より長波長のレーザを発振する波長可変パルスレーザと、上記発振波長固定パルスレ

本発明は上記の欠点がなく、高精度、高感度で発振線幅が  $1 \sim 2 \text{ GHz}$  程度の非常に狭帯域なレーザ光波長を絶対測定できるコヒーレント反ストークスラマン分光用レーザ波長測定装置を得ることを目的とする。

#### 〔発明の概要〕

ネオン、アルゴン等の原子あるいはよう素のような分子を封入した中空陰極放電管を直流放電し、この放電部にレーザ光を入射すると、レーザ波長がネオン、アルゴン、よう素などの吸収波長に一致した場合は、放電条件が変化しこれに基づいて放電電圧が変化する光ガルバノ効果が知られている。この場合にパルスレーザ光を入射すれば電圧変化もパルス状になり、コンデンサを介して変化電位差だけを取り出すことができる。ネオン、アルゴンなどの希ガス原子の吸収スペクトルは7桁程度の精度で絶対波長が既に知られており、紫外波長から近赤外波長領域にわたって、波長間隔  $0.1 \sim 5 \text{ nm}$  程度で吸収がある。同様にしてよう素分子も紫外波長から赤外波長にわたって波長間隔  $0.04$

レーザ光および波長可変パルスレーザ光を試料部に集光させる光学系と、上記試料のレーザ集光部から発生する固定波長パルスレーザ光より短波長のコヒーレント反ストークスラマン光を集光する光学系と、上記コヒーレント反ストークスラマン光を検出、記録する記録部とからなるコヒーレント反ストークスラマン分光用レーザ波長測定装置において、上記試料透過後の波長可変パルスレーザ光をネオンあるいはアルゴン封入およびよう素封入の各中空陰極放電管に入射し、直流放電することにより得られるネオンあるいはアルゴンの原子吸収線波長とよう素分子の分子吸収線波長とが、上記波長可変パルスレーザ光の波長に一致した場合に、上記中空陰極放電管内にそれぞれ生じる電圧変化量を検出する手段と、上記電圧変化量をコヒーレント反ストークスラマンスペクトルと並列に上記記録部に記録する手段とを備えたものである。

#### 〔発明の実施例〕

つぎに本発明の実施例を図面とともに説明する。

第1図は本発明によるコヒーレント反ストークスラマン分光用レーザ波長測定装置の一実施例を示すブロック図、第2図は光ガルバノ効果による吸収スペクトルの一例を示す図で、(a)はネオンの場合、(b)はよう素分子の場合をそれぞれ示す。第1図において、発振波長固定のパルスレーザ1から発振されたレーザ光2は、一部をハーフミラー3で分割して波長可変パルスレーザ4の励起光源に用いている。上記波長可変パルスレーザ4から発振されたレーザ光5はダイクロイックミラー6で上記波長固定パルスレーザ光2と同一光軸に重ねられ、集光レンズ7によって試料8中に焦点を結ぶ。焦点部から発生したコヒーレント反ストークスラマン光11と上記レーザ光2およびレーザ光5は、レンズ9によってそれぞれ平行光束に戻される。コヒーレント反ストークスラマン光11はダイクロイックミラー10によって光路を90°曲げられ、光学フィルタ12によりさらにレーザ光2とレーザ光5とを除かれたのち、光検出器13で検出される。また、レーザ光2とレーザ光5とはダイ

クロイックミラー10を透過後にダイクロイックミラー17で分離され、該ダイクロイックミラー17を透過したパルスレーザ光2は光検出器14で検出されトリガ信号15を発生する。上記光検出器13で検出されたコヒーレント反ストークスラマン光11は、上記トリガ信号15に同期してゲート検出器16で検出され記録計27に記録される。またダイクロイックミラー17で上記パルスレーザ光2と分離されたパルスレーザ光5はさらにハーフミラー18で2分割され、それぞれネオンを充填した中空陰極放電管19およびよう素を充填した中空陰極放電管20に入射する。バラスト抵抗21、21'と直流電源22、22'とで直流放電する上記中空陰極放電管19、20におけるパルスレーザ光5の吸収に伴う光ガルバノ効果によって生じるパルス状変動電位差は、それぞれコンデンサ23および24を経て取出され、上記ゲート信号15に同調してゲート検出器25および26により検出され記録計27に記録される。

上記のようにして波長可変パルスレーザ4からのパルスレーザ光5の波長を連続的に変化させる

定することができる。

#### 〔発明の効果〕

上記のように本発明によるコヒーレント反ストークスラマン分光用レーザ波長測定装置は、発振波長固定のパルスレーザと、該パルスレーザに同期して上記発振波長固定パルスレーザの発振波長より長波長のレーザを発振する波長可変パルスレーザと、上記発振波長固定パルスレーザ光および波長可変パルスレーザ光を試料部に集光させる光学系と、上記試料のレーザ集光部から発生する固定波長パルスレーザ光より短波長のコヒーレント反ストークスラマン光を集光する光学系と、上記コヒーレント反ストークスラマン光を検出、記録する記録部とからなるコヒーレント反ストークスラマン分光用レーザ波長測定装置において、上記試料透過後の波長可変パルスレーザ光をネオンあるいはアルゴン封入およびよう素封入の各中空陰極放電管に入射し、直流放電することにより得られるネオンあるいはアルゴンの原子吸収線波長とよう素分子の分子吸収線波長とが、上記波長可変

ことにより、コヒーレント反ストークスラマン光11の強度変化が上記記録計27にスペクトルとして記録され、これと同時にネオンおよびよう素によるパルスレーザ光5の光ガルバノ効果に基づく吸収スペクトルが、上記記録計27に記録される。第2図(a)はネオンを封入した中空陰極放電管19にパルスレーザ光5を入射して、発振波長を連続的に変えた場合に得られる光ガルバノ効果に基づくネオンの吸収スペクトルの一例を示す図で、第2図(b)はよう素を封入した中空陰極放電管20によって上記同様に測定される光ガルバノ効果に基づくよう素分子の吸収スペクトルの一例を示す図である。よう素分子の吸収スペクトルは紫外波長から可視波長の全域にわたって、第2図(b)と同様に多数の吸収線が光ガルバノ効果に基づいて測定される。したがって記録計27にコヒーレント反ストークスラマン光11と同時に記録されたネオンおよびよう素の既知吸収波長を標準とすることにより、コヒーレント反ストークスラマン光11を発生する波長可変パルスレーザ4の波長を高精度に測



パルスレーザ光の波長に一致した場合、上記中空陰極放電管内にそれぞれ生じる電圧変化量を検出する手段と、上記電圧変化量をコヒーレント反ストークスラマンスペクトルと並列に上記記録部に記録する手段とを備えたことによって、周囲温度の影響を受けないネオンあるいはアルゴンの原子スペクトルおよびよう素分子の分子スペクトルを波長測定の基準として用いるため、測定に際して温度のコントロールが一切不要であり、またホトマルやダイオード等の妨害光の影響を受けやすい光検出器を用いないため、照明光等の設置環境の条件も少なく、安定して高精度に、コヒーレント反ストークスラマン分光用波長可変パルスレーザの波長測定を行うことができる。

#### 4. 図面の簡単な説明


第1図は本発明によるコヒーレント反ストークスラマン分光用レーザ波長測定装置の一実施例を示すブロック図、第2図は光ガルバノ効果による吸収スペクトルの一例を示す図で、(a)はネオンの場合、(b)はよう素分子の場合を示すものであ

る。

1…波長固定パルスレーザ、2…波長固定パルスレーザ光、4…波長可変パルスレーザ、5…波長可変パルスレーザ光、8…試料、11…コヒーレント反ストークスラマン光、13、14…光検出器、16、25、26…ゲート検出器、19…中空陰極放電管(ネオンまたはアルゴン用)、20…中空陰極放電管(よう素分子用)、27…記録計。

代理人弁理士 中 村 純之助



第 1 図



昭和60年 6月 5日

## 図 2

(a)



特許庁長官 志 賀 学 殿

1. 事件の表示 昭和60年特許願第24415号

2. 発明の名称 コヒーレント反ストークスラマン  
分光用レーザ波長測定装置

3. 補正をする者

事件との関係 特許出願人

名 称 (510) 株式会社 日立製作所

4. 代理人

住 所 (〒100) 東京都千代田区丸の内一丁目5番1号  
新丸ノ内ビルディング3階44区 (電話214-0502)

氏 名 (6835) 弁理士 中 村 純 之 助

5. 補正命令の日付 昭和60年 5月28日

6. 補正の対象 明細書の発明の詳細な説明の欄

7. 補正の内容 添付別紙のとおり

## 補正の内容

1. 明細書第2頁下から1行目～第3頁上から3行目の「A I A A - 83 - 1478 (1983) ... G A S E S」を  
エーアイエーエー (A I A A) - 83 - 1478 (1983)  
におけるスタッフルビーム、ベルディエック (Stuffelbeam, Verdieck) およびホール (Hall) による「カーズ ダイアグノスティックス オブ ハイ プレッシャー アンド テンパラチャー ガスイズ」 (CARS DIAGNOSTICS OF HIGH PRESSURE AND TEMPERATURE GASES)」

と補正する。

2. 明細書第3頁上から第4行目「Fabry - Perot」を「ファブリーペロット (Fabry - Perot)」と補正する。

3. 明細書第3頁上から第6行目「Fabry - Perot」を「ファブリーペロット (Fabry - Perot)」と補正する。

4. 明細書第3頁下から第8行目「Fabry - Perot」を「ファブリーペロット (Fabry -

Perot)」と補正する。

5. 明細書第3頁下から第6行目「Fabry - Perot」を「ファブリーペロット (Fabry - Perot)」と補正する。



- (51) International Patent Classification:  
*C12M 1/34* (2006.01)
- (21) International Application Number:  
PCT/US2013/043453
- (22) International Filing Date:  
30 May 2013 (30.05.2013)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
- |            |                              |    |
|------------|------------------------------|----|
| 61/653,328 | 30 May 2012 (30.05.2012)     | US |
| 61/653,245 | 30 May 2012 (30.05.2012)     | US |
| 61/715,819 | 18 October 2012 (18.10.2012) | US |
| 61/715,836 | 19 October 2012 (19.10.2012) | US |
| 61/816,819 | 29 April 2013 (29.04.2013)   | US |
- (71) Applicant (for all designated States except US): **CYTONE JENE CORP.** [US/US]; 4097 Cortona Court, San Jose, CA 95135 (US).
- (72) Inventor; and  
(71) Applicant (for US only): **CHEN, Yong, Qin** [US/US]; 4097 Cortona Court, San Jose, CA 95135 (US).
- (74) Agent: **SCHREIBER, Donald, E.**; Post Office Box 2926, Kings Beach, CA 96143-2926 (US).
- (81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.
- (84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,

[Continued on next page]

(54) Title: FLOW CYTOMETER




FIG. 1

(57) Abstract: The disclosed flow cytometer (40) includes; 1. a laser diode ("LD") based optical subsystem (50) for impinging a beam of light upon particles passing through a viewing zone; 2. a composite microscope objective (60) for gathering and imaging light scattered from or fluoresced by particles passing through the viewing zone; 3. a fluidic subsystem (70) for supplying a liquid sheath flow to the viewing zone; 4. a peristaltic pump (80) for injecting into the liquid sheath flow a liquid sample flow carrying particles that passes together with the liquid sheath flow through the viewing zone; 5. a multimode optical fiber (852) that receives scattered and fluoresced light from the viewing zone that the composite microscope objective (60) gathers and images; and 6. a wavelength division multiplexer (90) for optically separating into color bands light received via the optical fiber (852).



TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN, TD, TG).

**Published:**

— *without international search report and to be republished upon receipt of that report (Rule 48.2(g))*

**Declarations under Rule 4.17:**

— *of inventorship (Rule 4.17(iv))*

- 1 -

**FLOW CYTOMETER****Technical Field**

The present disclosures relate generally to the technical field of flow cytometry and, more particularly, to the structure and operation of an improved flow cytometer together with various individual subassemblies included therein.

**Background Art**

Flow cytometry is a biophysical technique employed in cell counting, sorting, biomarker detection and protein engineering. In flow cytometry, cells suspended in a stream of liquid pass through an electronic detection apparatus. Flow cytometry allows simultaneous multiparametric analysis of physical and/or chemical characteristics of up to thousands of cells per second.

Flow cytometry has various applications including in the fields of molecular biology, pathology, immunology, plant biology and marine biology. Flow cytometry also has broad application in medicine (especially in transplantation, hematology, tumor immunology and chemotherapy, prenatal diagnosis, genetics and sperm sorting for sex preselection). In marine biology, the autofluorescent properties of photosynthetic plankton can be exploited by flow cytometry in characterizing abundance and community composition. In protein engineering, flow cytometry is used in conjunction with yeast display and bacterial display to identify cell surface-displayed protein variants with desired properties. A common variation of flow cytometry is physically sorting particles based on their properties thereby purifying a population of interest.

An entire flow cytometer system includes the following main components.

1. A flow cell through which a liquid stream, usually called a sheath flow, liquid or fluid, carries and hydrodynamically aligns cells or particles so that they pass single file through the flow cell.

- 2 -

2. A measuring subsystem system coupled to the flow cell that detects cells or particles passing through the flow cell and is usually either:

- 5           a. an impedance or conductivity measuring subsystem; or
- b. an optical illumination subsystem together with an optical sensing subsystem.

10       3. A conversion subsystem for converting the output signal from the measuring subsystem into computer processable data.

4. A computer for analyzing the data produced by the conversion subsystem.

15       The optical illumination subsystems provides a collimated and then focused beam of light, usually laser light of a single wavelength, that impinges upon the hydrodynamically-focused stream of liquid passing through the flow cell. Accordingly, the flow cytometer system may have one or more light sources that may include:

- 20           1. one or more lamps, e.g. mercury or xenon;
2. one or more high-power water-cooled lasers, e.g. argon, krypton or dye laser;
3. one or more low-power air-cooled lasers, e.g. argon (488 nm), HeNe (red-633 nm), HeNe (green) and HeCd (UV); and/or
- 25           4. one or more diode lasers (blue, green, red and violet).

      The optical sensing subsystem includes one or more detectors aimed where the focused liquid stream passes through the light beam. Such detectors may include:

- 30           1. detectors in line with the light beam (Forward Scatter or FSC);
2. detectors perpendicular to it (Side Scatter or SSC); and
3. fluorescence detectors.

35       Each suspended particle passing through the beam scatters the light, and fluorescent material present in the particle or attached to the particle excited by the impinging light emit light at a longer wavelength than that of the impinging light.

- 3 -

Detecting and analyzing brightness changes in a combination of scattered and fluorescent light at each detector (one for each fluorescent emission peak) permits deriving various types of information about the physical and chemical structure of each individual particle. FSC correlates with cell volume. Due to light being scattered off of internal components within a cell, SSC depends on the inner complexity of the particle (i.e., shape of the nucleus, the amount and type of cytoplasmic granules or the membrane roughness). Some flow cytometers omit a fluorescence detector and detect only scattered light. Other flow cytometers form images of each cell's fluorescence, scattered light, and transmitted light.

The flow cytometer system's conversion subsystem, which may include one or more amplifiers which may be either linear or logarithmic, generally includes one or more Analogue-to-Digital Converters ("ADCs") for converting the measuring subsystem's output signal into data that is then processed by the computer.

Modern flow cytometers usually include up to four (4) lasers and numerous fluorescence detectors. Increasing the number of lasers and detectors permits labeling cells with several different antibodies, and can more precisely identify a target population by their phenotypic markers. Some instruments can even capture digital images of individual cells, allowing for the analysis of a fluorescent signal location within or on the surface of cells.

#### **Sample Illumination**

In most of the instruments, particles of interest, such as blood cells or microspheres, are carried by the sheath flow using hydrodynamic focusing into a viewing zone inside a cuvette or jet stream and illuminated there by a focused laser beam. The technique provides the means to accurately identify and count particles of interest without being overwhelmed by background noise occurring outside a registration time window (Practical Flow Cytometry, Howard M. Shapiro, Wiley (2003) ISBN 0471411256). To increase detection sensitivity, the cross section of the focused laser beam is usually elliptical, with

- 4 -

the minor axis along the direction of flow. In order to maintain the threshold integrity, the laser profile must have a smooth or bell shaped profile along the flow direction. One common method for producing such an beam is to elongate a  
5 nearly collimated circular Gaussian beam along the direction of flow with a beam expander made of either prism or cylindrical lens pair, then focus the beam down with a spherical lens. Since the shape of the beam at the focus is the spatial Fourier transform of the beam at far field, this  
10 produces a Gaussian shaped elliptical spot with minor axis along the flow.

Conventional lasers are expensive, bulky and power hungry. More recently, laser diodes ("LD") have become available. Differing from conventional lasers, the new generation of LDs  
15 is cost effective, compact and power efficient, and shows great promise for new generation of compact biomedical instruments. A LD emits light having an elliptical cross-section with the ellipse's major axis, frequently called the fast axis, perpendicular to the LD's junction, and the ellipse's minor  
20 axis, frequently called the slow axis, parallel to the LD's junction. Unfortunately, the beam quality of a typical LD, particularly along its fast axis, leaves much to be desired, preventing its wide acceptance in flow cytometric applications.

In principle, the quality of the LD beam can be  
25 significantly improved by spatial filtering. If a small pinhole or a single mode optical fiber is positioned at the focal point of a lens, such that it only accepts the lowest order spatial mode, the beam passing through the pinhole or single mode optical fiber will be of nearly perfect Gaussian  
30 shape. United States Patent no. 5,788,927 discloses that such a beam can then be collimated and expanded in the direction of flow through the cytometer, and finally focused down to an elliptical shaped Gaussian beam with minor axis along the flow direction. Unfortunately, the size of desktop instrumentation  
35 limits the diameter of a pinhole to less than 5 micron. The core size of a visible wavelength single mode optical fiber also has a similar dimension. The challenge to manufacture such a precision spatial filter and maintain its long-term



- 5 -

stability not only increases the cost of LD based laser system, but also reduces its reliability.

More recently, in an effort to reduce the possible side lobes due to the edge effect of limited numerical aperture of collimating lens, United States Patent no. 6,713,019 ("the '019 patent") discloses rotating the LD by ninety degrees (90°) such that its slow axis is parallel to the direction of flow. A beam diffusing section, such as a concave cylindrical lens, is then introduced to diffuse the collimated beam in the direction perpendicular to the flow, followed by a beam spot forming section, such as a spherical focusing lens, to form an elliptical spot within the cytometer's particle viewing zone. As described in detail in the '019 patent, the laser beam after the spot forming section is extremely astigmatic. In particular, the width of the beam at the viewing zone in the direction perpendicular to the flow is comparable or even wider than the width of the flow channel. This not only reduces the amount of laser energy impinging upon the particle and consequently the signal intensity, but also increases undesired background scattering from the liquid-flow cell interface. Instead of rotating the LD, United States Patent nos. 7,385,682 and 7,561,267 disclose using a large numerical aperture aspheric lens for LD collimation. Such a design, however, cannot correct the fringe effect inherent in the LD's beam profile. Consequently, there presently exists a need for a simple LD based optical system for use in flow cytometers that can reliably produce a focused elliptical beam with near Gaussian shape along its minor axis and a width along major axis.

#### **Viewing Zone Microscope Objective**

Modern flow cytometers include a spatial filter, usually either a mechanical pinhole or a large core optical fiber, located at an image location of an objective lens to prevent undesired background light from entering the cytometer's detector(s). Because particles remain in the cytometer's viewing zone for a few microseconds, microscope objectives with large numerical aperture must be used to maximize light

- 6 -

collection efficiency. To support multiple spatially separated excitation laser beams in flow cytometers, as disclosed in United States Patent no. 4,727,020, it is also desirable to use an objective with large field of view. In order to achieve these goals, United States Patent nos. 6,510,07 and 7,110,192 disclose an objective design using modified apochromat with a gel-coupled or epoxy bonded near hemisphere lens as the optical element closest to the sample that is followed by multiple meniscus lenses. While such microscope objectives provide both a satisfactory numerical aperture and field of view, they significantly sacrificed image quality thereby:

1. limiting effective use of the spatial filter; and
2. exhibiting poor background light discrimination.

Further, such refractive microscope objectives are bulky, expensive to manufacture and often exhibit severe chromatic aberration. To overcome these limitations Published Patent Cooperation Treaty ("PCT") Patent Application no. WO 01/27590 discloses an alternative objective design based on a spherical concave mirror. The design offers large numerical aperture and good image quality along the optical axis. However, due to its poor off-axis characteristics, such a design is unsuitable for flow cytometers having multiple, spatially separated laser beams.

## **25 Sheath Liquid Supply**

The performance of a flow cytometer depends critically on a stable liquid sheath flow. In particular, flow cytometers that have multiple spatially separated excitation laser beams or perform droplet sorting rely on a constant velocity of the liquid sheath flow for timing synchronization. As disclosed in United States Patent no. 5,245,318, conventional flow cytometers provide a stable liquid sheath flow by using an air-tight fluidic system that either:

1. applies constant air pressure in a sheath liquid reservoir to push the fluid through the flow cell; or
2. by sucking the fluid from the sheath liquid reservoir through the flow cell using a vacuum pump.

- 7 -

These systems are bulky, expensive to manufacture and prone to failure. More recently, United States Patent no. 8,187,888 discloses including a sheath liquid subsystem that pumps the liquid sheath flow from the sheath liquid reservoir into the viewing zone and a waste sheath liquid pump that pumps waste sheath liquid from the viewing zone into the waste tank. Although it appears that the disclosed sheath liquid subsystem has never been used in velocity critical flow cytometers, this patent reports that the disclosed sheath liquid subsystem overcomes most of the drawbacks of conventional sheath liquid flow stabilization by:

1. damping pump pulsations by locating:
  - a. one fluidic capacitor between the sheath liquid pump and the flow cell; and
  - b. another fluidic capacitor between the flow cell and the waste pump; and
2. a pump controller whose operation is responsive to a pressure sensor that measures the pressure differential between the inlet and outlet of the flow cell.

The disclosed sheath liquid subsystem has other limitations. For example, the pressure sensor located near the outlet of the flow cell could be a potential source of contamination.

#### **Peristaltic Pump Sample Liquid Supply**

Peristaltic pumps are volumetric pumps in which a set of linearly or circularly moving rollers progressively compresses a compressible tube to propel the fluid through the tube. Peristaltic pumps are widely used particularly to pump clean/sterile or aggressive fluids to avoid cross contamination with exposed pump components.

Conventional peristaltic pump exhibits a pulsation each time a roller rolls off the tube near the pump outlet, caused by the temporary increase of tube volume when the compressed tube expands back to its original shape. The pulsation is undesirable in applications that require smooth flow. Many attempts have been made in the past to reduce the pulsation. For example, United States Patent nos. 3,726,613 and 3,826,593

- 8 -

introduced a cam operated pusher which synchronously exerts an external pressure on the tube to compensate for the tube expansion. In United States Patent no. 4,834,630, a plurality of tubes mounted on segmented rollers are joined together at the pump inlet and outlet by T-shaped couplers such that pulsations from individual tubes would be reduced by averaging. United States Patent no. 7,645,127 proposed a pump tube with slightly larger inner diameter near the inlet so that the tube decompression near the pump outlet is compensated by the compression of a larger volume tube near the inlet. The various methods either significantly increased the complexity of the peristaltic pump or had limited success in reducing the pulsation effect.

#### 15 **Mmulticolor Fluorescence Detection**

In many multicolor fluorescence detection instrumentations, such as flow cytometers, (Practical Flow Cytometry, Howard M. Shapiro, Wiley (2003) ISBN 0471411256), the fluorescence light emitted from the object of interest is:

- 20 1. collected by a microscope objective;
2. reimaged through a small pinhole or a multimode optical fiber;
3. then collimated and separated into multiple colored bands; and
- 25 4. finally detected by photo detectors such as photomultiplier tube (PMT), PIN photodiode or avalanche photodiode (APD).

A PMT is essentially a special type of electron tube. This "pre-semiconductor age" device is bulky and expensive. In addition, it has poorer quantum efficiency and less reproducible spectral response than silicon based semiconductor detectors, particularly in the biologically important red to near infrared spectral region. Despite the disadvantages, PMT has excellent noise characteristics. For example, the dark current of a typical 13mm PMT (e.g., the R9305 from Hamamatsu Corporation of Japan) is only about 1nA. In contrast, an APD's dark current would be 10 times greater even if its active area were reduced to 1/20<sup>th</sup> of that of the PMT. As a result, PMT

- 9 -

has been the de-facto low-level light detector in many commercial fluorescence detection flow cytometers. Only in certain scientific applications where event rate is low and dark current may be discriminated against by expensive photon-counting techniques that the PMT has been replaced by APD detectors. (c.f., High-Throughput Flow Cytometric DNA Fragment Sizing, A.V. Orden, R.A. Keller, and W. P. Ambrose, *Anal. Chem.*, 2000, 72 (1), p 37-41). More recently, a Geiger mode APD array was also promoted as PMT replacement. (For example, the multi-pixel photon counter of Hamamatsu Photonics of Japan and the solid-state photomultiplier of SensL Inc. of Ireland.) These detectors, however, also have high dark current and are nonlinear at high event rate.

The only industry where APD has found wide acceptance is in optical communication. It is known that if the APD's active area is reduced to less than  $1\text{mm}^2$ , the corresponding dark current will be reduced to the same level as a PMT. In optical communication, the light is a laser beam out of single mode optical fiber. Such a beam can be easily collimated then focused down to an area much smaller than  $1\text{mm}^2$ . It should be noted that the color separation devices used in the fluorescence light detection instruments, as described in United States Patent no. 6,683,314 and references therein, are almost identical in function and architecture to the wavelength division multiplexers (WDM) widely used in optical communication, as described in United States Patent nos. 4,482,994, and 5,786,915. A fundamental reasons preventing the use of small area APD in fluorescence detection instrumentation is the well known theorem of etendue conservation: the fluorescence light coming through a pinhole or multimode optical fiber is an extended light source with an etendue hundreds of times greater than that of a laser beam out of a single mode optical fiber. Consequently, as illustrated in FIG. 26, it cannot be collimated over an extended distance unless the diameter of the beam is significantly expanded. Unfortunately, the larger the beam diameter, the greater the technical challenge to focus it down to a small spot. Since efficient color separation can only be accomplished

- 10 -

economically with collimated light beam, small area APD has not been considered viable for multicolor fluorescence light detection applications. Clearly, a technology capable of collimating a large etendue light beam over an extended distance without significantly expanding the beam diameter would be highly desirable. Such a technology would enable a WDM like device for fluorescence light detection with characteristics comparable to low noise semiconductor detectors.

10

### Disclosure

The present disclosure provides an improved flow cytometer together with various improved components included therein.

It is an object of the present disclosure to provide a simple and reliable diode laser based optical system capable of delivering a focused laser beam of elliptical cross section with a Gaussian like intensity distribution along its minor axis and a width along major axis optimized for flow cytometric applications.

20 An object of the present disclosure is an imaging quality microscope objective that is easy to manufacture. has long working distance, large numerical aperture. large field of view and minimal chromatic aberration.

25 An object of the present disclosure ia a simple fluidics system for flow cytometers that is not only reliable, compact and easy to manufacture, but also capable of supporting velocity critical applications such as in instruments with multiple spatitally separated excitation laser beams or in droplet sorters.

30 A object of the present disclosure is simple design for a peristaltic pumb can provide a pulseless liquid flow is highly desirable.

An object of the present disclosure to provide a peristaltic pump with minimal pulsation.

35 A object of the present disclosure to provide a peristaltic pump that is simple to manufacture and operate.

an object of the present disclosure to provide a device capable of collimating a light beam from an extended light

- 11 -

source over an extended distance without significantly expanding the said beam diameter. It is also an object of the present disclosure to provide a WDM system using the said device to separate the said light beam into multiple colored bands.

5 Further, it is an object of the present disclosure to provide such a WDM system that is compatible with low noise semiconductor detectors. In addition, due to the diversity of fluorescent probes, it is an object of the present disclosure to provide such a WDM system that is reconfigurable.

10 Disclosed herein is a flow cytometer that includes:

1. a LD based optical subsystem for impinging a beam of light upon particles passing through a viewing zone;
2. a composite microscope objective for gathering and  
15 imaging light scattered from or fluoresced by particles passing through the viewing zone;
3. a fluidic subsystem for supplying a liquid sheath flow to the viewing zone;
4. a peristaltic pump for injecting into the liquid  
20 sheath flow a liquid sample flow carrying particles that passes together with the liquid sheath flow through the viewing zone;
5. a multimode optical fiber that receives scattered and fluoresced light from the viewing zone that the composite microscope objective gathers and images;  
25 and
6. a wavelength division multiplexer for optically separating into color bands light received via the optical fiber .

The LD based optical subsystem in accordance with the  
30 present disclosure for illuminating particles passing through the flow cytometer's viewing zone generally includes:

1. a laser diode oriented with its slow axis parallel to the direction of flow;
2. a collimating lens that converts the diverging beam  
35 from the LD into a collimated beam of elliptical shape with its major axis perpendicular to the flow;

- 12 -

3. a focusing lens system that reduces the laser beam at the viewing zone to an optimal width in the direction perpendicular to the flow; and
4. finally a high power cylindrical focusing element placed in the proximity of the viewing zone with its axis perpendicular to the direction of flow.

The high power cylindrical focusing element transposes the far field profile of the LD along its slow axis to its Fourier conjugate at the viewing zone along the direction of flow, while maintains the transverse beam profile, such that the laser beam profile at the viewing zone is optimal for flow cytometric applications.

The composite microscope objective in accordance with the present disclosure generally includes:

1. a concave spherical mirror;
  2. a transparent aberration compensation plate
- with the flow cytometer's a viewing zone being located between the mirror and the plate. Scatter and fluorescence light emitted from particles in the viewing zone is collected by the mirror and reflected back toward the compensation plate. Optical aberrations originating from the mirror are significantly reduced after light passes through the compensation plate. In one embodiment of the present disclosure, the viewing zone is located inside a flow cell provided by rectangular glass cuvette with a small rectangular channel through which a particle carrying liquid flows. The concave mirror is made of an optically transparent material, such as glass or optical quality plastics, of piano-convex shape with a highly-reflective coating on the convex side for internal reflection. The piano-side of the mirror is either gel-coupled or bonded to one side surface of the cuvette. The plano-aspheric compensation plate is made of a transparent material, such as glass or optical quality plastics, with the piano side gel-coupled or bonded to the opposite side of the cuvette. The piano-convex shaped mirror and the aspheric compensation plate may also be formed integrally with the cuvette. In yet another embodiment of the present disclosure, the viewing zone is in a jet stream with both the concave



- 13 -

mirror and the compensation plate being free standing from the viewing zone, and the mirror is preferably a front surface concave mirror.

5 The fluidic system in accordance with the present disclosure generally includes a sheath liquid reservoir from which a liquid pump draws sheath liquid. Sheath liquid then flows from the liquid pump to an inlet of a T-coupling. One outlet arm of the T-coupling connects to a bypass that returns a fraction of the pumped sheath liquid back to the sheath  
10 liquid reservoir with the returned sheath liquid flowing into air within the sheath liquid reservoir. A second outlet arm of the T-coupling connects to a sheath route that includes a reservoir capsule followed by a particle filter and then the flow cell. The sheath liquid exiting the flow cell then goes  
15 to the waste tank. The fluidic resistance along the bypass is designed to be lower than the fluidic resistance along the sheath route. Consequently, only a small fraction of the sheath liquid goes through the flow cell. Note that typical sheath flow rate in flow cytometric applications is a few tens  
20 of milliliter per minute. The bypass therefore permits using higher flow rate liquid pumps that not only are much less expensive and more reliable, but also operates at higher pulsation frequency which is much easier to attenuate. Since the exit of the bypass route connects to air, it also serves  
25 as a large fluidic capacitor for significantly reducing pulsation in sheath liquid flowing along the sheath route. During operation, the inlet portion of the filter cartridge is filled with air. Therefore, the filter cartridge also serves as a fluidic capacitor, for further reducing pulsation in the  
30 sheath liquid at the flow cell to negligible level. Due to the large fluidic resistance at the flow cell, the air trapped near the inlet of the filter cartridge becomes compressed. If the liquid pump is turned off, the compressed air in filter cartridge being pushed back towards the sheath liquid reservoir  
35 becomes stored in the reservoir capsule whose size is chosen to prevent the trapped air from reaching the T-coupling.

The peristaltic pump in accordance with the present disclosure generally includes a plurality of rollers located

- 14 -

at the periphery of a rotor that moves the rollers circularly inside a housing's arcuate curved track and a compressible tube that the rollers compress against the track. In one embodiment of the present disclosure, the track of the peristaltic pump's housing has one recess so the compressible tube is progressively decompressed to full expansion then compressed to full closure every time one of the rollers moves past the recess. The location and shape of the recess maintains the total volume of liquid within the compressible tube from the recess to the pump's outlet substantially invariant. The effect of tube expansion as a roller moves past the pump's outlet is compensated by the tube compression when a different other roller immediately upstream of the pump outlet moves into the recess' compressing section. In another embodiment of the present disclosure, the track of the pump housing may contain a plurality of recesses, providing for a plurality of roller upstream of the pump outlet to progressively modify the tube compression in multiple sections along the compressible tube. The locations and shapes of the plurality of recesses are designed such that the modification of tube compression at these sections substantially compensates the effect due to the tube expansion near the pump outlet. In yet another embodiment of the present disclosure, the compressible tube is kept fully closed underneath the roller except in the inlet and exit sections. A variable speed motor is used to drive the pump. When a roller reaches the exit section, the motor's rotation programmatically speeds up to compensate for the tube's expansion.

The wavelength division multiplexer ("WDM") in accordance with the present disclosure generally includes at least two optical elements. The first optical element collimate a beam of light received from an extended light source, such as the light from a pinhole or from a multimode optical fiber. The first optical element magnifies the extended light source, for example, as defined by the pinhole, or the core of the multimode optical fiber, to an image having a size similar to the effective cross section of the first optical element thereby creating a collimated light beam between the first

- 15 -

optical element and its image. A second optical element is positioned near the image, and relays the first optical element with unit magnification down the optical path. In this way the second optical element effectively doubles the collimated path length. Additional optical elements in the same 1:1 image relay configuration may also be included in the present disclosure to further extend the collimated optical path. The cascaded unit-magnification image relay architecture of the present disclosure provides a greatly extend the collimated optical path length without large beam expansion. As a result, WDM techniques well-established in the optical communication industry can be readily adapted for fluorescence light detection. In particular, multiple colored bands present in the beam of light can be separated using dichroic filters, located along the optical path with the separated light being tightly focused into small spots compatible with low noise semiconductor photodetectors.

In one embodiment of WDM, the first optical element is a lens and the second element is a concave mirror, although it is apparent to those skilled in the art that other types of refractive and/or reflective optical components may also be used to achieve the same design goal. Similar to its counterpart in optical communication, the optical path in the WDM of the present disclosure may be folded using dichroic filters. In one embodiment of the present disclosure, the light path is folded into a zig-zag configuration. Preferably, to facilitate the flow cytometer's reliable reconfiguration each dichroic filter is bonded to a mechanical holder having a reference surface that is optically parallel to the filter's reflective surface. As a result, all of the WDM's filters can be accurately positioned along the optical path by referencing the filter's holder against a common optical flat.

In another embodiment of the present disclosure, the collimated beam passing through the dichroic filter is further branched out into multiple colored bands using secondary dichroic filters. It is apparent to those skilled in the art that dichroic filters may be inserted anywhere along the long, narrow and collimated beam path afforded by the present

- 16 -

disclosure's relay imaging to thereby permit delivering a tightly focused beam to photo detectors using a variety of optical configurations, such as the star configuration discussed in United States Patent no. 6,683,314, the branched configuration discussed in United States Patent no. 4,727,020 and other types of WDM optical configuration widely practiced in the optical communication industry. Instead of concave mirrors, the WDM may be replaced by curved dichroic filters to further increase the number of colored bands selected by the WDM.

These and other features, objects and advantages will be understood or apparent to those of ordinary skill in the art from the following detailed description of the preferred embodiment as illustrated in the various drawing figures.

#### Brief Description of Drawings

FIG. 1 is a diagram schematically illustrating a preferred embodiment of a flow cytometer in accordance with the present disclosure that includes:

- a) a LD based optical illumination subsystem;
- b) a composite microscope objective upon which light emitted from the LD based optical illumination subsystem impinges, the composite microscope objective having a fluid-passing channel formed therethrough with a particle illumination viewing zone located inside a cuvette thereof;
- c) a fluidic system for supplying a pulsation free flow of sheath liquid to the fluid-passing channel formed through the composite microscope objective;
- d) a peristaltic pump for introducing a pulsation free flow of sample liquid that carries cells or particles to be analyzed into the sheath flow of liquid supplied by the fluidic system; and
- e) a wavelength division multiplexer ("WDM") having a zig-zag configuration for separating a beam of light into several different colored bands, the WDM receiving via an optical fiber light that is scattered from cells or particles as they pass

- 17 -

through the composite microscope objective's fluid-passing channel and are illuminated therein by light emitted from the LD based optical illumination subsystem.

5       FIG. 2 is a schematic view depicting a typical high power edge emitting LD that illustrates the fast and slow axes of light emitted therefrom.

FIG. 2A shows a typical far field profile for a laser beam emitted from the LD chip depicted in FIG. 2.

10       FIG. 3A depicts a 3-dimensional view of a conventional, prior art LD based optical illumination subsystem for flow cytometric instruments together with the system's flow cell.

FIG. 3B depicts a typical time dependent profile of light scattering from a cell or particle passing through the laser beam depicted in FIG. 3A at the focus thereof within the system's flow cell.

15       FIG. 4A is an elevational view of an alternative prior art LD based optical illumination subsystem configuration across the liquid flowing through the fluid-passing channel that improves the beam profile at the focus thereof in the flow cytometer system's viewing zone.

FIG. 4B is a plan view along the liquid flowing through the fluid-passing channel of the alternative prior art LD based optical illumination subsystem depicted in FIG. 4A.

25       FIG. 5A is an elevational view across liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1 wherein the LD's slow axis oriented transversely to the liquid flow.

FIG. 5B is a plan view along liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1 wherein the LD's slow axis oriented transversely to the liquid flow.

30       FIG. 5C depicts a typical time dependent profile of light scattering from a cell or particle passing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1.

FIG. 6 is a perspective view of an alternative embodiment of a LD based optical illumination subsystem in accordance with

- 18 -

the present disclosure adapted for use in a flow cytometer system in which a jet stream of liquid passes through the viewing zone.

FIG. 6A is an enlarged perspective view of the alternative  
5 embodiment of a LD based optical illumination subsystem of depicting in greater detail the jet stream of liquid passes through the viewing zone.

FIG. 7 is a perspective view of an alternative embodiment  
LD based optical illumination subsystem in accordance with the  
10 present disclosure adapted for use in a flow cytometer system which orients the LD's slow axis parallel to the direction of liquid flowing through the fluid-passing channel of the composite microscope objective depicted in FIG. 1.

FIG. 8 is a perspective view of a composite microscope  
15 objective in accordance with the present disclosure adapted for use in the flow cytometer system depicted in FIG. 1, the composite microscope objective having a fluid-passing channel formed therethrough with the particle illumination viewing zone located inside a cuvette therein.

FIG. 9A is a cross-sectional elevational view of the  
20 composite microscope objective taken along the line 9A-9A in FIG. 8 that includes ray traces from three (3) spatially separated locations in the viewing zone to an image plane for the objective illustrating scatter and fluorescence emission  
25 propagation.

FIGs. 9B1-9B3 are spot diagrams near the image plane depicted in FIG. 9A for the three (3) spatially separated light emission locations depicted in FIG. 9A.

FIG. 10 is a cross-sectional elevational view similar to  
30 that of FIG. 9A for an alternative embodiment composite microscope objective in accordance with the present disclosure that includes ray traces from three (3) spatially separated locations in a viewing zone therein to an image plane for the objective illustrating scatter and fluorescence emission  
35 propagation.

FIG. 11 is a perspective view of yet another alternative embodiment a composite microscope objective in accordance with the present disclosure adapted for use in the flow cytometer

- 19 -

system depicted in FIG. 1, the alternative embodiment composite microscope objective having a fluid-passing channel formed therethrough with the particle illumination viewing zone located inside a cuvette therein.

5        FIG. 12 is a perspective view of yet another alternative embodiment a composite microscope objective in accordance with the present disclosure adapted for use in the flow cytometer system depicted in FIG. 1, the alternative embodiment composite microscope objective being adapted for a viewing zone that is  
10        located inside the jet stream depicted in FIGs. 6 and 6A.

FIG. 13 is a perspective view of yet another alternative embodiment a composite microscope objective in accordance with the present disclosure adapted for use wherein a viewing zone is located on the surface of a microscope slide.

15        FIG. 14 is a schematic diagram depicting a fluidic subsystem in accordance with the present disclosure for supplying stable liquid sheath flow to a flow cytometers flow cell that includes:

- 20        1. a small capsule located between a sheath liquid pump and the flow cell; and
2. a particle filter located between the small capsule and the flow cell,

both the particle filter and the small capsule providing air reservoirs for dampening pump pulsations.

25        FIG. 15 is a schematic diagram depicting an alternative embodiment fluidic subsystem similar to that illustrated in FIG 14 that replaces the small capsule with a length of tubing for providing an air reservoir.

30        FIGs. 16A and 16B are histograms that compare measured particle flight times at the flow cell when the inlet portion of the particle filter has air trapped therein (FIG. 16A), and when there is no air within the fluidic subsystem between sheath liquid pump the and the flow cell (FIG. 16B).

35        FIG. 17 is a perspective view of a 3-roller peristaltic pump in accordance with the present disclosure depicting the pump's rollers, tube and surrounding pump housing.

- 20 -

FIGs. 18A through 18D depict simplified views for several states of the 3-roller peristaltic pump depicted in FIG. 17 with the rollers in different locations.

FIGs. 19 is a detailed longitudinal cross-sectional view of the peristaltic pump's tube being partially compressed by the pump's roller.

FIG. 19A and 19B are detailed cross-sectional views orthogonal to the peristaltic pump's tube's length taken along the lines 19A and 19B in FIG. 19 illustrating the tube's partial compression by the roller.

FIGs. 20A and 20B are schematic diagrams illustrating the pump's rollers and tube viewed along the pump's circular coordinates to depicting the pulseless provided by the peristaltic pump.

FIGs. 21 is graph depicting the functional relationship with respect to the roller position when it rolls off the exit section of the compressible tube of:

1. the total volume of liquid in the exit half of the pump; as well as
2. the liquid volumes in the pump's:
  - a. recess section; and
  - b. exit section.

FIGs. 22 is a simplified plan view of a 4-roller peristaltic pump in accordance with the present disclosure.

FIGs. 23 is a simplified plan view of a 6-roller peristaltic pump in accordance with the present disclosure.

FIG. 24A is a longitudinal cross-sectional illustration of rollers and a compressible tube for a pulsation minimizing 3-roller peristaltic pump in accordance with the present disclosure having a rotor with programmable speed.

FIG. 24B is simplified plan view illustrating the pulsation minimizing 3-roller peristaltic pump in accordance with the present disclosure having a rotor with programmable speed.

FIG. 24C is a graph depicting for the pulsation minimizing peristaltic pump depicted in FIG. 24B having a programmable speed rotor:



- 21 -

1. negative volume change rate with respect to the roller position;
2. rotor speed; and
3. pump flow rate.

5 FIG. 25 is a diagram illustrating optical ray tracing for an exemplary 6 port wavelength division multiplexer ("WDM") using zig-zag configuration in accordance with the present disclosure.

10 FIG. 26 is a diagram illustrating ray tracing of prior art collimating devices showing the device's limitation in collimating an extended light source.

FIG. 27 is a perspective illustration of an embodiment of a 6 ports WDM using a combination of zig-zag and branched configurations in accordance with the present disclosure.

15 FIG. 28 is a perspective illustration of another embodiment of a WDM having a concave dichroic filters in accordance with the present disclosure.

FIGs. 29A and 29B are perspective illustrations depicting assembly process for constructing replaceable dichroic filter assembly for an reconfigurable WDM in accordance with the present disclosure.

FIGs. 29C is a perspective illustration of a replaceable dichroic filter assembly build in accordance with the illustrations of FIGs. 29A and 29B.

25 FIGs. 30A and 30B are perspective illustrations of a WDM in accordance with the present disclosure depicting installing into the WDM the replaceable dichroic filter assembly depicted in FIG. 29C and its removal therefrom.

30 **Best Mode for Carrying Out the Disclosure**

**Flow Cytometer**

FIG. 1 depicts a flow cytometer in accordance with the present disclosure identified by the general reference number

35 40. The flow cytometer 40 includes:

1. a LD based optical subsystem 50;
2. a composite microscope objective 60;

- 22 -

3. a fluidic subsystem 70 for supplying a liquid sheath flow;
4. a peristaltic pump 80 for injecting a liquid sample flow that contains particles to be analyzed into the liquid sheath flow supplied by the fluidic subsystem 70, the liquid sample flow becoming hydrodynamically focused by the liquid sheath flow passes through a viewing zone with the composite microscope objective 60 gathering and imaging light scattered and/or fluoresced by particles in the viewing zone;
5. an optical fiber 852 that receives light scattered and/or fluoresced by particles in the viewing zone that the composite microscope objective 60 gathers and images; and
6. a wavelength division multiplexer 90 ("WDM 90") for optically processing scattered and/or fluoresced light received from the optical fiber 852.

**Optical Subsystem 50**

The optical subsystem 50 includes a LD 501 that, as depicted in greater detail in FIG. 2, emits a diverging beam of light from an edge thereof. As more graphically depicted in FIGs 2 and 2A, the diverging beam of light has an elliptically shaped cross-sectional profile with both a major axis, a.k.a. the fast axis, and a minor axis, a.k.a. the slow axis. The diverging beam of light emitted from the LD 501 impinges upon a collimating lens 502 which converts the diverging beam of light emitted by LD 501 into a collimated beam of light having an elliptical cross-section. Although not essential, the optical subsystem 50 may also include an optional mirror 503 positioned to direct the collimated elliptical beam of light towards the composite microscope objective 60. A plano convex lens 504, positioned near the the elliptically shaped beam of light that is oriented perpendicular to the direction in which the liquid sample and the surrounding liquid sheath flow through the viewing zone

- 23 -

within the composite microscope objective 60. At the viewing zone, the width of the elliptically shaped beam of light:

1. perpendicular to the direction in which the liquid sample flow passes through the viewing zone is preferably slightly less than the width of the liquid sheath flow; while
2. still sufficiently wide so particles in the sample flow pass through a nearly flat portion of the elliptically shaped beam of light at the beam's maximum intensity.

In accordance with the present disclosure, it is apparent to those skilled in the art that the plano convex lens 504 may be replaced by other types of optical elements such as an achromatic doublet lens or combination of spherical lenses, cylindrical lenses, and/or prism pairs. Alternatively, the mirror 503 and the lens 504 may also be replaced by a concave mirror. For polarization sensitive applications of the flow cytometer 40, an optional polarization conditioning element, such as a half-wave plate, may also be placed in the collimated section of the beam of light extending from the collimating lens 502 to the lens 504. Finally, before passing through the viewing zone the beam of light passes through a high power cylindrical lens 505, positioned adjacent to the viewing zone. As depicted in FIG. 1, the axis of the cylindrical lens 505 is oriented perpendicular to the direction in which the liquid sample flow passes through the viewing zone, and the focal length of the cylindrical lens 505 produces a tight focusing of the beam of light's minor axis at the viewing zone.

An advantage of the optical subsystem 50 in comparison with conventional LD based optical subsystem may be discerned more clearly in FIGs. 2 and 2A. Most commercially available laser diodes suitable for use in a flow cytometer emit a beam of light from an edge thereof. As depicted in FIG. 2, a gain section 509 of such a LD chip 510 is highly confined in the transverse direction indicated by an arrow 511. Consequently, to achieve high output power LD manufacturers often sacrifice beam quality, particularly along the transverse or fast axis direction that is oriented parallel to the arrow 511. FIG. 2A

- 24 -

shows this characteristic of light emitted from a LD wherein multiple fringes 512 due to gain confinement are clearly visible at the far field in the minor axis direction of the emitted beam of light. It should be noted that the fringes 512 appearing in the illustration of FIG. 2A contain only a minute amount of total energy in the beam of light, and therefore have little impact on the conventional M-square characterization of the corresponding beam profile. However, as discussed in greater detail below, the fringes 512 do have a detrimental effect on the performance of conventional flow cytometers. Alternatively, gain confinement along the slow axis direction of an edge emitting LD that is oriented perpendicular to the arrow 511 is much more relaxed. Consequently, as shown in FIG. 2A, the far field beam profile is much smoother along the slow axis of the LD's beam of light.

FIG. 3A depicts a conventional LD based optical subsystem for a flow cytometer. Those elements depicted in FIG. 3A that are common to the optical subsystem 50 illustrated in FIG. 1 carry the same reference numeral distinguished by a prime (') designation. As depicted in FIG. 3A, the conventional optical subsystem orients the fast axis of the LD 501 parallel to the direction in which the liquid sample flow passes through the viewing zone. In its most simplified configuration, the elliptical beam profile of the LD 501' is directly transposed by the spherical focusing lens 504' into the viewing zone. In an attempt to achieve optimal aspect ratio for the focused beam of light, various different conventional LD based optical subsystems have also included beam shaping optical elements in addition to those depicted in FIG. 3A

The detrimental effect of fringes 512 along the fast axis of the LD 501' for conventional optical subsystem configurations clearly appears in the light scattering time profile depicted in FIG. 3B. Since scattering or fluorescence intensity is directly proportional to the local laser power impinging upon a particle, any fine structure in the beam of light's profile along the direction in which the liquid sample flow passes through the viewing zone will appear in the time profile of the signal produced by the flow cytometer. Such

- 25 -

structures in the time profile are indistinguishable from signals generated by small particles, and will therefore cause the flow cytometer to trigger falsely and misidentify particles. In addition, the fringes 512 will also lead to  
5 uncertainty in the measurement of other cytometric parameters, such as in the area and width of the pulse depicted in FIG. 3B.

FIGs. 4A and 4B depict a yet another prior art optical subsystem for LD based flow cytometric applications disclosed in the '019 patent identified previously. Those elements  
10 depicted in FIGs. 4A and 4B that are common to the optical subsystem 50 illustrated either in FIG. 1 or 3A carry the same reference numeral distinguished by a double prime ("') designation. As depicted in FIGs. 4A and 4B, by orienting the slow axis of the LD 501" parallel to the direction in which the  
15 liquid sample flow passes through the viewing zone the optical subsystem depicted in FIGs. 4A & 4B effectively overcomes the problem caused by the fringes 512 as described above. Unfortunately, the beam-diffusing element 513" placed before the spherical focusing lens 504" in FIGs. 4A and 4B to diffuse  
20 the beam of light perpendicular to the direction in which the liquid sample flow passes through the viewing zone produces a highly astigmatic beam of light near the viewing zone. Specifically, focusing this astigmatic beam of light at the viewing zone in the direction in which the liquid sample flow  
25 passes through the viewing zone increases the width of the beam of light perpendicular to the direction in which the liquid sample flow passes through the viewing zone so the beam's width become similar to or even wider than the sheath flow. Consequently, the optical subsystem depicted in FIGs. 4A and  
30 4b not only diminished the amount of light energy impinging upon particles flowing through the viewing zone, the optical subsystem also increases undesirable scattering of light from the interface between the liquid sheath flow and adjacent parts of the composite microscope objective 60.

35 FIG. 5 highlights the main differences between the optical subsystem disclosed in the '019 patent and the optical subsystem 50 depicted in FIG. 1. Instead of placing an out-of-plane beam-diffusing element 513" before the spherical beam

- 26 -

focusing lens 504 as shown in FIG. 4, the high power cylindrical lens 505, depicted in FIGs. 5A and 5B as a cylindrical plano-convex lens, is placed along the beam of light after the spherical beam focusing lens 504 and is preferably juxtaposed with the composite microscope objective 60. As shown in FIGs. 5A and 5B, the cylindrical lens 505 focuses the minor axis of the beam of light in the viewing zone while leaving the major axis of the beam of light essentially unchanged. Consequently, the optical subsystem 50 depicted in FIGs. 1, 5A and 5B establishes a beam of light profile at the viewing zone which is elliptical with:

1. a tightly focused minor axis that spans across the combined liquid sample and sheath flows; and
2. a smooth minor axis profile in the direction of the combined liquid sample and sheath flows that is the Fourier conjugate of the far field beam profile along the slow axis of LD 501.

Meanwhile, as shown in FIG. 5B, the out-of-plane beam width is unaffected by the cylindrical lens 505. FIG. 5C shows a measured time profile of light scattered from a micro particle using the optical subsystem 50 depicted in FIGs. 1, 5A and 5B. The LD 501 used in making the measurement presented in FIG. 5C is the same as that used in generating the measured time profile of light scattered from a micro particle appearing in FIG. 3B. As shown in FIG. 5C, the side lobes caused by the fringes 512 along the fast axis of the LD 501 no longer have any material effect on performance of the flow cytometer 40.

FIG. 6 depicts yet another alternative diode laser based optical subsystem in accordance with of the present disclosure adapted for use in a flow cytometer. Those elements depicted in FIGs. 6 and 6A that are common to the optical subsystem 50 illustrated in FIGs. 1, 5A and 5B carry the same reference numeral distinguished by a triple prime ('') designation. The optical subsystem 50''' depicted in FIGs. 6A and 6B is almost identical to that shown in FIGs. 1, 5A and 5B except that the viewing zone occurs without a composite microscope objective 60 because it occurs in a free-flowing jet stream 519 that includes both the sample and sheath flows that is emitted from

- 27 -

a nozzle 518. Consequently, for the configuration of the optical subsystem 50'" depicted in FIGs. 6A and 6B the high power cylindrical lens 505 is detached from the viewing zone that is located within the jet stream 519.

5 In the exemplary embodiments of the present disclosure depicted in FIGs. 1, 5A, 5B, 6A and 6B, the minor axis, i.e. the slow axis, of the LD 501 is oriented perpendicular to the direction in which the liquid sample flow passes through the viewing zone. However, it will be apparent to those skilled  
10 in the art that using an alternative optical configuration the major axis, i.e. the fast axis, of the LD 501 may be reoriented to be perpendicular to the direction in which the liquid sample flow passes through the viewing zone. FIG. 7 depicts one example of such an alternative configuration of optical  
15 elements. Those elements depicted in FIG.7 that are common to the optical subsystem 50 illustrated in FIGs. 1, 5A, 5B, 6A and 6B carry the same reference numeral distinguished by a quadruple prime ("") designation. As shown, the slow axis of the LD 501"" is oriented in the z-direction. The beam of light  
20 emitted from the LD 501"" is then rotated to the in-plane y-direction by a pair of ninety degrees (90°) reflection mirrors 523a and 523b. In the illustration of FIG. 7, a normal to the first elliptically-shaped light beam reorienting mirror 523a is oriented in the x-y plane at forty-five degrees (45°)  
25 to the x-axis, and a normal to the second elliptically-shaped light beam reorienting mirror 523b is oriented in the y-z plane at forty-five degrees (45°) to the z-axis.

#### **Composite Microscope Objective 60**

30 FIG. 8 depicts one embodiment in accordance with the present disclosure for the composite microscope objective 60 depicted in FIGs. 1, 5A, 5B and 7. As depicted in FIG. 8, the composite microscope objective 60 images a viewing zone that is located inside a prismatically-shaped glass cuvette 603  
35 within a small flow channel 604, that preferably has a rectangular cross-sectional shape, through which passes the particle carrying combined liquid sample and sheath flows. A piano-concave back-surface mirror 601 included in the composite

- 28 -

microscope objective 60 is made of an optically transparent material preferably having a refractive index similar to that of the glass cuvette 603, such as glass or optical quality plastics. To minimize optical loss, the back-surface mirror 5 601 includes a flat front surface that is optically coupled to an abutting flat surface of the prismatically-shaped cuvette 603. Optical coupling of the back-surface mirror 601 to the cuvette 603 may employ an index-matching gel, optical adhesive or direct optical bonding. Alternatively, the back-surface 10 mirror 601 may also be formed integrally with the cuvette 603.

The composite microscope objective 60 also includes a plano-ashperic corrector plate 602 that is also made of an optically transparent material preferably having a refractive index similar to that of the glass cuvette 603, such as glass 15 or optical quality plastics. To reduce optical loss, a flat surface of the corrector plate 602 may be optically coupled to an abutting flat surface of the prismatically-shaped cuvette 603 on a face thereof that is diametrically opposite to the back-surface mirror 601. Optical coupling of the corrector 20 plate 602 to the cuvette 603 may employ an index-matching gel, optical adhesive or direct optical bonding. The aspheric surface of the corrector plate 602 furthest from the corrector plate 602 may carry an anti-reflective coating to reduce optical transmission loss, although such a coating is not a 25 mandatory requirement for a composite microscope objective 60 in accordance with the present disclosure. The shape of the aspheric surface of the corrector plate 602 is similar to that in a classical Schmidt camera, (Schmidt, B., *Mitt. Hamburg Sternwart* 7 (36) 1932). As known by those skilled in the art, 30 the corrector plate of a Schmidt camera includes a circularly shaped neutral zone where the corrector plate does not deviate rays of light passing through the plate. For use in the composite microscope objective 60, outside of the neutral zone of the corrector plate 602, where the plate thickness is 35 thinnest, the corrector plate 602 has negative optical power while inside the neutral zone the corrector plate 602 has positive optical power. The exact shape of the aspheric corrector plate 602 may be readily obtained using any



- 29 -

commercially available optical ray tracing tool by any person having ordinary skill in the art. Note that in the flow cytometer 40 the beam of light generated by the optical subsystem 50 depicted in FIGs. 1, 5A, 5B and 7 enters the  
5 cuvette 603 perpendicularly to the flow channel 604 through one (1) of the two (2) faces of the cuvette 603 that do not abut the back-surface mirror 601 or corrector plate 602.

FIG. 9A depicts the result of ray tracing for the embodiment of composite microscope objective 60 illustrated in  
10 FIG. 8. As depicted in FIG. 9A, scatter and fluorescence emission from three (3) spatially separated locations in the flow channel 604 near the center of the cuvette 603:

1. initially propagate toward back-surface mirror 601 to be internally reflected by the back-surface  
15 mirror 601;
2. then pass first through the cuvette 603;
3. subsequently pass through the aspheric corrector plate 602; and
4. finally forms three (3) distinct images near an  
20 image plane 605.

Note that rays traversing the composite microscope composite microscope objective 60 depicted in FIG. 9A are nearly optically-uniform and that light emitted near the center of the cuvette 603 traverses the corrector plate 602 at near normal  
25 incidence. Consequently, the composite microscope objective 60 introduces very little chromatic dispersion in light emitted near the center of the cuvette 603.

Further, it is well known in the astrophysics community that Schmidt camera offers the unparalleled combination of a  
30 fast focal ratio and a large field of view with near diffraction limited optical performance. The principal drawback in a conventional Schmidt camera is that the image surface lies inside the instrument. For the composite microscope objective 60, light near the center of the cuvette  
35 603 propagates opposite to that of a conventional Schmidt camera and therefore the image surface lies outside the composite microscope objective 60. Consequently, the present disclosure takes full advantage of the optical performance of

- 30 -

the Schmidt camera without experiencing its limitation. FIGs. 9B1 through 9B3 depict spot diagrams near the image plane 605 for three (3) emission locations in viewing zone within the flow channel 604 that are separated 150 micron from each other.

5 The diameters of all images depicted in FIGs. 9B1 through 9B3 are less than 35 microns.

Light emitted from the viewing zone within the flow channel 604 of the composite microscope objective 60 depicted in FIGs. 8 and 9A that traverses the aspheric corrector plate 10 602 suffers from a small amount of chromatic aberration. FIG. 10 depicts an alternative embodiment for the composite microscope objective 60 depicted in FIGs. 1, 5A, 5B and 7 in accordance with the present disclosure. Those elements depicted in FIG. 10 that are common to the composite microscope 15 objective 60 illustrated in FIGs. 8 and 9A carry the same reference numeral distinguished by a prime (') designation. The shapes of the back-surface mirror 601' and the aberration corrector plate 602' depicted in FIG. 10 are modified slightly to produce collimated afocal images of the emission locations 20 near the viewing zone within the flow channel 604'. In FIG. 10 the composite microscope objective 60' also includes a chromatic compensating doublet lens 609 inserted between the corrector plate 602' and the image plane 605'. In addition to focusing the light emitted from the corrector plate 602' onto 25 the image plane 605', the doublet lens 609 also serves to further reduce the residual chromatic aberration introduced by the aspheric corrector plate 602'.

It is not essential that the flat surface of the corrector plate 602 to be optically coupled to the cuvette 603. FIG. 11 30 depicts an alternative embodiment of the composite microscope objective 60 of the present disclosure. Those elements depicted in FIG. 11 that are common to the composite microscope objective 60 illustrated in FIGs. 8 and 9A carry the same reference numeral distinguished by a double prime (") 35 designation. FIG. 11 depicts the aberration corrector plate 602" optically decoupled from the cuvette 603". Although not essential for operation of the composite microscope objective 60", to improve the light transmission efficiency both surfaces

- 31 -

of the corrector plate 602" and the exposed flat surface of the cuvette 603" may carry an anti-reflectively coating. It is understood that the corrector plate 602" shown in FIG. 11 is held in fixed relationship to the combined back-surface mirror 5 601 and cuvette 603 by a mechanical support not depicted in FIG. 11. Similar to the composite microscope objective 60 and 60' depicted respectively in FIGs. 9A and 10, the composite microscope objective 60" with detached corrector plate 602" may be configured to provide either finite focal length image, or 10 an afocal system which in turn is focused to a finite distance image plane by addition of the chromatic compensating doublet lens 609.

FIG. 12 depicts yet another alternative embodiment of the composite microscope objective 60. Those elements depicted in 15 FIG. 12 that are common to the composite microscope objective 60 illustrated in FIGs. 8, 9A and 11 carry the same reference numeral distinguished by a triple prime ('') designation. The composite microscope objective 60'" depicted in FIG. 12 is adapted for collecting scatter and fluorescence emission from 20 cells or other microscopic particles carried in the jet stream 519 emitted by the nozzle 518. The composite microscope objective 60'" consists of a concave, spherically shaped, front surface mirror 610 and an aberration corrector plate 612. The front surface mirror 610 may be made of glass or other types 25 of hard material with a highly reflective coating on the concave surface 611. or made of metal with polished concave surface 611. Similar to the corrector plate 602, the plano-aspheric corrector plate 612 is made of a thin piece of transparent material, such as glass or optical quality 30 plastics. The aspheric surface may be formed on either side of the corrector plate 612. Preferably, both surfaces of the corrector plate 612 are coated with an anti-reflective coating to reduce optical transmission loss, although such a coating is not a mandatory requirement for a corrector plate 612 in 35 accordance with the present disclosure. It is understood that the front surface mirror 610 and the corrector plate 612 are held in fixed relationship to each other by a mechanical support not depicted in FIG. 12. Scatter and fluorescence

- 32 -

light emitted from cells or other types of microscopic particles in the viewing zone inside the jet stream 519 is reflected by the concave surface 611 of the front surface mirror 610. The aberration due to reflection from the concave surface 611 is corrected by the corrector plate 612 after light traverses through the corrector plate 612. It is understood by those having skill in the art that the composite microscope objective 60'" may be configured to provide either a finite-focused image similar to that depicted in FIG. 9A, or a collimated afocal image which is focused at finite distance from the composite microscope objective 60'" by a chromatic aberration correction doublet similar to the doublet lens 609 depicted in FIG. 10.

FIG. 13 depicts an adaptation of the composite microscope objective 60 for imaging specimens fixed to the surface of a transparent substrate such as a glass slide. Those elements depicted in FIG. 13 that are common to the composite microscope objective 60 illustrated in FIGs. 8, 9A and 11 carry the same reference numeral distinguished by a quadruple prime ("") designation. The composite microscope objective 60"" depicted in FIG. 13 includes two (2) optical elements, one a piano-concave back surface mirror 617 made of a transparent material such as glass or optical quality plastics, and an aberration corrector plate 618. As depicted in FIG. 13, the specimen to be imaged is fixed to a front surface 615 of a transparent, usually glass slide 616. The slide 616 is optically coupled, preferably using a thin layer of index matching fluid, to the flat surface of the back surface mirror 617. Scatter and fluorescence light emitted by the specimen:

1. initially propagates through the slide 616 and the back surface mirror 617;
2. is internally reflected by the back surface mirror 617 back through the slide 616;
3. then through the corrector plate 618; and
4. finally forms an image at an image plane that is located beyond the corrector plate 618.

- 33 -

**Fluidic Subsystem 70**

FIG. 15 depicts a fluidic subsystem 70 in accordance with the present disclosure that includes a sheath liquid reservoir 702 and a liquid pump 701 that draws sheath liquid from the sheath liquid reservoir 702. The liquid pump 701 may be a diaphragm pump, or a peristaltic pump, or a piston pump or any types of continuous fluid pump. An outlet of the liquid pump 701 connects to an inlet of a T-coupling 703 that receives sheath liquid from the liquid pump 701. The T-coupling 703 has two (2) outlets a first one of which connects to a bypass conduit 710 for returning a fraction of the sheath liquid received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702. Returning a fraction of the sheath liquid received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702 is advantageous for two (2) reasons.

1. As depicted in FIG. 1, the bypass conduit 710 is left open to the surrounding atmosphere which effectively dampens pulsation to thereby significantly reducing the pulsation inherent in the operation of the liquid pump 701.
2. Returning a fraction of the sheath liquid received by the T-coupling 703 from the liquid pump 701 back to the sheath liquid reservoir 702 also effectively reduces the throughput of the liquid pump 701 thereby allowing the use of comparatively high flow rate, low cost pumps in the flow cytometer 40.

Denote the flow resistance of the bypass conduit 710 as " $r$ " and the flow resistance of path from the T-coupling 703 to the flow channel 604 of the cuvette 603 as " $R$ ." The output resistance to the sheath pump is then

$$R_p = \frac{rR}{r+R} \quad (1)$$

Since  $R \gg r$ , the behavior of the liquid pump 701 is therefore dominated by the resistance of the bypass conduit 710 whose fluid dynamic properties are temperature insensitive. Thus, the configuration of the fluidic subsystem 70 depicted in FIG.

- 34 -

15 also provides a simple mechanism for achieving a temperature insensitive sheath liquid flow to the flow channel 604.

As depicted in FIG. 15, a second outlet of the T-coupling 703 connects to the to the flow channel 604 that extends  
5 through the cuvette 603 preferably first via a small reservoir capsule 704 and then via a filter cartridge 705. As depicted in FIG. 16, a piece of tubing 704' approximately 4 ft. long may be substituted for the small reservoir capsule 704. During initialization of the fluidic subsystem 70, some air becomes  
10 trapped in the filter cartridge 705 near its inlet which as depicted in FIG. 15 is located above an outlet of the filter cartridge 705. The air trapped in the filter cartridge 705 acts as an additional fluidic capacitor effectively reducing to negligible level the pulsation in sheath liquid emitted into  
15 the flow channel 604. Due to the large fluidic resistance at the flow channel 604, the air trapped inside the filter cartridge 705 becomes compressed. When the liquid pump 701 is turned off, a trapped in the filter cartridge 705 is pushed back towards the T-coupling 703 analogous to a discharging  
20 capacitor. Without the small reservoir capsule 704, some air ejected from the filter cartridge 705 reaches the bypass conduit 710 due to its low fluidic resistance, and will be pushed out of the fluidic subsystem 70 once the liquid pump 701 is turned on again. Without additional air supply, such a  
25 scenario will repeat until most of the air becomes purged from the fluidic subsystem 70 causing the filter cartridge 705 to lose its effectiveness as a pulsation damper. The purpose of the small reservoir capsule 704 or the piece of tubing 704' is therefore to provide a reservoir for isolating the filter  
30 cartridge 705 from the bypass conduit 710 ensuring that air trapped inside the filter cartridge 705 remains within the fluidic subsystem 70 despite repeated on-off operations of the liquid pump 701.

The pulsation damping effect of the trapped air near the  
35 inlet of the filter cartridge 705 is clearly evident in the histograms depicted in FIG. 16A and 16B. FIG. 16A depicts measured particle flight times at the flow channel 604 when a pocket of air is trapped near the inlet of the filter cartridge

- 35 -

705. FIG. 16B depicts measured particle flight times at the flow channel 604 when the trapped air is purged from the fluidic subsystem 70. The result depicted in the histograms of FIGs. 16A and 16B is made using two (2) knife edge shaped  
5 laser beams focused near the center of the flow channel 604 that are spaced approximately 200 micrometers apart. The horizontal axis of the FIGs. 16A and 16B is the flight time a particle takes from one laser beam to the other measured by recording the peak arrival time of light scattered from the  
10 particle at ninety degrees (90°) from the excitation beams. In both cases, the average flight time for particles to cross the two laser beams is the same. As shown in FIG. 16A, when the filter cartridge 705 retains some air, all particles take about the same amount of time to cross the two laser beams.  
15 If the filter cartridge 705 retains no air, as shown in FIG. 16B, the distribution of flight times not only broadens, but also becomes bimodal. In other words, some particles take less time while others take longer than average amount of time to cross the two laser beams, a phenomenon that can be easily  
20 attributed to sheath liquid velocity pulsation at the flow channel 604.

In the embodiments of the present disclosure discussed so far, the fluidic resistance along bypass conduit 710 as well as between the T-coupling 703 and the flow channel 604 is not  
25 adjustable. As should be apparent to those ordinary skilled in the art, flow restrictors such a fixed restrictor or adjustable valves 711, 711' and 712, 712' may be advantageously inserted in the bypass conduit 710 and between the T-coupling 703 and the flow channel 604 to permit adjusting the flow rate  
30 through the flow channel 604. Alternatively, the velocity of sheath liquid flowing through the flow channel 604 may also be adjusted using a liquid pump 701 that is driven by a variable speed brushless DC motor.

### 35 **Peristaltic Pump 80**

One embodiment of an peristaltic pump 80 in accordance with the present disclosure appears in FIG. 17. The pump includes a housing 809 with arcuate curved track 808, three

- 36 -

rollers 810, 811 and 812 attached to a rotor 816 rotatable within the housing 809, and a compressible tube 807 sandwiched between the compressible tube 807 of the housing 809 and the rollers 810, 811 and 812. As depicted schematically in FIGs.

5 18A through 18D, the rollers 810, 811 and 812 of the peristaltic pump 80 are spaced at substantially equal angular distances, separations or spacings from each other around the perimeter of the rotor 816. For simplicity, it is assumed in the following discussions that the rotor 816 rotates  
10 counterclockwise, although it is to be understood that the discussions apply equally well to a peristaltic pump with clockwise rotating rotor. The compressible tube 807 of the housing 809 may be divided into several sections:

1. an open section between point 801 and point 806  
15 where the experiences no compression;
2. a pump inlet section between point 801 and point 802 where the is progressively compressed until fully closed when a roller rolls over the section;
3. two pumping sections between point 802 and point  
20 803, as well as between point 804 and point 805 wherein the is fully closed by the roller;
4. a recess section between point 803 and point 804 in which the progressively expands from fully closed to fully open as a roller rolls through the  
25 expansion part of the recess section from point 803 to point 813;
5. then the is progressively compressed to fully closed as a roller rolls through a compression part of the recess section from point 813 to point 804;  
30 and
6. the exit section between point 805 and point 806 where the progressively expands from fully closed to fully open as a roller rolls through the section.

In other words, when a roller rolls anticlockwise over the  
35 from inlet point 801 to outlet point 806, the inner gap of the  
:



- 37 -

1. progressively decreases from fully open at point 801, to fully closed at point 802 and remain closed until point 803;
2. then progressively expands back to fully open at point 813;
3. then progressively decreases to fully closed at point 804, and remain closed until the roller reaches point 805; and
4. finally progressively expands back to fully open at point 806.

The size of the gap inside the is schematically illustrated in FIGs. 18A through 18D as the spacing between dashed circle and the solid compressible tube 807. As illustrated in FIGs. 18A through 18D, in this embodiment of the peristaltic pump 80 the angular distances, separations or spacings between points 801 and 803, points 802 and 813, point 813 and 805, as well as between point 804 and 866 are identical to the angle between adjacent rollers. As a result, when the roller 810 rolls through the pumping section from point 804 to point 805, as depicted in FIGs. 18A through 18B, its interaction with the completely determines the fluid flow rate of the peristaltic pump 80. Once the roller 810 reaches the exit section between point 805 and 806, as shown in FIG. 18C, the underneath the roller 810 starts to progressively expand and a gap starts to grow. Meanwhile, the roller 811 arrives at the compression part of the recess section and starts to progressively compress the . In the peristaltic pump 80, the shape of the compression part of the recess section between point 813 and point 804 along the compressible tube 807 is such that the volume of liquid pushed out by the compression of the underneath roller 811 in the compression part of the recess section between point 813 and point 804 substantially fills the volume created by the expansion underneath roller 810 in the exit section between point 5 and point 6. During this period, the compressible is partially open underneath both rollers 810 and 811 and completely closed underneath roller 12. Consequently, the pumping action is mainly delivered by roller 12. In particular, since by design the total volume of liquid in the

- 38 -

section of the between point 13 and point 6 remains substantially constant during this period, the flow rate of the peristaltic pump 80 in the state shown in FIG. 18C remains substantially the same as that in the state shown in FIGs. 18A and 18B. Once the roller 810 passes point 806, roller 811 reaches the pumping section between point 804 and point 805. Note there is no physical difference between the rollers 810, 811 and 812, the flow rate of the peristaltic pump 80 therefore remains substantially constant throughout the entire process.

The mechanism of the pulseless peristaltic pump of the present disclosure may be understood more clearly if it is viewed along a circular coordinate following the movement of the rollers. Referring to FIG. 19, denote as  $V$  the volume of the fluid inside a compressible tube 819 from the outlet to a nearest roller 820 that closes off the compressible tube 819, i.e., the amount of fluid represented by the hatched area 818 hatched area 818 shown in FIG. 19. Clearly,  $V$  depends on the angular position,  $\theta$ , of the roller 20, as well as  $\delta$ , the amount of tube compression exerted by all other downstream rollers.

$$V = V(\theta, \delta_1, \delta_2, \dots) \quad (1)$$

Consequently, the flow rate,  $F$ , of a peristaltic pump is related to the time derivative of  $V_c$  by:

$$-F = \frac{dV}{dt} = \frac{\partial V}{\partial \theta} R + \sum_i \frac{\partial V}{\partial \delta_i} \frac{d\delta_i}{dt} \quad (2)$$

Here  $R$  is the rotational speed of the rotor and the subscripts are used to identify multiple downstream rollers. The first term on the right hand side of Eqn. (2) represents the contribution from the roller that closes off the tube. The partial derivative  $\frac{\partial V}{\partial \theta}$  is therefore independent of  $\theta$ . The summation term represents contributions from all other downstream rollers partially compressing the compressible tube 819. Now let  $\Delta S$  be the cross sectional area change due to the compression of the compressible tube 819 by the , and  $L$  the length of tube where its cross sectional shape is affected by the tube compression. Then, it is obvious to a person skilled in the art that  $L$  is proportional to the tube compression  $\delta$ , and  $\Delta S$  proportional to its square,  $\delta^2$ . Consequently,  $\Delta V$ , the

- 39 -

volume of fluid lost due to the compression of the tube by the roller, follows Eqn. (3):

$$\Delta V \propto L \cdot \Delta S \propto \delta^3 = (D - G)^3 \quad (3)$$

5 where D is the inner diameter of the compressible tube and G the minimum gap indicated in FIGs. 19, 19A and 19B which is also represented in FIGs. 18A through 18D by the spacing between the dashed circle and the solid compressible tube 807 of the housing 809. Now referring to FIGs. 20A AND 20B, in the  
10 circular coordinate system FIG. 20A corresponds to the state of pump shown in FIGs. 18A and 18B. During this period, there is no roller downstream of the roller 810' and the summation term in Eqn. (2) vanishes. FIG. 20B corresponds to the state of the pump shown in FIG. 18C. The is closed off by roller  
15 12' and partially compressed by the rollers 810' and 811'. However, volumetric changes introduced by the two rollers 810' and 811' substantially cancel each other. Consequently, the summation term in Eqn. (2) vanishes as well. As a result, the flow rate of the peristaltic pump 80 remains substantially  
20 constant regardless of roller positions.

The shape of the compressible tube 807 satisfying the above requirement can be readily derived from Eqn. (3). Referring to FIG. 18C, if the gaps of the arcuate compressible tube 807 in the compression part of the recess section between  
25 point 813 and point 804,  $G_{13,4}$ , and in the exit section between point 805 and point 806,  $G_{5,6}$ , follow the equation

$$(D - G_{13,4})^3 + (D - G_{5,6})^3 = D^3 \quad (4)$$

then the total fluid volume in the two sections remains  
30 substantially constant, as shown in FIG. 21. In the peristaltic pump 80, the shape of the pump housing 809 is symmetrical with respect to its center line, such that the entrance half of the pump housing 809 is the mirror image of the exit half of the housing 809, as shown in FIG. 17. The  
35 peristaltic pump 80 can therefore be operated both in counterclockwise and clockwise rotation with very little pulsation, although it is understood that the symmetry is not required to realize a pulseless peristaltic pump in accordance with the

- 40 -

present disclosure. For example, as long as the gaps of the arcuate compressible tube 807 in the section between point 13 and point 3,  $G_{13,3}$ , and in the section between point 2 and point 1,  $G_{2,1}$ , follow Eqn. (5),

$$(D - G_{13,3})^3 + (D - G_{2,1})^3 = D^3 \quad (5)$$

a peristaltic pump in accordance with the present disclosure will exhibit little pulsation when the rotor 816 rotates clockwise.

FIG. 22 depicts an alternative embodiment of a peristaltic pump in accordance with the present disclosure. Those elements depicted in FIG. 22 that are common to the peristaltic pump 80 illustrated in FIG. 17 carry the same reference numeral distinguished by a prime (') designation. The peristaltic pump 80' includes a compressible tube 807' having two (2) recesses 820 and 821, and four (4) rollers 822, 823, 824 and 825. In the embodiment depicted in FIG. 22, the fluid volume loss due to the tube expansion near the outlet of the pump is compensated by the combined effect of the compression of the compressible tube by rollers 822 and 823 near the two recesses 820 and 821.

FIG. 23 depicts yet another alternative embodiment of a peristaltic pump in accordance with the present disclosure. Those elements depicted in FIG. 23 that are common to the peristaltic pump 80 illustrated in FIG. 17 and the peristaltic pump 80' illustrated in FIG. 22 carry the same reference numeral distinguished by a double prime (") designation. The peristaltic pump 80" includes six (6) rollers and an arcuate compressible tube 807" having two recesses 818" and 819". In the peristaltic pump 80", the fluid volume loss due to the tube expansion near the outlet of the pump is compensated by the action of the roller immediately upstream of the one recess 818" or 819" near the pump outlet.

Pulsation due to the expansion of a compressed compressible tube near the outlet of a peristaltic pump may also be overcome by a peristaltic pump having a programmable rotor speed. FIGs. 24A through 24C illustrate pertinent aspects of an alternative embodiment mechanism for minimizing

- 41 -

peristaltic pump pulsation in accordance with the present disclosure for a 3-roller peristaltic pump. As depicted in FIG. 24B, the track 828 is substantially circular between the pump inlet and pump exit section. Consequently, as indicated by the spacing between the dashed circle 829 and the solid curve of the track 828 the compressible tube is completely closed by various ones of the pump's three (3) rollers 826, 827 and 829 between the pump inlet and pump outlet. FIG. 24A illustrates schematically in a circular coordinate system the roller positions for the peristaltic pump depicted in FIG. 24B. Since there is only one roller downstream of the one that closes off the tube, Eqn. (2) is much simplified:

$$-F = R \left( \frac{\partial v_c}{\partial \theta} + \frac{\partial v_c}{\partial \delta} \frac{d\delta}{d\theta} \right) \quad (6)$$

Here the tube compression  $\delta(\theta)$  is explicitly expressed as a function of roller position  $\theta$ . The terms inside the parentheses represent the change rate of fluid volume with respect to roller position. The first term is the contribution from the roller that closes off the tube, i.e., roller 827 in FIG. 24A, and the second term the contribution from the roller in the exit section. Note that by definition, the volume change rate is negative and the second term inside the parentheses vanishes when there is no roller in the exit section. The dotted curve in FIG. 24C is a representative plot of the negative volume change rate with respect to the position of the roller. The bump along the curve, due to the tube expansion when a roller rolls off the tube near the pump outlet, is the cause for pulsation in conventional peristaltic pumps having a constant rotor speed. However, for the peristaltic pump depicted in FIGs. 24A through 24C the rotor speed,  $R$ , shown as dashed curve in FIG. 24C, is set to vary in synchronism with the rotor position and inversely proportional to the change rate of the fluid volume. Consequently, the flow rate of the pump, which is the product of the rotor speed and the change rate of the fluid volume, remains constant, as indicated by the solid line at the top of FIG. 24C. Note the terms inside the parentheses of Eqn. (6) are uniquely determined by the mechanical structure of the pump. The rotor

- 42 -

speed profile can therefore be readily generated from the shape of the track 828 in accordance with Eqn. (3). To those skilled in the art, there are many ways to realize a programmable rotor, for example, with stepping motor or DC servo motor.

5

**WDM Device 90**

FIG. 25 shows the optical ray trace for an exemplary 6 ports wavelength division multiplexer of the present disclosure using zig-zag configuration. As shown in FIG. 25, fluorescence light going through a pinhole or emitted from the facet of a multimode optical fiber, such as the optical fiber 852 depicted in FIG. 1, forms an extended object or light source at location 901, i.e. the optical input of the WDM 90. The size of the object is defined by the diameter of the pinhole or the core diameter of the multimode optical fiber. Note that the practical size of the pinhole or the core diameter of the multimode optical fiber is measured in millimeters, in contrast to the diameter of single mode optical fibers that are measured in micrometers. Consequently, the etendue of the fluorescence light source, defined as the product of beam size and its divergence angle, is hundreds times greater than its counterpart in optical communication. According to the theorem of the conservation of etendue (Julio Chaves, *Introduction to Nonimaging Optics*, CRC Press, 2008 [ISBN 978-1420054293]), light from such an extended source, similar to that from a flash light, can only be kept collimated for a very limited distance, particularly when the diameter of the collimated portion needs to be small.

As depicted in FIG. 25, a collimating optical element, in this case an achromatic doublet lens 902, captures the light from source 901, and projects a magnified image of the object near a final focusing lens 905. The size of the image near 905 is kept approximately the same as the effective size of the collimating optical element 902. Consequently, beam of light propagating between lens 902 and the lens 905 is effectively collimated. As shown in FIG. 25, so long as the magnification factor is kept small, for example, less than around 10, using a simple singlet lens 905 the collimated beam of light can

- 43 -

readily focused down to a spot smaller than that of the beam of light received by the WDM 90 at location 901. The ability to focus the beam of light down to such a small size permits placing a small area semiconductor detector at a focal point  
5 906 of the focusing lens 905 for efficient photo detection.

A dichroic filter 903, oriented at a slanted angle, is inserted into the optical path approximately midway between the collimating optical element 902 and the lens 905. The dichroic filter 903 passes the color band of interest and reflects the  
10 remaining colors in the beam of light for further processing within the WDM 90. An optional band pass filter 904 may be inserted following the dichroic filter 903 to further improve the color isolation capability of the WDM 90.

Light reflected from the dichroic filter 903 impinges upon  
15 a second optical element 907, preferably a concave mirror. The concave mirror 907 has a radius of curvature approximately equal to the distance between the collimating optical element 902 and the image near focusing lens 905. The concave mirror 907 therefore creates a second image of the collimating lens  
20 902 near a second focusing lens 908. The light beam between the concave mirror 907 and the second image at the lens 908 has substantially the same diameter as the beam of light between the collimating lens 902 and the first image near the focusing lens 905. The relay imaging concave mirror 907 therefore  
25 effectively doubles the collimated beam path without expanding the beam's diameter. Again, the extended yet collimated beam can be easily focused down to a spot smaller than that of the light source at 901. A second dichroic filter 909 is then inserted approximately midway between the relay imaging concave  
30 mirror 790 and the second image near focusing lens 908. The second dichroic filter 909 passes another band of color in the beam of light received by the WDM 90 at location 901 and reflects the remainder of the impinging beam of light for further processing.

35 As shown in FIG. 25, additional relay collimating optical elements 910, 911, 912, 913 and dichroic filters 914, 915, 916, 917 can be cascaded in the same way to produce multiple images near focusing lenses 918, 919, 920 and 921, each of these

- 44 -

images corresponding to a specific color band of light received by the WDM 90 at location 1. As shown in FIG. 25, due to the present disclosure's 1:1 imaging relay architecture, the spots of light produced by focusing lenses 906, 908, 918, 919, 920 and 921 are all smaller than the source of the beam of light, and therefore can be easily captured by small area APD's.

Although FIG 25 illustrates a 6-port wavelength division multiplexer for a beam of light from the extended light source, it is readily apparent to those skilled in the art that WDM's having different numbers of ports can be easily built in accordance with the present disclosure. It is also apparent to those skilled in the art that although the WDM 90 preferably uses achromatic doublets as the first collimating optical element, singlet lens can also be used since the images created before the focusing lenses 906, 908, 918, 919, 920 and 921 are all nearly monochromatic. Instead of using concave mirrors for relaying the beam of light reflected from the dichroic filters, one may also use refractive optics as relay element to extend the path of the collimated beam of light. A clear advantage of the zig-zag architecture used in the WDM 90, however, is the possibility for using array detectors, which would lead to a more compact WDM suitable for portable instrumentation.

FIG. 26 illustrates an optical ray trace for a prior art collimating device. The technique depicted in FIG. 26 is extensively used in conventional multicolor fluorescence instruments, for example, in United States Patent no. 6,683,314. As shown in FIG. 26, the beam of light diverges rapidly beyond the image 924 created by the collimating optical element 923. Consequently, the only option for constructing a multi-color device is to insert dichroic filters in between the collimating element 923 and its image 924.

Due to the constraint of etendue conservation, the diameter of the collimated beam must be significantly expanded to accept multiple dichroic filters in the section. The expanded beam creates serious challenge to refocusing the collimated beam down to small spots suitable for small area semiconductor detectors. To overcome these difficulties, some instrument manufacturers have chosen to use Mt exclusively for



- 45 -

fluorescence detection such as in the main stream flow cytometers manufactured by Becton-Dickinson, Becman Coulter and Partec 's and the MegaBACE series of DNA sequencers by GE Amersham. Other instruments, such as the Luminex multiplexed  
5 bead analyzers, have selected certain color bands with known bright fluorescence, and uses large area APD for detecting light in the selected color bands.

FIG. 27 illustrates a perspective view of an alternative embodiment for a 6-port WDM 90 using a combination of zig-zag and branched configurations. The design is a modification of  
10 zig-zag configuration depicted in FIG. 25. In the alternative embodiment depicted in FIG. 27, band pass filter 904 of FIG. 25 is replaced by a dichroic filter 904'. The filter 904' is positioned to let one color pass through and reflects other  
15 colors at ninety degrees ( $90^\circ$ ). The optical path length of the beam of light passing through the dichroic filter 904' and that being reflected from the 904' are substantially the same, such that one arm is focused by lenses 905 and the other by lens 905' to small spots compatible with small area semiconductor  
20 detectors placed at focal location 906 and 906'. As shown in FIG. 25, the remaining color of the light reflected by dichroic filter 903 is relay imaged by a concave mirror 907 and the configuration including optical elements 903, 904', 905 and 905' is cascaded two (2) more times to form a 6 port-WDM.

FIG. 28 illustrates a perspective view of an alternative embodiment for a 8-port WDM 90. By replacing the concave relay imaging mirrors 907 and 910 in FIG. 27 with concave shaped dichroic filters 907' and 910', the WDM depicted in FIG. 28 provides 2 more color bands in comparison with the WDMs  
30 depicted in FIGs. 25 and 27.

Numerous fluorescence probes for use in flow cytometry have been developed over the years. More recently, multiple fluorescence proteins have also become an important tool in biomedical studies. To accommodate different types of  
35 fluorescence probe, various techniques have been developed to enable user selection of dichroic filters suitable for their particular needs. A significant challenge for replaceable dichroic filters is avoiding direct contact of the coated

- 46 -

filter surface with any hard flow cytometer reference frame. Repeated direct contact between the coated filter surface and any hard reference frame may damage a replaceable dichroic filter. Presently, most conventional solutions addressing this  
5 problem use precision-machined mechanical spacers for holding replaceable dichroic filters in place. One example of such a solution appears in United States Patent no. 6,683,314. However, such a solution becomes unreliable if the detector's active area is smaller than  $1.0 \text{ mm}^2$ .

10 FIGs. 29A and 29B depict fabricating a replaceable dichroic filter assembly 934 illustrated in FIG. 29C suitable for small area detectors. Assembly of the replaceable dichroic filter assembly 934 begins in FIG. 29A which depicts constructing a reference template for its fabrication. The  
15 reference template is a staircase made of two (2) optically parallel glass plates 925 and 926. Bonding the two (2) glass plates 925 and 926 together in optical contact ensures that a surface 929 of the glass plate 925 becomes optically parallel to a surface 930 of the glass plate 926. A front surface 932  
20 of a replaceable dichroic filter 927 is then pressed against the surface 929 of the template. A filter holder 928, which loosely fits the dichroic filter 927, includes a reference surface 931 and a filter slot 933. During assembly of the replaceable dichroic filter, the filter slot 933 is partially  
25 filled with epoxy adhesive and the reference surface 931 of the filter holder 928 is pressed against the surface 930 of the template while filter holder 928 slides toward the dichroic filter 927. While the epoxy adhesive sets, part of the dichroic filter 927 remains seated within the filter slot 933  
30 while pressure is applied against the dichroic filter 927 and filter holder 928. It should be apparent to those skilled in the art that the epoxy adhesive may be either UV or thermally curable, or made by blending together components of an A/B mixture. FIG. 29C depicts the E934~ fabricated as depicted in  
35 FIGs. 29A and 29B and described above. The assembly process depicted in FIGs. 29A and 29B and described above ensures that front surface 932 of the replaceable dichroic filter assembly 934 will be optically parallel to the reference surface 931,

- 47 -

and indented with respect to the latter at a spacing accurately determined by the thickness of the glass plate 925.

FIGs. 30A and 30B depict an embodiment of the present disclosure where the fore-mentioned replaceable dichroic filter assembly 934 is used in the WDM 90 for optically processing a beam of light from an extended light source. A notable feature of the WDM 90 is a glass reference block 935 having an optically flat surface. As will be apparent to those skilled in the art, the glass reference block 935 may be made of other materials. As shown in FIG 30B, when installing a dichroic filter 927 the reference surface 931 of the replaceable dichroic filter assembly 934 slides against the flat surface of the glass reference block 935 and is kept in contact therewith by a spring loaded screw 936. Consequently, the coated front surface 932 of the replaceable dichroic filter assembly 934 remains optically parallel to the optical flat and accurately located. In the meantime, the indentation of front surface 932 with respect to the reference reference surface 931 protects it from in physical contact with any object during filter replacement.

It is apparent to those skilled in the art that many modifications and variations of the described embodiments of the replaceable dichroic filter assembly 934 are possible. For example, an alternative embodiment of the present disclosure is a pedestal assembled using a first and a second round optical flat. When assembling the replaceable dichroic filter assembly 934, the reference surface of a filter holder rests against a surface of the first optical flat and the coated surface of the dichroic filter rests against the flat surface of the second optical flat. Epoxy bonding then holds the coated surface of the dichroic filter optically parallel to the reference surface of a filter holder, yet indented at a distance accurately determined by the thickness of the second optical flat.

35

#### Industrial Applicability

Although an embodiment of the present disclosure of an LD based optical system for flow cytometric application has been

- 48 -

described in some detail, and equally advantageous embodiments have also been described for a stream based flow cytometric instrument, it will be apparent to those of ordinary skill in the art that many modifications and variations of the described  
5 embodiment are possible in the light of the above teachings without departing from the principles and concepts of the disclosure as set forth in the claims.

Although an embodiment of the present disclosure of wavelength division multiplexing device for separating light  
10 beam from an extended light source into multiple color bands has been described in some detail, and several other equally advantageous embodiments have also been described, it will be apparent to those ordinary skilled in the art that many modifications and variations of the described embodiments are  
15 possible in the light of the above teachings without departing from the principles and concepts of the disclosure as set forth in the claims.

Although the present invention has been described in terms of the presently preferred embodiment, it is to be understood  
20 that such disclosure is purely illustrative and is not to be interpreted as limiting. Consequently, without departing from the spirit and scope of the disclosure, various alterations, modifications, and/or alternative applications of the disclosure will, no doubt, be suggested to those skilled in the  
25 art after having read the preceding disclosure. Accordingly, it is intended that the following claims be interpreted as encompassing all alterations, modifications, or alternative applications as fall within the true spirit and scope of the disclosure.

- 49 -

The Claims

What is claimed is:

1. A flow cytometer (40) comprising:

a) a laser diode ("LD") based optical subsystem (50) for directing a beam of light into a viewing zone of said flow cytometer (40) through which a sample liquid carrying particles flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, the optical subsystem (50) including:

i. a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;

ii. a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass through the viewing zone;

iii. a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath flow; and

v. a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which particles pass through the viewing zone whereby:

- 50 -

- 35                   1)    said minor axis of said beam of light  
                      becomes focused at the viewing zone; and
- 2)    the size of said major axis of said  
                      elliptical beam of light at the viewing  
                      zone remains essentially unchanged;
- 40           b)    a composite microscope objective (60) for imaging  
                  light scattered from and fluoresced by a particle  
                  present within the viewing zone, the composite  
                  microscope objective (60) including:
- i.    a concave mirror upon which scattered and  
45                    fluoresced light impinges;
- ii.   an aberration corrector plate made of optically  
                      transparent material wherein said aberration  
                      corrector plate is an aspheric lens that has:
- 1)    a first zone of said aberration corrector  
50                        plate outside a neutral zone thereof where  
                              said aberration corrector plate:  
                              A.    is thinnest; and  
                              B.    has negative optical power; and
- 2)    a second zone of said aberration corrector  
55                        plate inside the neutral zone has positive  
                              optical power
- light reflected from the composite microscope  
                  objective (60) passing through said aberration  
                  corrector plate,
- 60           the viewing zone of said flow cytometer (40) being  
                  located between said concave mirror and said  
                  aberration corrector plate;
- c)    a fluidic subsystem (70) for supplying the liquid  
                  sheath flow to the viewing zone, the liquid sheath  
65                    flow lacking pulsations, the fluidic subsystem (70)  
                  including:
1.    a liquid pump for supplying liquid drawn from  
                      a reservoir;
- ii.   a T-coupling having at least one (1) inlet and  
70                       two (2) outlets,
- 1)    the inlet of said T-coupling receiving  
                              liquid from said liquid pump;

- 51 -

- 75                   2)    a first fraction of the liquid received by  
                    the inlet flowing via a first one of the  
                    outlets and via a bypass conduit back to  
                    the reservoir; and
- 80                   3)    a second fraction of the liquid received  
                    by the inlet flowing via a second one of  
                    the outlets and via a particle filter to  
                    the viewing zone of said flow cytometer  
                    (40);
- 85           d)    a peristaltic pump 80 for supplying the sample  
                  liquid carrying the particles, the sample liquid  
                  being hydrodynamically focused within the viewing  
                  zone by the liquid sheath flow, the peristaltic pump  
                  80 comprising:
- i.    a pump housing having a arcuate curved track  
                        formed therein that extends between a pump  
                        inlet and a pump outlet;
- 90                   ii.   a plurality of rollers that are attached to a  
                        rotor, the rollers having a substantially equal  
                        angular spacing between each pair of  
                        immediately adjacent rollers, the rotor being  
                        rotatable together with the rollers attached  
95                   thereto inside said pump housing; and
- ii    a compressible tube sandwiched between said  
                        rollers and the arcuate curved track of said  
                        pump housing, the arcuate curved track  
                        including:
- 100                   1)    an exit section wherein, as a roller rolls  
                        through the exit section, said  
                        compressible tube adjacent to said roller  
                        progressively expands from fully closed at  
                        a beginning of said exit section to fully  
105                   open at the pump outlet where said roller  
                        breaks contact with said compressible  
                        tube; and
- 2)    at least one pumping section along the  
                        arcuate curved track between the pump  
110                   inlet and the pump outlet wherein said

- 52 -

compressible tube is compressed to fully closed by at least one of said rollers; and

- 115 e) a wavelength division multiplexer 90 ("WDM (90)") for separating into multiple colored bands a beam of light emitted initially from the viewing zone and imaged by the composite microscope objective (60) into an optical fiber for transmission to the WDM (90), the WDM (90) comprising:
- 120 i. a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;
- 125 ii. at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light into two (2) branches of distinctive colors;
- 130 iii. a focusing optical element located in one of said branches, wherein the beam of light in said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and
- 135 iv. an image relay optical element located near the image produced by said collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.

2. The flow cytometer (40) of claim 1 wherein said cuvette has a rectangularly-shaped , and wherein the viewing zone of the flow cytometer (40) is located within a channel having a rectangularly-shaped cross-section that is located within said cuvette.



- 53 -

3. The flow cytometer (40) of claim 1 wherein said cuvette has a tubularly-shaped cross-section, and wherein the viewing zone of the flow cytometer (40) is located within a channel having a circularly-shaped cross-section that is located within said cuvette.

4. The flow cytometer (40) of claim 1 wherein the sample liquid and the liquid sheath flow form a jet stream in which the viewing zone of the flow cytometer (40) is located.

5. The flow cytometer (40) of claim 2 wherein said cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

6. The flow cytometer (40) of claim 2 wherein said cylindrical focusing element is separated from said rectangularly-shaped cuvette.

7. The flow cytometer (40) of claim 3 wherein said cylindrical focusing element is separated from said tubularly-shaped cuvette.

8. The flow cytometer (40) of claim 4 wherein said cylindrical focusing element is separated from said jet stream.

9. The flow cytometer (40) of claim 1 further comprising a polarization conditioning element through which said collimated elliptical beam of light passes.

10. The flow cytometer (40) of claim 1 wherein an optical image of the viewing zone is formed outside the composite microscope objective (60).

11. The flow cytometer (40) of claim 10 wherein the viewing zone is located within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

- 54 -

12. The flow cytometer (40) of claim 11 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

13. The flow cytometer (40) of claim 12 wherein the piano-surface of said piano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

14. The flow cytometer (40) of claim 13 wherein an optical adhesive material accomplishes the optical coupling.

15. The flow cytometer (40) of claim 13 wherein an index matching gel accomplishes the optical coupling.

16. The flow cytometer (40) of claim 13 wherein an index matching fluid accomplishes the optical coupling.

17. The flow cytometer (40) of claim 13 wherein optical contact bonding accomplishes the optical coupling.

18. The flow cytometer (40) of claim 13 wherein the piano-concave back surface mirror formed integrally with said cuvette means.

19. The flow cytometer (40) of claim 11 wherein said aberration corrector plate is a piano-aspherical lens.

20. The flow cytometer (40) of claim 19 wherein a piano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said piano-concave back surface mirror.

21. The flow cytometer (40) of claim 20 wherein an index matching gel accomplishes the optical coupling.

22. The flow cytometer (40) of claim 20 wherein an index matching fluid accomplishes the optical coupling.

- 55 -

23. The flow cytometer (40) of claim 20 wherein optical contact bonding accomplishes the optical coupling.

24. The flow cytometer (40) of claim 20 wherein the piano-aspherical lens is formed integrally with said cuvette.

25. The flow cytometer (40) of claim 19 wherein said aberration corrector plate is detached from said cuvette.

26. The flow cytometer (40) of claim 10 wherein the viewing zone is inside a jet stream.

27. The flow cytometer (40) of claim 25 wherein said concave mirror is a front surface mirror.

28. The flow cytometer (40) of claim 10 wherein the viewing zone is located on a surface of a flat, transparent substrate.

29. The flow cytometer (40) of claim 28 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

30. The flow cytometer (40) of claim 29 wherein the piano-surface of said piano-concave back surface mirror is optically coupled to said flat, transparent substrate.

31. The flow cytometer (40) of claim 30 wherein an optical adhesive material accomplishes the optical coupling.

32. The flow cytometer (40) of claim 30 wherein an index matching gel accomplishes the optical coupling.

33. The flow cytometer (40) of claim 30 wherein an index matching fluid accomplishes the optical coupling.

34. The flow cytometer (40) of claim 30 wherein optical contact bonding accomplishes the optical coupling.

- 56 -

35. The flow cytometer (40) of claim 29 wherein said piano-concave back surface mirror is formed integrally with said flat, transparent substrate.

36. The flow cytometer (40) of claim 28 wherein said aberration corrector plate is detached from said flat, transparent substrate.

37. The flow cytometer (40) of claim 1 wherein the particle filter has inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so that air becomes trapped within the particle filter at the inlet thereto.

38. The flow cytometer (40) of claim 37 wherein when said liquid pump is turned off air cannot enter into the bypass conduit.

39. The flow cytometer (40) of claim 38 further comprising a small capsule disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

40. The flow cytometer (40) of claim 38 further comprising a length of tubing disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

41. The flow cytometer (40) of claim 38 further comprising an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

42. The flow cytometer (40) of claim 38 further comprising an adjustable valve located between the second one

- 57 -

of the outlets of the T-coupling and the viewing zone for restricting liquid flow therebetween.

43. The flow cytometer (40) of claim 38 wherein the throughput of the liquid pump is adjustable.

44. The flow cytometer (40) of claim 1 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said  
5 pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

45. The flow cytometer (40) of claim 44 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to the pump  
5 outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

46. The flow cytometer (40) of claim 44 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume  
5 inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

47. The flow cytometer (40) of claim 44 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

48. The flow cytometer (40) of claim 46 wherein both:

- 58 -

a) angular spacing between adjacent pairs of recess sections; and

5 b) angular spacing between said exit section of said arcuate curved track and an adjacent recess section to said exit section

are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

49. The flow cytometer (40) of claim 47 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said  
5 compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

50. The flow cytometer (40) of claim 1 wherein a speed of said rotor is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

51. The flow cytometer (40) of claim 1 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces  
5 two (2) branches of the beam of light having distinctive colors.

52. The flow cytometer (40) of claim 51 wherein another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

53. The flow cytometer (40) of claim 52 wherein successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to

- 59 -

produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

54. The flow cytometer (40) of claim 52 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

55. The flow cytometer (40) of claim 54 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90) thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).

56. A LD based optical subsystem (50) for impinging a beam of light into a viewing zone in which a particle is present, the optical subsystem (50) comprising:

- a) a LD for emitting a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;
- b) a collimating lens for converting the diverging beam of light emitted from said LD into a collimated elliptical beam of light, wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which particles pass through the viewing zone;
- c) a beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented perpendicular to the direction in which particles pass through the viewing zone is less than a width of said liquid sheath flow; and

- 60 -

- 25 d) a cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which particles pass through the viewing zone whereby:
- i. said minor axis of said beam of light becomes focused at the viewing zone; and
  - ii. the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

57. The optical subsystem (50) of claim 56 further comprising a cuvette having a rectangularly-shaped cross-section, and wherein the viewing zone is located within a channel having a rectangularly-shaped cross-section that is located within said cuvette.

58. The optical subsystem (50) of claim 56 further comprising a cuvette having a tubularly-shaped cross-section, and wherein the viewing zone is located within a channel having a circularly-shaped cross-section that is located within said cuvette.

59. The optical subsystem (50) of claim 56 wherein the sample liquid and the liquid sheath flow form a jet stream in which the viewing zone is located.

60. The optical subsystem (50) of claim 57 wherein said cylindrical focusing element is in optical contact with an entrance face of said rectangularly-shaped cuvette.

61. The optical subsystem (50) of claim 57 wherein said cylindrical focusing element is separated from said rectangularly-shaped cuvette.

62. The optical subsystem (50) of claim 58 wherein said cylindrical focusing element is separated from said tubularly-shaped cuvette.



- 61 -

63. The optical subsystem (50) of claim 59 wherein said cylindrical focusing element is separated from said jet stream.

64. The optical subsystem (50) of claim 56 further comprising a polarization conditioning element through which said collimated elliptical beam of light passes.

65. A method for delivering an elliptically shaped beam of light using a LD based optical subsystem (50), the beam of light having a smooth profile at a focus of a minor axis thereof that is located at a viewing zone through which a  
5 sample liquid flows, the sample liquid being hydrodynamically focused within the viewing zone by a liquid sheath flow that also flows through the viewing zone, the method comprising the steps of:

- 10 a) providing a LD that emits a diverging beam of light from an edge thereof, the diverging beam of light having an elliptically shaped cross-sectional profile with both a major axis and a minor axis;
- 15 b) impinging the diverging beam of light emitted by the LD upon a collimating lens for converting the diverging beam of light emitted therefrom into a collimated elliptical beam of light wherein the minor axis of said collimated elliptical beam of light is oriented parallel to a direction in which sample liquid passes through the viewing zone;
- 20 c) after passing through said collimating lens, impinging the collimated elliptical beam of light upon an beam compressing optical element for reducing the size of said elliptical beam of light at the viewing zone whereby a width of said major axis of said elliptical beam of light oriented  
25 perpendicular to the direction in which sample liquid passes through the viewing zone becomes less than a width of said liquid sheath flow; and
- 30 d) after passing through said beam compressing optical element, impinging the beam of light upon a

- 62 -

35 cylindrical focusing element positioned adjacent to the viewing zone with an axis of said cylindrical focusing element being oriented perpendicular to the direction in which sample liquid passes through the viewing zone whereby:

- i. said minor axis of said beam of light becomes focused at the viewing zone; and
- ii. the size of said major axis of said elliptical beam of light at the viewing zone remains essentially unchanged.

66. The method of claim 65 wherein the viewing zone is located within a channel having a rectangularly-shaped cross-section that is located within a cuvette.

67. The method of claim 65 wherein the viewing zone is located within a channel having a circularly-shaped cross-section that is located within a cuvette.

68. The method of claim 65 wherein the viewing zone is located within a jet stream.

69. The method of claim 66 further comprising a step of establishing an optical contact between said cylindrical focusing element and an entrance face of said cuvette.

70. The method of claim 66 further comprising a step of establishing a spacing between said cylindrical focusing element and said cuvette.

71. The method of claim 67 further comprising a step of establishing a spacing between said cylindrical focusing element and said cuvette.

72. The method of claim 68 further comprising a step of establishing a spacing between said cylindrical focusing element and said jet stream.

- 63 -

73. The method of claim 65 further comprising a step of inserting a polarization conditioning element between the collimating lens and the beam compressing optical element whereby the collimated elliptical beam of light passes through the polarization conditioning element.

74. A composite microscope objective (60) adapted for imaging light scattered from and fluoresced by a particle present within a viewing zone comprising:

a) a concave mirror upon which scattered and fluoresced light impinges;

b) an aberration corrector plate made of optically transparent material wherein said aberration corrector plate is an aspheric lens that has:

i. a first zone of said aberration corrector plate outside a neutral zone thereof where said aberration corrector plate:

1) is thinnest; and

2) has negative optical power; and

ii. a second zone of said aberration corrector plate inside the neutral zone has positive optical power,

light reflected from the composite microscope objective (60) passing through said aberration corrector plate,

the viewing zone being located between said concave mirror and said aberration corrector plate.

75. The composite microscope objective (60) of claim 74 wherein an optical image of the viewing zone is formed outside the composite microscope objective (60).

76. The composite microscope objective (60) of claim 75 wherein the viewing zone is located within a flow channel included in a rectangularly-shaped cuvette made of optically transparent material.

- 64 -

77. The composite microscope objective (60) of claim 76 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

78. The composite microscope objective (60) of claim 77 wherein a piano-surface of said piano-concave back surface mirror is optically coupled to a flat surface of said cuvette.

79. The composite microscope objective (60) of claim 78 wherein an optical adhesive material accomplishes the optical coupling.

80. The composite microscope objective (60) of claim 78 wherein an index matching gel accomplishes the optical coupling.

81. The composite microscope objective (60) of claim 78 wherein an index matching fluid accomplishes the optical coupling.

82. The composite microscope objective (60) of claim 78 wherein optical contact bonding accomplishes the optical coupling.

83. The composite microscope objective (60) of claim 78 wherein the piano-concave back surface mirror formed integrally with said cuvette means.

84. The composite microscope objective (60) of claim 76 wherein said aberration corrector plate is a piano-aspherical lens.

85. The composite microscope objective (60) of claim 84 wherein a piano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette opposite of said piano-concave back surface mirror.

- 65 -

86. The composite microscope objective (60) of claim 85 wherein an index matching gel accomplishes the optical coupling.

87. The composite microscope objective (60) of claim 85 wherein an index matching fluid accomplishes the optical coupling.

88. The composite microscope objective (60) of claim 85 wherein optical contact bonding accomplishes the optical coupling.

89. The composite microscope objective (60) of claim 85 wherein the piano-aspherical lens is formed integrally with said cuvette.

90. The composite microscope objective (60) of claim 84 wherein said aberration corrector plate is detached from said cuvette.

91. The composite microscope objective (60) of claim 75 wherein the viewing zone is inside a jet stream.

92. The composite microscope objective (60) of claim 90 wherein said concave mirror is a front surface mirror.

93. The composite microscope objective (60) of claim 75 wherein the viewing zone is located on a surface of a flat, transparent substrate.

94. The composite microscope objective (60) of claim 93 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

95. The composite microscope objective (60) of claim 94 wherein a piano-surface of said piano-concave back surface mirror is optically coupled to said flat, transparent substrate.

- 66 -

96. The composite microscope objective (60) of claim 95 wherein an optical adhesive material accomplishes the optical coupling.

97. The composite microscope objective (60) of claim 95 wherein an index matching gel accomplishes the optical coupling.

98. The composite microscope objective (60) of claim 95 wherein an index matching fluid accomplishes the optical coupling.

99. The composite microscope objective (60) of claim 95 wherein optical contact bonding accomplishes the optical coupling.

100. The composite microscope objective (60) of claim 94 wherein said piano-concave back surface mirror is formed integrally with said flat, transparent substrate.

101. The composite microscope objective (60) of claim 93 wherein said aberration corrector plate is detached from said flat, transparent substrate.

102. A method for characterizing microscopic species using a microscope objective device comprising:

- a) A concave mirror;
- b) An aberration corrector plate made of optically transparent material wherein said aberration corrector plate is an aspheric lens with the zone of said plate means outside of the neutral zone wherein the thickness of said plate means is thinnest, having negative optical power, and the zone inside the neutral zone having positive optical power
- c) A viewing zone located in between said concave mirror and said aberration corrector plate.

- 67 -

103. The method of claim 102 wherein an optical image of the viewing zone is formed outside the device.

104. The method of claim 103 wherein the viewing zone is located within a flow channel contained in a rectangularly-shaped cuvette means made of optically transparent material.

105. The method of claim 104 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

106. The method of claim 105 wherein a piano-surface of said piano-concave back surface mirror means is optically coupled to a flat surface of said cuvette means.

107. The method of claim 106 wherein an optical adhesive material accomplishes the optical coupling.

108. The method of claim 106 wherein an index matching gel accomplishes the optical coupling.

109. The method of claim 106 wherein an index matching fluid accomplishes the optical coupling.

110. The method of claim 106 wherein optical contact bonding accomplishes the optical coupling.

111. The method of claim 106 wherein the piano-concave back surface mirror is formed integrally with said cuvette.

112. The method of claim 104 wherein said aberration corrector plate is a plano-aspherical lens.

113. The method of claim 112 wherein a piano-surface of said aberration corrector plate is optically coupled to a flat surface of said cuvette means opposite of said concave mirror.

- 68 -

114. The method of claim 113 wherein an index matching gel accomplishes the optical coupling.

115. The method of claim 113 wherein an index matching fluid accomplishes the optical coupling.

116. The method of claim 113 wherein optical contact bonding accomplishes the optical coupling.

117. The method of claim 113 wherein the piano-aspherical lens is formed integrally with said cuvette.

118. The method of claim 112 wherein said aberration corrector plate is detached from said cuvette.

119. The method of claim 102 wherein the viewing zone is inside a jet stream.

120. The method of claim 119 wherein said concave mirror is a front surface mirror.

121. The method of claim 102 wherein the viewing zone is located on a surface of a flat, transparent substrate.

122. The method of claim 121 wherein said concave mirror is a piano-concave back surface mirror made from an optically transparent material.

123. The method of claim 122 wherein a piano-surface of said piano-concave back surface mirror means is optically coupled to said flat, transparent substrate.

124. The method of claim 123 wherein an optical adhesive material accomplishes the optical coupling.

125. The method of claim 123 wherein an index matching gel accomplishes the optical coupling.



- 69 -

126. The method of claim 123 wherein an index matching fluid accomplishes the optical coupling.

127. The method of claim 123 wherein optical contact bonding accomplishes the optical coupling.

128. The method of claim 122 wherein said piano-concave back surface mirror is formed integrally with said flat, transparent substrate.

129. The method of claim 128 wherein said aberration corrector plate is detached from said flat, transparent substrate.

130. A fluidic subsystem (70) for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem (70), the fluidic subsystem (70) comprising:

- 5           a) a liquid pump for supplying liquid drawn from a reservoir;
- b) a T-coupling having at least one (1) inlet and two (2) outlets,
  - 10           i. the inlet of said T-coupling receiving liquid from said liquid pump;
  - ii. a first fraction of the liquid received by the inlet flowing via a first one of the outlets and via a bypass conduit back to the reservoir; and
  - 15           iii. a second fraction of the liquid received by the inlet flowing via a second one of the outlets and via a particle filter to the outlet of the fluidic subsystem (70).

131. The fluidic subsystem (70) of claim 130 wherein the particle filter has inlet thereto for receiving liquid from the T-coupling, the inlet of the particle filter being disposed so that air becomes trapped within the particle filter at the inlet thereto.

- 70 -

132. The fluidic subsystem (70) of claim 131 wherein when said liquid pump is turned off air cannot enter into the bypass conduit.

133. The fluidic subsystem (70) of claim 132 further comprising a small capsule disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

134. The fluidic subsystem (70) of claim 132 further comprising a length of tubing disposed between the second one of the outlets of said T-coupling and the particle filter for storing air ejected from the particle filter when the liquid pump is turned off.

135. The fluidic subsystem (70) of claim 132 further comprising an adjustable valve located in the bypass conduit between the first one of the outlets of the T-coupling and the reservoir for restricting liquid flow therebetween.

136. The fluidic subsystem (70) of claim 132 further comprising an adjustable valve located between the second one of the outlets of the T-coupling and the outlet of the fluidic subsystem (70) for restricting liquid flow therebetween.

137. The fluidic subsystem (70) of claim 132 wherein the throughput of the liquid pump is adjustable.

138. A method for supplying a liquid flow pulsation free to an outlet of the fluidic subsystem (70), the method comprising:

- a) a liquid pump for supplying liquid drawn from a reservoir;
- b) a T-coupling having at least one (1) inlet and two (2) outlets,
  - i. the inlet of said T-coupling receiving liquid from said liquid pump;

5

- 71 -

- 10           ii. a first fraction of the liquid received by the  
              inlet flowing via a first one of the outlets  
              and via a bypass conduit back to the reservoir;  
              and
- 15           iii. a second fraction of the liquid received by the  
              inlet flowing via a second one of the outlets  
              and via a particle filter to the outlet of the  
              fluidic subsystem (70).

139. The method of claim 138 wherein during normal operation certain amount of air is trapped near the inlet portion of said filter cartridge means.

140. The method of claim 139 wherein said reservoir means holds sufficient amount of liquid such that when said pump means is turned off, portion of the tubing between said Tee means and said reservoir means is still filled with liquid,  
5 preventing said trapped air from leaking into said bypass means.

141. The method of claim 140 wherein said reservoir means is a capsule.

142. The method of claim 140 wherein said reservoir means is a piece of tubing.

143. The method of claim 140 wherein an adjustable flow restrictor means is placed in the bypass route.

144. The method of claim 140 wherein an adjustable flow restrictor means is placed in the sheath route.

145. The method of claim 140 wherein the throughput of the sheath pump is adjustable.

146. A peristaltic pump 80 comprising:

- 72 -

- a) a pump housing having a arcuate curved track formed therein that extends between a pump inlet and a pump outlet;
- 5 b) a plurality of rollers that are attached to a rotor, the rollers having a substantially equal angular spacing between each pair of immediately adjacent rollers, the rotor being rotatable together with the rollers attached thereto inside said pump housing;
- 10 and
- c) a compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing, the arcuate curved track including:
  - 15 i. an exit section wherein, as a roller rolls through the exit section, said compressible tube adjacent to said roller progressively expands from fully closed at a beginning of said exit section to fully open at the pump outlet where said roller breaks contact with
  - 20 said compressible tube; and
  - ii. at least one pumping section along the arcuate curved track between the pump inlet and the pump outlet wherein said compressible tube is compressed to fully closed by at least one of said rollers.

147. The peristaltic pump 80 of claim 146 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said  
5 pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

148. The peristaltic pump 80 of claim 147 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet, the angular spacing between the compression part of said recess section adjacent to the pump

- 73 -

- 5 outlet and said exit section of said arcuate curved track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

149. The peristaltic pump 80 of claim 147 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume  
5 inside a section of said compressible tube extending from said recess section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

150. The peristaltic pump 80 of claim 147 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

151. The peristaltic pump 80 of claim 149 wherein both:  
a) angular spacing between adjacent pairs of recess sections; and  
b) angular spacing between said exit section of said  
5 arcuate curved track and an adjacent recess section to said exit section  
are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

152. The peristaltic pump 80 of claim 150 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said  
5 compressible tube at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

153. The peristaltic pump 80 of claim 146 wherein a speed of said rotor is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said

- 74 -

compressible tube due to its changing compression near the exit section of said arcuate curved track.

154. A method for delivering liquid using a peristaltic pump 80 comprising:

- a) a pump housing with arcuate curved track;
- b) A plurality of rollers attached to a rotor means rotatable inside said pump housing;
- c) Said plurality of rollers spaced at substantially equal angular spacing from each other;
- d) A compressible tube sandwiched between said rollers and the arcuate curved track of said pump housing;
- e) Said arcuate curved track of said pump housing including an exit section, wherein said compressible tube being progressively decompressed to full expansion when one of said rollers rolls off the compressible tube at the pump outlet;
- f) At least one pumping section along the arcuate curved track of said pump housing between the pump inlet and pump outlet wherein said compressible tube is compressed to full closure by one of said rollers.

155. The method of claim 154 wherein the arcuate curved track of said pump housing includes at least two (2) pumping sections, the arcuate curved track further including at least one recess section located between said pumping sections along the arcuate curved track, and wherein said compressible tube at said recess section becomes decompressed to full expansion then compressed to fully closed when one (1) of said rollers rolls through said recess section.

156. The method of claim 155 wherein the peristaltic pump 80 includes a plurality of recess sections along said arcuate curved track upstream of the pump outlet; The angular spacing between the compression part of said recess section adjacent to the pump outlet and said exit section of said arcuate curved

- 75 -

track being substantially the same as the angular spacing between each pair of immediately adjacent rollers.

157. The method of claim 155 wherein said compression part of said recess section adjacent to the pump outlet has a shape complementing a shape of said exit section of said arcuate curved track to maintain the total fluid volume inside a section of said compressible tube extending from said recess  
5 section to the pump outlet substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

158. The method of claim 155 having a plurality of recess sections respectively interspersed between immediately adjacent pairs of a plurality of pumping sections.

159. The method of claim 157 wherein both:

- a) angular spacing between adjacent pairs of recess sections; and
- b) angular spacing between said exit section of said  
5 arcuate curved track and an adjacent recess section to said exit section

are substantially the same as the angular spacing between each pair of immediately adjacent rollers.

160. The method of claim 158 wherein shapes of a plurality of recess sections of said arcuate curved track complement a shape of said exit section of said arcuate curved track to maintain a fluid volume in sections of said compressible tube  
5 at the plurality of recess sections and said exit section substantially invariant when one of said rollers progressively rolls off said exit section of the arcuate curved track.

161. The method of claim 154 wherein a speed of said rotor of the peristaltic pump 80 is programmably controlled to vary substantially in inverse proportion to the fluid volume change rate in said compressible tube due to its changing compression near the exit section of said arcuate curved track.

- 76 -

162. A WDM (90) for separating a beam of light emitted from an into multiple colored bands, the WDM (90) comprising:

- a) a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;
- b) at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light into two (2) branches of distinctive colors;
- c) a focusing optical element located in one of said branches, wherein the beam of light in said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and
- d) an image relay optical element located near the image produced by said collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.

163. The WDM (90) of claim 162 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of the beam of light having distinctive colors.

164. The WDM (90) of claim 163 wherein another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

165. The WDM (90) of claim 164 wherein successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce



- 77 -

additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.

166. The WDM (90) of claim 164 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using  
5 the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

167. The WDM (90) of claim 166 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90) thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).

168. A method for separating beam of light emitted from an into colored bands using a WDM (90) comprising

- 5 a) a collimating optical element that magnifies an to produce an image of substantially the same size as the effective size of said collimating optical element;
- 10 b) at least one dichroic filter located between said collimating optical element and said image, wherein said dichroic filter separates the collimated beam of light into two (2) branches of distinctive colors;
- 15 c) a focusing optical element located in one of said branches, wherein the beam of light of said branch is focused to a spot having a diameter of less than 1.0 mm by said focusing optical element; and
- 20 d) an image relay optical element located near the image produced by said collimating optical element in the other branch, wherein said image relay optical element produces an image of said collimating optical element at substantially unit magnification.

- 78 -

169. The method of claim 168 wherein at least one additional dichroic filter is located between said image relay optical element and the image produced by said image relay optical element, wherein said dichroic filter produces two (2) branches of beam of light having distinctive colors.


170. The method of claim 169 wherein another focusing optical element is located in one of said branches and focuses the beam of light in the branch into a spot having a diameter of less than 1.0 mm.

171. The method of claim 170 wherein successive combinations of said image relay optical element, dichroic filter and focusing optical element are cascaded to produce additional focused spots having a diameter of less than 1.0 mm for multiple colored bands of said beam of light.


172. The method of claim 170 wherein the dichroic filter is assembled using a template that include two (2) optically flat glass plates bonded together in optical contact, and wherein the dichroic filter is bonded to a filter holder using  
5 the template such that a coated filter surface of the dichroic filter is indented and optically parallel to a reference surface of the filter holder.

173. The method of claim 172 wherein the reference surface of the filter holder rests against an optically flat surface of an reference block included in the WDM (90) thereby providing consistent optical alignment when installing the dichroic filter into the WDM (90).


1 / 23

**FIG. 1**


2 / 23




**FIG. 2**

512




**FIG. 2A**

3 / 23



**FIG. 3A**

**FIG. 3B****FIG. 4A****FIG. 4B**



5 / 23





**FIG. 5A****FIG. 5B****FIG. 5C**

6 / 23















9 / 23





10 / 23

**FIG. 12****FIG. 13**


11 / 23





**FIG. 14****FIG. 15**

12 / 23

**FIG. 16A****FIG. 16B**

13 / 23

**FIG. 17**








**FIG. 19**




**FIG. 19A**

**FIG. 19B**




**FIG. 20A**




**FIG. 20B**

17 / 23




**FIG. 21**




**FIG. 22**







**FIG. 23**

18 / 23

**FIG. 24A****FIG. 24B****FIG. 24C**




**FIG. 25**




FIG. 26




FIG. 27

21 / 23









FIG. 28

**FIG. 29A****FIG. 29B****FIG. 29C**



23 / 23





Espacenet

**Bibliographic data: JP2003505707 (A) — 2003-02-12**

# SYSTEM FOR MICROVOLUME LASER SCANNING CYTOMETRY

**Inventor(s):**

**Applicant(s):**

**Classification:** - international: **G01N15/00; G01N15/14; G01N21/64; G01N33/483; G06K9/00;** (IPC1-7): G01N15/00; G01N15/14; G01N21/64; G01N33/483

- cooperative: **G01N15/1475; G06K9/00127; G01N15/1484**

**Application number:** JP20010513096 20000426

**Priority number (s):** WO2000US11133 20000426 ; US19990144798P 19990721

**Also published as:** AU4491100 (A) CA2379836 (A1) EP1203339 (A1) EP1203339 (A4) KR20020013970 (A) more


**Abstract not available for JP2003505707 (A)**

**Abstract of corresponding document: WO0108081 (A1)**

The present invention provides an improved integrated system for biological marker identification. The system uses Microvolume Laser (11) Scanning Microscopy (MLSC) (16) in order to measure patterns of expression of biological markers in biological fluids (10).

The system includes improved instrumentation for performing MLSC, and

also includes improved particle detection and analysis methods. The system further comprises an informatics architecture for the analysis of data obtained from the MLSC in tandem with other medical information.



(19) 日本国特許庁 (J P)

(12) 公表特許公報 (A)

(11) 特許出願公表番号

特表2003-505707

(P2003-505707A)

(43) 公表日 平成15年2月12日 (2003.2.12)

| (51) Int.Cl. <sup>7</sup> | 識別記号 | F I           | テグコード <sup>8</sup> (参考) |
|---------------------------|------|---------------|-------------------------|
| G 0 1 N 21/64             |      | G 0 1 N 21/64 | F 2 G 0 4 3             |
| 15/00                     |      | 15/00         | B 2 G 0 4 5             |
| 15/14                     |      | 15/14         | C                       |
|                           |      |               | D                       |
| 33/483                    |      | 33/483        | Z                       |
|                           |      | 審査請求 未請求      | 予備審査請求 有 (全 69 頁)       |

(21) 出願番号 特願2001-513096(P2001-513096)  
(86) (22) 出願日 平成12年4月26日 (2000.4.26)  
(85) 翻訳文提出日 平成14年1月21日 (2002.1.21)  
(86) 国際出願番号 P C T / U S 0 0 / 1 1 1 3 3  
(87) 国際公開番号 W O 0 1 / 0 0 8 0 8 1  
(87) 国際公開日 平成13年2月1日 (2001.2.1)  
(31) 優先権主張番号 6 0 / 1 4 4 , 7 9 8  
(32) 優先日 平成11年7月21日 (1999.7.21)  
(33) 優先権主張国 米国 (U S)


(71) 出願人 サーロメッド・インコーポレーテッド  
アメリカ合衆国カリフォルニア州94043,  
マウンテン・ビュー, ガルシア・アベニュー  
2375  
(72) 発明者 ディーツ, ルイス・ジェイ  
アメリカ合衆国カリフォルニア州94041,  
マウンテン・ビュー, サウス・ショアライン  
・ブルヴァード 550  
(72) 発明者 ウォルトン, イアン  
アメリカ合衆国カリフォルニア州94062,  
レッドウッド・シティ, レイクビュー・ウ  
ェイ 346  
(74) 代理人 弁理士 社本 一夫 (外5名)

最終頁に続く

(54) 【発明の名称】 微小体積レーザ・スキャニング・サイトメトリのためのシステム

(57) 【要約】

本発明は生物学的マーカ識別用に改良された統合システムを提供する。生物学的流体 (10) の中で生物学的マーカの表現のパターンを測定するために、微小体積レーザ (11) スキャニング顕微鏡法 (MLSC) (16) を使用する。システムはMLSCを実行するために改良された計測器を含んでおり、また改良された粒子検出及び分析法も含む。さらにシステムは、他の医療情報と提携してMLSCから得られたデータを分析するための情報処理システム・アーキテクチャを含む。



**【特許請求の範囲】**

**【請求項1】** 蛍光性のバックグラウンドを保持し、バックグラウンド特性を示す固定容積の毛細管において複数の検知可能な特性を持つターゲット粒子を検知し特性を決定するために粒子を含有しているサンプルを分析するための方法であって、

(a) データの各チャンネルは明瞭な検知可能な特性及び明瞭なバックグラウンド特性を含み、サンプルを含んでいる固定容積の毛細管を走査してデータの複数のチャンネルを生成するステップと、

(b) データのチャンネルの各々をサンプリングして対応する組のピクセル値を作成するステップと、

(c) 各組のピクセル値を個別に修正することによって増強されたピクセル値の組を生成し、ターゲット粒子を示す空間の特徴を選択的に増強するステップと、

(d) 1つ以上の組の増強されたピクセル値から、対応するチャンネルの明瞭なバックグラウンド特性を取り除くステップと、

(e) 増強された各組のピクセル値に対して、前記粒子を検出するためのノイズ閾値を別々に確立するステップと、

(g) 増強された各組のピクセル値において、前記粒子の診断パターンに配置された上記閾値ピクセルのグループを別々に識別するステップと、

(h) 特定の組の増強されたピクセル値において診断パターンに配置された上記閾値ピクセルの各グループに対して、残りの組の増強されたピクセル値における対応する閾値より下あるいは閾値のピクセルを別々に識別するステップと、

(i) ステップ (g) 及び (h) において別々に識別されたピクセルの分析によって、サンプル内のターゲット粒子の特性を決定するステップとを含み、

粒子は、前記粒子の診断に用いるパターンに配置された上記閾値ピクセルにより、チャンネルにおいて最初に識別され分析され、その後、最初に識別された上記閾値ピクセルと同じ位置にピクセルを配置することにより、残りのすべてのチャンネルにおいて前記粒子は別々に分析されることを特徴とする方法。

【請求項2】 励起光による照明において複数の波長成分を備えた光を発する粒子を含有しているサンプル上で微小体積レーザ・スキャニング・サイトメトリ（MLSC）を実行するための器具において、

- (a) 前記励起光のための1つ以上の光源と、
- (b) 複数の所定の走査速度で前記励起光を前記サンプル上に走査するための手段と、
- (c) 前記励起光に応答して前記サンプルによって放射された光を収集し走査解除するための手段と、
- (d) 前記放射光線を複数の明瞭な成分波長に分け、各々の前記明瞭な成分波長を別々の光学通路に沿って方向付けるための複数のダイクロイック・フィルタ手段と、
- (e) 放射光線に反応し、明瞭な成分波長を収集するために配置され、可変帯域幅を備えたアナログ・フィルタ手段に動作的に連結される、複数の光検出器と、
- (f) 各アナログ・フィルタ手段に効果的に連結され、かつ各々の光検出器からのデジタル信号出力を与えるために複数の所定のデジタル・サンプリング・レートで操作することができる、デジタル・サンプリング手段とを含み、

前記走査速度、各前記アナログ・フィルタ手段の帯域幅、及びデジタル・サンプリング・レートは、前記粒子の検出を最適化するために統合的に調整されることができることを特徴とする器具。

【請求項3】 励起光を備えた照明上に少なくとも4つの明瞭な波長成分を備えた光を発する微粒子を含有しているサンプル上で微小体積レーザ・スキャニング・サイトメトリ（MLSC）を実行するための器具であって、

- (a) 前記励起光のための1つ以上の光源と、
- (b) 前記励起光を前記サンプル上に走査するための手段と、
- (c) 前記励起光に応答して前記サンプルによって放射された光を収集しスキャニング解除するための手段と、
- (d) 前記放射光線を少なくとも4つの明瞭な成分波長に分け、各々の前記

明瞭な成分波長を別々の光学通路に沿って方向付けるための複数のダイクロイック・フィルタ手段と、

(e) 各光検出器が明瞭な成分波長を収集するために配置され、デジタル・サンプリング手段に効果的に連結される、放射光線に反応する少なくとも4つの光検出器と

を含むことを特徴とする器具。

【請求項4】 器官から得られるサンプル上で微小体積レーザ・スキャニング・サイトメトリ (MLSC) を実行するための統合システムであって、前記サンプルが、励起光を備えた照明上に複数の波長成分を備えた光を発する微粒子を含有する、統合システムにおいて、

(a) 前記励起光のための1つ以上の光源と、

(b) 複数の所定の走査速度で前記励起光を、前記サンプル上に走査するための手段と、

(c) 前記励起光に応じて前記サンプルによって照射された光を収集しスキャニング解除するための手段と、

(d) 前記放射光線を複数の明瞭な成分波長に分け、各々の前記明瞭な成分波長を別々の光学通路に沿って方向付けるための複数のダイクロイック・フィルタ手段と、

(e) 各光検出器が明瞭な成分波長を収集するために配置され、変更可能な帯域幅を備えたアナログ・フィルタ手段に効果的に連結される、放射光線に反応する複数の光検出器と、

(f) 各アナログ・フィルタ手段に効果的に連結され、かつ各々の光検出器からのデジタル信号出力を提供するために多くの所定のデジタル・サンプリング・レートで操作することができる、デジタル・サンプリング手段と、

(g) 1つ以上のコンピュータからなる制御及びデータ分析システムであって、

(i) 各々の臨床プロトコルが、

前記粒子を最適に検出するために必要とされる走査速度と、

前記粒子を最適に検出するために必要とされる各々の前記アナログ・フィルタ

手段の帯域幅と、

前記粒子を最適に検出するために必要とされるデジタル・サンプリング速度と

、

前記サンプルの分析条件と、

前記器官の医療歴と、

前記デジタル信号出力の分析用アルゴリズムと

に関する情報を含む臨床プロトコルを格納するステップと、

(ii) 前記臨床プロトコルからの情報を用いて、前記走査する手段、前記アナログ・フィルタ手段、及びデジタル・サンプリング手段を制御するステップと、

(iii) 前記デジタル信号出力を受け取り、格納するステップと、

(iv) 前記粒子データに関するデータを提供するために、前記臨床プロトコルからの情報を用いて、前記デジタル信号出力を分析するステップと、

(v) 医療条件に関する情報を、前記微粒子に関するデータに格納するステップと、

(vi) (v) からの情報を用いて、前記器官の医療条件を決定するステップと、

(7) 前記粒子に関するデータに、医療条件に係る新情報を生成するステップと

を行う能力がある、制御及びデータ分析システムと

からなることを特徴とする統合システム。

【請求項5】 蛍光性のバックグラウンドを保持し、バックグラウンド特性を示す、固定容積の毛細管内で、複数の検知可能な特性を持つターゲット粒子を検知し特徴を決定するために、粒子を含有しているサンプルを分析するための方法において、前記方法は

(a) データの複数のチャンネルを生成するように、サンプルを含んでいる固定容積の毛細管を走査するステップであって、データの各チャンネルが明瞭な検知可能な特性、及び明瞭なバックグラウンド特性を含む、ステップと、

(b) 対応する組のソース・ピクセル値を作成するように、データのチャン

ネルの各々をサンプリングするステップと、

(c) 合成イメージを生成するためにソース・ピクセル値の組を合計するステップと、

(d) 前記合成イメージ内の粒子検出用の閾値を計算するステップと、

(e) 前記閾値を用いて、前記合成イメージ内の粒子検出を実行するステップと、

(f) 前記合成イメージ内で識別された各粒子に対して、ソース・ピクセル値の組内の対応するピクセルを識別するステップと、

(g) ステップ(f)で識別されたピクセルを分析するステップとを含み、改良点が、

(1) ソース・ピクセル値の各組内で、粒子検出用の閾値を別々に計算するステップと、

(2) ソース・ピクセル値の各組内で、対応する閾値を用いて、粒子検出を別々に実行するステップと、

(3) ステップ(2)におけるソース・ピクセル値の特定の組内で識別された各ピクセルに対して、ソース・ピクセル値の残りの組内の対応するピクセルを識別するステップと、

(4) ステップ(2)及び(3)で識別されたピクセルを分析するステップとを含むことを特徴とする方法。

【請求項6】 蛍光性のバックグラウンドを保持し、バックグラウンド特性を示す、固定容積の毛細管内で、複数の検知可能な特性を持つターゲット微粒子を検知するために、微粒子を含有しているサンプルを分析するための方法において、前記方法が

(a) データの複数のチャンネルを生成するように、サンプルを含んでいる固定容積の毛細管を走査するステップであって、データの各チャンネルが明瞭な検知可能な特性、及び明瞭なバックグラウンド特性を含む、ステップと、

(b) ソース・ピクセル値の対応する組を作成するように、データのチャンネルの各々をサンプリングするステップと、



(c) 合成イメージを生成するためにソース・ピクセル値の組を合計するステップと、

(d) 前記合成イメージ内の微粒子検出用の閾値を計算するステップと、

(e) 前記閾値を用いて、前記合成イメージ内の微粒子検出を実行するステップと

を含み、改良点が、

(1) ソース・ピクセル値の各組内で、最初にソースイメージを合計せずに、微粒子検出用の閾値を別々に計算するステップと、

(2) ソース・ピクセル値の各組内で、対応する閾値を用いて、微粒子検出を別々に実行するステップと

を含むことを特徴とする方法。

**【発明の詳細な説明】****【0001】**発明の技術分野

本発明は、微小体積・レーザ・スキャニング・サイトメトリ (Microvolume Laser Scanning Cytometry) (MLSC) を用いる、生物学的マーカー (biological marker) の分析に関する。本発明は、MLSCを実行するための計測器、その計測器から得られるイメージデータを分析するためのシステム、及び生物学的マーカー・データ及び医療情報の統合分析を行うための情報処理システムを含む。

発明の背景

遺伝子技術 (genomics)、組合わせ化学、及び高スループット・スクリーニングを含む薬品発見における新しい技術革新の結果、臨床試験に利用可能な薬品候補の数が、製薬産業の開発及び経済的許容量を超過している。1998年、世界トップの薬品会社及びバイオテクノロジー会社は、研究開発に500億ドル以上を費やし、そのうちの3分の1以上が、臨床開発に直接費やされた。増大する競争、並びに管理医療組織及び他の支払人からの圧力を含む多くの要因の結果、製薬産業は、市場に出される新薬の安全性及び効率性を含めた品質向上、並びに臨床開発の効率の改善を求めている。

**【0002】**

したがって、最近の薬品発見の技術革新が、臨床試験を困難にする一因となった。確認されている治療ターゲット、並びに生成されている鉛化合物の数は、現時点で実行されているような、製薬会社が臨床試験を行なう容量をはるかに越えている。さらに、新薬を開発する平均コストがほぼ5億ドルであると当産業が現時点で推定しているように、可能性のある薬品候補のすべてを開発することは法外に費用がかかる。

**【0003】**

製薬産業は、薬品開発における相応の技術改善を求めるよう迫られている。臨床試験は非常に高価で、非常にリスクのある状態のままであり、多くの場合、意志決定が非常に主観的な分析に基づいてなされている。その結果、薬品が最も有

効な患者母集団、所定の薬品に対する適切な服用量、及びその使用に伴う副作用の可能性を、判定することは多くの場合困難である。このことは、臨床開発において、より多くの障害をもたらすだけでなく、不適切に服用され、処方され、あるいは危険な副作用を引き起こすかもしれない製品が承認されることになることもある。それらの進行中の薬品数が増加するにつれて、製薬会社は、薬品開発工程の初期において、薬品候補の安全性及び効能のプロフィールについての客観的な測定値を確認する技術を必要としている。

#### 【0004】

生物学的マーカーは、測定されたり、あるいは評価される時に、通常の生物学的なプロセス、病原性のプロセス、又は治療の介入に対する薬理学的な反応、に関する指標として、離散関係あるいは相関を持つ特性である。治療の介入に対する薬理学的な反応は、以下に限定されるものではないが、介入に対する一般的な反応（例えば効能）、介入に対する服用量反応、介入による副作用のプロフィール、並びに薬品代謝の速さ及び薬品代謝の確認といったような薬物動態学の特性、を含む。反応は、特効があるか、又はその逆に作用する（例えば有毒な）変化のどちらかと相関する。生物学的マーカーは、病理学的なプロセスと関連して変化し、診断値及び／又は予想値を持つ、セル又は分子のパターンを含む。生物学的マーカーは、セル母集団及びそれらの関係する分子のレベル、可溶性要素のレベル、他の分子のレベル、遺伝子発現レベル、遺伝子突然変異、並びに病気の存在及び／又は進行と相関する臨床パラメータを含む。病気の進行又は再発といったような臨床エンドポイント、あるいは生活の質の測定（通常、評価に長時間を要する）とは対照的に、生物学的マーカーは、薬品の臨床的なプロフィールについてより迅速な量的な測定を提供することができる。臨床業務及び薬品開発の両方において現時点で用いられる単一の生物学的マーカーは、コレステロール、前立腺の特定抗原（「PSA」）、CD4 Tセル、及びウイルスRNAを含む。高コレステロールと心臓病との間、PSAと前立腺癌との間、及びCD4プラスTセルの減少とエイズのウイルスRNAとの間で、よく知られている相関とは異なって、他のほとんどの病気と相関する生物学的マーカーは、まだ確認されていない。その結果、政府機関及び製薬会社の両方が、臨床試験で使用するための生物学的マーカーの

開発をますます求めているが、薬品開発における生物学的マーカの使用は、現在まで制限されてきた。

#### 【0005】

病気、病気進行、及び治療法に対する反応、並びに生物学的マーカとの相関を確立するために必要とされる膨大な量の情報を分類することができる生物学的マーカ同定システムに対するニーズがある。そのような生物学的マーカ同定システムは、1999年4月26日に提出された「Biological Marker Identification System (生物学的マーカ同定システム)」と題された米国暫定特許出願第60/131,105号、並びにこの出願と同時に提出された「Phenotype and Biological Marker Identification System (フェノタイプおよび生物学的マーカ同定システム)」と題され共に所有されている米国実用出願において、記述されており、それらは共に、その全体がここに参考文献として明確に組み入れられる。この技術は、何百から何千という生物学的マーカを測定するのに必要とされる計測器、このデータが容易にアクセスされるようにする情報処理システム、マーカのパターンを臨床データと相関させるソフトウェア、及びその結果として生じる情報を薬品開発工程内に利用する能力を含む。そのシステムは微小体積・レーザ・スキャニング・サイトメトリ (MLSC) を広範囲に利用する。

#### 【0006】

マーカ同定システムの望ましい実施形態では、生物学的流体を、その流体内の特定の分子と結び付くことのできる1つ以上の蛍光標識付けされた検出分子と接触させる。通常、その生物学的流体は血液サンプルで、検出分子は、1つ以上のサブタイプの血液セルの上あるいは中に存在するセル会合分子に特有の蛍光染料で標識付けされた抗体である。その後、標識付けされたサンプルが毛細管に置かれ、その毛細管がMLSC器具に取り付けられる。この器具は、顕微鏡の対物レンズを通して血液サンプルに向けられたレーザ光を走査する。サンプルから発せられる蛍光は、顕微鏡の対物レンズによって収集され、各蛍光チャンネル内のサンプルの画像が形成される一連の光電子増倍管に渡される。その後、そのシス

テムは、セルを識別するために各チャンネルからの生の画像を処理し、次に、蛍光抗体で標識付けられた各タイプのセルに対して、完全なセル数、及び相対的な抗原密度レベルを決定する。

#### 【0007】

またマーカMLSCは、生物学的流体内の可溶性要素の量を計るために、その要素に対する蛍光標識付けされた二次抗体に加えて、その要素に対する微小球体束縛一次抗体を用いることによって、使用されることができる。そうすることで、その要素は、微小球体に結び付けられ、その結び付けられた要素を、二次抗体の結合が蛍光で標識付けする。この実施形態におけるシステムは、溶性の各要素の濃度を決定するために、血液サンプル内の各ビードに関する蛍光信号を測定する。複数のビード・タイプ（各々が異なる一次抗体と結合する）を用いることにより、同じサンプル量で複数の分析を実行することが可能である。各ビード・タイプを識別するために、異なるビードが別個のサイズを持つか、又は異なる内部の色を持つか、あるいは各二次抗体が異なる蛍光体で標識付けされる。

#### 【0008】

本発明の望ましい実施形態は、生物学的マーカを検知するために抗体を用いるが、特に特定の生物学的マーカに結び付くことのできる任意の他の検出分子も意図される。例えば、様々なタイプの受容分子は、蛍光標識付けされた同系統の配位子との相互作用を通して検知されることができる。

#### 【0009】

分析の対象であったセル母集団及び可溶性要素に関するデータを作成するために、MLSC器具からの生データが、画像分析ソフトウェアによって処理される。その後、このデータがデータベースに転送される。生物学的マーカと病気又は医療条件との間の相関を確立する目的で、このセル母集団及び可溶性要素のデータに加えて格納されることができる他のデータは、それに制限されるものではないが、薬品投与と薬物生体反応（身体内での薬品の濃度とその代謝の測定）、並びに個人の年齢、性、体重、身長、体型、病歴（病的状態と同等のもの、投薬などを含む）、（もしあれば）病気又は医療条件の発現と分類、及び医師によってなされた他の標準的な臨床観察を含む臨床パラメータ、を含む。また臨床パラメ

ータに含まれるものは、それに制限されるものではないが、標準E L I S Aテスト、酵素活性に対する比色機能検定、及び質量分光測定を含む、個人の体液の中に存在する特定分子の濃度を測定するための他の技術から得られる結果だけでなく、環境的な及び家系的な履歴要素である。またデータは、レントゲン写真、脳のスキャン、又はMRIといったようなイメージ、あるいは個人の状態についての生体組織検査、心電図、ストレステスト又は他の測定から得られる情報を含む。

### 【0010】

そうして情報処理システムは、a) そのデータを、(同じ個人から、病気の進行又は治療評価目的のいずれかから) 格納されているプロフィールと、及び／又は(病気診断用の) 他の個人からのプロフィールとを比較し、そしてb) 新しいプロフィールを引き出すためにそのデータを「調べる」。このような方法で、診断及び前兆となる情報がデータベースから得られ、引き出されることができる。

1999年4月26日に提出された米国特許出願第60/131,105号の「Biological Marker Identification System (生物学的マーカ同定システム)」と、共通に所有される米国実用出願において、この出願と同時に提出された「Phenotype Biological Marker Identification System (フェノタイプの生物学的マーカ同定システム)」と題された出願との両方が、参考文献としてその全体がここに組み入れられ、多くの様々なアプリケーションにおいて、MLSCの用途が非常に詳しく記述される。システムは、従来の技術システムがドナー・サンプル中の変動によって妨げられる分析であっても、強い一貫した分析データを提供することができる。アプリケーションは、病気進行中及び治療中の、セルタイプ母集団の変化及び可溶性要素の変化を測定するためにMLSCの使用を含む。例えば、MLSCは多発性硬化症及び慢性関節リウマチに対する斬新な生物学的マーカを識別するために用いられることができる。

### 発明の概要

本発明は微小体積・レーザ・スキャニング・サイトメトリ (MLSC) を実行するために改良されたシステムを提供する。システムはSurroScanシス

テムと名付けられる。それは、可変の走査速度で動作することができ、かつ、4つの異なる蛍光チャンネル内で同時にデータを収集することができる改良されたMLSC器具を含む。本発明は、MLSC器具から得られた生データ上でイメージ処理を実行するための改良された方法、及び関連データベース内でこのデータを機能させる改良された方法を含む。ここで記述される改良点は、高速で多要素からなる病気データベースの構築及び使用を大いに促進する。このデータベースは、ユーザが、a) 前兆となる結果又は診断に役立つ結果を得るために、レーザ・スキャニング・サイトメータで得られた血液プロフィールを、よく知られた病気で苦しむ個人について格納されたプロフィールと比較できるようにし、そしてb) ユーザが特定の病気に対する新しい前兆及び診断に役立つプロフィールを速やかに構築できるようにし、c) 生物学的マーカのパターンと任意の器官内の病気との間の新しい関連を発見できるようにする。

#### 発明の詳細な記述

##### 定義

ここで用いられているような用語「生物学的マーカ」又は「マーカ」あるいは「バイオマーカ」は、通常の生物学的工程、病原性工程、又は治療の介入に対する薬理学的反応の、インディケータとして測定され数値を求められる特性を意味する。治療の介入に対する薬理学的反応は、制限されるものではないが、一般的な介入に対する反応（例えば効能）、服用量による介入に対する反応、介入の副作用プロフィール、及び薬物動態学的特性を含む。反応は、有効であるか、又はその逆の（例えば有毒な）変化と相関する。生物学的マーカは、病理学的工程に関連して変化し、かつ診断及び／又は前兆となる値を持つ、セル又は分子のパターン又は集合を含む。

##### **【0011】**

生物学的マーカは、制限されるものではないが、病気の存在及び進行、並びに治療に対する通常の生物学的工程及び反応と相関する。セル母集団の総数、並びに会合分子のレベル、可溶性要素のレベル、他の分子のレベル、遺伝子発現レベル、遺伝子突然変異、及び臨床パラメータを含む。臨床業務及び薬品開発の両方において現時点で用いられる単一の生物学的マーカは、コレステロール、P S A

、CD4 Tセル、及びウイルスRNAを含む。高コレステロールと心臓病、PSAと前立腺がん、並びにCD4プラスTセル及びウイルスRNAとエイズ、の間でよく知られている相関とは異なって、他のほとんどの病気と相関する生物学的マーカーは、まだ確認されていない。その結果、政府機関及び製薬会社の両者が、臨床試験で使用するための生物学的マーカーの開発を一層求めているけれども、薬品開発における生物学的マーカーの使用は、現在のところ制限されている。

#### 【0012】

制限されるものではないが、例として、生物学的マーカーは、通常の生物学的状態、病気、又は医療条件と個々別々の関係を持つとしばしば考えられていて、例えば、高コレステロールは心臓病の危険を増大させることに関連し、高いPSAレベルは前立腺がんの危険を増大させることに関連し、CD4 Tセルの減少及びウイルスRNAの増大はエイズの存在／進行と関連する。しかしながら、様々な病気又は医療条件に対して有効なマーカーが、非常に複雑なパターンから成ることは、かなりよくあることである。例えば、特定のセルタイプ上での1つ以上の特定のセル表面抗原レベルの低下が、高レベルの1つ以上の溶性タンパク質、恐らくサイトカインと共に発見される場合、それが特定の自己免疫疾患を示すものであると発見されることがある。したがって、本発明の目的のために、生物学的マーカーは多くのインディケータのパターンを参照する。

#### 【0013】

ここで用いられる用語「生物学的マーカー同定システム」は、患者母集団から情報を得て、データの相関関係及び生物学的マーカーの識別を可能にするやり方で、その情報を消化するためのシステムを意味する。患者母集団は任意の生物体を含むことができる。生物学的マーカー同定システムは、複数のデータカテゴリからなる統合データベースと、前記データカテゴリの各々に対応する複数の個人からのデータと、データカテゴリ内のデータを相互に関係づけるための処理手段とからなり、前記病気又は医療条件を持つ個人を、前記病気又は医療条件を持たない個人と区別することができるように、データカテゴリ又はカテゴリを識別するためのデータカテゴリの相関分析がなされることが可能であり、また前記識別されたカテゴリ（複数可）が前記病気又は医療条件に対するマーカーである。さらにマ-



方は、異なる時点、例えば薬品投与の前と後で、一人の個人に対する様々なデータ・カテゴリ内のデータを比較することにより識別されることができる。S u r r o S c a nシステムと名付けられた本出願であるMLSCシステムは、生物学的マーカ同定システムの1つの例である。

#### 【0014】

ここで用いられる用語「データ・カテゴリ」は、個人の差分を識別することができる測定のタイプを意味する。本発明において有用であるデータ・カテゴリの例は、制限されるものではないが、個人の生物学的流体内での多くのそして何タイプものセル母集団及びそれらの関連する分子と、個人の生物学的流体内での多くのそして何タイプもの可溶性要素と、個人の臨床パラメータに関連する情報と、個人の生物学的流体内での1ml当たりのセルの容積測定カウントと、個人の生物学的流体内での多くのそして何タイプもの小さな分子と、個人のDNAに関連するゲノム情報とを含む。例えば、単一のデータ・カテゴリは、個人の血液内のIL-1の濃度に相当する。さらに、あるデータ・カテゴリは、血液又は尿内の薬品又はその代謝のレベルであってもよい。データ・カテゴリのさらなる例は、CD4Tセルの確実な総数である。

#### 【0015】

ここで用いられる用語「生物学的流体」は、限定されるものではないが、血液（全血、赤血球の溶解によって作られる白血球、周辺の血液単核セル、血しょう、及び血清を含む）、痰、唾液、尿、精液、脳脊髄液、気管支の吸引液、汗、便、関節液、リンパ液、涙、また任意の器官から得られる柔らかくされた組織を含む任意の生物学的物質を意味する。生物学的流体は、通常は、セルとそれらの会合分子、可溶性要素、小分子、及び他の物質を含む。血液は、多くの理由のために、本発明における望ましい生物学的流体である。まず第1に、血液は容易に利用可能で、複数回、抜き取ることができる。血液は、時間が経てば、骨髓内の前駆（セル）から部分的に補充される。血液は抗原投与に反応し、抗原投与についての記憶を保つ。血液は中心に配置され、再循環し、潜在的に身体全体にわたる変化について伝える。血液は、表面の分子、内部の分子、及び個々のセルに関連して分泌された分子を含む、多数のセル母集団を含む。また血液は、サイトカイ

ン、抗体、及び急性期タンパク質などのような自分自身のものと、伝染病に関する化学薬品及び製品のような外部からのものとの両方である、可溶性要素を含む。

#### 【0016】

ここで用いられる用語「セル母集団」は、共通の特性を備えたセル一式を意味する。その特性は、1、2、3、又はそれ以上のセル会合分子の存在及びレベル、サイズなどを含む。1、2、又はそれ以上のセル会合分子は、セル母集団を定義することができる。一般的には、いくつかの追加のセル会合分子が、1つのセル母集団をさらにサブ組化するために使用されることができる。セル母集団は、母集団レベルで識別されるのであって、タンパク質レベルで識別されるのではない。セル母集団は、1、2、又はそれ以上のセルによって定義されることができる。いかなるセル母集団も潜在的なマーカーである。

#### 【0017】

ここで用いられる用語「セル会合分子」は、セルに関連するいかなる分子をも意味する。これは、次のものに制限されるものではないが、1) タンパク質、糖タンパク質、脂質、及び糖脂質のような本来備わっているセル表面分子、2) その受容体に結び付くサイトカイン、Fc受容体に結び付く免疫グロブリン、Bセル又はTセル受容器に結び付く外部からの抗体、及び自己抗原に結び付く自己抗体、のような外来的なセル表面分子、3) セル質のタンパク質、糖質、脂質、及びmRNAのような本来備わっている内部分子、並びに核のタンパク質及びDNA（ゲノム及び身体の核酸を含む）、4) ウイルス・タンパク質及び核酸のような外来的な内部分子、を含む。望ましいセル会合分子は、通常はセル表面のタンパク質である。一例として、白血球分化抗原（現時点でCD-166を通してCD抗原を含む）、（Bセル受容体及びTセル受容体のような）抗原受容器、及び主要組織適合複合体を含む、何百もの白血球のセル表面タンパク質又は抗原がある。これらの部類の各々は、莫大な数のタンパク質を包含する。

#### 【0018】

ここで用いられる用語「可溶性要素」は、生物学的流体、通常は血液内で発見されるすべての可溶性の分子を意味する。可溶性要素は、制限されるものではない。

いが、溶性タンパク質、糖質、脂質、リポタンパク質、ステロイド類、他の小分子、並びに前述の成分の任意の複合体、例えばサイトカインと溶性受容体、抗体と抗原、及び任意のものに複合する薬品、を含む。可溶性要素には、サイトカイン、抗体、急性期タンパク質などのような自分自身のものと、伝染病の化学薬品及び製品のような外部からのものとの両方がある。可溶性要素は、本来備わっているもの、つまり、個人によって作成されたものであるか、あるいはビールス、薬品又は環境上の毒素のような外来性のものである。可溶性要素はプロスタグランディン、ビタミン、代謝物質（鉄、糖類、アミノ酸などのような）、薬品及び薬品代謝のような小さな分子化合物でありうる。

#### 【0019】

ここで用いられる用語「小分子」又は「器官分子」あるいは「小器官分子」は、2～2000の範囲内の分子量を持つ、可溶性要素あるいはセルに関連する要素を意味する。小分子は、制限されるものではないが、プロスタグランディン、ビタミン、代謝物質（鉄、糖類、アミノ酸などのような）、薬品、及び薬品代謝を含む。1つの重要な実施形態では、MLSCシステムが、治療法制度中に他の生物学的マーカと力を合わせて、生物学的流体内での薬品濃度及び薬品代謝の変化を測定するために用いられる。

#### 【0020】

ここで用いられる用語「病気」又は「医療条件」は、任意の生体内での身体機能、システム、あるいは器官の、障害、休止、不調又は変化を意味する。病気又は医療条件の例は、制限されるものではないが、免疫欠乏及び炎症性の状態、癌、心臓血管の病気、伝染病、精神医学的状态、肥満症、また他のそのような病気を含む。図解の方法で、免疫及び炎症性の状態は、慢性関節リウマチ（RA）、多発性硬化症（MS）、糖尿病などをさらに含む自己免疫疾患を含む。

#### 【0021】

ここで用いられる用語「臨床パラメータ」は、病気又は医療条件に関連する臨床的なセッティングにおいて得られる情報を意味する。臨床パラメータの例は、制限されるものではないが、年齢、性、体重、身長、身体タイプ、病歴、民族性、家族の履歴、遺伝要素、環境要因、病気又は医療条件の発現と分類、並びに、

血圧、MRI、レントゲン写真などのような任意の臨床的な実験テストの結果を含む。

### 【0022】

ここで用いられる用語「臨床エンドポイント」は、患者がどのように感じ、機能し、生存しているかを測定する特性又は変数を意味する。

ここで用いられる用語「微小体積・レーザ・スキャニング・サイトメトリ」又は「MLSC」あるいは「MLSCシステム」は、蛍光で標識付けされた検出分子を用いて、サンプルを蛍光放射が記録される光学スキャニングにさらして、小容積のサンプル内の組成の存在を検知する方法を意味する。MLSCシステムは、他の技術とその相違を示すいくつかのキーとなる特徴を持っていて、1) 多くの分析に対して、少量の血液 ( $5-50 \mu\text{l}$ ) だけが必要とされ、2) 確実なセル数 ( $1 \mu\text{l}$  当たりのセル数) が得られ、3) 分析を、全血上か、又は浄化された白血球上のどちらかでダイレクトに実行することができる。この技術が実現すれば、一回の血液採取から、数百の異なるセル母集団の測定が容易になされる。MLSC技術は、米国特許第5,547,849号及び第5,556,764号、及びディーツ等による((1996年の)サイトメトリ23:177-186)、並びに1998年8月21日に提出された「Laser-Scanner Confocal Time-Resolved Fluorescence Spectroscopy System (レーザ・スキャナの焦点を共有する時間分解蛍光分光システム)」と題された米国暫定特許出願第60/097,506号、及び1999年8月20日に提出された「Novel Optical Architectures for Microvolume Laser-Scanning Cytometers (微小体積・レーザスキャニング・サイトメータのための斬新な光学アーキテクチャ)」と題された米国特許出願第09/378,259号に記述されており、それらの各々が、その全体がここに組み入れられる。微小体積毛細管を備えたレーザ・スキャニング・サイトメトリは、全血、処理された血液、及び生物学的流体を含む他の流体内の、蛍光で標識付けされたセル及び分子をモニタするための強力な方法を提供する。さらに本発明は、少量の血液から複数の生物学的マーカーの同時測定を行うためのMLSC

器具の容量を向上させることにより、MLSC技術を向上させる。本発明の改良されたMLSCシステムは、「SurroScanシステム」と名付けられる。

#### 【0023】

ここで用いられる用語「検出分子」は、重要な分子、特にタンパク質に結び付くことができる任意の分子を意味する。望ましい検出分子は抗体である。抗体は単クローン性又は多クローン性でありうる。

#### 【0024】

ここで用いられる用語「色素」、「蛍光体」、「蛍光色素」、「蛍光標識」、又は「蛍光性のグループ」は、レーザによる励起で蛍光を発することができる分子を意味するために、交互に用いられる。間接的なリンクもまたここで包含されるが、色素は通常、本発明内の検出分子と直接的にリンクされる。多くの色素がこの技術分野ではよく知られている。特定の望ましい実施形態では、スペクトルの(600nmを越える)赤い領域で起動することができる蛍光体が用いられる。2つの赤い色素、Cy5及びCy5.5が通常は用いられる。それらは、665及び695ナノメートルの放射ピークをそれぞれ持っており、抗体に容易に連結することができる。両方とも、ヘリウムネオンレーザでもって633nmで起動することができる。使用されることができる3つの赤い色素の組は、Cy5、Cy5.5及びCy7、あるいはCy5、Cy5.5及びCy7-APCを含む。また、1999年7月6日に提出された「Bridged Fluorescent Dyes, Their Preparation and Their Use in Assays (ブリッジ蛍光色素、分析に際してのその準備及びその使用)」と題された米国仮特許出願第60/142,477号を参照のこと。

#### 【0025】

ここで用いられる用語「微粒子」は、いくつかの実施形態中で、生物学的マーカに関する情報を得るためにMLSCによって検知される、すべての巨大分子の構造を意味する。いくつかの実施形態では、その検知される微粒子は、セルであり、他の実施形態では、検知される微粒子は、抗体に標識付けされたビードである。

## 【0026】

本発明は、SurroScanシステム又は単にSurroScanと名付けられた、改良された微小体積・レーザ・スキャニング・サイトメトリ（「MLSC」）システムを提供する。先のシステムは、米国特許第5,547,849号及び第5,556,764号、並びに1999年4月21日に提出された「Biological Marker Identification System（生物学的マーカ同定システム）」と題された米国特許出願第60/131,105号、1998年8月21日に提出された「Laser-Scanner Confocal Time-Resolved Fluorescence Spectroscopy System（レーザ・スキャナの焦点を共有する時間分解蛍光分光システム）」と題された米国暫定特許出願第60/097,506号、ディーツ等による（（1996年の）サイトメトリ23:177-186）、及び1999年8月20日に提出された「Novel Optical Architectures for Microvolume Laser-Scanning Cytometers（微小体積・レーザスキャニング・サイトメータのための斬新な光学アーキテクチャ）」と題された米国特許出願第09/378,259号に記述されており、それらの各々が、その全体がここに組み入れられる。バイオメトリック・イメージング（Biometric Imaging）社から市販されているImagn2000システムは、従来技術のMLSCシステムの例である。

## 【0027】

本発明の改良されたMLSCシステムは、次のコンポーネントを含む、

- （a）被検体サンプルから生データを得るための電子制御システムを含むMLSC器具、
- （b）MLSC器具から生データを収集し向上させるための画像分析システム、
- （c）多重パラメータ分析設計、測定器制御、最終データ分析、及びデータ・アーカイビング用の統合された情報処理システム・アーキテクチャ。

## 【0028】

現在の発明は、MLSCシステムの操作のいくつかのキーとなる側面における

重要な改良、つまり a) MLSC 光学、b) MLSC システム制御電子工学、c) 画像表示及び分析のアルゴリズム、並びに d) 情報処理システム・アーキテクチャを提供する。また本発明は、業界標準であるフロー・サイトメトリ・スタンダード (FCS ファイル形式) に画像表示及びデータ変換するための改良された方法を提供する。

### MLSC 計器

SurroScan システムは、MLSC 器具の光学アーキテクチャにおいて重要な改良を提供する。前の MLSC 器具は、通常は 2 本のチャンネルの蛍光信号を検知することができたが、そのために、単一の実験で同時に検知することができる被検体の数が制限された。いくつかのアプリケーションでは、特定のセルを識別するために、2 つ以上の異なる蛍光信号を検知する必要がある。例えば、CD 4、CD 45 RA 及び CD 62 L を示す単純な T セルのようないくつかのセル母集団を識別するには、3 つ以上の抗原の同時測定が必要である。本発明の改良された SurroScan 器具は、少なくとも 4 つの別個の蛍光信号を検知することができ、そのために、単一の実験内で少なくとも 4 つの別個の蛍光試薬を使用することができる。改良された光学的構成の 1 つの実施形態が図 1 に示される。毛細管アレイ 10 は、分析のためのサンプルを含む。望ましい実施形態では、平行にされた励起光が、1 つ以上のレーザによって提供される。特に望ましい実施形態では、633 nm の励起光がヘリウム・ネオン・レーザ 11 によって提供される。この波長は、生体試料の自己蛍光に関連する問題を回避する。レーザの出力が 3~17 mW まで増大させられる。レーザ・パワーを高めると、2 つの潜在的利点、つまり感度の増大及び走査速度の増大がもたらされる。平行にされたレーザ光は、励起ダイクロイック・フィルタ 12 によって偏光させられる。反射して、光は検流計駆動の走査反射鏡 13 上に入射する。走査反射鏡は、固定された範囲の角度上を、例えば  $\pm 2.5$  度、検流計によって急速に揺れ動かされることができる。走査反射鏡は、顕微鏡の対物レンズ 16 の入射瞳孔上に、その走査反射鏡を映し出す 2 つのリレーレンズ 14 及び 15 の中にその入射光を反射する。この光学的構成は、反射鏡で走査された特定の角度を、顕微鏡の対物レンズの焦点での特定のフィールド・ポジションに変換する。 $\pm$  角度の走査は

、対物レンズの焦点での1ミリメートルのスキャン幅になる。走査角度とフィールド・ポジションの関係は、この構成において、及びこの範囲の角度上では、本質的に線形である。さらに、顕微鏡の対物レンズは、入ってくる平行ビームを対物レンズの焦点平面で1つのスポットに集束させる。光学的解像度を設定するそのスポットの直径は、平行ビームの直径及び対物レンズの焦点距離によって決定される。

#### 【0029】

走査される励起ビームの経路に置かれる蛍光サンプルは、ストークスシフトされた光を発する。この光は対物レンズによって収集されコリメートされる。このコリメートにされた光は、2つのリレーレンズ14及び15から、コリメートされたままで現れ、走査反射鏡に突き当たり、反射鏡はそれを反射しスキャン解除する。その後、ストークスシフトされた光は、ダイクロイック励起フィルタ（より短い波長光を反射し、より長い波長光を通す）を通り抜け、そしてその後、さらに任意の反射された励起光を濾過する働きをする第1の長いパス・フィルタを通過する。

#### 【0030】

その後、本発明の改良された器具は、4つの異なる発光バンドにストークスシフトされた光を分けるために、さらに一連のダイクロイック・フィルタを用いる。第1の蛍光ダイクロイック・フィルタ18は、2つの最も赤い蛍光色から、2つの最も青い蛍光色を分割する。その後、いかなる焦点の外れた蛍光信号をも著しく減少させるために、第1の集束レンズ20を通して、2つの最も青い色が、第1のアパーチャ19上に集束させられる。アパーチャを通過した後、第2の蛍光ダイクロイック・フィルタ21がさらに、個々の青い色を互いに分離する。そうして、その個々の青い色が、2つの別個の光電子増倍管22及び23で分析される。最も赤い2つの色は、第1の蛍光ダイクロイック・フィルタ28によって最も青い2色から分割された後、第2の長いパス・フィルタ25、ミラー26、及び第2の集束レンズ27を通して、第2のアパーチャ24上に集束させられる。アパーチャ24を通り抜けた後に、最も赤い色は、第3の蛍光ダイクロイック・フィルタ28によって互いに分離される。その後、個々の赤い色が、光電子増



倍管29及び30で分析される。このようにして、4つの別個の蛍光信号が、毛細管の中に保持されたサンプルから、同時に個々の光電子増倍管に伝送されることができる。この改良によって、初めて、別個の4つの被検体が同時にモニタされることが可能になる。各光電子増倍管は、入ってくる蛍光光子束に応じて、電子の流れを生成する。これらの個々の電流は、検出電子工学で、1つ以上のプリアンプによって個々の電圧に変換される。その電圧は、走査されたイメージに対して、ピクセルの輝度を決定するために、アナログ・デジタル変換器によって規則的な間隔でサンプルされる。本発明の4チャンネルは、0、1、2及び3と名付けられる。

### 【0031】

意味のあるデータが、単一の励起波長、例えばヘリウム・ネオン・レーザからの633nmを用いて、得られるようにするためには、単一の励起波長から励起されることができ、オーバーラップが最小で識別可能な波長を発する、色素が必要である。ヘリウム・ネオン・レーザを用いる3チャンネル検出システムに対して、3種の色素の適切な1つの組合せは、Cy5（670nmで放射ピーク）、Cy5.5（694nmで放射ピーク）、及びCy7（767nmで放射ピーク）である。代案となる実施形態では、アロヒコシアニン（allophycocyanin（APC））がCy5と置換される。Cy7（743nm）に対する吸収ピークが、ヘリウム・ネオン励起レーザの波長（633nm）からずっと離れているので、通常、この分野の技術を持つ者であれば、ヘリウム・ネオン励起システムにおいてCy7が有用であるとは見なさない。しかしながら、本発明者は、全血内の特定のセルを数え上げるために、Cy7が633nmで十分に励起させられることが可能であることを発見した。この励起は、おそらく長い励起テールが存在に起因し、それはMujumdar, R. B.、L. A. Ernst、S. R. Mujumdar、C. J. Lewis、及びA. S. Waggonerによって1993年に「Cyanine dye labeling reagents: sulfoindocyanine succinimidyl esters（試薬にラベルを付けるシアニン色素であるスルホインドシアニン・スクシンイミディル・エステル）」と題されたBioconj Chem

、4:105-11に記述されていて、その全体がここに参考文献として組み入れられる。Cy 7の励起及び検出は、レーザーパワーを増大させること、及びスペクトルの赤色領域に対してより敏感な検出器を用いることにより改良されることができる。

#### 【0032】

他の実施形態では、APC励起波長で励起可能であるが、Cy 7放射波長で放射する、縦並びの色素を作るために、Cy 7がAPCに連結される。この縦並びの色素は、アクセプタ（Cy 7）を励起させるために、ドナー（APC）からのエネルギー移動を用いるが、そのことは、Beavis, A. J.、K. J. Pennlineによって1996年に「Allo-7: a new fluorescent tandem dye for use in flow cytometry (Allo-7: 流動セル分析において使用するための新しい蛍光の縦並び色素)」と題されたCytometry, 24:390-5、並びにRoederer, M.、A. B. Kantor、D. R. Parks、及びL. A. Herzenbergによって1996年に「Cy7 PE and Cy7 APC: bright new probes for immunofluorescence (Cy7 PE及びCy7 APC: 蛍光抗体法のための鮮やかな新しいプローブ)」と題されたCytometry, 24:191-7において記述されており、その両方ともその全体がここに参考文献として組み入れられる。

#### 【0033】

本発明のいくつかの実施形態では、1つ以上の励起波長が使用される。1つ以上の励起波長を用いることによって、各色素が同じ励起要件を持つ必要がないように、種々様々な蛍光色素を用いることが可能である。複数の励起波長が、少なくとも3つの方法、(1) 488 nm、568 nm、及び647 nmの励起波長を備えた励起光源としてAr-Krレーザを用い、そのために、3つの異なる蛍光性のグループ（例えばフルオレセイン、ローダミン、及びTexas Red（登録商標））からの3種類の励起に対する使用が可能となる方法、(2) コリメートされた励起光の異なる波長を各々が供給する1つ以上のレーザ・ソースを

用いる方法、(3)多光子の蛍光励起用のTi-Sレーザ(〜700nmの励起光)又はNd:YLFレーザ(1047nmの励起光)といったようなフェムト秒のパルスを生成することができるレーザを用いる方法、で得られる。

#### 【0034】

上に記述された本発明の実施形態は、別個の4本のチャンネルを用いるが、ここで開示される光学アーキテクチャは、より多くの偶数個のチャンネルを備えた器具の設計を考慮に入れる。

#### 【0035】

望ましい実施形態では、走査されるサンプルが、X、Y及びZ平面に自動翻訳可能なステージに取り付けられる。検流計で操作される反射鏡が、Y軸における励起ビームを走査するが、その時、ステージはX軸においてサンプルを等速度で移動させる。走査されたビーム速さで乗算された各アナログ・デジタル変換器のサンプル採取間隔が、イメージのY軸にけるピクセル間隔を決定する。線レートで割り算されたXステージ走査速度は、イメージのX軸におけるピクセル間隔を決定する。

#### 【0036】

ステージはX軸において個々のサンプルを走査するだけでなく、顕微鏡の対物レンズに対して多くのサンプルを左右に動かすことができる。このようにして、いかなるオペレータも介入せずに、コンピュータ制御によって、多くの個々のサンプルを順次走査することができる。このことが、器具のスループットを大幅に増大させ、器具による臨床セッティング内の血液サンプルの高速での自動分析をより行いやすくする。

#### 【0037】

本発明の望ましい実施形態では、SurroScanのMLSCのステージが、1つ以上の毛細管アレイを保持し、その各々が96-ウェル・プレートのフットプリントを持つ。各毛細管は、分析されるべきサンプルを保持する。多重チャンネル・ピペットと互換性をもつ各々32本の固定された毛細管及び間隔を持つ使い捨ての毛細管アレイは、1999年4月23日に提出された「Disposable Optical Cuvette Cartridge (使い捨ての

光学キュベット・カートリッジ)」、「Spectrophotometric Analysis System Employing a Disposable Optical Cuvette Cartridge (使い捨ての光学キュベット・カートリッジを使用する分光光度分析システム)」、及び「Vacuum Chuck for Thin Film Optical Cuvette Cartridge (薄膜の光学キュベット・カートリッジ用の真空チャック)」と題された米国仮特許出願の代理人登録第032517-004号、005号及び006号、並びに2000年4月21日に提出された「Disposable Optical Cuvette Cartridge (使い捨ての光学キュベット・カートリッジ)」と題された共有される米国特許出願、において記述されていて、その全体がここに参考文献として組み込まれる。各アレイは、毛細管の内側の大きさを規定するように型抜きされている、2倍の粘質を持つ粘着層で共に間にはさまれた2層のマイラーから造られる。その結果生じるカートリッジは、フレックスー32と呼ばれ、大量に低価格で製造されることができる。カートリッジは柔軟であり、そのために、真空圧力によって光学的に平らな底板上に保持されることが可能であり、製造工程において平らであることに対する要件が除去される。毛細管の間隔は、多重チャンネル・マイクロプレート・ピペッタ及びロボット工学との互換性を保持するように設計された。

#### 【0038】

望ましい実施形態では、オペレータが、32本の毛細管を持つ2つのプレートを一度に取り付けることができる。プレートが走査され、イメージが処理されている間は、オペレータの介入は必要ない。代案として、Imagn2000 (VC120) 用に設計された16本の個別の毛細管が、別のホルダに取り付けられる。

#### 【0039】

ステージのZ運動は、対物レンズの焦点平面に各サンプルを置くための手段を提供する。またZ運動は、各々の個別のサンプルに対する焦点平面イメージのスタックを捕捉することができるよう走査されることが可能である。オペレータ介入の必要性を回避するために、コンピュータ制御システムによって、各サンプル

に対する最適の焦点位置を、この走査されたZイメージから決定できることが望ましい。さらに、サンプルの2つの両端に対して、最適の焦点を決定することができる。サンプルがX軸において走査されている間、ステージは、2つの両端の間の焦点差を通じて等速度で動かされ、そうしてサンプルあるいは取付具に存在するかもしれないすべての傾斜を修正する。

#### 【0040】

レーザ光線の走査速度は、各ピクセルで光信号を統合するのに費やされる時間を決定するが、統合時間が長いほど、信号対雑音比が良くなる。また走査速度は、システムのスループット速度に比例する。以前のMLSC器具は、単一の速度でサンプルを走査した。これは多くのアプリケーションにとって適切であるが、本発明は走査速度が変更可能なシステムの使用を意図する。そのように走査速度が変更可能なシステムであれば、各々の個別のサンプルに対してシステム感度を最適化することが可能である。例えば、ある種の分析は、サンプル内に非常に低濃度で存在する検体の検出を必要とするかもしれない。そのような低濃度の検体からの蛍光信号は、バックグラウンド・ノイズに比べて、相当低い可能性がある。このような場合、走査をゆっくり行うことによりシステム感度を増大させることができ、各ピクセルで光信号を統合するための時間をより多くすることが可能である。このことにより、信号対雑音比内が大きく改善されることになる。対照的に、ある種の分析では、サンプル内に検出される特定の検体の濃度が比較的高いために、はるかに明るい蛍光信号の検出を伴うかもしれない。この場合、より速い走査速度が望ましく、満足な信号対雑音比を達成する各ピクセルの信号を統合するために必要な時間は少しでよい。また走査速度が速ければ、それだけ大きなサンプル・スループットが得られる。したがって、ここで考えられている走査速度が変更可能なシステムは、従来技術である走査速度が固定されたシステムにとって大きな改善である、なぜならば、それは、a) 各検体の信号対雑音比を最適化することができ、そのために、各検体にとって可能な最も高い品質のデータを収集でき、そして、b) 可能な最も効率的なスループット速度でシステムを機能させることができるからである。すべての場合に、検流計に取り付けられた反射鏡の走査速度を調整することによって、及びサンプル・イメージング中にス

テージがX軸において移動する速さを調整することによって、その走査速度は変更されることができる。

#### 【0041】

またS u r r o S c a nシステムは、各走査速度でシステム感度を最適化するために、アナログ処理回路に組み込まれる斬新な切り替え可能フィルタ・スキームを提供する。低域通過フィルタは、一般に重要な信号を通過させるため、及び測定工程で作られる不必要な高周波ノイズを拒絶するために用いられる。S u r r o S c a nシステムでは、各走査速度に対する最適フィルタ帯域幅が、異なっていて、通常は走査速度に比例する。望ましい実施形態では、少なくとも2つの帯域幅が、切り替え可能なフィルタによって各チャンネルに提供される。特に望ましい実施形態では、4つの帯域幅が提供される。図2 A及び2 Bは、4、8、12、及び16 kHz（64、128、192、及び256ヘルツの走査速度用の最適帯域幅にそれぞれ対応する）の帯域幅を提供する切り替え可能なフィルタ・スキームのための回路図を示す。望ましい実施形態では、そのようなフィルタ帯域幅スイッチング・スキームが、各光電子増倍管チャンネルと関係する。

#### 【0042】

したがって、本システムは、1) システムの走査速度が信号対雑音比を最適化するように変更可能であり、2) 各信号チャンネルでの各アナログ・フィルタの帯域幅もまた信号対雑音比をさらに最適化するために変更されるという、2つの別個の方法で最適化されるので、本発明は従来技術のMLSCシステムを越える大きな改良である。この斬新な組合せは、相乗してMLSC器具及びシステムの感度及び効率を向上させる。

#### 【0043】

本発明の望ましい実施形態では、S u r r o S c a nシステムの最適の走査速度及びフィルタ帯域幅が、各々の実行される特定の分析に対して決定される。これらの変数は、後にオペレータが同じ分析の再実行を選択する場合に、これらの設定値を自動的に選択することができる臨床プロトコル・データベース（以下を参照）に格納される。このようにして、同じステージ上で、多くの様々な分析を行うことが可能であり、コンピュータは、各サンプルに対して、前もって定義し

た最適の走査速度及びフィルタ設定を自動的に選択することができる。この利点  
が、S u r r o S c a nシステムの柔軟性に大きく寄与している。

#### 【0044】

上に記述されたすべての実施形態は、微粒子を検知するために、可視か、ある  
いは電磁スペクトルの赤外線部分の近くで発する蛍光体のレーザ励起を使用する  
ことに注目すること。しかしながら、本発明はまた、赤外線のような他のタイプ  
の電磁放射及び放射プローブの使用を意図する。さらに、本発明は、ただの単一  
のプローブだけではなく、プローブのアセンブリの使用を意図する。また本発明  
は、制限されるものではないが、ラマン散乱、ミー散乱、ルミネセンス、及び燐  
光を含む、蛍光以外の光散乱モードの使用を意図する。

#### S u r r o I m a g e 画像分析ソフトウェア

イメージ処理は、レーザ・スキャニング・サイトメトリにとって、重大な要件  
である。イメージ処理プログラムは、セルの蛍光又は他の微粒子の蛍光（チャン  
ネル）の異なるスペクトル領域を描写する複数のバイナリ・イメージを処理する  
必要がある、また、各チャンネルのバックグラウンド蛍光レベルを決定する必要  
がある、また、ノイズからセル又は他の微粒子を数えあげることができるような  
、各チャンネルの全体のノイズ、また、バブル、ゴミ微粒、及び他の「汚れ」や  
「ほこり」の源といったような外来の信号を無視する必要がある、また、制限さ  
れるものではないが、加重フラックス、サイズ、楕円率、並びに同じ位置にある  
他チャンネル内の信号間の比率及び相関を含むパラメータをレポートするために  
、各々の識別されたセル又は微粒子の特性を決定する必要がある。S u r r o S  
c a nシステムは、上記の基準を満たし、テキスト・リストモード・フォーマッ  
トでの分析結果を出力するS u r r o I m a g eシステムと呼ばれるイメージ処  
理及び微粒子検出システムを含む。

#### 【0045】

S u r r o I m a g eシステムについての次の説明は、バイナリ・イメージ入  
力ファイル（. s m l）で始まり、関連する様々なアルゴリズムの記述及び説明  
を備えたテキスト・リストモード出力ファイル（. l s m）までの、関数の形式  
で与えられる。図3は、S u r r o I m a g eシステムによって実行される操作

のフローチャートを描く。後に続く有効にする記述において、SurroImageシステムは、セル検出のコンテキストで記述されることにも注意すること。しかしながら、上に記述されるように、SurroImageシステムは、抗体標識付けされたビードのような、定義済みの物理パラメータを備えるいかなる構造をも検知することができる。SurroImageシステムは、制限されるものではないが、「Biological Marker Identification System (生物学的マーカ同定システム)」と題された米国暫定特許出願第60/131,105号、及びこの出願と同時に提出された「Phenotype and Biological Marker Identification System (フェノタイプの生物学的マーカ同定システム)」と題された共有される米国実用出願において記述されている実施形態を含めて、従来技術において記述されるMLSCのいかなる実施形態での使用に対しても意図される。

## 入力

本発明の望ましい実施形態では、バイナリの組み合わせられたフォーマットが、イメージデータを格納するために用いられる。図4に図解されたフォーマットで、いかなる数の16ビット・データ・チャネル（イメージ）でも組み合わせることができる。チャンネル・イメージ・アレイは、各行に沿って格納される：（行0：列0、列1、列2、...、列n列；行1：...、行n行へ）、ただし、n列は通常250ピクセルで、n行は通常10000ピクセルである。図4に示されるようなSM1ヘッダは、記述子当たり4バイトを備えたヘッダ内に28バイトを持つ。各ファイル記述子は、下位—上位ワードの形式で配列される。「4文字記述子」は「SM01」のようなユニークなイメージ・タイプを記述する任意の4文字でありうる。

## 【0046】

本発明の1つの実施形態で、システムはピクセル当たり2バイトあるいは16ビットを使用しているので、各ピクセルは、65536の値のうちのいずれかを持つことができる。しかしながら、フィールド記述子「ピクセル当たりのバイト」が、ワードからフロートまで、又は他のデータフォーマットまで、イメージタ



イブを拡張する柔軟性を可能にする。さらに、変数フィールド「ヘッダ内のバイト」が、さらなるフィールド記述子を追加する能力を見込む。例えば、このフォーマットを利用する4バイトのフロート・イメージは、1ピクセル当たりのバイト＝4を設定することになり、次いで恐らく、さらなる記述子フィールドが、フロートとしてフォーマット・タイプを記述するために追加される。その「インターリーブ」フィールドは、シーケンシャルモードでチャンネルを書くオプションを与える。例えば、本発明のいくつかの実施形態では、走査システムが、チャンネル情報を同時にではなく、順次に集める、例えば、最初にチャンネル0のすべてのデータを格納し、次にチャンネル1が続くといった具合である。図4は、望ましいファイル・フォーマットの図式を示す。

#### 【0047】

望ましい実施形態では、\*.SM1ファイルが、SurroImageから読み取られ、各チャンネルがハンドル記述子を備えたメモリに格納される。データの各チャンネルに関する情報は、イメージ・ハンドル特性と共に、SmImageInfoと称されるクラスに格納されるが、hImはその構造の1メンバである。

#### 実行：任意パラメータ

望ましい実施形態では、SurroImageは実行可能なコマンド行である。プログラムを実行するために、次のフォーマットが使用されることができる。

C:>SurroImage {SM1入力ファイル} {任意のLSM出力ファイル} {任意パラメータ・リスト}

ただし、

SM1入力ファイル： \*.sm1ファイルへのフルパス、

任意のLSM出力ファイル： \*.lsmの出力位置を指定する任意のフルパス。  
このパラメータが省略される場合、ベース名\*を含む\*.sm1と同じパスが使用される。

任意パラメータ・リスト： スペースで区切られた複数のパラメータが割り当てられる。フォーマットの例は、

SurroImage C:/SM1\_Files/Image1.sm1 C

: \LSM\_Files\Image1.lsm ThreshRatio=1  
 , 2 Write RAWFiles

である。

# 【0048】

任意パラメータは、制限されるものではないが、以下のものを含む。

ThreshRatio: セル検知閾値レベルを決定するために使用される倍数因子。

iNumCorrelations: チャンネルのiNumCorrelations数への相関を提供する。

UseBandPassForBlob: 1の場合、セルを検知するために濾過されたイメージを使用する (UsePeaksForBlobsと相互排除でなければならない)。

UsePeaksForBlobs: 1の場合、セルを検知するために、5x5核の中心と、外部ピクセルとの間の差分を使用する。

UseFullPerimDetect: 1の場合、セルを見つけるために中心と関連する外部のすべての周囲ピクセルを使用する。

Blobarealo: 検知すべき最小のセル直径。

MaxCellSize: MaxCellSizeへのセルの直径を直径>MaxCellSizeに設定する。

RowsPerNoiseBlock: ピークーピーク・ノイズ計算において、

ブロック当りに使用する行の数

SampleRowsPerNoiseBlock: ノイズ計算用に各ブロック内でサンプリングすべき行の数

MaxBlobPix: 閾値化されたメジアン減算ソースイメージが、特定のセグメントをイメージ・マスクに追加されるべき「プロブ」として指定する、隣接ピクセルの数

MaxBubblePix: 負に閾値化されたメジアン減算ソースイメージが、

特定のセグメントをイメージ・マスクに追加されるべき「バブル」として指定する、隣接ピクセルの数

**BubbleThreshFactor** : バブル検出のためにメジアン減算ソースイメージに適用される  $\text{threshold} * \text{NoiseFactor}$ 。代わりに、**NoiseFactor** は、ベースライン値（本文参照）に置き換えることができる。

**BlobThreshFactor** : 汚れ検出のためにメジアン減算ソースイメージに適用される  $\text{threshold} * \text{NoiseFactor}$ 。代わりに、**NoiseFactor** は、ベースライン値（本文参照）に置き換えることができる。

**MaskDilationPix** : 最終マスク・イメージは、拡大した **MaskDilationPix** ピクセルである。

**WriteRAWFiles** : すべての中間の画像ファイルが C:\A のディレクトリに書き込まれるべきかどうかを示す診断に用いるブール変数

**SameCellRadius** : それらの重心間の距離（フロート・フォーマットにおける）が、**SameCellRadius** 以下である場合、代替チャンネル内のセルは、同じセルと見なされる。

**NomCellMicrons** : 次の3つのパラメータは、すべてのセル計算のために用いられる核・サイズを決定する。

**BeamMicrons** :  $\text{NomCellPix} = \text{hypot}(\text{NomCellMicrons}, \text{BeamMicrons}) / \text{MicronsPerPix}$

**MicronsPerPix** :  $i\text{NomCellPix} = (\text{int})(\text{NomCellPix} + 1.)$  で、 $i\text{NomCellPix}$  は  $(\text{KernelSize} - 1) / 2$  である。

**PrintMode** : LSMファイルのテキスト出力フォーマットを決定するための数えられる変数で、0の場合は人間に読み取り易く、1の場合はタブで区切られ、2の場合はカンマで区切られる。

各チャンネルからのソースイメージの処理

SurroImage内の主要ルーチンは、SMProcessImages  
 ①と称される。望ましい実施形態では、制限されるものではないが、SurroImageシステムが、各ソースイメージ、すなわち各チャンネルからのイメージ上に、濾過を行い、マスクをし、汚れ及びバブルを見つけ、最初のセルリストを確立することを含めて、多くの機能を実行する。SurroImageシステムの主要な機能は、発生している個々のチャンネルを合計することなく、各チャンネルが別々に分析されるということである。手短かに言えば、SurroImageシステムは、ノイズ及びバックグラウンド機構（バブルや汚れのような）を除去し、かつ識別される微粒子の空間特性を備えた特徴を増強させるために、各ソースイメージ上で多くの操作を別々に実行する。またシステムは、各チャンネルの微粒子決定用の閾値を決定し、この閾値及び微粒子パラメータに基づいて、各チャンネルの微粒子を別々に識別し分析する。その後、システムは、微粒子がそのチャンネルに対する閾値未満であったために微粒子が検知されなかった残りのチャンネルにおいて、同じピクセルを発見し、それらのチャンネル内の微粒子のパラメータも測定する。この方法で、SurroImageシステムは、微粒子が最初は識別されなかったチャンネルでさえ、各識別された微粒子のデータを収集する。

#### 【0049】

望ましい実施形態では、1) 濾過されたソースイメージ（たたみこみ核のアプリケーション）、2) メジアン減算ソースイメージ、及び3) 一時記憶用に使用される作業イメージ、を格納するために用いられる、多くの浮動小数点イメージにハンドルを開くことによって、SurroImageシステムが始動する。さらに、多くのBYTEイメージが、後で説明されるマスク・イメージを含む、上記の浮動小数点イメージの閾値バージョンを格納するために作成される。

#### 【0050】

各チャンネルに対して、ベースラインとなる分析を実行することにより、ルーチンが始動することが望ましい。このサブルーチン・コールは、y（注釈：後の参考のために、xは、通常は40ミリメートルあるいはn行=10000ピクセルである長い毛細管の方向であり、yは、通常は1ミリメートルあるいはnC0

Is = 250ピクセルである検流計走査の方向である)に関するベースラインの全体的な変動に対する統計値を返す。統計値は、ベースラインが、定義済みの制限(一般に、最大値-最小値 > 0.3メジアン値)を越えて変化したことを示すブーリアン値のBaselineErrorFlagを含めて、全体的に格納されることができる。図5は、フローチャート形式でこのプロセスを描く。

#### 【0051】

それから望ましい実施形態では、15x15のメジアン核が、TurboMedian<sup>®</sup>と称される高速のメジアン・アルゴリズムを用いて、各ソースイメージに適応される。核は、15x15核内の中心ピクセルを、核内の全ピクセルのメジアン値に置き換えることにより作動する。各ピクセルにこのメジアン核を適応することは、Y軸におけるイメージに沿って生じる、ピクセル輝度内の緩やかな変動を「スムーズにする」ように作用する。スムーズにする作業の第一の役割は、セルによる輝度への寄与分を取り除くことであり、その結果、イメージのバックグラウンド表示を得る。メジアンイメージは、ソースイメージから差し引かれ、hImbgndと称されるグローバル・ハンドルに格納される。制限されるものではないが、全フラックス、楕円率、及びセル直径(フィット・エリアとも呼ばれる)を含むセルパラメータを決定するために、セルリストが生成された後に、このイメージは使用されることができる。

#### 【0052】

その後、望ましい実施形態では、複数のイメージが、定義済み核でたたみこまれ、imBlobSrcと称されるグローバル・ハンドルに格納される。そのようなたたみこみ核は、この技術分野ではよく知られている。選択される核構造(核の大きさ及び核内の加重値)は、検知されることになっている微粒子に依存する。例えば、血液セルの決定であれば、7x7核が、ほぼ血液セルの大きさであるので、通常はこの核が用いられる。本説明のためのたたみこみ核は7x7核であると仮定されるが、他の核が他の実施形態において有用であることが理解されるべきである。このたたみこみの結果は、検知されようとしているセルタイプに対応する定義済みの空間成分でもってそれらの特徴を増強するフィルタ補正されたイメージである。このイメージの閾値バージョンは、セル検出に対して、及

びさらに加重フラックス計算に対して、使用されることができる。

### 【0053】

いくつかの実施形態では、検知されようとするセルタイプに対応する定義済みの空間成分でもって、最初にそれらの特徴を増強するために、上に記述されたたたみこみ法ではなく「ペリメータ」法が用いられる。ペリメータ法は、差分ソースイメージである「差分」イメージを作成し、異なる2つの方法で実行されることができる。ペリメータ法のいくつかの実施形態では、すべてのピクセルが、7 x 7 核のそれと、外部の4つのピクセルとの間の最小差分に設定される。他の実施形態では、各ピクセルが、7 x 7 核のその値と、外部のすべてのピクセルとの間の最小差分に設定される。畳み込まれたイメージではなく、これらの「差分」イメージを使用することは、Use Peaks For Blobs と称されるプリアン・コマンド行の引数を介して指定することができる。この場合もやはり、増強されたイメージは、グローバル・ハンドル `imBlobSrc` に格納される。図6は、フローチャートの形式で、ペリメータ法及びたたみこみフィルタ法の使用を示す。

### 【0054】

どちらの方法が最初の増強に対して用いられても、生じるイメージは閾値化され、細分化分析がセル位置を決定するために実施される。セル検出用の閾値を確立するには、各ソースイメージ内のノイズを突き止めなければならない。望ましい実施形態では、イメージのセグメントあるいはブロック上のピークピーク・ノイズを計算するアルゴリズムが使用される。図7は、フローチャートの形式でこのプロセスを示す。各ブロックは、`n` 列幅（イメージの全幅）で、`RowsPerNoiseBlock`（コマンド行の引数）の長さである。各ブロックに対する各ノイズ値は、`(int) (nRows / RowsPerNoiseBlock)` エレメントを持つアレイに格納される。その後、このアレイは、`thresholdratio`（コマンド行の引数）で乗算され、閾値判定に使用される `n` 行長さのアレイに挿入される。閾値のサブルーチンは、閾値判定された `BYTE` イメージである `imBlobSeg` を生成するために、畳み込まれたイメージ、あるいは「差分」イメージのどちらかを使用する。

## 【0055】

望ましい実施形態では、ソースイメージがチャンネル0に関連したものである場合、MaskGrungeAndBubbles ① と呼ばれるサブルーチンが、imBlobSeg上で細分化又はセル検出を実行する前に呼び出される。図8は、フローチャートの形式で、このサブルーチンを示す。チャンネル0は、バブル及び汚れを発見するために用いられ、それらの領域がマスク・イメージに追加される。これは、サンプルからの最短の放射波長に対応するこのチャンネル内で、サンプル内のゴミが一貫して発生する傾向があるからである。しかしながら、他の実施形態では、他のチャンネル（1つ以上）がマスク・イメージのために使用されることができる。

## 【0056】

マスク・バイト・イメージは、3つの異なる状態を介して付加される。MaskGrungeAndBubbles ① が、これらの状態をテストする。それは、バブルとボルブ閾値であるBubbleThreshFactor及びBlobThreshFactor（ピークピーク・ノイズ値を乗算された）をそれぞれ適用するために、メジアン減算ソースイメージであるイメージhImbgndを用いる。例えば、バブルに関しては、ソースイメージの特定のブロックに対してhImbgndのいかなる部分も、 $-1 * \text{BubbleThreshFactor} * p - p\text{Noise}$ 以下であり（バブルはバックグラウンド蛍光が無い事によって示される）、かつ隣接のピクセル総数がMaxBubblePixを超過する場合、それらの対応するピクセルがマスク・イメージ内で「バブル」を示す特定の値に設定される。同様に、ボルブ検出は、 $\text{BlobThreshFactor} * p - p\text{Noise}$ 及びMaxBlobPixを用いてなされる。別の望ましい実施形態では、バブル及びボルブの閾値判定が、ピークピーク・ノイズレベルの因数ではなく、平均ベースライン値の百分率に基づく。したがって、バブル及びボルブの閾値レベルは、それぞれ $\text{BubbleThreshFactor} * \text{BaseLine}(y)$ 、及び $\text{BlobThreshFactor} * \text{BaseLine}(y)$ によって与えられ、その場合のBaseLine(y)とは、与えられたy値に対してピクセルのx範囲を越えた（つまり毛細管の幅を越える）

ベースラインのメジアン値である。マスクへの最終追加は、セグメント化されフィルタ補正された `imBlobSeg` イメージに基づいてなされる。またそれは、コマンドラインにおいて与えられたのと同じ `ThreshRatio` を用いるが、`MaxBubblePix` を超過する場合にだけ、マスクに追加する。最終的に、`n=MaskDilationPix` のピクセルの拡張（バイナリ拡張とは、そのピクセルが、領域の一部である別のピクセルに既に触れている場合、その任意のバックグラウンド・ピクセルを「オン」に設定する）がマスク上でなされ、セルがバブルの縁で識別されたりすることがないように予防する。たまたみこみフィルタのアーティファクトは、バブルの周縁が、誤ってセルとして識別されることがある輪に畳み込まれる傾向があるということである。拡張は、この誤差を抑制するのに役立つ。

#### 【0057】

その後、望ましい実施形態では、`imBlobSeg` イメージ内のセルが、8ポイント接続性ルールを用いて、検数される。図9は、フローチャート形式でこのプロセスを示す。いかなる数の隣接ピクセルもセルリストに追加され、基本パラメータが各々に対して決定される。これらのパラメータは、制限されるものではないが、インデックス、最大の  $x$  と  $y$  のピクセル値、ピクセルの総数、均一に閾値化されるセル領域に基づく  $x-y$  重心値、並びに閾値を超過する同じピクセルを用いるけれども、ソースイメージ内のピクセル値でそれらの位置に重みを加える加重重心、を含む。この重心値は、すべての後の計算に対して用いられる浮動小数点値である。重心値がマスク内の0でない領域にある場合（マスクに追加された各々は、バブルのために追加されたものが、プロブのために追加されたものと区別されるように、異なる「識別子」でそれらのピクセルに標識付けがなされていることを思い出すこと）、そのセルはセルリストから削除される。`SMPProcessImages` の中でなされる計算の最後の部分は、前述の要素（汚れ、バブル、及びフィルタ・アーティファクト）の各々のために見えなくさせられるイメージの百分率を決定するマスク・イメージのヒストグラムである。またイメージがマスクされたパラメータの全合計が計算される。これは、重要な部分がマスクされる場合に、毛細管の容積を再計算できるようにする。



## 【0058】

上で説明されたように、MLSCシステムはまた、MLSC器具の操作のためのパラメータ、例えば走査速度、フィルタ帯域幅値などを臨床プロトコル・データベースに格納する。SurroImageシステムを備えたMLSC器具の操作パラメータを、見事に調整する能力によって、各分析ができる限り最も効率的で最も敏感な方法で、実行される

### セル分析及びlsm出力

望ましい実施形態で、SurroImageシステム内の大多数のセル分析及びファイル出力は、WriteLsmFileのルーチン内で生じる。このルーチンの目的は、任意のチャンネルで検知されたすべてのセルイベントについてのテキストベースのリストファイルを出力することである。さらに、\*.LSMファイルのヘッダ部分は、全体的なセル統計値（各チャンネルに検知されたセルの数、及び最小サイズと最大サイズ）だけでなく、イメージ統計値（ベースライン・レベルで測定された雑音レベル、平均、メジアン値、及び標準偏差統計値、バブル及びプロブのためにマスクされたイメージの百分率、並びにイメージ作成日）を保持する。その所定のチャンネル用の検知閾値を超過する「プロブ」を1本のチャンネルが持っていたとしても、セル特性情報がすべてのチャンネルに対して出力される。例えば、1つの「プロブ」がチャンネル1に検知され、そのプロブが（ $x=22$ 、 $y=2342$ 、3）という加重重心値を持っていたならば、 $7 \times 7$ 核の中心は（22、2342）となり、どのチャンネルが閾値を超過したセルを実際に持っていたかにかかわらず、その $7 \times 7$ アレイ上で計算されるセル統計値が、すべてのチャンネル・イメージにおいて決定される。各チャンネルのこのように統合された分析が、各セルに対するすべての蛍光データの収集を保証するので、MLSCシステムの精度を非常に向上させる。このようにして、例えば検知された分子が非常に低濃度であった場合でも、意味ある情報を供給する非常に弱い蛍光性の信号は無視されない。2本のチャンネル走査用の\*.LSMファイルの一部の例が、テーブル1で示される。テーブル1内の例は、2つの独立したセルイベント用のセルデータを一覧にする。この特定の例において、パラメータ・イベントソースで分かるように、第1のセルが両方のチャンネルで検知され

た(1=CH0、2=CH1、4=CH2等々で、多重チャンネル検出がその値の合計によって示されることに注目すること)。しかしながら、第2のセルは、チャンネル0でのみ検知されたが、それでもパラメータは、チャンネル1の同じ位置に対して計算された。そのことはこの例からは明白ではないけれども、\*、LSM内のデータ出力がy-重心値によって完全に分類される。個々のチャンネルセルリストからの望ましい実施形態の中で、このデータがどのようにして生成されているかについての説明が続く。

#### 【0059】

そのルーチンは、各チャンネル内のセルリストの分類により始まる。「FindCell」ルーチンが、y方角へ「少しずつ移動する」ことによって、それが最初に見つけるすべてのセルペリメータをセルリストに添付するので、それはy-重心値によって必ずしも並び替える必要はない。したがって、バブルの並び替えが、このリストを生成するために用いられる(少ない数の再配列を行う必要がある場合に、バブルの並び替えが最良のソート・アルゴリズムである)。

#### 【0060】

次のステップは、チャンネル内のセルを一緒にし、y-重心によって並べ替えた汎用セルリストを作成することである。このルーチンの詳細は、以下のとおりである。処理されるべき次の利用可能なセル向けのインデックスは、CellFirstAvailIndex [チャンネル] と呼ばれ、各チャンネルに対して作成される。そのルーチンは、まだ印字されていない最低のy-重心値を備えたセルを見つけるために、チャンネル上をループする。その後、このセルインデックス、及びその対応するチャンネル番号が、一時的な設定の変数に保管される。リストであるCellPrintListIndex [ChannelsMax] は、これまで見つけられたセルのSameCellRadius内にその重心がある、別のチャンネル内のセルのインデックスを含めて、作成される。このリストのnChanエレメントを満たすために、そのルーチンはすべてのチャンネル内のセルをループする。しかしながら、別のチャンネル内のセルが、分析済みであるという「マーク」を既に付けられていた場合、それは読み飛ばして、その指定されたチャンネル内の残りのセルへ移動する。(このループに入ると、ソース

セルインデックスは、CellPrintListIndex[source\_channel] エlementに最初に追加される（つまり分析される「予定である」というマークが付けられる）ことに注意すること）。その重心が、元のセルからのSameCellRadius距離未満であるいかなるセルも、CellPrintListIndexアレイにそのインデックスが追加される。

#### 【0061】

いったん単一のセルイベントが、関連するチャンネルに適合すると、テキストベースの、LSMファイルに出力される準備が整う。このサブルーチンPrintCell() は、WriteLsmFile() ルーチンからコールされ、2つの引数、セルチャンネル・リストへのインデックス、及び現在のセルイベント・カウントを保持するCellPrintListIndexアレイを得る。そのルーチンはすべてのチャンネルを通してループし、CellPrintListIndexアレイ中でインデックスを付けられたセルの重心値にアクセスする。その後、ルーチンは、数値が求められようとしている特定のセルに対して、チャンネル間のx及びyにおける平均重心値を計算する。その結果はX、Yにおいて最も近い全ピクセルに丸められ、X、Yに関して中心にある7 x 7ピクセル領域内のセルパラメータを計算するAnalyzeCell() と呼ばれる別のルーチンをコールするために用いられる。このルーチンはチャンネル番号を通じてループ内でコールされる。セル構造AnalyzeCell() が満たすC++は、以下のとおりである。

#### 【0062】

#### 【表1】

```
typedef struct
{
    double          x,      y,
                    Area,
                    TotalFlux,
                    WeightedFlux,
                    Diameter,
                    Ellipticity,
                    Brightest;

    int              Printed; /* TRUE if printed already */
} CELLINFO;
```

### 【0063】

AnalyzeCell () は、imBlobSrc イメージへのポインタを得て、セルの X、Y 位置へそのポインタを再配置することにより始まる。X、Y 位置及び呼出しチャンネル番号以外に、AnalyzeCell () に渡されるパラメータのうちの 1 つは、この特定チャンネルが「ソース」チャンネルだったかどうか（つまり、セルがこのチャンネルで実際に検知されたかどうか）を示すブーリアン・フラグである。それがソース・チャンネルである場合、imBlobSrc イメージ内の 7 x 7 関心領域 (ROI) で見つけられた最大値の位置が、返される。これが核の中央 X、Y 位置と一致しない場合、この特定チャンネルに対してグローバル・パラメータ nBlobsOffsetFromPeak が増加させられる。このようにして、中央セル位置を判定するために使用される方法が評価される。さらに、重複を明瞭にする手段として、セル構造それ自身にこのパラメータを追加することができる。

### 【0064】

AnalyzeCell () をコールしたチャンネル内で、セルが検知されよ

うが検知されまいが、加重フラックスは、`imBlobSrc` イメージ内の  $X$ 、 $Y$  位置で単にピクセル値を評価することにより計算される。このピクセル値は、下のテーブル2で与えられる定義済みの  $7 \times 7$  核によって加重される、 $7 \times 7$  領域内のすべてのソースイメージ・ピクセル値の加重合計を表す。

#### 【0065】

別の実施形態では、`AnalyzeCell()` 内で数値が求められる他のパラメータは、制限されるものではないが、全フラックス、楕円率、及び平均直径を含む。全フラックスと平均直径は、別の機能コール `ComputeMeanRadius()` によって、数値が求められる。図10はこの機能コールを、フローチャート形式で示す。`ComputeMeanRadius()` は平均直径を計算するだけでなく、全フラックスがメジアンを差し引いた同じイメージ `hImbgnd` から計算されるので、このルーチンにも含まれる。`hImbgnd` を引き出すために、 $15 \times 15$  ピクセル・メジアン・フィルタがソースイメージに適用され、その結果がソースイメージから減算されたことを思い起こすこと。平均直径を決定するために、重心値が最初に計算される（注釈：この重心は、そのチャンネル用の閾値を超過するピクセルから計算された以前の重心と対比して、 $7 \times 7$  正方形内のピクセルから計算されるので、セルの中心を決定するために計算された重心値とは異なる）。そうして数学的には次の式によって、示されるように、各ピクセルの重心からの距離は、ピクセル値に対して加重される。

#### 【0066】

【数1】

$$D = 2 \cdot \frac{\sum_{n=1}^N P_{x_n, y_n} \sqrt{(C_x - x_n)^2 + (C_y - y_n)^2}}{\sum_{n=1}^N P_{x_n, y_n}} \quad (1)$$

#### 【0067】

ただし、重心値  $C_x$  及び  $C_y$  は、次式により与えられる。

#### 【0068】

【数2】

$$C_x = \frac{\sum_{n=1}^N x_n P_{x_n, y_n}}{\sum_{n=1}^N P_{x_n, y_n}} \quad \text{and} \quad C_y = \frac{\sum_{n=1}^N y_n P_{x_n, y_n}}{\sum_{n=1}^N P_{x_n, y_n}}, \quad (2)$$

【0069】

$P_{x_n, y_n}$ は位置  $x, y$  でのピクセルの値であり、 $N$ は  $7 \times 7$  核に対して49である。

小さな微粒子の直径を計算するためのこのモーメント法のアルゴリズムは、2次元のガウス・フィット・ルーチン上でより良い性能を提供することが発見された。ガウス・フィット・ルーチンは、図11に示されるように、低輝度のセルに対する実際の直径を小さく見積もる傾向がある。この偏向は、モーメント法のアルゴリズムで発見されたが、非常に少ししか公言されていない。

【0070】

全フラックスは、方程式(1)及び(2)の分母によって簡単に与えられる。全フラックスがゼロ以下である場合(それはバックグラウンドから差し引かれたイメージ中で起こることがある)、合計はオーバーフローを防ぐために値1.0に指定され、平均直径は0に設定される。

【0071】

`PrintCell()` ルーチンで数値が与えられる他の2つのセルパラメータは、チャンネル間の比率及び相関の値を含む。比率(テーブル1の例を参照)は、次式により与えられる。

【0072】

【数3】

$$R_{m/n} = \frac{Wtd.Flux_m}{Wtd.Flux_n}, \quad \text{where } m > n. \quad (3)$$

【0073】

ピアソンの相関、 $\rho_{n,n}$  係数は次式により計算される。

【0074】

【数4】

$$\rho_{m,n} = \frac{\sum_{k=1}^N (P_{x_n, y_n}^{(m)} - \bar{P}^{(m)})(P_{x_n, y_n}^{(n)} - \bar{P}^{(n)})}{(N-1)S_m S_n}, \quad (4)$$

【0075】

ここで  $S_m$  及び  $S_n$  は、それぞれチャンネル  $m$  及び  $n$  におけるソースイメージ (  $\text{imSrc}$  ) ピクセル値の標準偏差であり、 $\bar{P}$  は平均ピクセル値を表す。各セルがチャンネルを横切ってグループ化するように、これらのセルパラメータの各々は、シーケンシャルな方式で、\*、LSMファイルに書き込まれる。

【0076】

`WriteLSMFile()` ルーチンは、`printCell()` 及びサブルーチン `AnalyzeCell()` をコールするたびに、すべてのセルを一定の順序に配列する。セル数の合計は検数され、\*、LSMファイルのヘッダ部分に書き込まれる。その後、ファイルが閉じられ、プログラムは終了する。

【0077】

ここで記述される `SurroImage` システムは、レーザ・スキャニング・サイトメトリのコンテキストにおいて微粒子検出を行う従来技術システム上の実質的な進歩である。1つのそのような従来技術システムは、その全体がここに参考文献として組み入れられる、米国特許第5,556,764号 ('764特許) に記述されている。'764特許に記述されたシステムは、まず第1に個々のチャンネルからのイメージを合計し、そして次に、その結果生じる合成イメージ上の粒子を実行するが、'764システムは、いかなるプロブとバブルのマスキングも実行しない。さらに、'764システムは、例えば、特定の粒径範囲内のセルを検知するといったように、分析の対象である特定のタイプのセルに対し、非常に選択的となるように設計されている。これとは対照的に、本システムはそれほど限定的でなく、このようにもっと様々なタイプのセルを検知する。ここで記述されたプロブ及びバブルマスキング技術によって結び付けられた別々のチャ

ンネル分析によって、Surro Imageは、'764システムより多くの本当のセルを、正確に識別することができ、かつそこからデータを収集することができる。従って、本システムは従来の技術システムより正確で、かつより感度がよい。

#### 【0078】

Surro Imageシステムの別の利点は、セル会合分子の蛍光について種々の形態構造、及び／又は異なるパターンあるいは輝度を備えた様々な異なるセルの検出に対して、容易に最適化されることができるということである。さらに、Surro Imageシステムは、セル以外の微粒子の検出に対して速やかに最適化されることができる。例えば、本発明のいくつかの実施形態では、Surro Imageシステムは毛細管内のマイクロビーズを検知するために用いられ、そのマイクロビーズは血液内に存在する特定の試薬に結び付く。Surro Imageシステムとは対照的に、従来の技術システムは特定のセルだけを検知することができ、重要なオペレータの介入なしでは、他の構造を検知するための型の変更ができない。たたみこみ核の構造のようなSurro Imageシステムの個々のサブルーチンのパラメータは、これらの微粒子の検出を最適化するために速やかに変更されることができる。これらのパラメータは臨床プロトコル・データベースに格納されることができる（以下を参照）。したがって、Surro Imageシステムは、MLSCシステムの柔軟性を増大させ、感度において妥協することなく種々の分析を実行することができる。

#### 情報処理システムのアーキテクチャ

本発明は、多くの重要な機能を実行する斬新な情報処理システム・アーキテクチャを含む。システムの心臓部は、マルチパラメータ分析を設計し、測定計測器を制御し、イメージ及びデータ分析を実行し、並びに結果をアーカイブするために必要とされる情報のすべてを統合するために用いられる関連データベースである。システムは、別々の機能を実行する多くの連結されたモジュールを含む。図11は、このシステムが望ましい実施形態の中で作用する方法についてフローチャートで表現したものを示す。手短かに言えば、計器制御ソフトウェアは、Surro Scanハードウェア（MLSC器具）を制御し、そうすることで、サン



プルを走査し、生の画像ファイル（、S M 1 ファイル）を作成する。その後、S M 1 ファイルは、（上の）S u r r o I m a g e 画像分析ソフトウェアによって処理され、増強される。このモジュールは各イメージを増強し、各イメージ内の各セル（あるいはいくつかのアプリケーション内の蛍光ビード）の位置及びサイズを決定し、次に、各チャンネル内での各セル（あるいはビード）の蛍光輝度を計算する。その結果生じる S u r r o I m a g e データは、テキストファイル（、L S M ファイル）として格納され、次に、F C S 変換ソフトウェア（F C S C o n v e r s i o n S o f t w a r e）によって、業界標準の、F C S フォーマットに変換されるか、又はその後の分析のための適切な他のファイル形式に変換されることができる。測定器制御ソフトウェア、画像分析ソフトウェア及びF C S 変換ソフトウェアはすべて、臨床プロトコルの実行の中で用いられる各タイプの分析のためのパラメータを格納する臨床プロトコル・データベースによって制御される。そのようなパラメータは、制限されるものではないが、M L S C 器具の走査速度、M L S C 器具の中で用いられるフィルタ帯域幅の値、及び S u r r o I m a g e システムの中で用いられる核構造を含む。その後、その形式、例えば、F C S 及び、L S M のファイル内のデータは、例えば市販の F I o w J o ソフトウェアを用いて、データをさらに処理するために、サーバに送出されることができる。またそのデータは、アーカイブするため、及び第3次メディアに周期的に送出するための、実験データファイル・サーバに送信され、またオラクルデータベースのような中央のデータベースにも送信される。中央のデータベースは、制限されるものではないが、臨床プロトコル・データベースの整合性を維持するため、器具結果、ファイル名、校正情報のための中央の貯蔵所として、（M L S C システムを通して得られようが、又は従来の E L I S A 分析を通して得られようが）セルの分析測定値及び可溶性要素の測定値を格納するため、並びに臨床アンケート情報を維持するために、使用される。

#### 【0079】

望ましい実施形態では、S u r r o S c a n 情報処理システムが、（適切な関連データベース・スキーマのこれまでの設計、及び校正された器具が使用可能であること、を仮定して）臨床研究のための次の方法で用いられる。まず第1に、

ユーザは、患者の数及び識別情報、患者当たりのサンプル数などのような情報を含む、臨床研究プロトコルを定義する。臨床研究は、何十から何百人もの患者を関与させ、何週間から何ヶ月も続く。またユーザは、分析プロトコルを定義し、それが各特定患者のサンプルで実行される分析の各々を詳細に定義する。各分析は、制限されるものではないが、使用される蛍光体、ターゲット分子、希釈、及び蛍光補正パラメータを含めて、試薬の各々に対する詳細な識別子及び説明を含む。サンプル調製方法及びサンプル希釈もまた含まれる。またプロトコルは、SurroScan器具及びデータ分析ソフトウェアを自動的に制御するのに必要な情報を含む。患者サンプルが（データベース制御の下で自動化されることができ）各分析に対して処理され、SurroScan上の測定カートリッジに取り付けられた後、ユーザが、スキャナ・ソフトウェア（その後、それは詳細な走査パラメータ例えばを決定するためにデータベースに質問する）にプロトコルID及びサンプルIDパラメータを入れ、そうして、そのソフトウェアが、詳細な走査パラメータ、例えば、走査速度、フィルタ帯域幅設定値、ステージ移動速度などを決定するために、データベースに質問する。走査が完了した後、器具は適切な分析パラメータを学習するために再びデータベースに質問し、そうしてFCS出力ファイルを生成して、SurroImage及びSurroFCSのソフトウェア・モジュールでもって正しいタイプの分析を自動的に実行する。FCS出力ファイルは、市販のFCS分析ソフトウェアを用いて、さらに分析される。その後、各患者サンプルに対するFCS出力データの要約が、FCSソフトウェアによって生成され、リレーショナル・データベース内のストレージを有効にするためにさらに処理される。その後、測定結果及び患者の臨床情報は、対象となる生物学的マーカを示すパターン及び相関を識別するための様々な統計的手法及びビジュアル化の手法でさらに処理される。サンプル及び分析情報が、生のイメージから、関連データベースへのリスト・モード・フォーマットまで、分析の全体に渡って、そのデータと関連する。

#### 【0080】

また本発明は、増強されたデータを如実に表示するためにイメージ・システムの使用を意図する。このシステムは、SurroViewと名付けられるが、S

urroImageソフトウェアによって識別された個々のセルを表示し、そのイメージ内の真実のセルを他のセルの形をした擬似信号と区別するために、各識別されるセルの周りに、1つのボックスを置くことができる。SurroViewソフトウェアは特に、すばやく様々なタイプのシステム障害モードを診断するのに役立つ。SurroScan器具の通常操作中に、セルのそのようなイメージをオペレータが常に見ている必要はないことが指摘されるべきである。

テーブル1：リスト・モード出力の例。データは2チャンネル走査に対応する。

【0081】

【表2】

| セル<br>No. | チャンネル:0 |    | 全流束  | 加重<br>流束 | セル<br>直径 | セル<br>精円率 | 発輝度<br>ピクセル | 相関<br>0-1 | 比率<br>1/0 | 相関<br>0-2 | 比率<br>2/0 |
|-----------|---------|----|------|----------|----------|-----------|-------------|-----------|-----------|-----------|-----------|
|           | X       | Y  |      |          |          |           |             |           |           |           |           |
| 1         | 191     | 23 | 4141 | 427      | 3.2      | 0.90      | 3798        | 0.91      | 0.56      | 0.48      | 0.08      |
| 2         | 196     | 26 | 2282 | 501      | 1.3      | 0.95      | 4124        | 0.917     | 0.36      | 0.71      | 0.11      |
| 3...      |         |    |      |          |          |           |             |           |           |           |           |

| セル<br>No. | チャンネル:1 |    | 全流束  | 加重<br>流束 | セル<br>直径 | セル<br>精円率 | 発輝度<br>ピクセル | 相関<br>1-2 | 比率<br>2/1 | イベント・<br>ソース |
|-----------|---------|----|------|----------|----------|-----------|-------------|-----------|-----------|--------------|
|           | X       | Y  |      |          |          |           |             |           |           |              |
| 1         | 191     | 23 | 1824 | 241      | 2.5      | 0.88      | 1962        | 0.41      | 0.14      | 3            |
| 2         | 196     | 26 | 1294 | 181      | 1.9      | 0.93      | 2027        | 0.77      | 0.29      | 1            |
| 3...      |         |    |      |          |          |           |             |           |           |              |

【0082】

テーブル2：フィルタ補正されたイメージimBlobSrcを作成するために使用されるたたみこみ核。imBlobSrcは、セル検出及びセルの加重フラックス評価の両方に用いられる。

【0083】

【表3】

|       |       |       |       |       |       |       |
|-------|-------|-------|-------|-------|-------|-------|
| -3.54 | -3.54 | -3.54 | -3.54 | -3.54 | -3.54 | -3.54 |
| -3.54 | 2.00  | 2.00  | 3.00  | 2.00  | 2.00  | -3.54 |
| -3.54 | 2.00  | 4.00  | 6.00  | 4.00  | 2.00  | -3.54 |
| -3.54 | 3.00  | 6.00  | 9.00  | 6.00  | 3.00  | -3.54 |
| -3.54 | 2.00  | 4.00  | 6.00  | 4.00  | 2.00  | -3.54 |
| -3.54 | 2.00  | 2.00  | 3.00  | 2.00  | 2.00  | -3.54 |
| -3.54 | -3.54 | -3.54 | -3.54 | -3.54 | -3.54 | -3.54 |

【図面の簡単な説明】

【図1】 本発明の1つの望ましい実施形態におけるMLSC器具の光アーキテクチャを示す。

【図2】 図2Aは切り替え可能なフィルタ・スキームの部分的な回路図である。

図2Bは切り替え可能なフィルタ・スキームの部分的な回路図である。

【図3】 SurroImageプロセスのフローチャートである。

【図4】 本発明によって意図される1つのファイル・ストレージの実施形態を図式的に示す。Nチャンネルのデータが、拡張子\*.sm1で指定されるバイナリ・ファイルにインタリーブ・フォーマットで格納される。様々なデータフォーマットが可能になるように、ヘッダが選定される。

【図5】 ベースライン分析プロセスのフローチャートである。

【図6】 セル検出プロセスのフローチャートである。

【図7】 ノイズ分析プロセスを示す。

【図8】 マスク生成プロセスのフローチャートである。

【図9】 セルを見つけるための8ポイント接続性ルールを図示するフローチャートである。

【図10】 本発明によって意図される、可能ないくつかのタイプのセル分析を示す。

【図11】 ガウス・フィット・アルゴリズムを、直径モーメント計算と比較したプロットである。イメージについて、各ポイントが、250カウントに等しいRMSノイズで1000個の粒子（セル）の擬似イメージの中から検出された微粒子の平均直径値である。

【図12】 SurroScanシステムの情報処理システム構成のフローチャートである。

【図1】





Figure 1



【例 2 A】

(52)


特表2003-505707




Page 508 of 630




【図3】




【図4】




【図5】



【図6】



【図7】



1行ノイズポイントCNT要素へ1行ノイズを分割する

**DIVIDE IMAGE ROWS INTO NOISE POINT CNT SECTIONS**

1行ノイズの左側に7x7核を中央に配置する

**CENTER 7x7 KERNEL AT "LEFT" SIDE OF IMAGE**

**FIND MAX AND MIN IN THE 7x7 KERNEL**

7x7核へ最大値と最小値を見つめる

**ADD MAX/MIN VALUE TO HISTOGRAM**

最大-最小値をヒストグラムに追加する

**MOVE ONE PIXEL TO THE RIGHT**

ヒストグラム7ピクセルを右側に移動させる

**REPEAT ABOVE (250 POINTS) UNTIL YOU REACH THE "RIGHT" SIDE OF THE IMAGE**

1行ノイズの右側に達するまで (1250ポイント) 繰り返す

**SKIP A GIVEN NUMBER OF ROWS**

所与の数の行をスキップする

**SMOOTH (BOXCAR FILTER) AND FIND MAX OF HISTOGRAM WITHIN THE EACH NOISE POINT CNT SECTION**

平滑化し (ボックスカー・フィルタ) を用いて各ノイズポイント領域内のヒストグラムの最大値を見つめる


**ADD TO NOISE POINT CNT ELEMENT NOISE ARRAY**

1行ノイズポイントCNT要素1行ノイズへ追加する


**NOISE ARRAY IS USED TO DETERMINE THRESHOLD IN CELL DETECTION ALGORITHM**

1行ノイズはセル検出アルゴリズムに於ける閾値を決定するために使用される

【図8】



【図9】



【図10】




Figure 10



【図10-1】




Figure 10 (cont.)






Figure 12

【図12-1】




Figure 12 (cont.)

## 【国際調査報告】

## INTERNATIONAL SEARCH REPORT

International application No.  
PCT/US99/11133

## A. CLASSIFICATION OF SUBJECT MATTER

IPC(7) : G06K 9/00

US CL : 382/128; 250/461.1; 356/300; 435/6; 600/311, 317, 319

According to International Patent Classification (IPC) or to both national classification and IPC

## B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

U.S. : 382/128; 250/461.1; 356/300; 435/6; 600/311, 317, 319

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched  
None

Electronic data base consulted during the international search (name of data base and, where practicable, search terms used)

East, IEEE  
search terms: fluorescent, pixel, diagnostic, dichroic, fiber, wavelength, channel

## C. DOCUMENTS CONSIDERED TO BE RELEVANT

| Category* | Citation of document, with indication, where appropriate, of the relevant passages                                                               | Relevant to claim No. |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------|
| Y         | US 5,456,252 A (VARI et al.) 10 October 1995, fig. 13, elements 50, 52; col. 5, lines 23-55; col. 7, lines 45-65,                                | 1-6                   |
| Y         | US 4,786,813 A (SVANBERG et al.) 22 November 1988, abstract, lines 1-12; col. 3, lines 5-65.                                                     | 1-6                   |
| Y         | US 5,127,730 A (BRELJE et al.) 07 July 1992, fig. 4, element 401; fig. 5, elements 500, 501, 507, 509; col. 2, lines 30-55; col. 3, lines 48-60. | 1-6                   |
| A         | US 5,377,003 A (LEWIS et al.) 27 December 1994, col. 8, lines 55-68.                                                                             | 1-6                   |
| Y         | US 5,741,411 A (YEUNG et al.) 21 April 1998, col. 10, lines 12-65.                                                                               | 1-6                   |

☐ Further documents are listed in the continuation of Box C. ☐ See patent family annex.

|                                                                                                                                                                         |     |                                                                                                                                                                                                                                               |
|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| * Special categories of cited documents:                                                                                                                                | * J | later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention.                                              |
| "A" document defining the general state of the art which is not considered to be of particular relevance                                                                | * X | document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone.                                                                     |
| "B" earlier document published on or after the international filing date                                                                                                | * Y | document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, each combination being obvious to a person skilled in the art. |
| "C" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) | * g | document number of the same patent family.                                                                                                                                                                                                    |
| "D" document referring to an oral disclosure, use, exhibition or other means                                                                                            |     |                                                                                                                                                                                                                                               |
| "P" document published prior to the international filing date but later than the priority date claimed                                                                  |     |                                                                                                                                                                                                                                               |

Date of the actual completion of the international search

23 AUGUST 2000

Date of mailing of the international search report

02 NOV 2000

Name and mailing address of the ISA/US  
Commissioner of Patents and Trademarks  
Box PCT  
Washington, D.C. 20231

Facsimile No. (703) 305-3230

Authorized officer

AMÉLIA AU

Telephone No. (703) 308-7728

Form PCT/ISA/210 (second sheet) (July 1998)\*

## フロントページの続き

(81)指定国 EP(AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OA(BE, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG), AP(GH, GM, KE, LS, MW, SD, SL, SZ, TZ, UG, ZW), EA(AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CR, CU, CZ, DE, DK, DM, DZ, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, UZ, VN, YU, ZA, ZW

(72)発明者 チャン, チンフア

アメリカ合衆国カリフォルニア州94539,  
フレモント, プレイリー・ドッグ・レーン  
93

(72)発明者 ノートン, スコット

アメリカ合衆国カリフォルニア州94085,  
サニーヴェイル, エスカロン・アベニュー  
100, アパートメント ビー2014

(72)発明者 ウィンクラー, ジェイムズ・エル

アメリカ合衆国カリフォルニア州94086,  
サニーヴェイル, サウス・フェアオークス  
・アベニュー 655, ナンバーディー  
313

(72)発明者 カンター, アーロン・ビー

アメリカ合衆国カリフォルニア州94070,  
サン・カルロス, ラバース・レーン 30

(72)発明者 リー, バイロン

アメリカ合衆国カリフォルニア州95111,  
サン・ホセ, アンブラー・コート 3971

(72)発明者 ツル, シャロム

アメリカ合衆国カリフォルニア州94040,  
マウンテン・ビュー, エル・モンテ・アベ  
ニュー 1076

F ターム(参考) 2G043 AA01 BA16 CA03 DA02 DA06  
EA01 FA01 FA02 GA25 GB21  
HA01 HA02 JA02 KA02 KA05  
KA09 LA02 NA01 NA02 NA05  
2G045 AA25 CA25 CB01 CB03 CB04  
CB07 CB08 CB11 CB12 CB14  
DA30 DA36 DA60 FA12 FB07  
FB12 JA01

## Electronic Acknowledgement Receipt

|                                             |                               |
|---------------------------------------------|-------------------------------|
| <b>EFS ID:</b>                              | 32869076                      |
| <b>Application Number:</b>                  | 15638461                      |
| <b>International Application Number:</b>    |                               |
| <b>Confirmation Number:</b>                 | 9847                          |
| <b>Title of Invention:</b>                  | FLOW CYTOMETER                |
| <b>First Named Inventor/Applicant Name:</b> | Yong Qin Chen                 |
| <b>Customer Number:</b>                     | 32425                         |
| <b>Filer:</b>                               | Mark G Tison/Hannah Wimberley |
| <b>Filer Authorized By:</b>                 | Mark G Tison                  |
| <b>Attorney Docket Number:</b>              | BECC.P0002US.CIP.C1           |
| <b>Receipt Date:</b>                        | 12-JUN-2018                   |
| <b>Filing Date:</b>                         | 30-JUN-2017                   |
| <b>Time Stamp:</b>                          | 10:27:57                      |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a)   |

### Payment information:

|                        |    |
|------------------------|----|
| Submitted with Payment | no |
|------------------------|----|

### File Listing:

| Document Number | Document Description | File Name                  | File Size(Bytes)/<br>Message Digest      | Multi Part /.zip | Pages (if appl.) |
|-----------------|----------------------|----------------------------|------------------------------------------|------------------|------------------|
| 1               |                      | BECCP0002USCIPC1_SIDS1.pdf | 191346                                   | yes              | 4                |
|                 |                      |                            | 305cea924fbf232ff55651cffdd811c5f48bd2fd |                  |                  |



|              | Multipart Description/PDF files in .zip description |                   |                                          |     |    |
|--------------|-----------------------------------------------------|-------------------|------------------------------------------|-----|----|
|              | Document Description                                |                   | Start                                    | End |    |
|              | Transmittal Letter                                  |                   | 1                                        | 2   |    |
|              | Information Disclosure Statement (IDS) Form (SB08)  |                   | 3                                        | 4   |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 2            | Foreign Reference                                   | JP2004500572A.pdf | 2123221                                  | no  | 74 |
|              |                                                     |                   | 35229ac4f78f9f728f708fda12d49981a3887907 |     |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 3            | Foreign Reference                                   | JP2008534960A.pdf | 645204                                   | no  | 14 |
|              |                                                     |                   | 4463356756a3e3e424293398d87a3279df95bad  |     |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 4            | Foreign Reference                                   | JP2010085194A.pdf | 735591                                   | no  | 15 |
|              |                                                     |                   | 1b74d8b010b8728146921d13e4be1b1347c32066 |     |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 5            | Foreign Reference                                   | JPH03197641A.pdf  | 584568                                   | no  | 7  |
|              |                                                     |                   | cb23392fe2b1af47cb6ad036b5a8734e6496fd06 |     |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 6            | Foreign Reference                                   | JPH05119035A.pdf  | 425420                                   | no  | 8  |
|              |                                                     |                   | d25489871e76e6e7d32c7718b8929bb5edd9807a |     |    |
| Warnings:    |                                                     |                   |                                          |     |    |
| Information: |                                                     |                   |                                          |     |    |
| 7            | Foreign Reference                                   | JPS55144226A.pdf  | 323221                                   | no  | 5  |
|              |                                                     |                   | 46beddc30661c57bf241787792cb487ecf46be33 |     |    |

Page 525 of 630

Warnings:

|                              |                                             |                    |                                           |    |     |
|------------------------------|---------------------------------------------|--------------------|-------------------------------------------|----|-----|
| Information:                 |                                             |                    |                                           |    |     |
| 8                            | Foreign Reference                           | JPS61184427A.pdf   | 429263                                    | no | 6   |
|                              |                                             |                    | 970375983a2dc649ecce9718c35a62522d3452cf  |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| 9                            | Foreign Reference                           | WO2013181453A2.pdf | 4603362                                   | no | 103 |
|                              |                                             |                    | 55a68e0c1e56fea76532861b218ae2082b147e97  |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| 10                           | Other Reference-Patent/App/Search documents | OA_JP.pdf          | 455590                                    | no | 4   |
|                              |                                             |                    | 15913b30b6d1324dcb7c241e9993dba96a72be7d  |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| 11                           | Other Reference-Patent/App/Search documents | OA_CN.pdf          | 2804285                                   | no | 8   |
|                              |                                             |                    | 25b2e4d4dc98306c39aa3a41e43a2e5abb65c7ce  |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| 12                           | Foreign Reference                           | JP2003505707.pdf   | 19095960                                  | no | 70  |
|                              |                                             |                    | e967c1fbe18e7da538c3569fa9f958f82815ee02e |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| 13                           | Other Reference-Patent/App/Search documents | OA_JPD1.pdf        | 938642                                    | no | 20  |
|                              |                                             |                    | 9c4f86dd8140093eeff2c437825e06096d841359  |    |     |
| Warnings:                    |                                             |                    |                                           |    |     |
| Information:                 |                                             |                    |                                           |    |     |
| Total Files Size (in bytes): |                                             |                    | 33355673                                  |    |     |

**This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.**

**New Applications Under 35 U.S.C. 111**

**If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.**

**National Stage of an International Application under 35 U.S.C. 371**

**If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.**

**New International Application Filed with the USPTO as a Receiving Office**

**If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.**

**PATENT**

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

In re Application of:  
IRIS INTERNATIONAL, INC.

Serial No.: 15/638,461

Filed: June 30, 2017

For: FLOW CYTOMETER

Group Art Unit: 2884

Examiner: Mindy D. Vu

Atty. Dkt. No.: BECC.P0002US.CIP.C1

Confirmation No.: 9847

Commissioner for Patents  
P.O. Box 1450  
Alexandria, Virginia 22313-1450

**CERTIFICATE OF ELECTRONIC TRANSMISSION  
37 C.F.R. § 1.8**

I hereby certify that this correspondence is being electronically filed with the United States Patent and Trademark Office via EFS-Web on the date below:

June 12, 2018  
Date

/Mark G. Tison/  
Mark G. Tison

**SUPPLEMENTAL INFORMATION DISCLOSURE STATEMENT**

Commissioner:

In compliance with the duty of disclosure under 37 C.F.R. § 1.56, it is respectfully requested that this Supplemental Information Disclosure Statement be entered and the documents listed on attached Form PTO-1449 be considered by the Examiner and made of record. Copies of the listed documents required by 37 C.F.R. § 1.98(a)(2) are enclosed for the convenience of the Examiner.

In accordance with 37 C.F.R §§ 1.97(g), (h), this Supplemental Information Disclosure Statement is not to be construed as a representation that a search has been made, and is not to be construed to be an admission that the information cited is, or is considered to be, material to patentability as defined in 37 C.F.R. § 1.56(b).

The present Supplemental Information Disclosure Statement is being filed prior to the receipt of a first Official Action reflecting an examination on the merits, and hence is believed to

be timely filed in accordance with 37 C.F.R. § 1.97(b). No fees are believed to be due in connection with the filing of this Supplemental Information Disclosure Statement, however, should any fees under 37 C.F.R. §§ 1.16 to 1.21 be deemed necessary for any reason relating to these materials, the Commissioner is authorized to deduct the appropriate fees from Norton Rose Fulbright US LLP Deposit Account No.: 50-1212/BECC.P0002US.CIP.C1.

Applicant respectfully requests that the listed documents be made of record in the present case.

Respectfully submitted,

/Mark G. Tison/

Mark G. Tison  
Reg. No. 65,985  
Attorney for Applicant

NORTON ROSE FULBRIGHT US LLP  
98 San Jacinto Blvd., Suite 1100  
Austin, TX 78701  
(512) 474-5201

Date: June 12, 2018



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NO.              | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|------------------------------|-------------|----------------------|---------------------|------------------|
| 15/638,461                   | 06/30/2017  | Yong Qin Chen        | BECC.P0002US.CIP.C1 | 9847             |
| 32425                        | 7590        | 06/29/2018           | EXAMINER            |                  |
| NORTON ROSE FULBRIGHT US LLP |             |                      | VU, MINDY D         |                  |
| 98 SAN JACINTO BOULEVARD     |             |                      | ART UNIT            |                  |
| SUITE 1100                   |             |                      | PAPER NUMBER        |                  |
| AUSTIN, TX 78701-4255        |             |                      | 2884                |                  |
|                              |             |                      | NOTIFICATION DATE   |                  |
|                              |             |                      | DELIVERY MODE       |                  |
|                              |             |                      | 06/29/2018          |                  |
|                              |             |                      | ELECTRONIC          |                  |

**Please find below and/or attached an Office communication concerning this application or proceeding.**

The time period for reply, if any, is set in the attached communication.

Notice of the Office communication was sent electronically on above-indicated "Notification Date" to the following e-mail address(es):

aoipdocket@nortonrosefulbright.com

|                              |                                      |                                       |                                                  |
|------------------------------|--------------------------------------|---------------------------------------|--------------------------------------------------|
| <b>Office Action Summary</b> | <b>Application No.</b><br>15/638,461 | <b>Applicant(s)</b><br>CHEN, YONG QIN |                                                  |
|                              | <b>Examiner</b><br>MINDY VU          | <b>Art Unit</b><br>2884               | <b>AIA (First Inventor to File) Status</b><br>No |

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address --**

### Period for Reply

A SHORTENED STATUTORY PERIOD FOR REPLY IS SET TO EXPIRE 3 MONTHS FROM THE MAILING DATE OF THIS COMMUNICATION.

- Extensions of time may be available under the provisions of 37 CFR 1.136(a). In no event, however, may a reply be timely filed after SIX (6) MONTHS from the mailing date of this communication.
  - If NO period for reply is specified above, the maximum statutory period will apply and will expire SIX (6) MONTHS from the mailing date of this communication.
  - Failure to reply within the set or extended period for reply will, by statute, cause the application to become ABANDONED (35 U.S.C. § 133).
- Any reply received by the Office later than three months after the mailing date of this communication, even if timely filed, may reduce any earned patent term adjustment. See 37 CFR 1.704(b).

### Status

- 1) ☐ Responsive to communication(s) filed on \_\_\_\_\_.  
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on \_\_\_\_\_.
- 2a) ☐ This action is **FINAL**.                      2b) ☒ This action is non-final.
- 3) ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on \_\_\_\_\_; the restriction requirement and election have been incorporated into this action.
- 4) ☐ Since this application is in condition for allowance except for formal matters, prosecution as to the merits is closed in accordance with the practice under *Ex parte Quayle*, 1935 C.D. 11, 453 O.G. 213.

### Disposition of Claims\*

- 5) ☒ Claim(s) 364-389 is/are pending in the application.  
5a) Of the above claim(s) \_\_\_\_\_ is/are withdrawn from consideration.
- 6) ☐ Claim(s) \_\_\_\_\_ is/are allowed.
- 7) ☒ Claim(s) 364-373, 376-380 and 382-389 is/are rejected.
- 8) ☒ Claim(s) 374, 375 and 381 is/are objected to.
- 9) ☐ Claim(s) \_\_\_\_\_ are subject to restriction and/or election requirement.

\* If any claims have been determined allowable, you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see [http://www.uspto.gov/patents/init\\_events/pph/index.jsp](http://www.uspto.gov/patents/init_events/pph/index.jsp) or send an inquiry to [PPHfeedback@uspto.gov](mailto:PPHfeedback@uspto.gov).

### Application Papers

- 10) ☐ The specification is objected to by the Examiner.
- 11) ☒ The drawing(s) filed on 6/30/17 is/are: a) ☒ accepted or b) ☐ objected to by the Examiner.  
Applicant may not request that any objection to the drawing(s) be held in abeyance. See 37 CFR 1.85(a).  
Replacement drawing sheet(s) including the correction is required if the drawing(s) is objected to. See 37 CFR 1.121(d).

### Priority under 35 U.S.C. § 119

- 12) ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

#### Certified copies:

- a) ☐ All    b) ☐ Some\*\*    c) ☐ None of the:
1. ☐ Certified copies of the priority documents have been received.
  2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_\_.
  3. ☐ Copies of the certified copies of the priority documents have been received in this National Stage application from the International Bureau (PCT Rule 17.2(a)).

\*\* See the attached detailed Office action for a list of the certified copies not received.

### Attachment(s)

- 1) ☒ Notice of References Cited (PTO-892)
- 2) ☒ Information Disclosure Statement(s) (PTO/SB/08a and/or PTO/SB/08b)  
Paper No(s)/Mail Date 8/2/17, 6/12/18.
- 3) ☐ Interview Summary (PTO-413)  
Paper No(s)/Mail Date. \_\_\_\_\_.
- 4) ☐ Other: \_\_\_\_\_.

### **DETAILED ACTION**

The present application is being examined under the pre-AIA first to invent provisions.

#### ***Information Disclosure Statement***

The examiner has considered information considered by the Office in the parent application(s) when examining this continuing application, and the application file reflects that fact. A list of the information need not be submitted in the continuing application unless applicant desires the information to be printed on the patent. MPEP § 609.

#### ***Claim Objections***

Claim 383 is objected to because of the following informalities: the word "and" in line 2 should probably be "an". Appropriate correction is required.

#### ***Claim Rejections - 35 USC § 112***

The following is a quotation of the first paragraph of 35 U.S.C. 112(a):

(a) IN GENERAL.—The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same, and shall set forth the best mode contemplated by the inventor or joint inventor of carrying out the invention.

The following is a quotation of the first paragraph of pre-AIA 35 U.S.C. 112:

The specification shall contain a written description of the invention, and of the manner and process of making and using it, in such full, clear, concise, and exact terms as to enable any person skilled in the art to which it pertains, or with which it is most nearly connected, to make and use the same, and shall set forth the best mode contemplated by the inventor of carrying out his invention.

Claim 368 rejected under 35 U.S.C. 112(a) or 35 U.S.C. 112 (pre-AIA), first paragraph, as failing to comply with the enablement requirement. The claim(s) contains



Art Unit: 2884

subject matter which was not described in the specification in such a way as to enable one skilled in the art to which it pertains, or with which it is most nearly connected, to make and/or use the invention. Claim 368 claims “**the optical relay is a concave-shaped dichroic filter**”, However, in the specification of the present application, it discloses the **optical relay is a concave mirror 907** and **dichroic filter 909** may be inserted in between the relay imaging concave mirror 907 and the second image near focusing lens 908 (para. 0411 of published application). As evidence from the specification, the dichroic filter is not an optical relay nor having a concave-shaped dichroic filter.

### ***Claim Rejections - 35 USC § 102***

The following is a quotation of the appropriate paragraphs of pre-AIA 35 U.S.C. 102 that form the basis for the rejections under this section made in this Office action:

A person shall be entitled to a patent unless –

(b) the invention was patented or described in a printed publication in this or a foreign country or in public use or on sale in this country, more than one year prior to the date of application for patent in the United States.

Claim(s) 364-366, 370-372, 376-380, 383 and 385-389 is/are rejected under pre-AIA 35 U.S.C. 102(b) as being anticipated by Heffelfinger et al. (US 2003/0044967).

With respect to claim 364, Heffelfinger discloses an optical module (abstract), the optical module comprising:

(a) a light source (beam combiner 18 combines first laser 12 and second laser 14 into illumination beam 24, see fig.1);

(b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a collimated beam [0039-0040]; and

(c) an optical relay (relay lens 42) arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay configured to project at least a portion of the collimated beam to a first focusing optical element (48), wherein the optical relay is one of a curved mirror and a refractive lens [0047, 0049].

With respect to claim 365, Heffelfinger discloses the light source is one of light passing through a pinhole [0061] and light emitted from a facet of a multimode optical fiber [0021, 0038].

With respect to claim 366, Heffelfinger discloses the first focusing optical element is configured to focus the collimated beam to a size smaller than 1 millimeter in diameter to a first semiconductor detector.

With respect to claim 370, Heffelfinger discloses a first optical filter arranged between the collimating optical element and the optical relay, the first optical filter configured to separate the collimated beam into a first branch and a second branch [0041].

With respect to claim 371, Heffelfinger discloses the collimated beam comprises light of a plurality of wavelengths, wherein the first optical filter is configured to reflect light of a first range of wavelengths to form the first branch of the collimated beam, wherein the first optical filter is configured to pass light of a second range of wavelengths to form the second branch of the collimated beam, wherein the first branch is directed to the optical relay (fig. 1 and its description).

With respect to claim 372, Heffelfinger discloses a second focusing optical element arranged to receive the second branch of the collimated beam, the second focusing optical element configured to focus the second branch of the collimated beam to a second semiconductor detector (fig. 1 and its description).

With respect to claims 376 and 377, Heffelfinger discloses an optical module (abstract), the optical module comprising:

- (a) a light source (12, see fig.4);
- (b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a collimated beam and a first image, wherein the collimated beam has a collimated distance [0039-0040, 0057]; and
- (c) an optical relay (relay lens 42, 46) arranged to receive the collimated beam, the optical relay configured to extend the collimated distance of the collimated beam, wherein the optical relay is one of a curved mirror and a refractive lens [0047, 0049].

With respect to claim 378, Heffelfinger discloses the optical relay projects a second image, wherein the second image and the first image are substantially the same size [0059-0061].

With respect to claim 379, Heffelfinger discloses wherein the optical relay projects a second image, wherein the collimated beam from the collimating optical element to the first image has substantially the same diameter as the collimated beam from the optical relay to the second image [0061].

With respect to claim 380, Heffelfinger discloses a first focusing optical element arranged to receive the collimated beam from the optical relay at the extended

collimated distance, the first focusing optical element configured to focus the extended collimated beam to a first semiconductor detector (fig. 4 and its description).

With respect to claim 383, Heffelfinger discloses an optical module (abstract), the optical module comprising:

- (a) a light source providing light that forms an object (12, see fig.4);
- (b) a collimating optical element arranged to receive light from the light source, the collimating optical element configured to project a first image of the object [0039-0040]; and
- (c) an optical relay (relay lens 42 and 46) arranged near the first image, the optical relay configured to receive light from the collimating optical element and to project a second image of the object; wherein the size of the first image is substantially the same as the size of the second image [0047, 0049, 0057-0061].

With respect to claim 385, Heffelfinger discloses the light source is an extended light source that forms the object, wherein the first image is a magnified image of the object [0042-0046].

With respect to claim 386, Heffelfinger discloses the light source is one of light passing through a pinhole [0057] and light emitted from a facet of a multimode optical fiber [0021, 0040].

With respect to claim 387, Heffelfinger discloses the collimating optical element has an effective size defined by its cross section, wherein the size of the first image is substantially the same as the effective size of the collimating optical element [0045, 0056].

With respect to claim 388, Heffelfinger discloses the first image is less than approximately 10 times the size of the object [0060].

With respect to claim 389, Heffelfinger discloses a first focusing optical element arranged near the second image, the first focusing optical element configured to focus the light from the optical relay to a size smaller than the object of the light source to a first semiconductor detector [0060-0061].

Claim(s) 364, 370, 376-378, 380 and 382-387 is/are rejected under pre-AIA 35 U.S.C. 102(b) as being anticipated by Oostman, Jr. et al. (US 2003/0044967).

With respect to claim 364, Oostman, Jr. discloses an optical module (abstract, fig. 5), the optical module comprising:

- (a) a light source (optical fiber 123, see fig.5);
- (b) a collimating optical element (collimating lens 145) arranged to receive light from the light source, the collimating optical element configured to project a collimated beam (col. 6 lines 40-44); and
- (c) an optical relay (dichroic mirror 151) arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay configured to project at least a portion of the collimated beam to a first focusing optical element (158), wherein the optical relay is one of a curved mirror and a refractive lens (col. 6 lines 40-50).

With respect to claim 370, Oostman, Jr. discloses a first optical filter (155) arranged between the collimating optical element (145) and the optical relay, the first

Art Unit: 2884

optical filter configured to separate the collimated beam into a first branch and a second branch (fig. 5).

With respect to claim 376, Oostman, Jr. discloses an optical module (abstract), the optical module comprising:

(a) a light source (123, see fig.5);

(b) a collimating optical element (145) arranged to receive light from the light source, the collimating optical element configured to project a collimated beam and a first image, wherein the collimated beam has a collimated distance (col. 6 lines 40-44); and

(c) an optical relay (dichroic mirror 151) arranged to receive the collimated beam, the optical relay configured to extend the collimated distance of the collimated beam (fig. 5 and its description).

With respect to claim 378, Oostman, Jr. discloses the optical relay projects a second image, wherein the second image and the first image are substantially the same size (fig. 5 and its description).

With respect to claim 379, Oostman, Jr. discloses wherein the optical relay projects a second image, wherein the collimated beam from the collimating optical element to the first image has substantially the same diameter as the collimated beam from the optical relay to the second image (fig. 5 and its description).

With respect to claim 380, Oostman, Jr. discloses a first focusing optical element arranged to receive the collimated beam from the optical relay at the extended

Art Unit: 2884

collimated distance, the first focusing optical element configured to focus the extended collimated beam to a first semiconductor detector (fig. 5 and its description).

With respect to claim 382, Oostman, Jr. discloses the optical distance from the collimating optical element to the optical relay is substantially the same as the optical distance from the optical relay to the first focusing optical element (fig. 5).

With respect to claim 383, Oostman, Jr. discloses an optical module (abstract), the optical module comprising:

- (a) a light source providing light that forms an object (123, see fig.5);
- (b) a collimating optical element (145) arranged to receive light from the light source, the collimating optical element configured to project a first image of the object; and
- (c) an optical relay (151) arranged near the first image, the optical relay configured to receive light from the collimating optical element and to project a second image of the object; wherein the size of the first image is substantially the same as the size of the second image (fig. 5 and its description).

With respect to claim 384, Oostman, Jr. discloses the optical distance from the collimating optical element to the first image is substantially the same as the optical distance from the optical relay to the second image (fig. 5 and its description).

With respect to claim 385, Oostman, Jr. discloses the light source is an extended light source that forms the object, wherein the first image is a magnified image of the object (col. 9 lines 44-47).

With respect to claim 386, Oostman, Jr. discloses the light source is emitted from a facet of a multimode optical fiber (col. 6 lines 5-7).

With respect to claim 387, Oostman, Jr. discloses the collimating optical element has an effective size defined by its cross section, wherein the size of the first image is substantially the same as the effective size of the collimating optical element (col. 10 lines 25-47).

***Claim Rejections - 35 USC § 103***

The following is a quotation of pre-AIA 35 U.S.C. 103(a) which forms the basis for all obviousness rejections set forth in this Office action:

(a) A patent may not be obtained though the invention is not identically disclosed or described as set forth in section 102, if the differences between the subject matter sought to be patented and the prior art are such that the subject matter as a whole would have been obvious at the time the invention was made to a person having ordinary skill in the art to which said subject matter pertains. Patentability shall not be negated by the manner in which the invention was made.

Claim 369 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Heffelfinger et al. (US 2003/0044967) in view of Johnson (US 4,385,234).

With respect to claim 369, Heffelfinger discloses collimating lenses but does not explicitly disclose the lens being achromatic doublet lens. In a similar field of endeavor, Johnson discloses using achromatic doublet lens for collimating is well-known (col. 3 lines 51-65). In view of this teaching, it would have been obvious to one of ordinary skill in the art at the time of the invention was made to substitute one known lens for another and the results of collimating would have been predictable.

Claim 366 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Oostman, Jr. et al. (US 2003/0044967).



With respect to claim 366, Oostman, Jr. discloses the focusing element but does not specify to what kind of diameter size the focusing element focuses light. However, it is common in an optical device that a focusing element focuses light to a spot the size of 1 mm or less, which is smaller than the diameter of an optical fiber. It is, therefore, within the ordinary skill of one in the art to choose any suitable size for the intended application. Therefore, it would have been obvious to one of ordinary skill in the art before the effective filing date of the claimed invention to adapt the recited ranges for focusing in view of the feature is merely a variation in design and the results would have been predictable.

Claim 367 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Oostman, Jr. et al. (US 2003/0044967) in view of Govorkov et al. (US 2005/0002425).

With respect to claim 367, Oostman, Jr. discloses the light source forms an object, wherein the collimating optical element is configured to project a magnified image of the object. Oostman, Jr. discloses an optical relay element is a dichroic mirror instead of a concave mirror, wherein the radius of curvature approximately equal to the distance between the collimating optical element and the magnified image projected thereby. In a similar field of endeavor, Govorkov discloses the imaging mirrors can be used to provide relay imaging are concave, spherical mirrors with a radius of curvature approximately equal to the distance between the mirrors [0043]. In view of this teaching, it would have been obvious to one of ordinary skill in the art at the time of the invention was made to substitute one known mirror (dichroic) with another (concave mirror) to

configure so that the optical path length between a collimating optical element and a focusing optical element is substantially the same as the optical path length between an image relay optical element and a second focusing optical system in view of obtaining the desired delay in smaller physical space and better alignment.

Claim 373 is/are rejected under pre-AIA 35 U.S.C. 103(a) as being unpatentable over Heffelfinger et al. (US 2003/0044967).

With respect to claim 373, Heffelfinger discloses the optical system as recited. Heffelfinger does not explicitly disclose the diameter of the collimated beam between the optical relay and the first focusing optical element is substantially the same as the diameter of the collimated beam between the collimating optical element and the second focusing optical element. However, it is within the ordinary skill of one in the art to choose any suitable size for the intended application. Therefore, it would have been obvious to one of ordinary skill in the art before the effective filing date of the claimed invention to have the diameter of the beams to be substantially the same in view of the feature is merely a variation in design and the results would have been predictable.

### ***Allowable Subject Matter***

Claims 374, 375 and 381 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

The following is a statement of reasons for the indication of allowable subject matter: the prior art does not teach or suggest a second optical filter, the second optical

Art Unit: 2884

filter arranged between the optical relay and the first focusing optical element, the second optical filter configured to pass light of a third range of wavelengths in the first branch of the collimated beam to the first focusing optical element, wherein the third range of wavelengths is a subset of the first range of wavelengths; optical filter arranged between the collimating optical element and the optical relay, the optical filter configured to separate the collimated beam into a first branch and a second branch, wherein the first branch and the second branch are different colors, wherein the optical relay receives the first branch; and a second focusing optical element arranged to receive the second branch, the second focusing optical element configured to focus the second branch to a second semiconductor detector.

### ***Conclusion***

Any inquiry concerning this communication or earlier communications from the examiner should be directed to MINDY VU whose telephone number is (571)272-8539. The examiner can normally be reached on M-F 9am - 5:30pm.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, Dave Porta can be reached on 571-272-2444. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

Art Unit: 2884

Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

/M. V./

Examiner, Art Unit 2884

/MARCUS TANINGCO/

Primary Examiner, Art Unit 2884

|                                   |                                       |                                                              |             |
|-----------------------------------|---------------------------------------|--------------------------------------------------------------|-------------|
| <b>Notice of References Cited</b> | Application/Control No.<br>15/638,461 | Applicant(s)/Patent Under<br>Reexamination<br>CHEN, YONG QIN |             |
|                                   | Examiner<br>MINDY VU                  | Art Unit<br>2884                                             | Page 1 of 1 |

**U.S. PATENT DOCUMENTS**

| * |   | Document Number<br>Country Code-Number-Kind Code | Date<br>MM-YYYY | Name                   | CPC Classification | US Classification |
|---|---|--------------------------------------------------|-----------------|------------------------|--------------------|-------------------|
| * | A | US-2003/0044967 A1                               | 03-2003         | Heffelfinger, David M. | G01J3/14           | 435/287.2         |
| * | B | US-2005/0002425 A1                               | 01-2005         | Govorkov, Sergei V.    | G03F7/7055         | 372/25            |
|   | C | US-                                              |                 |                        |                    |                   |
|   | D | US-                                              |                 |                        |                    |                   |
|   | E | US-                                              |                 |                        |                    |                   |
|   | F | US-                                              |                 |                        |                    |                   |
|   | G | US-                                              |                 |                        |                    |                   |
|   | H | US-                                              |                 |                        |                    |                   |
|   | I | US-                                              |                 |                        |                    |                   |
|   | J | US-                                              |                 |                        |                    |                   |
|   | K | US-                                              |                 |                        |                    |                   |
|   | L | US-                                              |                 |                        |                    |                   |
|   | M | US-                                              |                 |                        |                    |                   |

**FOREIGN PATENT DOCUMENTS**

| * |   | Document Number<br>Country Code-Number-Kind Code | Date<br>MM-YYYY | Country | Name | CPC Classification |
|---|---|--------------------------------------------------|-----------------|---------|------|--------------------|
|   | N |                                                  |                 |         |      |                    |
|   | O |                                                  |                 |         |      |                    |
|   | P |                                                  |                 |         |      |                    |
|   | Q |                                                  |                 |         |      |                    |
|   | R |                                                  |                 |         |      |                    |
|   | S |                                                  |                 |         |      |                    |
|   | T |                                                  |                 |         |      |                    |

**NON-PATENT DOCUMENTS**

| * |   | Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages) |
|---|---|-------------------------------------------------------------------------------------------|
|   | U |                                                                                           |
|   | V |                                                                                           |
|   | W |                                                                                           |
|   | X |                                                                                           |

\*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)  
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.



## UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
 United States Patent and Trademark Office  
 Address: COMMISSIONER FOR PATENTS  
 P.O. Box 1450  
 Alexandria, Virginia 22313-1450  
 www.uspto.gov

## BIB DATA SHEET

CONFIRMATION NO. 9847

| SERIAL NUMBER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | FILING or 371(c)<br>DATE                                                                                          | CLASS                                                    | GROUP ART UNIT                    | ATTORNEY DOCKET<br>NO.                                                                                                                                                                                                                                                    |                               |                                    |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|-----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------|------------------------------------|
| 15/638,461                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | 06/30/2017                                                                                                        | 250                                                      | 2884                              | BECC.P0002US.CIP.C                                                                                                                                                                                                                                                        |                               |                                    |
| <b>RULE</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |                                                                                                                   |                                                          |                                   |                                                                                                                                                                                                                                                                           |                               |                                    |
| <b>APPLICANTS</b><br>IRIS INTERNATIONAL, INC., Chatsworth, CA;<br><b>INVENTORS</b><br>Yong Qin Chen, San Jose, CA;<br><b>** CONTINUING DATA *****</b><br>This application is a CON of 14/555,102 11/26/2014 PAT 9746412<br>which claims benefit of 61/911,859 12/04/2013<br>and is a CIP of PCT/US2013/043453 05/30/2013<br>which claims benefit of 61/653,245 05/30/2012<br>and claims benefit of 61/653,328 05/30/2012<br>and claims benefit of 61/715,819 10/18/2012<br>and claims benefit of 61/715,836 10/19/2012<br>and claims benefit of 61/816,819 04/29/2013<br><b>** FOREIGN APPLICATIONS *****</b><br><b>** IF REQUIRED, FOREIGN FILING LICENSE GRANTED **</b><br>07/18/2017 |                                                                                                                   |                                                          |                                   |                                                                                                                                                                                                                                                                           |                               |                                    |
| Foreign Priority claimed <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No<br>35 USC 119(a-d) conditions met <input type="checkbox"/> Yes <input checked="" type="checkbox"/> No<br>Verified and /MINDY D VU/<br>Acknowledged Examiner's Signature                                                                                                                                                                                                                                                                                                                                                                                                                    |                                                                                                                   | <input type="checkbox"/> Met after Allowance<br>Initials | <b>STATE OR<br/>COUNTRY</b><br>CA | <b>SHEETS<br/>DRAWINGS</b><br>35                                                                                                                                                                                                                                          | <b>TOTAL<br/>CLAIMS</b><br>26 | <b>INDEPENDENT<br/>CLAIMS</b><br>3 |
| <b>ADDRESS</b><br>NORTON ROSE FULBRIGHT US LLP<br>98 SAN JACINTO BOULEVARD<br>SUITE 1100<br>AUSTIN, TX 78701-4255<br>UNITED STATES                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |                                                                                                                   |                                                          |                                   |                                                                                                                                                                                                                                                                           |                               |                                    |
| <b>TITLE</b><br>FLOW CYTOMETER                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |                                                                                                                   |                                                          |                                   |                                                                                                                                                                                                                                                                           |                               |                                    |
| <b>FILING FEE<br/>RECEIVED</b><br>2480                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | FEES: Authority has been given in Paper<br>No. _____ to charge/credit DEPOSIT ACCOUNT<br>No. _____ for following: |                                                          |                                   | <input type="checkbox"/> All Fees<br><input type="checkbox"/> 1.16 Fees (Filing)<br><input type="checkbox"/> 1.17 Fees (Processing Ext. of time)<br><input type="checkbox"/> 1.18 Fees (Issue)<br><input type="checkbox"/> Other _____<br><input type="checkbox"/> Credit |                               |                                    |

|                                                                                                                                   |                                                 |                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------|
| Form PTO-1449 (modified)                                                                                                          | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1</b> | Serial No.:<br><b>15/638,461</b> |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) | Applicant:<br><b>IRIS INTERNATIONAL, INC.</b>   |                                  |
|                                                                                                                                   | Filing Date:<br><b>June 30, 2017</b>            | Group:<br><b>2884</b>            |
| U.S. Patent Documents<br><i>See Page 1</i>                                                                                        | Foreign Patent Documents<br><i>See Page 1</i>   | Other Art<br><i>See Page 2</i>   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name          |
|-------------|-----------|-----------------|----------|---------------|
|             | A173      | 2005/0134836    | 06/23/05 | Paldus et al. |
|             | A174      | 2012/0211679    | 08/23/12 | Heng et al.   |
|             | A175      | 4,673,289       | 06/16/87 | Gaucher       |
|             | A176      | 7,630,147       | 12/08/09 | Kar et al.    |
|             | A177      | 7,889,263       | 02/15/11 | Ortyn et al.  |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                    |
|-------------|-----------|-----------------|----------|---------|-----------------------------|
|             | B41       | JP 2003-505707  | 02/12/03 | Japan   | Japanese (English Abstract) |
|             | B42       | JP 2004-500572  | 01/08/04 | Japan   | Japanese (English Abstract) |
|             | B43       | JP 2008-534960  | 08/28/08 | Japan   | Japanese (English Abstract) |
|             | B44       | JP 2010-085194  | 04/15/10 | Japan   | Japanese (English Abstract) |
|             | B45       | JP H03-197641   | 08/29/91 | Japan   | Japanese (English Abstract) |
|             | B46       | JP H05-119035   | 05/14/93 | Japan   | Japanese (English Abstract) |
|             | B47       | JP S55-144226   | 11/11/80 | Japan   | Japanese (English Abstract) |
|             | B48       | JP S61-184427   | 08/18/86 | Japan   | Japanese (English Abstract) |
|             | B49       | WO 2013/181453  | 12/05/13 | WIPO    | English                     |

29764669.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                 |                                  |
|-----------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|----------------------------------|
| Form PTO-1449 (modified)                                                                                                          | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1</b> | Serial No.:<br><b>15/638,461</b> |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) | Applicant:<br><b>IRIS INTERNATIONAL, INC.</b>   |                                  |
|                                                                                                                                   | Filing Date:<br><b>June 30, 2017</b>            | Group:<br><b>2884</b>            |
| U.S. Patent Documents<br><i>See Page 1</i>                                                                                        | Foreign Patent Documents<br><i>See Page 1</i>   | Other Art<br><i>See Page 2</i>   |

### Other Art (Including Author, Title, Date Pertinent Pages, Etc.)

| Exam.<br>Init. | Ref.<br>Des. | Citation                                                                                                                                                 |
|----------------|--------------|----------------------------------------------------------------------------------------------------------------------------------------------------------|
|                | C9           | Office Action issued in Chinese Patent Application No. 201380039184.6, dated February 12, 2018 (Attorney Docket No. BECC.P0002CN)                        |
|                | C10          | Office Action issued in Japanese Patent Application No. 2015-515208, dated May 02, 2018 (Attorney Docket No. BECC.P0002JP)                               |
|                | C11          | Office Action issued in Japanese Patent Application No. 2016-216891, dated December 04, 2017 (English Translation) (Attorney Docket No. BECC.P0002JP.D1) |

29764669.1

|                                                                                                                                                                                                                                         |                             |
|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|
| EXAMINER: /MINDY D VU/                                                                                                                                                                                                                  | DATE CONSIDERED: 06/13/2018 |
| EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT. |                             |



EAST Search History

EAST Search History (Prior Art)

| Ref # | Hits   | Search Query                                                                                                                                                            | DBs                                                                        | Default Operator | Plurals | Time Stamp       |
|-------|--------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|------------------|---------|------------------|
| L1    | 13     | ((("20050134836") or ("20120211679") or ("4673289") or ("7630147") or ("7889263"))).PN.                                                                                 | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | OFF     | 2018/06/19 19:16 |
| S1    | 29325  | (G01N15/1436 or G01N15/1459 or G01N15/1434 or G02B27/0025 or G02B21/361 or G02B21/04 or G02B6/29365 or G02B6/26 or G01N2015/144 or G01N2015/1006 or G01N2015/1452).cpc. | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:12 |
| S2    | 57223  | optical\$2 with relay\$3                                                                                                                                                | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:14 |
| S3    | 13096  | S2 same (mirror or (refractive adj lens))                                                                                                                               | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:14 |
| S4    | 247890 | pin\$1hole or (pin adj hole)                                                                                                                                            | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:23 |
| S5    | 1177   | S3 and S4                                                                                                                                                               | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:23 |
| S6    | 645    | S5 and fiber                                                                                                                                                            | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR               | ON      | 2018/06/11 16:24 |
| S7    | 292    | collimat\$3 and filter\$3 and S6                                                                                                                                        | US-PGPUB;                                                                  | OR               | ON      | 2018/06/11       |

|     |        |                                               |                                                                            |    |    |                     |
|-----|--------|-----------------------------------------------|----------------------------------------------------------------------------|----|----|---------------------|
|     |        |                                               | USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB              |    |    | 16:27               |
| S8  | 31600  | chen-yong\$.in.                               | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>21:17 |
| S9  | 57223  | optical\$2 with relay\$3                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>21:18 |
| S10 | 11     | S9 and S8                                     | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>21:18 |
| S11 | 928938 | diameter with siz\$4                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>22:29 |
| S12 | 57223  | optical\$2 with relay\$3                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>22:29 |
| S13 | 13096  | S12 same (mirror or (refractive adj<br>lens)) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>22:29 |
| S14 | 247890 | pin\$1hole or (pin adj hole)                  | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/11<br>22:29 |
| S15 | 1177   | S13 and S14                                   | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;            | OR | ON | 2018/06/11<br>22:29 |

|     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                            |    |                     |                     |
|-----|-----|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|----|---------------------|---------------------|
|     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | IBM_TDB                                                                    |    |                     |                     |
| S16 | 645 | S15 and fiber                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON                  | 2018/06/11<br>22:29 |
| S17 | 292 | collimat\$3 and filter\$3 and S16                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON                  | 2018/06/11<br>22:29 |
| S18 | 93  | S17 and S11                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON                  | 2018/06/11<br>22:29 |
| S19 | 622 | ("20020141902"   "20060292021"  <br>"4073574"   "4244045"   "4727020"  <br>"5230614"   "5583683"   "5615200"  <br>"5788927"   "6870976"   "6975400"  <br>"7430048"   "7450229"   "7952981"  <br>"8009189"   "8436371"   "6159686"  <br>"20050084402"   "20060245964"  <br>"20130020498"   "3946239"   "3989381"  <br>"4189236"   "4576556"   "4745285"  <br>"4950136"   "6200101"   "6683314"  <br>"6941047"   "7260328"   "7268953"  <br>"7381565"   "7385682"   "8157547"  <br>"8337096"   "8488244"   "20040165828"  <br>"2385495"   "2764147"  <br>"20120274925"   "20130050782"  <br>"20130070243"   "3953727"   "4188543"  <br>"4515274"   "4920275"   "5251060"  <br>"5470211"   "5748372"   "5781351"  <br>"5850292"   "6608682"   "6748133"  <br>"6954722"   "7212343"   "8149525"  <br>"8229707"   "8253938"   "8405048"  <br>"20030142720"   "20070124947"  <br>"20090091746"   "20120281204"  <br>"20120282126"   "20120287419"  <br>"20130204538"   "3411293"   "3542491"  <br>"4834630"   "5177641"   "5299066"  <br>"5373395"   "5396487"   "5467225"  <br>"5548395"   "5746585"   "5777674"  <br>"6252719"   "6572255"   "6618143"  <br>"6839367"   "6876079"   "6897954"  <br>"7305018"   "7453915"   "7496463"  <br>"7623243"   "7645127"   "7835000"  <br>"20020067895"   "5157917"  <br>"20130010181"   "0315667"   "4482994"  <br>"4778253"   "4997275"   "5050963"  <br>"5245318"   "5786915"   "5971713"  <br>"6315952"   "6647175"   "6768593"  <br>"6813017"   "7505131"   "7580120"  <br>"7668422"   "7768120"   "8432541"  <br>"8436993"   "8507279"   "3199341"  <br>"6683314"   "20060256335" | OR                                                                         | ON | 2018/06/13<br>18:47 |                     |

of 630

|     |      |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |                                                                            |    |     |                     |
|-----|------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|----|-----|---------------------|
|     |      | "20090190128"   "20110032522"  <br>"20120156074"   "3726613"   "5142462"<br>  "5369476"   "5475210"   "5805363"  <br>"6008920"   "6510007"   "6713019"  <br>"7072540"   "7110192"   "7456960"  <br>"7507588"   "7758324"   "7981661"  <br>"8213472"   "8284402"   "20040218184"<br>  "20080024758"   "20110014075"  <br>"20130094102"   "4564342"   "5915925"<br>  "6135734"   "6794671"   "7038778"  <br>"7113266"   "7129505"   "7262838"  <br>"7876436"   "8187888"   "8233146"  <br>"8270098"   "8345237"   "2669709"  <br>"20060221325"   "20080241911"  <br>"3661460"   "3826593"   "3873204"  <br>"4623225"   "4871249"   "4976590"  <br>"5317162"   "6017194"   "6102678"  <br>"6542306"   "6638481"   "6767188"  <br>"6788409"   "7127356"   "7561267"  <br>"7781227"   "7787197"   "7894047"  <br>"8049185").PN. |                                                                            |    |     |                     |
| S20 | 5    | ((("6683314") or ("20040165828")).PN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | OFF | 2018/06/13<br>19:42 |
| S21 | 1071 | concave with mirror with relay\$3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON  | 2018/06/14<br>17:49 |
| S22 | 57   | S21 with filter\$3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON  | 2018/06/14<br>18:09 |
| S23 | 2417 | concave with mirror with curvature with<br>radius                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON  | 2018/06/14<br>19:20 |
| S24 | 118  | S23 same relay\$3                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON  | 2018/06/14<br>19:21 |
| S25 | 1028 | achromat\$3 near3 doublet near3 lens                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;            | OR | ON  | 2018/06/15<br>11:17 |

|     |     |                                                                      |                                                                            |    |    |                     |
|-----|-----|----------------------------------------------------------------------|----------------------------------------------------------------------------|----|----|---------------------|
|     |     |                                                                      | IBM_TDB                                                                    |    |    |                     |
| S26 | 175 | S25 with collimat\$3                                                 | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/15<br>11:17 |
| S27 | 12  | relay\$3 same (curv\$6 near4 mirror)<br>same (refractive near3 lens) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/15<br>16:22 |
| S28 | 989 | relay\$3 with (concave near4 mirror)                                 | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | OR | ON | 2018/06/15<br>19:24 |

EAST Search History (Interference)

< This search history is empty >

6/ 19/ 2018 7:25:16 PM  
C:\ Users\ mvu\ Documents\ EAST\ Workspaces\ 15638461.wsp

|                                                                                                              |                                                |                                                                      |
|--------------------------------------------------------------------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|
| <b>Search Notes</b><br><br> | <b>Application/Control No.</b><br><br>15638461 | <b>Applicant(s)/Patent Under Reexamination</b><br><br>CHEN, YONG QIN |
|                                                                                                              | <b>Examiner</b><br><br>MINDY VU                | <b>Art Unit</b><br><br>2884                                          |

| CPC- SEARCHED                               |         |          |
|---------------------------------------------|---------|----------|
| Symbol                                      | Date    | Examiner |
| G01N 15/1436, 15/1459, 15/1434              | 6/15/18 | MV       |
| G02B 21/361, 27/0025, 21/804, 6/26, 6/29365 | 6/15/18 | MV       |

| CPC COMBINATION SETS - SEARCHED |      |          |
|---------------------------------|------|----------|
| Symbol                          | Date | Examiner |
|                                 |      |          |

| US CLASSIFICATION SEARCHED |          |      |          |
|----------------------------|----------|------|----------|
| Class                      | Subclass | Date | Examiner |
|                            |          |      |          |

\* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

| SEARCH NOTES                           |         |          |
|----------------------------------------|---------|----------|
| Search Notes                           | Date    | Examiner |
| Inventor name search                   | 6/11/18 | mv       |
| Parent data considered                 | 6/11/18 | mv       |
| EAST BRS - See search history printout | 6/18/18 | mv       |

| INTERFERENCE SEARCH     |                         |      |          |
|-------------------------|-------------------------|------|----------|
| US Class/<br>CPC Symbol | US Subclass / CPC Group | Date | Examiner |
|                         |                         |      |          |

|  |  |
|--|--|
|  |  |
|--|--|

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name             | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|------------------|-------|-----------|---------------------|
|             | A1        | 315667          | 4/14/85  | Serdinko         | 417   | 475       | 10/20/84            |
|             | A2        | 2385495         | 9/25/45  | Brian            | 250   | 487.1     | 8/21/43             |
|             | A3        | 2669709         | 2/16/54  | Glancy et al.    | 348   | 784       | 10/19/60            |
|             | A4        | 2764147         | 9/25/56  | Brunner          | 126   | 247       | 2/23/51             |
|             | A5        | 3199341         | 08/10/65 | Heuer Jr. et al. | 73    | 807       | 05/28/62            |
|             | A6        | 3411293         | 11/19/68 | Akins            | 60    | 454       | 10/20/66            |
|             | A7        | 3542491         | 11/24/70 | Newman           | 417   | 295       | 5/27/69             |
|             | A8        | 3661460         | 5/9/72   | Elking et al.    | 356   | 36        | 8/28/70             |
|             | A9        | 3726613         | 4/10/73  | von Casimir      | 417   | 477.1     | 10/12/70            |
|             | A10       | 3826593         | 7/30/74  | von Casimir      | 417   | 53        | 5/11/73             |
|             | A11       | 3873204         | 3/25/75  | Friedman et al.  | 356   | 39        | 11/29/72            |
|             | A12       | 3946239         | 3/23/76  | Salzman et al.   | 250   | 461.2     | 1/24/75             |
|             | A13       | 3953727         | 4/27/76  | d' Auria et al.  | 398   | 88        | 1/17/75             |
|             | A14       | 3989381         | 11/2/76  | Fulwyler         | 356   | 39        | 5/5/75              |
|             | A15       | 4073574         | 2/14/78  | Clarke et al.    | 359   | 728       | 10/1/76             |
|             | A16       | 4188543         | 2/12/80  | Brunsting et al. | 250   | 458.1     | 4/24/78             |
|             | A17       | 4189236         | 2/19/80  | Hogg et al.      | 356   | 317       | 3/20/78             |
|             | A18       | 4244045         | 1/6/81   | Nosu et al.      | 398   | 86        | 1/31/79             |
|             | A19       | 4482994         | 11/13/84 | Ishikawa         | 398   | 86        | 6/7/82              |
|             | A20       | 4515274         | 5/7/85   | Hollinger et al. | 209   | 3.1       | 12/2/81             |
|             | A21       | 4564342         | 1/14/86  | Weber et al.     | 417   | 477.6     | 7/24/84             |
|             | A22       | 4576556         | 3/18/86  | Thompson         | 417   | 477.12    | 4/2/80              |
|             | A23       | 4623225         | 11/18/86 | Forkner          | 359   | 669       | 6/29/84             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><b>IRIS INTERNATIONAL, INC</b>             |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A24       | 4727020         | 2/23/88  | Recktenwald        | 435   | 6.11      | 2/25/85             |
|             | A25       | 4745285         | 5/17/88  | Recktenwald et al. | 250   | 458.1     | 8/21/86             |
|             | A26       | 4778253         | 10/18/88 | Siga et al.        | 359   | 819       | 3/26/86             |
|             | A27       | 4834630         | 5/30/89  | Godwin             | 417   | 475       | 2/16/88             |
|             | A28       | 4871249         | 10/3/89  | Watson             | 356   | 73        | 7/1/88              |
|             | A29       | 4920275         | 4/24/90  | Itoh               | 250   | 574       | 12/30/88            |
|             | A30       | 4950136         | 8/21/90  | Haas et al.        | 417   | 477.7     | 8/14/89             |
|             | A31       | 4976590         | 12/11/90 | Baldwin            | 417   | 53        | 6/8/88              |
|             | A32       | 4997275         | 3/5/91   | Gaucher et al.     | 356   | 72        | 9/23/88             |
|             | A33       | 5050963         | 9/24/91  | Murakami           | 359   | 808       | 10/9/90             |
|             | A34       | 5142462         | 8/25/92  | Kashima            | 362   | 268       | 4/27/90             |
|             | A35       | 5157917         | 10/27/92 | Liang et al.       | 60    | 2261.1    | 05/20/91            |
|             | A36       | 5177641         | 1/5/93   | Kobayashi et al.   | 359   | 820       | 10/30/90            |
|             | A37       | 5230614         | 7/27/93  | Zanger et al.      | 417   | 477.9     | 6/3/92              |
|             | A38       | 5245318         | 9/14/93  | Tohge et al.       | 340   | 611       | 12/15/92            |
|             | A39       | 5251060         | 10/5/93  | Uenishi et al.     | 359   | 328       | 9/30/92             |
|             | A40       | 5257917         | 11/02/93 | Minarik et al.     | 417   | 475       | 10/02/92            |
|             | A41       | 5299066         | 3/29/94  | Rombult            | 359   | 819       | 8/12/92             |
|             | A42       | 5317162         | 5/31/94  | Pinsky et al.      | 250   | 461.2     | 9/9/92              |
|             | A43       | 5369476         | 11/29/94 | Bowers et al.      | 399   | 49        | 1/28/92             |
|             | A44       | 5373395         | 12/13/94 | Adachi             | 359   | 652       | 5/10/93             |
|             | A45       | 5396487         | 3/7/95   | Abe et al.         | 359   | 819       | 10/31/91            |
|             | A46       | 5467225         | 11/14/95 | Manabe             | 359   | 661       | 11/1/94             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name            | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-----------------|-------|-----------|---------------------|
|             | A47       | 5470211         | 11/28/95 | Knott et al.    | 417   | 477.9     | 8/11/94             |
|             | A48       | 5475210         | 12/12/95 | Taguchi et al.  | 250   | 205       | 6/8/93              |
|             | A49       | 5548395         | 8/20/96  | Kosaka          | 356   | 73        | 8/31/92             |
|             | A50       | 5583683         | 12/10/96 | Scobey          | 398   | 79        | 6/15/95             |
|             | A51       | 5615200         | 3/25/97  | Hoshino et al.  | 369   | 112.04    | 4/14/95             |
|             | A52       | 5746585         | 5/5/98   | McDunn et al.   | 417   | 477.11    | 12/31/96            |
|             | A53       | 5748372         | 5/5/98   | Kitagawa        | 359   | 565       | 4/17/96             |
|             | A54       | 5777674         | 7/7/98   | Ohmuro          | 348   | 338       | 4/10/95             |
|             | A55       | 5781351         | 7/14/98  | Murakami et al. | 359   | 808       | 5/31/96             |
|             | A56       | 5786915         | 7/28/98  | Scobey          | 398   | 82        | 10/22/96            |
|             | A57       | 5788927         | 8/4/98   | Farrell et al.  | 422   | 63        | 6/30/96             |
|             | A58       | 5805363         | 9/8/98   | Okuda et al.    | 359   | 819       | 7/17/97             |
|             | A59       | 5850292         | 12/15/98 | Braun           | 356   | 419       | 11/13/97            |
|             | A60       | 5915925         | 6/29/99  | North Jr.       | 417   | 36        | 1/7/97              |
|             | A61       | 5971713         | 10/26/99 | North Jr.       | 417   | 36        | 12/29/98            |
|             | A62       | 6008920         | 12/28/99 | Hendrix         | 398   | 79        | 3/11/98             |
|             | A63       | 6017194         | 1/25/00  | North Jr.       | 417   | 36        | 12/31/98            |
|             | A64       | 6102678         | 8/15/00  | Peclat          | 417   | 477.7     | 4/3/98              |
|             | A65       | 6135734         | 10/24/00 | Isozumi et al.  | 417   | 542       | 9/23/98             |
|             | A66       | 6159686         | 12/12/00 | Kardos et al.   | 435   | 6         | 01/30/98            |
|             | A67       | 6200101         | 3/13/01  | North Jr.       | 417   | 36        | 7/6/99              |
|             | A68       | 6252719         | 6/26/01  | Eichenbaum      | 359   | 634       | 3/19/99             |
|             | A69       | 6315952         | 11/13/01 | Sklar et al.    | 422   | 63        | 6/10/99             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                         |                                                          |                                           |
|---------------------------------------------------------|----------------------------------------------------------|-------------------------------------------|
| Form PTO-1449 (modified)                                | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>          |
| <b>List of Patents and Publications for Applicant's</b> | <b>Applicant:</b><br><b>IRIS INTERNATIONAL, INC</b>      |                                           |
| <b>INFORMATION DISCLOSURE STATEMENT</b>                 | <b>Filing Date:</b><br><b>June 30, 2017</b>              | <b>Group:</b><br><b>Not Yet Assigned</b>  |
| (Use several sheets if necessary)                       |                                                          |                                           |
| <b>U.S. Patent Documents</b><br><i>See Page 1-8</i>     | <b>Foreign Patent Documents</b><br><i>See Page 8-11</i>  | <b>Other Art</b><br><i>See Page 10-11</i> |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A70       | 6510007         | 1/21/03  | Blasenheim         | 359   | 659       | 8/21/01             |
|             | A71       | 6542306         | 4/1/03   | Goodman            | 359   | 634       | 3/16/01             |
|             | A72       | 6572255         | 6/3/03   | Husher             | 366   | 132       | 4/24/01             |
|             | A73       | 6608682         | 8/19/03  | Ortyn et al.       | 356   | 419       | 10/12/01            |
|             | A74       | 6618143         | 9/9/03   | Roche et al.       | 356   | 339       | 10/2/01             |
|             | A75       | 6638481         | 10/28/03 | Sklar et al.       | 422   | 63        | 9/19/01             |
|             | A76       | 6647175         | 11/11/03 | LoRegio et al.     | 385   | 24        | 10/8/01             |
|             | A77       | 6683314         | 1/27/04  | Oostman Jr. et al. | 250   | 461.2     | 8/28/01             |
|             | A78       | 6713019         | 3/30/04  | Ozasa et al.       | 422   | 82.09     | 3/27/02             |
|             | A79       | 6748133         | 6/8/04   | Liu et al.         | 385   | 24        | 11/26/01            |
|             | A80       | 6767188         | 7/27/04  | Vrane et al.       | 417   | 40        | 8/15/02             |
|             | A81       | 6768593         | 7/27/04  | Jutamulia          | 359   | 641       | 7/24/03             |
|             | A82       | 6788409         | 9/7/04   | Goodwin            | 356   | 339       | 9/3/02              |
|             | A83       | 6794671         | 9/21/04  | Nicoli et al.      | 250   | 574       | 7/17/02             |
|             | A84       | 6813017         | 11/2/04  | Hoffman et al.     | 356   | 317       | 10/19/00            |
|             | A85       | 6839367         | 1/4/05   | Nagamatsu et al.   | 372   | 34        | 3/16/01             |
|             | A86       | 6870679         | 3/22/05  | Randall et al.     | 359   | 580       | 6/10/02             |
|             | A87       | 6870976         | 3/22/05  | Chen et al.        | 385   | 14        | 3/13/01             |
|             | A88       | 6897954         | 5/24/05  | Bishop et al.      | 356   | 317       | 12/20/02            |
|             | A89       | 6941047         | 9/6/05   | Capewell et al.    | 385   | 47        | 3/1/04              |
|             | A90       | 6954722         | 10/11/05 | Parks et al.       | 702   | 194       | 10/17/03            |
|             | A91       | 6975400         | 12/13/05 | Ortyn et al.       | 356   | 419       | 7/28/03             |
|             | A92       | 7038778         | 5/2/06   | Yamauchi           | 356   | 419       | 8/13/02             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name               | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|--------------------|-------|-----------|---------------------|
|             | A93       | 7072540         | 7/4/06   | Szapiel et al.     | 385   | 24        | 4/22/03             |
|             | A94       | 7110192         | 9/19/06  | Sauter et al.      | 359   | 754       | 1/12/05             |
|             | A95       | 7113266         | 9/26/06  | Wells              | 356   | 73        | 3/30/05             |
|             | A96       | 7127356         | 10/24/06 | Nicoli et al.      | 702   | 26        | 5/18/04             |
|             | A97       | 7129505         | 10/31/06 | Oostman Jr. et al. | 250   | 458.1     | 10/17/03            |
|             | A98       | 7212343         | 5/1/07   | He et al.          | 359   | 618       | 7/11/03             |
|             | A99       | 7260328         | 8/21/07  | Kropp              | 398   | 82        | 2/24/03             |
|             | A100      | 7262838         | 8/28/07  | Fritz              | 356   | 73        | 1/16/04             |
|             | A101      | 7268953         | 9/11/07  | Matthae et al.     | 359   | 656       | 6/7/06              |
|             | A102      | 7305018         | 12/4/07  | Otoma              | 372   | 50.1      | 12/29/05            |
|             | A103      | 7381565         | 6/3/08   | Kurabayashi et al. | 436   | 63        | 3/20/06             |
|             | A104      | 7385682         | 6/10/08  | Chu et al.         | 356   | 73        | 9/7/06              |
|             | A105      | 7430048         | 9/30/08  | Reel et al.        | 356   | 432       | 2/16/06             |
|             | A106      | 7450229         | 11/11/08 | Ortyn et al.       | 356   | 326       | 5/4/05              |
|             | A107      | 7453915         | 11/18/08 | Imai               | 372   | 50.1      | 12/5/06             |
|             | A108      | 7456960         | 11/25/08 | Cerni et al.       | 356   | 336       | 11/15/05            |
|             | A109      | 7496463         | 2/24/09  | Nicoli et al.      | 702   | 104       | 9/12/06             |
|             | A110      | 7505131         | 3/17/09  | Roth               | 356   | 317       | 3/6/08              |
|             | A111      | 7507588         | 3/24/09  | Mehrpouyan et al.  | 436   | 518       | 4/14/06             |
|             | A112      | 7561267         | 7/14/09  | Luo et al.         | 356   | 336       | 12/22/06            |
|             | A113      | 7580120         | 8/25/09  | Hamada et al.      | 356   | 73        | 4/6/06              |
|             | A114      | 7623243         | 11/24/09 | Kato               | 356   | 419       | 9/13/04             |
|             | A115      | 7645127         | 1/12/10  | Hagen et al.       | 417   | 477.12    | 6/29/06             |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><b>IRIS INTERNATIONAL, INC</b>             |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name              | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-------------------|-------|-----------|---------------------|
|             | A116      | 7668422         | 2/23/10  | Kropp             | 385   | 47        | 3/12/04             |
|             | A117      | 7758324         | 6/20/10  | Baumann et al.    | 417   | 477.2     | 5/12/05             |
|             | A118      | 7768120         | 8/3/10   | Takashima         | 257   | 706       | 12/27/07            |
|             | A119      | 7781227         | 8/24/10  | Mehrpouyan et al. | 436   | 523       | 3/4/09              |
|             | A120      | 7787197         | 8/31/10  | Chen              | 359   | 793       | 9/4/08              |
|             | A121      | 7835000         | 11/16/10 | Graves et al.     | 356   | 338       | 11/3/06             |
|             | A122      | 7876436         | 1/25/11  | Chu               | 356   | 338       | 10/31/07            |
|             | A123      | 7894047         | 2/22/11  | Hamada et al.     | 356   | 39        | 7/24/09             |
|             | A124      | 7952981         | 3/31/11  | Suzuki            | 369   | 121       | 10/23/08            |
|             | A125      | 7981661         | 7/19/11  | Rich              | 435   | 286.5     | 4/17/07             |
|             | A126      | 8009189         | 8/30/11  | Ortyn et al.      | 348   | 80        | 6/3/08              |
|             | A127      | 8049185         | 11/1/11  | Hayashi et al.    | 250   | 459.1     | 2/4/09              |
|             | A128      | 8149525         | 4/3/12   | Do                | 359   | 797       | 3/28/07             |
|             | A129      | 8157547         | 4/17/12  | Vrielink          | 417   | 477.3     | 4/23/07             |
|             | A130      | 8187888         | 5/29/12  | Rich              | 436   | 63        | 7/8/11              |
|             | A131      | 8213472         | 7/3/12   | Hirai et al.      | 372   | 36        | 1/23/08             |
|             | A132      | 8229707         | 7/24/12  | Olson et al.      | 702   | 189       | 7/4/11              |
|             | A133      | 8233146         | 7/31/12  | Chen              | 356   | 246       | 1/5/10              |
|             | A134      | 8253938         | 8/28/12  | Vacca et al.      | 356   | 337       | 5/26/11             |
|             | A135      | 8270098         | 9/18/12  | Fukuta et al.     | 359   | 784       | 2/19/09             |
|             | A136      | 8284402         | 10/9/12  | Frazier et al.    | 356   | 419       | 2/26/10             |
|             | A137      | 8337096         | 12/25/12 | Shen et al.       | 385   | 89        | 11/30/09            |
|             | A138      | 8345237         | 1/1/13   | Tsukii et al.     | 356   | 338       | 12/23/11            |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name                  | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-----------------------|-------|-----------|---------------------|
|             | A139      | 8405048         | 3/26/13  | Hayashi               | 250   | 458.1     | 2/4/09              |
|             | A140      | 8432541         | 4/30/13  | Rich                  | 356   | 246       | 11/4/10             |
|             | A141      | 8436371         | 5/7/13   | Medendorp Jr., et al. | 257   | 88        | 5/24/07             |
|             | A142      | 8436993         | 5/7/13   | Kaduchak et al.       | 356   | 337       | 2/3/12              |
|             | A143      | 8488244         | 7/16/13  | Li et al.             | 359   | 618       | 2/17/11             |
|             | A144      | 8507279         | 8/13/13  | Ball et al.           | 436   | 10        | 6/2/10              |
|             | A145      | 2004165828      | 08/26/04 | Capewell et al.       | 385   | 47        | 03/01/04            |
|             | A146      | 20020067895     | 06/06/02 | Flanders              | 385   | 88        | 12/01/00            |
|             | A147      | 20020141902     | 10/3/02  | Ozasa et al.          | 422   | 82.09     | 3/27/02             |
|             | A148      | 20030142720     | 7/31/03  | Bradburn et al.       | 372   | 108       | 5/24/02             |
|             | A149      | 20040218184     | 11/4/04  | Joregenson et al.     | 356   | 419       | 2/27/04             |
|             | A150      | 20050084402     | 4/21/05  | Vanek                 | 417   | 477.3     | 10/27/04            |
|             | A151      | 20060221325     | 10/5/06  | Wells                 | 356   | 73        | 3/30/05             |
|             | A152      | 20060245964     | 11/2/06  | Koslov                | 417   | 477.1     | 6/29/06             |
|             | A153      | 20060256335     | 11/16/06 | Chen                  | 356   | 369       | 5/3/06              |
|             | A154      | 20060292021     | 12/28/06 | Tu                    | 417   | 477.1     | 11/7/02             |
|             | A155      | 20070124947     | 6/7/07   | Munroe et al.         | 33    | 286       | 10/25/06            |
|             | A156      | 20080024758     | 1/31/08  | Tabata                | 356   | 39        | 7/26/07             |
|             | A157      | 20080241911     | 10/2/08  | Ueno et al.           | 435   | 287.1     | 3/28/08             |
|             | A158      | 20090091746     | 4/9/09   | Fukuda et al.         | 356   | 73        | 10/1/08             |
|             | A159      | 20090190128     | 7/30/09  | Cerni et al.          | 356   | 336       | 11/24/08            |
|             | A160      | 20110014075     | 1/20/11  | Reif et al.           | 417   | 477.12    | 7/1/10              |
|             | A161      | 20110032522     | 2/10/11  | Graves et al.         | 356   | 338       | 10/12/10            |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### U.S. Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Name              | Class | Sub Class | Filing Date of App. |
|-------------|-----------|-----------------|----------|-------------------|-------|-----------|---------------------|
|             | A162      | 20120156074     | 6/21/12  | Kusch et al.      | 417   | 477.3     | 2/4/10              |
|             | A163      | 20120274925     | 11/1/12  | Chen et al.       | 356   | 73        | 11/1/12             |
|             | A164      | 20120281204     | 11/8/12  | Hoshishima et al. | 356   | 72        | 1/13/11             |
|             | A165      | 20120282126     | 11/8/12  | Brandt et al.     | 417   | 477.9     | 11/4/10             |
|             | A166      | 20120287419     | 11/15/12 | Sharpe et al.     | 356   | 51        | 5/11/12             |
|             | A167      | 20130010181     | 1/10/13  | Baba              | 348   | 360       | 3/14/11             |
|             | A168      | 20130020498     | 1/24/13  | Ebi et al.        | 250   | 435       | 7/18/12             |
|             | A169      | 20130050782     | 2/28/13  | Heng et al.       | 358   | 494       | 2/17/12             |
|             | A170      | 20130070243     | 3/21/13  | Goehde            | 356   | 338       | 11/9/12             |
|             | A171      | 20130094102     | 4/18/13  | Baba              | 359   | 784       | 7/13/10             |
|             | A172      | 20130204538     | 8/8/13   | Rich              | 702   | 21        | 10/25/11            |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                   |
|-------------|-----------|-----------------|----------|---------|----------------------------|
|             | B1        | CN 102087198    | 6/8/11   | China   | Chinese (English abstract) |
|             | B2        | CN 102818794    | 12/12/12 | China   | Chinese (English abstract) |
|             | B3        | CN 102818795    | 12/12/12 | China   | Chinese (English abstract) |
|             | B4        | CN 102818796    | 12/12/12 | China   | Chinese (English abstract) |
|             | B5        | CN 201917509U   | 8/3/11   | China   | Chinese (English abstract) |
|             | B6        | CN 201936066U   | 8/17/11  | China   | Chinese (English abstract) |
|             | B7        | CN 201984209U   | 9/21/11  | China   | Chinese (English abstract) |
|             | B8        | EP 0889319      | 1/7/99   | EPO     | German (English abstract)  |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><b>IRIS INTERNATIONAL, INC</b>             |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language                       |
|-------------|-----------|-----------------|----------|---------|--------------------------------|
|             | B9        | EP 1004907      | 4/22/09  | EPO     | English                        |
|             | B10       | EP 1953526      | 8/6/08   | EPO     | English                        |
|             | B11       | EP 2381475      | 3/4/15   | EPO     | English                        |
|             | B12       | EP 459764A2     | 12/4/91  | EPO     | English                        |
|             | B13       | EP 459764B1     | 12/11/96 | EPO     | English                        |
|             | B14       | EP 757346A1     | 2/5/97   | EPO     | English                        |
|             | B15       | EP 757346B1     | 11/14/01 | EPO     | English                        |
|             | B16       | EP 758755A2     | 2/19/97  | EPO     | English                        |
|             | B17       | JP 05333245     | 12/17/93 | Japan   | Japanese (English abstract)    |
|             | B18       | JP 2004-341204  | 12/02/04 | Japan   | Japanese (English Abstract)    |
|             | B19       | JP 2012-026837  | 02/09/12 | Japan   | Japanese (English Abstract)    |
|             | B20       | JP 829726       | 2/2/96   | Japan   | Japanese (English translation) |
|             | B21       | JP H04-184241   | 07/01/92 | Japan   | Japanese (English Abstract)    |
|             | B22       | JP H09-502794   | 03/18/97 | Japan   | Japanese (English Abstract)    |
|             | B23       | JP H10-73528    | 03/17/98 | Japan   | Japanese (English Abstract)    |
|             | B24       | WO 0057173      | 9/28/00  | WIPO    | English                        |
|             | B25       | WO 0127590      | 4/19/01  | WIPO    | English                        |
|             | B26       | WO 0140764      | 6/7/01   | WIPO    | English                        |
|             | B27       | WO 03012403     | 2/13/03  | WIPO    | French (English abstract)      |
|             | B28       | WO 2005033654   | 4/14/05  | WIPO    | English                        |
|             | B29       | WO 2006013316   | 2/9/06   | WIPO    | English                        |
|             | B30       | WO 2009095358   | 8/6/09   | WIPO    | German (English abstract)      |
|             | B31       | WO 2009098867   | 8/13/09  | WIPO    | Japanese (English abstract)    |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                                   |                                                  |                                                          |                                   |
|-----------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|----------------------------------------------------------|-----------------------------------|
| Form PTO-1449 (modified)                                                                                                          |                                                  | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b> | Serial No.:<br><b>15/638,461</b>  |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) |                                                  | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>         |                                   |
|                                                                                                                                   |                                                  | Filing Date:<br><b>June 30, 2017</b>                     | Group:<br><b>Not Yet Assigned</b> |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i> | Other Art<br><i>See Page 10-11</i>                       |                                   |

### Foreign Patent Documents

| Exam. Init. | Ref. Des. | Document Number | Date     | Country | Language |
|-------------|-----------|-----------------|----------|---------|----------|
|             | B32       | WO 2011026942   | 3/10/11  | WIPO    | English  |
|             | B33       | WO 2012056217   | 5/3/12   | WIPO    | English  |
|             | B34       | WO 2012177367   | 12/27/12 | WIPO    | English  |
|             | B35       | WO 2013013229   | 1/24/13  | WIPO    | English  |
|             | B36       | WO 2013093035   | 6/27/13  | WIPO    | English  |
|             | B37       | WO 9307471      | 4/15/93  | WIPO    | English  |
|             | B38       | WO 9316368      | 8/16/93  | WIPO    | English  |
|             | B39       | WO 9429695      | 12/22/94 | WIPO    | English  |
|             | B40       | WO 9714066A2    | 4/17/97  | WIPO    | English  |

### Other Art (Including Author, Title, Date Pertinent Pages, Etc.)

| Exam. Init. | Ref. Des. | Citation                                                                                                                                                   |
|-------------|-----------|------------------------------------------------------------------------------------------------------------------------------------------------------------|
|             | C1        | Brogioli et al., "Heterodyne near-field scattering," <i>Applied Physics Letters</i> 81(22):4109-4111, 2002.                                                |
|             | C2        | Extended European Search Report for EP 13796734.5, mailed March 18, 2016                                                                                   |
|             | C3        | Goda et al., "Serial time-encoded amplified imaging for observation of fast dynamic phenomena," <i>Nature</i> 458:1145-1149. 2009                          |
|             | C4        | International Search Report and Written Opinion for PCT/US2013/043453 mailed December 20, 2013.                                                            |
|             | C5        | International Search Report and Written Opinion for PCT/US2014/067682 mailed April 9, 2015.                                                                |
|             | C6        | Office Action issued in Japanese Patent Application No. 2015-515208, issued May 29, 2017 (English Translation Provided) (Attorney Docket No. BECC.P0002JP) |
|             | C7        | Schmidt, B., "Ein lichtstarkes komafreies Spiegelsystem," <i>Mitteilungen der Haburger Sternwarte in Bergedorf</i> 7(36):15-17, 1932.                      |

28461423.1

**EXAMINER:****DATE CONSIDERED:**

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.



|                                                                                                                                   |                                                                                 |                                    |
|-----------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------|------------------------------------|
| Form PTO-1449 (modified)                                                                                                          | Atty. Docket No.:<br><b>BECC.P0002US.CIP.C1/11706355</b>                        | Serial No.:<br><b>15/638,461</b>   |
| List of Patents and Publications for Applicant's<br><br>INFORMATION DISCLOSURE STATEMENT<br><br>(Use several sheets if necessary) | Applicant:<br><br><b>IRIS INTERNATIONAL, INC</b>                                |                                    |
|                                                                                                                                   | Filing Date:<br><b>June 30, 2017</b>                                            | Group:<br><b>Not Yet Assigned</b>  |
| U.S. Patent Documents<br><i>See Page 1-8</i>                                                                                      | Foreign Patent Documents<br><i>See Page 8-11</i>                                | Other Art<br><i>See Page 10-11</i> |
| <b>Other Art (Including Author, Title, Date Pertinent Pages, Etc.)</b>                                                            |                                                                                 |                                    |
| C8                                                                                                                                | Smiley, C. H., "The Schmidt Camera," <i>Popular Astronomy</i> 44:415-421, 1936. |                                    |

28461423.1

EXAMINER: /MINDY D VU/

DATE CONSIDERED: 06/13/2018

EXAMINER: INITIAL IF REFERENCE CONSIDERED, WHETHER OR NOT CITATION IS IN CONFORMANCE WITH MPEP609; DRAW LINE THROUGH CITATION IF NOT IN CONFORMANCE AND NOT CONSIDERED. INCLUDE COPY OF THIS FORM WITH NEXT COMMUNICATION TO APPLICANT.

|                                                                                                                        |                                                |                                                                      |
|------------------------------------------------------------------------------------------------------------------------|------------------------------------------------|----------------------------------------------------------------------|
| <b><i>Index of Claims</i></b><br><br> | <b>Application/Control No.</b><br><br>15638461 | <b>Applicant(s)/Patent Under Reexamination</b><br><br>CHEN, YONG QIN |
|                                                                                                                        | <b>Examiner</b><br><br>MINDY VU                | <b>Art Unit</b><br><br>2884                                          |

|   |                 |   |                   |   |                     |   |                 |
|---|-----------------|---|-------------------|---|---------------------|---|-----------------|
| ✓ | <b>Rejected</b> | - | <b>Cancelled</b>  | N | <b>Non-Elected</b>  | A | <b>Appeal</b>   |
| = | <b>Allowed</b>  | ÷ | <b>Restricted</b> | I | <b>Interference</b> | O | <b>Objected</b> |

| <input type="checkbox"/> Claims renumbered in the same order as presented by applicant |          | <input type="checkbox"/> CPA |  | <input type="checkbox"/> T.D. |  | <input type="checkbox"/> R.1.47 |  |  |  |
|----------------------------------------------------------------------------------------|----------|------------------------------|--|-------------------------------|--|---------------------------------|--|--|--|
| CLAIM                                                                                  |          | DATE                         |  |                               |  |                                 |  |  |  |
| Final                                                                                  | Original | 06/18/2018                   |  |                               |  |                                 |  |  |  |
|                                                                                        | 364      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 365      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 366      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 367      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 368      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 369      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 370      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 371      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 372      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 373      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 374      | O                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 375      | O                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 376      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 377      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 378      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 379      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 380      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 381      | O                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 382      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 383      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 384      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 385      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 386      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 387      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 388      | ✓                            |  |                               |  |                                 |  |  |  |
|                                                                                        | 389      | ✓                            |  |                               |  |                                 |  |  |  |

**IN THE UNITED STATES PATENT AND TRADEMARK OFFICE**

First Named Inventor: Yong Qin CHEN

App. No.: 15/638,461

Group Art Unit: 2884

Filed: June 30, 2017

Examiner: VU, Mindy D.

Customer No.: 129381

Atty. Dkt. No.:

BECC.P0002US.CIP.C1/1000195036

Title: FLOW CYTOMETER

Confirmation No.: 9847

M/S: Amendment  
Commissioner for Patents  
PO Box 1450  
Alexandria, VA 22313-1450

**CERTIFICATE OF ELECTRONIC TRANSMISSION**  
37 C.F.R. § 1.8

I hereby certify that this correspondence is being electronically filed with the United States Patent and Trademark Office via EFS-Web on the date below:

November 29, 2018  
Date

/Mark G. Tison/  
Mark G. Tison

**RESPONSE TO NON-FINAL OFFICE ACTION**

Dear Commissioner:

In response to the Non-Final Office Action mailed June 29, 2018 (the “Action”), please reconsider the above-identified application in light of the following remarks. A petition for a two-month extension of time, with appropriate fee, is filed concurrently via EFS. Accordingly, with the two-month extension of time, this response is properly filed on or before November 29, 2018. No additional fees are believed due in connection with this response; however, should Applicant’s payment information be missing, or any other fees be due, Applicant authorizes the Commissioner to debit the deficiency or fee from Norton Rose Fulbright US LLP’s Deposit Account No. 50-1212/1000195036.

**Amendments to the Claims** are reflected in the listing of claims, which begins on page 2 of this paper.

**Remarks** begin on page 8 of this paper.

# AMENDMENTS TO THE CLAIMS

This listing of claims will replace all prior versions, and listings, of claims in the application:

1-363. (Canceled).

364. (Currently Amended) An optical ~~module~~ subsystem for a flow cytometer, the optical ~~module~~ subsystem comprising:

~~(a) a light source;~~

~~(b)~~ a collimating optical element arranged to receive light from ~~the~~ a light source, the collimating optical element configured to project a collimated beam; ~~and~~

~~(c)~~ an optical relay element arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay element comprising a curved mirror configured to ~~project at least a~~ reflect the portion of the collimated beam received from the collimating optical element to produce a first image;

a first focusing optical element, ~~wherein the optical relay is one of a curved mirror and a refractive lens~~ arranged to receive at least a portion of the collimated beam reflected by the optical relay element; and

a first semiconductor detector.

wherein the first focusing optical element is configured to focus the portion of the collimated beam received from the optical relay element onto the first semiconductor detector.

365. (Currently Amended) The optical ~~module~~ subsystem of claim 364, further comprising the light source, wherein the light source ~~is one of~~ comprises light passing through a pinhole ~~and~~ or light emitted from a facet of a multimode optical fiber.

366. (Currently Amended) The optical ~~module~~ subsystem of claim 365, wherein the first focusing optical element is configured to focus the portion of the collimated beam received from the optical relay element to a size smaller than 1 millimeter in diameter ~~to a first semiconductor detector.~~

367. (Currently Amended) The optical ~~module~~ subsystem of ~~claim 364~~ claim 365, wherein the light source forms an object, wherein the collimating optical element is configured to project a magnified image of the object, wherein the optical ~~relay is~~ relay element comprises a concave mirror having a radius of curvature approximately equal to the distance between the collimating optical element and the magnified image projected thereby.

368. (Canceled).

369. (Currently Amended) The optical ~~module~~ subsystem of claim 364, wherein the collimating optical element ~~is~~ comprises an achromatic doublet lens.

370. (Currently Amended) The optical ~~module~~ subsystem of claim 364, further comprising a first optical filter ~~arranged~~ disposed along an optical path between the collimating optical element and the optical relay element, the first optical filter configured to separate the collimated beam into a first branch and a second branch.

371. (Currently Amended) The optical ~~module~~ subsystem of claim 370, wherein the collimated beam comprises light of a plurality of wavelengths, wherein the first optical filter is configured to reflect light of a first range of wavelengths of the plurality of wavelengths to form the first branch of the collimated beam, wherein the first optical filter is configured to pass light of a second range of wavelengths of the plurality of wavelengths to form the second branch of the collimated beam, wherein the first branch ~~is directed to~~ includes the portion of the collimated beam projected from the collimating optical element and received by the optical relay element.

372. (Currently Amended) The optical ~~module~~ subsystem of claim 371, further comprising a second focusing optical element and a second semiconductor detector, the second focusing optical element arranged to receive the second branch of the collimated beam, ~~the second focusing optical element and~~ configured to focus the second branch of the collimated beam to a onto the second semiconductor detector.

373. (Currently Amended) The optical ~~module~~ subsystem of claim 372, wherein the diameter of the portion of the collimated beam ~~between~~ reflected by the optical relay element and

received by the first focusing optical element is substantially the same as the diameter of the second branch of the collimated beam~~between the collimating optical element and the second focusing optical element.~~

374. (Currently Amended) The optical ~~module~~ subsystem of claim 372, further comprising a second optical filter, the second optical filter arranged along an optical path between the optical relay element and the first focusing optical element, the second optical filter configured to pass light of a third range of wavelengths in the first branch of the collimated beam to the first focusing optical element, wherein the third range of wavelengths is a subset of the first range of wavelengths.

375. (Currently Amended) The optical ~~module~~ subsystem of claim 374, ~~wherein~~ further comprising successive combinations of optical relay element, optical filter, and focusing optical element ~~are~~ cascaded to produce focused spots having a diameter of less than 1 millimeter for multiple ranges of wavelengths of light of the collimated beam.

376. (Currently Amended) An optical ~~module~~ subsystem for a flow cytometer, the optical ~~module~~ subsystem comprising:

~~(a) a light source;~~

~~(b)~~ a collimating optical element arranged to receive light from ~~the~~ a light source, the collimating optical element configured to project a collimated beam ~~and~~ including a first image, wherein the collimated beam has a collimated distance; and

~~(c)~~ an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam,

wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter configured to produce a second image.

377. (Canceled).

378. (Currently Amended) The optical ~~module~~ subsystem of claim 376, ~~wherein the optical relay projects a second image,~~ wherein the second image and the first image are substantially the same size.

379. (Currently Amended) The optical ~~module~~ subsystem of claim 376, ~~wherein the optical relay projects a second image~~, wherein the collimated beam from the collimating optical element to the first image has substantially the same diameter as the collimated beam from the optical relay element to the second image.

380. (Currently Amended) The optical ~~module~~ subsystem of claim 376, further comprising a first focusing optical element arranged to receive the collimated beam from the optical relay element at the extended collimated distance, the first focusing optical element configured to focus the ~~extended~~ collimated beam onto a first semiconductor detector.

381. (Currently Amended) The optical ~~module~~ subsystem of claim 380, further comprising:

an optical filter arranged along an optical path between the collimating optical element and the optical relay element, the optical filter configured to separate the collimated beam into a first branch and a second branch, wherein the first branch and the second branch ~~are~~ comprise light of different colors, wherein the optical relay ~~receives~~ element is arranged to receive the first branch; and

a second focusing optical element arranged to receive the second branch, the second focusing optical element configured to focus the second branch to a second semiconductor detector.

382. (Currently Amended) The optical ~~module~~ subsystem of claim 380, wherein the length of an optical distance path of the collimated beam from the collimating optical element to the optical relay element is substantially the same as the length of an optical distance path of the collimated beam from the optical relay element to the first focusing optical element.

383. (Currently Amended) An optical ~~module~~ subsystem for a flow cytometer, the optical ~~module~~ subsystem comprising:

- ~~(a) a light source providing light that forms an object;~~
- ~~(b) a collimating optical element arranged to receive light from the a light source, the collimating optical element configured to project a first image of the object; and~~

(e) an optical relay element arranged near the first image, the optical relay element configured to receive light from the collimating optical element and to project a second image ~~of the object~~;

wherein the size of the first image is substantially the same as the size of the second image, and

wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter.

384. (Currently Amended) The optical ~~module~~ subsystem of claim 383, wherein the optical distance from the collimating optical element to the first image is substantially the same as the optical distance from the optical relay element to the second image.

385. (Currently Amended) The optical ~~module~~ subsystem of claim 383, further comprising the light source, wherein the light source ~~is~~ comprises an extended light source that forms ~~the~~ an object, wherein the first image is a magnified image of the object.

386. (Currently Amended) The optical ~~module~~ subsystem of claim 385, wherein the light source ~~is one of~~ comprises light passing through a pinhole ~~and~~ or light emitted from a facet of a multimode optical fiber.

387. (Currently Amended) The optical ~~module~~ subsystem of claim 385, wherein the collimating optical element has an effective size defined by its cross section in a plane parallel to the first image, wherein the size of the first image is substantially the same as the effective size of the collimating optical element.

388. (Currently Amended) The optical ~~module~~ subsystem of claim 385, wherein the first image is less than approximately 10 times the size of the object.

389. (Currently Amended) The optical ~~module~~ subsystem of claim 385 further comprising a first focusing optical element arranged near the second image, the first focusing optical element configured to focus the light from the optical relay element to a size smaller than the object of the light source to a first semiconductor detector.



390. (New) The optical subsystem of claim 364, wherein the collimating optical element is further configured to produce a second image, wherein the first image is a reimage of the second image.

391. (New) The optical subsystem of claim 364, wherein the first image is an image of the collimating optical element.

## **REMARKS**

### **Status of the Claims**

Claims 1-363 were previously canceled without prejudice or disclaimer prior to this response. With this response, claims 368 and 377 have been canceled without prejudice or disclaimer, claims 364-367, 369-376, and 378-389 have been amended, and new claims 390 and 391 have been added. No new matter has been added. Support for the claim amendments and the new claims can be found in the published Application at least at ¶¶ [0282], [0401]-[0423], [0445], [0464], and FIGS. 25, 27, and 28.

### **Incompleteness Of The Office Action**

In rejecting one or more claims, the Office identified U.S. Pat. App. Pub. No. 2003/0044967 to Oostman, Jr. et al. However, U.S. Pat. App. Pub. No. 2003/0044967 corresponds to Heffelfinger et al. and does not correspond to Oostman, Jr. et al. Applicant is unable to readily identify with certainty which reference the Office intended to apply as Oostman, Jr. et al. Accordingly, the Office Action is incomplete with respect to all matters and Applicant has not been given a fair opportunity to respond to each of the rejections presented by the Office. Applicant respectfully submits that at least because the current Office Action is incomplete, that a next Office Action in this case cannot be made final.

### **Allowable Subject Matter**

Applicant thanks the Examiner for indicating that claim 374, 375, and 381 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims.

### **Claim Objections**

The Office objected to claim 383 because of an informality. Claim 383 has been amended to correct the informality rendering the objection moot. Withdrawal of the objection is requested.

### **35 U.S.C. § 112(a)**

The Office rejected claim 368, under 35 U.S.C. § 112(a), as allegedly failing to comply with the enablement requirement. Claim 368 has been canceled without prejudice or disclaimer, rendering the rejection moot. Withdrawal of the 35 U.S.C. § 112(a) rejection is requested.


**Claims 364-366, 370-372, 376, 378-380, 383, and 385-389**

The Office rejected claims 364-366, 370-372, 376-380, 383, and 385-389, under 35 U.S.C. § 102(a), as allegedly being anticipated by U.S. Pat. App. Pub. No. 2003/0044967 (“Heffelfinger”). Claim 377 has been canceled without prejudice or disclaimer. Without agreeing with the Office, and in an effort to advance prosecution, each of claims 364, 376, and 383 has been amended.

Claims 364-366 and 370-372

The cited portions of Heffelfinger fail to disclose the specific combination of claim 364. For example, Heffelfinger fails to disclose “an optical relay element arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay element comprising a curved mirror configured to reflect the portion of the collimated beam received from the collimating optical element to produce a first image”, as in claim 364.

*Heffelfinger does not disclose an optical relay element that includes a curved mirror (and/or a concave-shaped dichroic filter).* In rejecting claim 364, the Office identified relay lens 42 and ¶¶ [0047] and [0049] of Heffelfinger as allegedly corresponding to and describing an optical relay. Heffelfinger describes an apparatus and method in which illumination light and collected emitted light share a pathway and subsequently are physically separated. *See* Heffelfinger at Title and Abstract. Referring to FIG. 1 (reproduced below) of Heffelfinger, Heffelfinger describes that a first laser 12 emits laser light 20 that is directed by steering mirror 16 through beam combiner (e.g. dichroic mirror) 18, and a second laser 14 directs a second laser light 22 to beam combiner 18 that combines first laser light 20 and second laser light 22 into illumination beam 24. *See* Heffelfinger at ¶ [0036].

**FIG. 1**

In Heffelfinger, illumination beam 24 is directed by steering mirror 26 through laser line filter 28 (e.g., band pass interference filters and absorption filters) and is impinged upon beam splitter 30 which directs a portion of the beam through focus detection lens 32 and onto output detector 34. *See* Heffelfinger at ¶¶ [0043] and [0044]. Additionally, beam splitter 30 may split diverted beam 25 into two component beams with each beam composed of a subset of the wavelengths of beam 25. *Id.* The light from excitation beam 24 that is not diverted to output detector 34 passes through zoom contractor/expander optics 36 and onto beam splitter optic 38. *See* Heffelfinger at ¶¶ [0045] and [0046]. Beam splitter 38 directs the excitation wavelengths onto beam scanner 40 (e.g., a galvanometer mirror, a rotating polygonal mirror, a resonant scanner, or an acousto-optical scanner, such as a Bragg cell) which produces a line scan of the focused beam. *See* Heffelfinger at ¶ [0046]. The beam is directed to relay lens 42 and is then directed by steering mirror 44 through objective relay lens 46 and objective 48 onto target substrate 50. *See* Heffelfinger at ¶¶ [0047] and [0049].

Additionally, with reference to FIG. 1B (reproduced below) of Heffelfinger, Heffelfinger


further states:

As illustrated in FIG. 1B, a Bragg cell may be used to effect the beam spot line scan. In this embodiment, fixed mirrors 61, 62, 63 direct excitation beam 80 to Bragg cell 65 at an angle  $\theta$  relative to the optical axis. RF drive 67 introduces an acoustic sound field within the Bragg cell. This acoustic field causes the excitation beam to be deflected through angle  $\theta'$ . This deflection produces a back and forth movement of the excitation beam along one axis. The optical scanner directs the beam to relay lenses 42 and 46 that keeps the focused laser light in register.

...

The light passes through relay lens 42 and is directed by steering mirror 44 through objective relay lens 46 and objective 48 and onto target substrate 50.

Heffelfinger at ¶¶ [0047] and [0049].



The cited portions of Heffelfinger are silent with respect to the relay lens 42 being a curved mirror and/or a concave-shaped dichroic filter. Therefore, Heffelfinger fails to disclose “an optical relay element arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay element comprising a curved mirror configured to reflect the portion of the collimated beam received from the collimating optical element to produce a first image”, as in claim 364.

***Further, Heffelfinger does not disclose an optical relay element (that includes a curved mirror) configured to reflect a portion of a collimated beam received from a collimating optical***

*element.* In rejecting claim 364, the Office identified relay lens 42 and ¶¶ [0047] and [0049] of Heffelfinger as allegedly corresponding to and describing an optical relay. As explained above, the beam splitter 38 directs the excitation wavelengths onto beam scanner 40 which produces a line scan of the focused beam that is directed to relay lens 42 and is then directed by steering mirror 44 through objective relay lens 46 and objective 48 onto target substrate 50. *See* Heffelfinger at ¶¶ [0046], [0047], and [0049]. Thus, Heffelfinger describes that the focused beam passes through relay lens 42. Heffelfinger does not describe that the relay lens reflects a portion of a collimated beam (received from a collimated optical element). For at least this additional reason, Heffelfinger fails to disclose the specific combination of claim 364.

Consequently, Heffelfinger fails to disclose each and every element of claim 364. Hence, claim 364 is patentable. Claims 365, 366, and 370-372 are patentable, at least by virtue of depending from a patentable claim.

#### Claims 376 and 378-380

The cited portions of Heffelfinger fail to disclose the specific combination of claim 364. For example, Heffelfinger fails to disclose “an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter configured to produce a second image”, as in claim 376.

As explained above, Heffelfinger describes an apparatus and method in which illumination light and collected emitted light share a pathway and subsequently are physically separated. *See* Heffelfinger at Title and Abstract. The cited portions of Heffelfinger are silent with respect to the relay lens 42 being a curved mirror and/or a concave-shaped dichroic filter. Therefore, Heffelfinger fails to disclose “an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter configured to produce a second image”, as in claim 376.

Consequently, Heffelfinger fails to disclose each and every element of claim 376. Hence, claim 376 is patentable. Claims 378-380 are patentable, at least by virtue of depending from a patentable claim.

Claims 383 and 385-389

As explained above, Heffelfinger does not disclose an optical relay element arranged to receive a collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, where the optical relay element includes a curved mirror or a concave-shaped dichroic filter configured to produce a second image. Therefore, Heffelfinger does not disclose “an optical relay element arranged near the first image, the optical relay element configured to receive light from the collimating optical element and to project a second image . . . wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter”, as in claim 383. Hence, claim 383 is patentable. Claims 385-389 are patentable, at least by virtue of depending from a patentable claim.

**Claims 364, 370, 376, 378, 380, and 382-387**

The Office rejected claims 364, 370, 376-378, 380, and 382-387, under 35 U.S.C. § 102(a), as allegedly being anticipated by U.S. Pat. App. Pub. No. 2003/0044967 (“Oostman”). As explained above, U.S. Pat. App. Pub. No. 2003/0044967 corresponds to Heffelfinger et al. and does not correspond to Oostman, Jr. et al. Applicant believes that the Office intended to identify U.S. Pat. No. 6,683,314 (“Oostman ‘314”) or U.S. Pat. No. 7,129,505 (“Oostman ‘505”), which is a continuation of Oostman ‘314. Accordingly, in an effort to advance prosecution, Applicant provides remarks based on Oostman ‘314. Claim 377 has been canceled without prejudice or disclaimer. Without agreeing with the Office, and in an effort to advance prosecution, each of claims 364, 376, and 383 has been amended.


Without agreeing with the Office, and in an effort to advance prosecution, claim 364 has been amended to recite:

Claims 364 and 370

The cited portions of Oostman ‘314 fail to disclose the specific combination of claim 364. For example, Oostman ‘314 fails to disclose “an optical relay element arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay element comprising a curved mirror configured to reflect the portion of the collimated beam received from the collimating optical element to produce a first image”, as in claim 364.

***Oostman ‘314 does not disclose an optical relay element that includes a curved mirror***

(*and/or a concave-shaped dichroic filter*). In rejecting claim 364, the Office identified element 151 and col. 6, lines 40-50 of Oostman '314 as allegedly corresponding to an optical relay. Oostman '314 describes a fluorescence detection instrument with reflective transfer legs for color decimation. See Oostman '314 at Title and Abstract. Referring to FIG. 5 (reproduced below) of Oostman '314, Oostman '314 describes a top planar polygonal detector arrangement showing decimation of an incoming beam with reflective transfer leg beam splitters, where the incoming beam is received from a fiber bundle. See Oostman '314 at 4:60-64 and 6:40-50.



In Oostman '314, the fluorescence detection instrument includes an optical fiber 122 having a fiber terminal 143, a collimating lens 145, beam splitting elements 151 (i.e., dichroic mirrors), and focusing elements 158, 168 to form a beam 155 emitted from a light source (e.g., 123), and a photomultiplier tube 159 to detect the beam 155. See Oostman '314 at 6:40-49. Referring to FIG. 5, it is noted that the beam splitting elements 151 are depicted as planar optical elements and are **not** curved. It is further noted that the only optical elements that are curved include the collimating lens 145 and the focusing elements 158, 168.



Oostman '314 further describes FIG. 5 and states:

The optical fiber 123 has a fiber terminal 143, which allow emergence of light and formation of a beam by means of a collimating lens 145. The output beam 147 is directed toward a beam-turning mirror 149 directing light at a first beam splitting element 151 which is a dichroic mirror transmitting light in beam 155 in a transmitted detector leg toward a filter 156, a beam-turning element 157, and a focusing element 158 which directs the beam onto a light sensitive element of a photomultiplier tube 159. The tube is adjusted so that its most sensitive area is exposed to the incoming beam. This beam is known as the transmitted detector leg because it is transmitted through the beam splitting element 151. The beam splitting element has a coating which allows transmission of one band of optical signals, while reflecting light in another band in the form of beam 153 which forms a reflective transfer leg for the light which was originally in beam 147. The reflective transfer leg 153 is seen to fall upon another beam splitting element 161 which is a dichroic mirror having different optical characteristics from the beam splitter 151. The colors removed by beam splitter 161, as well as the other beam splitters, are different, each beam splitter removing a selected band of colored light in the same manner, but different wavelengths . . .

Oostman '314 at 6:40-64. The cited portions of Oostman '314 are silent with respect to the beam splitting elements 151 being a curved mirror and/or a concave-shaped dichroic filter. Therefore, Oostman '314 fails to disclose “an optical relay element arranged to receive at least a portion of the collimated beam from the collimating optical element, the optical relay element comprising a curved mirror configured to reflect the portion of the collimated beam received from the collimating optical element to produce a first image”, as in claim 364.

Consequently, Oostman '314 fails to disclose each and every element of claim 364. Hence, claim 364 is patentable. Claim 370 is patentable, at least by virtue of depending from a patentable claim.

#### Claims 376, 378, 380, and 382

The cited portions of Oostman '314 fail to disclose the specific combination of claim 364. For example, Oostman '314 fails to disclose “an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter configured to produce a second image”, as in claim 376.

As explained above, Oostman '314 describes a fluorescence detection instrument with

reflective transfer legs for color decimation. *See* Oostman '314 at Title and Abstract. The cited portions of Oostman '314 are silent with respect to the beam splitting elements 151 being a curved mirror and/or a concave-shaped dichroic filter. Therefore, Oostman '314 fails to disclose “an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter configured to produce a second image”, as in claim 376.

Consequently, Oostman '314 fails to disclose each and every element of claim 376. Hence, claim 376 is patentable. Claims 378, 380, and 382 are patentable, at least by virtue of depending from a patentable claim.

#### Claims 383-387

As explained above, Oostman '314 does not disclose an optical relay element arranged to receive a collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, where the optical relay element includes a curved mirror or a concave-shaped dichroic filter configured to produce a second image. Therefore, Oostman '314 does not disclose “an optical relay element arranged near the first image, the optical relay element configured to receive light from the collimating optical element and to project a second image . . . wherein the optical relay element comprises a curved mirror or a concave-shaped dichroic filter”, as in claim 383. Hence, claim 383 is patentable. Claims 384-387 are patentable, at least by virtue of depending from a patentable claim.

#### **Claim 369**

The Office rejected claim 369, under 35 U.S.C. § 103(a), as allegedly being unpatentable over Heffelfinger in view of U.S. Pat. No. 4,385,234 (“Johnson”). Applicant disagrees with the rejection.

Claim 369 depends from claim 364. As explained above, claim 364 is patentable over Heffelfinger. The Office has not shown that Johnson would supply the deficiencies of Heffelfinger, and dependent claim 369 is therefore patentable over Heffelfinger and Johnson for at least the same reasons. Reconsideration and withdrawal of the rejection is requested.

**Claim 366**

The Office rejected claim 366, under 35 U.S.C. § 103(a), as allegedly being unpatentable over U.S. Pat. App. Pub. No. 2003/0044967 (“Oostman”). As explained above, U.S. Pat. App. Pub. No. 2003/0044967 corresponds to Heffelfinger et al. and does not correspond to Oostman, Jr. et al. Applicant believes that the Office intended to identify Oostman ‘314 or Oostman ‘505, which is a continuation of Oostman ‘314. Accordingly, in an effort to advance prosecution, Applicant provides remarks based on Heffelfinger and, alternatively, Oostman ‘314. Applicant disagrees with the rejection.

Claim 366 depends from claim 364. As explained above, claim 364 is patentable over each of Heffelfinger and Oostman ‘314. Therefore, claim 366 is patentable, at least by virtue of depending from a patentable claim. Reconsideration and withdrawal of the rejection is requested.

**Claim 367**

The Office rejected claim 367, under 35 U.S.C. § 103(a), as allegedly being unpatentable over U.S. Pat. App. Pub. No. 2003/0044967 (“Oostman”) in view of U.S. Pat. App. Pub. No. 2005/0002425 (“Govorkov”). As explained above, U.S. Pat. App. Pub. No. 2003/0044967 corresponds to Heffelfinger et al. and does not correspond to Oostman, Jr. et al. Applicant believes that the Office intended to identify Oostman ‘314 or Oostman ‘505, which is a continuation of Oostman ‘314. Accordingly, in an effort to advance prosecution, Applicant provides remarks based on Heffelfinger and, alternatively, Oostman ‘314. Applicant disagrees with the rejection.

Claim 367 depends from claim 364. As explained above, claim 364 is patentable over each of Heffelfinger and Oostman ‘314. The Office has not shown that Govorkov would supply the deficiencies of Heffelfinger or Oostman ‘314, and dependent claim 367 is therefore patentable over Heffelfinger and Govorkov, or Oostman ‘314 and Govorkov, for at least the same reasons. Reconsideration and withdrawal of the rejection is requested.

**Claim 373**

The Office rejected claim 373, under 35 U.S.C. § 103(a), as allegedly being unpatentable over Heffelfinger. Applicant disagrees with the rejection.

Claim 373 depends from claim 364. As explained above, claim 364 is patentable over

Heffelfinger. Therefore, claim 373 is patentable, at least by virtue of depending from a patentable claim. Reconsideration and withdrawal of the rejection is requested.

**Claims 374, 375, and 381**

Applicant thanks the Examiner for indicating that claim 374, 375, and 381 are objected to as being dependent upon a rejected base claim, but would be allowable if rewritten in independent form including all of the limitations of the base claim and any intervening claims. Claims 374 and 375 depend from claim 364, which Applicant has shown to be patentable. Hence, claims 374 and 375 are patentable, at least by virtue of depending from a patentable claim. Claim 381 depends from claim 376, which Applicant has shown to be patentable. Hence, claim 381 is patentable, at least by virtue of depending from a patentable claim.

**New Claims 390 and 391**

New claims 390 and 391 have been added and are supported by the Specification. No new matter has been added. Claims 390 and 391 depend from claim 364, which Applicant has shown to be patentable. Hence, claims 390 and 391 are patentable, at least by virtue of depending from a patentable claim.

\* \* \*

**CONCLUSION**

The pending claims are in condition for allowance for at least the reasons set forth above. Applicant does not acquiesce to the Office's characterizations of the claim language or the cited reference(s), and reserves the right to challenge any such characterizations in the future. Any changes to the claims in this response, which have not been specifically noted to overcome a rejection based upon the cited portions of the above-cited reference(s), should be considered to have been made for a purpose unrelated to patentability, and no estoppel should be deemed to attach thereto. The Examiner is invited to contact the undersigned attorney at the telephone number listed below if such a call would in any way facilitate allowance of this application.

Respectfully submitted,

Date: November 29, 2018

/Mark G. Tison/  
Mark G. Tison, Reg. No. 65,985  
NORTON ROSE FULBRIGHT US LLP  
98 San Jacinto Blvd., Suite 1100  
Austin, TX 78701  
Telephone: (512) 536-3033  
Facsimile: (512) 536-4598

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

|                                                             |                                |                                                            |
|-------------------------------------------------------------|--------------------------------|------------------------------------------------------------|
| <b>PETITION FOR EXTENSION OF TIME UNDER 37 CFR 1.136(a)</b> |                                | Docket Number (Optional)<br>BECC.P0002UC.CIP.C1/1000195036 |
| Application Number<br><b>15/638,461</b>                     | Filed<br><b>June 30, 2017</b>  |                                                            |
| For<br><b>Flow Cytometer</b>                                |                                |                                                            |
| Art Unit<br><b>2884</b>                                     | Examiner<br><b>Mindy D. Vu</b> |                                                            |

This is a request under the provisions of 37 CFR 1.136(a) to extend the period for filing a reply in the above-identified application.

The requested extension and fee are as follows (check time period desired and enter the appropriate fee below):

|                                                                    | <u>Fee</u> | <u>Small Entity Fee</u> | <u>Micro Entity Fee</u> |               |
|--------------------------------------------------------------------|------------|-------------------------|-------------------------|---------------|
| <input type="checkbox"/> One month (37 CFR 1.17(a)(1))             | \$200      | \$100                   | \$50                    | \$ _____      |
| <input checked="" type="checkbox"/> Two months (37 CFR 1.17(a)(2)) | \$600      | \$300                   | \$150                   | \$ <b>600</b> |
| <input type="checkbox"/> Three months (37 CFR 1.17(a)(3))          | \$1,400    | \$700                   | \$350                   | \$ _____      |
| <input type="checkbox"/> Four months (37 CFR 1.17(a)(4))           | \$2,200    | \$1,100                 | \$550                   | \$ _____      |
| <input type="checkbox"/> Five months (37 CFR 1.17(a)(5))           | \$3,000    | \$1,500                 | \$750                   | \$ _____      |

☐ Applicant asserts small entity status. See 37 CFR 1.27.☐ Applicant certifies micro entity status. See 37 CFR 1.29.  
Form PTO/SB/15A or B or equivalent must either be enclosed or have been submitted previously.☐ A check in the amount of the fee is enclosed.☒ Payment by credit card. Form PTO-2038 is attached.☐ The Director has already been authorized to charge fees in this application to a Deposit Account.☒ The Director is hereby authorized to charge any fees which may be required, or credit any overpayment, to  
Deposit Account Number 50-1212/1000195036.☒ Payment made via EFS-Web.**WARNING: Information on this form may become public. Credit card information should not be included on this form. Provide credit card information and authorization on PTO-2038.**

I am the

☐ applicant.☒ attorney or agent of record. Registration number 65,985.☐ attorney or agent acting under 37 CFR 1.34. Registration number \_\_\_\_\_./Mark G. Tison/

Signature

November 29, 2018

Date

Mark G. Tison

Typed or printed name

(512) 536-3033

Telephone Number

**NOTE:** This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. Submit multiple forms if more than one signature is required, see below\*.☐ \* Total of \_\_\_\_\_ forms are submitted.

This collection of information is required by 37 CFR 1.136(a). The information is required to obtain or retain a benefit by the public, which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 6 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Mail Stop PCT, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

## Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (*i.e.*, GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

## Electronic Patent Application Fee Transmittal

|                                                       |                          |                 |               |                             |
|-------------------------------------------------------|--------------------------|-----------------|---------------|-----------------------------|
| <b>Application Number:</b>                            | 15638461                 |                 |               |                             |
| <b>Filing Date:</b>                                   | 30-Jun-2017              |                 |               |                             |
| <b>Title of Invention:</b>                            | FLOW CYTOMETER           |                 |               |                             |
| <b>First Named Inventor/Applicant Name:</b>           | Yong Qin Chen            |                 |               |                             |
| <b>Filer:</b>                                         | Mark G Tison/Julia Hohle |                 |               |                             |
| <b>Attorney Docket Number:</b>                        | BECC.P0002US.CIP.C1      |                 |               |                             |
| Filed as Large Entity                                 |                          |                 |               |                             |
| <b>Filing Fees for    Utility under 35 USC 111(a)</b> |                          |                 |               |                             |
| <b>Description</b>                                    | <b>Fee Code</b>          | <b>Quantity</b> | <b>Amount</b> | <b>Sub-Total in USD(\$)</b> |
| <b>Basic Filing:</b>                                  |                          |                 |               |                             |
| <b>Pages:</b>                                         |                          |                 |               |                             |
| <b>Claims:</b>                                        |                          |                 |               |                             |
| <b>Miscellaneous-Filing:</b>                          |                          |                 |               |                             |
| <b>Petition:</b>                                      |                          |                 |               |                             |
| <b>Patent-Appeals-and-Interference:</b>               |                          |                 |               |                             |
| <b>Post-Allowance-and-Post-Issuance:</b>              |                          |                 |               |                             |
| <b>Extension-of-Time:</b>                             |                          |                 |               |                             |



| Description                        | Fee Code | Quantity | Amount | Sub-Total in USD(\$) |
|------------------------------------|----------|----------|--------|----------------------|
| Extension - 2 months with \$0 paid | 1252     | 1        | 600    | 600                  |
| <b>Miscellaneous:</b>              |          |          |        |                      |
| <b>Total in USD (\$)</b>           |          |          |        | <b>600</b>           |

## Electronic Acknowledgement Receipt

|                                             |                             |
|---------------------------------------------|-----------------------------|
| <b>EFS ID:</b>                              | 34436903                    |
| <b>Application Number:</b>                  | 15638461                    |
| <b>International Application Number:</b>    |                             |
| <b>Confirmation Number:</b>                 | 9847                        |
| <b>Title of Invention:</b>                  | FLOW CYTOMETER              |
| <b>First Named Inventor/Applicant Name:</b> | Yong Qin Chen               |
| <b>Customer Number:</b>                     | 32425                       |
| <b>Filer:</b>                               | Mark G Tison/Julia Hohle    |
| <b>Filer Authorized By:</b>                 | Mark G Tison                |
| <b>Attorney Docket Number:</b>              | BECC.P0002US.CIP.C1         |
| <b>Receipt Date:</b>                        | 29-NOV-2018                 |
| <b>Filing Date:</b>                         | 30-JUN-2017                 |
| <b>Time Stamp:</b>                          | 15:09:26                    |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a) |

### Payment information:

|                                          |                       |
|------------------------------------------|-----------------------|
| Submitted with Payment                   | yes                   |
| Payment Type                             | CARD                  |
| Payment was successfully received in RAM | \$ 600                |
| RAM confirmation Number                  | 113018INTEFSW15105400 |
| Deposit Account                          |                       |
| Authorized User                          |                       |

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

|                              |                                                       |                                 |                                          |                  |                  |
|------------------------------|-------------------------------------------------------|---------------------------------|------------------------------------------|------------------|------------------|
|                              |                                                       |                                 |                                          |                  |                  |
| File Listing:                |                                                       |                                 |                                          |                  |                  |
| Document Number              | Document Description                                  | File Name                       | File Size(Bytes)/ Message Digest         | Multi Part /.zip | Pages (if appl.) |
| 1                            |                                                       | BECCP0002USCIPC1_ROA_filing.pdf | 285852                                   | yes              | 19               |
|                              |                                                       |                                 | 697f5f60cbb0988fe415eb2c69d299c24738349f |                  |                  |
|                              | Multipart Description/PDF files in .zip description   |                                 |                                          |                  |                  |
|                              | Document Description                                  |                                 | Start                                    | End              |                  |
|                              | Amendment/Req. Reconsideration-After Non-Final Reject |                                 | 1                                        | 1                |                  |
|                              | Claims                                                |                                 | 2                                        | 7                |                  |
|                              | Applicant Arguments/Remarks Made in an Amendment      |                                 | 8                                        | 19               |                  |
| Warnings:                    |                                                       |                                 |                                          |                  |                  |
| Information:                 |                                                       |                                 |                                          |                  |                  |
| 2                            | Extension of Time                                     | BECCP0002USCIPC1_EOT.pdf        | 153313                                   | no               | 2                |
|                              |                                                       |                                 | 236f1693a357f01e485ef5fbb8f5fa518f599b26 |                  |                  |
| Warnings:                    |                                                       |                                 |                                          |                  |                  |
| Information:                 |                                                       |                                 |                                          |                  |                  |
| 3                            | Fee Worksheet (SB06)                                  | fee-info.pdf                    | 30818                                    | no               | 2                |
|                              |                                                       |                                 | 477f962ae73baea0de3a8fdda90ec53690448352 |                  |                  |
| Warnings:                    |                                                       |                                 |                                          |                  |                  |
| Information:                 |                                                       |                                 |                                          |                  |                  |
| Total Files Size (in bytes): |                                                       |                                 | 469983                                   |                  |                  |

**This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.**

**New Applications Under 35 U.S.C. 111**

**If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.**

**National Stage of an International Application under 35 U.S.C. 371**

**If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.**

**New International Application Filed with the USPTO as a Receiving Office**

**If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.**

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

|                                                                                                                                 |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|---------------------------------------------------------------------------------------------------------------------------------|------------------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|--------------------------------------------|---------------|---------------------------|--|---------------------------------------|--|--|
| <b>PATENT APPLICATION FEE DETERMINATION RECORD</b><br>Substitute for Form PTO-875                                               |                                                                                          |                                                                                                                                                                                                                               |              | Application or Docket Number<br>15/638,461 |               | Filing Date<br>06/30/2017 |  | <input type="checkbox"/> To be Mailed |  |  |
| ENTITY: <input checked="" type="checkbox"/> LARGE <input type="checkbox"/> SMALL <input type="checkbox"/> MICRO                 |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
| <b>APPLICATION AS FILED - PART I</b>                                                                                            |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 |                                                                                          | (Column 1)                                                                                                                                                                                                                    | (Column 2)   |                                            |               |                           |  |                                       |  |  |
| FOR                                                                                                                             |                                                                                          | NUMBER FILED                                                                                                                                                                                                                  | NUMBER EXTRA | RATE (\$)                                  |               | FEE (\$)                  |  |                                       |  |  |
| <input type="checkbox"/> BASIC FEE<br>(37 CFR 1.16(a), (b), or (c))                                                             |                                                                                          | N/A                                                                                                                                                                                                                           | N/A          | N/A                                        |               |                           |  |                                       |  |  |
| <input type="checkbox"/> SEARCH FEE<br>(37 CFR 1.16(k), (l), or (m))                                                            |                                                                                          | N/A                                                                                                                                                                                                                           | N/A          | N/A                                        |               |                           |  |                                       |  |  |
| <input type="checkbox"/> EXAMINATION FEE<br>(37 CFR 1.16(o), (p), or (q))                                                       |                                                                                          | N/A                                                                                                                                                                                                                           | N/A          | N/A                                        |               |                           |  |                                       |  |  |
| TOTAL CLAIMS<br>(37 CFR 1.16(i))                                                                                                |                                                                                          | minus 20 =                                                                                                                                                                                                                    | *            | x \$80 =                                   |               |                           |  |                                       |  |  |
| INDEPENDENT CLAIMS<br>(37 CFR 1.16(h))                                                                                          |                                                                                          | minus 3 =                                                                                                                                                                                                                     | *            | x \$420 =                                  |               |                           |  |                                       |  |  |
| <input type="checkbox"/> APPLICATION SIZE FEE (37 CFR 1.16(s))                                                                  |                                                                                          | If the specification and drawings exceed 100 sheets of paper, the application size fee due is \$310 (\$155 for small entity) for each additional 50 sheets or fraction thereof. See 35 U.S.C. 41(a)(1)(G) and 37 CFR 1.16(s). |              |                                            |               |                           |  |                                       |  |  |
| <input type="checkbox"/> MULTIPLE DEPENDENT CLAIM PRESENT (37 CFR 1.16(j))                                                      |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
| * If the difference in column 1 is less than zero, enter "0" in column 2.                                                       |                                                                                          |                                                                                                                                                                                                                               |              | TOTAL                                      |               |                           |  |                                       |  |  |
| <b>APPLICATION AS AMENDED - PART II</b>                                                                                         |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 |                                                                                          | (Column 1)                                                                                                                                                                                                                    | (Column 2)   | (Column 3)                                 |               |                           |  |                                       |  |  |
| <b>AMENDMENT</b>                                                                                                                | 11/29/2018                                                                               | CLAIMS REMAINING AFTER AMENDMENT                                                                                                                                                                                              |              | HIGHEST NUMBER PREVIOUSLY PAID FOR         | PRESENT EXTRA | RATE (\$)                 |  | ADDITIONAL FEE (\$)                   |  |  |
|                                                                                                                                 | Total<br>(37 CFR 1.16(i))                                                                | * 26                                                                                                                                                                                                                          | Minus        | ** 26                                      | = 0           | x \$100 =                 |  | 0                                     |  |  |
|                                                                                                                                 | Independent<br>(37 CFR 1.16(h))                                                          | * 3                                                                                                                                                                                                                           | Minus        | *** 3                                      | = 0           | x \$460 =                 |  | 0                                     |  |  |
|                                                                                                                                 | <input type="checkbox"/> Application Size Fee (37 CFR 1.16(s))                           |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 | <input type="checkbox"/> FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               | TOTAL ADD'L FEE           |  | 0                                     |  |  |
|                                                                                                                                 |                                                                                          | (Column 1)                                                                                                                                                                                                                    | (Column 2)   | (Column 3)                                 |               |                           |  |                                       |  |  |
| <b>AMENDMENT</b>                                                                                                                |                                                                                          | CLAIMS REMAINING AFTER AMENDMENT                                                                                                                                                                                              |              | HIGHEST NUMBER PREVIOUSLY PAID FOR         | PRESENT EXTRA | RATE (\$)                 |  | ADDITIONAL FEE (\$)                   |  |  |
|                                                                                                                                 | Total<br>(37 CFR 1.16(i))                                                                | *                                                                                                                                                                                                                             | Minus        | **                                         | =             | x \$0 =                   |  |                                       |  |  |
|                                                                                                                                 | Independent<br>(37 CFR 1.16(h))                                                          | *                                                                                                                                                                                                                             | Minus        | ***                                        | =             | x \$0 =                   |  |                                       |  |  |
|                                                                                                                                 | <input type="checkbox"/> Application Size Fee (37 CFR 1.16(s))                           |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 | <input type="checkbox"/> FIRST PRESENTATION OF MULTIPLE DEPENDENT CLAIM (37 CFR 1.16(j)) |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
|                                                                                                                                 |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               | TOTAL ADD'L FEE           |  |                                       |  |  |
| * If the entry in column 1 is less than the entry in column 2, write "0" in column 3.                                           |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               | LIE                       |  |                                       |  |  |
| ** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 20, enter "20".                                       |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               | /ZURIASHWORK ZENEBE/      |  |                                       |  |  |
| *** If the "Highest Number Previously Paid For" IN THIS SPACE is less than 3, enter "3".                                        |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |
| The "Highest Number Previously Paid For" (Total or Independent) is the highest number found in the appropriate box in column 1. |                                                                                          |                                                                                                                                                                                                                               |              |                                            |               |                           |  |                                       |  |  |

This collection of information is required by 37 CFR 1.16. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

*If you need assistance in completing the form, call 1-800-PTO-9199 and select option 2.*



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

## NOTICE OF ALLOWANCE AND FEE(S) DUE

32425 7590 02/07/2019  
NORTON ROSE FULBRIGHT US LLP  
98 SAN JACINTO BOULEVARD  
SUITE 1100  
AUSTIN, TX 78701-4255

|                        |              |
|------------------------|--------------|
| EXAMINER               |              |
| BOOSALIS, FANI POLYZOS |              |
| ART UNIT               | PAPER NUMBER |
| 2884                   |              |

DATE MAILED: 02/07/2019

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
| 15/638,461      | 06/30/2017  | Yong Qin Chen        | BECC.P0002US.CIP.C1 | 9847             |

TITLE OF INVENTION: FLOW CYTOMETER

| APPLN. TYPE    | ENTITY STATUS | ISSUE FEE DUE | PUBLICATION FEE DUE | PREV. PAID ISSUE FEE | TOTAL FEE(S) DUE | DATE DUE   |
|----------------|---------------|---------------|---------------------|----------------------|------------------|------------|
| nonprovisional | UNDISCOUNTED  | \$1000        | \$0.00              | \$0.00               | \$1000           | 05/07/2019 |

**THE APPLICATION IDENTIFIED ABOVE HAS BEEN EXAMINED AND IS ALLOWED FOR ISSUANCE AS A PATENT. PROSECUTION ON THE MERITS IS CLOSED. THIS NOTICE OF ALLOWANCE IS NOT A GRANT OF PATENT RIGHTS. THIS APPLICATION IS SUBJECT TO WITHDRAWAL FROM ISSUE AT THE INITIATIVE OF THE OFFICE OR UPON PETITION BY THE APPLICANT. SEE 37 CFR 1.313 AND MPEP 1308.**

**THE ISSUE FEE AND PUBLICATION FEE (IF REQUIRED) MUST BE PAID WITHIN THREE MONTHS FROM THE MAILING DATE OF THIS NOTICE OR THIS APPLICATION SHALL BE REGARDED AS ABANDONED. THIS STATUTORY PERIOD CANNOT BE EXTENDED. SEE 35 U.S.C. 151. THE ISSUE FEE DUE INDICATED ABOVE DOES NOT REFLECT A CREDIT FOR ANY PREVIOUSLY PAID ISSUE FEE IN THIS APPLICATION. IF AN ISSUE FEE HAS PREVIOUSLY BEEN PAID IN THIS APPLICATION (AS SHOWN ABOVE), THE RETURN OF PART B OF THIS FORM WILL BE CONSIDERED A REQUEST TO REAPPLY THE PREVIOUSLY PAID ISSUE FEE TOWARD THE ISSUE FEE NOW DUE.**

### HOW TO REPLY TO THIS NOTICE:

I. Review the ENTITY STATUS shown above. If the ENTITY STATUS is shown as SMALL or MICRO, verify whether entitlement to that entity status still applies.

If the ENTITY STATUS is the same as shown above, pay the TOTAL FEE(S) DUE shown above.

If the ENTITY STATUS is changed from that shown above, on PART B - FEE(S) TRANSMITTAL, complete section number 5 titled "Change in Entity Status (from status indicated above)".

For purposes of this notice, small entity fees are 1/2 the amount of undiscounted fees, and micro entity fees are 1/2 the amount of small entity fees.

II. PART B - FEE(S) TRANSMITTAL, or its equivalent, must be completed and returned to the United States Patent and Trademark Office (USPTO) with your ISSUE FEE and PUBLICATION FEE (if required). If you are charging the fee(s) to your deposit account, section "4b" of Part B - Fee(s) Transmittal should be completed and an extra copy of the form should be submitted. If an equivalent of Part B is filed, a request to reapply a previously paid issue fee must be clearly made, and delays in processing may occur due to the difficulty in recognizing the paper as an equivalent of Part B.

III. All communications regarding this application must give the application number. Please direct all communications prior to issuance to Mail Stop ISSUE FEE unless advised to the contrary.

**IMPORTANT REMINDER: Maintenance fees are due in utility patents issuing on applications filed on or after Dec. 12, 1980. It is patentee's responsibility to ensure timely payment of maintenance fees when due. More information is available at**

**www.uspto.gov/Patent/MaintenanceFees.**

# **PART B - FEE(S) TRANSMITTAL**

Complete and send this form, together with applicable fee(s), by mail or fax, or via EFS-Web.

By mail, send to:     Mail Stop ISSUE FEE  
                                  Commissioner for Patents  
                                  P.O. Box 1450  
                                  Alexandria, Virginia 22313-1450

By fax, send to:     (571)-273-2885

**INSTRUCTIONS:** This form should be used for transmitting the ISSUE FEE and PUBLICATION FEE (if required). Blocks 1 through 5 should be completed where appropriate. All further correspondence including the Patent, advance orders and notification of maintenance fees will be mailed to the current correspondence address as indicated unless corrected below or directed otherwise in Block 1, by (a) specifying a new correspondence address; and/or (b) indicating a separate "FEE ADDRESS" for maintenance fee notifications.

CURRENT CORRESPONDENCE ADDRESS (Note: Use Block 1 for any change of address)

Note: A certificate of mailing can only be used for domestic mailings of the Fee(s) Transmittal. This certificate cannot be used for any other accompanying papers. Each additional paper, such as an assignment or formal drawing, must have its own certificate of mailing or transmission.

32425                      7590                      02/07/2019  
**NORTON ROSE FULBRIGHT US LLP**  
**98 SAN JACINTO BOULEVARD**  
**SUITE 1100**  
**AUSTIN, TX 78701-4255**

## **Certificate of Mailing or Transmission**

I hereby certify that this Fee(s) Transmittal is being deposited with the United States Postal Service with sufficient postage for first class mail in an envelope addressed to the Mail Stop ISSUE FEE address above, or being transmitted to the USPTO via EFS-Web or by facsimile to (571) 273-2885, on the date below.

|  |                         |
|--|-------------------------|
|  | (Typed or printed name) |
|  | (Signature)             |
|  | (Date)                  |

| APPLICATION NO. | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|-------------|----------------------|---------------------|------------------|
| 15/638,461      | 06/30/2017  | Yong Qin Chen        | BECC.P0002US.CIP.C1 | 9847             |

TITLE OF INVENTION: FLOW CYTOMETER

| APPLN. TYPE    | ENTITY STATUS | ISSUE FEE DUE | PUBLICATION FEE DUE | PREV. PAID ISSUE FEE | TOTAL FEE(S) DUE | DATE DUE   |
|----------------|---------------|---------------|---------------------|----------------------|------------------|------------|
| nonprovisional | UNDISCOUNTED  | \$1000        | \$0.00              | \$0.00               | \$1000           | 05/07/2019 |

| EXAMINER               | ART UNIT | CLASS-SUBCLASS |
|------------------------|----------|----------------|
| BOOSALIS, FANI POLYZOS | 2884     | 250-458100     |

1. Change of correspondence address or indication of "Fee Address" (37 CFR 1.363).

☐ Change of correspondence address (or Change of Correspondence Address form PTO/SB/122) attached.

☐ "Fee Address" indication (or "Fee Address" Indication form PTO/SB/47; Rev 03-09 or more recent) attached. **Use of a Customer Number is required.**

2. For printing on the patent front page, list

(1) The names of up to 3 registered patent attorneys or agents OR, alternatively,

1 \_\_\_\_\_

(2) The name of a single firm (having as a member a registered attorney or agent) and the names of up to 2 registered patent attorneys or agents. If no name is listed, no name will be printed.

2 \_\_\_\_\_

3 \_\_\_\_\_

3. ASSIGNEE NAME AND RESIDENCE DATA TO BE PRINTED ON THE PATENT (print or type)

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document must have been previously recorded, or filed for recordation, as set forth in 37 CFR 3.11 and 37 CFR 3.81(a). Completion of this form is NOT a substitute for filing an assignment.

(A) NAME OF ASSIGNEE

(B) RESIDENCE: (CITY and STATE OR COUNTRY)

Please check the appropriate assignee category or categories (will not be printed on the patent) : ☐ Individual ☐ Corporation or other private group entity ☐ Government

4a. Fees submitted: ☐ Issue Fee ☐ Publication Fee (if required) ☐ Advance Order - # of Copies \_\_\_\_\_

4b. Method of Payment: (Please first reapply any previously paid fee shown above)

☐ Electronic Payment via EFS-Web ☐ Enclosed check ☐ Non-electronic payment by credit card (Attach form PTO-2038)

☐ The Director is hereby authorized to charge the required fee(s), any deficiency, or credit any overpayment to Deposit Account No. \_\_\_\_\_

5. **Change in Entity Status** (from status indicated above)

☐ Applicant certifying micro entity status. See 37 CFR 1.29

☐ Applicant asserting small entity status. See 37 CFR 1.27

☐ Applicant changing to regular undiscounted fee status.

**NOTE:** Absent a valid certification of Micro Entity Status (see forms PTO/SB/15A and 15B), issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.

**NOTE:** If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.

**NOTE:** Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.

**NOTE:** This form must be signed in accordance with 37 CFR 1.31 and 1.33. See 37 CFR 1.4 for signature requirements and certifications.

Authorized Signature \_\_\_\_\_

Date \_\_\_\_\_

Typed or printed name \_\_\_\_\_

Registration No. \_\_\_\_\_

**Page 595 of 630**



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NO.              | FILING DATE | FIRST NAMED INVENTOR | ATTORNEY DOCKET NO.    | CONFIRMATION NO. |
|------------------------------|-------------|----------------------|------------------------|------------------|
| 15/638,461                   | 06/30/2017  | Yong Qin Chen        | BECC.P0002US.CIP.C1    | 9847             |
| 32425                        | 7590        | 02/07/2019           | EXAMINER               |                  |
| NORTON ROSE FULBRIGHT US LLP |             |                      | BOOSALIS, FANI POLYZOS |                  |
| 98 SAN JACINTO BOULEVARD     |             |                      |                        |                  |
| SUITE 1100                   |             |                      |                        |                  |
| AUSTIN, TX 78701-4255        |             |                      | ART UNIT               | PAPER NUMBER     |
|                              |             |                      | 2884                   |                  |

DATE MAILED: 02/07/2019

## Determination of Patent Term Adjustment under 35 U.S.C. 154 (b) (Applications filed on or after May 29, 2000)

The Office has discontinued providing a Patent Term Adjustment (PTA) calculation with the Notice of Allowance.

Section 1(h)(2) of the AIA Technical Corrections Act amended 35 U.S.C. 154(b)(3)(B)(i) to eliminate the requirement that the Office provide a patent term adjustment determination with the notice of allowance. See Revisions to Patent Term Adjustment, 78 Fed. Reg. 19416, 19417 (Apr. 1, 2013). Therefore, the Office is no longer providing an initial patent term adjustment determination with the notice of allowance. The Office will continue to provide a patent term adjustment determination with the Issue Notification Letter that is mailed to applicant approximately three weeks prior to the issue date of the patent, and will include the patent term adjustment on the patent. Any request for reconsideration of the patent term adjustment determination (or reinstatement of patent term adjustment) should follow the process outlined in 37 CFR 1.705.

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Customer Service Center of the Office of Patent Publication at 1-(888)-786-0101 or (571)-272-4200.



## OMB Clearance and PRA Burden Statement for PTOL-85 Part B

The Paperwork Reduction Act (PRA) of 1995 requires Federal agencies to obtain Office of Management and Budget approval before requesting most types of information from the public. When OMB approves an agency request to collect information from the public, OMB (i) provides a valid OMB Control Number and expiration date for the agency to display on the instrument that will be used to collect the information and (ii) requires the agency to inform the public about the OMB Control Number's legal significance in accordance with 5 CFR 1320.5(b).

The information collected by PTOL-85 Part B is required by 37 CFR 1.311. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 30 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, Virginia 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, Virginia 22313-1450. Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

### Privacy Act Statement

**The Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether disclosure of these records is required by the Freedom of Information Act.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspection or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

|                               |                                      |                                       |                         |
|-------------------------------|--------------------------------------|---------------------------------------|-------------------------|
| <b>Notice of Allowability</b> | <b>Application No.</b><br>15/638,461 | <b>Applicant(s)</b><br>Chen, Yong Qin |                         |
|                               | <b>Examiner</b><br>FANI P BOOSALIS   | <b>Art Unit</b><br>2884               | <b>AIA Status</b><br>No |

**-- The MAILING DATE of this communication appears on the cover sheet with the correspondence address--**

All claims being allowable, PROSECUTION ON THE MERITS IS (OR REMAINS) CLOSED in this application. If not included herewith (or previously mailed), a Notice of Allowance (PTOL-85) or other appropriate communication will be mailed in due course. **THIS NOTICE OF ALLOWABILITY IS NOT A GRANT OF PATENT RIGHTS.** This application is subject to withdrawal from issue at the initiative of the Office or upon petition by the applicant. See 37 CFR 1.313 and MPEP 1308.

1. ☒ This communication is responsive to submission of November 29, 2018.  
☐ A declaration(s)/affidavit(s) under **37 CFR 1.130(b)** was/were filed on \_\_\_\_.

2. ☐ An election was made by the applicant in response to a restriction requirement set forth during the interview on \_\_\_\_; the restriction requirement and election have been incorporated into this action.

3. ☒ The allowed claim(s) is/are 364-367, 369-376 and 378-391. As a result of the allowed claim(s), you may be eligible to benefit from the **Patent Prosecution Highway** program at a participating intellectual property office for the corresponding application. For more information, please see [http://www.uspto.gov/patents/init\\_events/pph/index.jsp](http://www.uspto.gov/patents/init_events/pph/index.jsp) or send an inquiry to **PPHfeedback@uspto.gov**.

4. ☐ Acknowledgment is made of a claim for foreign priority under 35 U.S.C. § 119(a)-(d) or (f).

**Certified copies:**

a) ☐ All      b) ☐ Some      \*c) ☐ None of the:

1. ☐ Certified copies of the priority documents have been received.

2. ☐ Certified copies of the priority documents have been received in Application No. \_\_\_\_.

3. ☐ Copies of the certified copies of the priority documents have been received in this national stage application from the International Bureau (PCT Rule 17.2(a)).

\* Certified copies not received: \_\_\_\_.

Applicant has THREE MONTHS FROM THE "MAILING DATE" of this communication to file areply complying with the requirements noted below. Failure to timely comply will result in ABANDONMENT of this application.  
**THIS THREE-MONTH PERIOD IS NOT EXTENDABLE.**

5. ☐ CORRECTED DRAWINGS (as "replacement sheets") must be submitted.  
☐ including changes required by the attached Examiner's Amendment / Comment or in the Office action of Paper No./Mail Date \_\_\_\_.

**Identifying indicia such as the application number (see 37 CFR 1.84(c)) should be written on the drawings in the front (not the back) of each sheet. Replacement sheet(s) should be labeled as such in the header according to 37 CFR 1.121(d).**

6. ☐ DEPOSIT OF and/or INFORMATION about the deposit of BIOLOGICAL MATERIAL must be submitted. Note the attached Examiner's comment regarding REQUIREMENT FOR THE DEPOSIT OF BIOLOGICAL MATERIAL.

**Attachment(s)**

|                                                                                                                  |                                                                                      |
|------------------------------------------------------------------------------------------------------------------|--------------------------------------------------------------------------------------|
| 1. <input checked="" type="checkbox"/> Notice of References Cited (PTO-892)                                      | 5. <input type="checkbox"/> Examiner's Amendment/Comment                             |
| 2. <input type="checkbox"/> Information Disclosure Statements (PTO/SB/08),<br>Paper No./Mail Date ____.          | 6. <input checked="" type="checkbox"/> Examiner's Statement of Reasons for Allowance |
| 3. <input type="checkbox"/> Examiner's Comment Regarding Requirement for Deposit<br>of Biological Material ____. | 7. <input type="checkbox"/> Other ____.                                              |
| 4. <input type="checkbox"/> Interview Summary (PTO-413),<br>Paper No./Mail Date ____.                            |                                                                                      |

|                                                               |                |
|---------------------------------------------------------------|----------------|
| /DAVID P PORTA/<br>Supervisory Patent Examiner, Art Unit 2884 | /FaniBoosalis/ |
|---------------------------------------------------------------|----------------|

***Notice of Pre-AIA or AIA Status***

1. The present application is being examined under the pre-AIA first to invent provisions.

**EXAMINER'S STATEMENT OF REASONS FOR ALLOWANCE**

***Response to Arguments***

2. Applicant's arguments, pages 8-19, filed November 29, 2018, with respect to claim(s) 364-373, 376-380, 382-389, have been fully considered and are persuasive. The rejection of claim(s) 364-373, 376-380, 382-389 has been withdrawn.

***Response to Amendment***

3. The amendment submitted November 29, 2018 has been accepted and entered. Claims 364-367, 369-376, 378-389 are amended. Claims 368, 377 are cancelled. New claims 390, 391 are added. Thus, claims 364-367, 369-376, 378-391 are examined.

***Allowable Subject Matter***

4. Claims 364-367, 369-376, 378-391 are allowable over the prior art.

Independent claims 364 is allowable for reasons of record as presented in applicant's remarks; filed on November 29, 2018, especially pages 11-12, regarding an optical relay element, including a curved mirror, configured to reflect a portion of a collimated beam received from a collimating optical element, as claimed in combination with the rest of the claim limitations, so as to improve structure an operation of a flow cytometer together with individual subassemblies.

Independent claims 376, 383 are allowable for reasons of record as presented in applicant's remarks; filed on November 29, 2018, especially pages 11-12, regarding an optical relay element arranged to receive the collimated beam, the optical relay element configured to extend the collimated distance of the collimated beam, wherein the optical relay element comprise a curved mirror or a concave-shaped dichroic filter configured to produce a second image, as claimed in combination with the rest of the claim limitations, without significantly expanding the beam diameter.

5. Claims 365-367, 369-375, 378-382, 384-391 are allowable based on their dependency.

**Conclusion**

6. The prior art made of record and not relied upon is considered pertinent to applicant's disclosure.

**Wells et al (US 7,113,266 B1)** discloses a flow cytometer for differentiating e.g. blood cell, has optical component positioned in laser beam between laser diode and optical flow cell and rotating plane of polarization of laser beam before beam irradiates particles

**Swalwell et al (US 8,928,881 B2)** discloses a system and method for performing flow cytometry is disclosed wherein the alignment of the light source with respect to the sensing region of the fluid stream is continuously controlled using a feedback control loop. An imaging apparatus is provided that images the system along the optical axis, between the field stop and the sensing region. In an embodiment, the cytometer comprises a field stop having an H-shaped aperture and light diverters over the ends of the aperture that divert a portion of the light to peripheral detectors.

**Osamu et al (JP 55144226 A)** discloses a concave mirror and fluorescent screen fixed to a holding and fixing means. An aberration correction lens is designed in the position suitable for the intermediate curvature of two kinds of screens 1, 2 fixed to a moving means and movable on the main beam axis Z-Z'.

7. Any inquiry concerning this communication or earlier communications from the examiner should be directed to FANI POLYZOS BOOSALIS whose telephone number is (571)272-2447. The examiner can normally be reached on 7:30-3:30 PM.

Examiner interviews are available via telephone, in-person, and video conferencing using a USPTO supplied web-based collaboration tool. To schedule an interview, applicant is encouraged to use the USPTO Automated Interview Request (AIR) at <http://www.uspto.gov/interviewpractice>.

If attempts to reach the examiner by telephone are unsuccessful, the examiner's supervisor, David Porta can be reached on 571-272-2444. The fax phone number for the organization where this application or proceeding is assigned is 571-273-8300.

8. Information regarding the status of an application may be obtained from the Patent Application Information Retrieval (PAIR) system. Status information for published applications may be obtained from either Private PAIR or Public PAIR. Status information for unpublished applications is available through Private PAIR only. For more information about the PAIR system, see <http://pair-direct.uspto.gov>. Should you have questions on access to the Private PAIR system, contact the Electronic Business Center (EBC) at 866-217-9197 (toll-free). If you would like assistance from a USPTO Customer Service Representative or access to the automated information system, call 800-786-9199 (IN USA OR CANADA) or 571-272-1000.

**/DAVID P PORTA/  
Supervisory Patent Examiner, Art  
Unit 2884**

/FB/

|                                   |                                       |  |                                                              |             |
|-----------------------------------|---------------------------------------|--|--------------------------------------------------------------|-------------|
| <b>Notice of References Cited</b> | Application/Control No.<br>15/638,461 |  | Applicant(s)/Patent Under<br>Reexamination<br>Chen, Yong Qin |             |
|                                   | Examiner<br>FANI P BOOSALIS           |  | Art Unit<br>2884                                             | Page 1 of 1 |

**U.S. PATENT DOCUMENTS**

| * |   | Document Number<br>Country Code-Number-Kind Code | Date<br>MM-YYYY | Name                      | CPC Classification | US Classification |
|---|---|--------------------------------------------------|-----------------|---------------------------|--------------------|-------------------|
| * | A | US-20050274890-A1                                | 12-2005         | Anderton, Rupert Nicholas | G01V8/005          | 250/334           |
| * | B | US-8928881-B2                                    | 01-2015         | Swalwell; Jarred E.       | G01N15/1434        | 356/336           |
| * | C | US-20110216401-A1                                | 09-2011         | Curry; Douglas N.         | G02B7/16           | 359/384           |
| * | D | US-7113266-B1                                    | 09-2006         | Wells; Mark A.            | G01N15/1404        | 356/336           |
|   | E |                                                  |                 |                           |                    |                   |
|   | F |                                                  |                 |                           |                    |                   |
|   | G |                                                  |                 |                           |                    |                   |
|   | H |                                                  |                 |                           |                    |                   |
|   | I |                                                  |                 |                           |                    |                   |
|   | J |                                                  |                 |                           |                    |                   |
|   | K |                                                  |                 |                           |                    |                   |
|   | L |                                                  |                 |                           |                    |                   |
|   | M |                                                  |                 |                           |                    |                   |

**FOREIGN PATENT DOCUMENTS**

| * |   | Document Number<br>Country Code-Number-Kind Code | Date<br>MM-YYYY | Country | Name | CPC Classification |
|---|---|--------------------------------------------------|-----------------|---------|------|--------------------|
|   | N |                                                  |                 |         |      |                    |
|   | O |                                                  |                 |         |      |                    |
|   | P |                                                  |                 |         |      |                    |
|   | Q |                                                  |                 |         |      |                    |
|   | R |                                                  |                 |         |      |                    |
|   | S |                                                  |                 |         |      |                    |
|   | T |                                                  |                 |         |      |                    |

**NON-PATENT DOCUMENTS**

| * |   | Include as applicable: Author, Title Date, Publisher, Edition or Volume, Pertinent Pages) |
|---|---|-------------------------------------------------------------------------------------------|
|   | U |                                                                                           |
|   | V |                                                                                           |
|   | W |                                                                                           |
|   | X |                                                                                           |

\*A copy of this reference is not being furnished with this Office action. (See MPEP § 707.05(a).)  
Dates in MM-YYYY format are publication dates. Classifications may be US or foreign.

|                                                                                                                 |                                              |                                                                  |
|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|
| <b><i>Search Notes</i></b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |
|                                                                                                                 | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |

| CPC - Searched*                                                                                             |            |          |
|-------------------------------------------------------------------------------------------------------------|------------|----------|
| Symbol                                                                                                      | Date       | Examiner |
| G01N 15/1436, 15/1459, 15/1434                                                                              | 6/15/18    | MV       |
| G02B 21/361, 27/0025, 21/804, 6/26, 6/29365                                                                 | 6/15/18    | MV       |
| Search Updated                                                                                              | 01/23/2019 | /FB/     |
| G01N2015/1006 G01N15/1434 G01N15/1436 G01N15/1459 G01N2015/1452 G01N2015/144 G02B21/04 G02B27/0025 G02B6/26 | 01/23/2019 | /FB/     |

| CPC Combination Sets - Searched* |      |          |
|----------------------------------|------|----------|
| Symbol                           | Date | Examiner |
|                                  |      |          |

| US Classification - Searched* |          |      |          |
|-------------------------------|----------|------|----------|
| Class                         | Subclass | Date | Examiner |
|                               |          |      |          |

\* See search history printout included with this form or the SEARCH NOTES box below to determine the scope of the search.

| Search Notes                                |            |          |
|---------------------------------------------|------------|----------|
| Search Notes                                | Date       | Examiner |
| Inventor name search                        | 6/11/18    | mv       |
| Parent data considered                      | 6/11/18    | mv       |
| EAST BRS - See search history printout      | 6/18/18    | mv       |
| EAST - Text Search                          | 01/23/2019 | /FB/     |
| EAST - Inventor Name Search                 | 01/23/2019 | /FB/     |
| EAST - Interference Search History Printout | 01/23/2019 | /FB/     |

|                                                                                                                 |                                              |                                                                  |
|-----------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|
| <b><i>Search Notes</i></b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |
|                                                                                                                 | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |

| Interference Search |                       |            |          |
|---------------------|-----------------------|------------|----------|
| US Class/CPC Symbol | US Subclass/CPC Group | Date       | Examiner |
| PGPub               | Text Search           | 01/23/2019 | /FB/     |
|                     |                       |            |          |



|                                                                                                                    |                                              |                                                                  |
|--------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|
| <b><i>Index of Claims</i></b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |
|                                                                                                                    | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |

|   |                 |   |                   |   |                     |   |                 |
|---|-----------------|---|-------------------|---|---------------------|---|-----------------|
| ✓ | <b>Rejected</b> | - | <b>Cancelled</b>  | N | <b>Non-Elected</b>  | A | <b>Appeal</b>   |
| = | <b>Allowed</b>  | ÷ | <b>Restricted</b> | I | <b>Interference</b> | O | <b>Objected</b> |

| CLAIMS                                                                                 |          |            |            |  |                              |  |                               |  |                                 |  |
|----------------------------------------------------------------------------------------|----------|------------|------------|--|------------------------------|--|-------------------------------|--|---------------------------------|--|
| <input type="checkbox"/> Claims renumbered in the same order as presented by applicant |          |            |            |  | <input type="checkbox"/> CPA |  | <input type="checkbox"/> T.D. |  | <input type="checkbox"/> R.1.47 |  |
| CLAIM                                                                                  |          | DATE       |            |  |                              |  |                               |  |                                 |  |
| Final                                                                                  | Original | 06/18/2018 | 01/23/2019 |  |                              |  |                               |  |                                 |  |
| 1                                                                                      | 364      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 2                                                                                      | 365      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 3                                                                                      | 366      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 4                                                                                      | 367      | ✓          | =          |  |                              |  |                               |  |                                 |  |
|                                                                                        | 368      | ✓          | -          |  |                              |  |                               |  |                                 |  |
| 5                                                                                      | 369      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 6                                                                                      | 370      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 7                                                                                      | 371      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 8                                                                                      | 372      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 9                                                                                      | 373      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 10                                                                                     | 374      | ○          | =          |  |                              |  |                               |  |                                 |  |
| 11                                                                                     | 375      | ○          | =          |  |                              |  |                               |  |                                 |  |
| 14                                                                                     | 376      | ✓          | =          |  |                              |  |                               |  |                                 |  |
|                                                                                        | 377      | ✓          | -          |  |                              |  |                               |  |                                 |  |
| 15                                                                                     | 378      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 16                                                                                     | 379      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 17                                                                                     | 380      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 18                                                                                     | 381      | ○          | =          |  |                              |  |                               |  |                                 |  |
| 19                                                                                     | 382      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 20                                                                                     | 383      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 21                                                                                     | 384      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 22                                                                                     | 385      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 23                                                                                     | 386      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 24                                                                                     | 387      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 25                                                                                     | 388      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 26                                                                                     | 389      | ✓          | =          |  |                              |  |                               |  |                                 |  |
| 12                                                                                     | 390      |            | =          |  |                              |  |                               |  |                                 |  |
| 13                                                                                     | 391      |            | =          |  |                              |  |                               |  |                                 |  |

|                                                                                                                  |                                              |                                                                  |  |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|--|
| <b>Issue Classification</b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |  |
|                                                                                                                  | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |  |

| CPC    |   |      |   |       |      |            |
|--------|---|------|---|-------|------|------------|
| Symbol |   |      |   |       | Type | Version    |
| G01N   | / | 15   | / | 1436  | F    | 2013-01-01 |
| G01N   | / | 15   | / | 1434  | I    | 2013-01-01 |
| G02B   | / | 6    | / | 29365 | I    | 2013-01-01 |
| G02B   | / | 6    | / | 26    | I    | 2013-01-01 |
| G01N   | / | 15   | / | 1459  | I    | 2013-01-01 |
| G02B   | / | 21   | / | 04    | I    | 2013-01-01 |
| G02B   | / | 21   | / | 361   | I    | 2013-01-01 |
| G02B   | / | 27   | / | 0025  | I    | 2013-01-01 |
| G01N   | / | 2015 | / | 1452  | A    | 2013-01-01 |
| G01N   | / | 2015 | / | 144   | A    | 2013-01-01 |
| G01N   | / | 2015 | / | 1006  | A    | 2013-01-01 |

| CPC Combination Sets |      |     |         |         |
|----------------------|------|-----|---------|---------|
| Symbol               | Type | Set | Ranking | Version |
| /                    |      |     |         |         |

|                                                             |                           |                                    |                        |
|-------------------------------------------------------------|---------------------------|------------------------------------|------------------------|
| /FaniBoosalis/<br>(Assistant Examiner)                      | 23 January 2019<br>(Date) | <b>Total Claims Allowed:</b><br>26 |                        |
| /DAVID P PORTA/<br>SPE, Art Unit 2884<br>(Primary Examiner) | 24 January 2019<br>(Date) | O.G. Print Claim(s)<br>1           | O.G. Print Figure<br>1 |

|                                                                                                                  |                                              |                                                                  |  |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|--|
| <b>Issue Classification</b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |  |
|                                                                                                                  | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |  |

|                                     |   |    |        |
|-------------------------------------|---|----|--------|
| <b>INTERNATIONAL CLASSIFICATION</b> |   |    |        |
| <b>CLAIMED</b>                      |   |    |        |
| G01N                                | / | 15 | / 1436 |
| G01N                                | / | 15 | / 434  |
| G02B                                | / | 6  | / 26   |
| <b>NON-CLAIMED</b>                  |   |    |        |
|                                     | / |    | /      |

|                                   |                 |
|-----------------------------------|-----------------|
| <b>US ORIGINAL CLASSIFICATION</b> |                 |
| <b>CLASS</b>                      | <b>SUBCLASS</b> |
|                                   |                 |

|                            |                                          |  |  |  |  |
|----------------------------|------------------------------------------|--|--|--|--|
| <b>CROSS REFERENCES(S)</b> |                                          |  |  |  |  |
| <b>CLASS</b>               | <b>SUBCLASS (ONE SUBCLASS PER BLOCK)</b> |  |  |  |  |
|                            |                                          |  |  |  |  |

|                                                             |                           |                                    |                        |
|-------------------------------------------------------------|---------------------------|------------------------------------|------------------------|
| /FaniBoosalis/<br>(Assistant Examiner)                      | 23 January 2019<br>(Date) | <b>Total Claims Allowed:</b><br>26 |                        |
| /DAVID P PORTA/<br>SPE, Art Unit 2884<br>(Primary Examiner) | 24 January 2019<br>(Date) | O.G. Print Claim(s)<br>1           | O.G. Print Figure<br>1 |

|                                                                                                                  |                                              |                                                                  |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|
| <b>Issue Classification</b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |
|                                                                                                                  | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |

☐ Claims renumbered in the same order as presented by applicant
 ☐ CPA
 ☐ T.D.
 ☐ R.1.47

| CLAIMS |          |       |          |       |          |       |          |       |          |       |          |       |          |       |          |
|--------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|
| Final  | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original |
|        | 1        |       | 50       |       | 99       |       | 148      |       | 197      |       | 246      |       | 295      |       | 344      |
|        | 2        |       | 51       |       | 100      |       | 149      |       | 198      |       | 247      |       | 296      |       | 345      |
|        | 3        |       | 52       |       | 101      |       | 150      |       | 199      |       | 248      |       | 297      |       | 346      |
|        | 4        |       | 53       |       | 102      |       | 151      |       | 200      |       | 249      |       | 298      |       | 347      |
|        | 5        |       | 54       |       | 103      |       | 152      |       | 201      |       | 250      |       | 299      |       | 348      |
|        | 6        |       | 55       |       | 104      |       | 153      |       | 202      |       | 251      |       | 300      |       | 349      |
|        | 7        |       | 56       |       | 105      |       | 154      |       | 203      |       | 252      |       | 301      |       | 350      |
|        | 8        |       | 57       |       | 106      |       | 155      |       | 204      |       | 253      |       | 302      |       | 351      |
|        | 9        |       | 58       |       | 107      |       | 156      |       | 205      |       | 254      |       | 303      |       | 352      |
|        | 10       |       | 59       |       | 108      |       | 157      |       | 206      |       | 255      |       | 304      |       | 353      |
|        | 11       |       | 60       |       | 109      |       | 158      |       | 207      |       | 256      |       | 305      |       | 354      |
|        | 12       |       | 61       |       | 110      |       | 159      |       | 208      |       | 257      |       | 306      |       | 355      |
|        | 13       |       | 62       |       | 111      |       | 160      |       | 209      |       | 258      |       | 307      |       | 356      |
|        | 14       |       | 63       |       | 112      |       | 161      |       | 210      |       | 259      |       | 308      |       | 357      |
|        | 15       |       | 64       |       | 113      |       | 162      |       | 211      |       | 260      |       | 309      |       | 358      |
|        | 16       |       | 65       |       | 114      |       | 163      |       | 212      |       | 261      |       | 310      |       | 359      |
|        | 17       |       | 66       |       | 115      |       | 164      |       | 213      |       | 262      |       | 311      |       | 360      |
|        | 18       |       | 67       |       | 116      |       | 165      |       | 214      |       | 263      |       | 312      |       | 361      |
|        | 19       |       | 68       |       | 117      |       | 166      |       | 215      |       | 264      |       | 313      |       | 362      |
|        | 20       |       | 69       |       | 118      |       | 167      |       | 216      |       | 265      |       | 314      |       | 363      |
|        | 21       |       | 70       |       | 119      |       | 168      |       | 217      |       | 266      |       | 315      | 1     | 364      |
|        | 22       |       | 71       |       | 120      |       | 169      |       | 218      |       | 267      |       | 316      | 2     | 365      |
|        | 23       |       | 72       |       | 121      |       | 170      |       | 219      |       | 268      |       | 317      | 3     | 366      |
|        | 24       |       | 73       |       | 122      |       | 171      |       | 220      |       | 269      |       | 318      | 4     | 367      |
|        | 25       |       | 74       |       | 123      |       | 172      |       | 221      |       | 270      |       | 319      |       | 368      |
|        | 26       |       | 75       |       | 124      |       | 173      |       | 222      |       | 271      |       | 320      | 5     | 369      |
|        | 27       |       | 76       |       | 125      |       | 174      |       | 223      |       | 272      |       | 321      | 6     | 370      |
|        | 28       |       | 77       |       | 126      |       | 175      |       | 224      |       | 273      |       | 322      | 7     | 371      |
|        | 29       |       | 78       |       | 127      |       | 176      |       | 225      |       | 274      |       | 323      | 8     | 372      |
|        | 30       |       | 79       |       | 128      |       | 177      |       | 226      |       | 275      |       | 324      | 9     | 373      |
|        | 31       |       | 80       |       | 129      |       | 178      |       | 227      |       | 276      |       | 325      | 10    | 374      |
|        | 32       |       | 81       |       | 130      |       | 179      |       | 228      |       | 277      |       | 326      | 11    | 375      |
|        | 33       |       | 82       |       | 131      |       | 180      |       | 229      |       | 278      |       | 327      | 14    | 376      |
|        | 34       |       | 83       |       | 132      |       | 181      |       | 230      |       | 279      |       | 328      |       | 377      |
|        | 35       |       | 84       |       | 133      |       | 182      |       | 231      |       | 280      |       | 329      | 15    | 378      |
|        | 36       |       | 85       |       | 134      |       | 183      |       | 232      |       | 281      |       | 330      | 16    | 379      |
|        | 37       |       | 86       |       | 135      |       | 184      |       | 233      |       | 282      |       | 331      | 17    | 380      |
|        | 38       |       | 87       |       | 136      |       | 185      |       | 234      |       | 283      |       | 332      | 18    | 381      |
|        | 39       |       | 88       |       | 137      |       | 186      |       | 235      |       | 284      |       | 333      | 19    | 382      |

|                                                             |                           |                                    |                        |
|-------------------------------------------------------------|---------------------------|------------------------------------|------------------------|
| /FaniBoosalis/<br>(Assistant Examiner)                      | 23 January 2019<br>(Date) | <b>Total Claims Allowed:</b><br>26 |                        |
| /DAVID P PORTA/<br>SPE, Art Unit 2884<br>(Primary Examiner) | 24 January 2019<br>(Date) | O.G. Print Claim(s)<br>1           | O.G. Print Figure<br>1 |

|                                                                                                                  |                                              |                                                                  |
|------------------------------------------------------------------------------------------------------------------|----------------------------------------------|------------------------------------------------------------------|
| <b>Issue Classification</b><br> | <b>Application/Control No.</b><br>15/638,461 | <b>Applicant(s)/Patent Under Reexamination</b><br>Chen, Yong Qin |
|                                                                                                                  | <b>Examiner</b><br>FANI P BOOSALIS           | <b>Art Unit</b><br>2884                                          |

**CLAIMS**

| Final | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original | Final | Original |
|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|-------|----------|
|       | 40       |       | 89       |       | 138      |       | 187      |       | 236      |       | 285      |       | 334      | 20    | 383      |
|       | 41       |       | 90       |       | 139      |       | 188      |       | 237      |       | 286      |       | 335      | 21    | 384      |
|       | 42       |       | 91       |       | 140      |       | 189      |       | 238      |       | 287      |       | 336      | 22    | 385      |
|       | 43       |       | 92       |       | 141      |       | 190      |       | 239      |       | 288      |       | 337      | 23    | 386      |
|       | 44       |       | 93       |       | 142      |       | 191      |       | 240      |       | 289      |       | 338      | 24    | 387      |
|       | 45       |       | 94       |       | 143      |       | 192      |       | 241      |       | 290      |       | 339      | 25    | 388      |
|       | 46       |       | 95       |       | 144      |       | 193      |       | 242      |       | 291      |       | 340      | 26    | 389      |
|       | 47       |       | 96       |       | 145      |       | 194      |       | 243      |       | 292      |       | 341      | 12    | 390      |
|       | 48       |       | 97       |       | 146      |       | 195      |       | 244      |       | 293      |       | 342      | 13    | 391      |
|       | 49       |       | 98       |       | 147      |       | 196      |       | 245      |       | 294      |       | 343      |       |          |

|                                                             |                           |                                    |                        |
|-------------------------------------------------------------|---------------------------|------------------------------------|------------------------|
| /FaniBoosalis/<br>(Assistant Examiner)                      | 23 January 2019<br>(Date) | <b>Total Claims Allowed:</b><br>26 |                        |
| /DAVID P PORTA/<br>SPE, Art Unit 2884<br>(Primary Examiner) | 24 January 2019<br>(Date) | O.G. Print Claim(s)<br>1           | O.G. Print Figure<br>1 |

EAST Search History

EAST Search History (Prior Art)

| Ref # | Hits  | Search Query                                                                                        | DBs                                                                        | Default Operator | Plurals | Time Stamp       |
|-------|-------|-----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|------------------|---------|------------------|
| L7    | 3     | (flow cytomet\$4 ((concav\$4 or curv\$4) (mirror or reflect\$4)) relay beam collimat\$4 focus).clm. | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:33 |
| L10   | 52393 | (optic\$4 relay) ( mirror or (refract\$4 lens))                                                     | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:35 |
| L11   | 8377  | (collimat\$4 filter ) and l10                                                                       | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:36 |
| L12   | 1118  | (pin\$1 adj hole) and l10                                                                           | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:36 |
| L13   | 1118  | l12 and l10                                                                                         | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:36 |
| L14   | 622   | (diamet\$4 siz\$4) and l13                                                                          | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:36 |
| L15   | 442   | l14 and filter                                                                                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND              | OFF     | 2019/01/23 13:36 |
| L16   | 96    | l15 and (relay concav\$4 mirror)                                                                    | US-PGPUB;                                                                  | AND              | OFF     | 2019/01/23       |

|     |         |                                                                                                                                                        |                                                                            |      |     |                     |
|-----|---------|--------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|------|-----|---------------------|
|     |         |                                                                                                                                                        | USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB              |      |     | 13:37               |
| L17 | 1       | I16 AND ( (G01N2015/1006 OR G01N15/1434 OR G01N15/1436 OR G01N15/1459 OR G01N2015/1452 OR G01N2015/144 OR G02B21/04 OR G02B27/0025 OR G02B6/26).CPC. ) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>13:37 |
| L18 | 4139548 | chen.in.                                                                                                                                               | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>13:37 |
| L20 | 234     | I11 AND ( (G01N2015/1006 OR G01N15/1434 OR G01N15/1436 OR G01N15/1459 OR G01N2015/1452 OR G01N2015/144 OR G02B21/04 OR G02B27/0025 OR G02B6/26).CPC. ) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>13:38 |
| L21 | 21      | I12 AND ( (G01N2015/1006 OR G01N15/1434 OR G01N15/1436 OR G01N15/1459 OR G01N2015/1452 OR G01N2015/144 OR G02B21/04 OR G02B27/0025 OR G02B6/26).CPC. ) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>13:38 |
| L22 | 25      | ("2003/0143391").URPN.                                                                                                                                 | USPAT                                                                      | OR   | OFF | 2019/01/23<br>13:38 |
| L24 | 12      | (flow cytometer) and collimat\$4 optic\$4 source beam image and (mirror curv\$4)                                                                       | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | SAME | OFF | 2019/01/23<br>13:38 |
| L25 | 11      | L24 AND ( (G01N2015/1006 OR G01N15/1434 OR G01N15/1436 OR G01N15/1459 OR G01N2015/1452 OR G01N2015/144 OR G02B21/04 OR G02B27/0025 OR G02B6/26).CPC. ) | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>13:38 |
| L26 | 0       | ("2017/0261419").URPN.                                                                                                                                 | USPAT                                                                      | OR   | OFF | 2019/01/23<br>13:39 |
| L27 | 13      | ("2008/0268469").URPN.                                                                                                                                 | USPAT                                                                      | OR   | OFF | 2019/01/23<br>13:39 |
| S28 | 606     | (cytometer collimat\$4 optic\$4 (mirror curv\$4))                                                                                                      | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;            | AND  | OFF | 2019/01/23<br>11:32 |

|     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |                                                                            |     |     |                     |
|-----|-----|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|-----|-----|---------------------|
|     |     |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | IBM_TDB                                                                    |     |     |                     |
| S29 | 286 | S28 and (focus\$4 detect\$4<br>semiconduct\$4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND | OFF | 2019/01/23<br>11:32 |
| S30 | 116 | S29 AND ( (G01N2015/1006 OR<br>G01N15/1434 OR G01N15/1436 OR<br>G01N15/1459 OR G01N2015/1452 OR<br>G01N2015/144 OR G02B21/04 OR<br>G02B27/0025 OR G02B6/26).CPC. )                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND | OFF | 2019/01/23<br>11:34 |
| S31 | 626 | ("20020141902"   "20060292021"  <br>"4073574"   "4244045"   "4727020"  <br>"5230614"   "5583683"   "5615200"  <br>"5788927"   "6870976"   "6975400"  <br>"7430048"   "7450229"   "7952981"  <br>"8009189"   "8436371"   "6159686"  <br>"20050084402"   "20060245964"  <br>"20130020498"   "3946239"  <br>"3989381"   "4189236"   "4576556"  <br>"4745285"   "4950136"   "6200101"  <br>"6683314"   "6941047"   "7260328"  <br>"7268953"   "7381565"   "7385682"  <br>"8157547"   "8337096"   "8488244"  <br>"20040165828"   "2385495"  <br>"2764147"   "20120274925"  <br>"20130050782"   "20130070243"  <br>"3953727"   "4188543"   "4515274"  <br>"4920275"   "5251060"   "5470211"  <br>"5748372"   "5781351"   "5850292"  <br>"6608682"   "6748133"   "6954722"  <br>"7212343"   "8149525"   "8229707"  <br>"8253938"   "8405048"  <br>"20030142720"   "20070124947"  <br>"20090091746"   "20120281204"  <br>"20120282126"   "20120287419"  <br>"20130204538"   "3411293"  <br>"3542491"   "4834630"   "5177641"  <br>"5299066"   "5373395"   "5396487"  <br>"5467225"   "5548395"   "5746585"  <br>"5777674"   "6252719"   "6572255"  <br>"6618143"   "6839367"   "6876079"  <br>"6897954"   "7305018"   "7453915"  <br>"7496463"   "7623243"   "7645127"  <br>"7835000"   "20020067895"  <br>"5157917"   "20130010181"  <br>"0315667"   "4482994"   "4778253"  <br>"4997275"   "5050963"   "5245318"  <br>"5786915"   "5971713"   "6315952"  <br>"6647175"   "6768593"   "6813017"  <br>"7505131"   "7580120"   "7668422"  <br>"7768120"   "8432541"   "8436993"  <br>"8507279"   "3199341"   "6683314"  <br>"20060256335"   "20090190128"  <br>"20110032522"   "20120156074"  <br>"3726613"   "5142462"   "5369476"  <br>"5475210"   "5805363"   "6008920"  <br>"6510007"   "6713019"   "7072540"  <br>"7110192"   "7456960"   "7507588" | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND | OFF | 2019/01/23<br>11:40 |



|     |         |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |                                                                            |      |     |                     |
|-----|---------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------|------|-----|---------------------|
|     |         | "7758324"   "7981661"   "8213472"  <br>"8284402"   "20040218184"  <br>"20080024758"   "20110014075"  <br>"20130094102"   "4564342"  <br>"5915925"   "6135734"   "6794671"  <br>"7038778"   "7113266"   "7129505"  <br>"7262838"   "7876436"   "8187888"  <br>"8233146"   "8270098"   "8345237"  <br>"2669709"   "20060221325"  <br>"20080241911"   "3661460"  <br>"3826593"   "3873204"   "4623225"  <br>"4871249"   "4976590"   "5317162"  <br>"6017194"   "6102678"   "6542306"  <br>"6638481"   "6767188"   "6788409"  <br>"7127356"   "7561267"   "7781227"  <br>"7787197"   "7894047"  <br>"8049185").PN. |                                                                            |      |     |                     |
| S32 | 4139548 | chen.in.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>11:41 |
| S33 | 25      | S28 and S32                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>11:41 |
| S34 | 12      | (flow cytometer) and collimat\$4 optic\$4<br>source beam image and (mirror<br>curv\$4)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | SAME | OFF | 2019/01/23<br>11:42 |
| S35 | 6       | ("20030044967"   "20050002425").PN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>12:02 |
| S37 | 19      | ("2003/0044967").URPN.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | USPAT                                                                      | OR   | OFF | 2019/01/23<br>12:03 |
| S38 | 1       | S37 and cytometer                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>12:03 |
| S43 | 1       | S35 and cytomet\$4                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | US-PGPUB;<br>USPAT;<br>USOCR;<br>FPRS;<br>EPO; JPO;<br>DERWENT;<br>IBM_TDB | AND  | OFF | 2019/01/23<br>12:05 |

**1/ 23/ 2019 1:39:26 PM**

**C:\ Users\ fpolyzos\ Documents\ EAST\ Workspaces\ 15638461\ 15638461.wsp**

Document Description: Issue Fee Payment (PTO-85B)

**Issue Fee Transmittal Form**

| Application Number | Filing Date | First Named Inventor | Atty. Docket No.    | Confirmation No. |
|--------------------|-------------|----------------------|---------------------|------------------|
| 15638461           | 30-Jun-2017 | Yong Chen            | BECC.P0002US.CIP.C1 | 9847             |

**TITLE OF INVENTION :**

FLOW CYTOMETER

| Entity Status        | Application Type            | Art Unit         | Class - Subclass | EXAMINER       |
|----------------------|-----------------------------|------------------|------------------|----------------|
| Regular Undiscounted | Utility under 35 USC 111(a) | 2884             | 458100           | FANI BOOSALIS  |
| Issue Fee Due        | Publication Due             | Total Fee(s) Due | Date Due         | Prev. Paid Fee |
| \$1000               | \$0                         | \$1000           | 07-May-2019      | \$0            |

**1.Change of Correspondence Address and/or Indication Of Fee Address (37 CFR 1.33 & 1.363)**

| Current Correspondence Address:                                                                                                                                                    | Current Indicated Fee Address :                                                                     |
|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------|
| 32425<br>NORTON ROSE FULBRIGHT US LLP<br><br>98 SAN JACINTO BOULEVARD<br>SUITE 1100<br>AUSTIN TX 78701-4255<br>UNITED STATES<br>512-474-5201<br>aoipdocket@nortonrosefulbright.com |                                                                                                     |
| <input type="checkbox"/> Change of correspondence address requested, system generated AIA/122-EFS form attached                                                                    | <input type="checkbox"/> Fee Address indication requested, system generated SB/47-EFS form attached |

**2.Entity Status****Change in Entity Status**

Applicant certifying micro entity status; system generated Micro Entity certification form attached. See 37 CFR 1.29.

Note: Absent a valid certification of micro entity status, issue fee payment in the micro entity amount will not be accepted at the risk of application abandonment.  
 If this box is checked, you will be prompted to choose a micro entity status on the gross income basis (37 CFR 1.29(a)) or the institution of higher education basis (37 CFR 1.29(d)), and make the applicable certification online.



Applicant asserting small entity status. See 37 CFR 1.27.

Note: If the application was previously under micro entity status, checking this box will be taken to be a notification of loss of entitlement to micro entity status.



Applicant changing to regular undiscounted fee status.

Note: Checking this box will be taken to be a notification of loss of entitlement to small or micro entity status, as applicable.



Document Description: Issue Fee Payment (PTO-85B)

3.The Following Fee(s) Are Submitted:

☒ Issue Fee

☐ I authorize USPTO to apply my previously paid issue fee to the current fees due

☐ Publication Fee

☐ The Director is hereby authorized to apply my previously paid issue fee to the current fee due and to charge deficient fees to Deposit Account Number \_\_\_\_\_

☐ Advance Order - # of copies \_\_\_\_\_

☐ If in **addition** to the payment of the issue fee amount submitted with this form, there are any discrepancies in any amount(s) due, the Director is authorized to charge any deficiency, or credit any overpayment, to Deposit Account Number \_\_\_\_\_.  
The **issue fee must be submitted** with this form. **If payment of the issue fee does not accompany this form, checking this box and providing a deposit account number will NOT be effective to satisfy full payment of the fee(s) due.**

4.Firm and/or Attorney Names To Be Printed

**NOTE: If no name is listed, no name will be printed**  
For printing on the patent front page, list to be displayed as entered

1. NORTON ROSE FULBRIGHT US LLP
2.
3.

5.Assignee Name(s) and Residence Data To Be Printed

PLEASE NOTE: Unless an assignee is identified below, no assignee data will appear on the patent. If an assignee is identified below, the document has been filed for recordation as set forth in 37 CFR 3.11. Completion of this form is NOT a substitute for filing an assignment.

| Name                     | City       | State      | Country       | Category    |
|--------------------------|------------|------------|---------------|-------------|
| IRIS INTERNATIONAL, INC. | CHATSWORTH | CALIFORNIA | united states | corporation |

6.Signature

I certify, in accordance with 37 CFR 1.4(d)(4) that I am an attorney or agent registered to practice before the Patent and Trademark Office who has filed and has been granted power of attorney in this application. I also certify that this Fee(s) Transmittal form is being transmitted to the USPTO via EFS-WEB on the date indicated below.

|           |                    |                     |            |
|-----------|--------------------|---------------------|------------|
| Signature | /Gina N. Shishima/ | Date                | 05-06-2019 |
| Name      | Gina N. Shishima   | Registration Number | 45104      |

## Electronic Patent Application Fee Transmittal

|                                                    |                            |                 |               |                             |
|----------------------------------------------------|----------------------------|-----------------|---------------|-----------------------------|
| <b>Application Number:</b>                         | 15638461                   |                 |               |                             |
| <b>Filing Date:</b>                                | 30-Jun-2017                |                 |               |                             |
| <b>Title of Invention:</b>                         | FLOW CYTOMETER             |                 |               |                             |
| <b>First Named Inventor/Applicant Name:</b>        | Yong Qin Chen              |                 |               |                             |
| <b>Filer:</b>                                      | Gina N. Shishima/Pam Gerik |                 |               |                             |
| <b>Attorney Docket Number:</b>                     | BECC.P0002US.CIP.C1        |                 |               |                             |
| Filed as Large Entity                              |                            |                 |               |                             |
| <b>Filing Fees for Utility under 35 USC 111(a)</b> |                            |                 |               |                             |
| <b>Description</b>                                 | <b>Fee Code</b>            | <b>Quantity</b> | <b>Amount</b> | <b>Sub-Total in USD(\$)</b> |
| <b>Basic Filing:</b>                               |                            |                 |               |                             |
| UTILITY APPL ISSUE FEE                             | 1501                       | 1               | 1000          | 1000                        |
| PUBL. FEE- EARLY, VOLUNTARY, OR NORMAL             | 1504                       | 1               | 0             | 0                           |
| <b>Pages:</b>                                      |                            |                 |               |                             |
| <b>Claims:</b>                                     |                            |                 |               |                             |
| <b>Miscellaneous-Filing:</b>                       |                            |                 |               |                             |
| <b>Petition:</b>                                   |                            |                 |               |                             |
| <b>Patent-Appeals-and-Interference:</b>            |                            |                 |               |                             |

| Description                       | Fee Code | Quantity | Amount | Sub-Total in USD(\$) |
|-----------------------------------|----------|----------|--------|----------------------|
| Post-Allowance-and-Post-Issuance: |          |          |        |                      |
| Extension-of-Time:                |          |          |        |                      |
| Miscellaneous:                    |          |          |        |                      |
| Total in USD (\$)                 |          |          |        | 1000                 |

## Electronic Acknowledgement Receipt

|                                             |                             |
|---------------------------------------------|-----------------------------|
| <b>EFS ID:</b>                              | 35923671                    |
| <b>Application Number:</b>                  | 15638461                    |
| <b>International Application Number:</b>    |                             |
| <b>Confirmation Number:</b>                 | 9847                        |
| <b>Title of Invention:</b>                  | FLOW CYTOMETER              |
| <b>First Named Inventor/Applicant Name:</b> | Yong Qin Chen               |
| <b>Customer Number:</b>                     | 32425                       |
| <b>Filer:</b>                               | Gina N. Shishima/Pam Gerik  |
| <b>Filer Authorized By:</b>                 | Gina N. Shishima            |
| <b>Attorney Docket Number:</b>              | BECC.P0002US.CIP.C1         |
| <b>Receipt Date:</b>                        | 06-MAY-2019                 |
| <b>Filing Date:</b>                         | 30-JUN-2017                 |
| <b>Time Stamp:</b>                          | 13:08:01                    |
| <b>Application Type:</b>                    | Utility under 35 USC 111(a) |

### Payment information:

|                                          |                       |
|------------------------------------------|-----------------------|
| Submitted with Payment                   | yes                   |
| Payment Type                             | CARD                  |
| Payment was successfully received in RAM | \$ 1000               |
| RAM confirmation Number                  | 050619INTEFSW13075900 |
| Deposit Account                          |                       |
| Authorized User                          |                       |

The Director of the USPTO is hereby authorized to charge indicated fees and credit any overpayment as follows:

| <b>File Listing:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |                             |              |                                          |                  |                  |
|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----------------------------|--------------|------------------------------------------|------------------|------------------|
| Document Number                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Document Description        | File Name    | File Size(Bytes)/<br>Message Digest      | Multi Part /.zip | Pages (if appl.) |
| 1                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Issue Fee Payment (PTO-85B) | Web85b.pdf   | 46034                                    | no               | 2                |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                             |              | 0ba42ac90fa8f57afe4d207a36937c5ccf8ca340 |                  |                  |
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                             |              |                                          |                  |                  |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                             |              |                                          |                  |                  |
| 2                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      | Fee Worksheet (SB06)        | fee-info.pdf | 31944                                    | no               | 2                |
|                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |                             |              | cd549aa99bb2081642bd8d9e538adeac1b3995a5 |                  |                  |
| <b>Warnings:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                             |              |                                          |                  |                  |
| <b>Information:</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                             |              |                                          |                  |                  |
| <b>Total Files Size (in bytes):</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |                             |              | 77978                                    |                  |                  |
| <p><b>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</b></p> <p><b><u>New Applications Under 35 U.S.C. 111</u></b><br/> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><b><u>National Stage of an International Application under 35 U.S.C. 371</u></b><br/> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><b><u>New International Application Filed with the USPTO as a Receiving Office</u></b><br/> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p> |                             |              |                                          |                  |                  |





# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
[www.uspto.gov](http://www.uspto.gov)

| APPLICATION NO. | ISSUE DATE | PATENT NO. | ATTORNEY DOCKET NO. | CONFIRMATION NO. |
|-----------------|------------|------------|---------------------|------------------|
| 15/638,461      | 06/25/2019 | 10330582   | BECC.P0002US.CIP.C1 | 9847             |

32425 7590 06/05/2019  
NORTON ROSE FULBRIGHT US LLP  
98 SAN JACINTO BOULEVARD  
SUITE 1100  
AUSTIN, TX 78701-4255

## ISSUE NOTIFICATION

The projected patent number and issue date are specified above.

### **Determination of Patent Term Adjustment under 35 U.S.C. 154 (b)** (application filed on or after May 29, 2000)

The Patent Term Adjustment is 0 day(s). Any patent to issue from the above-identified application will include an indication of the adjustment on the front page.

If a Continued Prosecution Application (CPA) was filed in the above-identified application, the filing date that determines Patent Term Adjustment is the filing date of the most recent CPA.

Applicant will be able to obtain more detailed information by accessing the Patent Application Information Retrieval (PAIR) WEB site (<http://pair.uspto.gov>).

Any questions regarding the Patent Term Extension or Adjustment determination should be directed to the Office of Patent Legal Administration at (571)-272-7702. Questions relating to issue and publication fee payments should be directed to the Application Assistance Unit (AAU) of the Office of Data Management (ODM) at (571)-272-4200.

APPLICANT(s) (Please see PAIR WEB site <http://pair.uspto.gov> for additional applicants):

IRIS INTERNATIONAL, INC., Chatsworth, CA;  
Yong Qin Chen, San Jose, CA;

The United States represents the largest, most dynamic marketplace in the world and is an unparalleled location for business investment, innovation, and commercialization of new technologies. The USA offers tremendous resources and advantages for those who invest and manufacture goods here. Through SelectUSA, our nation works to encourage and facilitate business investment. To learn more about why the USA is the best country in the world to develop technology, manufacture products, and grow your business, visit [SelectUSA.gov](http://SelectUSA.gov).

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it displays a valid OMB control number.

# CHANGE OF CORRESPONDENCE ADDRESS *Application*

Address to:  
Commissioner for Patents  
P.O. Box 1450  
Alexandria, VA 22313-1450

|                        |                       |
|------------------------|-----------------------|
| Application Number     | 15/638,461            |
| Filing Date            | June 30, 2017         |
| First Named Inventor   | Yong Chen             |
| Art Unit               | 2884                  |
| Examiner Name          | Fani Polyzos BOOSALIS |
| Attorney Docket Number | BECC.P0002US.CIP.C1   |

Please change the Correspondence Address for the above-identified patent application to:

The address associated with  
Customer Number:

129381

OR

Firm or  
Individual Name

Address

City

State

Zip

Country

Telephone

Email

This form cannot be used to change the data associated with a Customer Number. To change the data associated with an existing Customer Number use "Request for Customer Number Data Change" (PTO/SB/124).

I am the:



Applicant

Attorney or agent of record. Registration Number 65,985.

Registered practitioner named in the application transmittal papers who acts in a representative capacity under 37 CFR 1.34. See 37 CFR 1.33(a)(1). Registration Number \_\_\_\_\_.

Signature /Mark G. Tison/

Typed or Printed  
Name Mark G. Tison

Date March 30, 2023

Telephone 512 536-3033

NOTE: This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications.  
Submit multiple forms if more than one signature is required, see below\*.



\*Total of \_\_\_\_\_ forms are submitted.

A Federal agency may not conduct or sponsor, and a person is not required to respond to, nor shall a person be subject to a penalty for failure to comply with an information collection subject to the requirements of the Paperwork Reduction Act of 1995, unless the information collection has a currently valid OMB Control Number. The OMB Control Number for this information collection is 0651-0035. Public burden for this form is estimated to average 3 minutes per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the information collection. Send comments regarding this burden estimate or any other aspect of this information collection, including suggestions for reducing this burden to the Chief Administrative Officer, United States Patent and Trademark Office, P.O. Box 1450, Alexandria, VA 22313-1450 or email InformationCollection@uspto.gov. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. If filing this completed form by mail, send to: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

## Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. The United States Patent and Trademark Office (USPTO) collects the information in this record under authority of 35 U.S.C. 2. The USPTO's system of records is used to manage all applicant and owner information including name, citizenship, residence, post office address, and other information with respect to inventors and their legal representatives pertaining to the applicant's/owner's activities in connection with the invention for which a patent is sought or has been granted. The applicable Privacy Act System of Records Notice for the information collected in this form is COMMERCE/PAT-TM-7 Patent Application Files, available in the Federal Register at 78 FR 19243 (March 29, 2013). <https://www.govinfo.gov/content/pkg/FR-2013-03-29/pdf/2013-07341.pdf>

Routine uses of the information in this record may include disclosure to: 1) law enforcement, in the event that the system of records indicates a violation or potential violation of law; 2) a Federal, state, local, or international agency, in response to its request; 3) a contractor of the USPTO having need for the information in order to perform a contract; 4) the Department of Justice for determination of whether the Freedom of Information Act (FOIA) requires disclosure of the record; 5) a Member of Congress submitting a request involving an individual to whom the record pertains, when the individual has requested the Member's assistance with respect to the subject matter of the record; 6) a court, magistrate, or administrative tribunal, in the course of presenting evidence, including disclosures to opposing counsel in the course of settlement negotiations; 7) the Administrator, General Services Administration (GSA), or their designee, during an inspection of records conducted by GSA under authority of 44 U.S.C. 2904 and 2906, in accordance with the GSA regulations and any other relevant (i.e., GSA or Commerce) directive, where such disclosure shall not be used to make determinations about individuals; 8) another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)); 9) the Office of Personnel Management (OPM) for personnel research purposes; and 9) the Office of Management and Budget (OMB) for legislative coordination and clearance.

If you do not furnish the information requested on this form, the USPTO may not be able to process and/or examine your submission, which may result in termination of proceedings, abandonment of the application, and/or expiration of the patent.

## Additional Uses

Additional USPTO uses of the information in this record may include disclosure to: 1) the International Bureau of the World Intellectual Property Organization, if the record is related to an international application filed under the Patent Cooperation Treaty; 2) the public i) after publication of the application pursuant to 35 U.S.C. 122(b), ii) after issuance of a patent pursuant to 35 U.S.C. 151, iii) if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections, or an issued patent, or iv) without publication of the application or patent under the specific circumstances provided for by 37 CFR 1.14(a)(1)(v)-(vii); and/or 3) the National Archives and Records Administration, for inspection of records.

## TRANSMITTAL FOR POWER OF ATTORNEY TO ONE OR MORE REGISTERED PRACTITIONERS

NOTE: This form is to be submitted with the Power of Attorney by Applicant form (PTO/AIA/82B) to identify the application to which the Power of Attorney is directed, in accordance with 37 CFR 1.5, unless the application number and filing date are identified in the Power of Attorney by Applicant form. If neither form PTO/AIA/82A nor form PTO/AIA82B identifies the application to which the Power of Attorney is directed, the Power of Attorney will not be recognized in the application.

|                        |                       |
|------------------------|-----------------------|
| Application Number     | 15/638,461            |
| Filing Date            | June 30, 2017         |
| First Named Inventor   | Yong Chen             |
| Title                  | FLOW CYTOMETER        |
| Art Unit               | 2884                  |
| Examiner Name          | Fani Polyzos BOOSALIS |
| Attorney Docket Number | BECC.P0002US.CIP.C1   |

### SIGNATURE of Applicant or Patent Practitioner

|                                                    |                 |                     |                |
|----------------------------------------------------|-----------------|---------------------|----------------|
| Signature                                          | /Mark G. Tison/ | Date (Optional)     | March 30, 2023 |
| Name                                               | Mark G. Tison   | Registration Number | 65,985         |
| Title (if Applicant is a juristic entity)          |                 |                     |                |
| Applicant Name (if Applicant is a juristic entity) |                 |                     |                |

**NOTE:** This form must be signed in accordance with 37 CFR 1.33. See 37 CFR 1.4(d) for signature requirements and certifications. If more than one applicant, use multiple forms.

☐

\*Total of \_\_\_\_\_ forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

## POWER OF ATTORNEY BY APPLICANT

I hereby revoke all previous powers of attorney given in the application identified in either the attached transmittal letter or the boxes below.

|                    |                   |
|--------------------|-------------------|
| Application Number | Filing Date       |
| 14/555,102         | November 26, 2014 |

(Note: The boxes above may be left blank if information is provided on form PTO/AIA/82A.)

- ☒ I hereby appoint the Patent Practitioner(s) associated with the following Customer Number as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above: 129381
- OR**
- ☐ I hereby appoint Practitioner(s) named in the attached list (form PTO/AIA/82C) as my/our attorney(s) or agent(s), and to transact all business in the United States Patent and Trademark Office connected therewith for the patent application referenced in the attached transmittal letter (form PTO/AIA/82A) or identified above. (Note: Complete form PTO/AIA/82C.)

**Please recognize or change the correspondence address for the application identified in the attached transmittal letter or the boxes above to:**

- ☒ The address associated with the above-mentioned Customer Number
- OR**
- ☐ The address associated with Customer Number: 129381
- OR**

|                         |  |       |  |     |  |
|-------------------------|--|-------|--|-----|--|
| Firm or Individual Name |  |       |  |     |  |
| Address                 |  |       |  |     |  |
| City                    |  | State |  | Zip |  |
| Country                 |  |       |  |     |  |
| Telephone               |  | Email |  |     |  |


I am the Applicant (if the Applicant is a juristic entity, list the Applicant name in the box):

IRIS INTERNATIONAL, INC.

- ☐ Inventor or Joint Inventor (title not required below)
- ☐ Legal Representative of a Deceased or Legally Incapacitated Inventor (title not required below)
- ☒ Assignee or Person to Whom the Inventor is Under an Obligation to Assign (provide signer's title if applicant is a juristic entity)
- ☐ Person Who Otherwise Shows Sufficient Proprietary Interest (e.g., a petition under 37 CFR 1.46(b)(2) was granted in the application or is concurrently being filed with this document) (provide signer's title if applicant is a juristic entity)

### SIGNATURE of Applicant for Patent

The undersigned (whose title is supplied below) is authorized to act on behalf of the applicant (e.g., where the applicant is a juristic entity).

|           |                                                                                     |                 |  |
|-----------|-------------------------------------------------------------------------------------|-----------------|--|
| Signature |  | Date (Optional) |  |
| Name      | Daniel B. Kim                                                                       |                 |  |
| Title     | Assistant Secretary, Iris International, Inc.                                       |                 |  |

**NOTE:** Signature - This form must be signed by the applicant in accordance with 37 CFR 1.33. See 37 CFR 1.4 for signature requirements and certifications. If more than one applicant, use multiple forms.

☒ Total of 1 forms are submitted.

This collection of information is required by 37 CFR 1.131, 1.32, and 1.33. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.11 and 1.14. This collection is estimated to take 3 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

## Privacy Act Statement

The **Privacy Act of 1974 (P.L. 93-579)** requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.



## ELECTRONIC ACKNOWLEDGEMENT RECEIPT

APPLICATION #  
**15/638,461**

RECEIPT DATE / TIME  
**03/30/2023 03:51:30 PM ET**

ATTORNEY DOCKET #  
**BECC.P0002US.CIP.C1**

### Title of Invention

FLOW CYTOMETER

### Application Information

APPLICATION TYPE    Utility - Nonprovisional Application  
                                 under 35 USC 111(a)

PATENT #    10330582

CONFIRMATION #    9847

FILED BY    Grace Adame-Delgado

PATENT CENTER #    61842733

FILING DATE    06/30/2017

CUSTOMER #    32425

FIRST NAMED  
INVENTOR    Yong Qin Chen

CORRESPONDENCE  
ADDRESS    -

AUTHORIZED BY    Mark Tison

### Documents

**TOTAL DOCUMENTS: 2**

| DOCUMENT                                                       | PAGES | DESCRIPTION       | SIZE (KB) |
|----------------------------------------------------------------|-------|-------------------|-----------|
| BECC.P0002US.CIP.C1 -<br>POA.pdf                               | 3     | Power of Attorney | 328 KB    |
| BECC.P0002US.CIP.C1<br>Change of Correspondence<br>Address.pdf | 2     | Change of Address | 262 KB    |

### Digest

| DOCUMENT                                 | MESSAGE DIGEST(SHA-512)                           |
|------------------------------------------|---------------------------------------------------|
| BECC.P0002US.CIP.C1 -<br>Page 627 of 630 | 738D39B940402F1C714DBB2017CD7B866949420A7E06AD23E |

|                          |                                                                                     |
|--------------------------|-------------------------------------------------------------------------------------|
| POA.pdf                  | D5110D9FC6CB38E0CEEDB7385CD648938B0936B36CE6A3BA<br>D0718AF6C8E29B0B20065B43F65B6ED |
| BECC.P0002US.CIP.C1      | 00EEEF256652D55DC60585E88C88FC32378AC9715292B4F021                                  |
| Change of Correspondence | AE56711CC87E1A92946DF5F1A2373B69BEAB00E5B74AEFE6E                                   |
| Address.pdf              | 81728850B6E653C5D5A3E76AB9C0A                                                       |

This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.

#### **New Applications Under 35 U.S.C. 111**

If a new application is being filed and the application includes the necessary components for filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.

#### **National Stage of an International Application under 35 U.S.C. 371**

If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.

#### **New International Application Filed with the USPTO as a Receiving Office**

If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.





# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NUMBER | FILING OR 371(C) DATE | FIRST NAMED APPLICANT | ATTY. DOCKET NO./TITLE |
|--------------------|-----------------------|-----------------------|------------------------|
| 15/638,461         | 06/30/2017            | Yong Qin Chen         | BECC.P0002US.CIP.C1    |

**CONFIRMATION NO. 9847**

**POA ACCEPTANCE LETTER**

129381  
NORTON ROSE FULBRIGHT US LLP - BCI  
98 San Jacinto Blvd., Suite 1100  
Austin, TX 78701



Date Mailed: 04/03/2023

## NOTICE OF ACCEPTANCE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 03/30/2023.

The Power of Attorney in this application is accepted. Correspondence in this application will be mailed to the above address as provided by 37 CFR 1.33.

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at (571) 272-4000 or (571) 272-4200 or 1-888-786-0101.

/vostuart/



# UNITED STATES PATENT AND TRADEMARK OFFICE

UNITED STATES DEPARTMENT OF COMMERCE  
United States Patent and Trademark Office  
Address: COMMISSIONER FOR PATENTS  
P.O. Box 1450  
Alexandria, Virginia 22313-1450  
www.uspto.gov

| APPLICATION NUMBER | FILING OR 371(C) DATE | FIRST NAMED APPLICANT | ATTY. DOCKET NO./TITLE |
|--------------------|-----------------------|-----------------------|------------------------|
| 15/638,461         | 06/30/2017            | Yong Qin Chen         | BECC.P0002US.CIP.C1    |

**CONFIRMATION NO. 9847**

## POWER OF ATTORNEY NOTICE



\*OC000000137685110\*

32425  
NORTON ROSE FULBRIGHT US LLP  
98 SAN JACINTO BOULEVARD  
SUITE 1100  
AUSTIN, TX 78701-4255

Date Mailed: 04/03/2023

## NOTICE REGARDING CHANGE OF POWER OF ATTORNEY

This is in response to the Power of Attorney filed 03/30/2023.

- The Power of Attorney to you in this application has been revoked by the assignee who has intervened as provided by 37 CFR 3.71. Future correspondence will be mailed to the new address of record(37 CFR 1.33).

Questions about the contents of this notice and the requirements it sets forth should be directed to the Office of Data Management, Application Assistance Unit, at (571) 272-4000 or (571) 272-4200 or 1-888-786-0101.

/vostuart/