



US012268397B2

(12) **United States Patent**
Dayton et al.

(10) **Patent No.:** **US 12,268,397 B2**
(45) **Date of Patent:** **Apr. 8, 2025**

(54) **BONE CUTTING GUIDE SYSTEMS AND METHODS**

(71) Applicant: **Treace Medical Concepts, Inc.**, Ponte Vedra Beach, FL (US)

(72) Inventors: **Paul Dayton**, Ankeny, IA (US); **Robert D. Santrock**, Morgantown, WV (US); **Daniel J. Hatch**, Greeley, CO (US); **W. Bret Smith**, Lexington, SC (US); **Carlos Eduardo Gil**, Memphis, TN (US); **Sean F. Scanlan**, Jacksonville, FL (US); **Joe William Ferguson**, Ponte Vedra Beach, FL (US); **F. Barry Bays**, Collierville, TN (US); **John T. Treace**, Ponte Vedra Beach, FL (US)

(73) Assignee: **Treace Medical Concepts, Inc.**, Ponte Vedra, FL (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 0 days.

(21) Appl. No.: **18/645,205**

(22) Filed: **Apr. 24, 2024**

(65) **Prior Publication Data**

US 2024/0268836 A1 Aug. 15, 2024

Related U.S. Application Data

(63) Continuation of application No. 18/487,548, filed on Oct. 16, 2023, which is a continuation of application (Continued)

(51) **Int. Cl.**

A61B 17/15 (2006.01)

A61B 17/16 (2006.01)

(52) **U.S. Cl.**

CPC **A61B 17/151** (2013.01); **A61B 17/15** (2013.01); **A61B 17/1682** (2013.01)

(58) **Field of Classification Search**

CPC A61B 17/15; A61B 17/151; A61B 17/1682
See application file for complete search history.

(56) **References Cited**

U.S. PATENT DOCUMENTS

3,664,022 A 5/1972 Small
4,069,824 A 1/1978 Weinstock
(Continued)

FOREIGN PATENT DOCUMENTS

AU 2009227957 B2 7/2014
CA 2491824 A1 9/2005
(Continued)

OTHER PUBLICATIONS

Rx-Fix Mini Rail External Fixator, Wright Medical Technology, Brochure, Aug. 15, 2014, 2 pages.

(Continued)

Primary Examiner — Andrew Yang


(74) *Attorney, Agent, or Firm* — Fredrikson & Byron, P.A.

(57)

ABSTRACT

A bone cutting guide may include a support that contains a shaft movable relative to the support. The shaft may carry a guide member having one or more cut guides through which a clinician inserts a cutting member to cut bone positioned under the guide cut guides. In operation, a clinician may fixate the support of the bone cutting guide to a bone and translate the guide member until the one or more cut guides are positioned at a desired cut location. The clinician may then perform a cut through the cut guide. In some examples, the bone cutting guide includes additional components, such as bridging member or secondary cut guide, to provide additional functionality.

30 Claims, 18 Drawing Sheets



Paragon 28 v. Treace Medical Concepts
PGR2026-00017
Paragon Ex. 1001

Related U.S. Application Data

No. 17/118,597, filed on Dec. 10, 2020, now Pat. No. 11,786,257, which is a continuation of application No. 16/792,880, filed on Feb. 17, 2020, now Pat. No. 10,888,335, which is a continuation of application No. 16/593,153, filed on Oct. 4, 2019, now Pat. No. 10,561,426, which is a continuation of application No. 15/603,056, filed on May 23, 2017, now Pat. No. 10,603,046, which is a continuation of application No. 14/990,574, filed on Jan. 7, 2016, now Pat. No. 9,687,250.

(60) Provisional application No. 62/100,641, filed on Jan. 7, 2015.

(56) References Cited**U.S. PATENT DOCUMENTS**

4,159,716 A	7/1979	Borchers	5,643,270 A	7/1997	Combs
4,187,840 A	2/1980	Watanabe	5,667,510 A	9/1997	Combs
4,335,715 A	6/1982	Kirkley	H1706 H	1/1998	Mason
4,338,927 A	7/1982	Volkov et al.	5,722,978 A	3/1998	Jenkins
4,349,018 A	9/1982	Chambers	5,749,875 A	5/1998	Puddu
4,364,381 A	12/1982	Sher et al.	5,779,709 A	7/1998	Harris et al.
4,409,973 A	10/1983	Neufeld	5,788,695 A	8/1998	Richardson
4,440,168 A	4/1984	Warren	5,803,924 A	9/1998	Oni et al.
4,501,268 A	2/1985	Comparetto	5,810,822 A	9/1998	Mortier
4,502,474 A	3/1985	Comparetto	5,843,085 A	12/1998	Graser
4,509,511 A	4/1985	Neufeld	5,893,553 A	4/1999	Pinkous
4,565,191 A	1/1986	Slocum	5,911,724 A	6/1999	Wehrli
4,570,624 A	2/1986	Wu	5,935,128 A	8/1999	Carter et al.
4,627,425 A	12/1986	Reese	5,941,877 A	8/1999	Viegas et al.
4,628,919 A	12/1986	Clyburn	5,951,556 A	9/1999	Faccioli et al.
4,632,102 A	12/1986	Comparetto	5,980,526 A	11/1999	Johnson et al.
4,664,102 A	5/1987	Comparetto	5,984,931 A	11/1999	Greenfield
4,708,133 A	11/1987	Comparetto	6,007,535 A	12/1999	Rayhack et al.
4,736,737 A	4/1988	Fargie et al.	6,027,504 A	2/2000	McGuire
4,750,481 A	6/1988	Reese	6,030,391 A	2/2000	Brainard et al.
4,754,746 A	7/1988	Cox	6,162,223 A	12/2000	Orsak et al.
4,757,810 A	7/1988	Reese	6,171,309 B1	1/2001	Huebner
4,895,141 A	1/1990	Koeneman et al.	6,203,545 B1	3/2001	Stoffella
4,952,214 A	8/1990	Comparetto	6,248,109 B1	6/2001	Stoffella
4,959,066 A	9/1990	Dunn et al.	6,391,031 B1	5/2002	Toomey
4,978,347 A	12/1990	Ilizarov	6,478,799 B1	11/2002	Williamson
4,988,349 A	1/1991	Pennig	6,511,481 B2	1/2003	von Hoffmann et al.
4,995,875 A	2/1991	Coes	6,547,793 B1	4/2003	McGuire
5,021,056 A	6/1991	Hofmann et al.	6,676,662 B1	1/2004	Bagga et al.
5,035,698 A	7/1991	Comparetto	6,719,773 B1	4/2004	Boucher et al.
5,042,983 A	8/1991	Rayhack	6,743,233 B1	6/2004	Baldwin et al.
5,049,149 A	9/1991	Schmidt	6,755,838 B2	6/2004	Trnka
5,053,039 A	10/1991	Hofmann et al.	6,796,986 B2	9/2004	Duffner
5,078,719 A	1/1992	Schreiber	6,859,661 B2	2/2005	Tuke
5,112,334 A	5/1992	Alchermes et al.	7,018,383 B2	3/2006	McGuire
5,147,364 A	9/1992	Comparetto	7,033,361 B2	4/2006	Collazo
5,176,685 A	1/1993	Rayhack	7,097,647 B2	8/2006	Segler et al.
5,207,676 A	5/1993	Canadell et al.	7,112,204 B2	9/2006	Justin et al.
5,246,444 A	9/1993	Schreiber	7,153,310 B2	12/2006	Ralph et al.
5,254,119 A	10/1993	Schreiber	7,182,766 B1	2/2007	Mogul
5,312,412 A	5/1994	Whipple	7,241,298 B2	7/2007	Nemec et al.
5,358,504 A	10/1994	Paley et al.	7,282,054 B2	10/2007	Steffensmeier et al.
5,364,402 A	11/1994	Mumme et al.	7,377,924 B2	5/2008	Raistrick et al.
5,374,271 A	12/1994	Hwang	7,465,303 B2	12/2008	Riccione et al.
5,413,579 A	5/1995	Toit	7,540,874 B2	6/2009	Trumble et al.
5,417,694 A	5/1995	Marik et al.	7,572,258 B2	8/2009	Stiernborg
5,449,360 A	9/1995	Schreiber	7,641,660 B2	1/2010	Lakin et al.
5,470,335 A	11/1995	Du Toit	D610,257 S	2/2010	Horton
5,490,854 A	2/1996	Fisher et al.	7,686,811 B2	3/2010	Byrd et al.
5,529,075 A	6/1996	Clark	7,691,108 B2	4/2010	Lavallee
5,540,695 A	7/1996	Levy	7,763,026 B2	7/2010	Egger et al.
5,578,038 A	11/1996	Slocum	D629,900 S	12/2010	Fisher
5,586,564 A	12/1996	Barrett et al.	7,967,823 B2	6/2011	Ammann et al.
5,601,565 A	2/1997	Huebner	7,972,338 B2	7/2011	O'Brien
5,613,969 A	3/1997	Jenkins, Jr.	D646,389 S	10/2011	Claypool et al.
5,620,442 A	4/1997	Bailey et al.	8,057,478 B2	11/2011	Kuczynski et al.
5,620,448 A	4/1997	Puddu	8,062,301 B2	11/2011	Ammann et al.
			D651,315 S	12/2011	Bertoni et al.
			D651,316 S	12/2011	May et al.
			8,080,010 B2	12/2011	Schulz et al.
			8,080,045 B2	12/2011	Wotton, III
			8,083,746 B2	12/2011	Novak
			8,123,753 B2	2/2012	Poncet
			8,137,406 B2	3/2012	Novak et al.
			8,147,530 B2	4/2012	Strnad et al.
			8,167,918 B2	5/2012	Strnad et al.
			8,172,848 B2	5/2012	Tomko et al.
			8,192,441 B2	6/2012	Collazo
			8,197,487 B2	6/2012	Poncet et al.
			8,231,623 B1	7/2012	Jordan
			8,231,663 B2	7/2012	Kay et al.
			8,236,000 B2	8/2012	Ammann et al.
			8,246,561 B1	8/2012	Agee et al.
			D666,721 S	9/2012	Wright et al.
			8,262,664 B2	9/2012	Justin et al.
			8,277,459 B2	10/2012	Sand et al.
			8,282,644 B2	10/2012	Edwards
			8,282,645 B2	10/2012	Lawrence et al.
			8,292,966 B2	10/2012	Morton

(56)

References Cited

U.S. PATENT DOCUMENTS

8,303,596 B2	11/2012	Plassky et al.	2002/0099381 A1	7/2002	Maroney
8,313,492 B2	11/2012	Wong et al.	2002/0107519 A1	8/2002	Dixon et al.
8,323,289 B2	12/2012	Re	2002/0165552 A1	11/2002	Duffner
8,337,503 B2	12/2012	Lian	2002/0198531 A1	12/2002	Millard et al.
8,343,159 B2	1/2013	Bennett	2004/0010259 A1	1/2004	Keller et al.
8,377,105 B2	2/2013	Buescher	2004/0039394 A1	2/2004	Conti et al.
D679,395 S	4/2013	Wright et al.	2004/0097946 A1	5/2004	Dietzel et al.
8,409,209 B2	4/2013	Ammann et al.	2004/0138669 A1	7/2004	Horn
8,435,246 B2	5/2013	Fisher et al.	2005/0004676 A1	1/2005	Schon et al.
8,475,462 B2	7/2013	Thomas et al.	2005/0059978 A1	3/2005	Sherry et al.
8,496,662 B2	7/2013	Novak et al.	2005/0070909 A1	3/2005	Egger et al.
8,523,870 B2	9/2013	Green et al.	2005/0075641 A1	4/2005	Singhatat et al.
8,529,571 B2	9/2013	Horan et al.	2005/0101961 A1	5/2005	Huebner et al.
8,540,777 B2	9/2013	Ammann et al.	2005/0149042 A1	7/2005	Metzger
8,545,508 B2	10/2013	Collazo	2005/0228389 A1	10/2005	Stiernborg
D694,884 S	12/2013	Mooradian et al.	2005/0251147 A1	11/2005	Novak
D695,402 S	12/2013	Dacosta et al.	2005/0267482 A1	12/2005	Hyde, Jr.
8,652,142 B2	2/2014	Geissler	2005/0273112 A1	12/2005	McNamara
8,657,820 B2	2/2014	Kubiak et al.	2006/0036257 A1	2/2006	Steffensmeier
D701,303 S	3/2014	Cook	2006/0129163 A1	6/2006	McGuire
8,672,945 B2	3/2014	Lavallee et al.	2006/0206044 A1	9/2006	Simon
8,696,716 B2	4/2014	Kartalian et al.	2006/0217733 A1	9/2006	Plassky et al.
8,702,715 B2	4/2014	Ammann et al.	2006/0229621 A1	10/2006	Cadmus
D705,929 S	5/2014	Frey	2006/0241607 A1	10/2006	Myerson et al.
8,715,363 B2	5/2014	Ratron et al.	2006/0241608 A1	10/2006	Myerson et al.
8,728,084 B2	5/2014	Berelsman et al.	2006/0264961 A1	11/2006	Murray-Brown
8,758,354 B2	6/2014	Habegger et al.	2007/0010818 A1	1/2007	Stone et al.
8,764,760 B2	7/2014	Metzger et al.	2007/0123857 A1	5/2007	Deffenbaugh et al.
8,764,763 B2	7/2014	Wong et al.	2007/0233138 A1	10/2007	Figueroa et al.
8,771,279 B2	7/2014	Philippon et al.	2007/0265634 A1	11/2007	Weinstein
8,777,948 B2	7/2014	Bernsteiner	2007/0276383 A1	11/2007	Rayhack
8,784,427 B2	7/2014	Fallin et al.	2008/0009863 A1	1/2008	Bond et al.
8,784,457 B2	7/2014	Graham	2008/0015603 A1	1/2008	Collazo
8,795,286 B2	8/2014	Sand et al.	2008/0039850 A1	2/2008	Rowley et al.
8,801,727 B2	8/2014	Chan et al.	2008/0091197 A1	4/2008	Coughlin
8,808,303 B2	8/2014	Stemniski et al.	2008/0140081 A1	6/2008	Heavener et al.
8,828,012 B2	9/2014	May et al.	2008/0147073 A1	6/2008	Ammann et al.
8,858,602 B2	10/2014	Weiner et al.	2008/0172054 A1	7/2008	Claypool et al.
8,882,778 B2	11/2014	Ranft	2008/0195215 A1	8/2008	Morton
8,882,816 B2	11/2014	Kartalian et al.	2008/0208252 A1	8/2008	Holmes
8,888,785 B2	11/2014	Ammann et al.	2008/0262500 A1	10/2008	Collazo
D720,456 S	12/2014	Dacosta et al.	2008/0269908 A1	10/2008	Warburton
8,900,247 B2	12/2014	Tseng et al.	2008/0288004 A1	11/2008	Schendel
8,906,026 B2	12/2014	Ammann et al.	2009/0036893 A1	2/2009	Kartalian et al.
8,945,132 B2	2/2015	Plassky et al.	2009/0036931 A1	2/2009	Pech et al.
8,998,903 B2	4/2015	Price et al.	2009/0054899 A1	2/2009	Ammann et al.
8,998,904 B2	4/2015	Zeetser et al.	2009/0093849 A1	4/2009	Grabowski
9,023,052 B2	5/2015	Lietz et al.	2009/0105767 A1	4/2009	Reiley
9,044,250 B2	6/2015	Olsen et al.	2009/0118733 A1	5/2009	Orsak et al.
9,060,822 B2	6/2015	Lewis et al.	2009/0198244 A1	8/2009	Leibel
9,089,376 B2	7/2015	Medoff et al.	2009/0198279 A1	8/2009	Zhang et al.
9,101,421 B2	8/2015	Blacklidge	2009/0222047 A1	9/2009	Graham
9,107,715 B2	8/2015	Blitz et al.	2009/0254092 A1	10/2009	Albiol
9,113,920 B2	8/2015	Ammann et al.	2009/0254126 A1	10/2009	Orbay et al.
D740,424 S	10/2015	Dacosta et al.	2009/0287309 A1	11/2009	Walch et al.
D765,844 S	9/2016	DaCosta	2010/0069910 A1	3/2010	Hasselmann
D766,434 S	9/2016	DaCosta	2010/0121334 A1	5/2010	Couture et al.
D766,437 S	9/2016	DaCosta	2010/0130981 A1	5/2010	Richards
D766,438 S	9/2016	DaCosta	2010/0152782 A1	6/2010	Stone et al.
D766,439 S	9/2016	DaCosta	2010/0168799 A1	7/2010	Schumer
9,452,057 B2	9/2016	Dacosta et al.	2010/0185245 A1	7/2010	Paul et al.
9,522,023 B2	12/2016	Haddad et al.	2010/0249779 A1	9/2010	Hotchkiss et al.
9,750,538 B2	9/2017	Soffiatti et al.	2010/0256687 A1	10/2010	Neufeld et al.
9,785,747 B2	10/2017	Geebelen	2010/0318088 A1	12/2010	Warne et al.
9,980,760 B2	5/2018	Dacosta et al.	2010/0324556 A1	12/2010	Tyber et al.
10,028,750 B2	7/2018	Rose	2011/0009865 A1	1/2011	Orfaly
10,064,631 B2	9/2018	Dacosta et al.	2011/0093084 A1	4/2011	Morton
10,159,499 B2	12/2018	Dacosta et al.	2011/0118739 A1	5/2011	Tyber et al.
10,292,713 B2	5/2019	Fallin et al.	2011/0178524 A1	7/2011	Lawrence et al.
10,327,829 B2	6/2019	Dacosta et al.	2011/0245835 A1	10/2011	Dodds et al.
10,376,268 B2	8/2019	Fallin et al.	2011/0288550 A1	11/2011	Orbay et al.
10,470,779 B2	11/2019	Fallin et al.	2011/0301648 A1	12/2011	Lofthouse et al.
10,779,867 B2	9/2020	Penzimer et al.	2012/0016426 A1	1/2012	Robinson
11,304,705 B2	4/2022	Fallin et al.	2012/0065689 A1	3/2012	Prasad et al.
2002/0058944 A1	5/2002	Michelson	2012/0078258 A1	3/2012	Lo et al.
			2012/0123420 A1	5/2012	Honiball
			2012/0123484 A1	5/2012	Lietz et al.
			2012/0130376 A1	5/2012	Loring et al.
			2012/0130382 A1	5/2012	Iannotti et al.

(56)

References Cited

U.S. PATENT DOCUMENTS

2012/0130383 A1 5/2012 Budoff
 2012/0184961 A1 7/2012 Johannaber
 2012/0185056 A1 7/2012 Warburton
 2012/0191199 A1 7/2012 Raemisch
 2012/0239045 A1 9/2012 Li
 2012/0253350 A1 10/2012 Anthony et al.
 2012/0265301 A1 10/2012 Demers et al.
 2012/0277745 A1 11/2012 Lizée
 2012/0303033 A1 11/2012 Weiner et al.
 2012/0330135 A1 12/2012 Millahn et al.
 2013/0012949 A1 1/2013 Fallin et al.
 2013/0035694 A1 2/2013 Grimm et al.
 2013/0085499 A1 4/2013 Lian
 2013/0085502 A1 4/2013 Harrold
 2013/0096563 A1 4/2013 Meade et al.
 2013/0131821 A1 5/2013 Cachia
 2013/0150900 A1 6/2013 Haddad et al.
 2013/0150903 A1 6/2013 Vincent
 2013/0158556 A1 6/2013 Jones et al.
 2013/0165936 A1 6/2013 Myers
 2013/0165938 A1 6/2013 Chow et al.
 2013/0172942 A1 7/2013 Lewis et al.
 2013/0184714 A1 7/2013 Kaneyama et al.
 2013/0190765 A1 7/2013 Harris et al.
 2013/0190766 A1 7/2013 Harris et al.
 2013/0204259 A1 8/2013 Zajac
 2013/0226248 A1 8/2013 Hatch et al.
 2013/0226252 A1 8/2013 Mayer
 2013/0231668 A1 9/2013 Olsen et al.
 2013/0237987 A1 9/2013 Graham
 2013/0237989 A1 9/2013 Bonutti
 2013/0267956 A1 10/2013 Terrill et al.
 2013/0310836 A1 11/2013 Raub et al.
 2013/0325019 A1 12/2013 Thomas et al.
 2013/0325076 A1 12/2013 Palmer et al.
 2013/0331845 A1 12/2013 Horan et al.
 2013/0338785 A1 12/2013 Wong
 2014/0005672 A1 1/2014 Edwards et al.
 2014/0025127 A1 1/2014 Richter
 2014/0039501 A1 2/2014 Schickendantz et al.
 2014/0039561 A1 2/2014 Weiner et al.
 2014/0046387 A1 2/2014 Waizenegger
 2014/0074099 A1 3/2014 Vigneron et al.
 2014/0074101 A1 3/2014 Collazo
 2014/0094861 A1 4/2014 Fallin
 2014/0094924 A1 4/2014 Hacking et al.
 2014/0135775 A1 5/2014 Maxson et al.
 2014/0163563 A1 6/2014 Reynolds et al.
 2014/0171953 A1 6/2014 Gonzalvez et al.
 2014/0180342 A1 6/2014 Lowery et al.
 2014/0188139 A1 7/2014 Fallin et al.
 2014/0194884 A1 7/2014 Martin et al.
 2014/0194999 A1 7/2014 Orbay et al.
 2014/0207144 A1 7/2014 Lee et al.
 2014/0249537 A1 9/2014 Wong et al.
 2014/0257308 A1 9/2014 Johannaber
 2014/0257509 A1 9/2014 Dacosta et al.
 2014/0276815 A1 9/2014 Riccione
 2014/0276853 A1 9/2014 Long et al.
 2014/0277176 A1 9/2014 Buchanan et al.
 2014/0277214 A1 9/2014 Helenbolt et al.
 2014/0288562 A1 9/2014 Von Zabern et al.
 2014/0296995 A1 10/2014 Reiley et al.
 2014/0303621 A1 10/2014 Gerold et al.
 2014/0336658 A1 11/2014 Luna et al.
 2014/0343555 A1 11/2014 Russi et al.
 2014/0350561 A1 11/2014 Dacosta et al.
 2015/0032168 A1 1/2015 Orsak et al.
 2015/0045801 A1 2/2015 Axelson, Jr. et al.
 2015/0045839 A1 2/2015 Dacosta et al.
 2015/0051650 A1 2/2015 Verstrecken et al.
 2015/0057667 A1 2/2015 Ammann et al.
 2015/0066094 A1 3/2015 Prandi et al.
 2015/0112446 A1 4/2015 Melamed et al.
 2015/0119944 A1 4/2015 Geldwert

2015/0142064 A1 5/2015 Perez et al.
 2015/0150608 A1 6/2015 Sammarco
 2015/0182273 A1 7/2015 Stemmiski et al.
 2015/0223851 A1 8/2015 Hill et al.
 2015/0245858 A1 9/2015 Weiner et al.
 2016/0015426 A1 1/2016 Dayton
 2016/0022315 A1 1/2016 Soffiatti et al.
 2016/0135858 A1 5/2016 Dacosta et al.
 2016/0151165 A1 6/2016 Fallin et al.
 2016/0175089 A1 6/2016 Fallin et al.
 2016/0192950 A1 7/2016 Dayton et al.
 2016/0199076 A1 7/2016 Fallin et al.
 2016/0213384 A1 7/2016 Fallin et al.
 2016/0235414 A1 8/2016 Hatch et al.
 2016/0242791 A1 8/2016 Fallin et al.
 2016/0256204 A1 9/2016 Patel et al.
 2016/0324532 A1 11/2016 Montoya et al.
 2016/0354127 A1 12/2016 Lundquist et al.
 2017/0042598 A1 2/2017 Santrock et al.
 2017/0143511 A1 5/2017 Cachia
 2017/0164989 A1 6/2017 Weiner et al.
 2018/0132868 A1 5/2018 Dacosta et al.
 2018/0344334 A1 12/2018 Kim et al.

FOREIGN PATENT DOCUMENTS

CA 2854997 A1 5/2013
 CH 695846 A5 9/2006
 CN 2930668 Y 8/2007
 CN 201558162 U 8/2010
 CN 201572172 U 9/2010
 CN 201586060 U 9/2010
 CN 201912210 U 8/2011
 CN 101237835 B 11/2012
 CN 202801773 U 3/2013
 CN 103462675 A 12/2013
 CN 103505276 A 1/2014
 CN 203458450 U 3/2014
 CN 103735306 A 4/2014
 CN 102860860 B 5/2014
 CN 203576647 U 5/2014
 CN 104490460 A 4/2015
 CN 104510523 A 4/2015
 CN 104523327 A 4/2015
 CN 104546102 A 4/2015
 CN 204379413 U 6/2015
 CN 204410951 U 6/2015
 CN 204428143 U 7/2015
 CN 204428144 U 7/2015
 CN 204428145 U 7/2015
 CN 204446081 U 7/2015
 DE 202006010241 U1 3/2007
 DE 102007053058 B3 4/2009
 EP 685206 B1 9/2000
 EP 1508316 B1 5/2007
 EP 1897509 B1 7/2009
 EP 2124772 A1 12/2009
 EP 2124832 B1 8/2012
 EP 2632349 A1 9/2013
 EP 2665428 A1 11/2013
 EP 2742878 A1 6/2014
 EP 2750617 A1 7/2014
 EP 2849684 A1 3/2015
 EP 2624764 B1 12/2015
 EP 3023068 A2 5/2016
 FR 2362616 A1 3/1978
 FR 2764183 B1 11/1999
 FR 2953120 B1 1/2012
 FR 3030221 A1 6/2016
 GB 2154143 9/1985
 GB 2154144 A 9/1985
 GB 2334214 1/2003
 IN 200903719 P1 6/2009
 IN 200904479 P2 5/2010
 IN 140/DELNP/2012 P1 2/2013
 IN 2004/KOLNP/2013 P2 11/2013
 JP S635739 A 1/1988
 JP H0531116 A 2/1993
 JP 2004174265 A 6/2004

(56)

References Cited**FOREIGN PATENT DOCUMENTS**

JP	2006158972	A	6/2006
JP	4134243	B2	8/2008
JP	2008537498	A	9/2008
JP	4162380	B2	10/2008
JP	2011092405		5/2011
JP	2011523889		8/2011
JP	4796943	B2	10/2011
JP	5466647	B2	4/2014
JP	2014511207		5/2014
JP	2014521384	A	8/2014
JP	5628875	B2	11/2014
KR	100904142	B1	6/2009
MD	756	Z	11/2014
RU	2098036	C1	12/1997
RU	2195892	C2	1/2003
RU	2320287	C1	3/2008
RU	2321366	C2	4/2008
RU	2321369	C1	4/2008
RU	2346663	C2	2/2009
RU	2412662	C1	2/2011
SU	1333328	A2	8/1987
WO	0166022	A1	9/2001
WO	03075775	A1	9/2003
WO	2004089227	A2	10/2004
WO	2008051064	A1	5/2008
WO	2009029798	A1	3/2009
WO	2009032101	A2	3/2009
WO	2011037885	A1	3/2011
WO	2012029008	A1	3/2012
WO	2013090392	A1	6/2013
WO	2013134387	A1	9/2013
WO	2013169475	A1	11/2013
WO	2014020561	A1	2/2014
WO	2014022055	A1	2/2014
WO	2014035991	A1	3/2014
WO	2014085882	A1	6/2014
WO	2014147099	A1	9/2014
WO	2014152219	A2	9/2014
WO	2014152535	A1	9/2014
WO	2014177783	A1	11/2014
WO	2014200017	A1	12/2014
WO	2015094409	A1	6/2015
WO	2015105880	A1	7/2015
WO	2015127515	A2	9/2015
WO	2016134160	A1	8/2016

OTHER PUBLICATIONS

Saltzman et al., "Prospective Controlled Trial of STAR Total Ankle Replacement Versus Ankle Fusion: Initial Results," *Foot & Ankle International*, vol. 30, No. 7, Jul. 2009, pp. 579-596.

Scanlan et al., "Technique Tip: Subtalar Joint Fusion Using a Parallel Guide and Double Screw Fixation," *The Journal of Foot and Ankle Surgery*, vol. 49, Issue 3, May-Jun. 2010, pp. 305-309, (Abstract Only).

Scranton Jr. et al., "Anatomic Variations in the First Ray: Part I. Anatomic Aspects Related to Bunions Surgery," *Clinical Orthopaedics and Related Research*, vol. 151, Sep. 1980, pp. 244-255.

Siddiqui et al., "Fixation Of Metatarsal Fracture With Bone Plate In A Dromedary Heifer," *Open Veterinary Journal*, vol. 3, No. 1, 2013, pp. 17-20.

Sidekick Stealth Rearfoot Fixator, Wright Medical Technology, Surgical Technique, Dec. 2, 2013, 20 pages.

Simpson et al., "Computer-Assisted Distraction Osteogenesis By Ilizarov's Method," *International Journal of Medical Robots and Computer Assisted Surgery*, vol. 4, No. 4, Dec. 2008, pp. 310-320, (Abstract Only).

Small Bone External Fixation System, Acumed, Surgical Technique, Effective date Sep. 2014, 8 pages.

"Smith & Nephew scores a HAT-TRICK with its entry into the high-growth hammer toe repair market," *Smith & Nephew*, Jul. 31, 2014, 2 pages.

Stableloc External Fixation System, Acumed, Product Overview, Effective date Sep. 2015, 4 pages.

Stahl et al., "Derotation Of Post-Traumatic Femoral Deformities By Closed Intramedullary Sawing," *Injury*, vol. 37, No. 2, Feb. 2006, pp. 145-151, (Abstract Only).

Talbot et al., "Assessing Sesamoid Subluxation: How Good is the AP Radiograph?," *Foot and Ankle International*, vol. 19, No. 8, Aug. 1998, pp. 547-554.

TempFix Spanning the Ankle Joint Half Pin and Transfixing Pin Techniques, Biomet Orthopedics, Surgical Technique, 2012, 16 pages.

Tricot et al., "3D-corrective osteotomy using surgical guides for posttraumatic distal humeral deformity," *Acta Orthopaedica Belgica*, vol. 78, No. 4, 2012, pp. 538-542.

Vitek et al., "Die Behandlung des Hallux rigidus mit Cheilektomie und Akin-Moberg-Osteotomie unter Verwendung einer neuen Schnittlehre und eines neuen Schraubensystems," *Orthopadische Praxis*, vol. 44, Nov. 2008, pp. 563-566, including English Abstract on p. 564.

Vitek, "Neue Techniken in der Fußchirurgie Das V-tek-System," ABW Wissenschaftsverlag GmbH, 2009, 11 pages, including English Abstract.

Weber et al., "A Simple System For Navigation Of Bone Alignment Osteotomies Of The Tibia," *International Congress Series*, vol. 1268, Jan. 2004, pp. 608-613, (Abstract Only).

Weil et al., "Anatomic Plantar Plate Repair Using the Weil Metatarsal Osteotomy Approach," *Foot & Ankle Specialist*, vol. 4, No. 3, 2011, pp. 145-150.

Wendl et al., "Navigation in der Knieendoprothetik," *OP-Journal*, vol. 17, 2002, pp. 22-27, including English Abstract.

Whipple et al., "Zimmer Herbert Whipple Bone Screw System: Surgical Techniques for Fixation of Scaphoid and Other Small Bone Fractures," Zimmer, 2003, 59 pages.

Yackacki et al., "Compression Forces of Internal and External Ankle Fixation Devices with Simulated Bone Resorption," *Foot and Ankle International*, vol. 31, No. 1, Jan. 2010, pp. 76-85, (Abstract Only).

Yasuda et al., "Proximal Supination Osteotomy of the First Metatarsal for Hallux Valgus," *Foot and Ankle International*, vol. 36, No. 6, Jun. 2015, pp. 696-704.

Alvine et al., "Peg and Dowel Fusion of the Proximal Interphalangeal Joint," *Foot & Ankle*, vol. 1, No. 2, 1980, pp. 90-94.

Bednarsz et al., "Modified Lapidus Procedure for the Treatment of Hypermobile Hallux Valgus," *Foot & Ankle International*, vol. 21, No. 10, Oct. 2000, pp. 816-821.

Carr et al., "Correctional Osteotomy for Metatarsus Primus Varus and Hallux Valgus," *The Journal of Bone and Joint Surgery*, vol. 50-A, No. 7, Oct. 1968, pp. 1353-1367.

Coetzee et al., "The Lapidus Procedure: A Prospective Cohort Outcome Study," *Foot & Ankle International*, vol. 25, No. 8, Aug. 2004, pp. 526-531.

Doty et al., "Hallux valgus and hypermobility of the first ray: facts and fiction," *International Orthopaedics*, vol. 37, 2013, pp. 1655-1660.

Galli et al., "Enhanced Lapidus Arthrodesis: Crossed Screw Technique With Middle Cuneiform Fixation Further Reduces Sagittal Mobility," *The Journal of Foot & Ankle Surgery*, vol. 54, vol. 3, May/Jun. 2015, published online: Nov. 21, 2014, pp. 437-440.

Lapidus, "The Author's Bunion Operation From 1931 to 1959," *Clinical Orthopaedics*, vol. 16, 1960, pp. 119-135.

Osher et al., "Accurate Determination of Relative Metatarsal Protrusion with a Small Intermetatarsal Angle: A Novel Simplified Method," *The Journal of Foot & Ankle Surgery*, vol. 53, No. 5, Sep./Oct. 2014, published online: Jun. 3, 2014, pp. 548-556.

Patel et al., "Modified Lapidus Arthrodesis: Rate of Nonunion in 227 Cases," *The Journal of Foot & Ankle Surgery*, vol. 43, No. 1, Jan./Feb. 2004, pp. 37-42.

Toth et al., "The Effect of First Ray Shortening in the Development of Metatarsalgia in the Second Through Fourth Rays After Metatarsal Osteotomy," *Foot & Ankle International*, vol. 28, No. 1, Jan. 2007, pp. 61-63.

Easley et al., "Current Concepts Review: Hallux Valgus Part II: Operative Treatment," *Foot and Ankle International*, vol. 28, No. 6, Jun. 2007, pp. 748-758.

(56)

References Cited

OTHER PUBLICATIONS

- Kim et al., "A Multicenter Retrospective Review of Outcomes for Arthrodesis, Hemi-Metallic Joint Implant, and Resectional Arthroplasty in the Surgical Treatment of End-Stage Hallux Rigidus," *The Journal of Foot and Ankle Surgery*, vol. 51, 2012, pp. 50-56.
- Easley et al., "Current Concepts Review: Hallux Valgus Part I: Pathomechanics, Clinical Assessment, and Nonoperative Management," *Foot and Ankle International*, vol. 28, No. 5, May 2007, pp. 654-659.
- Sandhu et al., "Digital Arthrodesis With a One-Piece Memory Nitinol Intramedullary Fixation Device: A Retrospective Review," *Foot and Ankle Specialist*, vol. 6, No. 5, Oct. 2013, pp. 364-366.
- Weber et al., "Use of the First Ray Splay Test to Assess Transverse Plane Instability Before First Metatarsocuneiform Fusion," *The Journal of Foot and Ankle Surgery*, vol. 45, No. 4, Jul./Aug. 2006, pp. 278-282.
- Smith et al., "Opening Wedge Osteotomies for Correction of Hallux Valgus: A Review of Wedge Plate Fixation," *Foot and Ankle Specialist*, vol. 2, No. 6, Dec. 2009, pp. 277-282.
- Easley et al., "What is the Best Treatment for Hallux Valgus?," *Evidence-Based Orthopaedics—The Best Answers to Clinical Questions*, Chapter 73, 2009, pp. 479-491.
- Shurnas et al., "Proximal Metatarsal Opening Wedge Osteotomy," *Operative Techniques in Foot and Ankle Surgery*, Section I, Chapter 13, 2011, pp. 73-78.
- Coetzee et al., "Revision Hallux Valgus Correction," *Operative Techniques in Foot and Ankle Surgery*, Section I, Chapter 15, 2011, pp. 84-96.
- Le et al., "Tarsometatarsal Arthrodesis," *Operative Techniques in Foot and Ankle Surgery*, Section II, Chapter 40, 2011, pp. 281-285.
- Collan et al., "The biomechanics of the first metatarsal bone in hallux valgus: A preliminary study utilizing a weight bearing extremity CT," *Foot and Ankle Surgery*, vol. 19, 2013, pp. 155-161.
- Eustace et al., "Hallux valgus, first metatarsal pronation and collapse of the medial longitudinal arch—a radiological correlation," *Skeletal Radiology*, vol. 23, 1994, pp. 191-194.
- Mizuno et al., "Detorsion Osteotomy of the First Metatarsal Bone in Hallux Valgus," *Japanese Orthopaedic Association*, Tokyo, 1956; 30:813-819.
- Okuda et al., "The Shape of the Lateral Edge of the First Metatarsal Head as a Risk Factor for Recurrence of Hallux Valgus," *The Journal of Bone and Joint Surgery*, vol. 89, 2007, pp. 2163-2172.
- Okuda et al., "Proximal Metatarsal Osteotomy for Hallux Valgus: Comparison of Outcome for Moderate and Severe Deformities," *Foot and Ankle International*, vol. 29, No. 7, Jul. 2008, pp. 664-670.
- D'Amico et al., "Motion of the First Ray: Clarification Through Investigation," *Journal of the American Podiatry Association*, vol. 69, No. 1, Jan. 1979, pp. 17-23.
- Groves, "Operative Report," St. Tammany Parish Hospital, Date of Procedure, Mar. 26, 2014, 2 pages.
- Claim Chart for Groves Public Use (Mar. 26, 2014), Exhibit B4 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 161 pages.
- "Accu-Cut Osteotomy Guide System," BioPro, Brochure, Oct. 2018, 2 pages.
- "Acumed Osteotomiesystem Operationstechnik," Acumed, 2014, 19 pages (including 3 pages English translation).
- Albano et al., "Biomechanical Study of Transcortical or Transtrabecular Bone Fixation of Patellar Tendon Graft with Bioabsorbable Pins in ACL Reconstruction in Sheep," *Revista Brasileira de Ortopedia (Rev Bras Ortop.)* vol. 47, No. 1, 2012, pp. 43-49.
- Anderson et al., "Uncemented STAR Total Ankle Prostheses," *The Journal of Bone and Joint Surgery*, vol. 86(1, Suppl 2), Sep. 2004, pp. 103-111, (Abstract Only).
- Blomer, "Knieendoprothetik—Herstellerische Probleme und technologische Entwicklungen," *Orthopäde*, vol. 29, 2000, pp. 688-696, including English Abstract on p. 689.
- Bouaicha et al., "Fixation of Maximal Shift Scarf Osteotomy with Inside-Out Plating: Technique Tip," *Foot & Ankle International*, vol. 32, No. 5, May 2011, pp. 567-569.
- Dayton et al., "Is Our Current Paradigm for Evaluation and Management of the Bunion Deformity Flawed? A Discussion of Procedure Philosophy Relative to Anatomy," *The Journal of Foot and Ankle Surgery*, vol. 54, 2015, pp. 102-111.
- Dayton et al., "Observed Changes in Radiographic Measurements of the First Ray after Frontal and Transverse Plane Rotation of the Hallux: Does the Hallux Drive the Metatarsal in a Bunion Deformity?," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 584-587.
- Dayton et al., "Relationship Of Frontal Plane Rotation Of First Metatarsal To Proximal Articular Set Angle And Hallux Alignment In Patients Undergoing Tarsometatarsal Arthrodesis For Hallux Abducto Valgus: A Case Series And Critical Review Of The Literature," *The Journal of Foot and Ankle Surgery*, vol. 52, No. 3, May/Jun. 2013, pp. 348-354.
- Dayton et al., "Quantitative Analysis of the Degree of Frontal Rotation Required to Anatomically Align the First Metatarsal Phalangeal Joint During Modified Tarsal-Metatarsal Arthrodesis Without Capsular Balancing," *The Journal of Foot and Ankle Surgery*, 2015, pp. 1-6.
- De Geer et al., "A New Measure of Tibial Sesamoid Position in Hallux Valgus in Relation to the Coronal Rotation of the First Metatarsal in CT Scans," *Foot and Ankle International*, Mar. 26, 2015, 9 pages.
- Didomenico et al., "Correction of Frontal Plane Rotation of Sesamoid Apparatus during the Lapidus Procedure: A Novel Approach," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 248-251.
- Dobbe et al., "Patient-Tailored Plate For Bone Fixation And Accurate 3D Positioning In Corrective Osteotomy," *Medical and Biological Engineering and Computing*, vol. 51, No. 1-2, Feb. 2013, pp. 19-27, (Abstract Only).
- EBI Extra Small Rail Fixator, Biomet Trauma, retrieved Dec. 19, 2014, from the Internet: <<http://footandanklefixation.com/product/biomet-trauma-ebi-extra-small-rail-fixator/>>, 7 pages.
- "Futura Forefoot Implant Arthroplasty Products," Tornier, Inc., 2008, 14 pages.
- Garthwait, "Accu-Cut System Facilitates Enhanced Precision," *Podiatry Today*, vol. 18, No. 6, Jun. 2005, 6 pages.
- Gonzalez Del Pino et al., "Variable Angle Locking Intercarpal Fusion System for Four-Corner Arthrodesis: Indications and Surgical Technique," *Journal of Wrist Surgery*, vol. 1, No. 1, Aug. 2012, pp. 73-78.
- Gotte, "Entwicklung eines Assistenzrobotersystems für die Knieendoprothetik," *Forschungsberichte, Technische Universität München*, 165, 2002, 11 pages, including partial English Translation.
- Gregg et al., "Plantar plate repair and Weil osteotomy for metatarsophalangeal joint instability," *Foot and Ankle Surgery*, vol. 13, 2007, pp. 116-121.
- Grondal et al., "A Guide Plate for Accurate Positioning of First Metatarsophalangeal Joint during Fusion," *Operative Orthopädie Und Traumatologie*, vol. 16, No. 2, 2004, pp. 167-178 (Abstract Only).
- "HAT-TRICK Lesser Toe Repair System," Smith & Nephew, Brochure, Aug. 2014, 12 pages.
- "HAT-TRICK Lesser Toe Repair System, Foot and Ankle Technique Guide, Metatarsal Shortening Osteotomy Surgical Technique," Smith & Nephew, 2014, 16 pages.
- Hetherington et al., "Evaluation of surgical experience and the use of an osteotomy guide on the apical angle of an Austin osteotomy," *The Foot*, vol. 18, 2008, pp. 159-164.
- Hirao et al., "Computer assisted planning and custom-made surgical guide for malunited pronation deformity after first metatarsophalangeal joint arthrodesis in rheumatoid arthritis: A case report," *Computer Aided Surgery*, vol. 19, Nos. 1-3, 2014, pp. 13-19.
- "Hoffmann II Compact External Fixation System," Stryker, Brochure, Literature No. 5075-1-500, 2006, 12 pages.
- "Hoffmann II Micro Lengthener," Stryker, Operative Technique, Literature No. 5075-2-002, 2008, 12 pages.

(56)

References Cited**OTHER PUBLICATIONS**

"Hoffmann Small System External Fixator Orthopedic Instruments," Stryker, retrieved Dec. 19, 2014, from the Internet: <http://www.alibaba.com/product-detail/Stryker-Hoffmann-Small-System-External-Fixator_1438850129.html>, 3 pages.

Kim et al., "A New Measure of Tibial Sesamoid Position in Hallux Valgus in Relation to the Coronal Rotation of the First Metatarsal in CT Scans," *Foot and Ankle International*, vol. 36, No. 8, 2015, pp. 944-952.

"Lag Screw Target Bow," Stryker Leibinger GmbH & Co. KG, Germany 2004, 8 pages.

Lieske et al., "Implantation einer Sprunggelenktotale-Endoprothese vom Typ Salto 2," *Operative Orthopädie und Traumatologie*, vol. 26, No. 4, 2014, pp. 401-413, including English Abstract on p. 403. MAC (Multi Axial Correction) Fixation System, Biomet Trauma, retrieved Dec. 19, 2014, from the Internet: <<http://footandanklefixation.com/product/biomet-trauma-mac-multi-axial-correction-fixation-system>>, 7 pages.

Magin, "Computernavigierter Gelenkersatz am Knie mit dem Orthopilot," *Operative Orthopädie und Traumatologie*, vol. 22, No. 1, 2010, pp. 63-80, including English Abstract on p. 64.

Magin, "Die belastungsstabile Lapidus-Arthrodesse bei Hallux-valgus-Deformität mittels IVP-Plattenfixateur (V-TEK-System)," *Operative Orthopädie und Traumatologie*, vol. 26, No. 2, 2014, pp. 184-195, including English Abstract on p. 186.

Michelangelo Bunion System, Surgical Technique, Instratek Incorporated, publication date unknown, 4 pages.

Mini Joint Distractor, Arthrex, retrieved Dec. 19, 2014, from the Internet: <<http://www.arthrex.com/foot-ankle/mini-joint-distractor/products>>, 2 pages.

MiniRail System, Small Bone Innovations, Surgical Technique, 2010, 24 pages.

Miyake et al., "Three-Dimensional Corrective Osteotomy for Malunited Diaphyseal Forearm Fractures Using Custom-Made Surgical Guides Based on Computer Simulation," *JBJS Essential Surgical Techniques*, vol. 2, No. 4, 2012, 11 pages.

Modular Rail System: External Fixator, Smith & Nephew, Surgical Technique, 2013, 44 pages.

Monnich et al., "A Hand Guided Robotic Planning System for Laser Osteotomy in Surgery," *World Congress on Medical Physics and Biomedical Engineering* vol. 25/6: Surgery, Minimal Invasive Interventions, Endoscopy and Image Guided Therapy, Sep. 7-12, 2009, pp. 59-62, (Abstract Only).

Moore et al., "Effect Of Ankle Flexion Angle On Axial Alignment Of Total Ankle Replacement," *Foot and Ankle International*, vol. 31, No. 12, Dec. 2010, pp. 1093-1098, (Abstract Only).

Mortier et al., "Axial Rotation of the First Metatarsal Head in a Normal Population and Hallux Valgus Patients," *Orthopaedics and Traumatology: Surgery and Research*, vol. 98, 2012, pp. 677-683.

Nagy et al., "The AO Ulnar Shortening Osteotomy System Indications and Surgical Technique," *Journal of Wrist Surgery*, vol. 3, No. 2, 2014, pp. 91-97.

NexFix from Nexa Orthopedics, MetaFix I from Merete Medical, Inc. and The BioPro Lower Extremities from BioPro, found in *Foot & Ankle International Journal*, vol. 28, No. 1, Jan. 2007, 4 pages.

Odenbring et al., "A guide instrument for high tibial osteotomy," *Acta Orthopaedica Scandinavica*, vol. 60, No. 4, 1989, pp. 449-451.

Okuda et al., "Postoperative Incomplete Reduction of the Sesamoids as a Risk Factor for Recurrence of Hallux Valgus," *The Journal of Bone and Joint Surgery*, vol. 91-A, No. 1, Jul. 2009, pp. 1637-1645.

Otsuki et al., "Developing a novel custom cutting guide for curved per-acetabular osteotomy," *International Orthopaedics (SICOT)*, vol. 37, 2013, pp. 1033-1038.

"Patient to Patient Precision, Accu-Cut, Osteotomy Guide System," *BioPro, Foot & Ankle International Journal*, vol. 23, No. 8, Aug. 2002, 2 pages.

Peters et al., "Flexor Hallucis Longus Tendon Laceration as a Complication of Total Ankle Arthroplasty," *Foot & Ankle International*, vol. 34, No. 1, 2013, pp. 148-149.

"Prophecy Inbone Preoperative Navigation Guides," Wright Medical Technology, Inc., Nov. 2013, 6 pages.

"RAYHACK Ulnar Shortening Generation II Low-Profile Locking System Surgical Technique," Wright Medical Technology, Inc., Dec. 2013, 20 pages.

Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 41 pages.

Prior Art Publications, Exhibit A of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 3 pages.

Claim Chart for Fishco, "Making the Lapidus Easy," The Podiatry Institute (Apr. 2014), Exhibit B1 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 97 pages.

Claim Chart for Fishco, "A Straightforward Guide to the Lapidus Bunionectomy," HMP Global (Sep. 6, 2013), Exhibit B2 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 67 pages.

Claim Chart for Groves, "Functional Position Joint Sectioning: Pre-Load Method for Lapidus Arthrodesis," Update 2015: Proceedings of the Annual Meeting of the Podiatry Institute, Chpt. 6, pp. 23-29 (Apr. 2015), Exhibit B3 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 151 pages.

Claim Chart for Mote, "First Metatarsal-Cuneiform Arthrodesis for the Treatment of First Ray Pathology: A Technical Guide," The Journal Foot & Ankle Surgery (Sep. 1, 2009), Exhibit B5 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 21 pages.

Claim Chart for U.S. Pat. No. 10,376,268 to Fallin et al., entitled "Indexed Tri-Planar Osteotomy Guide and Method," issued Aug. 13, 2019, Exhibit B6 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 155 pages.

Claim Chart for U.S. Pat. No. 8,282,645 to Lawrence et al., entitled "Metatarsal Bone Implant Cutting Guide," issued Jan. 18, 2010, Exhibit B7 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 76 pages.

Claim Chart for U.S. Pat. No. 9,452,057 to Dacosta et al., entitled "Bone Implants and Cutting Apparatuses and Methods," issued Apr. 8, 2011, Exhibit B8 of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 110 pages.

Obviousness Chart, Exhibit C of Defendant Fusion Orthopedics LLC's Invalidity Contentions, No. CV-22-00490-PHX-SRB, US District Court for the District of Arizona, Aug. 27, 2022, 153 pages.

"Foot and Ankle Instrument Set," Smith & Nephew, 2013, 2 pages.

"Lapidus Pearls: Gaining Joint Exposure to Decrease Non-Union," Youtube, Retrieved online from <<https://www.youtube.com/watch?v=jqJyE7pj-Y>>, dated Nov. 2, 2009, 3 pages.

"Reconstructive Surgery of the Foot & Ankle," The Podiatry Institute, Update 2015, Conference Program, May 2015, 28 pages.

"Speed Continuous Active Compression Implant," BioMedical Enterprises, Inc., A120-029 Rev. 3, 2013, 4 pages.

"Visionaire: Patient Matched Cutting Blocks Surgical Procedure," Smith & Nephew, Inc., 2009, 2 pages.

Arthrex, "Comprehensive Foot System," Retrieved online from <https://www.arthrex.com/resources/animation/8U3iaPvY6kO8bwFAwZF50Q/comprehensive-foot-system?referringTeam=foot_and_ankle>, dated Aug. 27, 2013, 3 pages.

Baravarian, "Why the Lapidus Procedure is Ideal for Bunions," Podiatry Today, Retrieved online from <<https://www.hmpglobal-learnhmpglobal.com/site/podipodi/article/5542>>, dated May 2006, 8 pages.

Bauer et al., "Offset-V Osteotomy of the First Metatarsal Shaft in Hallux Abducto Valgus," McGlamry's Comprehensive Textbook of Foot and Ankle Surgery, Fourth Edition, vol. 1, Chapter 29, 2013, 26 pages.

(56)

References Cited**OTHER PUBLICATIONS**

- Cottom, "Fixation of the Lapidus Arthrodesis with a Plantar Interfragmentary Screw and Medial Low Profile Locking Plate," *The Journal of Foot & Ankle Surgery*, vol. 51, 2012, pp. 517-522.
- Coughlin, "Fixation of the Lapidus Arthrodesis with a Plantar Interfragmentary Screw and Medial Low Profile Locking Plate," *Orthopaedics and Traumatology*, vol. 7, 1999, pp. 133-143.
- Dayton et al., "Observed Changes in Radiographic Measurements of the First Ray after Frontal Plane Rotation of the First Metatarsal in a Cadaveric Foot Model," *The Journal of Foot & Ankle Surgery*, vol. 53, 2014, pp. 274-278.
- Dayton et al., "Relationship of Frontal Plane Rotation of First Metatarsal to Proximal Articular Set Angle and Hallux Alignment in Patients Undergoing Tarsometatarsal Arthrodesis for Hallux Abducto Valgus: A Case Series and Critical Review of the Literature," *The Journal of Foot & Ankle Surgery*, 2013, Article in Press, Mar. 1, 2013, 7 pages.
- DiDomenico et al., "Lapidus Bunionectomy: First Metatarsal-Cuneiform Arthrodesis," *McGraw-Hill's Comprehensive Textbook of Foot and Ankle Surgery*, Fourth Edition, vol. 1, Chapter 31, 2013, 24 pages.
- Fallin et al., US Provisional Application Entitled Indexed Tri-Planar Osteotomy Guide and Method, U.S. Appl. No. 62/118,378, filed Feb. 19, 2015, 62 pages.
- Fishco, "A Straightforward Guide To The Lapidus Bunionectomy," *Podiatry Today*, Retrieved online from <<https://www.hmpgloballearningnetwork.com/site/podiatry/blogged/straightforward-guide-lapidus-bunionectomy>>, dated Sep. 6, 2013, 5 pages.
- Fishco, "Making the Lapidus Easy," *The Podiatry Institute*, Update 2014, Chapter 14, 2014, pp. 91-93.
- Fleming et al., "Results of Modified Lapidus Arthrodesis Procedure Using Medial Eminence as an Interpositional Autograft," *The Journal of Foot & Ankle Surgery*, vol. 50, 2011, pp. 272-275.
- Fuhrmann, "Arthrodesis of the First Tarsometatarsal Joint for Correction of the Advanced Splayfoot Accompanied by a Hallux Valgus," *Operative Orthopädie und Traumatologie*, No. 2, 2005, pp. 195-210.
- Gerard et al., "The Modified Lapidus Procedure," *Orthopedics*, vol. 31, No. 3, Mar. 2008, 7 pages.
- Giannoudis et al., "Hallux Valgus Correction," *Practical Procedures in Elective Orthopaedic Surgery, Pelvis and Lower Extremity*, Chapter 38, 2012, 22 pages.
- Greiner, "The Jargon of Pedal Movements," *Foot & Ankle International*, vol. 28, No. 1, Jan. 2007, pp. 109-125.
- Groves, "Functional Position Joint Sectioning: Pre-Load Method for Lapidus Arthrodesis," *The Podiatry Institute*, Update 2015, Chapter 6, 2015, pp. 23-29.
- Hardy et al., "Observations on Hallux Valgus," *The Journal of Bone and Joint Surgery*, vol. 33B, No. 3, Aug. 1951, pp. 376-391.
- Holmes, Jr., "Correction of the Intermetatarsal Angle Component of Hallux Valgus Using Fiberwire-Attached Endo-buttons," *Revista Internacional de Ciencias Podológicas*, vol. 6, No. 2, 2012, pp. 73-79.
- Integra, "Integra Large Qwix Positioning and Fixation Screw, Surgical Technique," 2012, 16 pages.
- Kilmartin et al., "Combined rotation scarf and Akin osteotomies for hallux valgus: a patient focused 9 year follow up of 50 patients," *Journal of Foot and Ankle Research*, vol. 3, No. 2, 2010, 12 pages.
- Lee et al., "Technique Tip: Lateral Soft-Tissue Release for Correction of Hallux Valgus Through a Medial Incision Using A Dorsal Flap Over the First Metatarsal," *Foot & Ankle International*, vol. 28, No. 8, Aug. 2007, pp. 949-951.
- Mote et al., "First Metatarsal-Cuneiform Arthrodesis for the Treatment of First Ray Pathology: A Technical Guide," *JFAS Techniques Guide*, vol. 48, No. 5, Sep./Oct. 2009, pp. 593-601.
- Myerson, "Cuneiform-Metatarsal Arthrodesis," *The Foot and Ankle*, Chapter 9, 1997, pp. 107-117.
- Sammarco, "Surgical Strategies: Mau Osteotomy for Correction of Moderate and Severe Hallux Valgus Deformity," *Foot & Ankle International*, vol. 28, No. 7, Jul. 2007, pp. 857-864.
- Schon et al., "Cuneiform-Metatarsal Arthrodesis for Hallux Valgus," *The Foot and Ankle*, Second Edition, Chapter 8, 2002, pp. 99-117.
- Sokoloff, "Lapidus Procedure," *Textbook of Bunion Surgery*, Chapter 15, 1981, pp. 277-287.
- Stamatis et al., "Mini Locking Plate as "Medial Buttress" for Oblique Osteotomy for Hallux Valgus," *Foot & Ankle International*, vol. 31, No. 10, Oct. 2010, pp. 920-922.
- Stewart, "Use for BME Speed Nitinol Staple Fixation for the Lapidus Procedure," date unknown, 1 page.
- Wukich et al., "Hypermobility of the First Tarsometatarsal Joint," *Foot and Ankle Clinics*, vol. 10, No. 1, Mar. 2005, pp. 157-166.
- Dayton et al., "Biwinged Excision for Round Pedal Lesions," *The Journal of Foot and Ankle Surgery*, vol. 35, No. 3, 1996, pp. 244-249.
- Dayton et al., "Medial Incision Approach to the First Metatarsophalangeal Joint," *The Journal of Foot and Ankle Surgery*, vol. 40, No. 6, Nov./Dec. 2001, pp. 414-417.
- Dayton et al., "Reduction of the Intermetatarsal Angle after First Metatarsophalangeal Joint Arthrodesis in Patients with Moderate and Severe Metatarsus Primus Adductus," *The Journal of Foot and Ankle Surgery*, vol. 41, No. 5, Sep./Oct. 2002, pp. 316-319.
- Dayton et al., "Use of the Z Osteotomy for Tailor Bunionectomy," *The Journal of Foot and Ankle Surgery*, vol. 42, No. 3, May/Jun. 2003, pp. 167-169.
- Dayton et al., "Early Weightbearing After First Metatarsophalangeal Joint Arthrodesis: A Retrospective Observational Case Analysis," *The Journal of Foot and Ankle Surgery*, vol. 43, No. 3, May/Jun. 2004, pp. 156-159.
- Dayton et al., "Dorsal Suspension Stitch: An Alternative Stabilization After Flexor Tenotomy for Flexible Hammer Digit Syndrome," *The Journal of Foot and Ankle Surgery*, vol. 48, No. 5, Sep./Oct. 2009, pp. 602-605.
- Dayton et al., "The Extended Knee Hemilithotomy Position for Gastrocnemius Recession," *The Journal of Foot and Ankle Surgery*, vol. 49, 2010, pp. 214-216.
- Wienke et al., "Bone Stimulation For Nonunions: What the Evidence Reveals," *Podiatry Today*, vol. 24, No. 9, Sep. 2011, pp. 52-57.
- Dayton et al., "Hallux Varus as Complication of Foot Compartment Syndrome," *The Journal of Foot and Ankle Surgery*, vol. 50, 2011, pp. 504-506.
- Dayton et al., "Measurement of Mid-Calcaneal Length on Plain Radiographs: Reliability of a New Method," *Foot and Ankle Specialist*, vol. 4, No. 5, Oct. 2011, pp. 280-283.
- Dayton et al., "A User-Friendly Method of Pin Site Management for External Fixators," *Foot and Ankle Specialist*, Sep. 16, 2011, 4 pages.
- Dayton et al., "Effectiveness of a Locking Plate in Preserving Midcalcaneal Length and Positional Outcome after Evans Calcaneal Osteotomy: A Retrospective Pilot Study," *The Journal of Foot and Ankle Surgery*, vol. 52, 2013, pp. 710-713.
- Dayton et al., "Does Postoperative Showering or Bathing of a Surgical Site Increase the Incidence of Infection? A Systematic Review of the Literature," *The Journal of Foot and Ankle Surgery*, vol. 52, 2013, pp. 612-614.
- Dayton et al., "Technique for Minimally Invasive Reduction of Calcaneal Fractures Using Small Bilateral External Fixation," *The Journal of Foot and Ankle Surgery*, Article in Press, 2014, 7 pages.
- Dayton et al., "Clarification of the Anatomic Definition of the Bunion Deformity," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 160-163.
- Dayton et al., "Observed Changes in Radiographic Measurements of the First Ray after Frontal Plane Rotation of the First Metatarsal in a Cadaveric Foot Model," *The Journal of Foot and Ankle Surgery*, Article in Press, 2014, 5 pages.
- Dayton et al., "Observed Changes in First Metatarsal and Medial Cuneiform Positions after First Metatarsophalangeal Joint Arthrodesis," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 32-35.
- Dayton et al., "Reduction of the Intermetatarsal Angle after First Metatarsal Phalangeal Joint Arthrodesis: A Systematic Review," *The Journal of Foot and Ankle Surgery*, Article in Press, 2014, 4 pages.

(56)

References Cited**OTHER PUBLICATIONS**

Feilmeier et al., "Reduction of Intermetatarsal Angle after First Metatarsophalangeal Joint Arthrodesis in Patients with Hallux Valgus," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 29-31.

Dayton et al., "Principles of Management of Growth Plate Fractures in the Foot and Ankle," *Clinics in Podiatric Medicine and Surgery, Pediatric Foot Deformities*, Oct. 2013, 17 pages.

Dayton et al., "Observed Changes in Radiographic Measurements of the First Ray after Frontal and Transverse Plane Rotation of the Hallux: Does the Hallux Drive the Metatarsal in a Bunion Deformity?," *The Journal of Foot and Ankle Surgery*, Article in Press, 2014, 4 pages.

Rodriguez et al., "Ilizarov method of fixation for the management of pilon and distal tibial fractures in the compromised diabetic patient: A technique guide," *The Foot and Ankle Journal Online*, vol. 7, No. 2, 2014, 9 pages.

Feilmeier et al., "Incidence of Surgical Site Infection in the Foot and Ankle with Early Exposure and Showering of Surgical Sites: A Prospective Observation," *The Journal of Foot and Ankle Surgery*, vol. 53, 2014, pp. 173-175.

Catanese et al., "Measuring Sesamoid Position in Hallux Valgus: When Is the Sesamoid Axial View Necessary," *Foot and Ankle Specialist*, 2014, 3 pages.

Dayton et al., "Comparison of Complications for Internal and External Fixation for Charcot Reconstruction: A Systematic Review," *The Journal of Foot and Ankle Surgery*, Article in Press, 2015, 4 pages.

Dayton et al., "A new triplanar paradigm for bunion management," *Lower Extremity Review*, Apr. 2015, 9 pages.


Dayton et al., "American College of Foot and Ankle Surgeons' Clinical Consensus Statement: Perioperative Prophylactic Antibiotic Use in Clean Elective Foot Surgery," *The Journal of Foot and Ankle Surgery*, Article in Press, 2015, 7 pages.


Dayton et al., "Complications of Metatarsal Suture Techniques for Bunion Correction: A Systematic Review of the Literature," *The Journal of Foot and Ankle Surgery*, Article in Press, 2015, 3 pages.


DeCarbo et al., "The Weil Osteotomy: A Refresher," *Techniques in Foot and Ankle Surgery*, vol. 13, No. 4, Dec. 2014, pp. 191-198.

DeCarbo et al., "Resurfacing Interpositional Arthroplasty for Degenerative Joint Diseases of the First Metatarsalphalangeal Joint," *Podiatry Management*, Jan. 2013, pp. 137-142.

DeCarbo et al., "Locking Plates: Do They Prevent Complications?," *Podiatry Today*, Apr. 2014, 7 pages.







3A
GLE




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 3E




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16

1

BONE CUTTING GUIDE SYSTEMS AND METHODS**RELATED APPLICATION**

This application is a continuation of U.S. patent application Ser. No. 18/487,548, filed Oct. 16, 2023, which is continuation of U.S. patent application Ser. No. 17/118,597, filed Dec. 10, 2020 and issued as U.S. Pat. No. 11,786,257 on Oct. 17, 2023, which is a continuation of U.S. patent application Ser. No. 16/792,880, filed Feb. 17, 2020 and issued as U.S. Pat. No. 10,888,335 on Jan. 12, 2021, which is a continuation of U.S. patent application Ser. No. 16/593,153, filed Oct. 4, 2019 and issued as U.S. Pat. No. 10,561,426 on Feb. 18, 2020, which is a continuation of U.S. patent application Ser. No. 15/603,056, filed May 23, 2017 and issued as U.S. Pat. No. 10,603,046 on Mar. 31, 2020, which is a continuation of U.S. patent application Ser. No. 14/990,574, filed Jan. 7, 2016 and issued as U.S. Pat. No. 9,687,250 on Jun. 27, 2017, which in turn claims the benefit of U.S. Provisional Application Ser. No. 62/100,641, filed Jan. 7, 2015. The entire contents of each of these applications are hereby incorporated by reference.

TECHNICAL FIELD

This disclosure relates generally to devices and methods for positioning and cutting bones.

BACKGROUND

Bones, such as the bones of a foot, may be anatomically misaligned. In certain circumstances, surgical intervention is required to correctly align the bones to reduce patient discomfort and improve patient quality of life.

SUMMARY

In general, this disclosure is directed to bone cutting guide systems and techniques for cutting bones. In some examples, a bone cutting guide includes a main body, or support, that houses a shaft that can translate relative to the main body. The shaft may have a main guide member positioned on the end of the shaft. The main guide member may define opposed guide surfaces configured to receive a cutting member. For example, the cutting member may be inserted between the opposed guide surfaces and bounded within a range of movement by the guide surfaces, causing the cutting member to be directed at a cutting location under the guide surfaces. Additionally or alternatively, the main guide member may define a single cutting surface/plane. The cutting surface/plane may be a surface against which a clinician can position a cutting member and then guide the cutting member along the cutting surface/plane to perform a cutting operation.

The main body of the bone cutting guide can include fixation members, such as fixation pins or apertures, that allow the main body to be fixated on or adjacent a bone to be cut. For example, in use, a clinician may fixate the main body to a bone (e.g., a first metatarsal). Thereafter, the clinician may translate the main guide member having at least one cutting guide surface (e.g., opposed cutting guide surfaces) relative to the fixed main body. The clinician can translate the main guide member by sliding or rotating the shaft housed within the main body, e.g., causing the distal end of the shaft and main guide member carried thereon away from or towards the main body. Once suitably posi-

2

tioned, the clinician may or may not lock the location of the shaft and perform one or more cuts through the guide surfaces of the main guide member.

In some configurations, the bone cutting guide also includes a bridge component that can form a bridge over a section of bone, such as a joint between adjacent bones (e.g., first metatarsal-medial cuneiform joint). For example, the bridge component may have a proximal end that is attachable to the main guide member carried on the shaft attached to the main body and a distal end separated by one or more rails. The proximal end may be insertable between the opposed cutting guide surfaces of the main guide member, e.g., such that the proximal end of the bridge can be inserted between the guide surfaces after performing a cut through the guide surfaces. The distal end of the bridging member can include fixation members, such as fixation pins or apertures, that allow the distal end of the bridging member to be fixated to bone. In one application, the distal end of the bridging member is fixated to a different bone than the bone the main body is fixated to such that the bridging member spans a joint. In such applications, joint spacing may be expanded or contracted by translating the shaft carried by the main body.

In addition to or in lieu of providing a bridging member, in some additional configurations, the bone cutting guide may include a secondary guide member. The secondary guide member can be positioned distally of the main guide member and may also include guide surfaces, such as opposed guide surfaces forming a channel sized and shaped to receive a cutting member. The secondary guide member may facilitate making a second bone cut distal of a location where a first bone cut is made using the main guide member.

In one example, a bone cutting guide is described that includes a support defining an inner cavity and a shaft disposed at least partially within the inner cavity, where the shaft is translatable within the inner cavity relative to the support. The bone cutting guide also includes a main guide member located on an end of the shaft, where the main guide member includes a first guide surface defining a first plane and a second guide surface defining a second plane, and where the first plane is parallel to the second plane.

In another example, a method for cutting bones is described. The method includes fixing a support to a bone and aligning a main guide member to be positioned at a location to be cut. The method further includes making a first cut at the location to be cut by inserting a cutting member through a space defined between a first guide surface of the main guide member and a second guide surface of the main guide member.

The details of one or more examples are set forth in the accompanying drawings and the description below. Other features, objects, and advantages will be apparent from the description and drawings, and from the claims.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a side view of an embodiment of a bone cutting guide, with some components shown in an exploded view.

FIG. 2 is a perspective view of the bone cutting guide of FIG. 1.

FIG. 3A is a perspective view of the bone cutting guide of FIG. 1 with a bridge component attached to a main guide member.

FIGS. 3B-3D are top plan view illustrations of a bone cutting guide with different example connecting blocks.

FIG. 3E is a side plan view of a bone cutting guide and an exemplary support.

3

FIG. 4 is a perspective view of the bone cutting guide of FIG. 1 assembled.

FIG. 5 is another perspective view of the bone cutting guide of FIG. 4.

FIG. 6 is a further perspective view of the bone cutting guide of FIG. 4.

FIG. 7 is a perspective view of a bone cutting guide support fixed to a bone.

FIG. 8 is a top view of the bone cutting guide support fixed to the bone of FIG. 7.

FIG. 9 is a perspective view of the bone cutting guide support fixed to the bone of FIG. 7 with a location of the main guide member adjusted.

FIG. 10 is a perspective view of a bridge component attached to the main guide member of the support of FIG. 7 with a fixation structure attached to the bridge component.

FIG. 11 is a perspective view of the fixation structure pinned across a bone.

FIG. 12 is another perspective view of the pinned fixation structure of FIG. 11.

FIG. 13 is a perspective view of the assembled bone cutting guide fixed to bones.

FIG. 14 is a further perspective view of the assembled bone cutting guide of FIG. 13.

FIG. 15 shows a perspective view of the assembled bone cutting guide of FIG. 13 with a secondary guide member translated along rails of the bridge component.

FIG. 16 is an additional perspective view of the assembled bone cutting guide of FIG. 15.

DETAILED DESCRIPTION

The following detailed description is exemplary in nature and is not intended to limit the scope, applicability, or configuration of the invention in any way. Rather, the following description provides some practical illustrations for implementing exemplary embodiments of the present invention. Examples of constructions, materials, and dimensions are provided for selected elements, and all other elements employ that which is known to those of ordinary skill in the field of the invention. Those skilled in the art will recognize that many of the noted examples have a variety of suitable alternatives.

Embodiments of the present invention include a bone cutting guide. In an exemplary application, the bone cutting guide can be useful during a surgical procedure, such as a bone alignment, osteotomy, fusion procedure, and/or other procedures where one or more bones are to be cut. Such a procedure can be performed, for example, on bones (e.g., adjacent bones separated by a joint or different portions of a single bone) in the foot or hand, where bones are relatively smaller compared to bones in other parts of the human anatomy. In one example, a procedure utilizing the bone cutting guide can be performed to correct an alignment between a metatarsal (e.g. a first metatarsal) and a cuneiform (e.g., a first cuneiform), such as a bunion correction. An example of such a procedure is a lapidus procedure. In another example, the procedure can be performed by modifying an alignment of a metatarsal (e.g. a first metatarsal). An example of such a procedure is a basilar metatarsal osteotomy procedure.

FIGS. 1, 2, and 3A show an embodiment of a bone cutting guide 20 with some components of the bone cutting guide 20 shown in an exploded view. FIG. 1 is a side view of the bone cutting guide 20, while FIGS. 2 and 3A are perspective views of the bone cutting guide 20. The bone cutting guide 20 can include a support 30 which defines an inner cavity 40

4

(FIG. 2). In one embodiment, the support 30 can include a first fixation aperture 50A and a second fixation aperture 50B, each of which can extend through the support 30 and receive fixation pins 60A and 60B, respectively, such that the fixation pins 60A and 60B extend through the support 30 via the fixation apertures 50A and 50B. In the embodiment shown, the fixation pins 60A and 60B have a threaded first end adapted to threadingly engage with a bone, and allow the support 30 to be translated along a longitudinal axis of both pins 60A and 60B. In the illustrated embodiments, the fixation apertures 50A and 50B are located on opposite longitudinal ends of the support 30, but in other embodiments the fixation apertures 50A and 50B can be located at various positions on the support 30.

The support 30 can further include one or more extensions 70A and/or 70B protruding generally radially out from the support 30, which may define a concave surface configured to receive a generally cylindrical bone portion. In the embodiment shown, fixation aperture 50B is provided with an extension member 72 which can be threadingly coupled to the support 30. Such an extension member 72 can be adjusted relative to the support 30 to allow the support to become parallel with a longitudinal axis of a bone, if desired. In such embodiments, the support 30 can rest on a bone via the extensions 70 A/B and extension member 72 in a position generally parallel to the bone. Fixation pin 60B may be received within an internal aperture of the extension member 72. As shown, apertures 74A and B, such as tapered apertures, may be provided proximal to extensions 70 A and B. Such apertures may extend through the support at a skewed angle relative to the longitudinal axis of the support, and may be used to engage a clamping instrument or receive fixation pins.

The support 30 can also include a slot 80 formed on at least a portion of a surface of the support 30. As illustrated in the embodiment of the cutting guide 20 shown in FIG. 3A, the slot 80 can extend in a surface of the support 30 between fixation apertures 50A and 50B. A securing component 90 can be configured to translate along the slot 80 relative to the support 30. For example, the securing component 90 can have a first end with a diameter greater than a diameter of a second opposite end, such that the first end of the securing component 90 is supported by the slot 80 (e.g., the first end has a diameter greater than a radial width of the slot 80) while the second end of the securing component 90 is positioned within the slot 80 (e.g., the second end has a diameter less than a radial width of the slot 80).

The inner cavity 40 of the support 30 can have a shaft 100 positioned at least partially within the inner cavity 40. The shaft 100 can be configured to translate within the inner cavity 40 relative to the support 30, such that an end of the shaft 100 can be made to project out from the inner cavity 40. The shaft 100 may define a slot 105 which may be aligned with the slot 80 defined by the support 30. This slot 105 may receive the pin 60A to reduce interference when the shaft 100 translates. Furthermore, the shaft 100 can include a securing aperture 110 which can be configured to receive at least a portion of the securing component 90. In one embodiment, both the second end of the securing component 90, within the slot 80, and the securing aperture 110 can be threaded to allow the securing component 90 to mate with the securing aperture 110. Such a configuration can allow the shaft 100 to be fixed, such as by compressing a surface of the support 30 that defines the slot 80, and thus prevented from translating within the inner cavity 40, relative to the support 30. In another embodiment, the securing component 90 can

5

be threadingly engaged with the support **30** to act against the shaft **100** to prevent the shaft **100** from traveling with the cavity **40** when desired.

On an end of the shaft **100**, a main guide member **120** can be disposed. In some embodiments the main guide member **120** can be integral with the shaft **100**, or in other embodiments the main guide member **120** and the shaft **100** can be separate components coupled together. The main guide member **120** can have a first guide surface **130A** and a second guide surface **130B**, and in some embodiments the main guide member **120** can include blocks **140A** and/or **140B**. The first and second guide surfaces **130A** and **130B** can be adjacent surfaces facing one another with a space defined between the first and second guide surfaces **130A** and **130B**. For example, the first guide surface **130A** can be a surface of the main guide member **120** immediately opposite a surface of the main guide member **120** that interfaces with the shaft **100**, and the second guide surface **130B** can be a surface of the main guide member **120** immediately opposite a surface of the main guide member **120** that includes blocks **140A** and **140B**.

In the illustrated embodiment, the second guide surface **130B** contains a gap, such that the second guide surface **130B** is not a single, continuous surface. In other embodiments, the second guide surface **130B** can be a single, continuous surface lacking any such gap. The first guide surface **130A** defines a first plane, while the second guide surface **130B** defines a second plane. As shown, the first guide surface **130A** and the second guide surface **130B** can be configured such that the first plane is parallel to the second plane, with the space between. In further embodiments (not illustrated), the guide surfaces **130A** and **130B** can be configured such that the first and/or second planes are skewed.

As previously noted, a surface of the main guide member **120** can include one or more blocks **140A** and **140B**, either integral with the main guide member **120** or as separate components attached to the main guide member **120**. As shown, the blocks **140A** and **140B** can be on a surface on a side of the main guide member **120** furthest from the interface with the shaft **100**. In other applications, the blocks **140A** and **140B** can be located at various other positions on the main guide member **120**. The blocks **140A** and **140B** can include fixation apertures **150A** and **150B** respectively. The fixation apertures **150A** and **150B** extend through the blocks **140A** and **140B** and provide a location for configuring additional fixation pins to, for example, position a bone or bones.

As shown in FIGS. 3B-3D, the main guide member **120** and at least one block **140A** can assume other configurations. In FIG. 3B, the block **140A** includes fixation apertures **150A** and **B** and is spaced from the guide surfaces a distance via connecting flanges **154A** and **154B**. In the embodiment of FIG. 3B, the fixation apertures **150A** and **B** are positioned in a line substantially parallel to the guide surfaces. In FIG. 3C, the orientation of the fixation apertures **150A** and **B** is substantially perpendicular to the guide surfaces. In FIG. 3D, only one fixation aperture **150A** is provided.

Another embodiment of a support **30** is depicted in FIG. 3E. In FIG. 3E, the support **30** has at least one (e.g., two) fixation aperture **156A** and **156B** formed in its side to receive fixation pins. Such apertures can also be included on the opposite side of the support (not shown). In some embodiments, the fixation apertures **156A** and **156B** can be positioned in a line substantially parallel with a longitudinal axis of the support, and can extend in a direction substantially perpendicular to the longitudinal axis of the support. In

6

certain embodiments, the apertures extend at an angle, such as about 20 degrees, from vertical. In such embodiments, the support **30** can be placed on a dorsal surface and after a first cut or cuts, can be rotated about a pin extending through one of the fixation apertures **156A** and **156B** to rotate the support relative to the bone and first cut or cuts. The support can then be further pinned to the bone and an additional cut or cuts can be made at a desired angle relative to the first cut or cuts.

In addition to the support **30**, the bone cutting guide **20** can include a bridge component **160**. As shown in FIG. 3A, the bridge component **160** can attach to the main guide member **120**. In particular, in some applications of the bone cutting guide **20**, the bridge component **160** can have a geometry that allows the bridge component **160** to attach to the main guide member **120** between the first and second guide surfaces **130A** and **130B** through an interference fit. Optionally, a locking mechanism can be provided to lock the bridge component to the main guide member, such as a locking tab, screw, pin, cam, etc. For example, the bridge component **160** may have a planar member **165** (shown in FIG. 2) that is received within the gap between the surfaces **130A** and **130B** and an extending block **166** (shown in FIG. 2) adapted to extend into the surface gap of **130B**. In other applications, the bridge component **160** can be coupled to the main guide member **120** by any attachment mechanism, such as screws or clamps. The bridge component **160** can include rails **170A** and **170B**, each extending out from the bridge component **160** in a same general direction. In other embodiments, the rails **170A** and **170B** can extend out from the bridge component **160** at different angles.

The bone cutting guide **20** can also include in some embodiments a fixating structure **180**. The fixating structure **180** can be supported on the rails **170A** and **170B**. For example, the fixating structure **180** can include apertures **185A** and **185B** to receive the rails **170A** and **170B**, respectively. The fixating structure **180** can be secured to the rails **170A** and **170B**, such that the fixating structure **180** is obstructed from translating along the rails **170A** and **170B**, by turning or otherwise actuating an actuator **186** of the fixating structure **180**, which moves a lock (not shown) to act against the rails. Furthermore, the fixating structure **180** can also include one or more fixation apertures **190A** and/or **190B**. Fixation apertures **190A** and **190B** extend through fixating structure **180** and can be located on opposite ends of the fixating structure **180**, at a skewed angle, and serve to receive fixation pins or other means for stabilizing the bone cutting guide **20** across a targeted anatomy and/or positioning a bone or bones.

Additionally, the bone cutting guide **20** can have a secondary guide member **200**. The secondary guide member **200** can be supported on the rails **170A** and **170B**. For example, the secondary guide member **200** may include slots **205A** and **205B** to receive the rails **170A** and **170B** such that the secondary guide member **200** is supported thereon. The secondary guide member **200** can also have a third guide surface **210A** and a fourth guide surface **210B**. The third and fourth guide surfaces **210A** and **210B** can be adjacent surfaces facing one another with a space defined between the third and fourth guide surfaces **210A** and **210B**. In the illustrated embodiments, third and fourth guide surfaces **210A** and **210B** are single, continuous surfaces that do not include a gap, but in other embodiments third and/or fourth guide surfaces **210A** and **210B** can include a gap. The third guide surface **210A** defines a third plane, while the fourth guide surface **210B** defines a fourth plane. As shown, the third guide surface **210A** and fourth guide surface **210B** can be configured such that the third plane is parallel to the

fourth plane, with the space between. In further embodiments (not illustrated), the guide surfaces **210A** and **210B** can be configured such that the third and/or fourth planes are skewed. Further, the third and/or fourth guide surfaces may be parallel to or skewed with respect to the first and/or second guide surfaces, such that the cutting guide can be adapted to make parallel cuts or angular cuts or cut shapes (e.g. a chevron shape). In some embodiments, the secondary guide member **200** can be locked to the rails **170A** and/or **170B** with a locking screw, cam, pin, etc. In the embodiment shown in FIG. **3A**, an aperture **214** is provided to receive a locking mechanism and/or an accessory, such as a handle.

FIGS. **4-6** illustrate perspective views of the embodiment of the bone cutting guide **20**, described with respect to FIGS. **1-3**, as assembled. In the embodiment illustrated in FIGS. **4-6**, the bridge component **160** is attached to the main guide member **120** and both the fixating structure **180** and secondary guide member **200** are supported along the rails **170A** and **170B** of the bridge component. In one application, the secondary guide member **200** can be supported on the rails **170A** and **170B** at a location along the rails **170A** and **170B** between the fixating structure **180** and the main guide member **120**. Additionally shown in FIGS. **4-6** are fixation pins **220A** and **220B** received within fixation apertures **190A** and **190B** such that the fixation pins **220A** and **220B** extend through the fixating structure **180**. In some applications of the bone cutting guide **20**, it may be desirable to provide the fixation pins **220A** and **220B** at an angle other than 90 degrees relative to a top surface of the fixating structure **180** by configuring the fixation apertures **190A** and **190B** to extend through the fixating structure **180** at a skewed angle to guide the fixating pins **220A** and **220B**. Fixation pins **220A** and **220B** can be used, for example, for stabilizing the bone cutting guide **20** across a targeted anatomy and/or positioning a bone or bones.

Embodiments of the bone cutting guide **20** can be useful in operation for temporarily positioning a bone or bones and guiding a cutting of a bone or bones at a targeted anatomy. Bone cutting can be useful, for instance, to facilitate contact between leading edges of adjacent bones, separated by a joint, or different portions of a single bone, separated by a fracture, such as in a bone alignment and/or fusion procedure. As such, embodiments of the present invention include methods for temporarily fixing an orientation of a bone or bones, such as during a surgical procedure, and guiding cutting at desired bone locations. In the embodiments described, cuts are made to bone with respect to the cutting guide, and the bones can be positioned for an additional surgical step, such as bone plating, after the cuts have been made.

FIGS. **7-16** illustrate steps of an embodiment of a method for temporarily positioning and cutting a bone or bones using the bone cutting guide **20**. Specifically, FIGS. **7** and **8** show a perspective and top view, respectively, of the support **30** fixed to a bone **230** (e.g. a first metatarsal). The support **30** is placed on the bone **230**. For embodiments of the bone cutting guide **20** that include the extensions **70A** and **70B**, the extensions **70A** and **70B** can be used to at least partially straddle the bone **230** and consequently provide both greater stability to the support **30** on the bone **230** and anatomical alignment of the support **30** on a longitudinal axis of the bone **230** (e.g., the slot **80** is generally parallel to the longitudinal axis of the bone **230**). Extension member **72** can be adjusted to a desired distance from support **30**. Further, in some embodiments it can be desirable to align and fix the support **30** along the longitudinal axis of the bone **230** using the fixation pins **60A** and **60B**. The pin **60A** can be inserted

through the fixation aperture **50A** such that an end of the pin **60A** protrudes out from the fixation aperture **50A** adjacent the bone **230**. The pin **60A** can then be fixed to the bone **230**. Similarly, the pin **60B** can be inserted through fixation aperture **50B** and fixed on an end to the bone **230**. In this manner, the support **30** can be fixed in place to and aligned along the longitudinal axis of the bone **230**.

In addition to fixing the support **30** to the bone **230**, the main guide member **120** can be aligned such that the main guide member **120** is positioned at a location where a bone (e.g., the bone **230**) is to be cut. In one embodiment, the main guide member **120** can be positioned at the location where a bone is to be cut by appropriately positioning and fixing the support **30**, e.g., such that the support **30** is fixed to the bone **230** at a location along bone **230** that results in the main guide member **120** being positioned at the location where a bone is to be cut. In some embodiments, a joint alignment blade (not shown) is inserted through the main guide member and into a joint space to help align the main guide member in a desired position. Further, in certain embodiments, a provisional fixation pin (not shown) can be inserted through a bone of interest and into an adjacent bone (e.g., through a first metatarsal and into a second metatarsal) to provide additional stability during the procedure.

In some applications, a location of the main guide member **120** relative to the longitudinal axis of the bone **230** can be adjusted without necessitating movement of the support **30**. To accomplish this, the shaft **100** at least partially within the inner cavity **40** can be translated relative to the support **30** as shown in the perspective view of FIG. **9**. As shown, the main guide member **120** has been translated along the longitudinal axis of the bone **230** a distance **D** as a result of the shaft **100** being moved the same distance **D**. Once the main guide member **120** is positioned at the location to be cut, the securing component **90** can be translated along the slot **80** such that the securing component **90** is aligned with securing aperture **110**. The securing component **90** can then be fixed within the securing aperture **110** such that the shaft **100** is fixed relative to the support **30**.

After the main guide member **120** has been positioned at the location to be cut, a cutting member (e.g. a saw blade) can be inserted through the space defined between the first guide surface **130A** and the second guide surface **130B** to cut, for example, the bone **230**. The guide surfaces **130A** and **130B** can serve to direct the cutting member to the location of the bone **230** to be cut, which in many applications can be a precise location. The break or window defined in the second guide surface **130B** can assist in visualizing the portion of the bone **230** being cut.

In some embodiments, the main guide member **120** can be used to make additional cuts. In such embodiments, the securing component **90** can be loosened and the shaft **100** can be translated within the cavity to a desired position. The securing component **90** can be then be fixed within the securing aperture so the shaft is again fixed relative to the support **30**. In some embodiments, fixation pins may be inserted through fixation aperture **150A** and/or **150B** and into the bone **230** to further stabilize the main guide member. After the main guide member **120** has been repositioned at the location to be cut, a cutting member (e.g. a saw blade) can be inserted through the space defined between the first guide surface **130A** and the second guide surface **130B** to cut, for example, the bone **240**. The guide surfaces **130A** and **130B** can serve to direct the cutting member to the location of the bone **240** to be cut.

In some applications, it may be desirable to provide additional, temporary fixation of the bone **230** to allow for

more accurate cutting. As best seen again in FIG. 9, blocks 140A and 140B can provide a means for additionally positioning the bone 230. Fixation pins can be inserted through the fixation aperture 150A and/or 150B and into the bone 230 to temporarily position the bone 230 and/or adjacent bone 240 for cutting. In other applications, blocks 140A and 140B may not be necessary.

As shown in the perspective view of FIG. 10, once the bone 230 has been cut the bridge component 160 can optionally be attached to the main guide member 120. In one embodiment, the bridge component 160 can have a geometry that allows the bridge component 160 to attach to the main guide member 120 between the first and second guide surfaces 130A and 130B through an interference fit, while in other embodiments the bridge component 160 can attach to the main guide member 120 by other attachment means. The rails 170A and 170B of the bridge component 160 can be arranged such that the rails 170A and 170B extend out from the bridge component 160 on a side of the bridge component 160 opposite the support 30. The rails 170A and 170B can serve to support additional components of the bone cutting guide 20.

One such component of the bone cutting guide 20 that can be supported on the rails 170A and 170B is the fixating structure 180. FIG. 10 shows the fixating structure 180 attached to the rails 170A and 170B. In one embodiment, the fixating structure 180 can have holes or slots for receiving the rails 170A and 170B such that the fixating structure 180 can translate along the rails 170A and 170B to a desired position. The fixating structure 180, for example, can also be secured to the rails 170A and 170B in a manner that prevents translation of the fixating structure 180 when desired by actuating the actuator 186.

FIGS. 11 and 12 illustrate perspective views of the fixating structure 180 with the fixation pins 220A and 220B received through the fixation apertures 190A and 190B (190B is shown in, e.g., FIG. 2). Fixation apertures 190A and 190B can be on opposite ends of the fixating structure 180 as shown. Fixation pins 220A and 220B can be fixed to a bone 240 (e.g. a first cuneiform as illustrated) to provide stability for the bone cutting guide 20 and/or to position the bone 240. After the pins 220A and 220B are set, the fixating structure 180 can be translated with respect to the rails 170A and 170B and the support 30 to a desired position to compress or expand the space between the bones 230 and 240 as needed. The position of the bones can be locked by securing the fixating structure 180 against the rails 170A and 170B. In other embodiments, such compression or expansion can be achieved by moving the shaft 100 relative to the support 30 and reengaging the securing component 90 at the new desired position.

FIGS. 13 and 14 show perspective views of the bone cutting guide 20 assembled to include the secondary guide member 200. The secondary guide member 200 can be supported on the rails 170A and 170B. In one embodiment, the slots 205A and 205B of the secondary guide member 200 can receive the rails 170A and 170B such that the secondary guide member 200 can translate along the rails 170A and 170B to a desired position. As illustrated, the secondary guide member 200 can be located along the rails 170A and 170B between the fixating structure 180 and the bridge component 160.

The secondary guide member 200 can be positioned at a location where a second bone cut is to be made. A cutting member (e.g. a saw blade) can be inserted through the space defined between the third and fourth guide surfaces 210A and 210B to cut, for example, the bone 240. The guide

surfaces 210A and 210B can serve to direct the cutting member to the location of the bone 240 to be cut, which in many applications can be a precise location. As illustrated, the cut made using the secondary guide member 200 (e.g. to bone 240) will be a cut that is generally parallel to the cut made using the main guide member 120. However, in other embodiments components of the bone cutting guide 20 (e.g. rails 170A and 170B) can be configured such that the cut made using the secondary guide member 200 is an angular cut (i.e. not parallel) relative to the cut made using the main guide member 120.

FIGS. 15 and 16 illustrate the bone cutting guide 20 as described previously, with the secondary guide member 200 translated along the rails 170A and 170B. The secondary guide member 200 can be translated along the rails 170A and 170B to precisely locate the secondary guide member 200 at the location to be cut (e.g. on bone 240). In the embodiment illustrated, the secondary guide member 200 can be shaped such that a portion of the secondary guide member 200 can overlap, or sit on top of, the bridge component 160. Such a configuration can be useful, for example, where the second cut made using the secondary guide member 200 is desired to be close to the first cut made using the main guide member 120 (e.g. portions of bones 230 and 240 interfacing at a joint).

When the bone 230 and/or bone 240 have been cut and positioned as desired, the bone cutting guide 20 can be removed. In some embodiments, the cutting guide 20 is temporarily removed from the fixation pins and cut bone is removed from the area. In certain embodiments, an autograft or other compound is delivered to the area of the bone cuts. Optionally, the guide may then be reset on the bones over the fixation pins and the shaft 100 can be translated within the cavity to adjust the relative position of the bones (e.g., to compress them together). The securing component 90 can be then be fixed within the securing aperture so the shaft is again fixed relative to the support 30. A bone plate may optionally be applied across the joint while the bones are held in the longitudinally fixed position by the cutting guide. After the plate is applied, the bone cutting guide and the fixation pins may be removed. Removing the bone cutting guide 20 can include removing all fixation pins and the support, and, in some embodiments, can include removing the bridge component, along with the fixation structure and secondary guide member 200. In certain embodiments, a second bone plate may optionally be applied across the joint. In a specific embodiment, the two bone plates are applied about 90 degrees from each other around the circumferences of the bones (e.g., at a dorsal side and a medial side).

Thus, embodiments of the invention are disclosed. Although the present invention has been described with reference to certain disclosed embodiments, the disclosed embodiments are presented for purposes of illustration, and not limitation, and other embodiments of the invention are possible. One skilled in the art will appreciate that various changes, adaptations, and modifications may be made without departing from the spirit of the invention.

The invention claimed is:

1. A bunion correction method comprising:
 - positioning a first bone cutting guide slot over a portion of a metatarsal to be cut;
 - attaching the first bone cutting guide slot to the metatarsal with a first fixation pin inserted into the metatarsal and a second fixation pin inserted into the metatarsal, the first fixation pin and the second fixation pin being positioned distally of the first bone cutting guide slot;

11

inserting a cutting member through the first bone cutting guide slot to cut the portion of the metatarsal;
 adjusting an alignment of the metatarsal relative to a cuneiform separated from the metatarsal by a joint to establish a moved position of the metatarsal;
 positioning a second bone cutting guide slot over a portion of the cuneiform to be cut, the second bone cutting guide slot being attached to the metatarsal by at least the first fixation pin inserted into the metatarsal and the second fixation pin inserted into the metatarsal, the first fixation pin and the second fixation pin being positioned distally of the second bone cutting guide slot;
 inserting the cutting member through the second cutting slot to cut the portion of the cuneiform; and
 causing the metatarsal to fuse to the cuneiform in the moved position.

2. The method of claim 1, further comprising, after adjusting the alignment of the metatarsal relative to the cuneiform to establish the moved position of the metatarsal, lifting the first bone cutting guide slot off the first fixation pin and the second fixation pin.

3. The method of claim 1, wherein:

inserting the cutting member through the first bone cutting guide slot to cut the portion of the metatarsal comprises inserting the cutting member through the first bone cutting guide slot to cut the portion of the metatarsal without the second bone cutting guide slot being positioned over the portion of the cuneiform to be cut; and
 inserting the cutting member through the second bone cutting guide slot to cut the portion of the cuneiform comprises inserting the cutting member through the second bone cutting guide slot to cut the portion of the cuneiform without the first bone cutting guide slot being positioned over the portion of the metatarsal to be cut and configured to receive the cutting instrument therethrough.

4. The method of claim 1, wherein positioning the first bone cutting guide slot over the portion of the metatarsal to be cut comprises positioning a support extending perpendicularly from the first bone cutting guide slot over a dorsal surface of the metatarsal with the support extending substantially parallel to a longitudinal axis of the metatarsal.

5. The method of claim 4, wherein attaching the bone cutting guide slot to the metatarsal with the first fixation pin inserted into the metatarsal and the second fixation pin inserted into the metatarsal comprises inserting the first fixation pin through a first fixation aperture of the support into the metatarsal and inserting the second fixation pin through a second fixation aperture of the support into the metatarsal.

6. The method of claim 1, wherein positioning the second bone cutting guide slot over the portion of the cuneiform to be cut comprises positioning a support extending perpendicularly from the second bone cutting guide slot over a dorsal surface of the metatarsal with the support extending substantially parallel to a longitudinal axis of the metatarsal.

7. The method of claim 6, wherein, when the second bone cutting guide slot is positioned over the portion of the cuneiform to be cut, the first fixation pin extends from the metatarsal through a first fixation aperture of the support and the second fixation pin extends from the metatarsal through a second fixation aperture of the support.

8. The method of claim 1, wherein attaching the first bone cutting guide slot to the metatarsal with the first fixation pin and the second fixation pin comprises:

12

inserting the first fixation pin extending substantially perpendicular to a dorsal surface of the metatarsal; and
 inserting the second fixation pin extending substantially perpendicular to the dorsal surface of the metatarsal with the second fixation pin being substantially parallel to the first fixation pin.

9. The method of claim 1, further comprising, after positioning the second bone cutting guide slot over the portion of the cuneiform to be cut, attaching the second bone cutting guide slot to the cuneiform with a third fixation pin inserted into the cuneiform.

10. The method of claim 1, wherein the first bone cutting guide slot and the second bone cutting guide slot are configured to result in a cut end of the metatarsal being substantially parallel to a cut end of the cuneiform.

11. The method of claim 1, wherein the first bone cutting guide slot and the second bone cutting guide slot are configured to result in a cut end of the metatarsal being angled relative to a cut end of the cuneiform.

12. The method of claim 1, wherein the cutting member is a saw blade.

13. The method of claim 1, wherein inserting the cutting member through the first bone cutting guide slot and inserting the cutting member through the second bone cutting guide slot comprises inserting the cutting member through the first bone cutting guide slot to cut the portion of the metatarsal prior to inserting the cutting member through the bone cutting guide slot to cut the portion of the cuneiform.

14. The method of claim 1, wherein inserting the cutting member through the bone cutting guide slot and inserting the cutting member through the second bone cutting guide slot comprises inserting the cutting member through the first bone cutting guide slot to cut the portion of the metatarsal after inserting the cutting member through the second bone cutting guide slot to cut the portion of the cuneiform.

15. The method of claim 1, wherein:

the first bone cutting guide slot is provided between a first guide surface defining a first plane and a second guide surface defining a second plane; and

the second bone cutting guide slot is provided between a third guide surface defining a third plane and a fourth guide surface defining a fourth plane.

16. The method of claim 1, comprising:

a first guide defining the first bone cutting guide slot; and
 a second guide defining the second bone cutting guide slot.

17. The method of claim 1, wherein causing the metatarsal to fuse to the cuneiform in the moved position comprises applying a bone plate across the joint.

18. The method of claim 1, further comprising compressing the metatarsal and the cuneiform together.

19. The method of claim 1, wherein the metatarsal is a first metatarsal and the cuneiform is a first cuneiform.

20. A bunion correction method comprising:

positioning a first bone cutting guide slot defined by a first guide over a portion of a metatarsal to be cut;

attaching the first guide to a dorsal surface of the metatarsal by inserting a first fixation pin through a first fixation aperture connected to the first guide and inserting a second fixation pin through a second fixation aperture connected to the first guide, wherein the first fixation aperture is offset along a length of the metatarsal from the second fixation aperture, and inserting the first fixation pin and inserting the second fixation pin extending substantially parallel to each other;

13

inserting a saw blade through the first bone cutting guide slot to cut the portion of the metatarsal;
 adjusting an alignment of the metatarsal relative to a cuneiform separated from the metatarsal by a joint to establish a moved position of the metatarsal;
 lifting the first guide off the first fixation pin and the second fixation pin;

positioning a second bone cutting guide slot defined by a second guide over a portion of the cuneiform to be cut, the second guide being attached to the metatarsal by at least the first fixation pin inserted into the metatarsal and the second fixation pin inserted into the metatarsal, and the second guide being attached to the cuneiform by at least a third fixation pin inserted into the cuneiform;

inserting the saw blade through the second cutting slot to cut the portion of the cuneiform; and
 causing the metatarsal to fuse to the cuneiform in the moved position.

21. The method of claim 20, wherein:

inserting the saw blade through the first bone cutting guide slot to cut the portion of the metatarsal comprises inserting the saw blade through the first bone cutting guide slot to cut the portion of the metatarsal without the second bone cutting guide slot being positioned over the portion of the cuneiform to be cut; and

inserting the saw blade through the second bone cutting guide slot to cut the portion of the cuneiform comprises inserting the saw blade through the second bone cutting guide slot to cut the portion of the cuneiform without the first bone cutting guide slot being positioned over the portion of the metatarsal to be cut and configured to receive the saw blade therethrough.

22. The method of claim 20, wherein a support extends substantially perpendicularly from the first guide and defines the first fixation aperture and the second fixation aperture.

23. The method of claim 20, wherein inserting the first fixation pin and inserting the second fixation pin extending substantially parallel to each other comprises:

inserting the first fixation pin extending substantially perpendicular to the dorsal surface of the metatarsal; and

inserting the second fixation pin extending substantially perpendicular to the dorsal surface of the metatarsal.

24. The method of claim 20, wherein the first bone cutting guide slot and the second bone cutting guide slot are configured to result in a cut end of the metatarsal being substantially parallel to a cut end of the cuneiform.

25. The method of claim 20, wherein inserting the saw blade through the first bone cutting guide slot and inserting the saw blade through the second bone cutting guide slot comprises inserting the saw blade through the first bone

14

cutting guide slot to cut the portion of the metatarsal prior to inserting the saw blade through the bone cutting guide slot to cut the portion of the cuneiform.

26. The method of claim 20, wherein the third fixation pin is at a skewed angle relative to the first fixation pin and the second fixation pin.

27. The method of claim 20, wherein causing the metatarsal to fuse to the cuneiform in the moved position comprises applying a bone plate across the joint.

28. The method of claim 20, further comprising compressing the metatarsal and the cuneiform together.

29. A bunion correction method comprising:

positioning a first bone cutting guide slot defined by a first guide over a portion of a first metatarsal to be cut;

attaching the first guide to a dorsal surface of the first metatarsal by inserting a first fixation pin through a first fixation aperture connected to the first guide and inserting a second fixation pin through a second fixation aperture connected to the first guide, wherein the first fixation aperture is offset along a length of the first metatarsal from the second fixation aperture, and inserting the first fixation pin and inserting the second fixation pin comprises inserting the first fixation pin and inserting the second fixation pin extending substantially parallel to each other and substantially perpendicular to the dorsal surface of the first metatarsal; inserting a saw blade through the first bone cutting guide slot to cut the portion of the first metatarsal;

adjusting an alignment of the metatarsal relative to a first cuneiform separated from the metatarsal by a joint to establish a moved position of the first metatarsal;

lifting the first guide off the first fixation pin and the second fixation pin;

positioning a second bone cutting guide slot defined by a second guide over a portion of the first cuneiform to be cut, the second guide being attached to the first metatarsal by at least the first fixation pin and the second fixation pin, and second guide being attached to the first cuneiform by at least a third fixation pin inserted into the first cuneiform at a skewed angle relative to the first fixation pin and the second fixation pin;

inserting the saw blade through the second cutting slot to cut the portion of the first cuneiform;

compressing the first metatarsal and the first cuneiform together; and

causing the first metatarsal to fuse to the first cuneiform in the moved position.

30. The method of claim 29, wherein causing the metatarsal to fuse to the cuneiform in the moved position comprises applying a bone plate across the joint.

* * * * *