US 20110288550A1

(19) **United States**

(12) **Patent Application Publication**

Orbay et al.

(10) **Pub. No.: US 2011/0288550 A1**

(43) **Pub. Date: Nov. 24, 2011**

(54) **DEVICES, IMPLEMENTS AND METHODS FOR THE TREATMENT OF A MULTI-AXIS JOINT**

(75) Inventors: **Jorge L. Orbay**, Miami, FL (US); **Thomas H. Norman**, Miami, FL (US); **Ronald Litke**, Shelton, CT (US)

(73) Assignee: **SKELETAL DYNAMICS LLC**, Miami, FL (US)

(21) Appl. No.: **13/114,648**

(22) Filed: **May 24, 2011**

Related U.S. Application Data

(60) Provisional application No. 61/347,517, filed on May 24, 2010, provisional application No. 61/390,420, filed on Oct. 6, 2010.

Publication Classification

(51) **Int. Cl.**

A61B 17/80	(2006.01)
A61F 2/42	(2006.01)
A61B 17/56	(2006.01)

(52) **U.S. Cl.** **606/70**; 606/87; 623/21.15

(57) **ABSTRACT**

A system, devices and methods for performing an osteotomy on a bone of a multi-axis joint are provided. A cutting guide system is provided for performing one or more cuts to the bone, using the articular surfaces of the articulating bones as a reference. If desired, a prosthesis can be used to emulate the osteotomy and substitute for a damaged articular surface of a bone of a multiaxis joint.



Paragon 28 v. Treace Medical Concepts
PGR2026-00031
Paragon Ex. 1010



Fig. 1A



Fig. 1B





Fig. 2



Fig. 3A

Fig. 3B


335
335'
350
240'
350a
300
324
230
200
325
326

Fig. 4A


335'
350
350a
328
250'
327
300
324
230
200
260

Fig. 4B



Fig. 5A



Fig. 5B



Fig. 5C



Fig. 5D



Fig. 5E



Fig. 5F



Fig. 6A



Fig. 6B



Fig. 6C



Fig. 7A



Fig. 7B



Fig. 8



Fig. 9A



Fig. 9B



Fig. 9C



Fig. 9D



Fig. 9E



Fig. 9F



Fig. 9G



Fig. 9H



Fig. 10A



Fig. 10B

DEVICES, IMPLEMENTS AND METHODS FOR THE TREATMENT OF A MULTI-AXIS JOINT

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] The present application claims priority to co-pending Provisional Patent Application No. 61/347,517, filed on May 24, 2010 and to co-pending Provisional Patent Application No. 61/390,420, filed on Oct. 6, 2010, both of which are entitled DEVICES, IMPLEMENTS AND METHODS FOR TREATMENT OF A MULTI-AXIS JOINT; those applications being incorporated herein, by reference, in their entireties.

FIELD OF INVENTION

[0002] The invention relates to the treatment of diseased, multi-axis joints, and more particularly, to devices, implements and methods useful for the surgical treatment of arthritic, multi-axis joints for the early reestablishment of adequate range of motion, reduction or elimination of pain, recovery of strength and stabilization of the joint. The invention is particularly useful in connection with surgical treatment of the carpo-metacarpal joint and other similarly configured joints.

BACKGROUND OF THE INVENTION

[0003] The first carpo-metacarpal (i.e., 1CMC) joint, found at the base of the thumb, is complicated in that it does not have a single axis of rotation. Rather, the first metacarpal sits on the trapezium in a saddle-shaped geometry. This allows each of the bones in the first carpo-metacarpal joint to rotate about each other around axes of rotation oriented transversely to one another.

[0004] The 1CMC joint has a propensity to wear out and develop arthritis, causing pain at the base of the thumb and resulting in weakness of the gripping and pinching abilities of the hand. In patients with osteoarthritis, this condition is referred to as basal joint arthritis of the thumb. Conservative and medical treatments of the condition, including splints, NSAIDs and cortisone, are commonly used but are not always effective, leading to consideration of surgical solutions.

[0005] One surgical approach involves the removal of the trapezium, linking the first and second metacarpals at their bases with tendon graft and inserting a pad made of tendon graft or artificial material to cushion the space left by the now absent trapezium.

[0006] Other surgical approaches include the use of a prosthetic device to substitute one half or all of the 1CMC joint. Examples of these are described in U.S. Pat. No. 5,645,605 to Klawitter, International Publication WO2010/033691 also to Klawitter, U.S. Pat. No. 7,182,787 to Hassler and U.S. Pat. No. 7,641,696 to Ogilvie.

[0007] It has been observed that known surgical techniques and devices to treat the arthritic 1CMC joint achieve one or more of early reestablishment of adequate range of motion, reduction or elimination of pain, recovery of strength and stabilization of the joint, but none achieves all of them to a satisfactory degree.

[0008] Additionally, accurate means for performing a wedge osteotomy in small bones, a particularly useful arthroplastic procedure for restoring pain free stability to a patient with basal joint arthritis of the thumb, are not currently available. Furthermore, a prosthetic device that can be used to emulate the result of a wedge osteotomy is currently unavailable for those cases when replacement of a damaged articular surface is indicated.

[0009] What is needed is a system, apparatus and methods that provide a surgeon with surgical options and the corresponding devices to treat a diseased joint and to overcome the limitations of the heretofore-known devices.

SUMMARY OF THE INVENTION

[0010] It is, accordingly, an object of this invention to provide the surgeon with surgical options and the corresponding devices to treat the diseased joint and to overcome the limitations of the heretofore-known devices. In one particular embodiment of the invention, a wedge osteotomy system is provided for performing arthroplasty of the first carpo-metacarpal joint. In another particular embodiment a prosthesis that emulates the post-osteotomy geometry is provided to substitute the native proximal articular surface of the first metacarpal when so indicated. In a further embodiment of the invention, the devices are provided as part of a set that includes different size prostheses, to accommodate varied patient anatomies.

[0011] Although the invention is illustrated and described herein as embodied in Devices, Implements and Methods for the treatment of a Multi-Axis Joint, it is nevertheless not intended to be limited to only the details shown, since various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

[0012] The construction of the invention, however, together with additional objects and advantages thereof will be best understood from the following description of the specific embodiment when read in connection with the accompanying drawings.

BRIEF DESCRIPTION OF THE FIGURES

[0013] FIG. **1**A is a diagrammatic view of the skeleton of the hand where the bones of the carpus and the first metacarpal are indicated.

[0014] FIG. **1**B is an exploded view of the two bones that compose the first carpometacarpal joint indicating the two saddle-shaped articular surfaces of the bones.

[0015] FIG. **2** is a side view of a first metacarpal bone, wherein the desired cutting lines for a wedge osteotomy are indicated.

[0016] FIGS. **3**A-**3**B are perspective views of a cutting guide in accordance with one particular embodiment of the instant invention.

[0017] FIGS. **4**A-**4**B are side elevational views of the use of the cutting guide of FIGS. **3**A-**3**B.

[0018] FIGS. **5**A-**5**D are perspective, plan from above, plan from below and lateral elevational views of a plate in accordance with another particular embodiment of the instant invention.

[0019] FIG. **5**E is a perspective cross sectional view of the plate of FIG. **5**B corresponding to cross section A-A'.

[0020] FIG. **5**F is a perspective view of a plate being contoured by contouring pliers, according to a further particular embodiment of the instant invention.

[0021] FIGS. **6**A-**6**C are side elevational views of a first metacarpal bone subjected to a wedge osteotomy according to a particular embodiment of the invention.

[0022] FIGS. **7**A-**7**B are side sectional views of a first metacarpal bone and a trapezium bone illustrating the geometrical relationship between the bones before and after the performance of a wedge osteotomy according to a particular embodiment of the invention.

[0023] FIG. **8** is a side view of a first metacarpal bone having a prosthesis in accordance with one particular embodiment of the invention and a trapezium bone illustrating the geometrical relationship between the bones that emulates the result of a wedge osteotomy.

[0024] FIG. **9**A is a perspective plan view from the dorsal side of a prosthesis according to one particular embodiment of the instant invention.

[0025] FIG. **9**B is a front elevational view of the prosthesis of FIG. **9**A

[0026] FIG. **9**C is a rear elevational view of the prosthesis of FIG. **9**A

[0027] FIG. **9**D is a top plan view of the dorsal side of the prosthesis of FIG. **9**A

[0028] FIG. **9**E is a cross-sectional view of the prosthesis of FIG. **9**D in corresponding to cross section B-B'

[0029] FIG. **9**F is a side elevational view of the prosthesis of FIG. **9**A

[0030] FIG. **9**G is a bottom plan view of the palmar side of the prosthesis of FIG. **9**A.

[0031] FIG. **9**H is a side elevational view of the prosthesis of FIG. **9**A indicating the geometrical relationship between the dorsal lip and the palmar lip.

[0032] FIGS. **10**A-**10**B are, respectively, side elevational and top plan views of the prosthesis of FIG. **9**A installed in a first metacarpal bone and its relationship to the trapezium bone and the flexor carpis radialis tendon.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0033] A system, devices and methods for performing small bone arthroplasty are provided. In one particular embodiment of the invention, a cutting guide system for performing an osteotomy is provided, which uses the articular surfaces of the articulating bones as a reference for installing one or more K-wires used to position a cutting guide block in order to perform an osteotomy. Further, in accordance with one particular embodiment of the invention, a pre-formed plate and fasteners are provided to lever a resected bone portion into a desired position relative to another bone portion and, subsequently, to stabilize the bone portions to allow healing. For purposes of illustration only, the cutting guide system and method will be described in connection with the performance of a wedge osteotomy of the first metacarpal. Furthermore, when so indicated, in another particular embodiment of the invention a prosthesis may be provided to replace a damaged proximal articular surface of an articulating bone (a first metacarpal in the present example) with an artificial articular surface that emulates the post-osteotomy geometry, while harmonizing with the articular surface of the trapezium.

[0034] Referring more particularly to FIG. **1**A, there is shown a skeletal representation of the human hand and, in particular, the bones of the carpus and the 1CMC joint; the trapezium **100**, the trapezoid **101**, the capitate **102**, the scaphoid **103**, the lunate **104**, the triquetral **105**, the pisiform **106**, the hamate **107** and the first metacarpal **200**. At their interface the first metacarpal **200** and trapezium **100** form the 1CMC joint at the base of the thumb.

[0035] Referring now to FIG. **1**B, there is shown an exploded view of a 1CMC joint, formed from the interaction between the first metacarpal **200** and the trapezium **100**, from which can be seen the saddle-shaped characteristics of the articular surfaces **220**, **120** of the first metacarpal **200** and the trapezium **100**, respectively. Such saddle-shaped articular surfaces **120**, **220**, are inherent in joints having more than one axis of rotation.

[0036] Referring now to FIG. **2**, there is shown a first metacarpal (e.g. "1MC") bone **200** having a distal head portion **230** and a proximal articular surface **220** representing the typical profile of the 1MC bone in an arthritic patient. A portion **225** (shown dotted) represents the part of the 1MC bone of a healthy patient that has been eroded away as a consequence of the disease, causing loss of stability of the joint. Additionally shown are the intended proximal **250** and distal **240** cutting lines defining a wedge **260** to be removed from the 1MC as a step of the osteotomy to be performed.

[0037] A cutting guide **300** for performing small bone osteotomy in accordance with one particular embodiment of the invention will now be described in connection with FIGS. **1**B, **2** and **3**A-**3**B. More particularly, the cutting guide **300** includes a body portion **320** and a removable handle **310**. The body portion **320** defines volarly projecting surfaces for aligning the cutting guide **300** at a desired angle and position relative to the 1MC for making a first intended distal cut along angled line **240** angled relative to the longitudinal axis of the 1MC. More particularly, the divider piece **324** of the guide **300** is placed into the joint between the 1MC **200** and trapezium **100** having its aligning surface **325** abutting the proximal articular surface **220** of the 1MC and its opposite surface **326** abutting the distal articular surface **120** of the trapezium. One or both surfaces **325**, **326** can be contoured to the anatomy of the bone surface against which it will be placed, if desired, or, alternately, can be flat, planar surfaces. These surfaces **325**, **326** align the saw guide at a desired, relative cutting angle and position. Furthermore, body portion **320** includes an angled plane surface **327**, adapted to align a cutting blade along the angled line **240**, and a vertical slot **328**, adapted to align a cutting blade along cutting line **250**, substantially perpendicular the longitudinal axis of the 1MC. In one particularly preferred embodiment of the invention, the angle of the angled plane surface **327** relative to a plane through the divider piece is 20 degrees +/−2 degrees. Additionally, body portion **320** includes at least one K-wire hole **330** configured to receive a K-wire therethrough, to provide stability for the cutting guide **300** while cuts are being made along the lines **240** and **250**. The handle **310** can removably engage the body portion **320**, for example, using a threaded shaft on the proximal end of the handle **310** that matingly engages a threaded bore of the body portion **320**, or vice-versa.

[0038] A method of using the cutting guide **300** will now be described in connection with FIGS. **3**A-**4**B. More particularly, once the divider piece **324** is inserted in a dorsal to palmar direction into the 1CMC joint with its aligning surface **325** abutting the proximal articular surface **220** of the 1MC, a first K-wire **335** is drilled into the 1MC **200**, also in a dorsal to palmar direction, via the K-wire hole **330** of body portion **320** of the saw guide **300**. The K-wire **335** provides stability for the saw guide **300** and, if desired, the resulting bore in the 1MC **200** may be used for future screws that may need to be placed at that location.

[0039] Once the body portion **320** is stabilized by the K-wire **335**, an oscillating saw **350** may be used to make a first distal cut **240'** in the 1MC **200**, by aligning the oscillating saw blade with angled plane surface **327**. Subsequently, the K-wire **335** may be bent into position **335'**, (shown in dotted line in FIG. **4**A) to provide clearance for the blade **350***a* of the oscillating saw **350** to be inserted into the vertical slot **328** to make the proximal cut **250'**, substantially perpendicular to the longitudinal axis of 1MC. As can be seen more particularly from FIG. **4**B, after completing the distal cut **240'** and the proximal cut **250'**, a wedge shaped portion of **260** of the 1MC bone will remain and, as will be described more particularly below, should be removed as one further osteotomy step in carrying out the arthroplasty.

[0040] If desired, as part of a system for the arthroplasty, a plurality of cutting guide body portions **320** may be provided, each having a plane surface **327** at a different angle from the rest, for making distal angled cuts **240'** to accommodate different patient anatomies. In another embodiment the cutting guide body portion **320** may include a mechanism (i.e., an angle adjustment screw) for adjusting the angle of plane surface **327** relative to the divider piece **324**, prior to making the distal cut.

[0041] Referring now to FIGS. **5**A-**5**F, in accordance with one particular embodiment of the present invention, a formable or pre-formed plate **400** is provided, which includes at least one hole **440** for receiving a bone fastener. The plate **400** is made of titanium or other bio-compatible metal or rigid material. In the particular embodiment shown in FIG. **5**A, a pre-formed plate **400** includes a body portion **410**, a Y-shaped head portion **430** oriented transverse to, and angled relative to, the body portion **410**. In other words, in the present particular embodiment of FIGS. **5**A-**5**E, the body portion **410** is not located in the same plane as the head portion **430**. Plate **400** further includes a neck portion **420** joining the body portion **410** and the head portion **430**. Head portion **430** includes at least one hole **440** which may be threaded and intended to receive a bone fastener (i.e. screw or peg **490** of FIG. **6**B) which may have a threaded (locking) or un-threaded head and at least one substantially smaller, non-threaded contouring hole **460** for receiving a contouring tool (not shown). Body portion **410** is elongated and includes at least one hole **440** and at least one contouring hole **460** for receiving, respectively, a bone fastener and a contouring tool, as previously described. Additionally, in one particular embodiment of the invention, the body portion **410** includes at least one unthreaded slot **450** that permits adjustment of the position of the plate after a fastener has been inserted through the slot and into an underlying bone.

[0042] In one particular embodiment of the invention shown in FIGS. **5**D-**5**F, the entire perimetral edge **470** of the plate **400** has a convex shape adapted to be securely held by one or more contouring pliers **475** that can apply bending and/or torqueing forces to the plate **400**, **400'** for bending it into a desired configuration before or after the plate **400**, **400'** has been affixed to one or more bone portions.

[0043] Referring now to FIG. **6**A, there is shown a lateral view of a 1MC bone **200** after cuts **240'** and **250'** of the above-described osteotomy have been made, thus creating three bone fragments: 1) a proximal bone fragment **270** including the proximal articular surface **220**; 2) a distal bone fragment **280** including distal head **230**; and 3) a wedge-shaped bone fragment **260**. Wedge-shaped bone fragment **260** is removed and discarded (see **260'**) to allow for further execution of the arthroplasty.

[0044] As previously described above, in one particular embodiment of the invention, the pre-formed plate **400** includes a body portion **410** angled relative to a head portion **430**. Optionally, the plate portion **400** may be manufactured and/or provided as a flat plate, and contoured preoperatively to have the desired angle using contouring tools or contouring pliers as will be further explained below.

[0045] As further shown in FIG. **6**B, head portion **430** can be affixed to the proximal bone fragment **270**, using bone fasteners **490**. Once so affixed, as further shown in FIG. **6**C, the angled body portion **410** can be used as a handle to manipulate the position of bone fragment **270** relative to bone fragment **280** and, once in the desired position, as a lever to pivot down the proximal bone fragment **270**, closing gap **260"**, into a desired abutting position relative to the distal bone fragment **280**. Once gap **260"** has been reduced to form contacting surfaces **260'"** conducive to bone healing, plate body portion **410** can, in turn, be secured to bone fragment **280** with bone fasteners **490**.

[0046] As may be required, prior to securing bone fragment **280** to the plate **400** with permanent bone fasteners **490**, the instant invention provides for adjustment of the relative position of bone fragments **280**, **270** by using a temporary fastener placed into bone fragment **280** through slot **450**, to permit longitudinal adjustment of the plate **400** along the bone portion **280**. Rotational adjustment of the bone fragments can be also achieved before or after placing permanent bone fasteners **490** by bending and/or torqueing the plate with the aid of contouring tools (i.e. bending irons, not shown) inserted into one or more contouring holes **460** in the head portion **430** and body portion **410** of plate **400** and, subsequently levering the tools. The contouring tool may be configured to penetrate to the depth of the contouring holes **460** to permit plate deformation only or, alternatively, may be configured to also extend, i.e., penetrate, into the underlying bone fragment, thus permitting plate deformation coupled with movement of the underlying bone fragment. Furthermore, the plate **400'** may be also be contoured by using contouring pliers **475** (see FIG. **5**F) with jaws **476**, **477** adapted to securely engage the convex profile **470** along any location on the periphery of the plate **400**, as is described more particularly in U.S. Patent Application Publication No. 2009/281543, published on Nov. 12, 2009, that publication being incorporated herein, by reference, in its entirety.

[0047] It is known that, when performing an arthroplasty of a CMC joint, it is often necessary to remove osteophytes from the distal articular surface of a carpal bone. In the case of the 1CMC joint, the relevant carpal bone is the trapezium. Typically, access to the osteophyte is limited and, if the osteophyte is large, it is difficult and time consuming to remove with a manual rongeur or osteotome, sometimes taking up to one third of the total surgical time. Further, manual removal of the osteophyte requires a high degree of surgical experience and "artistry" in order to avoid damage to the articular surface. Conversely, using a powered device for removal, such as an unprotected rotating burr, can lead to inadvertent removal of good bone and permanent damage to the articular surface.

[0048] It is, therefore, advantageous to provide tools and methods for a more rapid, precise and safe removal of the osteophyte(s). Such a combination of tools is provided by a thin saddle-shaped shield (not shown) in conjunction with a

powered diamond tip burr to accurately remove the osteophyte while, simultaneously, protecting the articular surface and surrounding soft tissue.

[0049] The shield is inserted into the joint and used to protect good bone and soft tissue while the osteophyte is removed and the trapezium is shaped with the powered burr.

[0050] Although desirable, a wedge osteotomy that preserves the proximal articular surface of the metacarpal **220** as described above in reference to the arthroplasty of the 1CMC, may be found, during surgery, to not be the indicated procedure. Therefore, it is advantageous, as an alternative to such wedge osteotomy, to provide in the surgical kit a set of prostheses that can be implanted to emulate what would be the post-osteotomy result of the above referred arthroplasty of the 1CMC.

[0051] Referring now to FIG. **7**A therein is shown a section in the dorsal-palmar plane through a 1MC bone **200**, the corresponding trapezium **100** and the 1CMC joint. As can be noted, a plane T tangent to the dorsal and palmar lips of the pre-osteotomy 1MC portion of the 1CMC joint is inclined at an angle of approximately 85 degrees relative to a longitudinal axis X of the 1MC bone.

[0052] As shown in FIG. **7**B, after wedge osteotomy, the palmar lip of the proximal articular surface protrudes significantly beyond the dorsal lip such that a plane T' tangent to both lips is inclined at an angle of approximately 105 degrees relative to longitudinal axis X. This rearranged geometry changes the tendon vector and is beneficial to the stability to the post-osteotomy 1CMC joint.

[0053] It is desirable that, in a similar manner, a prosthesis intended to substitute the native proximal articular surface of the 1MC emulate the post-osteotomy geometry illustrated above in FIG. **7**B. Such similar geometry is shown in FIG. **8**, with reference to a prosthesis **500** implanted into a 1MC bone **290**, wherein a plane T" tangent to the dorsal and palmar lips of the prosthesis **500** is inclined at an angle of approximately 105 degrees relative to longitudinal axis X. Compare FIG. **8** with FIG. **7**B.

[0054] Consequently, according to a further advantageous embodiment of the instant invention, a set of prostheses of different sizes is provided to accommodate a substitution for varying anatomies of the native articular surface of a 1MC bone that include a palmar lip protruding significantly relative to the dorsal lip. This provides a desired post-arthroplasty geometry leading to increased stability and will prevent subluxation of the joint.

[0055] Referring now to FIG. **9**A, there is shown one particular embodiment of a prosthesis **500**, in accordance with the present invention. Prosthesis **500** includes a distal stem portion **503** adapted for insertion into the medullary cavity of a first bone and a proximal head portion **505** adapted to articulate with a second bone forming a joint with the first bone. Stem portion **503** includes a proximal frusto-conical portion **503***a* and a distal bullet shaped portion **503***b*. The head portion **505** includes a saddle shaped articular surface **501** that is circularly concave **501'** in the dorsal-palmar plane and circularly convex **501"** in the lateral-medial plane.

[0056] Further referring now to FIGS. **9**A and **9**B, head portion **505** of prosthesis **500** also includes a generally ovoidal (i.e. egg-shaped), peripheral surface of continuous curvature **506** surrounding the totality of the head portion, with the pole of the ovoid having less curvature oriented towards the dorsal side and with an edge being defined at the interface of the peripheral surface **506** and the articular surface **501**. This edge further defines a dorsal lip **529** at the dorsal pole of the head portion and a palmar (or volar) lip **530** at the opposite volar pole of the head portion. As can be better appreciated in FIG. **9**A the palmar lip **530** protrudes significantly relative to dorsal lip **529**.

[0057] Referring now to FIGS. **9**A-**9**C, the head portion **505** also includes a flat portion **502** opposite the articular surface **501**. Flat portion **502** is adapted to abut against the edge of a bone that has been resected as part of an osteotomy procedure. Emerging from flat portion **502** and blending in a distal direction with stem portion **503**, the prosthesis **500** includes a keel portion **510**, configured to impede the rotation of stem portion **503** during and after insertion into the medullary cavity of a bone.

[0058] Referring now to FIGS. **9**A-**9**H, in one particular embodiment of the instant invention, the head portion **505** also includes a plurality of suture holes **520** which, beginning and ending within peripheral surface **506**, traverse the head portion **505** vertically in a dorsal to palmar direction and include, on the dorsal side, a recess **520***a* adapted to accommodate the knot of a suture. The suture holes **520** exit on the palmar side of surface **506** inside a transverse groove **540**. As will be further described below, this transverse groove **540** is adapted to allow the passage of the Flexor Carpi Radialis ("FCR") tendon under the prosthesis **500**.

[0059] Additionally, as described above, should a prosthesis be required, it is advantageous to have access to a set of prostheses of different sizes to accommodate varying anatomies. Consequentially, in one particular embodiment of the instant invention, at least three sizes of prosthesis **500** are provided, ranging from the largest to the smallest that have been selected by anatomical observation. In one embodiment, the approximate dimensions of the largest prosthesis are: head portion **505**, height and width (0.61 in×0.60 in); stem portion **503**, length and major diameter (0.98 in×0.33 in); saddle-shape articular surface **501**, convex radius of curvature and concave radius of curvature (0.47 in×0.33 in). In this same embodiment, the approximate sizes of the smallest prosthesis are: head portion **505** height and width (0.48 in×0.39 in); stem portion **503** length and major diameter (0.71 in×0.23 in); saddle-shape articular surface **501**, convex radius of curvature and concave radius of curvature (0.3 in×0.26 in). Prostheses of intermediate sizes may be dimensioned by interpolation of the largest and smallest dimensions.

[0060] The inclusion of only three prostheses in a set is not meant to be limiting, as the number of different sizes of prosthesis to be provided in the set can vary. However, it is preferred that a range of three to five prostheses of varying sizes be provided in a set, as desired. However, a greater number or smaller number of prostheses can be provided in a set, without departing from the scope of the present invention. Similarly, the dimensions referred to above are exemplary and are not intended to be limiting in any way.

[0061] A set of trial prostheses (not shown), generally matching the dimensions of the prosthesis **500**, may also be provided if desired. These trial prostheses can be used to help in the selection of the final prosthesis to be installed. Additional instruments in the form of rasps, cutting guides, punches and impactors (not shown) may also be provided as part of the surgical set, if desired.

[0062] As described hereinabove, the provided prostheses advantageously include a palmar lip that protrudes significantly relative to the dorsal lip to provide the desired post-arthroplasty geometry leading to increased stability and pre-

vention of subluxation of the joint. Referring more particularly to FIG. **9**H, there is shown one particular example of the extent to which it is desirable that the palmar lip protrude beyond the dorsal lip. Considering a line T" tangent to the most proximal point on the dorsal lip that is also tangent to the most proximal point of the palmar lip, such line will be inclined at an angle of more than 270 degrees relative to the longitudinal axis X of the prosthesis, and preferably at an angle ranging between 283 degrees and 287 degrees. However, the invention is not intended to be limited to only these dimensions, as other dimensions and angles can be effective and/or used without departing from the scope and spirit of the instant invention.

[0063] Referring now to FIGS. **10**A-**10**B, as described above, the prosthesis **500** is provided with suture holes **520** and a transverse groove **540** to allow the unimpeded passage of the FCR tendon **600** under the prosthesis **500**. The FCR tendon **600** passes under the trapezium **100** to insert itself into the second metacarpal bone. FIGS. **10**A-**10**B show, respectively, a lateral and dorsal view of the FCR tendon **600** passing under the trapezium **100** and transversely under the FCR groove **540** to finally attach itself to second metacarpal bone **295**. In order to maintain this position while the arthroplaticized joint heals, it has been found to be advantageous to have the FCR tendon **600** sutured temporarily within the groove **540**. This can be achieved by using absorbable sutures through the FCR tendon **600**, passing the sutures through the suture holes **520** provided, and tying the sutures at the notch **520***a* in the dorsal side of the peripheral surface **506** of the prosthesis **500**.

[0064] In one particular preferred embodiment of the invention, the prostheses **500** are made of highly polished cobalt chromium and may be coated with titanium plasma spray coating on any or all of the flat surface **502**, the stem **503** and the keel **510**. The trial prostheses, if provided, may be made of aluminum or other bio-compatible material.

[0065] A method will now be described for installing prosthesis **500** as a substitute for the proximal articular surface of the 1MC bone. A surgeon will expose the 1CMC joint with an incision centered over the joint, along the course of the extensor pollicis brevis ("EBP") tendon and releases the tendon from proximal to distal and retracts it ulnarly. The abductor pollicis longus ("APL") tendon is then partially released, and the joint capsule is released circumferentially to allow access to the 1CMC joint. To gain further access to the joint space, the base of the first metacarpal is resected just below the articular surface and the volar aspect of the 1CMC capsule is released to allow identification and removal of osteophytes on the trapezium. The medullary canal is broached with a rasp until cortical bone is contacted circumferentially and the proximal end of the 1MC is resected perpendicularly using a guide attached to the rasp, if provided. A punch is used to create a cavity for receiving the keel **510** of a prosthesis **500**. Trial prostheses, if provided, may be installed to test the reduction and help to select the size of the final prosthesis **500**. If desired, a locking stitch may be performed through the FCR, using absorbable sutures, leaving even lengths of suture at both ends. These two free ends of the sutures are passed through the two suture holes **520** of the prosthesis **500** in a palmar to volar direction and kept taut. The prosthesis **500** is installed by inserting the stem **503** into the prepared medullary canal and impacting it in place and the free ends of the suture are secured on the dorsal side of the prosthesis **500** with a knot in the provided recess **520***a*. After installation, proper kinematics and stability are tested by manipulating the joint through its full range of motion and confirmed fluoroscopically. Finally, soft tissues are repaired as needed before the incision is closed.

[0066] Although the foregoing examples have been given in connection with a carpo-metacarpal joint, it should be understood that this is not meant to be limiting, as the guides, instruments, plates and prostheses described herein can be adapted for use in different joints without departing from the scope of the present invention. For example, the implements described herein can be made in accordance with the description herein, but of different size or scale, so as to treat instability or dislocations of other multi-axis hinged joints, as desired. Thus, although the preferred embodiments of the invention are illustrated and described herein, various modifications and structural changes may be made therein without departing from the spirit of the invention and within the scope and range of equivalents of the claims.

1. A surgical guide, comprising:

a body portion terminating at one end in an angled plane, said body portion additionally including a vertical slot extending through said body portion, said vertical slot being located a first predetermined distance from said one end forming said angled plane; and

a divider piece extending from said body portion at a second predetermined distance from said end forming said angled plane and configured for placement between two bones of a joint.

2. The surgical guide of claim **1**, wherein said first predetermined distance and an angle of said angled plane define a wedge to be removed from a bone of the joint.

3. The surgical guide of claim **1**, wherein said second predetermined distance is longer than said first predetermined distance.

4. The surgical guide of claim **1**, wherein said body portion further includes a hole through said body portion between said slot and said divider portion, said hole being configured to receive a K-wire therethrough.

4. (canceled)

5. A method of performing a wedge osteotomy, comprising the steps of:

providing the guide of claim **1**;

locating the divider piece of the guide between the two bones of the joint;

making a first cut through one bone of the two bones using the angled surface as a cutting guide;

making a second cut through the one bone using the vertical slot as a cutting guide; and

removing a wedge created by the first cut and the second cut.

6. The method of claim **5**, wherein the body portion further includes a hole through the body portion between the slot and the divider portion, and the method further includes the step of installing a K-wire through the body portion into the one bone, to stabilize the body portion relative to the one bone prior to making the first cut.

7. A system for use in a wedge osteotomy, comprising:

a plate including a proximal fixation portion and a distal fixation portion, said proximal fixation portion being configured for fixation to a proximal bone fragment left by the wedge osteotomy and said distal fixation portion being configured for fixation to a distal bone fragment left by the wedge osteotomy, said plate further including a convex perimetral edge; and

a neck portion joining said proximal fixation portion and said distal fixation portion.

8. The system of claim **7**, wherein said plate additionally includes at least one contouring hole through said plate, said at least one contouring hole through said plate being engagable by a contouring tool.

9. The system of claim **8**, wherein the angle between said proximal fixation portion and said distal fixation portion is created by contouring said neck portion using a contouring tool engaged with said at least one contouring hole through said plate.

10. The system of claim **9**, wherein said neck portion is contoured before said plate is fixed to a bone.

11. The system of claim **7**, wherein the proximal fixation portion is angled relative to the distal fixation portion at the neck portion.

12. The system of claim **9**, wherein the neck portion is contoured after said plate is fixed to a bone.

13. The system of claim **7** including a cutting guide for cutting the wedge osteotomy.

14. The system of claim **13**, wherein the cutting guide includes:

a body portion terminating at one end in an angled plane, said body portion additionally including a vertical slot extending through said body portion, said vertical slot being located a first predetermined distance from said one end forming said angled plane; and

a divider piece extending from said body portion at a second predetermined distance from said end forming said angled plane and configured for placement between two bones of a joint.

15. A method of performing a wedge osteotomy, comprising the steps of:

removing a wedge from between a proximal fragment and a distal fragment of a bone;

providing the system of claim **7**;

fixing the proximal fixation portion of the plate to the proximal fragment;

using the distal fixation portion of the plate to manipulate the proximal fragment to a desired position relative to the distal fragment;

after the using step, fixing the distal fixation portion to the distal fragment.

16. The method of claim **15**, wherein the manipulation of the proximal fragment includes using the distal fixation portion to lever the proximal fragment to a desired position relative to the distal fragment.

17. The method of claim **15**, wherein the plate further includes contouring holes and the method further includes the steps of:

providing a contouring tool; and

using the contouring tool to engage the contouring holes to bend the plate.

18. The method of claim **15**, wherein the removing step includes the step of using a cutting guide when cutting the wedge from between the proximal fragment and the distal fragment of the bone.

19. A prosthesis for a first bone of a joint, comprising:

a head portion adapted to articulate with a second bone of the joint, said head portion including an articular surface emulating a native post-osteotomy articular surface of the first bone;

a stem portion adapted for insertion into the medullary cavity of the first bone.

20. The prosthesis of claim **19**, wherein the head portion includes a dorsal lip and a palmar lip, and a plane tangent to the dorsal and palmar lips of the prosthesis is inclined distally in the dorsal side at an angle of approximately 105 degrees relative to a longitudinal axis through the prosthesis.

21. The prosthesis of claim **19**, wherein the stem portion includes a proximal frusto-conical portion and a bullet-shaped distal portion.

22. The prosthesis of claim **21**, wherein the stem portion further includes a keel configured to impede the rotation of stem portion in a medullary canal.

23. The prosthesis of claim **19**, wherein said articular surface includes a saddle shaped articular surface that is circularly concave in the dorsal-palmar plane and circularly convex in the lateral-medial plane.

24. The prosthesis of claim **23**, wherein the head portion includes a generally ovoidal, peripheral surface of continuous curvature surrounding the head portion, with the pole of the ovoid of lesser curvature being oriented towards the dorsal side

25. The prosthesis of claim **19**, wherein the head portion includes a transverse groove configured to allow the passage of the Flexor Carpi Radialis ("FCR") tendon.

26. The prosthesis of claim **19**, wherein the head portion includes at least one suture hole traversing the head portion in a dorsal to palmar direction

27. The prosthesis of claim **26**, wherein the at least one suture hole is disposed in a transverse groove of the head portion.

28. A set of prostheses of different sizes to accommodate varying anatomies, each prosthesis of said set of prostheses being configured according to claim **19**.

29. A method of installing a prosthesis, comprising:

exposing and resecting a first bone of a joint below an articular surface of the bone;

providing the prosthesis of claim **19**; and

inserting the stem of the prosthesis into the medullary canal until a flat surface on the head portion abuts a surface of the resected first bone.

30. The method of claim **29**, wherein the stem portion further includes a keel configured to impede the rotation of stem portion in a medullary canal.

31. The method of claim **29**, wherein at least one trial prosthesis is used to help select the size of a final prosthesis.

32. The method of claim **29**, further including the steps of:

before said inserting step, using a suture to place at least one locking stitch through the FCR tendon; and

passing the free end of the suture through the at least one suture hole and keeping the suture taut; and

after the inserting step, knotting the suture on the dorsal side of the prosthesis.

33. The method of claim **32**, wherein the head portion of the prosthesis additionally includes a transverse groove, said transverse groove including at least one suture hole through which the suture is passed and knotted in the knotting step.

34. The guide of claim **3**, wherein said body portion is additionally configured to releasably engage a handle.

* * * * *