

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	2BROS.019A
		Application Number	
Title of Invention	CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE		
<p>The application data sheet is part of the provisional or nonprovisional application for which it is being submitted. The following form contains the bibliographic data arranged in a format specified by the United States Patent and Trademark Office as outlined in 37 CFR 1.76.</p> <p>This document may be completed electronically and submitted to the Office in electronic format using the Electronic Filing System (EFS) or the document may be printed and included in a paper filed application.</p>			

Secrecy Order 37 CFR 5.2

- ☐ Portions or all of the application associated with this Application Data Sheet may fall under a Secrecy Order pursuant to 37 CFR 5.2 (Paper filers only. Applications that fall under Secrecy Order may not be filed electronically.)

Applicant Information:

Applicant 1					Remove	
Applicant Authority		☒ Inventor		☐ Legal Representative under 35 U.S.C. 117		☐ Party of Interest under 35 U.S.C. 118
Prefix	Given Name	Middle Name	Family Name	Suffix		
	Jeff		Whitten			
Residence Information (Select One)		☒ US Residency ☐ Non US Residency ☐ Active US Military Service				
City	Santa Ana	State/Province	CA	Country of Residence ⁱ		
Citizenship under 37 CFR 1.41(b) ⁱ		US				
Mailing Address of Applicant:						
Address 1		401 South Grand Avenue				
Address 2						
City	Santa Ana	State/Province	CA			
Postal Code	92705	Country ⁱ				
All Inventors Must Be Listed - Additional Inventor Information blocks may be generated within this form by selecting the Add button. Add						

Correspondence Information:

Enter either Customer Number or complete the Correspondence Information section below. For further information see 37 CFR 1.33(a).			
☐ An Address is being provided for the correspondence information of this application.			
Customer Number	20995		
Email Address	efiling@kmob.com	Add Email	Remove Email

Application Information:

Title of the Invention	CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE		
Attorney Docket Number	2BROS.019A	Small Entity Status Claimed ☒	
Application Type	Nonprovisional		
Subject Matter	Utility		
Suggested Class (if any)		Sub Class (if any)	
Suggested Technology Center (if any)			
Total Number of Drawing Sheets (if any)	11	Suggested Figure for Publication (if any)	

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	2BROS.019A
		Application Number	
Title of Invention	CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE		

Publication Information:

☐	Request Early Publication (Fee required at time of Request 37 CFR 1.219)
☐	Request Not to Publish. I hereby request that the attached application not be published under 35 U.S.C. 122(b) and certify that the invention disclosed in the attached application has not and will not be the subject of an application filed in another country, or under a multilateral international agreement, that requires publication at eighteen months after filing.

Representative Information:

Representative information should be provided for all practitioners having a power of attorney in the application. Providing this information in the Application Data Sheet does not constitute a power of attorney in the application (see 37 CFR 1.32). Enter either Customer Number or complete the Representative Name section below. If both sections are completed the Customer Number will be used for the Representative Information during processing.			
Please Select One:	☒ Customer Number	☐ US Patent Practitioner	☐ Limited Recognition (37 CFR 11.9)
Customer Number	20995		

Domestic Benefit/National Stage Information:

This section allows for the applicant to either claim benefit under 35 U.S.C. 119(e), 120, 121, or 365(c) or indicate National Stage entry from a PCT application. Providing this information in the application data sheet constitutes the specific reference required by 35 U.S.C. 119(e) or 120, and 37 CFR 1.78(a)(2) or CFR 1.78(a)(4), and need not otherwise be made part of the specification.			
Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)
	non provisional of	61585933	2012-01-12
Prior Application Status	Pending	Remove	
Application Number	Continuity Type	Prior Application Number	Filing Date (YYYY-MM-DD)
	non provisional of	61653618	2012-05-31
Additional Domestic Benefit/National Stage Data may be generated within this form by selecting the Add button.			Add

Foreign Priority Information:

This section allows for the applicant to claim benefit of foreign priority and to identify any prior foreign application for which priority is not claimed. Providing this information in the application data sheet constitutes the claim for priority as required by 35 U.S.C. 119(b) and 37 CFR 1.55(a).			
Remove			
Application Number	Country ⁱ	Parent Filing Date (YYYY-MM-DD)	Priority Claimed
			☐ Yes ☒ No
Additional Foreign Priority Data may be generated within this form by selecting the Add button.			Add

Application Data Sheet 37 CFR 1.76		Attorney Docket Number	2BROS.019A
		Application Number	
Title of Invention	CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE		

Assignee Information:

Providing this information in the application data sheet does not substitute for compliance with any requirement of part 3 of Title 37 of the CFR to have an assignment recorded in the Office.

Assignee 1

[Remove](#)

If the Assignee is an Organization check here. ☒

Organization Name Two Brothers Racing U.S.A.

Mailing Address Information:

Address 1 401 South Grand Avenue

Address 2

City Santa Ana

State/Province

CA

Country i

Postal Code

92705

Phone Number

Fax Number

Email Address

Additional Assignee Data may be generated within this form by selecting the Add button.

[Add](#)

Signature:

A signature of the applicant or representative is required in accordance with 37 CFR 1.33 and 10.18. Please see 37 CFR 1.4(d) for the form of the signature.

Signature	/Curtiss C. Dosier/		Date (YYYY-MM-DD)	2012-08-23	
First Name	Curtiss	Last Name	Dosier	Registration Number	46670

This collection of information is required by 37 CFR 1.76. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 23 minutes to complete, including gathering, preparing, and submitting the completed application data sheet form to the USPTO. Time will vary depending upon the individual case. Any comments on the amount of time you require to complete this form and/or suggestions for reducing this burden, should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. **SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.**

Privacy Act Statement

The Privacy Act of 1974 (P.L. 93-579) requires that you be given certain information in connection with your submission of the attached form related to a patent application or patent. Accordingly, pursuant to the requirements of the Act, please be advised that: (1) the general authority for the collection of this information is 35 U.S.C. 2(b)(2); (2) furnishing of the information solicited is voluntary; and (3) the principal purpose for which the information is used by the U.S. Patent and Trademark Office is to process and/or examine your submission related to a patent application or patent. If you do not furnish the requested information, the U.S. Patent and Trademark Office may not be able to process and/or examine your submission, which may result in termination of proceedings or abandonment of the application or expiration of the patent.

The information provided by you in this form will be subject to the following routine uses:

1. The information on this form will be treated confidentially to the extent allowed under the Freedom of Information Act (5 U.S.C. 552) and the Privacy Act (5 U.S.C. 552a). Records from this system of records may be disclosed to the Department of Justice to determine whether the Freedom of Information Act requires disclosure of these records.
2. A record from this system of records may be disclosed, as a routine use, in the course of presenting evidence to a court, magistrate, or administrative tribunal, including disclosures to opposing counsel in the course of settlement negotiations.
3. A record in this system of records may be disclosed, as a routine use, to a Member of Congress submitting a request involving an individual, to whom the record pertains, when the individual has requested assistance from the Member with respect to the subject matter of the record.
4. A record in this system of records may be disclosed, as a routine use, to a contractor of the Agency having need for the information in order to perform a contract. Recipients of information shall be required to comply with the requirements of the Privacy Act of 1974, as amended, pursuant to 5 U.S.C. 552a(m).
5. A record related to an International Application filed under the Patent Cooperation Treaty in this system of records may be disclosed, as a routine use, to the International Bureau of the World Intellectual Property Organization, pursuant to the Patent Cooperation Treaty.
6. A record in this system of records may be disclosed, as a routine use, to another federal agency for purposes of National Security review (35 U.S.C. 181) and for review pursuant to the Atomic Energy Act (42 U.S.C. 218(c)).
7. A record from this system of records may be disclosed, as a routine use, to the Administrator, General Services, or his/her designee, during an inspection of records conducted by GSA as part of that agency's responsibility to recommend improvements in records management practices and programs, under authority of 44 U.S.C. 2904 and 2906. Such disclosure shall be made in accordance with the GSA regulations governing inspection of records for this purpose, and any other relevant (i.e., GSA or Commerce) directive. Such disclosure shall not be used to make determinations about individuals.
8. A record from this system of records may be disclosed, as a routine use, to the public after either publication of the application pursuant to 35 U.S.C. 122(b) or issuance of a patent pursuant to 35 U.S.C. 151. Further, a record may be disclosed, subject to the limitations of 37 CFR 1.14, as a routine use, to the public if the record was filed in an application which became abandoned or in which the proceedings were terminated and which application is referenced by either a published application, an application open to public inspections or an issued patent.
9. A record from this system of records may be disclosed, as a routine use, to a Federal, State, or local law enforcement agency, if the USPTO becomes aware of a violation or potential violation of law or regulation.

CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE**CROSS-REFERENCE TO RELATED APPLICATIONS**

[0001] This application claims the benefit of U.S. Provisional Patent Application Nos. 61/585,933, entitled “PHONE CASE AND MOUNT SYSTEM,” filed January 12, 2012, and 61/653,618, entitled “CASE MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE,” filed May 31, 2012.

[0002] This application hereby incorporates by reference the above-identified provisional applications in their entirety.

BACKGROUND OF THE INVENTIONField of the Invention

[0003] The invention relates generally to protective cases for handheld electronic devices.

Description of the Related Art

[0004] Handheld and/ or portable electronic devices (e.g., digital media players, phones, smartphones, tablet computers, handheld readers, and similar devices) are becoming important and common tools. These tools are constantly in use, both at home and on the go.

[0005] However, with this frequency and variety of use comes the problem of proper protection. Without proper protection, a device may become damaged due to being dropped or by falling from an unsecured position. This damage may be permanent and cause loss of data or information and high replacement costs.

SUMMARY OF THE INVENTION

[0006] In at least one embodiment, the present application relates to a protective system for a handheld electronic device that overcomes the shortcomings of the prior art noted above.

[0007] In some embodiments, a protective system for a handheld electronic device is disclosed. The protection system comprises a shell comprised of a rear wall, a plurality of wall surfaces arranged to enclose a plurality of peripheral edges of a handheld electronic device, and an outer surface. The rear wall further defines an attachment region designed to receive an interlocking member and a non-slip region designed to receive a non-slip member.

The attachment region comprises a first open space, an inner interlocking surface and an outer interlocking surface, both the interlocking surfaces surrounding the first open space, the inner interlocking surface being located above the plane of the outer surface of the rear wall and wherein the inner and outer interlocking surfaces are radially offset to provide an interlocking area. The interlocking member comprises a plate having a plurality of engaging members generally located at right angles, the engaging members being configured to interact with the inner and outer interlocking surfaces such that in an interlocked position each of the engaging members is disposed within the interlocking area. The interlocking member further comprises at least one mounting base. The non-slip region comprises a second open space and a recessed surface formed by the disposition of a small diameter opening within a larger diameter opening. The non-slip member comprises a non-slip material shaped to fit within the second open space, the non-slip member having a circumferential groove dividing the non-slip member into a gripping surface and an interior surface, the interior surface having a greater diameter than the gripping surface, the groove in the non-slip member engaging with the recessed surface to attach the non-slip member to the shell. The non-slip member further comprises an indentation on the interior surface designed to incorporate a magnet.

[0008] 1. An embodiment involves a protection system for a handheld electronic device, including a shell comprising a rear wall and a side wall extending from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device. The rear wall further comprises an inner surface and an outer surface. The rear wall defines an attachment region designed to receive an interlocking member and a non-slip region designed to receive a non-slip member. The attachment region comprises a first open space, a first interlocking surface and a second interlocking surface. Both of the first and second interlocking surfaces surrounding at least a portion of the first open space. The first and second interlocking surfaces are located behind the inner surface of the rear wall with the first interlocking surface being located substantially in a first plane and the second interlocking surface having at least a portion that extends substantially perpendicular to the first plane. The first interlocking surface is circumferentially offset from at least a portion of the second interlocking surface to provide an interlocking area. The interlocking member comprises a plate portion having at least one engagement member that, in use, is passed

through the first open space and disposed within the interlocking area to achieve an interlocked position between the interlocking member and the shell. The interlocking member further comprises at least one mounting base. The non-slip region comprises a second open space and a recessed surface formed by the disposition of a smaller opening within a larger opening. The non-slip member comprises a non-slip material shaped to fit within the second open space. The non-slip member has a peripheral groove that, in use, engages the recessed surface to attach the non-slip member to the shell. The non-slip member further comprises an indentation within an interior surface that, in use, faces the associated handheld electronic device. A magnet is received within the indentation of the non-slip member.

[0009] 2. The system of paragraph 1, wherein the shell further comprises at least one access opening that allows access to control features of the handheld electronic device.

[0010] 3. The system of paragraph 1, wherein the non-slip member is disposed outwardly of the outermost portion of the outer surface of the rear wall of the shell.

[0011] 4. The system of paragraph 1, wherein the mounting base further comprises an adhesive layer that, in use, attaches to a mounting surface via adhesion.

[0012] 5. The system of paragraph 1, wherein the interlocked position is achieved by rotation of the interlocking member within the attachment region.

[0013] 6. An embodiment involves a protection system for a handheld electronic device, including a shell comprising a rear wall and a side wall extending from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device. The rear wall further comprises an inner surface and an outer surface. The rear wall defines an attachment region designed to receive an interlocking member and a non-slip region designed to receive a non-slip member. The attachment region comprises a first open space and a plurality of interlocking surface portions, and each of the interlocking surface portions including a retaining surface and a stop surface that cooperate to provide an interlocking area. The interlocking member comprises a plurality of engaging members, each of which are configured to interact with one of the plurality of interlocking surface portions such that, in an interlocked position, each of the plurality of engaging members is disposed within one of the plurality of interlocking areas. The non-slip region comprises a second open space and a recessed surface formed by the disposition of a smaller opening within a larger

opening. The non-slip member comprises a non-slip material shaped to fit within the second open space, the non-slip member having a peripheral groove that, in use, engages the recessed surface to attach the non-slip member to the shell.

[0014] 7. The system of paragraph 6, wherein the shell further comprises at least one access opening that allows access to control features of a handheld electronic device.

[0015] 8. The system of paragraph 6, further comprising a magnet disposed within the non-slip member.

[0016] 9. The system of paragraph 6, further comprising at least one mounting base attached to the interlocking member.

[0017] 10. The system of paragraph 9, wherein the mounting base comprises an adhesive layer that allows the mounting base to be affixed to a surface through adhesion.

[0018] 11. An embodiment involves a protection system for a handheld electronic device, which includes a shell comprising a rear wall and a side wall extending in a first direction from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device. The rear wall comprises a first surface facing in the first direction and a second surface facing in a second direction opposite the first direction. The rear wall comprises an opening extending through the second surface. The opening defines at least one shell interlock surface. The system also includes a mount having at least one mount interlock surface, wherein, in use, a portion of the mount is passed through the opening of the shell and the at least one shell interlock surface is engaged with the at least one mount interlock surface to selectively couple the shell to the mount.

[0019] 12. The protection system of paragraph 11, wherein the mount comprises an adhesive layer that permits the mount to be secured to a surface via adhesion.

[0020] 13. The protection system of paragraph 11, wherein the mount is a bike mount that, in use, is mounted to a component of a bicycle.

[0021] 14. The protection system of paragraph 13, wherein the bike mount comprises a cap portion that, in use, is secured to a steerer tube of the bicycle.

[0022] 15. The protection system of paragraph 14, further comprising an arm portion that extends between the cap portion and the at least one mount interlock surface, wherein the arm portion is rotatably adjustable relative to the cap portion.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023] These and other features, aspects, and advantages of the present invention will now be described in connection with a preferred embodiment of the present invention, in reference to the accompanying drawings. The illustrated embodiments, however, are merely examples and are not intended to limit the invention.

[0024] FIG. 1 is a perspective view of an exploded assembly of protective system for a handheld electronic device according to a preferred embodiment of the invention;

[0025] FIG. 2 is a view of the interior rear surface of a shell of the protective system;

[0026] FIG. 3 is a view of the exterior rear surface of a shell of the protective system;

[0027] FIG. 4 is a perspective view of a shell of the protective system;

[0028] FIG. 5 is a perspective view of a lower shell of the protective system;

[0029] FIG. 6 is a cross sectional view of a shell of the protective system and a mounting member;

[0030] FIG. 7 is a cross sectional view of a shell of the protective system and a non-slip member;

[0031] FIG. 8A is a perspective view of a non-slip member;

[0032] FIG. 8B is a second perspective view of a non-slip member;

[0033] FIG. 8C is a perspective view of an exploded assembly of a non-slip member containing a rare-earth magnet and a magnet cover piece;

[0034] FIG. 9A is a perspective view of a first side of an interlocking member;

[0035] FIG. 9B is a second perspective view of a second side of the interlocking member;

[0036] FIG. 9C is a perspective view of a mounting base; and

[0037] FIG. 10 is a perspective view of an assembled mounting member.

[0038] FIG. 11 is perspective view of the protective system secured to a bicycle mount.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

[0039] The following detailed description is directed to certain specific embodiments of the invention. However, the invention may be embodied in a multitude of different ways as defined and covered by the claims.

[0040] Embodiments of the invention can provide the features of a protection system for a portable or handheld electronic device (hereinafter “handheld electronic device”). Some embodiments of the invention desirably may incorporate an attachment region for attaching a removable mounting member preferably able to support the handheld electronic device within the protection system and affix to a variety of surfaces. Other embodiments of the invention may also incorporate an anti-slip surface wherein a magnet is disposed for attachment of the device to magnetic surfaces and slip prevention.

[0041] A preferred embodiment of the present invention comprises a shell for rigidly securing and protecting a handheld electronic device. In a preferred embodiment, the shell may be in multiple pieces for ease of assembly around a handheld electronic device. The upper piece of the shell preferably provides an attachment region for a removable mounting member that can attach to various solid surfaces, such as but not limited to a desk, vehicle dashboard, mirror, etc. The shell preferably also incorporates an anti-slip insert in which a magnet is disposed, allowing for magnetic adherence to surfaces without interfering with the anti-slip benefit provided by the anti-slip insert. The shell preferably is formed using a material that is generally rigid and lightweight, such as but not limited to an injection molded polycarbonate or other suitable plastic material(s). Preferably, the shell comprises rigid sidewalls that surround an entirety or portions of the peripheral edges of the device. The sidewalls preferably are arranged to protect the device by absorbing incidental shock forces and/or inhibiting or preventing direct contact between the device and another object. The sidewalls also desirably contain various openings to allow access to the control buttons, inputs, and outputs of the handheld electronic device. The rear surface of the shell is preferably further designed with various openings to allow additional access to features of the handheld electronic device that may be located on the rear of the device (such as a camera) or to reduce the weight of the shell.

[0042] FIG. 1 depicts a preferred embodiment having certain features, aspects and advantages of the present invention. In FIG.1, protection system 100 may include more,

fewer or different components than those shown. Protection system 100 includes a body or shell that, in the illustrated arrangement, is comprised of an upper shell piece 102 and lower shell piece 104. Protection system 100 is shown in two pieces to facilitate installation of the protection system 100 on a handheld electronic device. Lower shell piece 104 is designed, in one embodiment, to fit together with upper shell piece 102 preferably using an interlocking or tab / slot attachment. However, in other arrangements, the upper shell piece 102 and lower shell piece 104 could be secured together with other arrangements (e.g., mechanical fasteners, such as screws) or could be portions of a unitary or single-piece shell in which installation of the electronic device is accomplished through another method, such as by deformation of the side walls or other portions of the shell to pass over the electronic device. Thus, references to the upper shell piece 102 or lower shell piece 104 herein are also intended to refer to the entire shell of an integrated or unitary shell arrangement.

[0043] Upper shell piece 102 preferably includes an attachment region 106 for attaching mounting member 108. The attachment region 106 contains an engagement structure that allows the upper shell piece 102 and, thus, the protection system 100 to be releasably attached the mounting member 108. A preferred engagement structure is described in greater detail below. As shown in FIG. 1 and FIGS. 9A-C, mounting member 108 may be comprised of an interlocking member 902 and at least one mounting base 904. As described further below and shown in Figure 6, the mounting member 108 can also include one or more optional spacers, which could be similar or identical to the mounting base 904. Upper shell piece 102 also preferably includes a non-slip region 110, which includes a non-slip arrangement that enhances frictional engagement of protection system 100 with a surface on which the protection system 100 may be placed. In the illustrated arrangement, the non-slip region 110 incorporates an opening or cavity in the protection system 100 (e.g., the upper shell piece 102) into which non-slip member 112 may be inserted. As depicted more clearly in FIG. 8C, non-slip member 112 may also preferably comprise a rare earth magnet 802 in order to removably attach the handheld electronic device contained within protection system 100 to a magnetic surface.

[0044] FIG. 1 further depicts a preferred embodiment of the invention further comprising a lanyard 140, which may attach to protection system 100 to facilitate easy

carrying and transport of a handheld electronic device. For example, the lanyard 140 can be looped through openings 142 and 144 on the upper shell piece 102 and lower shell piece 104, respectively. Additional accessories, not shown in FIG. 1, may be used with protection system 100. For example, one accessory that may be used with protection system 100 includes a bike mount, one embodiment of which is shown in Figure 11. Another accessory that may be used with protection system 100 includes a tripod (not shown), which can support the protection system 100 and associated electronic device in a suitable position (e.g., portrait or landscape) preferably at an elevated position relative to a surface on which the tripod rest to take photographs or video. The accessory can be coupled to the protection system 100 via an interlocking arrangement the same as or similar to the mounting member 108 or via other suitable arrangements, such as the same as or similar to the lanyard 140 arrangement. In addition to the lanyard 140, bike mount and tripod, other types of accessories can also be provided, such as adjustable or non-adjustable stands, mounting or securing clip arrangements, etc.

[0045] As shown in FIGS. 1-4, the assembled upper shell piece 102 and lower shell piece 104 of the protection system 100 together define an interior region or space in which a handheld electronic device may be enclosed. Each of the upper shell piece 102 and the lower shell piece 104 has a rear wall portion 200 that defines an interior rear surface 202 positioned adjacent the back surface of an electronic device placed in the protection system 100. The upper shell piece 102 and the lower shell piece 104 also include at least one or a plurality of enclosing edges to surround the sides of a handheld electronic device and provide protection for the handheld electronic device. In the illustrated arrangement, the enclosing edges are defined by a sidewall portion 150 that extends from the rear wall portion 200. The illustrated sidewall portion 150 extends along an entire periphery of the rear wall portion 200. As described above, however, the sidewall portion 150 is not necessarily solid or continuous, but can include one or more openings configured to allow access to controls or other components or features of the handheld electronic device, or simply to reduce weight. In alternative arrangements, the sidewall portion 150 can be constructed of one or several distinct sidewall portions, such as four corner portions, for example. A forward wall portion is spaced from the rear wall portion 200 by the sidewall portion 150. The forward wall

portion defines a forward interior surface that is positioned adjacent a forward surface of the handheld electronic device placed in the protection system 100. In the illustrated arrangement, the forward wall portion is defined by a lip 152 that extends in an inward direction from the sidewall portion 150. Preferably, the lip 152 extends around the entire periphery of the rear wall portion 200. However, in other arrangements, the lip 152 can extend only around a portion of the periphery, which can be the same portion or a different portion than the portion surrounded by the sidewall portion 150. As discussed above, the upper shell piece 102 and lower shell piece 104 can be unitarily-formed. Accordingly, the sidewall portion 150 and/or lip 152 could be unitary, as well.

[0046] As more clearly illustrated in FIG. 2, upper shell piece 102 also preferably includes an attachment region 106. The illustrated attachment region 106 defines an opening 160 in the interior rear surface 202 of upper shell piece 102. As described above, attachment region 106 is configured to allow attachment of mounting member 108 through an interlocking attachment that selectively secures the shell 102 to the mounting member 108 and inhibits or prevents removal in at least one direction. As pictured, attachment region 106 comprises at least one tab 162, each of which preferably defines two interlocking surfaces, 116 and 126. In the illustrated arrangement, the attachment region 106 includes four tabs 162; however, other numbers of tabs 162 could also be provided, such as two, three, five, six or more tabs 162. Interlocking surface 116 is disposed towards the interior rear surface 202 of upper shell piece 102, while interlocking surface 126 is disposed within a different plane than that defined by interlocking surface 116. Preferably, the interlocking surface 116 is perpendicular or substantially perpendicular to the interlocking surface 126. Preferably, the interlocking surface 116 is perpendicular or substantially perpendicular to the interior rear surface 202. The plane of interlocking surface 126 preferably is offset or disposed “below” the plane defined by the interior rear surface 202 or towards the outer rear surface of upper shell piece 102. In addition, preferably, the interlocking surface 116 is offset from at least a portion of the interlocking surface 126 in a circumferential direction to provide a space 164 in which a portion (e.g., tab 912) of the interlocking member 902 may be inserted. The opening 160 preferably also includes at least one access space 166 located beside or circumferentially offset from the at least one tab 162. Preferably, the number of access spaces 166 corresponds

to the number of tabs 162. In the illustrated arrangement, four access spaces 166 are provided; however, the number of access spaces 166 can vary in the same manner as the number of tabs 162. Each of the tabs 912 of the interlocking member 902 can be inserted through one of the access spaces 166 and then turned to enter the space 164 and rest against the interlocking surfaces 116 and 126 to form an attachment with upper shell piece 102. Preferably, the access opening 166 is located on an opposite side of the interlocking surface 126 from the interlocking surface 116. In the illustrated arrangement, a circumferential dimension of the access opening 166 is smaller than a circumferential dimension of the tab 162 and can be approximately one-half of the circumferential dimension of the tab 162. The circumferential dimension of the space 164 is less than the circumferential dimension of the tab 162 and can be approximately one-half of the circumferential dimension of the tab 162. In the illustrated arrangement, the interlocking surface 116 is defined by a rib 168 that extends at least partially, and preferably entirely, around the opening 160. Preferably, the opening 160 passes completely through the upper shell piece 102 such that the surface of the associated electronic device is exposed through the opening 160. Such an arrangement advantageously minimizes the overall thickness of the protection system 100, while still providing the desired interlocking mount functionality. In an alternative arrangement, however, a rear wall portion can be provided to define a closed internal end of the opening 160, such that the rear wall portion is positioned in between the interlocking mount and the associated electronic device. Such an arrangement may increase the overall thickness of the protection system 100, but can also provide increased protection to the associated electronic device.

[0047] The interior rear surface 202 preferably also includes a non-slip region 110 within which a non-slip arrangement can be provided. For example, a non-slip member 112 may be inserted within the non-slip region 110 of the protective device 100. As shown, non-slip region 110 is comprised of a smaller opening 120 disposed within a larger opening 130. In the illustrated arrangement, the smaller opening 120 extends completely through the rear wall portion 200 and the larger opening 130 extends partially through the rear wall portion 200 from the interior rear surface 202. The recessed surface formed by the disposition of smaller opening 120 within larger opening 130 forms an interference surface to retain non-slip member 112 within the non-slip region 110. FIG. 2 shows one orientation of attachment

region 106 and non-slip region 110, though other embodiments may include different orientations. A number of additional open spaces (generally 170) may be provided in the interior rear surface 202 of upper shell piece 102 for any of a number of reasons, including providing access to rear-mounted features of a handheld electronic device such as a camera, microphone, or speaker, or to reduce the weight of the protection system 100. Upper shell piece 102 may further comprise one or more of recesses 204 configured to accommodate one or more tabs 206 to facilitate attachment and retention of lower shell piece 104 to upper shell piece 102 to provide further protection for a handheld electronic device. In the illustrated arrangement, a pair of recesses 204 are located on the rear wall portion 200 of the upper shell piece 102 and a pair of tabs 206 are located on the rear wall portion 200 of the lower shell piece 104. However, in other arrangements, the recesses 204 and tabs 206 could be located elsewhere (e.g., sidewall 150 or front wall/lip 152) and/or could be provided in different numbers. In addition, the arrangement could be reversed such that the tabs 206 are provided on the upper shell piece 102 and the recesses 204 are provided on the lower shell piece 104.

[0048] One embodiment of the exterior rear surface 302 of upper shell piece 102 is pictured in FIG. 3. The attachment region 106 as viewed from the rear of upper shell piece 102 is preferably disposed above or outwardly of the plane defined by at least a portion of the exterior rear surface 302, which can be a peripheral portion. In a preferred embodiment, the attachment region 106 has an opening 160 defined by a plurality of equally spaced radial lobes or tabs 162 designed to correspond with the tabs 912 of an interlocking member 902, more clearly viewed in FIGS. 9A and 9B. Mounting member 108 attaches to the exterior rear surface 302 side of the rear wall portion 200 of the upper shell piece 102 of protection system 100 preferably via an interlocking attachment. Once inserted, the tabs 912 of the interlocking member 902 may then rotate until further rotation is prevented by the interlocking surface 116, as seen in FIG. 2. After rotation, the tabs of interlocking member 902 will preferably be located adjacent to the interior side of interlocking surface 126 and against the edge of interlocking surface 116, forming an interlocking connection which preferably attaches mounting member 108 to the upper shell piece 102 of protection system 100.

[0049] Preferably, non-slip region 110 will also be disposed above the plane defined by exterior rear surface 302, as seen in FIG. 3. In the illustrated arrangement, when

inserted, the non-slip member 112 will protrude outwardly as far as or further than any other rearward surface portion of the protection system 100 such that the non-slip member 112 will contact a surface upon which the protection system 100 is placed (assuming the surface is relatively flat or otherwise appropriately shaped) to accomplish a non-slip function. Therefore, when non-slip member 112 is disposed within non-slip region 110, the non-slip surface will extend beyond at least the plane of exterior rear surface 302 to grip a surface and provide a non-slip feature.

[0050] A perspective view of a preferred embodiment of upper shell piece 102 is pictured in FIG. 4. In this view, the different surfaces of attachment region 106 are more clearly visible. As described above with respect to FIG. 2, interlocking surface 116 is disposed towards the interior rear surface 202 of upper shell piece 102 relative to the interlocking surface 126, while interlocking surface 126 is disposed “below” the plane defined by interlocking surface 116, or towards the outer rear surface of upper shell piece 102. As is more clearly seen in FIG. 4, the interlocking surface 116 is circumferentially offset from the access opening 166 to provide the space 164 in which an interlocking member 902 may be inserted and then turned to form an attachment with upper shell piece 102. The rotation of the interlocking member 902 within attachment region 106 forms an interlocking connection with the upper shell piece 102. This interlocking connection is defined by the tabs 912 of the interlocking member 902 passing without obstruction into the defined areas (e.g., access openings 166) of attachment region 106 and then rotating against the interior surface of interlocking surface 126 until the tabs of interlocking member 902 are prevented from further rotation by encountering the interlocking surface 116. After rotation, the interior-facing surfaces of the interlocking member 902 and the interlocking surface 116 preferably will be substantially within the same plane.

[0051] FIG. 4 also more clearly depicts a preferred embodiment of the non-slip region 110 and openings 120 and 130. The smaller opening 120 is disposed within the larger opening 130. A small lip or ridge 180 is formed by the overlap of the two openings because the larger opening 130 is disposed towards the interior rear surface 202 of upper shell piece 102. Preferably, this lip or ridge 180 is disposed beneath the plane of the interior rear surface 202. The flexible non-slip member 112, such as that described in greater detail below with

regard to FIGS. 8A-C, may be disposed within the non-slip region 110. An interior portion of the non-slip member 112 preferably has a greater diameter than the smaller opening 120 but also has a diameter sized to fit within larger opening 130. When inserted into the non-slip region 110, the larger diameter of the interior surface prevents the non-slip member 112 from falling out of the non-slip region 110. The smaller diameter of opening 120 will substantially prevent the non-slip member 112 from falling out of the non-slip region 110. The opening 120 defined by the non-slip region 110 will therefore allow a portion of the non-slip member 112 to contact a surface. The inclusion of the non-slip member 112 into protection system 100 provides non-slip properties and benefits to the protection system 100, such as preventing a handheld electronic device within the protection system from sliding off a smooth surface such as a desk or counter. The non-slip member 112 can include a peripheral recess 182 that is configured to receive the lip 180 to more securely hold the non-slip member 112 within the opening 120.

[0052] Lower shell piece 104 is shown in FIG. 5. In a preferred embodiment, lower shell piece 104 comprises an interior surface and side surfaces that surround the lower sides of a handheld electronic device to provide additional protection. Lower shell piece 104 preferably joins with upper shell piece 102 to provide protection around the sides and back of a handheld electronic device. The lower shell piece 104 can contain one or more openings to allow access to controls and ports on the handheld electronic device, such as a headphone jack or microphone jack. Furthermore, lower shell piece 104 also preferably contains an opening 190 to allow access to the charging area and/or microphone and speakers on the handheld electronic device such that the handheld electronic device does not need to be removed from protection system 102 in order to charge the device. FIG. 5 depicts only a preferred embodiment of the invention and other openings not shown may be included.

[0053] FIG. 6 illustrates a cross section of upper shell piece 102 and mounting member 108. In this figure, mounting member 108 is affixed to upper shell piece 102 in a preferred embodiment. As shown in this figure, the mounting member 108 is affixed to the rear surface of upper shell piece 102 within attachment region 106. Mounting member 108 extends out from the rear surface 302 of upper shell piece 102 such that protection system 100 may be mounted on a solid surface without being flush against the solid surface. The

mounting member 108 depicted in the preferred embodiment is composed of two mounting pieces (e.g., mounting bases 904) joined together, along with an interlocking member 902. Mounting member 108 may be composed of greater or fewer mounting pieces joined together, depending on how far a user desires to mount the handheld electronic device from a solid surface. The interlocking member 902 of the mounting member 108 is joined to the interlocking member 902 preferably via a screw 906, but other forms of attachment may be used. The mounting bases 904 can be joined together by any suitable arrangement (e.g., snap-fit or mechanical fasteners) or the screw 906 could also hold the mounting bases 904 together in addition to securing the interlocking member 902 to the mounting base(s). If desired, an optional adhesive layer 908 can be provided on the rearward surface of the mounting member 108 to allow the mounting member 108 to be adhesively coupled to a desired surface.

[0054] A cross-sectional view of a preferred embodiment of protection system 100 containing non-slip member 112 is shown in FIG. 7. In the preferred embodiment shown, the non-slip surface of non-slip member 112 extends in a rearward direction at least as far and, preferably, beyond any other portion of exterior rear surface 302 of upper shell piece 102 (and lower shell piece 104) in order to provide a gripping surface to prevent a handheld electronic device from slipping on a solid surface. The non-slip member 112 also preferably contains a magnetic member, such as a rare-earth magnet 802, as further described below in regards to FIG. 8C. The magnet 802 is positioned or embedded within non-slip member 112 in order to provide a means of attaching protection system 100 to a magnetic surface without impacting the non-slip benefits provided by non-slip member 112 or scratching the surface.

[0055] One preferred embodiment of a non-slip member 112 is shown in FIGS. 8A, 8B, and 8C. The non-slip member 112 is composed of a gripping outer surface shown in FIG. 8B and an interior-facing surface, as shown in FIG. 8A. This figure depicts a generally round or cylindrical indentation 192 into which a rare-earth magnet or other magnetic material may be placed without interfering with the non-slip benefits provided by non-slip member 112.

[0056] FIG. 8B depicts the exterior-facing surface of non-slip member 112. This figure more clearly illustrates the larger diameter of the interior-facing surface of non-slip member 112 versus the exterior-facing surface. These surfaces are separated by the groove or

recess 182, which interacts with the smaller opening 120 in upper shell piece 102, as discussed above with regard to FIG. 4. As discussed above, the larger diameter of the interior surface prevents the non-slip member 112 from falling out of the non-slip region 110 because of interference between the larger diameter of the interior surface of non-slip member 112 and the smaller diameter of opening 120. The exterior surface of non-slip member 112 preferably has a ridged or roughened surface features in order to provide a better gripping surface and prevent the protection system from slipping on a solid surface. The exterior surface may also comprise different logos or other surface textures as desired.

[0057] The inclusion of rare-earth magnet 802 into non-slip member 112 is shown in FIG. 8C. This figure illustrates that the rare-earth magnet is preferably inserted into the indentation 192 on the interior surface of non-slip member 112. An optional cover piece 804 preferably made of the same material as non-slip member 112 can be placed on the interior-facing side of the rare-earth magnet 802 to provide a buffer between the magnet and the handheld electronic device within protection system 100.

[0058] FIGS. 9A-C illustrate one embodiment of the different components of mounting member 108. As shown in FIG. 9A, interlocking member 902 has a plurality of engaging members 912 located preferably at 90 degree intervals around the circumference of the interlocking member 902. This surface of interlocking member 902 may also display a logo or other information.

[0059] The connecting surface of interlocking member 902 is shown in FIG. 9B. Interlocking member 902 is attached to at least one mounting base 904, shown in FIG. 9C, preferably via a screw 906 (Figure 6) received within a boss 920 of the interlocking member 902. However, other means of attachment may be used to connect the interlocking member 902 to at least one mounting base 904. Preferably, the interlocking member 902 and the mounting base 904 include complementary interference features that locate the interlocking member 902 and mounting base 904 relative to one another in a rotational direction and inhibit or prevent the relative rotation of the interlocking member 902 and the mounting base 904. In the illustrated arrangement, the interference features include a projection 922 and a recess 924, which are generally rectangular in shape but could be other suitable shapes, as well. The projection 922 is positioned on the interlocking member 902 and the recess 924 is

located on the mounting base 904; however, these positions could be reversed. The projection 922 and recess 924 locate the interlocking member 902 such that the engaging members or tabs 912 are located in a desirable position relative to corresponding projections or feet 926 on the surface of the mounting base 904 that faces the interlocking member 902. The feet 926 are circumferentially offset from the tabs 912 and contact the tabs 162 of the upper shell piece 102 to provide a stop surface to the rotation of the upper shell piece 102 at a properly aligned position relative to the mounting member 108 when assembled thereto. The illustrated arrangement includes the same number of feet 926 as tabs 912; however, a lesser number of feet 926 could also be used. The circumferential dimension of the feet 926 can be configured such that the feet 926 contact an edge of the access opening 166 to provide some amount of resistance to rotation of the upper shell piece 102 in a directing tending to remove the upper shell piece 102 from the mounting member 108 thereby inhibiting unintentional disconnection of the upper shell piece 102 from the mounting member 108. If desired, active locks could also be provided to prevent unintentional disconnection of the upper shell piece 102 from the mounting member 108.

[0060] FIG. 10 depicts one embodiment of an assembled mounting member 108 preferably comprised of two mounting bases 904 and an interlocking member 902. In other embodiments, mounting member 108 may be further comprised of additional mounting bases 904 or a spacer, not shown, between the mounting bases.

[0061] The side of interlocking member 902 shown in FIGS. 9A and 10 is inserted into the attachment region 106 formed by interlocking surfaces 116 and 126 by aligning the tabs or engaging members 912 of interlocking member 902 with the access openings 166 in the attachment region 106, as seen in FIG. 2. Preferably rotating or twisting mounting member 108 in a clockwise direction results in the tabs or engaging members 912 of interlocking member 902 rotating behind or inside of interlocking surface 126 until further rotational movement is stopped by interaction with interlocking surface 116. This rotational movement of interlocking member 902 results in the rigid yet removable attachment of mounting member 108 to protection system 100. Similarly, rotation or twisting of interlocking member 902 in the opposite direction allows for removal of mounting member 108.

[0062] Attachment or detachment of protection system 100 from the mounting member 108 occurs either through rotation of mounting member 108 (resulting in rotation of interlocking member 902) or through rotation of the handheld electronic device within the protection system 100, as when the mounting member 108 is securely attached to another surface.

[0063] With reference to Figure 11, one accessory that may be used with protection system 100 includes a bike mount 1100. The illustrated bike mount 1100 may be mounted on or as a replacement of the top cap of a bicycle steering stem arrangement, preferably using screw 1120. In particular, the bike mount piece 1110 preferably replaces the top cap of a standard bicycle steering headset system and rests on the upper surface of the front fork steerer tube or steering stem spacer. As is known, the top cap is utilized to adjust a preload of the bearings in the bicycle steering headset system. Once the steering stem is clamped to the steerer tube, the top cap is no longer providing any function. The present bike mount 1100 can replace the standard top cap. Preferably, the mount piece 1110 is adjustable (e.g., rotatable) with respect to the bike mount attachment piece 1130. In particular, in the illustrated arrangement, the bike mount attachment piece 1130 includes an arm portion that extends from the mount piece 1110. The arm portion is rotatably coupled to the mount piece 1110 by a pivot assembly. The bike mount attachment piece 1130 may attach to the upper shell piece 102 using the interlocking mounting arrangement discussed above.

[0064] Although this application discloses certain preferred embodiments and examples, it will be understood by those skilled in the art that the present inventions extend beyond the specifically disclosed embodiments to other alternative embodiments and/or uses of the invention and obvious modifications and equivalents thereof. Further, the various features of these inventions can be used alone, or in combination with other features of these inventions other than as expressly described above. While the disclosed embodiments are primarily directed to a protection system for a handheld electronic device, aspects of the invention may be used in connection with other types of protection systems. Thus, it is intended that the scope of the present inventions herein disclosed should not be limited by the particular disclosed embodiments described above, but should be determined only by a fair reading of the claims that follow.

WHAT IS CLAIMED IS:

1. A protection system for a handheld electronic device, comprising:

a shell comprising a rear wall and a side wall extending from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device;

wherein the rear wall further comprises an inner surface and an outer surface, the rear wall defining an attachment region designed to receive an interlocking member and a non-slip region designed to receive a non-slip member;

the attachment region comprising a first open space, a first interlocking surface and a second interlocking surface, both of the first and second interlocking surfaces surrounding at least a portion of the first open space, the first and second interlocking surfaces being located behind the inner surface of the rear wall, the first interlocking surface being located substantially in a first plane and the second interlocking surface having at least a portion that extends substantially perpendicular to the first plane, and wherein the first interlocking surface is circumferentially offset from at least a portion of the second interlocking surface to provide an interlocking area;

the interlocking member comprising a plate portion having at least one engagement member that, in use, is passed through the first open space and disposed within the interlocking area to achieve an interlocked position between the interlocking member and the shell;

wherein the interlocking member further comprises at least one mounting base;

wherein the non-slip region comprises a second open space and a recessed surface formed by the disposition of a smaller opening within a larger opening;

wherein the non-slip member comprises a non-slip material shaped to fit within the second open space, the non-slip member having a peripheral groove that, in use, engages the recessed surface to attach the non-slip member to the shell;

wherein the non-slip member further comprises an indentation within an interior surface that, in use, faces the associated handheld electronic device; and

a magnet received within the indentation of the non-slip member.

2. The system of Claim 1, wherein the shell further comprises at least one access opening that allows access to control features of the handheld electronic device.

3. The system of Claim 1, wherein the non-slip member is disposed outwardly of the outermost portion of the outer surface of the rear wall of the shell.

4. The system of Claim 1, wherein the mounting base further comprises an adhesive layer that, in use, attaches to a mounting surface via adhesion.

5. The system of Claim 1, wherein the interlocked position is achieved by rotation of the interlocking member within the attachment region.

6. A protection system for a handheld electronic device, comprising:

a shell comprising a rear wall and a side wall extending from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device;

wherein the rear wall further comprises an inner surface and an outer surface, the rear wall defining an attachment region designed to receive an interlocking member and a non-slip region designed to receive a non-slip member;

wherein the attachment region comprises a first open space and a plurality of interlocking surface portions, each of the interlocking surface portions including a retaining surface and a stop surface that cooperate to provide an interlocking area;

wherein the interlocking member comprises a plurality of engaging members, each of the engaging members being configured to interact with one of the plurality of interlocking surface portions such that, in an interlocked position, each of the plurality of engaging members is disposed within one of the plurality of interlocking areas;

wherein the non-slip region comprises a second open space and a recessed surface formed by the disposition of a smaller opening within a larger opening; and

wherein the non-slip member comprises a non-slip material shaped to fit within the second open space, the non-slip member having a peripheral groove that, in use, engages the recessed surface to attach the non-slip member to the shell.

7. The system of Claim 6, wherein the shell further comprises at least one access opening that allows access to control features of a handheld electronic device.

8. The system of Claim 6, further comprising a magnet disposed within the non-slip member.

9. The system of Claim 6, further comprising at least one mounting base attached to the interlocking member.

10. The system of Claim 9, wherein the mounting base comprises an adhesive layer that allows the mounting base to be affixed to a surface through adhesion.

11. A protection system for a handheld electronic device, comprising:

a shell comprising a rear wall and a side wall extending in a first direction from the rear wall, wherein, in use, the side wall encloses a plurality of peripheral edges of an associated handheld electronic device, the rear wall comprising a first surface facing in the first direction and a second surface facing in a second direction opposite the first direction;

wherein the rear wall comprises an opening extending through the second surface, the opening defining at least one shell interlock surface;

a mount having at least one mount interlock surface, wherein, in use, a portion of the mount is passed through the opening of the shell and the at least one shell interlock surface is engaged with the at least one mount interlock surface to selectively couple the shell to the mount.

12. The protection system of Claim 11, wherein the mount comprises an adhesive layer that permits the mount to be secured to a surface via adhesion.

13. The protection system of Claim 11, wherein the mount is a bike mount that, in use, is mounted to a component of a bicycle.

14. The protection system of Claim 13, wherein the bike mount comprises a cap portion that, in use, is secured to a steerer tube of the bicycle.

15. The protection system of Claim 14, further comprising an arm portion that extends between the cap portion and the at least one mount interlock surface, wherein the arm portion is rotatably adjustable relative to the cap portion.

CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE

ABSTRACT OF THE DISCLOSURE

A protective case for a handheld electronic device is provided. The protective case can include a removable mounting system comprised of an interlocking member and a plurality of mounting bases. The protective case may further include a non-slip member to prevent the device from slipping on a surface and a magnet for attaching the device to a magnetic surface.

3844356





FIG. 1

**FIG. 2**





FIG. 3

*FIG. 4*





FIG. 5

*FIG. 6*




FIG. 7




FIG. 8A




FIG. 8B




FIG. 8C




FIG. 9A

FIG. 9B





FIG. 9C




FIG. 10




FIG. 11

Electronic Acknowledgement Receipt

EFS ID:	13574931
Application Number:	13593220
International Application Number:	
Confirmation Number:	1198
Title of Invention:	CASE AND MOUNT SYSTEM FOR HANDHELD ELECTRONIC DEVICE
First Named Inventor/Applicant Name:	Jeff Whitten
Customer Number:	20995
Filer:	Curtiss C. Dosier/Sandra Autry
Filer Authorized By:	Curtiss C. Dosier
Attorney Docket Number:	2BROS.019A
Receipt Date:	23-AUG-2012
Filing Date:	
Time Stamp:	17:43:18
Application Type:	Utility under 35 USC 111(a)

Payment information:

Submitted with Payment	no
------------------------	----

File Listing:

Document Number	Document Description	File Name	File Size(Bytes)/ Message Digest	Multi Part /.zip	Pages (if appl.)
1	Application Data Sheet	ADS_2BROS_019A.pdf	895333 d770df3d8d86c9cf015a69ca533903051cefdb10	no	4

Warnings:

Information:

2		Application_2BROS_019A.pdf	1088649	yes	21
	73942fc895f0b5a2baf14b1bb6699b8ef1e02cb9				
	Multipart Description/PDF files in .zip description				
	Document Description		Start	End	
	Specification		1	17	
	Claims		18	20	
	Abstract		21	21	
Warnings:					
Information:					
3	Drawings-only black and white line drawings	Drawings_2BROS_019A.pdf	317481	no	11
	86baa7ef2ca3146f1972ac43296bf74ff194c744				
Warnings:					
Information:					
Total Files Size (in bytes):			2301463		
<p>This Acknowledgement Receipt evidences receipt on the noted date by the USPTO of the indicated documents, characterized by the applicant, and including page counts, where applicable. It serves as evidence of receipt similar to a Post Card, as described in MPEP 503.</p> <p><u>New Applications Under 35 U.S.C. 111</u> If a new application is being filed and the application includes the necessary components for a filing date (see 37 CFR 1.53(b)-(d) and MPEP 506), a Filing Receipt (37 CFR 1.54) will be issued in due course and the date shown on this Acknowledgement Receipt will establish the filing date of the application.</p> <p><u>National Stage of an International Application under 35 U.S.C. 371</u> If a timely submission to enter the national stage of an international application is compliant with the conditions of 35 U.S.C. 371 and other applicable requirements a Form PCT/DO/EO/903 indicating acceptance of the application as a national stage submission under 35 U.S.C. 371 will be issued in addition to the Filing Receipt, in due course.</p> <p><u>New International Application Filed with the USPTO as a Receiving Office</u> If a new international application is being filed and the international application includes the necessary components for an international filing date (see PCT Article 11 and MPEP 1810), a Notification of the International Application Number and of the International Filing Date (Form PCT/RO/105) will be issued in due course, subject to prescriptions concerning national security, and the date shown on this Acknowledgement Receipt will establish the international filing date of the application.</p>					